



US010735653B1

(12) **United States Patent**
Huang

(10) **Patent No.:** **US 10,735,653 B1**
(45) **Date of Patent:** **Aug. 4, 2020**

(54) **ELECTRONIC IMAGE STABILIZATION TO IMPROVE VIDEO ANALYTICS ACCURACY**

(71) Applicant: **Ambarella International LP**, Santa Clara, CA (US)

(72) Inventor: **Cheng-Yu Huang**, Chupei (TW)

(73) Assignee: **Ambarella International LP**, Santa Clara, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/458,227**

(22) Filed: **Mar. 14, 2017**

(51) **Int. Cl.**
G06K 9/00 (2006.01)
H04N 5/232 (2006.01)
B64C 39/02 (2006.01)
B64D 47/08 (2006.01)

(52) **U.S. Cl.**
CPC **H04N 5/23267** (2013.01); **B64C 39/024** (2013.01); **B64D 47/08** (2013.01); **G06K 9/00268** (2013.01); **G06K 9/00744** (2013.01); **B64C 2201/024** (2013.01); **B64C 2201/108** (2013.01); **B64C 2201/127** (2013.01); **B64C 2201/146** (2013.01); **H04N 5/23258** (2013.01)

(58) **Field of Classification Search**
CPC G06F 3/04815; G06F 17/30047; G02B 2027/0138; G06T 7/70; G06T 7/579; G06T 2207/10016; G06T 2207/30201; G06K 9/00302; G06K 9/00711
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

9,854,155	B1 *	12/2017	Sikka	H04N 5/23238
2007/0081081	A1 *	4/2007	Cheng	G06T 3/4038
				348/218.1
2011/0298829	A1 *	12/2011	Stafford	G06K 9/00248
				345/659
2015/0142213	A1 *	5/2015	Wang	G05D 1/0016
				701/2
2015/0149000	A1 *	5/2015	Rischmuller	B64C 39/024
				701/7
2015/0249806	A1 *	9/2015	Gabel	H04N 5/23296
				348/14.12
2015/0338499	A1 *	11/2015	Horvath	G01S 1/02
				348/169
2016/0033077	A1 *	2/2016	Chen	F16M 13/04
				294/139
2016/0127641	A1 *	5/2016	Gove	G06T 1/0007
				348/143
2016/0352992	A1 *	12/2016	Saika	H04N 5/2328
2017/0185081	A1 *	6/2017	Steele	G05D 1/0016
2017/0199588	A1 *	7/2017	Ahn	G06F 3/0346
2017/0227162	A1 *	8/2017	Saika	F16M 13/02
2018/0025498	A1 *	1/2018	Omari	G06T 7/248
2019/0174063	A1 *	6/2019	Huang	B64C 39/024
2019/0373103	A1 *	12/2019	Oga	H04M 1/72569


* cited by examiner

Primary Examiner — Guillermo M Rivera-Martinez
(74) *Attorney, Agent, or Firm* — Christopher P. Maiorana, PC

(57) **ABSTRACT**

An apparatus includes an image sensor and a processor. The image sensor may be configured to generate a sequence of video frames based on a targeted view of an environment. The processor may be configured to (A) perform an image stabilization on the sequence of video frames and (B) generate video analytics for the sequence of video frames, wherein the image stabilization comprises maintaining a horizon of the targeted view and is performed prior to generating the video analytics.

16 Claims, 9 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

ELECTRONIC IMAGE STABILIZATION TO IMPROVE VIDEO ANALYTICS ACCURACY

FIELD OF THE INVENTION

The invention relates to video capture generally and, more particularly, to a method and/or apparatus for implementing electronic image stabilization to improve video analytics accuracy.

BACKGROUND

In computer vision, a class of algorithms generally known as Video Analytics has results that depend on the stability of the video signal. Video analytics can include human face tracking, a feature that is in high demand. Vibration, rotation and shaking affect the efficiency of video analytics algorithms. This is the case for face tracking and human tracking algorithms, many of which are based on an assumption about human face orientation. If the human face rotates too much, the detection and tracking will fail easily.

In a handheld device, rotation of the human face is typically corrected by a human hand stabilizing the camera. However, in a drone or a flying camera, vibration and rotation of the drone/camera during flight can make human face tracking difficult. A gimbal can help solve the problem, but the size and the cost of the gimbal make it very hard to adopt in low cost, low power consumer drone markets.

It would be desirable to implement electronic image stabilization to improve video analytics accuracy.

SUMMARY

The invention concerns an apparatus including an image sensor and a processor. The image sensor may be configured to generate a sequence of video frames based on a targeted view of an environment. The processor may be configured to (A) perform an image stabilization on the sequence of video frames and (B) generate video analytics for the sequence of video frames, wherein the image stabilization comprises maintaining a horizon of the targeted view and is performed prior to generating the video analytics.

BRIEF DESCRIPTION OF THE FIGURES

Embodiments of the invention will be apparent from the following detailed description and the appended claims and drawings in which:

FIG. 1 is a diagram illustrating an embodiment of the invention;

FIG. 2 is a diagram illustrating motion axis conventions for flying objects;

FIG. 3 is a block diagram illustrating an example embodiment of a system on chip for generating a video analytics in accordance with an example embodiment of the invention;

FIG. 4 is a flow diagram illustrating an image processing scheme in accordance with an example embodiment of the invention;

FIG. 5 is a diagram illustrating an example result of running a face detection algorithm to detect a face or faces in an image;

FIG. 6 is a diagram illustrating a pattern used in a face detection scheme in accordance with an example embodiment of the invention;

FIG. 7 is a diagram illustrating an example where an image capture device fails to maintain an appropriate orientation on a target face;

FIG. 8 is a diagram illustrating an electronic image stabilization process in accordance with an embodiment of the invention;

FIG. 9 is a diagram illustrating a horizon stabilization process in accordance with an embodiment of the invention; and

FIG. 10 is a diagram illustrating a system on chip (SoC) implementing an example embodiment of the invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Embodiments of the present invention include providing electronic image stabilization to improve video analytics accuracy that may (i) implement electronic image stabilization, (ii) compensate motion based on horizon monitoring, (iii) detect objects in a video, (iv) perform intelligent video analytics, (v) be implemented in a flying camera, (vi) be implemented for a camera associated with a drone, and/or (vi) be implemented as one or more integrated circuits.

In computer vision applications, a class of techniques generally known as video analytics provide results that depend on the stability of the video signal. Vibration, rotation and shaking can affect the efficiency of the video analytics algorithms. This, for instance, is the case for face tracking and human tracking algorithms, many of which are based on an assumption about human face orientation. If the human face in an image is rotated too much from the assumed orientation, the detection and tracking can fail easily.

In handheld devices, variation in the orientation of faces is generally fixed (corrected) by a human hand stabilizing the camera. However in drones or flying cameras, the vibration and rotation of the drone during flight can make human face tracking very difficult. A conventional solution uses a gimbal. The gimbal isolates the camera from the motion of the drone. The gimbal helps to solve the problem, but the size of the gimbal and the cost of the gimbal make the gimbal very hard to adopt in low cost, low power consumer drones.

In various embodiments, a drone or flying camera is provided that combines an electronic image stabilization (EIS) and horizon keeping processing phase with the video analytics (e.g., object tracking, motion tracking, face tracking) phase to allow the video analytics to work reliably with a drone design that does not use a gimbal. In general, embodiments of the invention enable the video analytics feature to work with much higher accuracy at lower cost relative to conventional systems.

Referring to FIG. 1, a diagram of a system 50 is shown illustrating an example embodiment of the invention. The system 50 may comprise an unmanned aerial vehicle (or drone or flying camera) 52, a playback (or viewing) device 54, a remote controller 56, a communication device 58, and a camera 60. The playback (or viewing) device 54 and the remote controller 56 may be used by a pilot 70 to control the unmanned aerial vehicle 52. In some embodiments, the camera 60 may be implemented as a separate device attached to the unmanned aerial vehicle 52. In some embodiments, the camera 60 may be integrated with the unmanned aerial vehicle 52 (e.g., a flying camera). In various embodiments, an apparatus 100 may be implemented as part of the camera 60. The system 50 may be implemented to control the unmanned aerial vehicle 52 and/or receive video from the perspective of the unmanned aerial vehicle 52.

The apparatus 100 may be implemented to generate video data and information about/from the video data (e.g., video

analytics). In various embodiments, the video data may be point-of-view digital video. The video data may be stored on the unmanned aerial vehicle **52** and/or communicated over a network (e.g., via the communication device **58**). In an example, the network may comprise a bandwidth-constrained network (e.g., a wireless network). The apparatus **100** may combine hardware de-warping, electronic image stabilization, horizon keeping, intelligent video analytics, and/or digital zooming.

In some embodiments, the camera **60** may also be capable of capturing panoramic video. Generally, a panoramic video may comprise a large field of view generated by one or more lenses/camera sensors. One example of a panoramic video may be an equirectangular **360** video. Equirectangular **360** video may also be called spherical panoramas. Panoramic video may be a video that provides a field of view that is larger than the field of view that may be displayed on a device used to playback the video (e.g., the playback device **54**). In some embodiments, the point-of-view digital video may be extracted from the panoramic video. In some embodiments, portions of the panoramic video may be cropped to the size of the display of the playback device **54** (e.g., portions of the panoramic video outside of the cropped portion may be discarded and/or not displayed). In some embodiments, the panoramic video may be panned in one or more directions to see additional portions of the panoramic video outside of the field of view of the playback device **54**. For example, the panoramic video may comprise a spherical video, a hemispherical video, a 360 degree video, a wide angle video, a video having less than a 360 field of view, etc.

Panoramic videos may comprise a view of the environment near the camera **60**. In one example, the entire field of view of the panoramic video may be captured at generally the same time (e.g., each portion of the panoramic video represents the view from the camera **60** at one particular moment in time). In some embodiments (e.g., when the camera **60** implements a rolling shutter sensor), a small amount of time difference may be present between some portions of the panoramic video. Generally, each video frame of the panoramic video comprises one exposure of the sensor (or multiple sensors) capturing the environment near the camera **60**.

In some embodiments, the panoramic video may provide coverage for a full 360 degree field of view. In some embodiments, less than a 360 degree view may be captured by the panoramic video (e.g., a 270 degree field of view, a 180 degree field of view, etc.). In some embodiments, the panoramic video may comprise a spherical field of view (e.g., capture video above and below the camera **60**). In some embodiments, the panoramic video may comprise a field of view that is less than a spherical field of view (e.g., the camera **58** may be configured to capture the ground below and the areas to the sides of the camera **60** but nothing directly above). The implementation of the panoramic video may be varied according to the design criteria of a particular implementation.

In some embodiments, the system **50** may be implemented for first-person view (FPV) racing of the drone **52** and/or aerial surveying. For example, aerial surveying may be used to implement security surveillance from above. In another example, aerial surveying may be used for broadcast purposes (news reporting, sporting events, concert events, etc.). The playback device **54** may receive the video stream live from the drone **52**. The pilot **70** may view the video stream using the playback device **54** to see a live view from the perspective of the drone **52**. The pilot **70** may react to the environment by viewing the video captured by the apparatus

100 and provide control to the drone **52** using the remote controller **56**. In a racing embodiment, the pilot **70** may need to react quickly to traverse a set course as fast as possible and/or prevent the drone **52** from crashing and/or traveling out of the bounds of the course. In a security surveillance embodiment, the pilot **70** may engage a tracking feature to automatically follow an object of interest (e.g., person, vehicle, etc.).

In one example, the bandwidth-constrained network may be a peer-to-peer (P2P) network (e.g., a direct connection between nodes without connecting to a central server). In another example, the bandwidth-constrained network may be a connection to a central server. The bandwidth-constrained network may be implemented as a wireless connection. In the example shown, a wireless network is shown communicating between the drone **52**, the remote controller **56** and/or the playback device **54**. In one example, the network may be implemented comprising a wired portion. In another example, the network may be implemented using a wireless connection or link (e.g., Wi-Fi, BLUETOOTH, ZIGBEE, radio frequency, etc.).

The drone **52** may be capable of hovering and/or moving in a variety of directions. For example, the drone **52** may accelerate and/or change direction quickly. The drone **52** may comprise the communication device **58**, the camera **60**, the apparatus **100**, and/or other components (not shown). In some embodiments, the communication device **58** may be a component of (e.g., integrated with) the apparatus **100**.

The playback device **54** may be implemented as a display, a wearable headset, or other video viewing device. The display **54** may be worn (or viewed) by the user (e.g., the pilot **70** and/or other viewers). The display **54** may be configured to display video frames (e.g., point-of-view video frames, panoramic video frames, portions of panoramic video frames, etc.) of the video transmitted from the unmanned aerial vehicle **52**. The display **54** may present a portion of each of the video frames generated by the apparatus **100**. The portion of each of the video frames that is displayed may be a region of interest. The region of interest may represent a portion of the panoramic video selected by the apparatus **100**. For example, the display **54** may receive the region of interest portion of the panoramic video from the apparatus **100** and/or the communication device **58**.

In some embodiments, a playback device **54'** may be implemented as part of the remote controller **56**, instead of the pilot **70** wearing the headset **54**. In one example, the playback device **54'** may be implemented as a touchscreen device. In some embodiments, the playback device **54'** may be implemented as a smartphone and/or a tablet computing device. A display of the smartphone and/or tablet computing device may display the current region of interest to the pilot **70**.

In some embodiments, the playback device **54'** may be a desktop computer, laptop computer, notebook computer, etc. A computer monitor may be used to view the current region of interest. Computer input peripherals may be used by the pilot **70** to provide control input to the drone **52**. In an example, a mouse cursor, keyboard controls, a joystick, and/or a software interface (e.g., API) may be implemented for the computer to control a flight path of the drone **52**. The implementation of the playback device **54'** may be varied according to the design criteria of a particular implementation.

The playback device **54** may be configured to receive the video stream from the drone **52**. The video stream may be a live (or near-live) video feed of the video stream. The video

stream may provide the pilot 70 with a point-of-view from the perspective of the drone 52. When the viewing device 54 is implemented as a headset, the video stream may provide a first-person view (FPV) of the drone 52. The playback device 54 may display the region of interest to the pilot 70.

The pilot 70 is shown holding the remote controller 56. In some embodiments, the playback device 54' may be implemented as a screen and/or handheld device (e.g., a screen that is part of the remote controller 56). The remote controller 56 may be configured to send control data to the drone 52 (e.g., provide flight control). For example, the remote controller 56 may implement a radio frequency (RF) transmission to control the drone 52. The pilot 70 may provide input to the remote controller 56 to direct the movement of the drone 52.

In some embodiments, the camera 60 may be implemented to provide a panoramic field of view (e.g., a camera configured to record panoramic video, spherical video, a 360 degree video and/or less than a 360 degree video, etc.) in addition to the point-of-view video stream. In one example, the panoramic field of view may allow an end user to view a video of the environment surrounding the camera 60 (e.g., a live stream). In another example, the panoramic field of view may allow the end user to view a previously recorded video of the environment surrounding the camera 60. The playback device 54 may be configured to selectably display the point-of-view or the panoramic field of view to the end user.

In some embodiments, the camera 60 may be implemented having one wide angle (or fisheye) lens. In some embodiments, the camera may be implemented as a multi-sensor camera. For example, the camera 60 may be implemented having more than one wide angle lens. The implementation of the camera 60 may be varied according to the design criteria of a particular implementation.

In some embodiments, the camera 60 may comprise the apparatus 100. In some embodiments, the apparatus 100 may be a component of the drone 52. The apparatus 100 may be implemented as a processor and/or a system on chip (SoC). For example, the apparatus 100 may be implemented as a printed circuit board comprising one or more components. The apparatus 100 may be configured to encode video frames captured by one or more capture devices of the camera 60. In some embodiments, the apparatus 100 may be configured to perform video stitching operations to stitch video frames captured by each of the capture devices. In some embodiments, the apparatus 100 may generate the panoramic video from one wide angle lens.

The apparatus 100 may be configured to capture images and/or video of the environment near the drone 52. For example, the apparatus 100 may capture the environment in the direction of flight and/or other directions selected by the pilot 70. The apparatus 100 may be configured to generate video signals based on the captured images from the camera 60. In some embodiments, the apparatus 100 may be configured to perform video stitching operations, de-warping operations, and/or video analytics operations on the video stream(s) received from the camera 60 to generate the video stream.

The apparatus 100 may format (or encode) the video signals to be transmitted wirelessly and/or stored locally. The apparatus 100 may be configured to perform intelligent video analysis on the video frames of the de-warped point-of-view or panoramic video. The apparatus 100 may be configured to crop and/or enhance the video frames.

The wireless communication device 58 may be configured to transmit the raw and/or cropped and/or enhanced video

signal to the playback device 54. The wireless communication device 58 may be configured to receive flight control signals from the remote controller 56. For example, the drone 52 may comprise the wireless communication device 58, and the apparatus 100 may provide the video signal to the wireless communication device 58. The drone 52 is shown transmitting data wirelessly. For example, the drone 52 may wirelessly transmit a video stream generated by the apparatus 100.

Different communication channels may be implemented to transmit video (e.g., the point-of-view video and/or portions of the panoramic video) and drone control/telemetry. In an example, the communication device 58 may implement one channel to transmit video and a different remote-control (RC) channel for drone control (e.g., input from the pilot 70 using the remote control 56) and telemetry. Example frequencies may comprise 900 MHz, 1.2 GHz, 2.4 GHz and/or 5.8 GHz. In an example, if the drone 52 implements a RC transmitter on one of the frequencies for control, then, in order to avoid interference, another one of the frequencies may be selected for the transmitting the panoramic video signal. For example, many video transmitters operate at 5.8 GHz. Other frequencies may be implemented. The channels used for a particular type of communication (e.g., video or control) and/or the frequencies used may be varied according to the design criteria of a particular implementation.

In some embodiments, the remote controller 56 and/or flight control signals from the pilot 70 may be optional. For example, the drone 52 may implement an autonomous drone. In embodiments where the drone 52 is autonomous, the drone 52 may travel a pre-determined path and/or make decisions about where to travel without input from the pilot 70. In some embodiments, data generated in response to the intelligent video analysis performed by the apparatus 100 (e.g., face tracking, etc.) may be used by the drone 52 to make decisions to determine the flight path. In embodiments where the drone 52 is autonomous, the communication device 58 may still transmit the video signal to the playback device 54.

To provide a useful view to the pilot 70, the video stream may be generated by the apparatus 100 with low and/or negligible delay. The pilot 70 may be unable to react appropriately if there is lag (e.g., a delay) between what is viewed on the playback device 54 and where the drone 52 is actually located. The apparatus 100 may be configured to generate a viewable portion of the video that may be transmitted using a lower bitrate that still provides a high quality visual representation of objects detected by the apparatus 100. The apparatus 100 may be configured to provide a low-latency video stream from the drone 52 to the playback device 54 without sacrificing video quality in the selected region of interest. The apparatus 100 may be configured to generate a high resolution image within the total size constraints of the cropped region of the video.

The drone 52 may be configured to fly and travel in many directions and/or have an extended range of flight. Generally, a wired connection between the drone 52 and the playback device 54 may not be practical. Similarly, a wired connection between the drone 52 and a central server and/or a computing device may be impractical. To communicate with the playback device 54, the drone may implement a wireless connection using the wireless communication device 58. The wireless connection may have a limited bandwidth for transmitting data. The videos may comprise a large amount of data. The apparatus 100 may be configured to encode the video to reduce a bitrate of the video, to

facilitate a wireless connection between the drone **52** and the playback device **54** that does not introduce lags and/or delay.

The apparatus **100** may be configured to reduce a bitrate of portions of the video while providing a high quality video to a viewer. The apparatus **100** may be implemented to enable a wireless transmission of the cropped portion of a panoramic video signal that may be played back smoothly using the playback device **54** (e.g., limited delay and/or buffering of the panoramic video).

The system **50** may be a peer-to-peer implementation. The drone **52** (using the wireless communication device **58**) may form a peer-to-peer connection with the playback device **54**. In an example, the video may be generated by components of the drone **52** (e.g., the apparatus **100**), cropped and/or enhanced on the drone **52** and transmitted directly from the drone **52** to the playback device **54**. To implement the peer-to-peer connection, the apparatus **100** may be configured to generate the video from the video streams captured by the camera **60** on-board the drone **52**.

To implement the communication of a selected region of interest of a panoramic video, the apparatus **100** may be configured to perform intelligent video analytics on the panoramic video frames. The apparatus **100** generally implements electronic image stabilization and horizon keeping in accordance with an embodiment of the invention to improve the accuracy of the video analytics. The improved video analytics accuracy may allow smarter field of view selection and/or cropping, which may also reduce bandwidth needed to transmit the video. The apparatus **100** may be configured to select the region of interest and/or dynamically adjust the region of interest for one or more upcoming frames of the panoramic video stream corresponding to objects detected and/or recognized and/or being tracked in the video frames. The apparatus **100** may encode and/or enhance the region of interest (e.g., to provide a high quality video).

Referring to FIG. 2, a diagram of the drone **52** is shown illustrating conventional principle axes of an aerial vehicle. An aerial vehicle in flight is free to rotate in three dimensions: pitch, nose up or down about an axis running from wing to wing; yaw, nose left or right about an axis running up and down; and roll, rotation about an axis running from nose to tail. These axes move with the vehicle and rotate relative to the Earth along with the aerial vehicle. These rotations are produced by torques (or moments) about the principal axes. On a drone, these are intentionally produced by means of varying propeller speeds, which vary the distribution of the net aerodynamic force about the center of mass of the drone.

The vertical axis, normal axis, or yaw axis is an axis drawn from top to bottom, and perpendicular to the other two axes. The lateral axis, transverse axis, or pitch axis is an axis running from the left side to right to the right side of an aircraft, and parallel to the wings of a winged aircraft. The longitudinal axis, or roll axis is an axis drawn through the body of the vehicle from tail to nose in the normal direction of flight. These axes are generally represented by the letters X, Y and Z in order to compare them with some reference frame, usually named x, y, z. In general, the association is made in such a way that the X is used for the longitudinal axis, but there are other possibilities to do it.

The vertical yaw axis is defined to be perpendicular to the wings and to the normal line of flight with its origin at the center of gravity and directed towards the bottom of the aircraft. Yaw moves the nose of the aircraft from side to side. A positive yaw, or heading angle, moves the nose to the right. On a plane, the rudder is the primary control of yaw.

The pitch axis (also called lateral or transverse axis) passes through the plane from wingtip to wingtip. Pitch moves the nose of the aircraft up and down. A positive pitch angle raises the nose and lowers the tail. On a plane, the elevators are the primary control of pitch. The roll axis (or longitudinal axis) passes through the plane from nose to tail. The angular displacement about the roll axis is called bank. On a plane, the pilot changes bank angle by increasing the lift on one wing and decreasing it on the other. On a drone, the pilot changes bank angle by increasing the lift from propellers on one side of the drone and decreasing the lift from propellers on the other side of the drone. A positive roll angle lifts the left side and lowers the right. On a plane, the ailerons are the primary control of bank. The rudder also has a secondary effect on bank.

Referring to FIG. 3, a block diagram illustrating an example of a system on chip (SoC) for performing electronic image stabilization and horizon keeping and generating video analytics in accordance with an embodiment of the invention is shown. In various embodiments, the apparatus **100** comprises a block (or circuit) **110**, a block (or circuit) **112**, a block (or circuit) **114**, and/or a block (or circuit) **116**. The circuit **110** may be implemented as a capture device. The circuit **112** may be implemented as a processor. The circuit **114** may be implemented as a memory. The circuit **116** may implement flight (or motion detection) sensors (e.g., gyroscopic sensor, gravitational sensor, accelerometer, etc.). In an example implementation, the circuit **112** may be implemented as a video processor. The processor **112** may comprise an input **120**, an input **122**, and/or other inputs. The processor **112** may comprise an output **124** and/or other outputs. The processor **112** may comprise an input/output **126**, an input/output **128**, and/or other input/outputs.

In the embodiment shown, the capture device **110** may be implemented as a component of the apparatus **100**. In some embodiments, the capture device **110** may be implemented as a separate device (e.g., part of the drone **52** and/or part of the camera **60**). When the device **110** is implemented as a separate device, the capture device **110** may be configured to send data to the apparatus **100**. Similarly, in some embodiments the flight sensors **116** may be implemented as a component of the apparatus **100** and in some embodiments the flight sensors **116** may be implemented as separate devices (e.g., part of the drone **52**). In some embodiments, the wireless communication device **58** may be a component of the apparatus **100** and in some embodiments the wireless communication device **58** may be a separate device (e.g., part of the drone **52**).

The apparatus **100** may receive a signal (e.g., IMF). The apparatus **100** may present a signal (e.g., VIDEO). The capture device **110** may receive the signal IMF from a corresponding lens assembly **80** of the camera **60**. The apparatus **100** may present the signal VIDEO to the communication device **58**. For example, the wireless communication device **58** may be a radio-frequency (RF) transmitter. In another example, the communication device **58** may be a Wi-Fi module. In another example, the communication device **58** may be a device capable of implementing RF transmission, Wi-Fi, BLUETOOTH and/or other wireless communication protocols.

The camera **60** may capture a signal (e.g., IM). The signal IM may be an image (e.g., an analog image) of the environment near the drone **52** that is in view of the camera **60**. The lens assembly **80** may present the signal IM to the capture device **110** as the signal IMF. The camera **60** may be implemented with an optical lens. The camera **60** may provide a zooming feature and/or a focusing feature. The

capture device **110** and the lens assembly **80** of the camera **60** may be implemented, in one example, as a single lens and sensor assembly. In another example, the lens assembly **80** of the camera **60** may be a separate implementation from the capture device **110**. The capture device **110** is shown within the circuit **100**. In an example implementation, the capture device **110** may be implemented outside of the circuit **100** (e.g., along with the camera **60** as part of a lens/capture device assembly).

The capture device **110** may be configured to capture image data for video (e.g., the signal IMF from the camera **60**). The capture device **110** may capture data received through the camera **60** to generate a bitstream (e.g., generate video frames). For example, the capture device **110** may receive sampled values of focused light from the camera **60**. The camera **60** may be directed, tilted, panned, zoomed and/or rotated to provide a targeted view from the drone **52** (e.g., to provide coverage for a field of view). The capture device **110** may generate a signal (e.g., FRAMES). The signal FRAMES may be video data (e.g., a sequence of video frames). The signal FRAMES may be presented to the input **120** of the processor **112**.

The capture device **110** may transform the received image data signal IMF into digital data (e.g., a bitstream). In some embodiments, the capture device **110** may perform an analog to digital conversion. The capture device **110** may transform the bitstream into video data, video files and/or video frames. In some embodiments, the video data generated by the capture device **110** may be uncompressed and/or raw data generated in response to the image data. In some embodiments, the video data may be digital video signals. The video signals may comprise video frames. In some embodiments, the video data may be encoded at a high bitrate. For example, the signal may be generated using a lossless compression and/or with a low amount of lossiness. The apparatus **100** may encode the video data captured by the capture device **110** to generate the signal VIDEO.

In some embodiments, the apparatus **100** may further comprise an audio capture device (e.g., a microphone). The audio capture device may capture audio of the environment. The apparatus **100** may be configured to synchronize the audio captured with the images captured by the capture device **110**.

The processor **112** may receive the signal FRAMES from the capture device **110** at the input **120** and/or a signal (e.g., DATA) from the memory **114** at the input/output **126**. The processor **112** may send/receive a signal (e.g., DIO) at the input/output **128** (e.g., to/from the drone **52**). The processor **112** may be connected through a bi-directional interface (or connection) to components of the drone **52**, the capture device **110**, to the communication device **58**, and/or to the memory **114**. The processor **112** may store data to and/or retrieve data from the memory **114**. The memory **114** may be configured to store computer readable/executable instructions (or firmware). The instructions, when executed by the processor **112** may perform a number of steps, including steps associated with electronic image stabilization, horizon keeping, and/or intelligent video analytics in accordance with an embodiment of the invention.

The processor **112** may be configured to receive the signal FRAMES, the signal DATA, the signal DIO and/or other inputs. The signal FRAMES may comprise video data (e.g., one or more video frames) providing a field of view captured by the camera **60**. The processor **112** may be configured to generate the signal VIDEO and/or other signals (not shown). The signal VIDEO may be generated based on one or more decisions made and/or functions performed by the processor

112. The decisions made and/or functions performed by the processor **112** may be determined based on data received by the processor **112** at the input **120** (e.g., the signal FRAMES), the input **122**, and/or other inputs.

The input **120**, the input **122**, the output **124**, the input/output **126**, the input/output **128** and/or other inputs/outputs may implement an interface. The interface may be implemented to transfer data to/from the processor **112**, the communication device **58**, the capture device **110**, the memory **114**, the sensors **116**, and/or other components of the apparatus **100** and/or the drone **52**. In one example, the interface may be configured to receive (e.g., via the input **120**) the video stream FRAMES from the capture device **110**. In yet another example, the interface may be configured to output one or more upcoming video frames (e.g., the signal VIDEO) to the communication device **58**. The interface may be configured to enable transfer of data and/or translate data from one format to another format to ensure that the data transferred is readable by the intended destination component. In an example, the interface may comprise a data bus, traces, connectors, wires and/or pins. The implementation of the interface may be varied according to the design criteria of a particular implementation.

The signal VIDEO may be presented to the communication device **58**. The signal VIDEO may be an encoded, cropped, stitched and/or enhanced version of the signal FRAMES. The signal VIDEO may be a high resolution, digital, encoded, de-warped, stabilized, cropped, blended, stitched and/or rolling shutter effect corrected version of the signal FRAMES. In some embodiments, the apparatus **100** may be configured to balance an amount of time needed to generate the signal VIDEO with the visual quality of the signal VIDEO.

The apparatus **100** may implement a camera system. In some embodiments, the camera system **100** may be implemented as a drop-in solution (e.g., installed as one component). In an example, the camera system **100** may be a device that may be installed as an after-market product for the drone **52** (e.g., a retro-fit for the drone **52**). In some embodiments, the apparatus **100** may be a component of the camera **60**. The number and/or types of signals and/or components implemented by the camera system **100** may be varied according to the design criteria of a particular implementation.

The video data of the targeted view from the drone **52** may be represented as the signal/bitstream/data FRAMES (e.g., a video signal). The capture device **110** may present the signal FRAMES to the input **120** of the processor **112**. The signal FRAMES may represent the video frames/video data. The signal FRAMES may be a video stream captured by the capture device **110**. In some embodiments, the capture device **110** may be implemented in the camera **60**. In some embodiments, the capture device **110** may be configured to add to existing functionality to the camera **60**.

The capture device **110** may comprise a block (or circuit) **130**, a block (or circuit) **132**, and/or a block (or circuit) **134**. The circuit **130** may implement a camera sensor interface. The circuit **132** may implement a camera processor/logic. The circuit **134** may implement a memory buffer. As a representative example, the capture device **110** is shown comprising the sensor interface **130**, the logic block **132** and the buffer **134**. In some embodiments, the camera sensor interface **130** may receive analog image data from the camera **60** and transform the image data into digital data (e.g., the bitstream).

The apparatus **100** may further comprise the interface **128** configured to send/receive data (e.g., the signal DIO)

to/from one or more components of the drone 52, the pilot 70 and/or other components of the camera system 100. The interface 128 may be configured to send data (e.g., instructions) from the processor 112 to the components of the drone 52 and receive data (e.g., telemetry, etc.) from the drone 52 to the processor 112. For example, the interface 128 may be bi-directional. In an example, data presented to the interface 128 may be used by the processor 112 to determine the movement of the drone 52 (e.g., to provide information to perform image stabilization, to calculate movements to determine expected rotations of objects detected by the processor 112 and/or to determine flight control output).

The interface 122 may receive information from a gyroscope sensor, information from an inertial measurement unit, information from one or more components of the drone 52, etc. In an example, the signal DIO may comprise information from the components of the drone 52 that may be used to calculate telemetry data that may be compared to telemetry information calculated by the processor 112 by analyzing the video data captured (e.g., detecting and/or measuring the horizon captured in the video data). The type of data and/or the number of components of the drone 52 that provide data may be varied according to the design criteria of a particular implementation.

The processor 112 may be configured to execute computer readable code and/or process information. The processor 112 may be configured to receive input from and/or present output to the memory 114. The processor 112 may be configured to present and/or receive other signals (not shown). The number and/or types of inputs and/or outputs of the processor 112 may be varied according to the design criteria of a particular implementation.

The processor 112 may receive the signal FRAMES, the signal DIO and/or the signal DATA. The processor 112 may make a decision based on data received at the input 120, the input 122, the input 126, the input 128 and/or other inputs. For example other inputs may comprise external signals generated in response to user input, external signals generated by the drone 52 and/or internally generated signals such as signals generated by the processor 112 in response to analysis of the signal FRAMES and/or objects detected in the signal FRAMES. The processor 112 may adjust the video data (e.g., crop, digitally move, physically move the camera sensor 130, etc.) of the signal FRAMES. The processor 112 may generate the signal VIDEO in response data received by the input 120, the input 122, the input 124, the input 126, and/or the decisions made in response to the data received by the inputs 120, the input 122, the input 126, and/or the input 128.

The signal VIDEO may be generated to provide an output for the communication device 58 in response to the captured video frames (e.g., the signal FRAMES) and the video analytics performed by the processor 112. For example, the video analytics may be performed by the processor 112 in real-time and/or near real-time (e.g., with minimal delay). The signal VIDEO may be a live (or nearly live) video stream. The signal VIDEO may be transmitted to the playback device 54 (e.g., using RF communication) to provide the pilot 70 with a cropped view of the panoramic video captured from the perspective of the drone 52.

Generally, the signal VIDEO may correspond to the data received at the input 120, the input 122, the input 124, the input 126, the input 128, and/or enhanced (e.g., stabilized, corrected, cropped, downsampled, packetized, compressed, etc.) by the processor 112. For example, the signal VIDEO may be a stitched, corrected, stabilized, cropped and/or

encoded version of the signal FRAMES. The processor 112 may further encode and/or compress the signal FRAMES to generate the signal VIDEO.

The cropping, downsampling, blending, stabilization, packetization, encoding, compression and/or conversion performed by the processor 112 may be varied according to the design criteria of a particular implementation. For example, the signal VIDEO may be a processed version of the signal FRAMES configured to fit the target area to the shape and/or specifications of the playback device 54 and/or to emulate a view from the perspective of the drone 52. For example, the playback device 54 may be implemented for real-time video streaming of the signal VIDEO received from the apparatus 100.

Generally, the signal VIDEO is some view (or derivative of some view) captured by the capture device 110. The signal VIDEO may comprise a portion of the video captured by the capture device 110. The signal VIDEO may be a video frame comprising the region of interest selected and/or cropped from the video frame by the processor 112. The signal VIDEO may have a smaller size than the video frames FRAMES. In some embodiments, the signal VIDEO may provide a series of cropped and/or enhanced panoramic video frames that improves upon the view from the perspective of the drone 52 (e.g., provides night vision, provides High Dynamic Range (HDR) imaging, provides more viewing area, highlights detected objects, provides additional data such as a numerical distance to detected objects, provides visual indicators for paths of a race course, etc.).

The memory 114 may store data. The memory 114 may be implemented as a cache, flash memory, DRAM memory, etc. The type and/or size of the memory 114 may be varied according to the design criteria of a particular implementation. The data stored in the memory 114 may correspond to a video file, status information (e.g., readings from the components of the drone 52, pre-selected fields of view, user preferences, user inputs, etc.) and/or metadata information.

The communication device 58 may send and/or receive data to/from the apparatus 100. In some embodiments, the communication device 58 may be implemented as a wireless communications module. In some embodiments, the communication device 58 may be implemented as a satellite connection to a proprietary system. In one example, the communication device 58 may be a hard-wired data port (e.g., a USB port, a mini-USB port, a USB-C connector, HDMI port, an Ethernet port, a DisplayPort interface, a Lightning port, etc.). In another example, the communication device 58 may be a wireless data interface (e.g., Wi-Fi, BLUETOOTH, ZIGBEE, cellular, etc.).

Data from the components of the drone 52 may be presented to the apparatus 100 at the input 128 as the signal DIO. The number and/or types of the components of the drone 52 may be varied according to the design criteria of a particular implementation. The data from the components of the drone 52 may be used by the camera system 100 to determine a movement direction of the drone 52. In one example, location-related information may be determined by a location module (e.g., to determine weather conditions for the current location of the drone 52). For example, the location module may be implemented as a GPS sensor. Orientation information may be determined by an orientation module. For example, the orientation module may be implemented as a magnetometer, an accelerometer and/or a gyroscope. In yet another example, temperature information may be determined by a temperature module. For example, the temperature module may be implemented as a thermometer. The types of the components of the drone 52 used to

implement the location module, the orientation module, the temperature module and/or any other types of sensors may be varied according to the design criteria of a particular implementation.

Different communication channels may be implemented to transmit video and drone control. In an example, the communication module **58** may implement one communication channel to transmit video and a different communication channel for drone control (e.g., movements input by the pilot **70** using the remote control **56**). In another example, the drone **52** may comprise the communication module **58** to implement one channel to transmit the signal VIDEO and a separate remote-control (RC) transmitter to implement a different channel for drone control. Example frequencies may comprise 900 MHz, 1.2 GHz, 2.4 GHz and/or 5.8 GHz. In an example, if the drone **52** uses a RC transmitter on one of the frequencies for control, then, in order to avoid interference, another one of the frequencies should be selected for the communication module **58**. In some embodiments, an option may be provided to select a sub-frequency for each pilot. In some embodiments, the wireless communication module **58** may automatically select a sub-frequency for each pilot. For example, many video transmitters operate at 5.8 GHz. Other frequencies may be implemented. The channels used for a particular type of communication (e.g., video, region of interest data or control) and/or the frequencies used may be varied according to the design criteria of a particular implementation.

In some embodiment, the apparatus **100** may perform video stitching operations on the signal FRAMES. In one example, each of the video signal FRAMES may provide a portion of a panoramic view and the processor **112** may crop, blend, synchronize and/or align the signal FRAMES to generate the panoramic video signal VIDEO. The processor **112** may perform de-warping on the signal FRAMES. In various embodiments, the processor **112** may be configured to perform electronic image stabilization (EIS) and horizon keeping. The processor **112** may perform intelligent video analytics on the de-warped and stabilized video frames in the signal FRAMES. The processor **112** may encode the signal FRAMES to a particular format.

The cropped and/or enhanced video generated by the processor **112** may be sent to the output **124** (e.g., the signal VIDEO). In one example, the signal VIDEO may be an HDMI output. In another example, the signal VIDEO may be a composite (e.g., NTSC) output (e.g., composite output may be a low-cost alternative to HDMI output). In yet another example, the signal VIDEO may be a S-Video output. In some embodiments, the signal VIDEO may be an output sent via interfaces such as USB, SDIO, Ethernet and/or PCIe. The video signal VIDEO may be output to the wireless communication device **58**. In an example, the wireless communication device **58** may be a RF (radio frequency) transmitter.

The video generated by the processor **112** may implement high-quality video in the region of interest. The video generated by the processor **112** may be used to implement a reduced bandwidth needed for transmission by cropping out a portion of the video that has not been selected by the intelligent video analytics as the region of interest. To generate a high-quality, enhanced video using the region of interest, the processor **112** may be configured to perform encoding, blending, cropping, aligning and/or stitching.

The encoded video may be stored locally and/or transmitted wirelessly to external storage (e.g., network attached storage, cloud storage, etc.). In an example, the encoded, panoramic video may be stored locally by the memory **114**.

In another example, the encoded, panoramic video may be stored to a hard-drive of a networked computing device. In yet another example, the encoded, panoramic video may be transmitted wirelessly without storage. The type of storage implemented may be varied according to the design criteria of a particular implementation.

The processor **112** may be configured to send analog and/or digital video (e.g., the signal VIDEO) to the video communication device **58**. In some embodiments, the signal VIDEO generated by the apparatus **100** may be a composite and/or HDMI output. The processor **112** may receive an input for the video signal (e.g., the signal FRAMES) from the sensor interface **130**. The input video signal FRAMES may be enhanced by the processor **112** (e.g., color conversion, noise filtering, auto exposure, auto white balance, auto focus, etc.).

Referring to FIG. 4, a diagram is shown illustrating an improved image processing flow in accordance with an example embodiment of the invention. The improved image processing flow may be implemented by the processor **112**. In various embodiments, the processor **112** may be implemented as a digital signal processor (DSP). In an example, the digital signal processor may be implemented as a plurality of hardware units that may be configured (programmed) to implement an image processing pipeline. In an example, the plurality of hardware units may be configured to implement an improved image processing flow including (i) an image processing phase **150**, (ii) an electronic image stabilization (EIS) and horizon keeping phase **152**, and (iii) a video analytics phase **154**. The image processing pipeline may be implemented using a combination of the hardware units and software to achieve real-time correction performance on high-resolution, high frame-rate video with a low latency.

In various embodiments, the EIS and horizon keeping phase **152** generally improves the accuracy of results **156** produced by the video analytics phase **154**, especially in drone applications. In various embodiments, the (EIS) and horizon keeping phase **152** comprises an EIS portion **160** and a horizon keeping portion **162**. In various embodiments, the EIS portion **160** and the horizon keeping portion **162** may be implemented using a combination of hardware and software to achieve real-time correction performance on high-resolution, high frame-rate video with low delay. The EIS portion **160** generally performs vibration correction and image stabilization to ensure the images are as clear as possible (e.g., without blur, etc.) for processing by the video analytics phase **154**. The horizon keeping portion **162** generally maintains a substantially horizontal orientation of the image (e.g., compensated for roll, etc.) so the orientation of objects are in a proper position for improved video analytics.

In various embodiments, the electronic image stabilization and horizon keeping phase **152** may be combined with the video analytics (e.g., object tracking, motion tracking, face tracking) phase **154** to allow the algorithms to work reliably in drone designs that do not use a gimbal. Combining electronic image stabilization and horizon keeping processing with the video analytics generally enables the video analytics feature(s) to work with much higher accuracy relative to conventional designs.

In various embodiments, the intelligent video analytics performed by the video analytics phase **154** may comprise analyzing, understanding and/or interpreting digital video to produce numerical and/or symbolic information about the digital video. The numerical and/or symbolic information may be used for interpreting visual information about the

15

digital video. In an example, the intelligent video analytics may comprise computer vision.

In some embodiments, the video analytics module **154** may be configured to extract data (e.g., the numerical and/or symbolic information) from the stabilized video signal. The extracted data may be used to determine the visual content of the stabilized video. Determining the visual content may comprise recognizing objects (e.g., faces, etc.). In one example, the video analytics phase **154** may interpret the numerical and/or symbolic information to recognize that the visual data represents, for example, a person. In some embodiments, the number of pixels and/or the colors of the pixels of the stabilized video signal may be used to recognize portions of the stabilized video signal as particular objects (e.g., faces, etc.). The types of objects recognized during the video analytics phase **154** may be varied according to the design criteria of a particular implementation.

In some embodiments, the memory **114** may store numerical and/or symbolic information of known objects (e.g., the shapes/colors associated with a person, the shapes/colors associated with a vehicle, the shapes/colors associated with animals, etc.). The video analytics phase **154** may receive the information associated with known objects from the memory **114** via the signal DATA. The video analytics phase **154** may compare the information in the signal DATA with the numerical and/or symbolic information extracted from the stabilized video signal. The video analytics phase **154** may select the region of interest of the panoramic video based on the detected objects.

The intelligent video analytics phase **154** may comprise one or more functions. In one example, one of the functions implemented as part of the intelligent video analytics phase **154** may be a “person detection”. The video analytics phase **154** may identify a particular person in the video frame. In another example, one of the functions implemented as part of the intelligent video analytics phase **154** may be a “follow me” function. The video analytics phase **154** may recognize a particular object over multiple video frames (e.g., from one frame to a future frame) and follow the object. For example, the video analytics phase **154** may identify a person and follow the identified person. In another example, the video analytics phase **154** may identify the drone pilot **70**. In yet another example, the video analytics phase **154** may follow an identified player as the player engages in a sporting activity.

Referring to FIG. 5, a diagram of a still picture **170** is shown illustrating an example operation of a face detecting video analytic. In the field of image processing, video analytics techniques typically operate under an assumption of an object or object in a captured source image having a particular orientation. For example, in the picture **170**, a digital still camera is running a face detection algorithm to detect faces in the image. In various embodiments, frames **172a-172n** may be superimposed over the picture **170** to indicate detected faces.

Referring to FIG. 6, a diagram is shown illustrating an example template that may be used by a face detecting video analytic. Technically, the video analytic algorithms operate on pattern matching of a particular feature or features. In an example face detection scheme, a face within a frame **172i** may be recognized based on the location and correlation of hair, eyes, mouth, nose, and ears. The location and correlation is generally based on predetermined patterns and assumptions (e.g., orientation with respect to the horizon).

Referring to FIG. 7, a diagram is shown illustrating failure of a face detecting video analytic. If the image captured by a device does not maintain a good orientation of the target

16

face, the face detection algorithm likely will fail to detect the face and, hence, cannot work. For example if, in a captured image **175**, a face is tilted sideways (as illustrated in FIG. 7), face recognition techniques based on predetermined patterns and assumptions may fail.

Typically, in a handheld camera the tilted condition might not happen because a consumer would adjust the camera by hand to maintain the captured image stable and in a proper orientation. However, in the world of drones (or flying cameras), with the vibration from propeller as well as the movement of the drone due to flying or other natural influences (e.g., such as a strong wind), the camera may likely capture rotated images, or images with strong vibration. Both pose challenging conditions for video analytics algorithms to work reliably.

One way to solve the problem is to adopt the mechanical gimbal system that is commonly used in high-end video recording system. Such systems use gimbals to ensure the video captured always has a proper orientation, and hence is free from any tilt, rotation or vibration. However such a gimbal system is big, expensive and hard to adopt for various application where a smaller design is desired. Instead, a method in accordance with an embodiment of the invention may be implemented that combines EIS and horizon keeping to improve the video analytics results without incurring the additional costs of the complicated gimbal system.

Referring to FIG. 8, a diagram of a process **200** is shown illustrating an electronic image stabilization process in accordance with an example embodiment of the invention. In various embodiments, the process (or method) **200** may comprise a step (or stage) **202**, a step (or stage) **204**, a step (or stage) **206**, a step (or stage) **208**, a step (or stage) **210**, and a step (or stage) **212**. In the step **202**, the process **200** may sample data from a gyroscopic sensor of the drone **52**. In the step **204**, the process **200** may detect X/Y/Z axes transitions. In the steps **206** and **208**, the process **200** may match axis transition samples with captured image data. In the step **210**, the process **200** may compensate the captured image data for X/Y axis transitions by performing an X/Y offset. In the step **212**, the process **200** may compensate the captured image data for Z axis transitions by performing a Z offset. The process **200** may be used to implement the electronic image stabilization portion **160**. When the image data has been compensated, the compensated image data may be passed from the electronic image stabilization portion **160** to the horizon keeping portion **162**.

Referring to FIG. 9, a diagram of a process **300** is shown illustrating a horizon keeping (stabilization) process in accordance with an example embodiment. In various embodiments, the process (or method) **300** may comprise a step (or stage) **302**, a step (or stage) **304**, a step (or stage) **306**, and a step (or stage) **308**. In the step **302**, the process **300** collects G-sensor data samples. In the step **304**, the process **300** collects gyroscopic data samples. In the step **306**, the process **300** computes the horizon level of the drone **52** (e.g., roll and pitch angles) based on the samples collected in the steps **302** and **304**. In the step **308**, the process **300** performs a rotational offset to maintain a horizon of the image represented by the image data received in the step **310** from the EIS portion **160**. The process **300** may be used to implement the horizon keeping portion **162**. When the image data has been compensated for orientation with the horizon, the compensated image data may be passed from the EIS and horizon keeping phase **152** to the video analytics phase **154**.

Referring to FIG. 10, a diagram of a camera system **400** is shown illustrating an example implementation of a com-

puter vision system in accordance with an embodiment of the present invention. In one example, the electronics of the camera system **400** may be implemented as one or more integrated circuits. In an example, the camera system **400** may be built around a processor/camera chip (or circuit) **402**. In an example, the processor/camera chip **402** may be implemented as an application specific integrated circuit (ASIC) or system on chip (SOC). The processor/camera circuit **402** generally incorporates hardware and/or software/firmware that may be configured to implement the processors, circuits, and processes described above in connection with FIGS. 1-9.

In an example, the processor/camera circuit **402** may be connected to a lens and sensor assembly **90**. In some embodiments, the lens and sensor assembly **90** may be a component of the processor/camera circuit **402** (e.g., a SoC component). In some embodiments, the lens and sensor assembly **90** may be a separate component from the processor/camera circuit **402** (e.g., the lens and sensor assembly may be an interchangeable component compatible with the processor/camera circuit **402**). In some embodiments, the lens and sensor assembly **90** may be part of a separate camera connected to the processor/camera circuit **402** (e.g., via a video cable, a high definition media interface (HDMI) cable, a universal serial bus (USB) cable, an Ethernet cable, or wireless link).

The lens and sensor assembly **90** may comprise a block (or circuit) **92** and/or a block (or circuit) **94**. The circuit **92** may be associated with a lens assembly. The circuit **94** may be an image sensor. The lens and sensor assembly **90** may comprise other components (not shown). The number, type and/or function of the components of the lens and sensor assembly **90** may be varied according to the design criteria of a particular implementation.

The lens assembly **92** may capture and/or focus light input received from the environment near the camera **60**. The lens assembly **92** may capture and/or focus light for the image sensor **94**. The lens assembly **92** may implement an optical lens. The lens assembly **92** may provide a zooming feature and/or a focusing feature. The lens assembly **92** may be implemented with additional circuitry (e.g., motors) to adjust a direction, zoom and/or aperture of the lens assembly **92**. The lens assembly **92** may be directed, tilted, panned, zoomed and/or rotated to provide a targeted view of the environment near the camera **60**.

The image sensor **94** may receive light from the lens assembly **92**. The image sensor **94** may be configured to transform the received focused light into digital data (e.g., bitstreams). In some embodiments, the image sensor **94** may perform an analog to digital conversion. For example, the image sensor **94** may perform a photoelectric conversion of the focused light received from the lens assembly **92**. The image sensor **94** may present converted image data as a color filter array (CFA) formatted bitstream. The processor/camera circuit **402** may transform the bitstream into video data, video files and/or video frames (e.g., human-legible content).

The processor/camera circuit **402** may also be connected to the memory **114**, which may include dynamic random access memory (DRAM), the communication device **58**, an optional audio input/output circuit including an audio codec **404**, a microphone **406** and a speaker **408**, non-volatile memory (e.g., NAND flash memory) **410**, a removable media **412** (e.g., SD, SDXC, etc.), one or more serial (e.g., RS-485, RS-232, etc.) devices **414**, and one or more universal serial bus (USB) devices (e.g., a USB host **416**).

In various embodiments, the processor/camera circuit **402** may comprise a block (or circuit) **420**, a block (or circuit) **422**, a block (or circuit) **424**, a block (or circuit) **426**, a block (or circuit) **428**, a block (or circuit) **430**, a block (or circuit) **434**, a block (or circuit) **436**, a block (or circuit) **438**, a block (or circuit) **440**, and/or a block (or circuit) **442**. The circuit **420** may be a processor circuit. In various embodiments, the circuit **420** may include one or more embedded processors (e.g., ARM, etc.). The circuit **422** may be a computer vision coprocessor circuit. The circuit **424** may be a digital signal processing (DSP) module. In some embodiments, the circuit **424** may implement separate image DSP and video DSP modules. The circuit **426** may be a storage interface. The circuit **426** may interface the processor/camera circuit **402** with the DRAM **114**, the non-volatile memory **410**, and the removable media **412**.

The circuit **428** may implement a local memory system. In some embodiments, the local memory system **428** may comprise a cache (e.g., L2CACHE), a direct memory access (DMA) engine, graphic direct memory access (GDMA) engine, fast random access memory, etcetera. The circuit **430** may implement a sensor input (or interface). The circuit **432** may implement one or more control interfaces including but not limited to an inter device communication (IDC) interface, an inter integrated circuit (I²C) interface, a serial peripheral interface (SPI), and a pulse width modulation (PWM) interface. The circuit **434** may implement an audio interface (e.g., an I²S interface, etc.). The circuit **436** may implement a clock circuit including but not limited to a real time clock (RTC), a watchdog timer (WDT), and/or one or more programmable timers. The circuit **438** may implement an input/output (I/O) interface. The circuit **440** may be a video output module. The circuit **442** may be a communication module. The circuits **420** through **442** may be connected to each other using one or more buses, interfaces, traces, protocols, etc.

The circuit **410** may be implemented as a nonvolatile memory (e.g., NAND flash memory, NOR flash memory, etc.). The circuit **412** may comprise one or more removable media cards (e.g., secure digital media (SD), secure digital extended capacity media (SDXC), etc.). The circuit **414** may comprise one or more serial interfaces (e.g., RS-485, RS-232, etc.). The circuit **416** may be an interface for connecting to or acting as a universal serial bus (USB) host. The circuit **58** may be a wireless interface for communicating with a user device (e.g., a smart phone, a computer, a tablet computing device, cloud resources, etc.). In various embodiments, the circuits **404-416** may be implemented as components external to the processor/camera circuit **402**. In some embodiments, the circuits **404-416** may be components on-board the processor/camera circuit **402**.

The control interface **432** may be configured to generate signals (e.g., IDC/I²C, STEPPER, IRIS, AF/ZOOM/TILT/PAN, etc.) for controlling the lens and sensor assembly **90**. The signal IRIS may be configured to adjust an iris for the lens assembly **920**. The interface **430** may enable the processor/camera circuit **402** to control the lens and sensor assembly **90**.

The storage interface **426** may be configured to manage one or more types of storage and/or data access. In one example, the storage interface **426** may implement a direct memory access (DMA) engine and/or a graphics direct memory access (CDMA). In another example, the storage interface **426** may implement a secure digital (SD) card interface (e.g., to connect to the removable media **412**). In various embodiments, programming code (e.g., executable instructions for controlling various processors and encoders

of the processor/camera circuit **402**) may be stored in one or more of the memories (e.g., the DRAM **114**, the NAND **410**, etc.). When executed by the processor **420**, the programming code generally causes one or more components in the processor/camera circuit **402** to configure video synchronization operations and start video frame processing operations. The resulting compressed video signal may be presented to the storage interface **426**, the video output **440** and/or communication interface **442**. The storage interface **426** may transfer program code and/or data between external media (e.g., the DRAM **114**, the NAND **410**, the removable media **412**, etc.) and the local (internal) memory system **428**.

The sensor input **430** may be configured to send/receive data to/from the image sensor **94**. In one example, the sensor input **430** may comprise an image sensor input interface. The sensor input **430** may be configured to transmit captured images (e.g., picture element, pixel, data) from the image sensor **94** to the DSP module **424**, the processor **420** and/or the coprocessor **422**. The data received by the sensor input **430** may be used by the DSP **424** to determine a luminance (Y) and chrominance (U and V) values from the image sensor **94**. The sensor input **430** may provide an interface to the lens and sensor assembly **90**. The sensor input interface **430** may enable the processor/camera circuit **402** to capture image data from the lens and sensor assembly **90**.

The audio interface **434** may be configured to send/receive audio data. In one example, the audio interface **434** may implement an audio inter-IC sound (I²S) interface. The audio interface **434** may be configured to send/receive data in a format implemented by the audio codec **404**.

The DSP module **424** may be configured to process digital signals. The DSP module **424** may comprise an image digital signal processor (IDSP), a video digital signal processor DSP (VDSP) and/or an audio digital signal processor (ADSP). The DSP module **424** may be configured to receive information (e.g., pixel data values captured by the image sensor **94**) from the sensor input **430**. The DSP module **424** may be configured to determine the pixel values (e.g., RGB, YUV, luminance, chrominance, etc.) from the information received from the sensor input **430**. The DSP module **424** may be further configured to support or provide a sensor RGB to YUV raw image pipeline to improve image quality, bad pixel detection and correction, demosaicing, white balance, color and tone correction, gamma correction, adjustment of hue, saturation, brightness and contrast adjustment, chrominance and luminance noise filtering.

The I/O interface **438** may be configured to send/receive data. The data sent/received by the I/O interface **438** may be miscellaneous information and/or control data. In one example, the I/O interface **438** may implement one or more of a general purpose input/output (GPIO) interface, an analog-to-digital converter (ADC) module, a digital-to-analog converter (DAC) module, an infrared (IR) remote interface, a pulse width modulation (PWM) module, a universal asynchronous receiver transmitter (UART), an infrared (IR) remote interface, and/or one or more synchronous data communications interfaces (IDC SPI/SSI).

The video output module **440** may be configured to send video data. For example, the processor/camera circuit **402** may be connected to an external device (e.g., a TV, a monitor, a laptop computer, a tablet computing device, etc.). The video output module **440** may implement a high-definition multimedia interface (HDMI), a PAL/NTSC interface, an LCD/TV/Parallel interface and/or a DisplayPort interface.

The communication module **442** may be configured to send/receive data. The data sent/received by the communi-

cation module **442** may be formatted according to a particular protocol (e.g., BLUETOOTH, USB, Wi-Fi, UART, etc.). In one example, the communication module **442** may implement a secure digital input output (SDIO) interface. The communication module **442** may include support for wireless communication by one or more wireless protocols such as Bluetooth®, ZigBee®, Institute of Electrical and Electronics Engineering (IEEE) 802.11, IEEE 802.15, IEEE 802.15.1, IEEE 802.15.2, IEEE 802.15.3, IEEE 802.15.4, IEEE 802.15.5, and/or IEEE 802.20, GSM, CDMA, GPRS, UMTS, CDMA2000, 3GPP LTE, 4G/HSPA/WiMAX, SMS, etc. The communication module **442** may also include support for communicating using one or more of the universal serial bus protocols (e.g., USB 1.0, 2.0, 3.0, etc.). The processor/camera circuit **402** may also be configured to be powered via a USB connection. However, other communication and/or power interfaces may be implemented accordingly to meet the design criteria of a particular application.

The processor/camera circuit **402** may be configured (e.g., programmed) to control the one or lens assemblies **92** and the one or more image sensors **94**. The processor/camera circuit **402** may receive raw image data from the sensor(s) **94**. The processor/camera circuit **402** may encode the raw image data into a plurality of encoded video streams simultaneously (in parallel). The plurality of video streams may have a variety of resolutions (e.g., VGA, WVGA, QVGA, SD, HD, Ultra HD, 4K, etc.). The processor/camera circuit **402** may receive encoded and/or uncoded (e.g., raw) audio data at the audio interface **434**. The processor/camera circuit **402** may also receive encoded audio data from the communication interface **442** (e.g., USB and/or SDIO). The processor/camera circuit **402** may provide encoded video data to the wireless interface **442** (e.g., using a USB host interface). The wireless interface **442** may include support for wireless communication by one or more wireless and/or cellular protocols such as BLUETOOTH, ZIGBEE, IEEE 802.11, IEEE 802.15, IEEE 802.15.1, IEEE 802.15.2, IEEE 802.15.3, IEEE 802.15.4, IEEE 802.15.5, IEEE 802.20, GSM, CDMA, GPRS, UMTS, CDMA2000, 3GPP LTE, 4G/HSPA/WiMAX, SMS, etc. The processor/camera circuit **402** may also include support for communication using one or more of the universal serial bus protocols (e.g., USB 1.0, 2.0, 3.0, etc.).

The functions and structures illustrated in the diagrams of FIGS. **1** to **10** may be designed, modeled, emulated, and/or simulated using one or more of a conventional general purpose processor, digital computer, microprocessor, microcontroller, distributed computer resources and/or similar computational machines, programmed according to the teachings of the present specification, as will be apparent to those skilled in the relevant art(s). Appropriate software, firmware, coding, routines, instructions, opcodes, microcode, and/or program modules may readily be prepared by skilled programmers based on the teachings of the present disclosure, as will also be apparent to those skilled in the relevant art(s). The software is generally embodied in a medium or several media, for example non-transitory storage media, and may be executed by one or more of the processors sequentially or in parallel.

Embodiments of the present invention may also be implemented in one or more of ASICs (application specific integrated circuits), FPGAs (field programmable gate arrays), PLDs (programmable logic devices), CPLDs (complex programmable logic device), sea-of-gates, ASSPs (application specific standard products), and integrated circuits. The circuitry may be implemented based on one or more hardware description languages. Embodiments of the pres-

ent invention may be utilized in connection with flash memory, nonvolatile memory, random access memory, read-only memory, magnetic disks, floppy disks, optical disks such as DVDs and DVD RAM, magneto-optical disks and/or distributed storage systems.

The terms “may” and “generally” when used herein in conjunction with “is(are)” and verbs are meant to communicate the intention that the description is exemplary and believed to be broad enough to encompass both the specific examples presented in the disclosure as well as alternative examples that could be derived based on the disclosure. The terms “may” and “generally” as used herein should not be construed to necessarily imply the desirability or possibility of omitting a corresponding element.

While the invention has been particularly shown and described with reference to embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made without departing from the scope of the invention.

The invention claimed is:

1. An apparatus comprising:

an image sensor configured to generate a sequence of video frames based on a targeted view of an environment; and

a processor configured to (i) collect data samples from a gravity sensor (G-sensor) and a gyroscopic sensor, (ii) detect X/Y/Z axes transitions using the data samples from said gyroscopic sensor, (iii) perform, in real-time, electronic image stabilization comprising (a) matching axes transition samples with captured image data of the sequence of video frames and (b) generating stabilized captured image data by compensating the captured image data for X/Y axes transitions using an X/Y offset and compensating the captured image data for Z axis transitions using a Z offset, (iv) compute a horizon level based on the data samples from said G-sensor and the data samples from said gyroscopic sensor, (v) perform, in real-time, a rotational offset compensation on the stabilized captured image data of the sequence of video frames to maintain alignment of a respective horizon in each frame of the sequence of video frames with the computed horizon level, and (vi) generate video analytics for the sequence of video frames using the compensated and stabilized captured image data, wherein the electronic image stabilization and rotational offset compensation provides improved accuracy of the video analytics generated for the sequence of video frames.

2. The apparatus according to claim 1, further comprising one or more sensors configured to capture movement information used to determine the electronic image stabilization applied to the captured image data prior to the rotational offset compensation.

3. The apparatus according to claim 2, wherein said one or more sensors comprise at least one of an inertial measurement unit and an accelerometer.

4. The apparatus according to claim 1, wherein said video analytics comprise face detection.

5. The apparatus according to claim 1, wherein said video analytics comprise face tracking.

6. The apparatus according to claim 1, wherein said apparatus is part of an unmanned aerial vehicle.

7. The apparatus according to claim 1, wherein (i) said processor comprises a digital signal processing hardware module and (ii) said electronic image stabilization is performed on said captured image data by said digital signal processing hardware module prior to the rotational offset compensation.

8. The apparatus according to claim 7, wherein said digital signal processing hardware module is further configured to perform said rotational offset compensation on said stabilized captured image data to maintain said horizon level of said targeted view.

9. The apparatus according to claim 1, wherein said apparatus is implemented as a system on chip (SoC).

10. A method of performing video analytics comprising: generating a sequence of video frames based on a targeted view of an environment using a video camera;

collecting, using a processor, data samples from a gravity sensor (G-sensor) and a gyroscopic sensor;

detecting X/Y/Z axes transitions, using said processor, based on the data samples from said gyroscopic sensor;

performing, in real-time using said processor, electronic image stabilization comprising (i) matching axes transition samples with captured image data of the sequence of video frames and (ii) generating stabilized captured image data by compensating the captured image data for X/Y axes transitions using an X/Y offset and compensating the captured image data for Z axis transitions using a Z offset;

computing, using said processor, a horizon level based on the data samples collected from said G-sensor and the data samples collected from said gyroscopic sensor;

performing, in real-time using said processor, a rotational offset compensation on the stabilized captured image data of the sequence of video frames to maintain alignment of a respective horizon in each frame of the sequence of video frames with the computed horizon level; and

generating video analytics for the sequence of video frames using the compensated and stabilized captured image data, wherein the electronic image stabilization and rotational offset compensation provides improved accuracy of the video analytics generated for the sequence of video frames.

11. The method according to claim 10, wherein said video analytics comprise face detection.

12. The method according to claim 10, wherein said video analytics comprise face tracking.

13. The method according to claim 10, wherein said video camera is part of an unmanned aerial vehicle.

14. The method according to claim 10, further comprising performing vibration correction on the sequence of video frames.

15. The method according to claim 10, further comprising using one or more sensors to capture movement information used to determine the electronic image stabilization applied to the captured image data prior to the rotational offset compensation.

16. The method according to claim 15, wherein said one or more sensors comprise at least one of an inertial measurement unit and an accelerometer.