



US010744649B2

(12) **United States Patent**
Lewis

(10) **Patent No.:** **US 10,744,649 B2**

(45) **Date of Patent:** **Aug. 18, 2020**

(54) **DRONE PAYLOAD SYSTEM**

(56) **References Cited**

(71) Applicant: **GearWurx**, Nibley, UT (US)

U.S. PATENT DOCUMENTS

(72) Inventor: **Collin Lewis**, Nibley, UT (US)

(73) Assignee: **GearWurx**, Nibley, UT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

9,641,810 B2 *	5/2017	Zufferey	G05D 1/0094
9,764,838 B2 *	9/2017	Priest	B64C 39/024
9,841,761 B2 *	12/2017	Shehata	H04N 7/181
9,988,140 B2 *	6/2018	Priest	B64C 27/06
10,384,804 B2 *	8/2019	Priest	B64D 47/08
2009/0050750 A1 *	2/2009	Goossen	B64C 39/024
			244/76 R
2011/0221692 A1 *	9/2011	Seydoux	G06F 3/04817
			345/173
2012/0226394 A1 *	9/2012	Marcus	A62B 5/00
			701/2
2015/0142211 A1 *	5/2015	Shehata	H04N 7/181
			701/2
2016/0244187 A1 *	8/2016	Byers	B64C 39/024
2016/0309346 A1 *	10/2016	Priest	B64C 39/024
2016/0353669 A1 *	12/2016	Xavier	B25J 18/025
2019/0054630 A1 *	2/2019	Lewis	B25J 13/06

(21) Appl. No.: **16/105,868**

(22) Filed: **Aug. 20, 2018**

(65) **Prior Publication Data**

US 2019/0054630 A1 Feb. 21, 2019

Related U.S. Application Data

(60) Provisional application No. 62/547,331, filed on Aug. 18, 2017.

(51) **Int. Cl.**

B25J 13/06	(2006.01)
G05D 1/00	(2006.01)
B64D 9/00	(2006.01)
B25J 15/00	(2006.01)
B64C 39/02	(2006.01)
B25J 15/08	(2006.01)
B25J 15/02	(2006.01)

(52) **U.S. Cl.**

CPC **B25J 13/06** (2013.01); **B25J 15/0033** (2013.01); **B25J 15/022** (2013.01); **B25J 15/086** (2013.01); **B64C 39/024** (2013.01); **B64D 9/00** (2013.01); **G05D 1/0016** (2013.01); **B64C 2201/146** (2013.01)

(58) **Field of Classification Search**

None
See application file for complete search history.

* cited by examiner


Primary Examiner — Bhavesh V Amin

(74) *Attorney, Agent, or Firm* — Kunzler Bean & Adamson

(57) **ABSTRACT**

A drone payload device includes a remote drone arm and a control module. The remote drone arm is coupleable to a drone. The remote drone arm includes a base, an arm, and a gripper. The base includes mounting hardware to couple to the drone. The arm extends from the base. The gripper is coupled to the arm at an end of the arm distal from the base. The control module is coupleable to a drone controller. The control module is to provide a control signal to the remote drone arm to control a movement of at least one of the arm and the gripper.

20 Claims, 12 Drawing Sheets






FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B1




FIG. 5B2




FIG. 6




FIG. 7




FIG. 8




FIG. 9

1000
↙




FIG. 10

DRONE PAYLOAD SYSTEM**CROSS-REFERENCES TO RELATED APPLICATIONS**

This application claims the benefit of U.S. Provisional Patent Application No. 62/547,331 entitled "DRONE PAYLOAD SYSTEM" and filed on 18 Aug. 2017 for Collin Lewis, which is incorporated herein by reference.

FIELD

This invention relates to remote-control drones and more specifically to an accessory for a remote-control drone.

BACKGROUND**Description of the Related Art**

Remote control drones are vehicles or platforms that are controlled via signals sent to the drone. In some cases, the drone returns a signal such as a sensor reading or camera feed. Drones provide access to areas or vantages that are unsafe or are not easily accessible. Drones generally carry a fuel or power source onboard as well as a drive system and a control system.

SUMMARY

A drone payload device is disclosed. The drone payload device includes a remote drone arm and a control module. The remote drone arm is coupleable to a drone. The remote drone arm includes a base, an arm, and a gripper. The base includes mounting hardware to couple to the drone. The arm extends from the base. The gripper is coupled to the arm at an end of the arm distal from the base. The control module is coupleable to a drone controller. The control module is to provide a control signal to the remote drone arm to control a movement of at least one of the arm and the gripper.

A drone cargo system is also disclosed. The drone cargo system includes a drone, a remote drone arm, and a control module. The remote drone arm is coupleable to the drone. The remote drone arm includes a base, an arm, and a gripper. The base includes mounting hardware to couple to the drone. The arm extends from the base. The gripper is coupled to the arm at an end of the arm distal from the base. The control module is coupleable to a drone controller. The control module is to provide a control signal to the remote drone arm to control a movement of at least one of the arm and the gripper.

A method of operation a remote drone arm is also disclosed. The method includes receiving an input at a control interface of a control module capable of being coupled to a drone controller. The method also includes generating an outgoing control signal at the control module. The method also includes sending the outgoing control signal to the remote drone arm capable being coupled to a drone. The method also includes receiving the outgoing control signal at the remote drone arm. The method also includes executing the outgoing control signal at the remote drone arm to move one or more components of the remote drone arm.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the advantages of the invention will be readily understood, a more particular description of the invention briefly described above will be rendered by ref-

erence to specific embodiments that are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention, and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings, in which:

FIG. 1 is a perspective view illustrating one embodiment of a remote drone arm system;

FIG. 2A is a perspective view illustrating one embodiment of a remote drone arm;

FIG. 2B is a perspective view illustrating another embodiment of a remote drone arm;

FIG. 3A is a perspective view illustrating one embodiment of a gripper of a remote drone arm in an open position;

FIG. 3B is a perspective view illustrating one embodiment of the gripper of FIG. 3A in a partially closed position;

FIG. 3C is a perspective view illustrating one embodiment of the gripper of FIG. 3A in a fully closed position;

FIG. 3D is a perspective view illustrating another embodiment of the gripper of FIG. 3A with a compliance spring and a locking linkage in a fully closed position;

FIG. 3E is a side view illustrating one embodiment of the gripper of FIG. 3D in the fully closed position;

FIG. 3F is a side view illustrating one embodiment of the gripper of FIG. 3D in a partially open position;

FIG. 4A is a perspective view illustrating one embodiment of a linkage assembly of a remote drone arm in a deployed position;

FIG. 4B is a perspective view illustrating one embodiment of the linkage assembly of FIG. 4A in a stowed position;

FIG. 5A is a perspective view illustrating one embodiment of a mounting structure of a remote drone arm;

FIG. 5B1 is a perspective view illustrating one embodiment of a quick coupling mounting hardware of a remote drone arm in an open position;

FIG. 5B2 is a perspective view illustrating one embodiment of a quick coupling mounting hardware of a remote drone arm in a closed position;

FIG. 6 is a side view illustrating one embodiment of an offset mounting arrangement for a remote drone arm;

FIG. 7 is a perspective view illustrating one embodiment of a control module of a remote drone arm system;

FIG. 8 is a perspective view illustrating one embodiment of the control module of FIG. 7 coupled to a drone controller;

FIG. 9 is a schematic view illustrating one embodiment of a drone cargo system; and

FIG. 10 is a flowchart illustrating one embodiment of a method of using a remote drone arm.

DETAILED DESCRIPTION

Reference throughout this specification to "one embodiment," "an embodiment," or similar language means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, appearances of the phrases "in one embodiment," "in an embodiment," and similar language throughout this specification may, but do not necessarily, all refer to the same embodiment, but mean "one or more but not all embodiments" unless expressly specified otherwise. The terms "including," "comprising," "having," and variations thereof mean "including but not limited to" unless expressly specified otherwise. An enumerated listing of items does not imply that any or all of the items are mutually

exclusive and/or mutually inclusive, unless expressly specified otherwise. The terms “a,” “an,” and “the” also refer to “one or more” unless expressly specified otherwise.

In the above description, certain terms may be used such as “up,” “down,” “upper,” “lower,” “upward,” “downward,” “horizontal,” “vertical,” “left,” “right,” and the like. These terms are used, where applicable, to provide some clarity of description when dealing with relative relationships. But, these terms are not intended to imply absolute relationships, positions, and/or orientations. For example, with respect to an object, an “upper” surface can become a “lower” surface simply by turning the object over. Nevertheless, it is still the same object. Further, the terms “including,” “comprising,” “having,” and variations thereof mean “including but not limited to” unless expressly specified otherwise.

Additionally, instances in this specification where one element is “coupled” to another element can include direct and indirect coupling. Direct coupling can be defined as one element coupled to and in some contact with another element. Indirect coupling can be defined as coupling between two elements not in direct contact with each other, but having one or more additional elements between the coupled elements. Further, as used herein, securing one element to another element can include direct securing and indirect securing. Additionally, as used herein, “adjacent” does not necessarily denote contact. For example, one element can be adjacent another element without being in contact with that element.

As used herein, the phrase “at least one of” or “one or more”, when used with a list of items, means different combinations of one or more of the listed items may be used and only one of the items in the list may be needed. The item may be a particular object, thing, or category. In other words, “at least one of” means any combination of items or number of items may be used from the list, but not all of the items in the list may be required. For example, “at least one of item A, item B, and item C” may mean item A; item A and item B; item B; item A, item B, and item C; or item B and item C. In some cases, “at least one of item A, item B, and item C” may mean, for example, without limitation, two of item A, one of item B, and ten of item C; four of item B and seven of item C; or some other suitable combination.

The flowcharts included herein are generally set forth as logical flow chart diagrams. As such, the depicted order and labeled steps are indicative of one embodiment of the presented method. Other steps and methods may be conceived that are equivalent in function, logic, or effect to one or more steps, or portions thereof, of the illustrated method. Additionally, the format and symbols employed are provided to explain the logical steps of the method and are understood not to limit the scope of the method. Although various arrow types and line types may be employed in the flow chart diagrams, they are understood not to limit the scope of the corresponding method. Indeed, some arrows or other connectors may be used to indicate only the logical flow of the method. For instance, an arrow may indicate a waiting or monitoring period of unspecified duration between enumerated steps of the depicted method. Additionally, the order in which a particular method occurs may or may not strictly adhere to the order of the corresponding blocks shown.

These features and advantages of the embodiments will become more fully apparent from the following description and appended claims, or may be learned by the practice of embodiments as set forth hereinafter. As will be appreciated

by one skilled in the art, aspects of the present invention may be embodied as a system, method, and/or computer program product.

The schematic flowchart diagrams and/or schematic block diagrams in the Figures illustrate the architecture, functionality, and operation of possible implementations of apparatuses, systems, and methods according to various embodiments of the present invention. In this regard, each block in the schematic flowchart diagrams and/or schematic block diagrams may represent a module, segment, or portion of code, which comprises one or more executable instructions of the program code for implementing the specified logical function(s).

It should also be noted that, in some alternative implementations, the functions noted in the block may occur out of the order noted in the Figures. For example, two blocks shown in succession may, in fact, be executed substantially concurrently, or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved. Other steps and methods may be conceived that are equivalent in function, logic, or effect to one or more blocks, or portions thereof, of the illustrated Figures.

Although various arrow types and line types may be employed in the flowchart and/or block diagrams, they are understood not to limit the scope of the corresponding embodiments. Indeed, some arrows or other connectors may be used to indicate only the logical flow of the depicted embodiment. For instance, an arrow may indicate a waiting or monitoring period of unspecified duration between enumerated steps of the depicted embodiment. It will also be noted that each block of the block diagrams and/or flowchart diagrams, and combinations of blocks in the block diagrams and/or flowchart diagrams, can be implemented by special purpose hardware-based systems that perform the specified functions or acts, or combinations of special purpose hardware and program code.

Embodiments described herein relate to a remote drone arm which adds object manipulation capabilities to a drone platform. Some embodiments of the remote drone arm provide an independent add-on device which can be added to a drone platform without interfering with other components of the drone. Some embodiments of the remote drone arm are incorporated into the drone during manufacture of the drone.

Some embodiments of the remote drone arm include an arm assembly that attaches to the drone platform with independent power, control, and signal components. Other embodiments of the remote drone arm rely on a central power source of the drone. Some embodiments of the remote drone arm include a control module which can be coupled to a drone controller to provide a control interface for the arm assembly without the need for a separate item to be handled apart from the drone controller.

Some embodiments of the remote drone arm provide the ability to interface with an object while the drone is static/landed or while the drone is dynamic/flying. Some embodiments of the remote drone arm add a payload or cargo carrying/retrieving/delivering capacity to a drone platform. Some embodiments provide the ability to remotely position the arm across a plurality of axes and manipulate the gripper from the drone controller.

Some embodiments of the remote drone arm have mechanical linkages with mechanical advantages to conserve power while providing the necessary force and movement to position the arm and manipulate an object. Additional details and examples are described below with reference to the several figures.

5

FIG. 1 is a perspective view illustrating one embodiment of a remote drone arm system 100. The illustrated embodiment includes a remote drone arm 102 attached to a drone 104. The remote drone arm 102 is coupled to a base 106 of the remote drone arm 102.

In some embodiments, the base 106 includes mounting hardware 108. In some embodiments, the mounting hardware 108 is attached to a portion of the drone 104. In the illustrated embodiment, the mounting hardware 108 is attached to the landing strut 110 of the drone 104. In some embodiments, the mounting hardware 108 has a geometry fit to a geometry of the landing strut 110 of the drone 104. The mounting hardware 108 is described in more detail below with reference to FIG. 5A.

In some embodiments, the mounting hardware 108 includes a locking structure. In some embodiments, the mounting hardware 108 includes a quick coupling to provide ease of attaching and removing the base 106. Examples of a quick coupling are described in more detail below with reference to FIGS. 5B1 and 5B2.

In the illustrated embodiment, the mounting hardware 108 is pivotably coupled to the base 106. In some embodiments, pivoting the base 106 relative to the mounting hardware 108 moves the remote drone arm 102. In the illustrated embodiment, the remote drone arm 102 is coupled to the base 106 in an off-center location on the base 106. In some embodiments, the off-center location of the remote drone arm 102 on the base 106 is to accommodate a component 112 under-mounted on the drone 104. In the illustrated embodiment, the remote drone arm 102 accommodates a camera mounted on the drone 104. In other embodiments, the component 112 includes a sensor suite, one or more cameras, or other equipment.

In the illustrated embodiment, the remote drone arm 102 includes a gripper 114 at an end of the remote drone arm 104 distal to the base 106. In some embodiments, the gripper 114 is operable to apply a gripping force to an object to secure the object for transport or manipulation. Embodiments of the gripper 114 are described in more detail below with reference to FIGS. 3A-C.

In the illustrated embodiment, the drone 104 is a multi-rotor drone with a plurality of rotors 116. In some embodiments, the drone 104 includes four rotors 116. In other embodiments, the drone 104 includes fewer or more than four rotors 116. In some embodiments, the drone 104 is capable of remote-piloted or pre-programmed flight. In some embodiments, the drone 104 receives control signals from a drone controller (not shown). In other embodiments, the drone 104 stores flight information and executes the stored flight information. In some embodiments, the drone 104 operates on a combination of real-time and stored commands.

In some embodiments, the drone 104 receives a control signal separately from a control signal received at the remote drone arm 102. In other embodiments, the drone 104 and the remote drone arm 102 receive a combined control signal. In some embodiments, there is no communication between the drone 104 and the remote drone arm 102. In other embodiments, the drone 104 and the remote drone arm 102 communicate one with another.

FIG. 2A is a perspective view illustrating one embodiment of a remote drone arm 200. The illustrated embodiment includes an arm 202. In the illustrated embodiment, the arm 202 is partially curved. In some embodiments, the curve in the arm 202 allows the arm 202 to operate through a range of motion without interfering with other components or structure of a drone. For example, the geometry of the arm

6

202 may allow the arm 202 to operate through a range of motion around a sensor package of a drone to which the remote drone arm 200 is coupled.

In some embodiments, the arm 202 is capable of at least one of pitch, yaw, roll, and extension movements. In some embodiments, the structure of the arm 202 itself allows for one or more of these movements. For example, the arm 202 may include one or more joints, pivots, or telescoping sections. In other embodiments, movement of the arm 202 is facilitated by other structures or characteristics of the remote drone arm 200.

In some embodiments, the arm 202 has a cross section that is at least partially rounded. In other embodiments, the arm 202 has a cross section that is at least partially angled. In some embodiments, the arm 202 has a hybrid cross section with both rounded and angled portions. In some embodiments, the arm 202 is hollow. In some embodiments, the arm 202 is reinforced.

In some embodiments, the cross section of the arm 202 varies depending on location along the arm 202. For example, the cross section of the arm 202 near an end may be wider than at a middle portion of the arm 202. In some embodiments, the geometry of the arm 202 varies subtly without pronounced transitions. In other embodiments, the geometry of the arm 202 varies abruptly with pronounced transitions from a first geometry to a second geometry.

In some embodiments, the arm 202 is rigid. In other embodiments, the arm 202 is flexible. For example, the arm 202 may include one or more flex points along the arm 202 at which the arm 202 may bend under the force of a load, gravity, or a drive system such as a servo motor. In other embodiments, the arm 202 may be a linkage which includes multiple rigid parts which move with respect to one another. In some embodiments, the arm 202 includes rotational and angular movement components.

In the illustrated embodiment, the arm 202 is coupled to the base 204. In some embodiments, the arm 202 is permanently or removably coupled to the base 204. For example, the arm 202 may be permanently fixed to the base 204 to prevent accidental detachment of the arm 202 from the base 204 resulting in loss of a payload carried by the arm 202. The arm 202 may also be removably coupled to the base 204 to facilitate changing the arm 202 to accommodate a specific operation or functionality.

For example, one version of the arm 202 may have a specific attachment, capacity, speed, arrangement, or other characteristics. that is suited for a specific mission or purpose. Another version of the arm 202 may have other characteristics which are suited to another mission or purpose. Swapping of the arm 202 to provide a functionality corresponding to a mission may be advantageous.

In the illustrated embodiment, the base 204 includes mounting hardware 206. In the illustrated embodiment, two mounting hardware 206 are included. In other embodiments, one or more than two mounting hardware 206 are used. In the illustrated embodiment, the mounting hardware 206 is a bolted cap coupler to be secured to a leg or landing strut of a drone. In other embodiments, the mounting hardware 206 includes a clamp, a hook, a through-bolt, or other hardware capable of providing sufficient force to secure the remote drone arm 200 to a drone. As described above the mounting hardware 206 may include a quick coupling feature to facilitate easy removal and installation. For example, the quick coupling feature may include a hinge and an attachment structure such as a thumbscrew, a snap, a latch, a clip, a friction lock, a clasp, or other retaining structures. In some embodiments, the attachment structure is captive relative to

the mounting hardware **206**. In other embodiments, the attachment structure is removable or separable relative to the mounting hardware **206**.

In the illustrated embodiment, at least one of the mounting hardware **206** is coupled to the base **204** via a linkage assembly **208**. In some embodiments, the linkage assembly **208** applies a force to the mounting hardware **206** to move the base **204** relative to the mounting hardware **206**. In the illustrated embodiment, the linkage assembly **208** is a two-bar rocker-rocker linkage to provide rotational movement of the base **204** relative to the mounting hardware **206**. Embodiments of the mounting hardware **206** are described in greater detail below with respect to FIGS. 5A-5B2.

In some embodiments, the linkage assembly **208** is driven by a servo or other driving force. In some embodiments, the movement of the linkage assembly **208** is electronically controlled. In some embodiments, the movement of the linkage assembly **208** and relative position of the linkage assembly **208** is tracked. Further details regarding embodiments of the linkage are included below with reference to FIG. 4A-B.

The illustrated embodiment of the base **204** also includes a connection point **210**. In some embodiments, the connection point **210** facilitates connection of a power or data source to the base **204**. For example, a cord to supply power to an internal battery of the base **204** may be connected at the connection point **210**. In another example, a data connection may be established via the connection point **210** to provide data to the base **204** of the remote drone arm **200**. Data may include commands to move the remote drone arm **200** based on a movement schedule or programming. Data may also include positional calibration for movement of the linkage assembly **208**. Other data may also be used, accessed, and/or communicated via the connection point **210**.

The illustrated embodiment of the base **204** also includes an indicator **212**. In some embodiments, the indicator **212** is an electronic or physical indicator to communicate a status of the remote drone arm **200**. In some embodiments, the indicator **212** communicates a charge status, connection status, movement status, capacity status, range status, or other status of the remote drone arm **200**.

In the illustrated embodiment, the remote drone arm **200** also includes a gripper **214**. In the illustrated embodiment, the gripper **214** is attached to an end of the arm **202** distal from the base **204**. In the illustrated embodiment, the gripper **214** includes two fingers **216** and a thumb **218**. In some embodiments, the gripper **214** is oriented substantially parallel relative to the arm **202**. In other embodiments, the gripper **214** is oriented at an angle relative to the arm **202**. In some embodiments, the gripper **214** is oriented at an angle relative to the arm **202** to facilitate manipulation of an object by the gripper **214** while the arm **202** is positioned at a downward angle.

In some embodiments, the angle of the gripper **214** relative to the arm **202** facilitates retrieval of an object by the gripper **214** while a drone, to which the remote drone arm **200** is coupled, is in flight. For example, if the drone is moving forward and the arm **202** is in a deployed position, the angle of the gripper **214** allows the fingers **216** to act as both a hook and a pincer to secure the object.

In some embodiments, the gripper **214** is capable of at least one of pitch, yaw, roll, and extension movements relative to the arm **202** in addition to actuation of the fingers **216** and thumb **218**. In the illustrated embodiment, the fingers **216** and thumb **218** actuate by each rotating at the gripper **216** towards one other in a scissor-like motion in

which the thumb **218** rotates to pass between the fingers **216**. This puts the fingers **216** and thumb **214** in double-shear.

In some embodiments, movement of at least one of the gripper **214** and the arm **202** is controlled manually by a manual input at a control interface of a control module in communication with the remote drone arm **200**. In other embodiments, movement of at least one of the gripper **214** and the arm **202** is computer controlled. In some embodiments, movement of at least one of the gripper **214** and the arm **202** occur in response to signals received from one or more sensors or detection systems.

In some embodiments, the arm **202** includes one or more sensors. In some embodiments, the sensors are placed in the gripper **214** or in the structure of the arm **202** apart from the gripper **214**. In some embodiments, sensors facilitate guided movement or action of the arm **202** and/or the gripper **214**. For example, the sensors may provide a target lock for an object to be retrieved and the remote drone arm **200** may send commands to the drone to navigate within a retrieval distance of the object. In some examples, the remote drone arm **200** may execute further commands to retrieve the object upon detection that the object is within the retrieval distance.

In some embodiments, the sensors facilitate automated operation of the gripper **214**. For example, the sensors may detect a proximity of the object to be retrieved and actuate the gripper **214** to secure the object. In some embodiments, the sensors provide information to generate closure instructions describing a degree of closure for the gripper **214** to secure the object. Further functionality may be achieved through the addition or incorporation of sensors on or near the remote drone arm **200**.

In some embodiments, the fingers **216** and the thumb **218** are synchronized by a mechanical connection between the fingers **216** and the thumb **218**. In other embodiments, the fingers **216** and the thumb **218** move independent of one another. The illustrated embodiment of the gripper **214** also includes a housing **220**. In some embodiments, the housing **220** at least partially encloses a servo motor or other drive system to move the fingers **216** and/or thumb **218**. Further details regarding embodiments of the gripper **214** are described below with reference to FIGS. 3A-C.

The illustrated embodiment also includes an external antenna **222a**. In some embodiments, the external antenna **222a** is arranged to extend from the base **204** in a direction opposite the arm **202**. In other embodiments, the external antenna **222a** extends parallel, orthogonal, or at another angle relative to the arm **202** or other structure of the remote drone arm **200**.

In the illustrated embodiment, the remote drone arm **200** includes an internal antenna **222b** disposed within the arm **202**. In some embodiments, the internal antenna **222b** reduces the likelihood of conflict with a drone platform, components of the drone platform, or with other surroundings of the remote drone arm **200**. In some embodiments, the internal antenna **222b** extends within the arm **202** from the base **204** to the gripper **214**. In other embodiments, the internal antenna **222b** extends partially to the gripper **214** within the arm **202**. In some embodiments, a first portion of the antenna **222** is internal to the remote drone arm **200** and a second portion of the antenna **222** is external to the remote drone arm **200**.

In some embodiments, the remote drone arm **200** includes a single antenna **222**. In other embodiments, the remote drone arm **200** includes at least two antennas **222** for redundancy or other improvements in communication. In

some embodiments, the remote drone arm **200** includes a plurality of antennas in a plurality of arrangements.

FIG. 2B is a perspective view illustrating another embodiment of a remote drone arm. In the illustrated embodiment, the remote drone arm **200** includes a slightly different geometry from that shown and described above with reference to FIG. 2A. In the illustrated embodiment, the remote drone arm **200** includes a reinforced structure **224** in the arm **202**. In some embodiments, the reinforced structure **224** is a stinger or skeletal system for reinforcing the arm **202**. In some embodiments, addition of the reinforced structure **224** reduces the weight and/or improve the stiffness of the arm **202**.

In the illustrated embodiment, the remote drone arm **200** also includes a stiffener element **226**. In some embodiments, the stiffener element **226** is applied to the arm **202** to stiffen the structure of the arm **202**. In some embodiments, the stiffener element **226** is a plate having a geometry matching a geometry of the arm **202**. In other embodiments, the stiffener element **226** is a tube or half-tube. In other embodiments, the stiffener element **226** has other geometries.

In some embodiments, the stiffener element **226** corresponds to a portion of the arm **202**. In other embodiments, the stiffener element **226** corresponds to the full length of the arm **202**. In some embodiments, the stiffener element **226** provides stiffness in a single direction. In other embodiments, the stiffener element **226** provides stiffness in more than one direction.

In some embodiments, the stiffener element **226** is, at least partially, made of a composite material. For example, the stiffener element **226** may include carbon fiber composite, glass fiber composite, nanotube composite, or another composite. In other embodiments, the stiffener element **226** is, at least partially, metallic. In some embodiments, the stiffener element **226** is, at least partially, ceramic. Other materials may be included in the stiffener element **226**.

In the illustrated embodiment, the gripper **214** includes an enclosed servo. In some embodiments, the gripper **214** may be sealed to reduce dust and water contamination of the gripper **214** and associated components such as sensors, servos, and other elements.

FIG. 3A is a perspective view illustrating one embodiment of a gripper **300** of a remote drone arm in an open position. In the illustrated embodiment, the gripper **300** includes a housing **302**. In some embodiments, the housing **302** is a plastic, metal, composite, ceramic, or other material. In some embodiments, the housing **302** substantially surrounds components corresponding to the gripper **300**. For example, the housing **302** may substantially surround at least one of a servo motor, a control module, a sensor, or other components.

In the illustrated embodiment, the gripper **300** also includes a thumb **304** and fingers **306**. In the illustrated embodiment, the thumb **304** is sickle-shaped. In other embodiments, the thumb **304** includes a serrated portion. In some embodiments, the serrated portion **308** provides additional grip for the gripper **300**. In some embodiments, the thumb **304** is positioned on an upper side of the remote drone arm gripper **300** to provide additional grip without presenting a possible snagging or hanging point for items upon drop or during introduction of the object to the gripper **300**. In some embodiments, the fingers **306** also include serrated portions or other structures or surface treatments to improve grip.

In the illustrated embodiment, the fingers **306** are positioned to oppose the thumb **304**. In the illustrated embodiment, two fingers **306** are aligned to pass on opposite sides

of the thumb **304** in a scissor-like closing motion. In other embodiments, the gripper **300** includes a single finger **306** or more than two fingers **306** opposite the thumb **304**. In some embodiments, the gripper **300** includes more than one thumb **304**.

In the illustrated embodiment, the thumb **304** and the fingers **306** include textured tips. In some embodiments, the textured tips provide additional grip to secure or manipulate an object or surface. In some embodiments, the textured tips are formed in the material forming the thumb **304** and fingers **306**. In other embodiments, the textured tips are a different material applied to the tips of the thumb **304** and the fingers **306**. In some embodiments, one of the thumb **304** and the fingers **306** includes a textured tip while the other does not.

In some embodiments, the tips of at least one of the thumb **304** and the fingers **306** is tapered to reduce the likelihood of the tip binding and preventing the thumb **304** and the fingers **306** from passing into double shear. In other embodiments, at least one of the thumb **304** and the fingers **306** have a taper applied to the length of the at least one of the thumb **304** and the fingers **306**.

In some embodiments, the thumb **304** and fingers **306** are formed of a material having a high strength-to-weight ratio. In some embodiments, the material forming the thumb **304** and the fingers **306** is a composite. In some embodiments, the composite is a carbon fiber matrix composite. In other embodiments, a metal or plastic forms one or more of the thumb **304** and the fingers **306**.

In the illustrated embodiment, the thumb **304** and fingers **306** are skeletonized or have material removed to result in a frame-like form to reduce weight while maintaining strength and rigidity. In some embodiments, at least one of the thumb **304** and the fingers **306** are reinforced. For example, the fingers **306** may be reinforced by joining the fingers **306** together at one or more points along a length of the fingers **306**.

In some embodiments, at least one of the thumb **304** and the fingers **306** includes a spring structure to provide grip and reduce a potential for damage to one or more drive systems controlling movement of the at least one of the thumb **304** and/or fingers **306**. For example, at least one of the thumb **304** and fingers **306** may include a deformable material to allow for deflection in the structure or shape of at least one of the thumb **304** and fingers **306**.

In another embodiment, the gripper **300** includes a spring element between a drive system of at least one of the thumb **304** and the fingers **306** which allows for deflection in the spring element to maintain grip and reduce a potential for data to the drive system. For example, if the gripper **300** is engaged with an object, the drive system may receive a command and attempt to reach a particular position with the thumb **304** and/or fingers **306**. Because at least a portion of the object is between thumb **304** and fingers **306**, the object prevents the gripper **300** from reaching the position specified by the command. To prevent the drive system from generating heat and potentially failing, the spring element allows the drive system to reach the command position and still maintain gripping force on the object.

In the illustrated embodiment, the thumb **304** and the fingers **306** interface with each other at a synchronization interface **310**. In the illustrated embodiment, the synchronization interface **310** includes a toothed portion on each of the thumb **304** and the fingers **306** which interact to synchronize movement of the thumb **304** and the fingers **306**. In some embodiments, synchronization of the thumb **304** and the fingers **306** allows a driving force to be applied to one of the

11

thumb **304** and the fingers **306** to drive the thumb **304** and the fingers **306** simultaneously. In some embodiments, each of the thumb **304** and the fingers **306** has a dedicated drive system to apply force with the synchronization interface **310** synchronizing the movement of the thumb **304** and the fingers **306** without providing the sole driving force for one or the other of the thumb **304** and the fingers **306**.

In some embodiments, the synchronization interface **310** includes a linked connection. In other embodiments, the synchronization interface **310** includes a smooth friction interface. Other embodiments include other mechanical, magnetic, or electrical approaches for synchronizing movement of the thumb **304** and the fingers **306**.

In some embodiments, the synchronization interface **310** includes an enclosed interface or shielding to prevent material or an object from jamming the synchronization interface **310**. In some embodiments, the synchronization interface **310** provides similar motion in the thumb **304** and the fingers **306**. In other embodiments, the synchronization interface **310** facilitates movement of one of the thumb **304** and the fingers **306** at a different rate from the other of the thumb **304** and the fingers **306**.

In some embodiments, at least one of the thumb **304** and the fingers **306** includes an indicator to visually or electronically indicate a relative displacement or state of at least one of the thumb **304** and the fingers **306**. For example, at least one of the thumb **304** and the fingers **306** includes an optical marking or plurality of markings to visually indicate a relative position of the thumb **304** and the fingers **306**. In other embodiments, at least one of the thumb **304** and the fingers **306** includes a sensor or emitter to communicate a location or state of at least one of the thumb **304** and the fingers **306**.

In some embodiments, the sensors or visual indicators are visible to the camera to facilitate visual feedback of the relative position of the fingers **306** and thumb **304** and the gripper **300** generally. In some embodiments, the visual indicators include a coating or other coloration difference. In other embodiments, the visual indicators include a visible structure incorporated into at least one of the fingers **306** and the thumb **304**.

FIG. 3B is a perspective view illustrating one embodiment of the gripper **300** of FIG. 3A in a partially closed position. In the illustrated embodiment, a thumb **304** and fingers **306** of the gripper **300** are partially closed with the thumb **304** passing in double shear between the fingers **306**. In some embodiments, the thumb **304** and fingers **306** impact at the tips in a closed position leaving an open region between the thumb **304** and finger **306**.

In some embodiments, at least one of the thumb **304** and the fingers **306** includes a physical stop to stop the other of thumb **304** and the fingers **306**. In some embodiments, the stop prevents overtravel of at least one of the thumb **304** and the fingers **306** relative to the other. In some embodiments, the stop prevents damage to or provides a resting position for at least one of the thumb **304** and the fingers **306**, prevents damage to or energy consumption of a servo motor or other movement control system, or prevents impact of at least one of the thumb **304** and the fingers **306** on another component of a drone or remote drone arm. In other embodiments, the stop provides structural support between the fingers **306** or within the structure of the thumb **304**.

FIG. 3C is a perspective view illustrating one embodiment of the gripper **300** of FIG. 3A in a fully closed position. In the illustrated embodiment, a thumb **304** and fingers **306** of the gripper **300** are closed in a dual bypass arrangement with the thumb **304** passing between the finger **306**. In other

12

embodiments, the thumb **304** moves along an outside of the fingers **306** instead of between the fingers **306**.

In some embodiments, the thumb **304** is fixed and the fingers **306** move to close the gripper **300** as illustrated. In other embodiments, the fingers **306** are fixed and the thumb **304** moves to close the gripper **300** as illustrated. Other movement and fixture schemes are also contemplated.

FIG. 3D is a perspective view illustrating another embodiment of the gripper **300** of FIG. 3A with a compliance element **318** and a locking linkage **312** in a fully closed position. In the illustrated embodiment, the locking linkage **312** reaches a fully extended position which corresponds with a fully closed position of the gripper **300**. While the thumb **304** and fingers **306** of the gripper **300** are shown as fully closed with a relatively small amount of space separating the thumb **304** and fingers **306**, in other embodiments, the fully closed position may include having the thumb **304** and fingers **306** separated by less space or more space. In some embodiments, the relative position of the thumb **304** and fingers **306** with the linkage **312** in the locked position is adjustable.

In the fully extended position, the linkage **312** uses relatively little energy to maintain the thumb **304** and fingers **306** in the closed position. In some embodiments, this may be referred to as a low-energy position. A low energy position may be achieved at at least one of a fully closed position, a fully open position, and an intermediate position. This reduces strain on the gripper **300** and energy demand.

The compliance element **318** is disposed on a base component **314** of the fingers **306**. The compliance element **318** is configured to deflect or experience a change in geometry which allows for more reliable gripping of a rigid object. Additionally, the compliance element **318** may provide a broader range of positions of the gripper **300** which will yield sufficient grip for a given object.

In some embodiments, the compliance element **318** provides the ability of the user to vary a gripping force from a light force to a heavy force proportional to a position input for the gripper **300**. This may serve to prevent damage to the gripper **300** at the thumb **304** and finger **306**, provide a more reliable grip, and reduce strain and energy variables for the servo motor or other drive system of the gripper **300**.

In the illustrated embodiment, the compliance element **318** comprises a coil spring. In some embodiments, the compliance element may comprise a piston, a bar spring, a gel element, or the like. In the illustrated embodiment, the compliance element **318** is positioned on a base component **314** of the fingers **306** with the fingers **306** coupled to the base element **306** via attachment features **316** such as screws or other hardware or structures. In some embodiments, the thumb **304** may include a compliance element **318**. In other embodiments, a compliance element is disposed on at least one of the thumb **304** and fingers **306** separately and/or individually.

FIG. 3E is a side view illustrating one embodiment of the gripper of FIG. 3D in the fully closed position.

FIG. 3F is a side view illustrating one embodiment of the gripper of FIG. 3D in a partially open position. In this embodiment, the locking linkage **312** has moved from the low-energy position and has begun to open the thumb **304** and finger **306** relative to one another. As described above, the gripper **300** may be configured to reach a second low-energy position as the gripper **300** reaches a fully-open position.

FIG. 4A is a perspective view illustrating one embodiment of a linkage assembly **400** of a remote drone arm in a deployed position. In the illustrated embodiment, the linkage

assembly 400 includes mounting hardware 402 coupled to a base 404 of a remote drone arm. In the illustrated embodiment, the mounting hardware 402 facilitates connection to a location of a drone. For example, the mounting hardware 402 may clamp to a landing gear or other structure of a drone. In some embodiments, the mounting hardware 402 remains fixed relative to the drone while the base 404 moves relative to the drone. In some embodiments, the mounting hardware 402 is a fixed or removable connection. In some embodiments, the mounting hardware 402 is a quick coupling.

In some embodiments, the base 404 is similar to base 204 described above with reference to FIG. 2A. Other embodiments may include variations of the base 204 described above. In the illustrated embodiment, the linkage assembly 400 also includes a mount link 406 and a base link 408. In some embodiments, the mount link 406 and the base link 408 are mechanical linkages. In some embodiment, the mount link 406 and the base link 408 are elongated rigid structures that are rotatably coupled at one or both ends. In some embodiments, at least one of the mount link 406 and the base link 408 receives a force input to drive one or both of the mount link 406 and the base link 408.

In some embodiments, the base 404 includes a drive system (not shown) to apply a force to the base link 408 to rotate or otherwise move the base link 408 relative to the base 404. In some embodiments, the base link 408 is rotatably coupled to the mount link 406 and applies a force to the mount link 406 in response to movement of the base link 408. In response to the force received at the mount link 406, the mount link 406 applies a force to the mounting hardware 402. In some embodiments, the force applied to the mounting hardware 402 moves the base 404 relative to the mounting hardware 402.

In another embodiment, the mounting hardware 402 includes a drive system to apply force to the mount link 406 to move the base 404 relative to the mounting hardware 402. In some embodiments, the drive system is coupled to the base 404. In other embodiments, the drive system is coupled to the mounting hardware 402. Other embodiments include other driving system arrangements.

In the illustrated embodiment, the mount link 406 is rotatably coupled to the mounting hardware 402 and the base link 408. In some embodiments, the mount link 406 slides relative to the at least one of the mounting hardware 402 and the base link 408. In some embodiments, the base link 408 slides relative to at least one of the mount link 406 and the base 404.

In some embodiments, the mount link 406 is rotatably coupled to the mounting hardware 402 via a link coupler 410. In some embodiments, the link coupler 410 includes a spacer to separate the mounting hardware 402 from the base 404 to provide sufficient space for installation and operation of the mount link 406 and the base link 408.

In the illustrated embodiment, the linkage assembly 400 is oriented with the base link 408 and the mount link 406 fully extended to tilt the base 404 relative to the mounting hardware 402. In some embodiments, with the base 404 tilted with respect to the mounting hardware 402, the linkage assembly is deployed to extend an arm attached to the base 404 for manipulating an object.

In some embodiments, in the deployed arrangement, the linkage assembly 400 includes the base link 408 and the mount link 406 in an aligned position. In some embodiments, the aligned position of the base link 408 relative to the mount link 406 provides a mechanical advantage in the linkage assembly 400. In some embodiments, the mechani-

cal advantage provides an improvement in stability of the linkage assembly 400. In other embodiments, the mechanical advantage provides a reduction in power required to maintain the deployed position of the linkage assembly 400. For example, in the deployed position, the linkage assembly 400 may apply relatively little to no torque on the associated drive system. In some embodiments, the mechanical advantage reduces battery and/or component wear and improves lifespan of the battery and/or component.

In the illustrated embodiment, the mounting hardware 402 is held relatively close to a corresponding end of the base 404. In other embodiments, the linkage assembly 400 moves the base 404 further from the mounting hardware 402. In some embodiments, the linkage assembly positions the base 404 to prevent or reduce blocking of one or more sensors or movement of a component of a drone platform as described in further detail below with respect to FIG. 6.

FIG. 4B is a perspective view illustrating one embodiment of the linkage assembly 400 of FIG. 4B in a stowed position. In the illustrated embodiment, the linkage 400 is in a stowed position with the base link 408 substantially parallel to the mount link 406.

Similar to the deployed position described above with relation to FIG. 4A, the stowed position illustrated in FIG. 4B approximately aligns the mount link 406 and the base link 408. In some embodiments, the stowed position of the linkage assembly 400 provides a mechanical advantage. In some embodiments, mechanical advantage of the stowed position of the linkage assembly 400 provides the same or similar benefits to those described above with relation to FIG. 4A. For example, in the stowed position, the linkage assembly 400 may apply relatively little to no torque on an associated drive system. Other advantages are also realized.

FIG. 5A is a perspective view illustrating one embodiment of a mounting structure 500 of a remote drone arm. In the illustrated embodiment, the mounting structure 500 is a structure coupled to a mounting hardware 502. In some embodiments, the mounting structure 500 provides additional interface to secure the mounting hardware 502 to a portion of a drone.

In the illustrated embodiment, the mounting structure 500 has a wedge-like geometry to interface with an interior structure of a landing strut of a drone. For example, the mounting structure 500 may match up with a ribbed portion within the structure of the landing strut of the drone.

In other embodiments, the mounting structure 500 has a non-wedge. For example, the mounting structure 500 may be rounded or planar, have square or non-square edges, and/or be rigid, semi-rigid, or flexible. In some embodiments, the mounting structure 500 includes a texture, grip material, or other structure or feature to provide increased stability and precise orientation of the mounting hardware 502 during operation of a remote drone arm.

FIG. 5B1 is a perspective view illustrating one embodiment of a quick coupling mounting hardware 502 of a remote drone arm in an open position. In the illustrated embodiment, the mounting hardware 502 includes a quick coupling 504. In the illustrated embodiment, the quick coupling 504 is shown in the open position. In some embodiments, the quick coupling 504 includes a hinge 506. In some embodiments, the hinge 506 allows the quick coupling 504 to open into the illustrated position.

The illustrated embodiment also includes an attachment structure 508. In the illustrated embodiment, the attachment structure 508 is a thumbs screw. In other embodiments, the

attachment structure **508** includes one of a thumbscrew, a snap, a latch, a clip, a friction lock, a clasp, or other retaining structures.

FIG. 5B2 is a perspective view illustrating one embodiment of a quick coupling mounting hardware **502** of a remote drone arm in a closed position. In the illustrated embodiment, the mounting hardware **502** includes the quick coupling **504** in the closed position. In some embodiments, the quick coupling **504** is in the closed position when the attachment structure **508** is engaged with the mounting hardware **502** to secure the quick coupling **504**.

In some embodiments, the quick coupling **508** includes a mounting structure such as the mounting structure **500** shown in FIG. 5A. In some embodiments, the quick coupling **508** is custom fit to a particular geometry corresponding to a particular drone or drone model. In other embodiments, the quick coupling **508** is compatible with a plurality of drones and/or drone models. In some embodiments, the quick coupling **508** is swappable relative to the mounting hardware **502** to facilitate attachment of a compatible quick connect **504**.

FIG. 6 is a side view illustrating one embodiment of an offset mounting arrangement **600** for a remote drone arm **602**. In the illustrated embodiment, the remote drone arm **602** is mounted on a drone platform **604**. In some embodiments, the remote drone arm **602** is capable of mounting to a landing strut **606** of the drone platform **604**. In other embodiments, the remote drone arm **602** mounts to another structure or surface of the drone platform **604**.

In the illustrated embodiment, the remote drone arm **602** is mounted in an offset mounting arrangement **600** moving a base **612** of the remote drone arm **602** away from a centerline of the drone platform **604** to reduce or avoid conflict between the remote drone arm **602** and one or more components or features of the drone platform **604**.

In some embodiments, the offset mounting arrangement **600** of the remote drone arm **602** avoids conflict between the arm **608** of the remote drone arm **602** and a sensor package **610** of the drone platform **604**. In other embodiments, the offset mounting arrangement **600** avoids conflict between a base **612** of the remote drone arm **602** and the drone platform **604**. In some embodiments, the offset mounting arrangement **600** of the remote drone arm **602** reduces or prevents detrimental incursion of the remote drone arm **602** into a sensor or camera field of view. In other embodiments, the offset mounting arrangement **600** of the remote drone arm **602** reduces or prevents signal interference between the remote drone arm **602** and the drone platform **604**.

In some embodiments, the offset mounting arrangement **600** avoids conflict between a gripper **614** of the remote drone arm **602** and the drone platform **604**. In some embodiments, the offset mounting arrangement **600** is achieved by a geometry of a linkage assembly **616**. In other embodiments, the offset mounting arrangement **600** is achieved by a geometry of a mounting hardware **620**. In some embodiments, other structures of the remote drone arm **602** move the base **612** out away from the centerline of the drone platform **604**.

FIG. 7 is a perspective view illustrating one embodiment of a control module **700** of a remote drone arm system. In the illustrated embodiment, the control module **700** includes a housing **702**. In some embodiments, the housing **702** forms an outer protective enclosure for internal components of the control module **700**. In some embodiments, the housing **702** includes one or more materials. In some embodiments, the housing **702** is at least partially made of plastic, metal, composite, or other materials. In some embodiments, the

geometry of the housing **702** corresponds with a geometry of a drone platform. For example, the geometry of the housing **702** may correspond to a drone platform from DJI™.

In the illustrated embodiment, the control module **700** includes an antenna **704**. In the illustrated embodiment, the antenna **704** is hingedly coupled to the housing **702**. In some embodiments, the antenna **704** is fixed at some angle relative to the housing **702**. In some embodiments, the antenna **704** is removeable from the housing **702**. In other embodiments, the antenna **704** is permanently attached to the housing **702**.

In some embodiments, the antenna **704** is integrated along an interior of the housing **702**. For example, the antenna **704** may be positioned within the housing **702**. For example, the antenna **704** may run along at least a portion of the interior of the housing **702** on an edge of the housing **702** so as not to protrude from the housing **702**. In some embodiments, the antenna **704** is arranged to lay on a surface of the housing **702**. In some embodiments, the antenna **704** is incorporated with another portion of the control module **700**.

In the illustrated embodiment, the control module **700** includes one or more control interfaces **706**. In the illustrated embodiment, the control interfaces **706** are sliders. In some embodiments, the control interfaces **706** include one or more of a joystick, a button, a touch interface, a switch, a wheel, a directional pad, a rocker, or a key. Other interface devices may also be included.

In some embodiments, the control interfaces **706** are activated in response to a power on input. In other embodiments, the control interfaces **706** are activated in response to detection that the control module **702** is coupled to a drone controller. In some embodiments, the control interfaces are activated in response to a determination that the drone controller is active. Other activation triggers are also contemplated.

In the illustrated embodiment, two control interfaces **706** are shown. In other embodiments, one or more than two control interfaces **706** are included. In the illustrated embodiment, the control interfaces **706** are shown on the same surface and general area as one another. In some embodiments, the control interfaces **706** are located on different parts of the housing **702**.

In some embodiments, the control interfaces **706** are together. In other embodiments, the control interfaces **706** are separated to opposite sides of the housing **702** to correspond to holding locations for the drone controller **802**. In the illustrated embodiment, the orientation or action of the control interfaces **706** is substantially similar. In some embodiments, the orientation of one of the control interfaces **706** is different from the orientation of the other.

In some embodiments, the control interfaces **706** are located on the control module **700** at locations which correspond to a hand position of a drone controller of a drone. For example, the control interfaces **706** may be located on the control module **700** to be at or near the position of a user's fingers while they are holding the drone controller. In one example, a user may use their thumbs to control the flight of a drone while they use their forefingers to operate the control interfaces **706** to move a remote drone arm.

The illustrated embodiment of the control module **700** also includes support structures **708**. In the illustrated embodiment, the support structures **708** protrude from the housing **702** of the control module **700**. In some embodiments, the support structures **708** provide physical support to the control module **700** when the control module **700** is set down on a resting surface such as the ground, a table, a floor, etc.

17

In some embodiments, the support structures **708** have sufficient geometry to provide enough clearance for the control interfaces **706** to avoid contact with the resting surface. In some embodiments, the support structures **708** provide a location on the housing **702** to receive wear and impact during use. In some embodiments, the support structures **708** include a material which is resistant to wear and breakage. In some embodiments, the support structure **708** include a replaceable component that absorbs impact and wear. While the illustrated embodiment depicts two support structures **708**, other embodiments include one or more than two support structures **708**.

The illustrated embodiment of the control module **700** includes retaining structures **710**. In some embodiments, the retaining structures **710** form locations in the housing **702** at which a drone controller is secured. In some embodiments, the retaining structures **710** have a hook-like geometry to snap onto a bar or similar structure of a drone controller. In other embodiments, the retaining structures **710** include a snap, post, magnet, buckle, clip, claw, friction lock, screw, tab, groove, raised portion, or other structure to interface with and at least partially secure the control module to a drone controller.

In some embodiments, the control module **700** includes internal components. In some embodiments, the internal components include a power source. For example, the power source may include a battery, an electrical connector, or other system to supply power to the control module **700**. In some embodiments, the control module **700** includes a connector to facilitate charging or exchanging of data.

In some embodiments, the internal components include a communication system coupled to the antenna **704**. In some embodiments, the communication system communicates, via the antenna **704**, with the remote drone arm such as that described above with reference to FIG. **2**. In some embodiments, the communication system communicates separately from a communication system of a drone controller to communicate with the drone platform. In other embodiments, the communication of the control module **700** interacts with the drone controller to communicate with the remote drone arm.

In some embodiments, the control module **700** includes a display. In some embodiments, the display indicates a state of the control module **700** or an associated remote drone arm. For example, the display may indicate a charge state of at least one of the control module **700** and the remote drone arm. In another example, the display may indicate communication strength relating to the communication link between the control module **700** and the remote drone arm. In a further example, the display may indicate a position or state of the remote drone arm such as stowed, deployed, degree of deployment, gripper opened, gripper closed, gripper degree of close, object secured in gripper, or other statuses or states relating to the control module, remote drone arm, drone controller, or drone platform.

FIG. **8** is a perspective view illustrating one embodiment of the control module **702** of FIG. **7** coupled to a drone controller **802**. In the illustrated embodiment, the control module **702** is coupled to the drone controller **802** by securing the retaining structures **710** to a structure of the drone controller **802**. In the illustrated embodiment, the retaining structures **710** interface with a bar **804** of the drone controller **802**.

In some embodiments, the retaining structures **710** apply a retaining force to the bar **804** to secure the control module **702** relative to the drone controller **802**. In some embodiments, the retaining structures **710** clamp onto the bar **804**

18

but allow the control module **702** to hinge about the bar **804**. In some embodiments, the control module **702** further includes locking structures **806**.

In some embodiments, the locking structures **806** secure the control module **702** in a fixed position relative to the drone controller **802**. In some embodiments, the locking structures **806** include a raised portion on the control module **702** near the retaining structures **710** which engage the bar **804** when the control module **702** is rotated to a locking position. In some embodiments, the locking structures **806** apply a retaining force to the bar **804** to resist movement of the control module out of the locking position.

In some embodiments, the locking position is a position of the control module **702** relative to the drone controller **802** which places the control interface **706** within reach of a user while operating the drone controller **802**. In some embodiments, the locking position facilitates communication of at least one of data and power between the drone controller **802** and the control module **702**.

In some embodiments, the locking structure **806** includes a raised structure on the surface of the control module **702**. In other embodiments, the locking structure **806** includes a strap, clip, clamp, pin, hook, catch, post, toggle, or other mechanism or structure.

In some embodiments, the locking structure **806** automatically engages with the bar **804** or other structure of the drone controller **802** in response to positioning of the control module **702** in the locking position relative to the drone controller **802**. In other embodiments, the locking structure **806** is manually manipulated to secure the control module **702** relative to the drone controller **802**.

FIG. **9** is a schematic view illustrating one embodiment of a drone cargo system **900**. In the illustrated embodiment, a drone **902** is outfitted with a remote drone arm **904**. In some embodiments, the remote drone arm **904** is similar to the remote drone arm **200** described above with reference to FIG. **2**. In the illustrated embodiment, the remote drone arm **904** is coupled to a landing strut **906** of the drone **902** by a mounting hardware **908**. In some embodiments, the mounting hardware **908** is similar to the mounting hardware **402** described above with respect to FIGS. **4A** and **4B**.

In the illustrated embodiment, the drone cargo system **900** includes a perch **910**. In some embodiments, the perch **910** provides a structure to support the drone **902** during a loading or unloading stage of a cargo transport. In the illustrated embodiment, the perch **910** interfaces with one or more landing struts **906** of the drone **902**. In some embodiments, the perch **910** allows the remote drone arm **904** to be extended to receive or release an object. In some embodiments, the perch **910** provides sufficient clearance for the remote drone arm **904** to be extended and manipulate an object. In other embodiments, the structure of the perch **910** provides sufficient clearance for the drone to land **902** and/or take off with an object secured in the remote drone arm **904**. In some embodiments, the perch **910** includes a holding structure (not shown) to receive or present the object at the remote drone arm **904**.

In some embodiments, the perch **910** includes one or more guidance assist components to allow the drone to execute a guided landing or take-off relative to the perch **910**. In some embodiments, the sensor components include radio-frequency (RF) emitters/detectors. Other embodiments include other sensors, markings, or guidance assist. In some embodiments, the drone detects the one or more guidance assist components and performs an automatic maneuver relative to the perch **910**. In other embodiments, the one or more guidance assist components provides a reference for a drone

pilot to maneuver the drone relative to the perch **910**. In some embodiments, the one or more guidance assist components are located in a leg and/or base of the perch **910**.

In the illustrated embodiment, the drone cargo system also includes a control module **912**. In some embodiments, the control module **912** generates and sends outgoing control signals to the remote drone arm **904** to control movement of the remote drone arm **904**. In some embodiments, the control module **912** receives incoming control signals from the remote drone arm **904** related to position, movement, sensor data, or other aspects of the remote drone arm **904**. In some embodiments, the control module **912** is capable of communicating with the drone **902**. In other embodiments, the control module **912** communicates with the remote drone arm **904** exclusive of the drone **902**.

While the illustrated embodiment of the drone cargo system **900** is shown with the above described components, other embodiments include fewer or more components with corresponding function and capability.

FIG. **10** is a flowchart illustrating one embodiment of a method **1000** of using a remote drone arm. In the illustrated embodiment, the method **1000** includes, at block **1002**, receiving an input at a control interface of a control module capable of being coupled to a drone controller. In some embodiments, the control interface receives the input directly from a user. In some embodiments, the control interface receives the input in the form of a signal from another device such as the drone controller.

In some embodiments, the control module is capable of being physically coupled to an underside of the drone controller. In other embodiments, the control module is capable of being physically coupled to another side, surface, or structure of the drone controller. In some embodiments, the control interface of the control module provides an interface to receive the input through mechanical manipulation, electronic detection, digital communication, or other detection systems.

In some embodiments, the control module is capable of being coupled to the drone controller by attaching to a structure of the drone controller. In some embodiments, the coupling of the control module to the drone controller is non-intrusive. In some embodiments, the control module is permanently or semi-permanently installed onto the control module. In other embodiments, the control module is an integrated component of the drone controller.

At block **1004**, the method **1000** includes generating an outgoing control signal and the control module. In some embodiments, the outgoing control signal includes one or more movement components. For example, the outgoing control signal may specify one or more of a deployment, stowage, pitch, yaw, roll, extension, grip, or bend of a linkage, arm, gripper, or other component of the remote drone arm. Other embodiments include commands or data specifying or controlling fewer or more aspects or movement of the remote drone arm.

At block **1006**, the method **1000** includes sending the outgoing control signal to a remote drone arm capable of being coupled to a drone. In some embodiments, the outgoing control signal is sent via a wired or wireless communication system or protocol. In some embodiments, the wireless communication protocol includes one of a near-field, Fresnel, far-field using radio, micro, infrared, light, ultraviolet, x-ray, gamma or other electromagnetic or non-electromagnetic communication signals.

In some embodiments, the outgoing signal is sent on a frequency or transmitted to avoid interference with a signal from the drone controller. In other embodiments, the out-

going signal piggybacks or is transmitted with a signal from the drone controller. In some embodiments, the outgoing signal is sent via an external antenna. In other embodiments, the outgoing signal is sent via an internal antenna or an integrated antenna.

In some embodiments, the remote drone arm is capable of being coupled to the drone in a non-intrusive manner. In some embodiments, the remote drone arm couples to the drone at a physical structure of the drone. In other embodiments, the remote drone arm couples to the drone via a magnetic, mechanical, or other connection. In some embodiments, the remote drone arm is an incorporated portion of the drone that is built into the drone during assembly of the drone or after the drone is assembled.

At block **1008**, the method **1000** also includes receiving the outgoing control signal at the remote drone arm. In some embodiments, the outgoing control signal is received at the remote drone arm via an external antenna of the remote drone arm. In other embodiments, the outgoing control signal is received at the remote drone arm via an internal antenna such as an antenna incorporated into an arm portion of the remote drone arm. In some embodiments, the outgoing control signal is received at the remote drone arm via an integrated antenna. Other embodiments include other antenna arrangements.

At block **1010**, the method **1000** includes executing the outgoing control signal at the remote drone arm to move one or more components of the remote drone arm. In some embodiments, executing the outgoing control signal at the remote drone arm includes moving the gripper, moving a linkage, moving a base of the remote drone arm, moving an arm of the remote drone arm, or moving another component of the remote drone arm.

In some embodiments, movement of the one or more components of the remote drone arm is monitored by a sensor. For example, the movement of the one or more components of the remote drone may be measured by a position sensor or a camera. Other manners of monitoring movement of the remote drone arm are contemplated.

The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

What is claimed is:

1. A drone payload device comprising:

a remote drone arm coupleable to a drone, the remote drone arm comprising:

a base comprising mounting hardware to couple to the drone;

an arm extending from the base; and

a gripper coupled to the arm at an end of the arm distal from the base; and

a control module coupleable to a drone controller, the control module to provide a control signal to the remote drone arm to control a movement of at least one of the arm and the gripper wherein both the remote drone arm and the control module are operable separate from the drone and the drone controller.

2. The drone payload device of claim **1**, wherein the control module is coupleable to the drone controller via a retaining structure.

21

3. The drone payload device of claim 2, wherein the retaining structure comprises a hook-like structure configured to clip onto a component of the drone controller.

4. The drone payload device of claim 1, wherein the comprising at least one control interface to configure the control signal from the control module. 5

5. The drone payload device of claim 4, wherein the at least one control interface comprises a slider.

6. The drone payload device of claim 1, wherein the mounting hardware is configured to position the remote drone arm to avoid interference with a system of the drone. 10

7. The drone payload device of claim 1, wherein the gripper comprises at least one finger and at least one thumb to grip a payload.

8. The drone payload device of claim 7, wherein the gripper comprises two fingers with the fingers positioned next to and spaced apart from one another sufficient to allow the thumb to pass between the two fingers in a scissor-like motion. 15

9. The drone payload device of claim 7, further comprising a synchronization interface to synchronize movement of the at least one finger with the at least one thumb. 20

10. The drone payload device of claim 7, wherein the gripper further comprises a compliance element disposed in at least one of the at least two fingers, the compliance spring configured to deflect in response to force applied at a corresponding at least one of the at least two fingers. 25

11. The drone payload device of claim 1, further comprising an antenna to facilitate wireless communication between at least two of the remote drone arm, the control module, the drone controller, and the drone. 30

12. The drone payload device of claim 11, wherein the antenna is an internal antenna.

13. The drone payload device of claim 12, wherein the antenna is an internal antenna disposed in the arm of the remote drone arm. 35

14. The drone payload device of claim 1, wherein the mounting hardware comprises a quick coupling to facilitate rapid coupling and uncoupling of the remote drone arm relative to the drone. 40

15. The drone payload device of claim 1, further comprising a stiffener element disposed in the arm.

16. A drone cargo system comprising:

a drone;

22

a remote drone arm coupleable to a drone to be beneath the drone and operationally separate from the drone, the remote drone arm comprising:

a base comprising mounting hardware to couple to the drone;

an arm extending from the base; and

a gripper coupled to the arm at an end of the arm distal from the base; and

a control module coupleable to a drone controller and operationally separate from the drone controller, the control module to provide a control signal to the remote drone arm to control a movement of at least one of the arm and the gripper.

17. The drone cargo system of claim 16, further comprising a perch configured to support the drone while landed in loading or unloading stage.

18. The drone cargo system of claim 16, wherein the gripper comprises three fingers with two of the fingers positioned next to and spaced apart from one another sufficient to allow the other finger to pass between the two fingers in a scissor-like motion, the motion of the fingers controlled by at least one linkage.

19. The drone cargo system of claim 18, wherein the at least one linkage comprises a plurality of linkages which reach a low-energy position at at least one of the fully open and fully closed positions.

20. A method of operating a remote drone arm, the method comprising:

receiving an input at a control interface of a control module operationally independent from a drone controller and capable of being coupled to the drone controller;

generating an outgoing control signal at the control module;

sending the outgoing control signal to the remote drone arm operationally independent from a drone and capable of being coupled to the drone;

receiving the outgoing control signal at the remote drone arm; and

executing the outgoing control signal at the remote drone arm to move one or more components of the remote drone arm.

* * * * *