



US010753715B2

(12) **United States Patent**
Garst et al.

(10) **Patent No.:** **US 10,753,715 B2**
(45) **Date of Patent:** ***Aug. 25, 2020**

(54) **LONG RANGE LARGE CALIBER FRANGIBLE ROUND FOR DEFENDING AGAINST UAVS**

(71) Applicant: **Ascendance International, LLC**, Highlands Ranch, CO (US)

(72) Inventors: **Joseph Garst**, Highlands Ranch, CO (US); **Robert Folaron**, Colorado Springs, CO (US)

(73) Assignee: **ASCENDANCE INTERNATIONAL, LLC.**, Highlands Ranch, CO (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/578,690**

(22) Filed: **Sep. 23, 2019**

(65) **Prior Publication Data**

US 2020/0033104 A1 Jan. 30, 2020

Related U.S. Application Data

(63) Continuation of application No. 16/367,881, filed on Mar. 28, 2019, now Pat. No. 10,466,023.

(60) Provisional application No. 62/716,341, filed on Aug. 8, 2018, provisional application No. 62/649,447, filed on Mar. 28, 2018.

(51) **Int. Cl.**
F42B 10/16 (2006.01)
F42B 7/08 (2006.01)
F42B 7/04 (2006.01)

(52) **U.S. Cl.**
CPC **F42B 10/16** (2013.01); **F42B 7/046** (2013.01); **F42B 7/08** (2013.01)

(58) **Field of Classification Search**
CPC F42B 7/02; F42B 7/04; F42B 7/043; F42B 7/08; F42B 10/14; F42B 10/143; F42B 10/16; F42B 10/18; F42B 10/20; F42B 12/56; F42B 12/58; F42B 12/62; F42B 12/64

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,292,374 A *	1/1919	Richardson	F42B 12/64
			102/490
3,565,010 A	2/1971	Sahlmann et al.	
3,702,588 A *	11/1972	Simmons	F42B 10/16
			102/340
3,703,866 A	11/1972	Eugene	
		(Continued)	

OTHER PUBLICATIONS

DroneDefender®; C-UAS Device [online]. Battelle Memorial Institute, 2018. [Retrieved on Apr. 27, 2018]. Retrieved from internet: <https://www.battelle.org/government-offerings/national-security/aerospace-systems/counter-UAS-technologies/dronedefender>.

(Continued)


Primary Examiner — Gabriel J. Klein

(74) *Attorney, Agent, or Firm* — Voz Patents, LLC

(57) **ABSTRACT**

The present invention is directed to a projectile configured to provide a submunition payload across a wide impact pattern, similar to that of a shotgun, at a range typically beyond the capability of standard shotgun rounds. The additional range is provided in some embodiments of the invention by allowing the tailoring deployment range of the submunition payload based upon a given threat.

13 Claims, 15 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,005,631	A	2/1977	Kaiser et al.	
4,682,546	A	7/1987	Chovich	
5,936,189	A	8/1999	Lubbers	
6,138,547	A	10/2000	Larsson et al.	
6,170,377	B1	1/2001	Larsson et al.	
6,260,484	B1	7/2001	Billings	
6,626,077	B1	9/2003	Gilbert	
6,988,450	B1	1/2006	Georgantzis et al.	
9,068,807	B1	6/2015	Thomas et al.	
9,115,965	B2	8/2015	Alculumbre	
9,879,957	B2	1/2018	Moser et al.	
9,896,221	B1	2/2018	Kilian et al.	
2010/0242775	A1*	9/2010	Schneider F41H 13/00 102/504
2013/0042783	A1	2/2013	Diller	
2016/0015499	A1	1/2016	Scott et al.	

OTHER PUBLICATIONS

DroneGun MKII; Highly Effective, Long Rangel drone Countermeasure; [online]. Dronesield, 2017. [Retrieved on Apr. 27, 2018]. Retrieved from internet: <https://www.dronesield.com/dronegun/>.

DroneGun Tactical; Highly Effective, Portable Drone Countermeasure; [online]. Dronesield, 2017. [Retrieved on Apr. 27, 2018]. Retrieved from internet: <https://www.dronesield.com/dronegun-tactical/>.

Nammo 40mm Airburst Round; Nammo BulletIN, 2018 pp. 4-7; [online]. Nammo, 2018. [Retrieved on Apr. 27, 2018]. Retrieved from internet: www.nammo.com.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B





FIG. 3C






FIG. 4




FIG. 5B




FIG. 5A




FIG. 6




FIG. 7




FIG. 8A

FIG. 8B




FIG. 9




FIG. 10A




FIG. 10B




FIG. 11

**LONG RANGE LARGE CALIBER
FRANGIBLE ROUND FOR DEFENDING
AGAINST UAVS**

CROSS REFERENCE TO REFERENCE TO
RELATED APPLICATIONS

This application is a continuing application of U.S. patent application Ser. No. 16/367,881, filed Mar. 28, 2019, which claims the benefit of U.S. Provisional Patent Application No. 62/649,447 entitled “LONG RANGE LARGE CALIBER FRANGIBLE ROUND FOR DEFENDING AGAINST UAVS” filed on Mar. 28, 2018; and U.S. Provisional Patent Application 62/716,341 entitled “LONG RANGE LARGE CALIBER FRANGIBLE ROUND FOR DEFENDING AGAINST UAVS” filed on Aug. 8, 2018—the entire contents of which are incorporated herein by reference in its entirety for all purposes.

FIELD OF THE INVENTION

The present invention is directed to a 40 mm (1.57 in) projectile round configured to provide a large submunition payload across a wide impact pattern, similar to that of a shotgun, at a range typically beyond the capability of standard shotgun rounds. The present invention relates to long range shotgun shells and similar projectiles for the destruction of CLASS I and II commercial drones and other unmanned aerial vehicles.

BACKGROUND OF THE INVENTION

Unmanned Aerial Vehicles, such as CLASS I and II commercial Aerial Drone Systems, herein referred to as drones, have become prevalent threats to privacy and safety in a wide variety of use cases. Until recently, the use of improvised explosive devices (IEDs) were responsible for approximately two-thirds of U.S. and Coalition casualties. Recent reports forecast that the use of weaponized drones will surpass the threat of IEDs in future conflicts. (Gouré, D. (2018, Feb. 8) [Retrieved from internet on 2018, Apr. 27] Drones will Surpass IED Threat in Future Conflicts. Retrieved from: <https://www.realcleardefense.com/articles/2018/02/08/drones_to_will_surpass_ied_threat_in_future_conflicts_113030.html>. Weaponization of drones, typically surrounds modifying a drone to allow it to carry and deliver lethal munitions. Weaponized drones have become increasingly common and pose a real and effective threat, particularly inside a range of 200 meters (656 feet) from a target.

Small commercial drones typically fly at altitudes below 200 meters (656 feet), and fly low and fast resulting in low exposure times. Thus, the neutralization of a drone threat is increasingly difficult as it requires detection and subsequent action. Common threat scenarios maximize the unique flight characteristics of the drones and the ability to fly low, in near proximity to the ground—whereas detection and identification of the drones is difficult.

Furthermore, the unauthorized use of drones has become problematic in environments such as search and rescue operations and emergency response efforts. For instance, reports of drones encroaching into airspace in the proximity of wildfires, pose a real threat to the operation of fire-fighting airplanes and helicopters. Airborne drones threaten the safety of crew aboard fire-fighting aircraft due to risk of collision, thereby grounding the fire-fighting aircraft until the drones are no longer encroaching in the airspace.

Due to the threat of weaponized drones, and the repeated impedance of emergency response operations there is a need for a solution for immobilizing drones with an effective range beyond the current capabilities presently available solutions.

SUMMARY OF THE INVENTION

Currently available solutions propose a variety of methods to immobilize a drone mid-flight. There is an identified need a portable solution for the immobilization of a drone which allows a user to—preferably at a range of 200 meters (656 feet) or more.

Many solutions have been proposed for the immobilization of a drone surrounding the use of jamming technologies, sometimes referred to as “directed energy”. Jamming technologies surround the use of electromagnetic noise at radio frequencies that drones operate and transmit video at, at a power level high enough to drown out effective communication between a drone and its pilot. A problem with such solutions surrounds the effects that jamming technologies have on surrounding infrastructure which maintains safety systems. For instance, a jammer intended to immobilize a drone can have negative effects on GPS systems as well as air traffic control. (O’Donnell, Michael J. A. A. E. “To Airport Sponsor.” 26 Oct. 2016. [Retrieved from internet on 2018, May 15] Retrieved from: <https://www.faa.gov/airports/airport_safety/media/UAS-Counter-Measure-Testing-letter.pdf> Furthermore, such solutions may result in a drone armed with explosives continuing toward its target due to forward momentum and falling toward its intended target with an unexploded payload. Thus, the drone, even if immobilized, poses a potential threat. In some scenarios, a jammer may result in a drone initiating a “return to home” action, in which it returns toward the operator. Although in some scenarios it is advantageous to for the initiation of such an action to allow the tracking the operator of the drone, it also poses a risk. If a drone is forced to initiate a “return to home” operation, and the operator is not found, the operator may be able to reuse the drone for a subsequent action against a target.

The use of a jamming technology is only effective as long as the jamming technology is active and directed toward a drone which poses a threat. Because portable jammer technologies require battery power, and because they disrupt radio communications sometimes critical for safety measures, the operational lifespan of such technologies is impractical for perpetual use. Thus, a drone that poses a threat must be safely disposed of prior to ceasing jamming functions. As a result, measures must be taken to dispose of, or permanently immobilize a drone prior to ceasing jamming functions.

It is an aspect of certain embodiments of the present invention to mitigate unintended negative effects which solutions such as like jammers and directed energy weapons sometimes have in an urban environment. Through the use of a kinetic defeat strategy, involving the use of ballistic particles directed at a target, it will be appreciated that the nature of this invention allows it to be both as a counter-measure against mobile targets and static targets while mitigating the shortfalls associated with some directed energy solutions.

Solutions such as jammers require personnel to carry additional equipment. This is both costly and encumbers the personnel’s mobility and ability to respond rapidly to a threat. It is an aspect of the present invention to provide effective countermeasures to immobilize and neutralize

drone threats with equipment commonly carried by law enforcement and military personnel.

Certain solutions surround the use of a drone to counter a drone which poses a threat. Drones may be used in terror attacks in both military and civilian environments. For instance, U.S. Pat. No. 9,896,221 to Kilian (“Killian”), incorporated herein in its entirety for all purposes, is directed to a drone with a net designed to ensnare other drones. This countermeasure is both more expensive than a single anti-drone projectile of the present invention, and is limited to immobilizing a single opposing drone at a time.

In certain solutions, law enforcement and military personnel use traditional weapons such as a shotgun—to attempt to immobilize a drone which poses a threat. However, weapons carried by law enforcement and military personnel, such as shotguns, are decreasingly effective at immobilizing a drone beyond 40 meters (131 feet) due to range limitations. A typical characteristic of shotgun shot is an approximately 2.5 cm (1 inch) in diameter of shot pattern, per meter distance to the target. Thus, the effective impact area of shotgun shot at 40 meters (131 feet), would be expected to be 100 cm (40 in) in diameter. However, the larger the area of the effective impact area, the larger the spacing between shotgun shot. It will be appreciated that the effective impact area refers to the area encompassing the points of impact of all payload elements, such as shot pellets, against a planar object perpendicular to the trajectory of the payload. Thus, a drone beyond 40 meters may not be immobilized by on-target shotgun shot due to spacing between shot. A drone which is within 40 meters (131 feet) of a target, poses a real threat. For instance, a drone travelling at speed which is immobilized by a shotgun may still travel 40 meters (131 feet) or more before coming to rest on the ground. Thus, the use of a shotgun to eliminate a threat posed by a drone may be ineffective in preventing the drone from reaching its intended target. As a result, there is a need for a solution for immobilizing a drone with an effective impact area at a range over 40 meters (131 feet), and more preferably with at a range of 200 meters (656 feet) or more.

Traditional weapons which are effective at 200 meters (656 feet) or more, such as rifles, surround the use of singular projectiles that are typically less than 1.3 cm (0.5 in) in diameter. Singular projectiles are not ideal for efficient immobilization of a drone, because the effective impact area of a singular projectile is limited to the profile of the singular projectile.

It is an aspect of the present invention to provide a munitions round capable of having a suitable effective impact area at a range of 200 meters (656 feet).

Existing solutions such as those disclosed by U.S. Pat. No. 9,879,957 to Moser (“Moser”), incorporated herein in its entirety for all purposes, use simple fins and deployable wall segments to stabilize and slow portions of a round. Such solutions are insufficient, in both range and amount of shot delivered as related to immobilizing a drone. The fins and wall segments as disclosed by Moser are deployed immediately upon firing to stabilize the wad and induce drag on the wad, allowing the shot held within the wad to more effectively separate from the wad. In essence, the invention of Moser allows the adjustment of patterning as related to a 40-yard target. However, Moser does not improve the effective range of a shotgun round.

Technologies such as those disclosed by U.S. Pat. No. 5,936,189 to Lubbers (“Lubbers”), incorporated herein in its entirety for all purposes, discloses a general cartridge case which acts similarly to a shotgun shell which is used existing

large caliber ammunition, such as the 40 mm (1.57 in) caliber utilized in this invention. The use of 40 mm (1.57 in) shotgun shells, such as the M576, is common in military and law enforcement applications. However, existing rounds are designed for defeating personnel a range of approximately 40 meters (131 feet).

Certain existing solutions surround the use of deployable fins for small arms to provide increased stability and accuracy for projectiles over long ranges. References such as U.S. Pat. No. 9,115,965 to Alculumbre (“Alculumbre”), incorporated herein in its entirety for all purposes, provides an example of a projectile utilizing this concept. However, Alculumbre is directed toward use with singular projectiles, such as 40 mm (1.57 in) grenades. Grenades are designed to spread fragments referred to as “flak.” While flak has a level of effectiveness in application for anti-aircraft measures, the debris pattern of flak is unpredictable and results in a significant danger when used in densely populated areas or in close proximity to unintended targets.

With the rising threat of terrorist attacks using drones in urban environments, there is also a rising need for counter-drone systems which can be both fully effective against drones and non-damaging to civilians and civilian property in proximity to the drone threat. Lead shot maintains kinetic energy well beyond 40 meters (131 feet) from deployment, resulting in a possibility for unintended casualties or collateral damage to unintended targets. Frangible lead-free shot, such as found in U.S. Pat. No. 9,587,918 to Burrow (“Burrow”), incorporated herein in its entirety for all purposes, can be used for the shot used in this invention.

Certain embodiments comprise shot using material as disclosed in U.S. Provisional Patent Application No. 62/573,632 to Folaron (“Folaron”), filed on Oct. 17, 2017, which is incorporated by reference herein in its entirety for all purposes. The frangible material of Folaron provides kinetic energy capable of destroying drones within 40 meters (131 feet) of deployment from the projectile. However, the frangible material of Folaron rapidly dissipates kinetic energy once beyond 40 meters (131 feet) from deployment such that is considered non-lethal in the event of contact with unintended targets. The material makeup of the payload of the present invention of this shot can be altered in view of Folaron, and other methods known to those skilled in the art to meet different use case requirements.

Certain embodiments of the present invention comprise a primer, propellant cup, fins, a mechanical timer, a segmented outer casing, and a wad loaded with frangible shot. When set to a 200-meter (656-foot) range, the round may be fired such that it travels approximately 200 meters (656 ft), prior to the shot being deployed. Upon deployment, in certain embodiments, the shot spreads in a pattern similar to that of shot deployed from a standard shotgun shell. The extended range capabilities, size of the effective impact area, combined with a larger submunition payload of this invention make it far more versatile than standard shotgun rounds, particularly in use for immobilizing drone threats.

Certain embodiments of the present invention utilize deployable fins to stabilize the round during flight and actuate a mechanical timer. The mechanical timer allows a user to programmably delay the deployment of the shot to result in an effective impact area similar to a standard shotgun shot at an increased range. This permits a user to tailor the effective range of the round to a particular use case. For instance, certain embodiments result in an effective impact area diameter of 100 cm (40 in) at a range of 40 meters (131 feet), when the mechanical timer is set to 0 meters (0 feet). Setting the mechanical timer of the same

embodiment to 200 meters (656 feet), would result in a 100 cm (40 in) diameter effective impact area at a range of 240 meters (787 feet).

It is an aspect of certain embodiments to provide a delayed deployment of shot from a projectile to result in an effective impact area at an appropriate range for neutralizing a drone threat. Certain embodiments deploy the payload using a mechanical timer once the round has traveled a predetermined distance. Certain embodiments use a mechanical timer—such as disclosed by in U.S. Pat. No. 3,703,866 to Semenza (“Semenza”), incorporated herein in its entirety for all purposes—to provide the ability for a delayed deployment of shot.

Certain embodiments are designed to be integrated in existing defense networks against drones. Because embodiments of the present invention can be manufactured to be fired from existing weapon platforms, the present invention can be quickly and easily integrated into operational service. It is an aspect of the present invention to allow production of embodiments intended to be fired from existing weapons platforms such that security personnel are not encumbered with burdened with ancillary equipment related to drone threats.

Certain embodiments of the present invention are configured to be used with existing 40 mm barreled weapons and other commonly used weapons available to military and law enforcement professionals. It will be appreciated by those skilled in the art that embodiments of the present invention can be adapted to the caliber of weapons other than 40 mm weapons while in keeping with the spirit and the scope of the present invention.

Certain embodiments comprise an outer casing having three segments surrounding the leading portion of the projectile. The outer casing is typically composed of a polymeric compound such as polyethylene, but is not limited thereto. A propellant-cup contains a charge, comprising an appropriate amount of gunpowder or other accelerant with a primer for the initiation of the charge. The outer case keeps the round together as it is fired, prior to reaching the predetermined range and full deployment.

Certain embodiments comprise shot held within a shot-cup, and mechanical timer enclosed in an outer casing. External to the outer casing, a fin assembly is affixed to the trailing end of the outer casing. The fin assembly is configured to fit within the open end of a propellant cup with a wad disposed between the fin assembly and the charge. It will be appreciated by those skilled in the art that a wad surrounds a barrier which holds the powder in the bottom of the propellant and helps deploy the shot.

Upon firing, the fin assembly of certain embodiments radially expands and provides stabilization and axial rotation. The axial rotation also actuates the mechanical timer. The axial rotation of the fin assembly spins a threaded shaft to which the fin assembly is affixed to. The threaded shaft is engaged with an aperture of a rod-puller within the outer casing, wherein the aperture comprises female threads. The rod-puller is affixed to rods which are engaged with the segments of the outer casing. In a closed-configuration, the rods retain the segments of the outer casing in place. In an open-configuration, the rods allow the segments of the outer casing to expand radially outward and separate from the projectile. Thus, when the fin assembly rotates, the rod-puller is drawn toward the trailing end of the projectile changing the projectile from a closed-configuration to an open-configuration to deploy the payload held within the shot-cup.

These and other advantages will be apparent from the disclosure of the inventions contained herein. The above-described embodiments, objectives, and configurations are neither complete nor exhaustive. As will be appreciated, other embodiments of the invention are possible using, alone or in combination, one or more of the features set forth above or described in detail below. Further, this Summary is neither intended nor should it be construed as being representative of the full extent and scope of the present invention. The present invention is set forth in various levels of detail in this Summary, as well as in the attached drawings and the detailed description below, and no limitation as to the scope of the present invention is intended to either the inclusion or non-inclusion of elements, components, etc. in this Summary. Additional aspects of the present invention will become more readily apparent from the detailed description, particularly when taken together with the drawings, and the claims provided herein.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A—a cross-sectional side view of certain embodiments

FIG. 1B—a perspective rear view of certain embodiments

FIG. 2A—a perspective rear view of certain embodiments showing undeployed fin assembly

FIG. 2B—a perspective rear view of certain embodiments showing deployed fin assembly

FIG. 3A—a perspective front view of an undeployed fin assembly of certain embodiments

FIG. 3B—a front view of an undeployed fin assembly of certain embodiments

FIG. 3C—a perspective rear view of a deployed fin assembly of certain embodiments

FIG. 3D—a front view of a deployed fin assembly of certain embodiments

FIG. 4—a perspective view of certain embodiments having a deployed fin assembly

FIG. 5A—front perspective view of a deployed fin assembly of certain embodiments

FIG. 5B—rear perspective view of a deployed fin assembly of certain embodiments

FIG. 6—exploded perspective view of certain embodiments

FIG. 7—a cross-sectional side view of certain embodiments

FIG. 8A—perspective side view of certain embodiments showing a closed-configuration

FIG. 8B—perspective side view of certain embodiments showing an open-configuration

FIG. 9—side view of a rod of certain embodiments

FIG. 10A—section view of certain embodiments

FIG. 10B—section view of certain embodiments

FIG. 11—exploded perspective view of certain embodiments

DETAILED DESCRIPTION OF VARIOUS EMBODIMENTS

Certain embodiments comprise a projectile **1000**, seen in FIG. 1A-FIG. 1B, affixed to a propellant cup **1030** with a wad **1040** therebetween. It will be appreciated by those skilled in the art that a wad, sometimes referred to as wadding, is an element used in barreled firearms to seal gas from the propellant behind a projectile, separating the charge from the projectile **1000** and transferring energy to propel the projectile **1000** and payload **1005**. Wadding can be

crucial to a firearm's efficiency by preventing the expanding gas from the charge from leaking past a projectile as it is being fired, ensuring that a maximum amount of energy of the charge is translated into propelling the projectile from the weapon. Wadding, as it pertains to shotgun shells, is typically a cup-shaped plastic form. It will also be appreciated by those skilled in the art that a propellant cup carries a charge of rapidly combustible material, such as gunpowder, used to propel a projectile. The propellant cup 1030 of certain embodiments further comprises a primer 1050, used to initiate a charge 1060. The initiation of the charge 1060 causes rapid combustion which results in rapid pressure increase between the wad 1040 and the propellant cup 1030, separating the projectile 1000 from the propellant cup 1030, and propelling the projectile 1000 from the weapon. Once the projectile 1000 leaves the barrel of the weapon, the wad 1040 falls away from the projectile 1000.

It will be appreciated by those skilled in the art that although a projectile traditionally uses combustible material to fire a projectile from a weapon, a projectile may be alternatively fired using other means known to those skilled in the art while in keeping with the scope and spirit of the present application. Such alternatives include, but are not limited to, electromagnetic propulsion and pneumatic propulsion.

In certain embodiments, shown in FIG. 2A-FIG. 2B, a projectile 1000 comprises a fin assembly 1100 comprising fins 1110 for the stabilization of the projectile 1000 while in flight. Certain embodiments comprise radially deployable fins 1110 which rotate radially outward from the projectile 1000 once the projectile leaves the barrel of the weapon from which it is fired. Certain embodiments comprise radially deployable fins 1110 which are affixed proximate to the trailing end 1020 of the projectile 1000 using a pinned connection 1130.

A fin 1110, in certain embodiments (FIG. 3A-FIG. 3D), rotates radially outward about the central axis 1140 of a pinned connection 1130. In certain embodiments, a fin 1110 is fixated to the fin assembly 1100 through a pinned connection 1130 between a first fin mount 1150 and a second fin mount 1150. A fin mount of certain embodiments comprises a boss 1160, providing a mechanical stop 1165 for a spring 1180. In embodiments comprising a torsional spring 1180, a first leg 1185 of the spring 1180 bears on the fin 1110, and a second leg 1185 of the spring 1180 bears on the mechanical stop 1165, thus applying a force to rotate the fin 1110 radially outward from the projectile 1000.

When the projectile 1000 (FIG. 4) leaves the barrel of a weapon, the fin 1110 is forced radially outward to a deployed position 1115 to provide stabilization. Certain embodiments of a fin 1110 are configured to induce radial rotation 1190 to the fin assembly 1100 in relation to the outer casing 1005. It will be appreciated that such radial rotation 1190 provides increased stabilization. It will be further appreciated that certain embodiments of a fin assembly 1100 may be configured to rotate clockwise or counter-clockwise rotation, while in keeping with the spirit and scope of the present invention.

In certain embodiments, shown in FIG. 5A-FIG. 5B, the fin mounts 1150 are affixed to a threaded shaft 1200. In certain embodiments, the fin mounts 1150 comprise an aperture 1170. The aperture 1170 is keyed and configured to mate with the threaded shaft, to limit radial rotation of the fin assembly 1100 in relation to the threaded shaft 1200. The threaded shaft 1200 passes through apertures 1170 of the fin mounts, and a bushing 1230 disposed between a first fin mount 1150 and a second fin mount 1150. The bushing 1230

is configured to allow the retention of the fins 1110 between a first fin mount 1150 and a second fin mount 1150 without compression of the fins 1110 between the fin mounts 1150. Compression of the fins 1110 between the fin mounts 1150 would result in binding, thus restricting the fins from rotating radially outward. In certain embodiments, the distance 1240 between fin mounts 1150 is greater than the height 1120 of a fin.

In certain embodiments, shown in FIG. 5A-FIG. 5B, a portion of the threaded shaft 1200 extends away from the fin assembly 1100, axially within the projectile 1000, toward the leading end 1010 of the projectile. A bearing 1310 interfaces between a portion of the threaded shaft 1200 and a retainer 1300. It will be appreciated that a bearing 1310, as used herein, surrounds a mechanical element configured to allow axial rotation with limited frictional interference. A bearing 1310 as used herein includes, but is not limited to a plain bearing, a rolling-element bearing, ball-bearing, roller-bearing, fluid bearing, jewel bearing, and a sleeve bearing—while in keeping with the spirit and scope of the present invention. A retainer 1300 of certain embodiments is referred to as an impeller. The retainer 1300 of certain embodiments comprises a mechanical stop 1320, referencing FIG. 6-FIG. 7, configured to abut a first mechanical stop 1410 of a segment of the outer casing, extending inward from the segment 1400 of an outer casing 1005, thereby limiting the rotation of the retainer 1300 in relation to the outer casing 1005. In certain embodiments, a segment 1400 of outer casing further comprises a second mechanical stop 1410. Furthermore, rotation induced by the fin assembly 1100, rotates the fin assembly 1100 in relation to the outer casing 1005. It will be appreciated that, due to the higher mass associated with some payloads—such as shot—contained within the outer casing 1005, the fin assembly 1100 of certain embodiments will axially rotate faster than the outer casing 1005.

In certain embodiments, as seen in FIG. 8A-FIG. 8B, a leading end 1210 (FIG. 5A) of a threaded shaft is affixed to a rod-puller 1500. An aperture 1510 of the rod-puller, typically central to the rod-puller 1500, comprises female threading 1520 (not shown) configured to engage with the threaded shaft 1200, and a plurality of rods 1530 radially offset from the aperture 1510, and affixed to the rod-puller 1500. The rod-puller 1500 is engaged with a portion of the leading end 1210 of the threaded shaft. In certain embodiments, the rods 1530 are affixed to the rod-puller 1500 by way of mechanical interference fit, with rod-apertures 1540 in the rod-puller, radially offset from a centrally located aperture 1510 of the rod-puller.

In certain embodiments, seen in FIG. 8A-FIG. 9, the rods 1530 further comprise a threaded end 1535 for engagement with rod-apertures 1540 in the rod-puller. In certain embodiments, the rod-puller 1500 comprises three rod-apertures 1540 which are equally offset from a centrally located aperture 1510, and radially spaced at 120-degree increments. When the fin assembly 1100 rotates in relation to the outer casing 1005, the threaded shaft 1200 is advanced further into the aperture 1510 of the rod-puller, thereby drawing the rod-puller 1500 rearward toward the fin assembly 1100. It will be appreciated that although embodiments described surround a rod-puller 1500 being drawn toward the trailing end 1020 of the projectile, a rod-puller 1500 of certain embodiments can be advanced toward the leading end 1010 of the projectile in efforts to pull or push rods 1530 to release segments 1400 of the outer casing. It will be appreciated by those skilled in the art, that the delay of deployment of payload 1610 (FIG. 6) of the present invention can be altered

through the modification of one or more features. For instance, the modification of the thread pitch of the threaded shaft **1200** to comprise a coarse thread would actuate the rod-puller **1500** into an open-configuration more rapidly than a threaded shaft having a fine thread.

In certain embodiments, shown in FIG. **8A-8B**, the actuation of a rod-puller **1500** results in drawing the rod-puller **1500** rearward toward the trailing end **1020** of the projectile. A plurality of rods **1530** having a first end **1580** affixed to the rod-puller **1500**, extend toward the leading end **1010** of the projectile from the rod-puller **1500**, substantially parallel to the central axis **1090** of the projectile. When the projectile **1000** is in a closed-configuration (FIG. **8A**), the rods engage with retaining features affixed to the interior surface of the segments of the outer casing. When the rod-puller **1500** is actuated, placing the projectile **1000** in an open-configuration (FIG. **8B**), the rods **1530** release from retaining features **1430** on an internal aspect of the segments of the outer casing.

In certain embodiments, referencing FIG. **8A-10B**, a rod **1530** comprises a first diameter **1550** consistent with a first end **1580** of the rod, a second diameter **1560** consistent with a second end **1590** of the rod, and a third diameter **1570** located between the first diameter **1550** and the second diameter **1560**. A first retaining feature **1430** of a segment has a groove **1440** having a substantially circular cross section configured to retain the first diameter **1550** of the rod, and the groove **1440** having a lateral opening **1450** with a width **1455** smaller than the first diameter **1550** of the rod and larger than the third diameter **1570**. The second diameter **1560** of a rod engages with a second retaining feature **1430** comprising an aperture **1460** having a substantially circular cross section. Thus, when the rod-puller **1500** draws the rods **1530** rearward toward the trailing end **1020** of the projectile, the first diameter **1550** disengages from the first retaining feature **1430** and the second diameter **1560** disengages from the second retainer feature **1430**. The third diameter **1570**, now aligned with the first retainer feature **1430**, is configured to pass through the lateral opening **1450** of the groove. Thus, the projectile transitions from a closed-configuration (FIG. **8A**), to an open-configuration, and a segment **1400** of the outer casing is permitted to expand and release radially outward, separating from the projectile **1000**.

The projectile of certain embodiments, as seen in FIG. **11**, comprises an outer casing **1005** having a plurality of segments **1400** surrounding a payload **1610**. The actuation of a retaining mechanism, such as a rod-puller **1500**, configures the retaining mechanism from a closed-configuration as shown in FIG. **8A**, to an open-configuration as shown in FIG. **8B**, releasing the segments **1400** of the outer casing. Thus, in flight, the segments **1400** of the outer casing are released, and permitted to expand radially outward from a central axis **1090** of the projectile. Upon the radial expansion of the outer casing **1005**, from the central axis **1090** of the projectile, the segments **1400** create aerodynamic drag. Thus, the segments separate from the projectile, and the shot **1620**—having a higher inertial mass and lower aerodynamic drag than the segments **1400** and shot-cup **1600**—separates from the projectile **1000** for final deployment toward an intended target.

The payload **1610** of certain embodiments, as seen in FIG. **11**, comprises shot **1620** having a first pellet **1630** having a first diameter **1640**, and a second pellet **1630** having a second diameter **1650**. It will be appreciated that different size of pellets **1630** used in the same payload **1610** allows the tailoring of effective impact area of the pellets **1630**. It will be appreciated by those skilled in the art that a pellet of

a larger diameter will spread outward less than a pellet of smaller diameter. Thus, the smaller diameter pellets will spread outward from path of the projectile **1000** more than the pellets of larger diameter. It will be further appreciated by those skilled in the art that although the fin assembly **1100** axially rotates in relation to the outer casing **1005**, the outer casing **1005** of certain embodiments also axially rotates, thus the payload **1610** also rotates axially. Due to axial rotation, the rotational inertia of the pellets **1630** of shot further induce an outward spread of pellets **1630**.

In certain embodiments the shot-cup **1600** is packed with shot **1620** having pellets **1630** of two different diameters: 6.35 mm (0.25 in) and 12.7 mm (0.5 in). The different diameter pellets **1630**, typically in spherical form, allow for a wider dispersal and thus a larger effective impact area. It will be appreciated that embodiments can comprise pellets **1630** of different diameters than disclosed herein without departing from the spirit of scope of the present invention. Certain embodiments of the shot **1620** comprise a lead-free frangible material. The frangible and low-density nature of the shot **1620** allows it to dissipate enough kinetic energy in the event the shot **1620** does not strike an intended target. The shot-cup **1600**, of certain embodiments, comprises a cylinder with an open end **1660**, and a plurality of slits **1670** cut along its length. As the shot **1620** is released from the shot-cup **1600**, it is deployed normally, as if fired from a standard shotgun.

While various embodiments of the present invention have been described in detail, it is apparent that modifications and alterations of those embodiments will occur to those skilled in the art. However, it is to be expressly understood that such modifications and alterations are within the scope and spirit of the present invention. Further, the inventions described herein are capable of other embodiments and of being practiced or of being carried out in various ways. In addition, it is to be understood that the phraseology and terminology used herein is for the purposes of description and should not be regarded as limiting. The use of “including,” “comprising,” or “adding” and variations thereof herein are meant to encompass the items listed thereafter and equivalents thereof, as well as, additional items.

What is claimed is:

1. A projectile comprising:
 - a mechanical timer configured to actuate the opening of an outer casing of the projectile after a predetermined duration of flight;
 - the mechanical timer comprising a fin assembly at a trailing end of the projectile coupled with a shaft connected to the fin assembly; and
 - a payload held within the outer casing;
 wherein the radial rotation of the fin assembly results in the rotation of shaft, thereby initiating a change of the configuration of the projectile from a closed configuration to an open configuration, thereby releasing the payload from the projectile,
 - and wherein the outer casing comprises a plurality of independent segments which are detached from one another and the projectile in the open configuration.
2. The projectile of claim 1, wherein the fin assembly comprises a plurality of fins distributed around a first fin mount, the fins each have a connection to the first fin mount wherein the fins are radially deployable;
 - the fins are configured to induce radial rotation to the fin assembly;
 - the shaft extends away from the fin assembly toward a leading end of the projectile; and
 - the outer casing located at the leading end of the projectile.

11

3. The projectile of claim 2, further comprising a second fin mount, wherein the fins are mounted between the first fin mount and the second fin mount.

4. The projectile of claim 3 further comprising torsional springs affixed to each of the fins, wherein a first leg of each torsional spring bears on a portion of the first fin mount, and a second leg of each torsional spring bears on the second fin mount, wherein the torsional springs apply force to rotate the fins radially outward from the projectile.

5. The projectile of claim 2 further comprising, threading on the shaft; and a rod-puller comprising female threading configured to mate with the threading of the shaft, wherein the rod-puller is mated to the shaft such that rotation of the shaft results in linear movement of the rod-puller along a longitudinal axis, resulting in the opening of the outer casing and releasing the payload from the projectile.

6. The projectile of claim 5, further comprising: a rod having a first end affixed to a rod-puller; a plurality of segments comprising the outer casing; and a first retaining feature on an internal aspect of one of the segments, the first retaining feature comprising an aperture with a diameter greater than a diameter of the rod, wherein the first retaining feature is configured to receive a second end of the rod; wherein linear movement of the rod-puller results in linear retraction of the rod from the first retaining feature, thereby detaching the segment from the projectile.

7. The projectile of claim 6, further comprising: a plurality of rods each having a first end affixed to the rod puller; and a plurality of first retaining features wherein each segment of the outer casing comprises a first retaining feature on an internal aspect, and each first retaining feature configured to receive the second end of one of the rods; wherein the linear movement of the rod-puller results in linear retraction of the rod from the retaining feature, thereby detaching the segment from the projectile.

12

8. The projectile of claim 7, wherein the projectile begins in a closed-configuration with the rods mated with the retaining features of the segments, and

wherein detaching the segments from the projectile changes the projectile from a closed-configuration to an open-configuration.

9. The projectile of claim 7 wherein, the rods each have a diameter; the segments of the outer casing each having a retaining feature comprising an aperture with a diameter greater than the diameter of the rods; and wherein the rods are aligned with the retaining features in a closed configuration, and wherein the rods are retracted from the retaining features in an open configuration.

10. The projectile of claim 7 wherein: the rods each have a first diameter, and a second diameter which is less than the first diameter; the segments of the outer casing each having a first retaining feature having a groove with a diameter equal to or greater than the first diameter of the rod; and the groove having a lateral opening width less than the first diameter of the rods and greater than the second diameter of the rods, wherein, for each rod, the first diameter is aligned with a corresponding one of the first retaining features in a closed configuration and the second diameter is aligned with the corresponding one of the first retaining features in an open configuration.

11. The projectile of claim 2, wherein the payload comprises shot pellets.

12. The projectile of claim 11, wherein the shot pellets comprise first pellets and second pellets, wherein the second pellets are larger than the first pellets.

13. The projectile of claim 12, wherein the payload is contained within a shot-cup having a cylindrical form, and wherein the second pellets are surrounded by the first pellets.

* * * * *