



US008541724B2

(12) **United States Patent**  
**Roerman**

(10) **Patent No.:** **US 8,541,724 B2**  
(45) **Date of Patent:** **Sep. 24, 2013**

(54) **SMALL SMART WEAPON AND WEAPON SYSTEM EMPLOYING THE SAME**

(75) Inventor: **Steven D. Roerman**, Highland Village, TX (US)

(73) Assignee: **Lone Star IP Holdings, LP**, Addison, TX (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/850,421**

(22) Filed: **Aug. 4, 2010**

(65) **Prior Publication Data**

US 2011/0017864 A1 Jan. 27, 2011

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 11/706,489, filed on Feb. 15, 2007, which is a continuation-in-part of application No. 11/541,207, filed on Sep. 29, 2006, now Pat. No. 7,690,304.

(60) Provisional application No. 61/231,141, filed on Aug. 4, 2009.

(51) **Int. Cl.**

**F42B 15/01** (2006.01)

**F41G 7/22** (2006.01)

**G05D 1/12** (2006.01)

**G02B 3/02** (2006.01)

**G02B 3/08** (2006.01)

(52) **U.S. Cl.**

USPC ..... **244/3.16**; 359/709

(58) **Field of Classification Search**

USPC ..... 244/3.15, 3.16, 3.17; 359/709, 717, 359/720

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,039,850	A	10/1912	Völler
1,077,989	A	11/1913	Maxim
1,240,217	A	9/1917	Ingram
1,312,764	A	8/1919	Straub
1,550,622	A	8/1925	Lesh
1,562,495	A	11/1925	Dalton
2,295,442	A	9/1942	Wilhelm
2,350,140	A	5/1944	Wilton
2,397,088	A	3/1946	Clay
2,445,311	A	7/1948	Cooke et al.
2,621,732	A	12/1952	Ahlgren
2,737,889	A	3/1956	Barker
2,767,656	A	10/1956	Zeamer

(Continued)

**FOREIGN PATENT DOCUMENTS**

EP 0 298 494 A2 1/1989

**OTHER PUBLICATIONS**

U.S. Appl. No. 10/841,192, filed May 7, 2004, Roerman, et al.

U.S. Appl. No. 10/997,617, filed Nov. 24, 2004, Tepera, et al.

(Continued)


*Primary Examiner* — Bret Hayes

(74) *Attorney, Agent, or Firm* — Boisbrun Hofman, PLLC

(57) **ABSTRACT**

A weapon and weapon system, and methods of manufacturing and operating the same. In one embodiment, the weapon includes a warhead including destructive elements and a guidance section with a seeker configured to guide the weapon to a target. The seeker includes a detector configured to receive a distorted signal impinging on an objective lens from the target, memory configured to store target criteria and a correction map, and a processor configured to provide a correction signal based on the distorted signal, the target criteria and the correction map to guide the weapon to the target.

**16 Claims, 17 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

2,809,583	A	10/1957	Ortynsky et al.	5,107,766	A	4/1992	Schliesske et al.
2,852,981	A	9/1958	Caya	5,107,767	A	4/1992	Schneider et al.
2,911,914	A	11/1959	Wynn et al.	5,127,605	A	7/1992	Atchison et al.
2,934,286	A	4/1960	Kiernan	5,132,843	A	7/1992	Aoyama et al.
2,958,260	A	11/1960	Anderson	5,231,928	A	8/1993	Phillips et al.
3,211,057	A	10/1965	White, Jr. et al.	5,311,820	A	5/1994	Ellingsen
3,242,861	A	3/1966	Reed, Jr.	5,322,998	A *	6/1994	Jackson ..... 250/216
3,332,348	A	7/1967	Myers et al.	5,325,786	A	7/1994	Petrovich
3,372,890	A *	3/1968	Bogard et al. .... 244/3.17	5,348,596	A	9/1994	Goleniewski et al.
3,377,952	A	4/1968	Crockett	5,413,048	A	5/1995	Werner et al.
3,379,131	A	4/1968	Webb	5,438,366	A *	8/1995	Jackson et al. .... 348/342
3,416,752	A *	12/1968	Hembree ..... 244/3.17	5,440,994	A	8/1995	Alexander
3,429,262	A	2/1969	Kincheloe et al.	5,445,861	A *	8/1995	Newton et al. .... 428/116
3,545,383	A	12/1970	Lucy	5,451,014	A	9/1995	Dare et al.
3,555,826	A	1/1971	Bennett	5,467,940	A	11/1995	Steuer
3,625,106	A	12/1971	Russo et al.	5,529,262	A	6/1996	Horwath
3,625,152	A	12/1971	Schneider, Jr. et al.	5,541,603	A	7/1996	Read et al.
3,667,342	A	6/1972	Warnock et al.	5,546,358	A	8/1996	Thomson
3,703,844	A	11/1972	Bleikamp, Jr.	5,561,261	A	10/1996	Lindstädt et al.
3,728,935	A	4/1973	Magorian	5,567,906	A	10/1996	Reese et al.
3,759,466	A	9/1973	Evers-Euteneck	5,567,912	A	10/1996	Manning et al.
3,763,786	A	10/1973	MacDonald	5,681,008	A	10/1997	Kinstler
3,771,455	A	11/1973	Haas	5,682,266	A *	10/1997	Meyers ..... 359/571
3,789,337	A	1/1974	Sheppard	5,691,502	A	11/1997	Craddock et al.
3,820,106	A	6/1974	Yamashita et al.	5,698,815	A	12/1997	Ragner
3,872,770	A	3/1975	McGuire	5,728,968	A	3/1998	Buzzett et al.
3,887,991	A	6/1975	Panella	5,796,031	A	8/1998	Sigler
3,941,059	A	3/1976	Cobb	5,816,532	A	10/1998	Zasadny et al.
3,943,854	A	3/1976	Zwicker	5,834,684	A	11/1998	Taylor
3,954,060	A	5/1976	Haag et al.	5,969,864	A	10/1999	Chen et al.
3,956,990	A	5/1976	Rowe	5,978,139	A	11/1999	Hatakoshi et al.
3,995,792	A	12/1976	Otto et al.	5,988,071	A	11/1999	Taylor
3,998,124	A	12/1976	Milhous et al.	6,019,317	A	2/2000	Simmons et al.
4,015,527	A	4/1977	Evans	6,021,716	A	2/2000	Taylor
4,036,140	A	7/1977	Korr et al.	6,105,505	A	8/2000	Jones
4,091,734	A	5/1978	Redmond et al.	6,174,494	B1	1/2001	Lowden et al.
4,106,726	A *	8/1978	Emmons et al. .... 244/3.17	6,216,595	B1	4/2001	Lamorlette et al.
4,172,407	A	10/1979	Wentink	6,253,679	B1	7/2001	Woodall et al.
4,211,169	A	7/1980	Brothers	6,293,202	B1	9/2001	Woodall et al.
4,291,848	A *	9/1981	Clark ..... 244/3.16	6,324,985	B1	12/2001	Petrusha
4,364,531	A	12/1982	Knoski	6,338,242	B1	1/2002	Kim et al.
4,383,661	A	5/1983	Ottenheimer et al.	6,374,744	B1	4/2002	Schmacker et al.
4,430,941	A	2/1984	Raech, Jr. et al.	6,389,977	B1	5/2002	Schmacker et al.
4,478,127	A	10/1984	Hennings et al.	6,523,477	B1	2/2003	Brooks et al.
4,498,394	A	2/1985	Regebro	6,523,478	B1	2/2003	Gonzalez et al.
4,522,356	A	6/1985	Lair et al.	6,540,175	B1	4/2003	Mayersak et al.
4,616,554	A	10/1986	Spink et al.	6,604,436	B1 *	8/2003	Lewandowski et al. .... 73/865.6
4,625,646	A	12/1986	Pinson	6,615,116	B2	9/2003	Ebert et al.
4,638,737	A	1/1987	McIngvale	6,666,123	B1	12/2003	Adams et al.
4,648,324	A	3/1987	McDermott	6,705,571	B2	3/2004	Shay et al.
4,709,877	A	12/1987	Goulding	6,779,754	B2	8/2004	Heilman
4,714,020	A	12/1987	Hertsgaard et al.	6,832,740	B1	12/2004	Ransom
4,744,301	A	5/1988	Cardoen	6,834,835	B1	12/2004	Knowles et al.
4,750,404	A	6/1988	Dale	6,869,044	B2	3/2005	Geswender et al.
4,750,423	A	6/1988	Nagabhushan	6,871,817	B1	3/2005	Knapp
4,756,227	A	7/1988	Ash et al.	6,880,780	B1	4/2005	Perry et al.
4,770,101	A	9/1988	Robertson et al.	6,910,661	B2	6/2005	Dockter et al.
4,775,432	A	10/1988	Kolonko et al.	6,933,877	B1	8/2005	Halladay et al.
4,777,882	A	10/1988	Dieval	7,019,650	B2	3/2006	Volpi et al.
4,803,928	A	2/1989	Kramer et al.	7,051,974	B2	5/2006	Stuhr
4,824,053	A	4/1989	Sarh	7,083,140	B1	8/2006	Dooley
4,834,531	A *	5/1989	Ward ..... 356/5.08	7,143,698	B2	12/2006	Lloyd
4,842,218	A	6/1989	Groutage et al.	7,156,347	B2	1/2007	Lam et al.
4,860,969	A	8/1989	Muller et al.	7,221,847	B2	5/2007	Gardiner et al.
4,870,885	A	10/1989	Grosselin et al.	7,325,769	B1	2/2008	Harnisch et al.
4,882,970	A	11/1989	Kovar	7,340,986	B1	3/2008	Gaigler
4,922,799	A	5/1990	Bartl et al.	7,474,476	B2 *	1/2009	Ueta et al. .... 359/741
4,922,826	A	5/1990	Busch et al.	7,503,527	B1	3/2009	Fairchild
4,932,326	A	6/1990	Ladriere	7,530,315	B2	5/2009	Tepera et al.
4,934,269	A	6/1990	Powell	7,690,304	B2	4/2010	Roerman et al.
4,936,187	A	6/1990	Teeter	7,789,343	B2	9/2010	Sarh et al.
4,957,046	A	9/1990	Puttock	7,958,810	B2	6/2011	Roerman et al.
4,996,923	A	3/1991	Theising	8,016,249	B2	9/2011	Sar et al.
5,027,413	A *	6/1991	Barnard ..... 382/103	8,127,683	B2	3/2012	Tepera et al.
5,056,408	A	10/1991	Joner et al.	2003/0051629	A1	3/2003	Zavitsanos et al.
				2003/0123159	A1	7/2003	Morita et al.
				2003/0192992	A1	10/2003	Olsen et al.
				2004/0174261	A1	9/2004	Volpi et al.
				2005/0127242	A1	6/2005	Rivers, Jr.



2005/0180337	A1	8/2005	Roemerma et al.	
2005/0201450	A1	9/2005	Volpi et al.	
2006/0017545	A1	1/2006	Volpi et al.	
2006/0077036	A1	4/2006	Roemerma et al.	
2006/0198033	A1	9/2006	Soyama et al.	
2007/0035383	A1	2/2007	Roemerma et al.	
2007/0157843	A1	7/2007	Roemerma et al.	
2009/0078146	A1	3/2009	Tepera et al.	
2009/0228159	A1 *	9/2009	Flowers et al.	701/3
2010/0031841	A1	2/2010	Michel et al.	
2010/0282893	A1	11/2010	Roemerma et al.	
2010/0326264	A1	12/2010	Roemerma et al.	
2012/0119013	A1	5/2012	Roemerma et al.	
2012/0145822	A1	6/2012	Roemerma et al.	
2012/0152091	A1	6/2012	Roemerma et al.	

## OTHER PUBLICATIONS

U.S. Appl. No. 11/501,348, filed Aug. 9, 2006, Roemerma, et al.  
U.S. Appl. No. 11/541,207, filed Sep. 29, 2006, Roemerma, et al.  
U.S. Appl. No. 11/706,489, filed Feb. 15, 2007, Roemerma, et al.  
U.S. Appl. No. 60/706,822, filed Aug. 9, 2005, Roemerma, et al.  
U.S. Appl. No. 60/722,475, filed Sep. 30, 2005, Roemerma, et al.  
U.S. Appl. No. 60/773,746, filed Feb. 15, 2006, Roemerma, et al.  
U.S. Appl. No. 60/855,084, filed Oct. 26, 2006, Roemerma, et al.

Andersson, O., et al., "High Velocity Jacketed Long Rod Projectiles Hitting Oblique Steel Plates," 19th International Symposium of Ballistics, May 7-11, 2001, pp. 1241-1247, Interlaken, Switzerland.  
Davitt, R.P., "A Comparison of the Advantages and Disadvantages of Depleted Uranium and Tungsten Alloy as Penetrator Materials," Tank Ammo Section Report No. 107, Jun. 1980, 32 pages, U.S. Army Armament Research and Development Command, Dover, NJ.  
"DOE Handbook: Primer on Spontaneous Heating and Pyrophoricity," Dec. 1994, 87 pages, DOE-HDBK-1081-94, FSC-6910, U.S. Department of Energy, Washington, D.C.  
Rabkin, N.J., et al., "Operation Desert Storm: Casualties Caused by Improper Handling of Unexploded U.S. Submunitions," GAO Report to Congressional Requestors, Aug. 1993, 24 pages, GAO/NSAID-93-212, United States General Accounting Office, Washington, D.C.  
Smart, M.C., et al., "Performance Characteristics of Lithium Ion Cells at Low Temperatures," IEEE AESS Systems Magazine, Dec. 2002, pp. 16-20, IEEE, Los Alamitos, CA.  
"UNICEF What's New?: Highlight: Unexploded Ordnance (UXO)," <http://www.unicef.org.vn/uxo.htm>, downloaded Mar. 8, 2005, 3 pages.

\* cited by examiner















FIG. 4








FIG. 10




FIG. 12B




FIG. 12A




FIG. 13A




FIG. 13B




FIG. 13C






FIG. 11




FIG. 13D




FIG. 13F




FIG. 13E




FIG. 14A



FIG. 14B




FIG. 14D




FIG. 14C




FIG. 15A




FIG. 15B




FIG. 15C



FIG. 15D




FIG. 16A





FIG. 16B








FIG. 18A








FIG. 20




FIG. 21




FIG. 22A




FIG. 22B




FIG. 22C








FIG. 22D



1

## SMALL SMART WEAPON AND WEAPON SYSTEM EMPLOYING THE SAME

This application is a continuation-in-part of U.S. patent application Ser. No. 11/706,489 entitled "Small Smart Weapon and Weapon System Employing the Same," filed Feb. 15, 2007, which is a continuation-in-part of U.S. patent application Ser. No. 11/541,207 entitled "Small Smart Weapon and Weapon System Employing the Same," filed Sep. 29, 2006, now U.S. Pat. No. 7,690,304, and also claims the benefit of U.S. Provisional Application No. 61/231,141 entitled "Novel Body Fixed Seekers and Variable Output Explosive Devices," filed Aug. 4, 2009, which applications are incorporated herein by reference.

### TECHNICAL FIELD

The present invention is directed, in general, to weapon systems and, more specifically, to a weapon and weapon system, and methods of manufacturing and operating the same.

### BACKGROUND

Present rules of engagement demand that precision guided weapons and weapon systems are necessary. According to well-documented reports, precision guided weapons have made up about 53 percent of all strike weapons employed by the United States from 1995 to 2003. The trend toward the use of precision weapons will continue. Additionally, strike weapons are used throughout a campaign, and in larger numbers than any other class of weapons. This trend will be even more pronounced as unmanned airborne vehicles ("UAVs") take on attack roles.

Each weapon carried on a launch platform (e.g., aircraft, ship, artillery) must be tested for safety, compatibility, and effectiveness. In some cases, these qualification tests can cost more to perform than the costs of the development of the weapon system. As a result, designers often choose to be constrained by earlier qualifications. In the case of smart weapons, this qualification includes data compatibility efforts. Examples of this philosophy can be found in the air to ground munitions ("AGM")-154 joint standoff weapon ("JSOW"), which was integrated with a number of launch platforms. In the process, a set of interfaces were developed, and a number of other systems have since been integrated which used the data sets and precedents developed by the AGM-154. Such qualifications can be very complex.

An additional example is the bomb live unit ("BLU")-116, which is essentially identical to the BLU-109 warhead in terms of weight, center of gravity and external dimensions. However, the BLU-116 has an external "shroud" of light metal (presumably aluminum alloy or something similar) and a core of hard, heavy metal. Thus, the BLU-109 was employed to reduce qualification costs of the BLU-116.

Another means used to minimize the time and expense of weapons integration is to minimize the changes to launch platform software. As weapons have become more complex, this has proven to be difficult. As a result, the delay in operational deployment of new weapons has been measured in years, often due solely to the problem of aircraft software integration.

Some weapons such as the Paveway II laser guided bomb [also known as the guided bomb unit ("GBU")-12] have no data or power interface to the launch platform. Clearly, it is

2

highly desirable to minimize this form of interface and to, therefore, minimize the cost and time needed to achieve military utility.

Another general issue to consider is that low cost weapons are best designed with modularity in mind. This generally means that changes can be made to an element of the total weapon system, while retaining many existing features, again with cost and time in mind.

Another consideration is the matter of avoiding unintended damage, such as damage to non-combatants. Such damage can take many forms, including direct damage from an exploding weapon, or indirect damage. Indirect damage can be caused by a "dud" weapon going off hours or weeks after an attack, or if an enemy uses the weapon as an improvised explosive device. The damage may be inflicted on civilians or on friendly forces.

One term of reference is "danger close," which is the term included in the method of engagement segment of a call for fire that indicates that friendly forces or non-combatants are within close proximity of the target. The close proximity distance is determined by the weapon and munition fired. In recent United States engagements, insurgent forces fighting from urban positions have been difficult to attack due to such considerations.

To avoid such damage, a number of data elements may be provided to the weapon before launch, examples of such data include information about coding on a laser designator, so the weapon will home in on the right signal. Another example is global positioning system ("GPS") information about where the weapon should go, or areas that must be avoided. Other examples could be cited, and are familiar to those skilled in the art.

Therefore, what is needed is a small smart weapon that can be accurately guided to an intended target with the effect of destroying that target with little or no collateral damage of other nearby locations. Also, what is needed is such a weapon having many of the characteristics of prior weapons already qualified in order to substantially reduce the cost and time for effective deployment.

### SUMMARY OF THE INVENTION

These and other problems are generally solved or circumvented, and technical advantages are generally achieved, by advantageous embodiments of the present invention, which includes a weapon and weapon system, and methods of manufacturing and operating the same. In one embodiment, the weapon includes a warhead including destructive elements and a guidance section with a seeker configured to guide the weapon to a target. The seeker includes a detector configured to receive a distorted signal impinging on an objective lens from the target, memory configured to store target criteria and a correction map, and a processor configured to provide a correction signal based on the distorted signal, the target criteria and the correction map to guide the weapon to the target.

The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter which form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures or processes for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent

constructions do not depart from the spirit and scope of the invention as set forth in the appended claims.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention, and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:

FIG. 1 illustrates a view of an embodiment of a weapon system in accordance with the principles of the present invention;

FIG. 2 illustrates a diagram demonstrating a region including a target zone for a weapon system in accordance with the principles of the present invention;

FIG. 3 illustrates a perspective view of an embodiment of a weapon constructed according to the principles of the present invention;

FIG. 4 illustrates a diagram demonstrating a region including a target zone for a weapon system in accordance with the principles of the present invention;

FIG. 5 illustrates a diagram of an embodiment of a folding lug switch assembly constructed in accordance with the principles of the present invention;

FIGS. 6A and 6B illustrate diagrams demonstrating a four quadrant semi active laser detector constructed in accordance with the principles of the present invention;

FIGS. 7A and 7B illustrate the properties of a conventional and fast fresnel lens ("FFL") constructed in accordance with the principles of the present invention;

FIG. 8 illustrates a diagram of an embodiment of a pseudorandom pattern for a FFL constructed in accordance with the principles of the present invention;

FIGS. 9A and 9B illustrate views of an embodiment of hybrid optics employable with a guidance section of a weapon constructed in accordance with the principles of the present invention;

FIG. 10 illustrates a view of an embodiment of an aft section constructed in accordance with the principles of the present invention;

FIG. 11 illustrates a view of an embodiment of an aft section constructed in accordance with the principles of the present invention;

FIGS. 12A and 12B illustrate views of an embodiment of a variable aspect wing ratio for the tail fins of an aft section constructed in accordance with the principles of the present invention;

FIGS. 13A to 13F illustrate views of an embodiment of a variable aspect wing ratio for the tail fins of an aft section constructed in accordance with the principles of the present invention;

FIGS. 14A to 14D illustrate views of another embodiment of a weapon including the tail fins of an aft section thereof constructed in accordance with the principles of the present invention;

FIGS. 15A to 15D illustrate side views of embodiments of nose cones of a warhead of a weapon in accordance with the principles of the present invention;

FIGS. 16A and 16B illustrate exploded views of an embodiment of a nose cone of a warhead of a weapon in accordance with the principles of the present invention;

FIG. 17 illustrates an isometric view of an embodiment of a seeker;

FIGS. 18A and 18B illustrate views of an embodiment of a seeker constructed according to the principles of the present invention;

FIG. 19 illustrates a cutaway view of an embodiment of a seeker with a calibration array constructed according to the principles of the present invention;

FIG. 20 illustrates a block diagram of an embodiment of a seeker constructed according to the principles of the present invention;

FIG. 21 illustrates a view of an embodiment of a seeker constructed according to the principles of the present invention;

FIGS. 22A to 22D illustrate views of embodiments of warheads of weapons; and

FIGS. 23 to 26 illustrate views of embodiments of portions of a warhead of a weapon constructed according to the principles of the present invention.

#### DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

The making and using of the presently preferred embodiments are discussed in detail below. It should be appreciated, however, that the present invention provides many applicable inventive concepts that can be embodied in a wide variety of specific contexts. The specific embodiments discussed are merely illustrative of specific ways to make and use the invention, and do not limit the scope of the invention.

It should be understood that the military utility of the weapon can only be fully estimated in the context of a so-called system of systems, which includes a guidance section or system, the delivery vehicle or launch platform, and other things, in addition to the weapon per se. In this sense, a weapon system is disclosed herein, even when we are describing a weapon per se. One example is seen in the discussion of the GBU-12, wherein design choices within the weapon were reflected in the design and operation of many aircraft that followed the introduction of the GBU-12. Another example is the use of a laser designator for laser guided weapons. Design choices in the weapon can enhance or limit the utility of the designator. Other examples can be cited. Those skilled in the art will understand that the discussion of the weapon per se inherently involves a discussion of the larger weapon system of systems. Therefore, improvements within the weapon often result in corresponding changes or improvements outside the weapon, and new teachings about weapons teach about weapon platforms, and other system of systems elements.

In accordance therewith, a class of warhead assemblies, constituting systems, methods, and devices, with many features, including multiple, modular guidance subsystems, avoidance of collateral damage, unexploded ordnance, and undesirable munitions sensitivity is described herein. In an exemplary embodiment, the warheads are Mark derived (e.g., MK-76) or bomb dummy unit ("BDU") derived (e.g., BDU-33) warheads. The MK-76 is about four inches in diameter, 24.5 inches in length, 95-100 cubic inches ("cu") in internal volume, 25 pounds ("lbs") and accommodates a 0.85 inch diameter practice bomb cartridge. This class of assemblies is also compatible with existing weapon envelopes of size, shape, weight, center of gravity, moment of inertia, and structural strength to avoid lengthy and expensive qualification for use with manned and unmanned platforms such as ships, helicopters, self-propelled artillery and fixed wing aircraft, thus constituting systems and methods for introducing new weapon system capabilities more quickly and at less expense. In addition, the weapon system greatly increases the number of targets that can be attacked by a single platform, whether manned or unmanned.

In an exemplary embodiment, the general system envisioned is based on existing shapes, such as the MK-76, BDU-33, or laser guided training round ("LGTR"). The resulting system can be modified by the addition or removal of various features, such as global positioning system ("GPS") guidance, and warhead features. In addition, non-explosive warheads, such as those described in U.S. patent application Ser. No. 10/841,192 entitled "Weapon and Weapon System Employing The Same," to Roemerma, et al., filed May 7, 2004, U.S. patent application Ser. No. 10/997,617 entitled "Weapon and Weapon System Employing the Same," to Tepera, et al., filed Nov. 24, 2004, now U.S. Pat. No. 7,530,315, and U.S. patent application Ser. No. 11/925,471 entitled "Weapon Interface System and Delivery Platform Employing the Same," to Roemerma, et al., filed Oct. 26, 2006, which are incorporated herein by reference, may also be employed with the weapon according to the principles of the present invention.

Another feature of the system is the use of system elements for multiple purposes. For example, the central structural element of the MK-76 embodiment includes an optics design with a primary optical element, which is formed in the mechanical structure rather than as a separate component. Another example is the use of an antenna for both radio guidance purposes, such as GPS, and for handoff communication by means such as those typical of a radio frequency identification ("RFID") system. For examples of RFID related systems, see U.S. patent application Ser. No. 11/501,348, entitled "Radio Frequency Identification Interrogation Systems and Methods of Operating the Same," to Roemerma, et al., filed Aug. 9, 2006, now U.S. Patent Application Publication No. 2007/0035383, U.S. Pat. No. 7,019,650 entitled "Interrogator and Interrogation System Employing the Same," to Volpi, et al., issued on Mar. 28, 2006, U.S. Patent Application Publication No. 2006/0077036, entitled "Interrogation System Employing Prior Knowledge About An Object To Discern An Identity Thereof," to Roemerma, et al., filed Sep. 29, 2005, U.S. Patent Application Publication No. 2006/0017545, entitled "Radio Frequency Identification Interrogation Systems and Methods of Operating the Same," to Volpi, et al., filed Mar. 25, 2005, U.S. Patent Application Publication No. 2005/0201450, entitled "Interrogator And Interrogation System Employing The Same," to Volpi, et al., filed Mar. 3, 2005, all of which are incorporated herein by reference.

Referring now to FIG. 1, illustrated is a view of an embodiment of a weapon system in accordance with the principles of the present invention. The weapon system includes a delivery vehicle (e.g., an airplane such as an F-14) **110** and at least one weapon. As demonstrated, a first weapon **120** is attached to the delivery vehicle (e.g., a wing station) and a second weapon **130** is deployed from the delivery vehicle **110** intended for a target. Of course, the first weapon **120** may be attached to a rack in the delivery vehicle or a bomb bay therein.

The weapon system is configured to provide energy as derived, without limitation, from a velocity and altitude of the delivery vehicle **110** in the form of kinetic energy ("KE") and potential energy to the first and second weapons **120, 130** and, ultimately, the warhead and destructive elements therein. The first and second weapons **120, 130** when released from the delivery vehicle **110** provide guided motion for the warhead to the target. The energy transferred from the delivery vehicle **110** as well as any additional energy acquired through the first and second weapons **120, 130** through propulsion, gravity or other parameters, provides the kinetic energy to the warhead to perform the intended mission. While the first and second

weapons **120, 130** described with respect to FIG. 1 represent precision guided weapons, those skilled in the art understand that the principles of the present invention also apply to other types of weapons including weapons that are not guided by guidance technology or systems.

In general, it should be understood that other delivery vehicles including other aircraft may be employed such that the weapons contain significant energy represented as kinetic energy plus potential energy. As mentioned above, the kinetic energy is equal to " $\frac{1}{2}mv^2$ ," and the potential energy is equal to "mgh" where "m" is the mass of the weapon, "g" is gravitational acceleration equal to 9.8 M/sec<sup>2</sup>, and "h" is the height of the weapon at its highest point with respect to the height of the target. Thus, at the time of impact, the energy of the weapon is kinetic energy, which is directed into and towards the destruction of the target with little to no collateral damage of surroundings. Additionally, the collateral damage may be further reduced if the warhead is void of an explosive charge.

Turning now to FIG. 2, illustrated is a diagram demonstrating a region including a target zone for a weapon system in accordance with the principles of the present invention. The entire region is about 200 meters (e.g., about 2.5 city blocks) and the structures that are not targets take up a significant portion of the region. For instance, the weapon system would not want to target the hospital and a radius including about a 100 meters thereabout. In other words, the structures that are not targets are danger close to the targets. A barracks and logistics structure with the rail line form the targets in the illustrated embodiment.

Turning now to FIG. 3, illustrated is a perspective view of an embodiment of a weapon constructed according to the principles of the present invention. The weapon includes a guidance section **310** including a target sensor (e.g., a laser seeker) **320**, and guidance and control electronics and logic to guide the weapon to a target. The target sensor **320** may include components and subsystems such as a crush switch, a semi-active laser based terminal seeker ("SAL") quad detector, a net cast corrector and lenses for an optical system. In accordance with SAL systems, net cast optics are suitable, since the spot for the terminal seeker is normally defocused.

The guidance section **310** may include components and subsystems such as a GPS, an antenna such as a ring antenna **330** (e.g., dual use handoff and data and mission insertion similar to radio frequency identification and potentially also including responses from the weapon via similar means), a multiple axis microelectromechanical gyroscope, safety and arming devices, fuzing components, a quad detector, a communication interface [e.g., digital subscriber line ("DSL")], and provide features such as low power warming for fast acquisition and inductive handoff with a personal information manager. In the illustrated embodiment, the antenna **330** is about a surface of the weapon. Thus, the antenna is configured to receive mission data such as location, laser codes, GPS ephemerides and the like before launching from a delivery vehicle to guide the weapon to a target. The antenna is also configured to receive instructions after launching from the delivery vehicle to guide the weapon to the target. The weapon system, therefore, includes a communication system, typically within the delivery vehicle, to communicate with the weapon, and to achieve other goals and ends in the context of weapon system operation. It should be understood that the guidance section **310** contemplates, without limitation, laser guided, GPS guided, and dual mode laser and GPS guided systems. It should be understood that this antenna may be configured to receive various kinds of electromagnetic

energy, just as there are many types of RFID tags that are configured to receive various kinds of electromagnetic energy.

The weapon also includes a warhead **340** (e.g., a unitary configuration) having destructive elements (formed from explosive or non-explosive materials), mechanisms and elements to articulate aerodynamic surfaces. A folding lug switch assembly **350**, safety pin **360** and cavity **370** are also coupled to the guidance section **310** and the warhead **340**. The guidance section **310** is in front of the warhead **340**. The folding lug switch assembly **350** projects from a surface of the weapon. The weapon still further includes an aft section **380** behind the warhead **340** including system power elements, a ballast, actuators, flight control elements, and tail fins **390**.

For instances when the target sensor is a laser seeker, the laser seeker detects the reflected energy from a selected target which is being illuminated by a laser. The laser seeker provides signals so as to drive the control surfaces in a manner such that the weapon is directed to the target. The tail fins **390** provide both stability and lift to the weapon. Modern precision guided weapons can be precisely guided to a specific target so that considerable explosive energy is often not needed to destroy an intended target. In many instances, kinetic energy discussed herein may be sufficient to destroy a target, especially when the weapon can be directed with sufficient accuracy to strike a specific designated target.

The destructive elements of the warhead **340** may be constructed of non-explosive materials and selected to achieve penetration, fragmentation, or incendiary effects. The destructive elements (e.g., shot) may include an incendiary material such as a pyrophoric material (e.g., zirconium) therein. The term "shot" generally refers a solid or hollow spherical, cubic, or other suitably shaped element constructed of explosive or non-explosive materials, without the aerodynamic characteristics generally associated with, for instance, a "dart." The shot may include an incendiary material such as a pyrophoric material (e.g., zirconium) therein. Inasmuch as the destructive elements of the warhead are a significant part of the weapon, the placement of these destructive elements, in order to achieve the overall weight and center of gravity desired, is an important element in the design of the weapon.

The non-explosive materials applied herein are substantially inert in environments that are normal and under benign conditions. Nominally stressing environments such as experienced in normal handling are generally insufficient to cause the selected materials (e.g., tungsten, hardened steel, zirconium, copper, depleted uranium and other like materials) to become destructive in an explosive or incendiary manner. The latent lethal explosive factor is minimal or non-existent. Reactive conditions are predicated on the application of high kinetic energy transfer, a predominantly physical reaction, and not on explosive effects, a predominantly chemical reaction.

The folding lug switch assembly **350** is typically spring-loaded to fold down upon release from, without limitation, a rack on an aircraft. The folding lug switch assembly **350** permits initialization after launch (no need to fire thermal batteries or use other power until the bomb is away) and provides a positive signal for a fuze. The folding lug switch assembly **350** is consistent with the laser guided bomb ("LGB") strategy using lanyards, but without the logistics issues of lanyards. The folding lug switch assembly **350** also makes an aircraft data and power interface optional and supports a visible "remove before flight" pin. The folding lug switch assembly **350** provides a mechanism to attach the weapon to a delivery vehicle and is configured to close after launching from the delivery vehicle thereby satisfying a cri-

terion to arm the warhead. It should be understood, however, that the folding lug switch assembly **350**, which is highly desirable in some circumstances, can be replaced with other means of carriage and suspension, and is only one of many features of the present invention, which can be applied in different combinations to achieve the benefits of the weapon system.

Typically, the safety pin **360** is removed from the folding lug switch assembly **350** and the folding lug switch assembly **350** is attached to a rack of an aircraft to hold the folding lug switch assembly **350** in an open position prior to launch. Thus, the safety pin **360** provides a mechanism to arm the weapon. Once the weapon is launched from the aircraft, the folding lug switch assembly **350** folds down into the cavity **370** and provides another mechanism to arm the weapon. A delay circuit between the folding lug switch assembly **350** and the fuze may be yet another mechanism to arm or provide time to disable the weapon after launch. Therefore, there are often three mechanisms that are satisfied before the weapon is ultimately armed enroute to the target.

A number of circuits are now well understood that use power from radio frequency or inductive fields to power a receiving chip and store data. The antenna includes an interface to terminate with the aircraft interface at the rack for loading relevant mission data including target, location, laser codes, GPS ephemerides and the like before being launched. Programming may be accomplished by a hand-held device similar to a fuze setter or can be programmed by a lower power interface between a rack and the weapon. Other embodiments are clearly possible to those skilled in the art. The antenna serves a dual purpose for handoff and GPS. In other words, the antenna is configured to receive instructions after launching from the delivery vehicle to guide the weapon to the target. Typically, power to the weapon is not required prior to launch, therefore no umbilical cable is needed. Alternative embodiments for power to GPS prior to launch are also contemplated herein.

The modular design of the weapon allows the introduction of features such as GPS and other sensors as well. Also, the use of a modular warhead **340** with heavy metal ballast makes the low cost kinetic [no high explosives ("HE")] design option practical and affordable.

As illustrated in an exemplary embodiment of a weapon in the TABLE 1 below, the weapon may be designed to have a similar envelope, mass, and center of gravity already present in existing aircraft for a practice bomb version thereof. Alternatively, the weapon may be designed with other envelopes, masses, and centers of gravity, as may be available with other configurations, as also being included within the constructs of this invention.

TABLE 1

FUNCTION	MATERIAL	DENSITY (LB/CU IN)	WEIGHT (LB)	VOLUME (CU IN)
Ballast/KE	Tungsten	0.695	20.329	29.250
Structure, Metal	Aluminum	0.090	0.270	3.000
Augmented Charge ("MAC")				
Explosive				
Dome	Pyrex	0.074	0.167	2.250
Structure	Steel	0.260	1.430	5.500



TABLE 1-continued

FUNCTION	MATERIAL	DENSITY (LB/CU IN)	WEIGHT (LB)	VOLUME (CU IN)
Guidance	Misc Electronics	0.033	0.800	24.000
Primary Explosive	Polymer Bonded Explosive ("PBX")	0.057	2.040	36.000
Total	SSW	0.250	25.036	100.000
MK-76		0.250	25.000	100.000

In the above example, the weapon is MK-76 derived, but others such as BDU-33 are well within the broad scope of the present invention. The weapon provides for very low cost of aircraft integration. The warhead **340** is large enough for useful warheads and small enough for very high carriage density. The modular design of the weapon allows many variants and is compatible with existing handling and loading methods.

The following TABLES 2 and 3 provide a comparison of several weapons to accentuate the advantages of small smart weapons such as the MK-76 and BDU-33.

TABLE 2

CANDIDATE	AIRCRAFT ("A/C") CLEARED	WEIGHT (LB)	DIAMETER (IN - APPROX)	REMARKS
LGB/MK-81	None	250+	10	Canceled variant
MK-76/BDU33	All	25	4	Low drag practice bomb
BDU-48	All	10	3.9	High drag practice bomb
MK-106	All	5	3.9	High drag practice bomb
SDB	Most US	285	7.5	GBU-39 Small Dia. Bomb

TABLE 3

CANDIDATE	CLEARED ON MANY A/C?	LARGE ENOUGH FOR WARHEAD?	VIABLE FOR EXPORT?	HIGH DENSITY CARRIAGE?	COMPATIBLE WITH TUBE LAUNCH?
LGB/MK-81	No	Yes	Yes	No	No
MK-76/BDU33	All	Yes	Yes	Yes	Yes
BDU-48	All	No	Yes	Yes	Yes
MK-106	All	No	Yes	Yes	Yes
SDB	Most US	Yes	No	Yes	No

The aforementioned tables provide a snapshot of the advantages associated with small smart weapons, such as, procurements are inevitable, and the current weapons have limited utility due to political, tactical, and legal considerations. Additionally, the technology is ready with much of it being commercial off-the-shelf technology and the trends reflect these changes. The smart weapons are now core doctrine and contractors can expect production in very large numbers. Compared to existing systems, small smart weapons exhibit smaller size, lower cost, equally high or better accuracy, short time to market, and ease of integration with an airframe, which are key elements directly addressed by the weapon disclosed herein. As an example, the small smart weapon could increase an unmanned combat air vehicle ("UCAV") weapon count by a factor of two or more over a small diameter bomb ("SDB") such as a GBU-39/B.

The small smart weapons also address concerns with submunitions, which are claimed by some nations to fall under the land mine treaty. The submunitions are a major source of unexploded ordnance, causing significant limitations to force

maneuvers, and casualties to civilians and blue forces. Submunitions are currently the only practical way to attack area targets, such as staging areas, barracks complexes, freight yards, etc. Unexploded ordnance from larger warheads are a primary source of explosives for improvised explosive devices. While the broad scope of the present invention is not so limited, small smart weapons including small warheads, individually targeted, alleviate or greatly reduce these concerns.

Turning now to FIG. 4, illustrated is a diagram demonstrating a region including a target zone for a weapon system in accordance with the principles of the present invention. Analogous to the regions illustrated with respect to FIG. 2, the entire region is about 200 meters (e.g., about 2.5 city blocks) and the structures that are not targets take up a significant portion of the region. In the illustrated embodiment, the lethal diameter for the weapon is about 10 meters and the danger close diameter is about 50 meters. Thus, when the weapon strikes the barracks, rail line or logistics structure as shown, the weapon according to the principles of the present invention provides little or no collateral damage to, for instance, the hospital. While only a few strikes of a weapon are illustrated

herein, it may be preferable to cause many strikes at the intended targets, while at the same time being cognizant of the collateral damage.

In an exemplary embodiment, a sensor of the weapon detects a target in accordance with, for instance, pre-programmed knowledge-based data sets, target information, weapon information, warhead characteristics, safe and arm events, fuzing logic and environmental information. In the target region, sensors and devices detect the target and non-target locations and positions. Command signals including data, instructions, and information contained in the weapon (e.g., a control section) are passed to the warhead. The data, instructions, and information contain that knowledge which incorporates the functional mode of the warhead such as safe and arming conditions, fuzing logic, deployment mode and functioning requirements.

The set of information as described above is passed to, for instance, an event sequencer of the warhead. In accordance therewith, the warhead characteristics, safe and arm events, fuzing logic, and deployment modes are established and

## 11

executed therewith. At an instant that all conditions are properly satisfied (e.g., a folding lug switch assembly is closed), the event sequencer passes the proper signals to initiate a fire signal to fuzes for the warhead. In accordance herewith, a functional mode for the warhead is provided including range characteristics and the like. Thereafter, the warhead is guided to the target employing the guidance section employing, without limitation, an antenna and global positioning system.

Thus, a class of warhead assemblies, constituting systems, methods, and devices, with many features, including multiple, modular guidance subsystems, avoidance of collateral damage, unexploded ordinance, and undesirable munitions sensitivity has been described herein. The weapon according to the principles of the present invention provides a class of warheads that are compatible with existing weapon envelopes of size, shape, weight, center of gravity, moment of inertia, and structural strength, to avoid lengthy and expensive qualification for use with manned and unmanned platforms such as ships, helicopters, self-propelled artillery and fixed wing aircraft, thus constituting systems and methods for introducing new weapon system capabilities more quickly and at less expense. In addition, the weapon system greatly increases the number of targets that can be attacked by a single platform, whether manned or unmanned.

Turning now to FIG. 5, illustrated is a diagram of an embodiment of a folding lug switch assembly constructed in accordance with the principles of the present invention. More specifically, a folding lug of the folding lug switch assembly is shown in an upright position **505** and in a folded position **510**. The folding lug switch assembly includes a rack and pinion **515**, which in an alternative embodiment can also be a cam. The folding lug switch assembly also includes a return spring **520** that provides the energy to fold the folding lug down and retract a retracting cam **525**, which interacts with a switch sear **530** to release an arming pin **535** and thus activate an arming rotor **540**, an arming plunger **545**, and finally a power switch **550**. This invention comprehends a folding lug switch assembly that may have multiple functions beyond arming including weapon guidance. It may also have multiple poles and multiple throws that, as an example, may be used for purposes such as isolating arming circuits from other circuits.

Referring once more to the target sensor discussed above, a semi-active laser ("SAL") seeker is typically the most complex item in SAL guided systems, and SAL is the most commonly used means of guiding precision weapons. Therefore, a low cost and compact approach, consistent with a very confined space, is highly desirable.

Turning now to FIGS. 6A and 6B, illustrated are diagrams demonstrating a four quadrant semi active laser detector constructed in accordance with the principles of the present invention. More specifically, FIG. 6A represents a typical four quadrant seeker having quadrants A, B, C, and D. This system is capable of providing both elevation information ("EL") and azimuth information ("AZ") according to the following equations:

$$EL = ((A+B) - (C+D)) / (A+B+C+D), \text{ and}$$

$$AZ = ((A+D) - (B+C)) / (A+B+C+D).$$

A reflected spot from a laser **605** is shown in quadrant B where the spot is focused on the plane of the active detecting area.

Turning now to FIG. 6B, illustrated is the same basic conditions of FIG. 6A, except that a spot **610** has been intentionally defocused so that, for a target near bore sight, a linear (i.e., proportional) output results. By these illustrations, it is

## 12

therefore seen that focused systems are prone to indicate in which quadrant a signal may reside, while a defocused system will support proportional guidance as shown by illuminating more than one quadrant in the region of boresight where proportional guidance is most important.

Turning now to FIGS. 7A and 7B, illustrated are the properties of a conventional and fast fresnel lens ("FFL") constructed in accordance with the principles of the present invention. More specifically, FIG. 7A illustrates an embodiment of the focusing element of a SAL employing a conventional convex lens. The small volumes require fast optics which are usually expensive. Also, linear outputs are hard to achieve with fast optics or low cost, and nearly impossible with both. Point **710** illustrates a correct focus point and point **705** illustrates error in the lens' focusing ability. For reasonable angles, this error is often quite small.

Turning now to FIG. 7B, illustrated is an illustration of an embodiment of the present invention employing a FFL. A fresnel lens is a type of lens invented by Augustin-Jean Fresnel and originally developed for lighthouses, as the design enables the construction of lenses of large aperture and short focal length without the weight and volume of material which would be required in conventional lens design. Compared to earlier lenses, the fresnel lens is much thinner, thus passing more light. Note that it is often constructed with separate concentric ridges. This innovative approach provides reductions in weight, volume, and cost. A point **720** illustrates a correct focus, wherein a point **715** illustrates an error in the FFL's ability to provide a correct focus. Though this lens is smaller and lighter, the error in correct focus, even for small angles off boresight is not insignificant.

An alternative embodiment that specifically addresses the focus errors discussed above for a FFL is to add lens stopping (i.e., optical barriers) in those regions where unwanted energy is most likely to originate. This slightly reduces the amount of light passed on by the lens, but also significantly reduces the focusing error for a net gain in performance.

Yet another embodiment of this invention is to replace the concentric circles of the FFL with randomized circles as illustrated in FIG. 8. Fresnel lens boundaries between surfaces are well known sources of some of the problems illustrated above. Concentric circles **805** are typical of this problem. By innovatively using a pseudo-random walk to define the boundaries, instead of concentric circles, the scattering is much more random, resulting in a less focused scattering pattern and therefore focusing errors are less likely to constructively interfere. Thus, the fast fresnel lens is formed from multiple substantially concentric circles to which is added a pseudo-random walk that results in small local perturbations of a respective substantially concentric circle. In other words, the fast fresnel lens is formed from multiple substantially concentric circles that include random perturbations **810**. Additionally, for lenses that are cast, rather than ground, there is no need for the lens surface boundaries to be circular. Yet another embodiment of this invention is to introduce multi-element hybrid optics employing both conventional and hybrid optics.

Turning now to FIGS. 9A and 9B, illustrated are views of an embodiment of hybrid optics employable with a guidance section of a weapon constructed in accordance with the principles of the present invention. FIG. 9A illustrates an embodiment employing a clear front lens **905** with no optical properties other than being transparent at the optical wavelength of interest. The focusing is accomplished by a FFL **910** as illustrated by rays **915**, **920** where it can be seen that no focusing is accomplished by the clear front lens. Contrast this with the embodiment illustrated in FIG. 9B where a front lens

## 13

925 of a target sensor of the guidance section, in concert with a FFL 930 focuses the incoming optical signals 935, 940 and, in so doing, generates a shorter focal length  $F_L$  than was generated in FIG. 9A for the same use of volume. The front lens 925 provides a cover to protect the target sensor from environmental conditions and the FFL 930 behind the front lens 925 cooperates with the front lens 925 to provide a multi-lens focusing system for the target sensor.

Therefore, by placing a small amount of optical focusing power in the front lens 925, the focal length of the FFL 930 is allowed to be longer, making it easier to manufacture, while the optical system of FIG. 9B has the desirable property of a shorter focal length. Also, for clarity, note that the drawings of the FFL are not to scale. These lenses often are composed of hundreds of very small rings that are familiar and commonly known to those skilled in the art. Thus, a hybrid system as described herein employs less glass with additional favorable properties of less weight and optical loss. Finally, yet another embodiment is to use the back planar surface of the FFL 930 as a location for an optical filter 945 for filtering of unwanted wavelengths, for example most of the solar spectrum. An embodiment of the invention is an integral aft section, tail fin, actuators, and prime power.

Turning now to FIG. 10, illustrated is a view of an embodiment of an aft section constructed in accordance with the principles of the present invention. More specifically, FIG. 10 illustrates an aft section showing the location of a battery and linear actuators 1005, and each single piece tail fin 1010 to which is attached an axel and linkage level connector. The power elements including batteries used in this application comprehend military batteries, but also include commercial types. As an example, lithium batteries are both light and have a considerable shelf life.

Turning now to FIG. 11, illustrated is a view of an embodiment of an aft section constructed in accordance with the principles of the present invention. More specifically, FIG. 11 demonstrates additional tail fin detail. This innovative design is based on near zero hinge moments and can use linkages and be subjected to forces consistent with radio controlled ("RC") models. Note that the linear actuator fits directly into the tubular aft section 1105. In one embodiment, each of two pairs of tail fins 1110 operate in tandem while in an alternative embodiment, each fin is an independent moving surface. Under certain circumstances, of varying flight conditions, there are advantages to be gained in flight performance by changing the aspect ratio of the wings. This capability is typically relegated to larger aircraft, but this invention comprehends an innovative implementation of providing variable aspect ratio in a very limited space.

Turning now to FIGS. 12A and 12B, illustrated are views of an embodiment of a variable aspect wing ratio for the tail fins of an aft section constructed in accordance with the principles of the present invention. In this embodiment, a rear fuselage 1205 and tail fins 1210 contain a rod 1215 that moves in a direction, back and forth, along the centerline of the rear fuselage. This causes links 1220 to force rods 1225 along the centerline of the tail fins 1210 in a direction that is normal to rod 1215. In so doing, surface 1230 is retracted and extended as illustrated by extendable surface 1235. An end view (see FIG. 12B) of the tail fin 1210 along with the extendable surface 1235 is also illustrated. Therefore, with surface 1230 retracted, using formulas familiar to those skilled in the art, the aspect ratio A, defined as the ratio of the span of the wings squared to the wing planform (e.g., shape and layout of the tail fin) area is  $A = ((B/2)^2)/(B * C)$ . With the extendable surface 1235 extended as shown, the aspect ratio becomes  $A = ((2 * ((B/2 + b)^2)/(B * C + 2 * b * c))$ , thus clearly showing a

## 14

change in aspect ratio. Thus, the tail fin 1210 has a modifiable control surface area, thereby changing an aspect ratio thereof. An alternative embodiment using spring steel plates is also comprehended by this invention as discussed below.

Turning now to FIGS. 13A to 13F, illustrated are views of an embodiment of a variable aspect wing ratio for the tail fins of an aft section constructed in accordance with the principles of the present invention. More specifically, FIG. 13A illustrates a planform view of a tail fin 1305 with a cutout including a rod 1310 that moves in a manner similar to that illustrated in FIGS. 12A and 12B, except that in this embodiment the variable surface is replaced by a deformable surface (e.g., spring steel sheet 1325) shown in the end view of FIG. 13B in an extended status. The spring steel sheet 1325 is coupled to the rod 1310 via a pin 1315 and dowel 1320 as illustrated in FIG. 13C, which provides a front view without the tail fin. Thus, by moving the rod 1330, variable aspect ratio is achieved again in a very confined space. As illustrated in FIG. 13D, the spring steel sheet 1325 is partially retracted to modify the control surface area of the tail fin (not shown in this FIGURE). Finally, FIG. 13E illustrates a planform view of the tail fin 1305 having a cutout with the spring steel sheet 1325 retracted thereby further modifying the control surface area of the tail fin 1305 and changing an aspect ratio thereof (see, also, FIG. 13F, which illustrates a front view with the tail fin removed). Thus, the tail fin 1305 has a deformable surface 1325 coupled to a rod 1310, pin 1315 and dowel 1320 configured to extend or retract the deformable surface 1325 within or without the tail fin 1305.

Yet another embodiment of variable aspect ratio is also comprehended by this invention wherein the tail fin dimensions may not change in flight. Referring now to FIGS. 14A to 14D, illustrated are views of another embodiment of a weapon including the tail fins of an aft section thereof constructed in accordance with the principles of the present invention. FIG. 14A illustrates an end view of a present tail fin 1405. For reliability and strength, it may be desirable to change its shape, however, in doing so, the aerodynamic characteristics of the tail fin 1405 may also change dramatically. Therefore, FIG. 14B of the weapon 1415 includes a variably shaped tail fin 1410 that does not vary the aerodynamic characteristics of the tail fin and therefore the weapon. This is because the body of the weapon 1415 as illustrated in FIG. 14C is large with respect to the cylindrical area of the tail section 1420, thereby prohibiting much of the airflow around the tail fins at their base. The end view of FIG. 14D illustrates the shaped tail fin 1425 with characteristics of the flat fin outside the diameter of the weapon body and also showing additional mass and therefore strength in that area of the fin that is not active due to body shading.

In accordance with a guidance section, a target sensor (also referred to as a seeker such as a laser seeker) detects energy that provides directional information to guide a weapon to a target. The seekers may be "active" emitting energy as in the case of radar, "passive" as in the case of a weapon using a television image based on natural illumination, or "semi-active" as in the case of laser guided bombs, wherein a laser spot designates the target. The weapon as described herein may employ active, passive or semi-active seekers. Additionally, the seeker as described herein takes into account arbitrary aerodynamic shapes without compromising the optical objective apertures and is consistent with the ongoing pressures for reduced cost, weight and volume.

Guided weapons were first used in World War II and, late in the war, Germany, the United States and others were developing and deploying the first guided weapons with "terminal guidance" or a "seeker" to attack moving targets, or to arrive

15

at an aim point with a small miss distance. These early systems, such as the German "Fritz-X" and the allied special weapons ordnance device ("SWOD") MK-9/air-to-surface missile ("ASM")-N-2 "BAT" are recognizable as guided weapons with functional block diagrams similar to those in service today.

However, the size and weight of the elements is remarkably different. The BAT is considered by many historians to be the first true fire and forget guided weapon with a seeker unaided by an operator and data link. The BAT is exemplary of seeker trends and challenges. The BAT weighed roughly 1000 kilograms ("kg") and had a wingspan of about 3 meters. Roughly 40% of the weight of the system was not the warhead. The BAT used three large lead acid batteries as a power source. These were much larger than the batteries commonly found in automobiles today, so just the power source for BAT was larger than some modern guided weapons such as the TOW or Javelin (Javelin weighs less than 30 kg).

The components of guided weapons have seen remarkable reduction in size and cost. The Javelin, with a warhead weight of less than 10 kg can penetrate more than half a meter of armor, a feat that would have required a warhead mass at least ten times greater in 1950. The signal processing electronics in the BAT relied on less than 20 vacuum tubes. Each tube was roughly a thousand times larger and used roughly a thousand times more power than one modern digital signal processor ("DSP"). So, components other than the seeker have seen four orders of magnitude, or more reduction in size and, in many cases, the costs have fallen dramatically as well.

Thus, the state of the art seekers' performance can be changed in response to modern objectives. In particular, the need to package seekers based on demands of airframes' allowance for weight (e.g., less than 1 kg), volume (e.g., less than 0.1 liters) and outer mold line have become quite challenging. In the past, the leading edge of the weapon was generally a compromise between airframe needs and the design constraints of the seeker. For instance, the flight and guidance times have been reduced from a minute to 10 seconds and the accuracy is critical to the reduction of warhead size and collateral damage. The seeker as described herein eliminates many of the past compromises.

Semi active laser ("SAL") seekers are among the simplest of weapon guidance devices. SAL seekers employ parabolic optical lenses and limited integration (e.g., Hellfire has electronic counter-countermeasures ("ECCM") in a separate chip and Paveway III has gyros on its gimbals as well as body fixed gyros). Also, the SAL seekers employ functional separation such as sensor stabilization separate from line-of-sight ("LOS") estimation and error correction (if any) is performed by additional optical elements (see, e.g., U.S. Patent Application No. 2007/0187546 entitled "Binary Optics SAL Seeker (BOSS)," to Layton, published Aug. 16, 2007, which is incorporated herein by reference. Generally, such seekers operate at only one or two optical wavelengths, and have detectors with as few as four elements. They are found in the least expensive guided weapons, such as laser guided bombs. While these systems have provided much of the stimulus for low cost, they have also continued to demonstrate many of the compromises discussed previously. Similar examples can be given for other classes of seekers. However, since even the most basic seekers demonstrate these undesirable attributes, it will be apparent to those skilled in the art that more sophisticated seekers also manifest these attributes.

Turning now to FIGS. 15A to 15D, illustrated are side views of embodiments of nose cones (e.g., tangent, secant, true and blunt ogive nose cones, respectively) of a warhead of a weapon in accordance with the principles of the present

16

invention. Basic ogives were used in rifled ammunition before the American Civil War and by both sides during the Civil War (for example, many Mason & McKee bullets). The shapes of this class include relatively simple classic ogives, as shown here, and more complex forms, such as the von Kármán Ogive. A summary of geometry of these bodies can be found at the web site of Virginia Tech ([http://www.aoe.vt.edu/~mason/Mason\\_f/CAtxtAppA.pdf](http://www.aoe.vt.edu/~mason/Mason_f/CAtxtAppA.pdf), which is incorporated herein by reference), wherein a summary of geometry for aerodynamicists is presented.

While the bodies presented may be well defined by algebraic equations, the considerations that determine these shapes is aerodynamic, and the effect of the shape on electromagnetic energy, that may need to pass through a transparent window in the nose or forepart, is often not a consideration. The shape of these bodies has been a challenge for seeker designers, and a number of compromises have been required to deal with the challenges. Some of the compromises are unsatisfactory and create significant system costs in terms of price, weight, performance, or other costs. Moreover, theoretical shapes are idealized representations of systems that can be practically realized. For this reason, these shapes are sometimes called ogival, or near ogive.

An arc of rotation is often used to describe an ogive. A formula is useful for modern machining and analysis methods. The formula for a tangent ogive is shown below, wherein x, y are coordinates, x being along the length of the cone, and y being the height (or radius) of the cone taken from the centerline of the cone.

$$y = \sqrt{\left(d\left(C^2 + \frac{1}{4}\right)\right)^2 - x^2} - \left(d\left(C^2 - \frac{1}{4}\right)\right)$$

The caliber of the cone is  $C=L/d$ , wherein L is the cone length and d is the cone base diameter.

A number of practical factors should be considered in the design of a nose shape. Examples of nose shapes include bi-conic, spherically blunted cones, spherically blunted ogives, HAACK, elliptical ogives, parabolic (which generally has a sharp tip similar to a tangent ogive), and so called power series (which often produces the best result in terms of drag). Some of these shapes are more practical than others. In addition, mission requirements such as the need for a fuzing crush switch (e.g., for contact fuzing) on or near the nose, or the need to provide for penetration kinematics can also be factors in the final design. So, it should be clear that a wide range of factors (aerodynamics, manufacturing processes, environmental demands, fuzing, penetration) should come to bear in the selection of the nose shape of a guided missile, and that optical (or antenna) issues cannot be the sole design criteria for selecting the shape, material and other nose features. Those skilled in the art will recognize that the factors described here are exemplary and not an exhaustive list. Clearly, a seeker approach that accommodated non-optical (or antenna) concerns would be very useful.

Turning now to FIGS. 16A and 16B, illustrated are exploded views of an embodiment of a nose cone (e.g., a blunt ogive nose cone) of a warhead of a weapon in accordance with the principles of the present invention. The nose cone includes a shaped region or section 1610 defined by a selected ogive or other shape (e.g., von Kármán Ogive) with fineness ratio determined by mach regime and payload considerations. The nose cone includes a transition region or section 1620 defined by a section of a true cone between the regions thereabout. The nose cone also includes a forward region or section

1630 with a diameter determined by nose cone material strength, mach regime, thermal characteristics and other considerations.

As illustrated in FIG. 16B, the forward section 1630 of the nose cone, which is transparent to the electromagnetic energy being sensed, can interact very differently with targets that are off bore sight to varying degrees (e.g., due to lensing effects or other aberrations in the nominally transparent material) to the extent that there may not be a one-to-one manifold between target line-of-sight and an output of a detector 1640. In the example shown, target A is only influenced by the spherical region of the seeker window. Depending on the dimensions of a hemi dome, and the index of refraction, and on other characteristics, a target in this region may be inverted as shown by the dashed arrows associated with the target A ray tracing. Note that the target A image is not in sharp focus because in this exemplary embodiment, a SAL seeker is depicted. The SAL seekers typically involve a degree of intentional defocus. Target A is relatively undistorted and the seeker designer would select the hemi-dome to be a parabolic section, rather than a spherical section, as a modest compromise between optical performance and aerodynamic theory.

In contrast, target C is not inverted by the nose cone, but because the geometry of the regions presents different angles of incidence to incoming rays, the resulting dashed arrow associated with target C is bent or distorted. As the maneuverability of guided weapons has increased, the importance of these considerations has increased because of the need to achieve high angles of attack, and to attack targets far from bore sight. If a ray is traced for target B, it would be influenced by all three regions. Note that significant errors have been introduced before an objective lens 1650. The optical train that begins with the objective lens 1650 and ends with a sensor of some type, will also have limitations such as imperfect collimation. As errors propagate and compound, it can be difficult or even impossible to generate useful guidance signals.

It is clear to those skilled in the art that complex nose shapes and large line-of-sight angles pose a challenge to the seeker designer. Further, the need to provide for a very large window, forward of an opaque region 1660 can be quite costly and in some applications materials with the right combination of thermal, optical, and structural characteristics can cause the dome to be the most expensive component in the seeker, if the design can be realized at all.

Turning now to FIG. 17, illustrated is an isometric view of an embodiment of a seeker employing a catadioptric optical system and a two axis gimbal set, with onboard gyroscopes for stabilization and line-of-sight measurement. The seeker includes a dome 1710 (with a dome retainer ring 1720), an el and az trunnion assembly 1730, 1740 about primary and second mirrors or lens 1750, 1760, a gimbal ring or gimbal 1770, a gyro 1780, a calibration motor 1790 and a focal plane array ("FPA")/dewar assembly 1795. In this case, a cryogenically cooled focal plane array resides on the gimbal 1770, so the cryogenic system moves with the gimbal 1770. Note that the seeker's hemi-dome 1710 is different from the types of shapes sought by aero dynamists and occupies nearly the frontal area of the warhead. The seeker shown here is a single mode device. When dual or tri mode seekers are employed more complexity is often the result.

Note that the primary optical aperture (primary mirror 1750) is smaller than the dome 1710. In this case, the primary mirror 1750 is set by the need for optical gain, and a fast f-number. The dome size, however, is set by the need to point the primary mirror 1750 toward the target because the instantaneous field of view is too small to engage all of the needed

target geometries. The dome size is also influenced by the dimensions of the telescope assembly and of the gimbal set. If a smaller telescope with a large instantaneous field of view is used, the seeker could be designed with less complexity and cost.

Thus, advantageous characteristics of seekers include a small diameter objective to permit placement as far forward as possible in the warhead and support for line-of-sight angles. Additionally, seekers should support nose shapes determined by aerodynamics, material properties, manufacturing tolerances and cost. Seekers should also employ simple means to correct for optical errors with the need to accommodate multi-mode sensors operating at different wavelengths. It would also be beneficial to avoid complexity and high component counts to include a low number of optical components, no gimbals, simple collimation and simple assembly.

Turning now to FIGS. 18A and 18B, illustrated are views of an embodiment of a seeker constructed according to the principles of the present invention. A spherical section (e.g., a hemi-dome 1810) is an objective lens whose external shape is set by non-optical considerations. The back surface 1850 of the objective lens integrates a number of features as set forth below. For SAL seekers, this implementation is practical because a sensitivity of a detector 1820 is adequate to support primary aperture areas less than the detector area. As illustrated, the area that can be an opaque region 1830 to optical wavelengths is obviously much larger than in the previous embodiment. This supports a variety of other seeker types and, therefore, accommodates dual and tri mode seekers. The seeker also includes a standoff (e.g., a standoff tube 1840) for placing the detector a fixed distance from the hemi-dome 1810, which is practical in view of the correction map described below.

In FIG. 18B, it is more clearly seen that the shape chosen for the hemi-dome 1810 is somewhat arbitrary from the optics designer's perspective. The central region 1860 of front surface 1880 of the objective lens is a flattened cone, and the outer region 1870 is a somewhat sharper cone and is thus termed biconic. The cross section is described by straight lines, not parabolic curves. This is exemplary of the types of choices that aerodynamic heating and manufacturing considerations might dictate, if optics were not considered. The back surface 1850 of the objective lens is a shape chosen by the optics designer to provide a complementary corrective curvature, so that the resulting optical performance roughly matches a more conventional lens. The concept of a complementary corrective curvature will be familiar to laymen whose optometrists have prescribed corrective lens for astigmatism. The lens within the human eye can have distortions, but a complementary correction can provide undistorted vision. For those skilled in telescope design, another example is the common practice of producing catadioptric optical systems with a spherical objective reflector, but correcting for spherical aberration by means of a corrector lens, thus lowering the cost of the overall telescope. Modern optical design software has made practical the design of corrective curvature, whether for eyeglasses, or for telescopes.

Those skilled in the art of optics design will recognize the rough approximation of a classic "fish eye" objective, with a wide field of view, but will also recognize that in addition to typical fish eye distortion, additional distortion has been created by the flattened front surface, and by the practical limits of correction of the back surface. The classic optics approach to solving these problems would be to add additional glass types, creating a doublet or triplet, to add additional elements (either lens or corrective holograms), or some combination of

these features. An example of such multi-element approach can be found in Layton introduced above.

Clearly, this approach is much less complex and, therefore, less expensive. For the SAL seeker, it is likely that the objective lens could be cast from a material such as Pyrex and would not need additional polishing, since the seeker does not require sharp focus. This aspect of the seeker, however, taken alone may not provide adequate guidance accuracy for some applications.

Turning now to FIG. 19, illustrated is a cutaway view of an embodiment of a seeker **1910** with a calibration array **1920** constructed according to the principles of the present invention. A number of calibration array embodiments are possible including a planar array and the calibration array **1920** may be set up during a manufacturing or calibration stage for the seeker **1910**. In this embodiment, a spherical section of the calibration array supports a number of emitters. As each emitter under control of an array controller **1930** illuminates the objective lens of the seeker, a data logger **1940** makes a record of the seeker response to the illumination.

In the illustrated embodiment, the illumination (depicted by the dashed arrow) is 60 degrees off bore sight. By illuminating the seeker from a plurality of locations across the calibration array **1920**, a seeker response map can be constructed. By comparing the seeker response map with the known angles of illumination, a seeker correction map can be constructed that render less complex and inexpensive weapons comparable in performance to weapons of higher complexity and cost.

For some sensor types, nonlinear response will dictate that a plurality of maps be constructed to accommodate illumination polarization, intensity and other characteristics. The details of the mapping strategy is dictated by the characteristics of the detector, and of the type of electromagnetic energy detected. However, the primary requirement for the calibration system to provide a useful seeker response map is that the transfer function provided by the optical system from incoming illumination to electrical output be a one-to-one manifold.

Turning now to FIG. 20, illustrated is a block diagram of an embodiment of a seeker (e.g., a SAL seeker) constructed according to the principles of the present invention. Incoming target illumination (e.g., a distorted signal) impinges on a front surface **2010** of an objective lens, whose shape may be determined by criteria other than optics. The illumination energy passes through the lens material, refracting and exiting via the back surface **2020**, whose shape was designed to approximate a corrective shape, correcting for the front surface **2010**.

The objective lens is positioned relative to a detector **2040** by a standoff (e.g., a standoff tube) **2030**. The detector is illuminated by the energy focused by the objective lens, creating a signal sent to the amplifier and analog-to-digital converter ("ADC") **2050**. A processor **2060** in connection with memory **2070** uses specified target criteria (for example, laser pulse to pulse interval) to determine if incoming signals are from a valid target, and uses the correction map to provide a more accurate line-of-sight estimate (i.e., output data including a correction signal to guide a weapon employing the seeker to the target).

The construction of the system shown here will vary with a number factors. For example, subsonic flight permits a wider range of optical materials and nose shapes than transonic or supersonic flight. The detector **2040**, objective lens, standoff **2030** and processor **2060** may be manufactured as single unit, so that errors in collimation are included in the correction map, thus lowering the cost and required precision of assembly. In this way, the correction map is integral to the seeker

head assembly reducing the chance that a correction map will be associated with the wrong seeker assembly.

The processor **2060** may be of any type suitable to the local application environment, and may include one or more of general-purpose computers, special purpose computers, microprocessors, digital signal processors ("DSPs"), field-programmable gate arrays ("FPGAs"), application-specific integrated circuits ("ASICs"), and processors based on a multi-core processor architecture, as non-limiting examples.

The memory **2070** may also include one or more memories of any type suitable to the local application environment, and may be implemented using any suitable volatile or nonvolatile data storage technology such as a semiconductor-based memory device, a magnetic memory device and system, an optical memory device and system, fixed memory, and removable memory. The programs stored in the memory may include program instructions or computer program code that, when executed by an associated processor, enable the seeker to perform tasks as described herein.

Thus, the ones of the modules of the seeker may be implemented in accordance with hardware (embodied in one or more chips including an integrated circuit such as an application specific integrated circuit), or may be implemented as software or firmware for execution by a processor. In particular, in the case of firmware or software, the exemplary embodiment can be provided as a computer program product including a computer readable medium or storage structure embodying computer program code (i.e., software or firmware) thereon for execution by the processor.

Furthermore, the seeker as disclosed herein permits very simple optical tube designs, which can be held in place by means of simple compression and fasteners, avoiding complex optical assemblies or exotic optical adhesives. Embodiments for high mach regimes will vary and may require thermal isolation for the detector **2040** and processing electronics. The seeker typically includes other modules such as a filter to block energy outside the desired band associated with the target designator. In the exemplary embodiment, the filter may include coatings deposited on the back surface **2020** of the objective lens.

Turning now to FIG. 21, illustrated is a view of an embodiment of a seeker constructed according to the principles of the present invention. The seeker demonstrates a separation of a seeker dome **2110**, which provides environmental protection, and an objective lens (e.g., a fast fresnel lens) **2120**. In this case, the fast fresnel lens includes the features previously described above. In addition to the detector **2130** and standoff **2140**, a calibration system provides a means to develop a correction map, thus generating line-of-sight information for guidance purposes as described above.

As mentioned previously, warheads are increasingly being used near sensitive population and structures wherein the distance between hostile and engaged troops is often less than 200 meters in urban operations and the hazard distance for a typical air delivered munition is more than 200 meters. While some low yield warheads have been successfully demonstrated (e.g., BLU-126, which is partially filled with inert fill before adding the explosive and is a variant of MK-82), there is still a lack of ability to select the level of output or variability once a mission has begun. It would be beneficial to employ a weapon that can provide full warhead output, or can be selectively reduced based on rules of engagement.

Turning now to FIGS. 22A to 22D, illustrated are views of embodiments of warheads of weapons including an MK-80 series bomb, an MK-80 series bomb with multiple fills, an MK-80 series bomb with multiple moderation and an MK-80 series bomb with spiral cutter, respectively. The illustrated

21

warheads create a shaped charge jet ("SJT") that may compromise the warhead case, explosive charge or both. The multiple fills have been used, in some cases with combination of inert and explosive fills (e.g., BLU-126), in other cases, multiple explosive fills, with the desired outcome being that detonation location or sequence moderates the output. A number of schemes have proposed multiple moderation devices (e.g., adaptable miniature initiation system technology ("AMIST")). As shown here, the moderation devices are interconnected, and yield is varied by means of selecting the location and sequence of moderation events. Finally, the Air Force Research Lab ("AFRL") explored the use of a spiral cutter charge (a spiraled linear shaped charge jet ("SLSCJ")).

Turning now to FIGS. 23 to 26, illustrated are views of embodiments of portions of a warhead of a weapon constructed according to the principles of the present invention. Beginning with FIG. 23, the weapon includes a mandrel 2310 employable to form and manipulate a SLSCJ 2320. The mandrel 2310 is desirable for the purpose of controlling the spiral configuration of the SLSCJ 2320 and can be integral as a mold to form a warhead liner (see below).

Regarding FIG. 24, illustrated is a SLSCJ with a variable wrap, which is desirable for the purpose of controlling a cutter transfer timing of the warhead. The linear progress of the cutter function, along the length of the warhead, is slower in the area of tighter wrap, providing for more precise control in this region. This can be achieved either by variable wrap along a single warhead, as shown here, or by using tighter wraps on devices that require more precise control, and looser wraps on those where precise control is unnecessary. The looser wrap provides a faster warhead function, and provides a lower cost SLSCJ, because it uses less cutter material.

It should be understood that a very fast linear burn rate of the SLSCJ can be difficult to precisely control in some circumstances. One means of achieving better control, and for some warhead shapes, better controlling hazardous fragmentation (e.g., case fragment size), is to use the variable wrap. Again, the variability may be employed across the length of the warhead, as shown in this figure, or may vary with shape for non-cylindrical warheads. In a related embodiment, different size cutter charges may be employed to accommodate variable warhead case thickness, or fill diameter. When multiple cutter sizes are used, the linear burn rate of the cutter can be affected by cutter size, and variable wrap rate is a means to compensate for these changes.

Turning now to FIG. 25, illustrated is an integrated liner 2510 that eases assembly and controls a configuration of an SLSCJ 2520. The illustrated embodiment provides a means to deliver the SLSCJ 2520 to a conventional warhead load assembly and pack ("LAP") facility without requiring SLSCJ tooling or other capital equipment and a low cost assembly with shaped charge jet ("SCJ") standoff control. A control of shaped charge jet standoff is an important factor in system operation because the location of the explosion from the shaped charge allows the shaped charge to be properly focused to allow good quality energy transfer to the recipient material. The liner 2510 provides a practical means to manage the standoff. Thus, the liner 2510 ensures that the configuration of the SLSCJ 2520 is properly maintained and properly positioned with respect to the warhead case. From a manufacturing perspective, this present design allows for the cutter assembly to be manufactured separately from the load assembly and pack.

Although the integrated assembly is called a liner or case liner, it is not limited to a conventional liner, conformal to the inner diameter of a warhead case. Other exemplary embodiments include instances wherein the integrated assembly

22

could be installed outside the warhead case, or as a sub-diameter assembly coaxial to the warhead case, or in other configurations. It should be clear to those skilled in the art that the mandrel is one desirable means to form the integrated assembly though not absolutely necessary to achieve the desired effects

As illustrated in FIG. 26, an integrated resistor ladder 2610 allows control electronics to monitor the progress of the cutter. The resistor ladder 2610 also provides a mechanism to control the timing of detonation of a main charge as the control circuit measures a decrease in resistance during the cutter burn. Other similar circuits should be clear to those skilled in the art, such as a capacitance ladder, or a simple series of connectors, which are interrupted by being cut, and directly form a type of digital logic indicating the position of the cutter burn. It should be clear to those skilled in the art that incorporating the resistance ladder 2610 is useful, and that integrating the ladder 2610 into a liner 2620 provides a means of simple warhead assembly, along with other benefits. It should be clear to those skilled in the art that the mandrel is one desirable means to form the integrated assembly though not absolutely necessary to achieve the novel advantages of this invention.

Additionally, exemplary embodiments of the present invention have been illustrated with reference to specific components. Those skilled in the art are aware, however, that components may be substituted (not necessarily with components of the same type) to create desired conditions or accomplish desired results. For instance, multiple components may be substituted for a single component and vice-versa. The principles of the present invention may be applied to a wide variety of weapon systems. Those skilled in the art will recognize that other embodiments of the invention can be incorporated into a weapon that operates on the principle of lateral ejection of a warhead or portions thereof. Absence of a discussion of specific applications employing principles of lateral ejection of the warhead does not preclude that application from falling within the broad scope of the present invention.

Although the present invention has been described in detail, those skilled in the art should understand that they can make various changes, substitutions and alterations herein without departing from the spirit and scope of the invention in its broadest form. Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the disclosure of the present invention, processes, machines, manufacture, compositions of matter, means, methods, or steps, presently existing or later to be developed, that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized according to the present invention. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means, methods, or steps.

What is claimed is:

1. A seeker, comprising:

a detector configured to receive a distorted signal impinging on an objective lens from a target, said objective lens comprising a front surface with a central region being a non-planar cone and outer regions being sharper cones, memory configured to store target criteria and a correction map, and

a processor configured to provide a correction signal based on said distorted signal, said target criteria and said correction map to guide a weapon to said target.

## 23

2. The seeker as recited in claim 1 wherein said objective lens is integrated with a hemi-dome of said seeker.

3. The seeker as recited in claim 1 wherein said objective lens includes a fast fresnel lens.

4. The seeker as recited in claim 1 wherein said objective lens comprises a back surface configured to provide a complementary corrective curvature to said front surface of said objective lens.

5. The seeker as recited in claim 1 wherein said objective lens comprises a back surface with at least a portion formed by a conic surface.

6. The seeker as recited in claim 1 further comprising a dome configured to provide environmental protection for said objective lens.

7. The seeker as recited in claim 1 further comprising a standoff between said objective lens and said detector.

8. The seeker as recited in claim 1 wherein said correction map is derivable in accordance with a response map from a calibration array in comparison to known angles of illumination.

9. A weapon, comprising:

a warhead including destructive elements; and

a guidance section with a seeker, including:

a detector configured to receive a distorted signal impinging on an objective lens from a target, said objective lens comprising a front surface with a central region being a non-planar cone and outer regions being sharper cones,

## 24

memory configured to store target criteria and a correction map, and

a processor configured to provide a correction signal based on said distorted signal, said target criteria and said correction map to guide said weapon to said target.

10. The weapon as recited in claim 9 wherein said objective lens is integrated with a hemi-dome of said seeker.

11. The weapon as recited in claim 9 wherein said objective lens includes a fast fresnel lens.

12. The weapon as recited in claim 9 wherein said objective lens comprises a back surface configured to provide a complementary corrective curvature to said front surface of said objective lens.

13. The weapon as recited in claim 9 wherein said objective lens comprises a back surface with at least a portion formed by a conic surface.

14. The weapon as recited in claim 9 wherein said seeker includes a dome configured to provide environmental protection for said objective lens.

15. The weapon as recited in claim 9 wherein said seeker includes a standoff between said objective lens and said detector.

16. The weapon as recited in claim 9 wherein said correction map is derivable in accordance with a response map from a calibration array in comparison to known angles of illumination.

\* \* \* \* \*