



US010739451B1

(12) **United States Patent**  
**Parker et al.**

(10) **Patent No.:** **US 10,739,451 B1**  
(45) **Date of Patent:** **Aug. 11, 2020**

(54) **SYSTEMS AND METHODS FOR DETECTING, TRACKING AND IDENTIFYING SMALL UNMANNED SYSTEMS SUCH AS DRONES**

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,668,403 A 6/1972 Meilander  
3,754,249 A 8/1973 Kearney, II  
(Continued)

(71) Applicant: **XiDrone Systems, Inc.**, Naples, FL (US)

FOREIGN PATENT DOCUMENTS

AU 2016332918 A1 4/2018  
CN 105214288 A 1/2016  
(Continued)

(72) Inventors: **Dwayne A. Parker**, Naples, FL (US);  
**Damon E. Stern**, Riverview, FL (US);  
**Lawrence S. Pierce**, Huntsville, AL (US)

(73) Assignee: **XiDrone Systems, Inc.**, Naples, FL (US)

OTHER PUBLICATIONS

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

N9310A RF Signal Generator, 9kHz to 3 GHz, Key Features & Specifications, Keysight Technologies (1994), retrieved Nov. 14, 2017, 2 pages.

(Continued)

(21) Appl. No.: **16/867,145**

*Primary Examiner* — Peter M Bythrow

(22) Filed: **May 5, 2020**

(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye, P.C.

**Related U.S. Application Data**

(63) Continuation of application No. 16/362,285, filed on Mar. 22, 2019, which is a continuation of application (Continued)

(57) **ABSTRACT**


(51) **Int. Cl.**  
**G01S 13/06** (2006.01)  
**G01S 13/88** (2006.01)  
(Continued)

A system for providing integrated detection and countermeasures against unmanned aerial vehicles include a detecting element, a location determining element and an interdiction element. The detecting element detects an unmanned aerial vehicle in flight in the region of, or approaching, a property, place, event or very important person. The location determining element determines the exact location of the unmanned aerial vehicle. The interdiction element can either direct the unmanned aerial vehicle away from the property, place, event or very important person in a non-destructive manner, or can cause disable the unmanned aerial vehicle in a destructive manner.

(52) **U.S. Cl.**  
CPC ..... **G01S 13/06** (2013.01); **F41H 11/02** (2013.01); **F41H 13/0075** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC . G01S 7/021; G01S 7/38; G01S 7/414; G01S 13/42; G01S 13/52; G01S 13/5244;  
(Continued)

**27 Claims, 4 Drawing Sheets**



**Related U.S. Application Data**

<p>No. 15/967,291, filed on Apr. 30, 2018, now Pat. No. 10,281,570, which is a continuation of application No. 15/598,112, filed on May 17, 2017, now Pat. No. 9,977,117, which is a continuation of application No. 14/821,907, filed on Aug. 10, 2015, now Pat. No. 9,689,976.</p>		6,262,679 B1	7/2001	Tran	
		6,529,820 B2	3/2003	Tomescu	
		6,563,453 B1	5/2003	Wilson	
		6,564,149 B2	5/2003	Lai	
		6,608,559 B1	8/2003	Lemelson et al.	
		6,690,296 B2	2/2004	Corwin	
		6,697,008 B1 *	2/2004	Sternowski .....	G01S 5/0284 342/14
		6,707,052 B1	3/2004	Wild	
		6,868,314 B1	3/2005	Frink	
		6,877,691 B2	4/2005	DeFlumere	
		6,903,676 B1	6/2005	Frady	
		6,992,614 B1	1/2006	Joyce	
		7,046,841 B1	5/2006	Dow et al.	
		7,149,366 B1	12/2006	Sun	
		7,202,809 B1	4/2007	Schade	
		7,205,932 B2	4/2007	Fiore	
		7,236,766 B2	6/2007	Freeburg	
		7,248,342 B1	7/2007	Degnan	
		7,283,840 B2	10/2007	Cho	
		7,336,939 B2	2/2008	Gomez	
		7,339,515 B2 *	3/2008	Ferm .....	G01S 7/38 342/13
		7,339,981 B2	3/2008	Dogan	
		7,430,257 B1	9/2008	Shattil	
		7,437,225 B1	10/2008	Rathinam	
		7,489,264 B2 *	2/2009	Ferm .....	G01S 7/38 342/14
		7,492,308 B2	2/2009	Benayahu	
		7,504,982 B2	3/2009	Berg	
		7,548,184 B2	6/2009	Lo	
		7,551,121 B1	6/2009	O'Connell	
		7,554,481 B2 *	6/2009	Cohen .....	G01S 19/015 342/13
		7,567,202 B2	7/2009	Pearson et al.	
		7,593,706 B2	9/2009	Bucknor et al.	
		7,619,555 B2	11/2009	Rolfe	
		7,668,505 B2	2/2010	Vacanti	
		7,680,192 B2	3/2010	Kaplinsky	
		7,683,782 B2	3/2010	Christopher	
		7,684,020 B1	3/2010	Marti et al.	
		7,706,979 B1	4/2010	Herwitz	
		7,710,463 B2	5/2010	Foote	
		7,728,755 B1 *	6/2010	Jocic .....	H04K 3/45 342/13
		7,782,256 B2	8/2010	Smith	
		7,653,261 B2	12/2010	Lewis et al.	
		7,898,454 B1	3/2011	Starkey	
		7,961,133 B2	6/2011	Vollin	
		7,969,346 B2	6/2011	Franceschini et al.	
		8,161,440 B2	4/2012	Lontka	
		8,204,494 B2	6/2012	Weinzieri	
		8,212,709 B2	7/2012	Bradley	
		8,212,995 B2	7/2012	Koehler et al.	
		8,254,847 B2	8/2012	Sen	
		8,258,994 B2	9/2012	Hamilton	
		8,301,075 B2 *	10/2012	Sherman .....	H04B 1/1036 455/1
		8,305,196 B2	11/2012	Kennedy et al.	
		8,330,641 B2	12/2012	Ryden	
		8,378,880 B1	2/2013	Boka	
		8,378,881 B2	2/2013	LeMire	
		8,464,949 B2	6/2013	Namey	
		8,528,998 B2	9/2013	Leal	
		8,543,053 B1	9/2013	Melamed et al.	
		8,543,265 B2	9/2013	Ekhaguere	
		8,599,367 B2	12/2013	Canham	
		8,625,854 B2	1/2014	Valkenburg et al.	
		8,655,348 B2	2/2014	Zha	
		8,750,903 B1	6/2014	Fitzsimmons et al.	
		8,750,934 B2	6/2014	Lucidarme	
		8,761,687 B2	6/2014	Chang et al.	
		8,798,922 B2	8/2014	Tillotson	
		8,811,720 B2	8/2014	Seida	
		8,824,966 B2	9/2014	Boes	
		8,909,304 B1	12/2014	Coleman	
		8,918,540 B2	12/2014	Carman et al.	
		8,939,081 B1	1/2015	Smith et al.	
		8,942,082 B2	1/2015	Shattil	

(60) Provisional application No. 62/094,154, filed on Dec. 19, 2014.

(51) **Int. Cl.**

- F41H 13/00** (2006.01)
- G01S 7/38** (2006.01)
- G01S 7/02** (2006.01)
- G01S 13/86** (2006.01)
- G01S 7/41** (2006.01)
- G01S 3/782** (2006.01)
- F41H 11/02** (2006.01)
- G01S 13/42** (2006.01)
- G01S 13/91** (2006.01)
- G01S 13/933** (2020.01)

(52) **U.S. Cl.**

- CPC ..... **G01S 3/782** (2013.01); **G01S 7/021** (2013.01); **G01S 7/38** (2013.01); **G01S 7/414** (2013.01); **G01S 13/42** (2013.01); **G01S 13/86** (2013.01); **G01S 13/88** (2013.01); **G01S 13/883** (2013.01); **G01S 13/91** (2013.01); **G01S 13/933** (2020.01)

(58) **Field of Classification Search**

- CPC ..... G01S 13/86; G01S 13/865; G01S 13/867; G01S 13/88; G01S 13/883; G01S 13/9303; G01S 13/91; G01S 13/93; F41H 11/00; F41H 11/02; F41H 13/0043; F41H 13/0075
- See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 3,981,010 A 9/1976 Michelsen
- 4,016,565 A 4/1977 Walker
- 4,160,974 A 7/1979 Stavis
- 4,178,596 A \* 12/1979 Rowlett ..... G01S 7/38  
342/187
- 4,468,656 A 8/1984 Clifford
- 4,652,885 A 3/1987 Saffold
- 4,692,638 A 9/1987 Stiegler
- 4,723,311 A 2/1988 Moustakas et al.
- 4,727,537 A 2/1988 Nichols
- 4,780,719 A 10/1988 Frei
- 4,825,435 A 4/1989 Amundsen et al.
- 4,990,814 A 2/1991 Tanski et al.
- 5,005,147 A 4/1991 Krishen
- 5,268,680 A 12/1993 Zantos
- 5,307,077 A 4/1994 Branigan
- 5,327,149 A 7/1994 Kuffer
- 5,341,142 A 8/1994 Reis
- 5,381,150 A 1/1995 Hawkins
- 5,402,129 A 3/1995 Gellner
- 5,442,168 A 8/1995 Gurner et al.
- 5,554,990 A 9/1996 McKinney
- 5,557,278 A 9/1996 Piccirillo
- 5,568,476 A 10/1996 Sherer et al.
- 5,728,965 A 3/1998 Fesland
- 5,884,040 A 3/1999 Chung
- 5,930,696 A 7/1999 Tzuang
- 5,996,646 A 10/1999 Lampe et al.
- 6,081,764 A 6/2000 Varon
- 6,087,974 A 7/2000 Yu

(56)

References Cited

U.S. PATENT DOCUMENTS

8,942,197	B2	1/2015	Rudnick et al.	2009/0093847	A1	4/2009	Noujeim	
8,955,110	B1	2/2015	Twitchell, Jr.	2009/0118875	A1	5/2009	Stroud	
8,983,455	B1	3/2015	Frolov et al.	2009/0174589	A1	7/2009	Moraites	
9,041,798	B1	5/2015	Yerkes	2009/0216757	A1	8/2009	Sen et al.	
9,042,333	B2	5/2015	Shattil	2009/0273504	A1	11/2009	Meyers	
9,048,944	B2	6/2015	Boes	2009/0292468	A1	11/2009	Wu	
9,083,425	B1	7/2015	Frolov et al.	2009/0326735	A1	12/2009	Wood et al.	
9,108,729	B2	8/2015	Duggan	2010/0042269	A1	2/2010	Kokkeby	
9,170,069	B1	10/2015	Smith	2010/0150209	A1	6/2010	Gonzalez	
9,170,117	B1	10/2015	Abuelsaad et al.	2010/0170383	A1*	7/2010	Willner	H04K 3/42
9,175,934	B1	11/2015	Kilian					86/50
9,204,488	B2	12/2015	Bai	2010/0174475	A1	7/2010	Estkowski	
9,212,869	B1	12/2015	Boardman	2010/0253567	A1	10/2010	Factor	
9,246,629	B2	1/2016	Coleman	2010/0272012	A1	10/2010	Knefelkamp	
9,275,645	B2	3/2016	Hearing et al.	2010/0315261	A1	12/2010	Rutjes et al.	
9,302,782	B2	4/2016	Frolov et al.	2011/0002687	A1	1/2011	Sabat, Jr. et al.	
9,337,889	B1	5/2016	Stapleford	2011/0009053	A1	1/2011	Anglin, Jr. et al.	
9,354,317	B2	5/2016	Halmos	2011/0058036	A1	3/2011	Metzger et al.	
9,356,727	B2	5/2016	Immendorf et al.	2011/0117870	A1	5/2011	Pera	
9,363,690	B1	6/2016	Singh et al.	2011/0292976	A1	12/2011	Sen et al.	
9,405,005	B1	8/2016	Arteaga	2012/0022719	A1	1/2012	Matos	
9,406,237	B2	8/2016	Downey et al.	2012/0057566	A1	3/2012	Ahmadi	
9,412,278	B1	8/2016	Gong et al.	2012/0092208	A1	4/2012	LeMire	
9,429,655	B2*	8/2016	Yun	2012/0092503	A1	4/2012	Cheng	
9,432,095	B2	8/2016	Berlin et al.	2012/0143482	A1	6/2012	Goossen	
9,479,392	B2	10/2016	Anderson et al.	2012/0169642	A1	7/2012	Chuang et al.	
9,479,964	B2	10/2016	Jalali	2012/0217301	A1	8/2012	Namey	
9,483,950	B2	11/2016	Wang et al.	2012/0235881	A1	9/2012	Pan	
9,495,877	B2	11/2016	Duffy	2012/0298748	A1	11/2012	Factor	
9,508,264	B2	11/2016	Chan	2012/0299765	A1	11/2012	Huang et al.	
9,523,773	B2*	12/2016	Fink	2012/0309288	A1	12/2012	Lu	
9,529,360	B1	12/2016	Melamed et al.	2012/0322360	A1	12/2012	Sen et al.	
9,537,561	B1	1/2017	Kotecha et al.	2012/0322459	A1	12/2012	Jaffri et al.	
9,670,390	B2	6/2017	Kalwa	2013/0009975	A1	4/2013	Hendry et al.	
9,689,976	B2	6/2017	Parker	2013/0099975	A1	4/2013	Cyganski et al.	
9,715,009	B1	7/2017	Parker	2013/0157599	A1*	6/2013	Ray	H04B 1/16
9,977,117	B2	5/2018	Parker					455/130
10,156,631	B2	5/2018	Parker	2013/0188008	A1	7/2013	Meadow et al.	
10,051,475	B2*	8/2018	Shattil	2013/0244712	A1	9/2013	Kuzio et al.	
10,281,570	B2	5/2019	Parker	2013/0316659	A1	11/2013	Ylamurto	
2001/0033600	A1	10/2001	Yang et al.	2013/0329052	A1	12/2013	Chew	
2003/0174763	A1	9/2003	Kouki	2014/0022051	A1	1/2014	Levien	
2004/0021852	A1	2/2004	DeFlumere	2014/0062757	A1	3/2014	Fox et al.	
2004/0057537	A1	3/2004	Kim	2014/0098185	A1	4/2014	Davari et al.	
2004/0061595	A1	4/2004	Yannone	2014/0102288	A1*	4/2014	Yeshurun	F41H 11/00
2004/0130488	A1	7/2004	DeChamplain					89/36.17
2004/0166878	A1	8/2004	Erskine et al.	2014/0111372	A1*	4/2014	Wu	G01S 7/418
2004/0167667	A1	8/2004	Goncalves et al.					342/146
2004/0203748	A1	10/2004	Kappes et al.	2014/0138474	A1*	5/2014	Sharpin	F41G 7/00
2004/0249519	A1	12/2004	Frink					244/3.22
2005/0040909	A1	2/2005	Waight	2014/0148978	A1	5/2014	Duncan et al.	
2005/0046703	A1	3/2005	Cutler	2014/0172200	A1	6/2014	Miralles	
2005/0108374	A1	5/2005	Pierzga	2014/0200875	A1*	7/2014	Yuksel Ergun	F41G 9/00
2006/0028373	A1	2/2006	Fullerton					703/21
2006/0028374	A1	2/2006	Fullerton	2014/0209678	A1*	7/2014	Factor	G01S 7/38
2006/0063485	A1	3/2006	Gainey et al.					235/400
2006/0092075	A1	5/2006	Bruce	2014/0219124	A1	8/2014	Chang et al.	
2006/0106506	A1	5/2006	Nichols	2014/0219449	A1	8/2014	Shattil	
2006/0164282	A1*	7/2006	Duff	2014/0249693	A1	9/2014	Stark et al.	
				2014/0251123	A1*	9/2014	Venema	F41H 11/02
								89/41.22
				2014/0253378	A1	9/2014	Hinman	
				2014/0257692	A1	9/2014	Stefani	
				2014/0266851	A1*	9/2014	Fink	G01S 19/015
								342/14
				2014/0267775	A1	9/2014	Lablans	
				2014/0269650	A1	9/2014	Sahota	
				2014/0277854	A1	9/2014	Jones	
				2014/0344927	A1	11/2014	Turgeman	
				2015/0009945	A1	1/2015	Shattil	
				2015/0133067	A1	5/2015	Chang et al.	
				2015/0226834	A1	6/2015	Floch	
				2015/0214926	A1	7/2015	Tohidian et al.	
				2015/0229434	A1*	8/2015	Shawn	G01S 7/38
								342/14
				2015/0236778	A1	8/2015	Jalali	
				2015/0249498	A1	9/2015	Rascon et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0254988 A1\* 9/2015 Wang ..... G08G 5/0021  
701/3

2015/0260824 A1 9/2015 Malveaux

2015/0278140 A1 10/2015 Motos

2015/0301529 A1 10/2015 Pillai et al.

2015/0302858 A1\* 10/2015 Hearing ..... G01H 1/00  
381/58

2015/0304783 A1 10/2015 Yang et al.

2015/0304869 A1 10/2015 Johnson

2015/0312835 A1 10/2015 Subramanian

2015/0339912 A1 11/2015 Farrand

2015/0370250 A1 12/2015 Bachrach

2016/0086621 A1 3/2016 Hearing et al.

2016/0095001 A1 3/2016 Jelk et al.

2016/0100415 A1 4/2016 Mishra et al.

2016/0116915 A1 4/2016 Pulleti

2016/0117931 A1 4/2016 Chan

2016/0118059 A1 4/2016 Hearing et al.

2016/0119938 A1 4/2016 Freking et al.

2016/0134358 A1 5/2016 Jalali

2016/0135204 A1 5/2016 Mishra et al.

2016/0142880 A1 5/2016 Talluri et al.

2016/0180719 A1 6/2016 Wouhaybi

2016/0189732 A1 6/2016 Hearing et al.

2016/0219506 A1 7/2016 Pratt et al.

2016/0225264 A1 8/2016 Taveira

2016/0246297 A1 8/2016 Song

2016/0274229 A1 9/2016 Oh

2016/0300493 A1 10/2016 Ubhi et al.

2016/0300495 A1 10/2016 Kantor et al.

2016/0309337 A1 10/2016 Priest et al.

2016/0330771 A1 11/2016 Tan

2016/0335476 A1 11/2016 Renkis

2016/0337671 A1 11/2016 Wieneke et al.

2016/0357192 A1 12/2016 McGrew et al.

2016/0358432 A1 12/2016 Branscomb et al.

2016/0358483 A1\* 12/2016 Park ..... G01S 13/91

2017/0039413 A1\* 2/2017 Nadler ..... H04N 5/2258

2017/0045684 A1 2/2017 Kablaoui

2017/0094527 A1 3/2017 Shattil

2017/0261613 A1 9/2017 Van Voorst

2017/0261999 A1 9/2017 Van Voorst

FOREIGN PATENT DOCUMENTS

CN 108353081 A 7/2018

EP 2 252 859 B1 12/2012

EP 3357214 A1 8/2018

FR 2983973 6/2013

GB 2536043 9/2016

KR 2013009895 1/2013

KR 20180049154 A1 5/2018

WO 2014116314 A1 7/2014

WO 2017041303 A1 3/2017

WO 2017058966 A1 4/2017

OTHER PUBLICATIONS

Smart Sensor Radar System, Vista Radar Systems (1994), Raven Aerostar, Product Overview, retrieved Nov. 14, 2017, 2 pages.

WiNRADiO MS-8118/G3 Multichannel Radio Monitoring System (1994), Product Overview, retrieved Nov. 14, 2017, 2 pages.

RF Power Amplifiers, High Power-6GHz and below, Empower RF Systems, Inc. (1994), retrieved Nov. 14, 2017, 1 page.

WiNRADiO WD-3300 High Performance Portable Direction Finding System (1994), Product Overview, retrieved Nov. 14, 2017, 2 pages.

International Preliminary Report on Patentability and Written Opinion of the International Searching Authority dated Jun. 29, 2017, issued in related International Application No. PCT/US2015/059698.

Kems, Andrew J., et al., "Unmanned Aircraft Capture and Control via GPS Spoofing," *Journal of Robotics*, vol. 31, No. 4, Jul. 2014, 29 pages.

Rassler, Don, "Remotely Piloted Innovation: Terrorism, Drones and Supportive Technology," *Combating Terrorism Center at West Point, United States Military Academy*, Oct. 2016, 77 pages.

Ying, Gao, et al., "Design and Realization of Virtual Scene System in UAV Electronic Warfare," *International Conference on Information Engineering and Computer Science, IEEE, 2009*, 4 pages.

"In the battle for Mosul, grenades rain down from ISIS drones," *Rudaw*, Jan. 7, 2017, 3 pages.

"Liteye and Tribalco Team to Deliver AUDS Counter Drone Systems to U.S. Military Customers," *PR Newswire*, Jan. 12, 2017, 3 pages.

Watson, Ben, "The Drones of ISIS," *Defense One*, Jan. 12, 2017, 10 pages.

Office Action dated Apr. 4, 2017, issued in related U.S. Appl. No. 14/821,907.

Notice of Allowance and Fee(s) Due dated May 15, 2017, issued in related U.S. Appl. No. 14/821,907.

A. Patro, et al.; "Air Track: Locating Non-WiFi Interferers using Commodity WiFi Hardware," *ACM SIGMOBILE Mobile Computing and Communications Review*; vol. 15 Issue 4, pp. 52-54; Oct. 2011.

K. Saylor, "A World of Proliferated Drones: A Technology Primer," <https://www.cnas.org/publications/reports/a-world-of-proliferated-drones-a-technology-primer>; Jun. 10, 2015.

T. Goodspeed, "Packets in Packets: Orson Welles' In-Band Signaling Attacks for Modern Radios," *WOOT'11 Proceedings of the 5th USENIX conference on Offensive technologies*; San Francisco, CA; 2011.

N.O. Tippenhauer, et al; "On the Requirements for Successful GPS Spoofing Attacks," *Conference: Proceedings of the 18th ACM Conference on Computer and Communications Security, CCS 2011, Chicago, Illinois, USA, Oct. 17-21, 2011*.

N. Kothari, et al.; "Finding Protocol Manipulation Attacks," *SIGCOMM '11 Proceedings of the ACM SIGCOMM 2011 conference* pp. 26-37; Toronto, Ontario, Canada-Aug. 15-19, 2011.

J. Bellardo and S. Savage, "802.11 Denial-of-Service Attacks: Real Vulnerabilities and Practical Solutions," *SSYM'03 Proceedings of the 12th conference on USENIX Security Symposium* vol. 12; pp. 2-2; Washington, DC---Aug. 4-8, 2003.

Amirhossein Fereidounbar, Gian Carlo Cardarilli, Luca Di Nunzio, Rocco Fazzolari; "UAV Channel Estimation with STBC in MIMO Systems"; *The International Conference on Advanced Wireless, Information, and Communication Technologies (AWICT 2015)*.

Liu Tao, Hu Yonghui, Hua Yu, Wu Meifang; "Study on Autonomous and Distributed Time Synchronization Method for formation UAVs"; *2nd International Conference on Electrical, Computer Engineering and Electronics (IGECEE 2015)*.

Hamed Rezaee, Farzaneh Abdollahi; "Synchronized Cross Coupled Sliding Mode Controllers for Cooperative UAVs with Communication Delays"; *51st IEEE Conference on Decision and Control*; Dec. 10-13, 2012. Maui, Hawaii, USA.

S. Rayanchu, et al.; "Airshark: Detecting Non-WiFi RF Devices using Commodity WiFi Hardware," *IMC '11 Proceedings of the 2011 ACM SIGCOMM conference on Internet measurement conference*; pp. 137-154; Berlin, Germany-Nov. 2-4, 2011.

Anderton, Donald C., "Synchronized Line-Scan LIDAR/EO Imager for Creating 3D Images of Dynamic Scenes: Prototype II," *Utah State University, All Graduate Plan B and Other Reports*, 2005, 148 pages.

Gezer, Berat Levent, "Multi-Beam Digital Antenna for Radar, Communications, and UAV Tracking Based on Off-The Shelf Wireless Technologies," *Thesis, Naval Postgraduate School*, Sep. 2006, 127 pages.

Pham, Tien, et al., "TTCP AG-6: Acoustic Detection and Tracking of UAVs," *Proceedings of SPIE*, vol. 5417, 2004, pp. 24-30.

Zhang, Shuqun, "Object Tracking in Unmanned Aerial Vehicle (UAV) Videos Using a Combined Approach," *IEEE*, 2005, pp. II-681-II-684.

\* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4



**SYSTEMS AND METHODS FOR  
DETECTING, TRACKING AND  
IDENTIFYING SMALL UNMANNED  
SYSTEMS SUCH AS DRONES**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 16/362,285, filed Mar. 22, 2019; which is a continuation of U.S. patent application Ser. No. 15/967,291 filed Apr. 30, 2018, now U.S. patent Ser. No. 10/281,570; which is a continuation of U.S. patent application Ser. No. 15/598,112 filed May 17, 2017, now U.S. Pat. No. 9,977,117; which is a continuation of U.S. patent application Ser. No. 14/821,907 filed Aug. 10, 2015, now U.S. Pat. No. 9,689,976; which claims benefit of U.S. Provisional Application No. 62/094,154 filed Dec. 19, 2014. The disclosures of the prior applications are incorporated herein in their entirety by reference.

FIELD OF THE INVENTION

The present invention relates to an integrated detection and countermeasure solution against unmanned aerial systems, which are commonly referred to as drones.

BACKGROUND OF THE INVENTION

Unmanned aerial systems, which are commonly referred to as drones, have become commercially available to the general public. While there may be many safe commercial and recreational uses for unmanned aerial systems these devices may potentially pose hazards to commercial and general aviation, the public, and private and government property if improperly operated. Furthermore unmanned aerial systems may be used to violate the privacy of personal, commercial, educational, athletic, entertainment and governmental activities. Most unfortunately unmanned aerial systems may potentially be used in the furtherance of invading privacy, or carrying out terrorist and/or criminal activities. There is a need for a device and method of detecting the approach of an unmanned aerial system towards a location where personal, public, commercial, educational, athletic, entertainment and governmental activities occur and where an unmanned aerial system could potentially be used for invading privacy, or carrying out terrorist and criminal activities. The present invention provides an integrated detection and countermeasure solution against unmanned aerial systems and offers increased security, privacy, and protection from the threats of violence involving small unmanned aerial vehicles/systems (sUAS) and is applicable to governmental, commercial, private, and public concerns.

SUMMARY OF THE INVENTION

There is provided in accordance with the present invention a system that detects, identifies, tracks, deters and or interdicts small unmanned aerial vehicles/systems (sUAS) from ground level to several thousand feet above ground level. The system disclosed herein is an integrated solution comprising components using: existing technology for a new use; multiplexing hardware components designed for this application; and development of the integrating software which calculates the exact x, y, z coordinates of the subject sUAS; subject sUAS RF signal analysis to determine the

most appropriate RF signal characteristics to affect the subject sUAS; precision alignment of high definition electro-optical (EO) sensors and infrared (IR) sensors and image recognition algorithms providing confirmation that the subject sUAS is in violation of airspace authorization. The integration of these components via the herein disclosed combination of software and hardware is novel, not related to existing art in purpose, is non-obvious, and provides a useful solution to uninvited, invasive and potentially hazardous sUAS operations.

The system of the present invention provides an integrated and diversified solution that can be deployed as a “permanent placement” or mobile system on land, sea, or air platform.

The system of the invention may be strategically deployed to monitor the airspace around a protected interest such as a property, place, event or very important person (VIP) offering 360 degree azimuth coverage extending from the receiving antennae of the system out to a maximum lateral distance of about 2 kilometers (6560 feet) and within the lateral boundaries up to a maximum altitude of about 1.5 kilometers (4920 feet) above ground level (AGL).

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic representation of the components and function of an integrated detection and countermeasure system for use against unmanned aerial systems.

FIG. 2 is a schematic representation of a countermeasure and interdiction to UAS system of the integrated detection and countermeasure system for use against unmanned aerial systems, 44 of FIG. 1.

FIG. 3 is a schematic representation of the Radio Frequency (RF) detection system of the integrated detection and countermeasure system for use against unmanned aerial systems, 44 of FIG. 1.

FIG. 4 is a schematic representation of the Radar detection system and Electro Optical and Infrared (EO/IR) detection system of the integrated detection and countermeasure system for use against unmanned aerial systems, 44 of FIG. 1.

DETAILED DESCRIPTION OF THE  
INVENTION

Part Numbers

- 10 Transmitting multi band high gain directional antenna array with vertical polarity
- 12 Receive directional antenna array
- 14 Receive Omni antenna array
- 16 EO/IR (Electro Optical/Infra Red) sensor
- 18 Automatic antenna alignment assembly
- 20 Multi-band LNA assembly
- 22 Automatic antenna alignment assembly
- 24 High fidelity RF receivers/host work station CPU
- 26 Azimuth and elevation vector coordinate data processor
- 28 Empower 1189-BBM3 wideband HPA assembly
- 30 Receive blanking
- 32 Direction detect and range estimation
- 34 Key sight N9310A RF signal generator with multiple modulation sources
- 36 Spectral signals detect and type identification
- 38 ECM modulation type select
- 40 Frequency and waveform parameters
- 42 Modulation database

- 43 Commercial 4 k×band radar
- 44 Subject UAS (Unmanned Aerial System)
- 45 Radar clutter and target filter processor
- 46 Azimuth and elevation vector coordinate data processor
- 99 System power and status monitor
- 100 Entire system
- 102 Countermeasure and deterrent section of entire system
- 103 Radio Frequency (RF) detection section of entire system
- 104 Radar detection section of entire system
- 105 Electro Optical and Infer Red (EO/IR) detection section of entire system

## Glossary

As used herein and in the claims each of the terms defined in this glossary is understood to have the meaning set forth in this glossary.

Algorithm—a process or set of rules to be followed in calculations or other problem-solving operations by a computer

Automatic Antenna Alignment Assembly—designated as 18 in FIGS. 1, 2 and 3, and as 22 in FIGS. 1 and 4, is specialized electronic equipment specifically designed to automatically point the directional antennae and or camera, laser systems to the desired location, namely a small unmanned aerial vehicles/systems (sUAS) designated as a target 44 in FIG. 1, based on longitude and or latitude information gained or received by the receiving antennae, designated as 12 and 14 in FIGS. 1 and 3, and or radar antennae designated as 43 in FIGS. 1 and 4; this specialized equipment can be purchased from and is proprietary to EnrGies Engineering located in Huntsville, Ala.

Azimuth and Elevation Vector Coordinate Data—designated as 26 in FIGS. 1 and 4, is specialized algorithm software that has been developed to be used with a spherical coordinate system for three-dimensional space where three numbers specify the position of a point measured in latitude, longitude and elevation obtained from an EO/IR Sensor designated as 16 in FIGS. 1 and 4 that includes a Laser Range Finder, and/or Radar designated as 43 in FIGS. 1 and 4

Blanking—designated as 30 in FIGS. 1, 2 and 3 is the time between the last radio transmitting signal and the beginning of the next radio transmitting signal

C2 Communications—Command and Control Communications links

Commercial—relating to or engaged in commerce (i.e. NON-military)

Counter—to offer in response or act in opposition

CUASs2—Counter Unmanned Aerial Systems of Systems, the system of the present invention used to detect, identify and deter or interdict unmanned aerial vehicles or systems

Directional Antenna—designated as 10 in FIGS. 1 and 2, and 12 in FIGS. 1 and 3, a class of directional or beam antenna that radiates greater power in one or more directions allowing for increased performance on transmits and receives and reduced interference from unwanted sources

Direction Detection and Range Estimation—designated as 32 in FIGS. 1-4, is specialized algorithm software that has been developed to detect a suspected target or signal of interest and calculated to obtain the azimuth and distance to that target or signal of interest based on data obtained by the Radio Frequency (RF) detection section 103 in FIG. 3, the

Radar detection section 104 in FIG. 4, and the Electro Optical and Infer Red (EO/IR) detection section 105 in FIG. 4

DF—designated as 12 in FIGS. 1 and 3, Direction Finding refers to the measurement of the direction from which a received signal was transmitted, this can refer to radio or other forms of wireless communication

Drone—designated as 44 in FIG. 1, refers to an unmanned aircraft operated by remote control, allows for human correction (i.e. semi-autonomous), or autonomous, see also UAV, UAS, sUAS, RPA

EAR—Export Administration Regulations are regulations that are administered by the United States Department of Commerce and regulate the export of “dual use” items; technology designed for commercial purposes and with potential military applications, such as computers, software, aircraft, and pathogens as well the re-export of items

Electro-Optical and Infrared Sensors—designated as 16 in FIGS. 1 and 4, is a combination of a standard high definition video camera capable of viewing in daylight conditions and an infrared video camera capable of viewing in the infrared light perspective; both camera systems can be purchased “Off-The-Shelf” as common technology, one common manufacturer of this type of camera systems is FLIR Systems

Electronic Counter Measure (ECM) Modulation Type Select—designated as 38 in FIGS. 1-3 is specialized algorithm software that has been developed to help narrow down the radio frequency identified by a modulation lookup table (defined in this glossary) of the specific unmanned aerial vehicle/system of interest, designated as a target 44 in FIG. 1, utilizing a database library that was created and categorized with the specific radio frequencies common to all unmanned aerial vehicles/systems

Emitter—to send or give out a matter of energy

EO—Electro-Optics is a branch of electrical engineering and materials science involving components, devices and systems that operate by modification of the optical properties of a material by an electric field, thus it concerns the interaction between the electromagnetic (optical) and the electrical (electronic) states of materials

Frequency—the rate at which a vibration occurs that constitutes a wave, either in a material (as in sound waves), or in an electromagnetic field (as in radio waves and light), usually measured per second

Frequency and Waveform Parameters—designated as 40 in FIGS. 1-3, Is specialized algorithm software that has been developed to identify unmanned aerial vehicles/systems utilizing a database library that was created and categorized with the specific radio frequency waveform common to all unmanned aerial vehicles/systems

IR—infrared is invisible (to the human eye) radiant energy, electromagnetic radiation with longer wavelengths than those of visible light, extending from the nominal red edge of the visible spectrum at 700 nanometers (frequency 430 THz) to 1 mm (300 GHz)

ISR—Intelligence, Surveillance, Reconnaissance is an activity that synchronizes and integrates the planning and operation of sensors, assets, and processing, exploitation, and dissemination systems in direct support of current and future operations

ITAR—International Traffic in Arms Regulations is a set of United States government regulations that control the export and import of defense-related articles and services on the United States Munitions List (USML)

Jam or Jammed or Jammers or Jamming—to interfere with or prevent the clear reception of broadcast signals by

electronic means to become unworkable or to make unintelligible by sending out interfering signals by any means

Laser—a device that emits light through a process of optical amplification based on the stimulated emission of electromagnetic radiation

Laser Range Finder—designated as **16** in FIGS. **1** and **4**, is a rangefinder which uses a laser beam, usually pulsed, to determine the distance to an object

LED—Light-Emitting Diode is a semiconductor device that emits visible light when an electric current passes through it

Matrix—an environment in which something develops

Matrix Directional Transmit Antenna Array—designated as **10** in FIGS. **1** and **2**, Is a signal processing technique used in sensor (Antenna) arrays for directional signal transmission; this is achieved by combining elements in a phased array in such a way that signals at particular angles experience constructive interference while others experience destructive interference; his equipment can be purchased “Off-The-Shelf” and one common manufacturer of this type of equipment is Motorola

Mobile Platform (MP)—the mobile Counter Unmanned Aerial System of Systems equipment installed on any vehicle with the intent to move from one location to another location as needed to fulfill a short-term need in the detection, identification and deterrence or interdiction of an unmanned aerial vehicle

Modulation—the process of varying one or more properties of a periodic waveform, called the carrier signal, with a modulating signal that typically contains information to be transmitted

Modulation Function Generation—designated as **34** in FIGS. **1-3**, Is specialized algorithm software that has been developed to transmit (Jam) a specific radio frequency, designated by **38** in FIGS. **1-3** and **42** in FIGS. **1** and **3**, which is unique to a specific unmanned aerial vehicles/systems utilizing a database library that was created and categorized with the specific radio frequencies used on all common unmanned aerial vehicles/systems

Modulation Lookup Table—designated as **42** in FIGS. **1** and **3**, is specialized algorithm software that has been developed to identify the broad range of radio frequencies being used by a specific unmanned aerial vehicle/system of interest, designated as a target **44** in FIG. **1**, utilizing a database library that was created and categorized with the specific radio frequencies common to all unmanned aerial vehicles/systems

Multi-Band—a communication device that supports multiple radio frequency bands

Multiband Low Noise Amplifier (LNA) Assembly—designated as **20** in FIGS. **1** and **3**, is a multi-radio frequency electronic amplifier used to amplify possibly very weak signals, for example captured by an antenna

Omni-directional Antenna—designated as **14** in FIGS. **1** and **3**, a class of antenna which receives or transmits radio wave power uniformly in all directions in one plane, with the radiated power decreasing with elevation angle above or below the plane, dropping to zero on the antenna’s axis

OTS—Off The Shelf refers to materials or equipment that currently exists and is readily available for purchased or use

Permanent Platform (PP)—the installation of the Counter Unmanned Aerial System of Systems equipment at a specific location to fulfill a long-term need in the detection, identification and deterrence or interdiction of an unmanned aerial vehicle

Pulse—a single vibration or short burst of sound, electric current, light, or other wave

RPA—Remotely Piloted Aircraft, aka UAV, UAS

RF—Radio Frequency is a rate of oscillation in the range of around 3 kHz to 300 GHz, which corresponds to the frequency of radio waves, and the alternating currents that carry radio signals

Receive Blanking—designated as **30** in FIGS. **1-3**, is specialized algorithm software that has been developed to stop the receiving antennae, designated as **12** and **14** in FIGS. **1** and **3**, from receiving radio frequency signals during the time that the counter measure transmitting frequency, designated as **34** in FIGS. **1-3**, is being transmitted by directional transmitting antennae, designated as **10** in FIGS. **1** and **2**, for the purpose of deterrence or interdiction of the suspect unmanned aerial vehicle/system, designated as a target **44** in FIG. **1**, identified as a known threat

Receive Directional Antenna Array—designated as **12** in FIGS. **1** and **3**, refers to multiple receiving antennae arranged such that the superposition of the electromagnetic waves is a predictable electromagnetic field and that the currents running through them are of different amplitudes and phases; this equipment can be purchased “Off-The-Shelf” and one common manufacturer of this type of equipment is Motorola

Receive Omni Antenna Array—designated as **14** in FIGS. **1** and **3**, is a class of antenna that receives radio wave power uniformly in all directions in one plane; this equipment can be purchased “Off-The-Shelf” and one common manufacturer of this type of equipment is Motorola

STC—Slew To Cue, the autonomous actions of electronic, radio or optical sensors to rotate using an automatic antenna alignment assembly designated as **18** in FIGS. **1-3**, and **22** in FIGS. **1** and **4** to move and point cameras **16** in FIGS. **1** and **4** and countermeasures **10** in FIGS. **1** and **2** in the direction of a suspect target **44** in FIG. **1**, based on input from data processed by components **26** in FIGS. **1** and **4**, and **46** in FIGS. **1**, **3** and **4**, thus, keeping the “cued” targets in view at all times with or without human intervention

Spectral Signal—designated as **36** in FIGS. **1** and **3**, the frequency spectrum of a time-domain signal is a representation of that signal in the frequency domain

Spectral Signal Detection and Type Identification—designated as **36** in FIGS. **1** and **3**, is specialized algorithm software that has been developed to detect and identify unmanned aerial vehicles/systems utilizing a database library that was created and categorized with the spectral signatures common to all unmanned aerial vehicles/systems

sUAS—designated as **44** in FIG. **1** small Unmanned Aerial System, usually weighing less than 20 kg or 55 lbs.

Target—designated as **44** in FIG. **1**, something or someone of interest to be affected by an action or development

Target Tracking Log—a graphic or table of coordinates documenting the target’s path in space during area of concern

Technology—the application of science, especially to industrial or commercial objectives

Threat—a declaration or an act of an intention or determination to inflict the destruction of property or harm, punishment, injury or death of person(s)

UAS—designated as **44** in FIG. **1**, Unmanned Aerial System, Unmanned Aircraft System (aka UAV, RPA)

UAV—designated as **44** in FIG. **1**, Unmanned Aerial Vehicle, Unmanned Aircraft Vehicle (aka UAS, RPA)

Uplink—the part of a network connection used to send, or upload, data from one device to a remote device

Uplink Video/Radio Transmitter Assembly—designated as **28** in FIGS. **1** and **2**, is a device that will take the received radio or video frequency information from database libraries

designated as **36** in FIGS. **1** and **3**, **40** in FIGS. **1-3**, and **42** in FIGS. **1** and **3** and send it through a radio amplifier designated as **34** in FIGS. **1-3** to a transmitting directional antenna or matrix directional transmit antenna array designated as **10** in FIGS. **1** and **2**; this equipment can be purchased “Off-The-Shelf” and one common manufacturer of this type of equipment is Motorola

Uplink/Video Standard Definition (SD) Receiver & Host Workstation—designated as **24** in FIGS. **1** and **3**, is a connection from the antennae to the video encoder where the information is processed by the main computer network; the uplink equipment can be purchased “Off-The-Shelf” and one common manufacturer of this type of equipment is Cisco Systems; the video receiver and main computer is also “Off-The-Shelf” technology and are readily available from numerous manufacturers

Vector—a quantity having direction as well as magnitude, especially as determining the position of one point in space relative to another

Watt—the system unit of power, equivalent to one joule per second, corresponding to the power in an electric circuit in which the potential difference is one volt and the current one ampere

Waveform—a graphic representation of the shape of a wave that indicates its characteristics as frequency and amplitude

Referring to FIGS. **1-4** there are shown schematic representations of the components and function of an integrated detection and countermeasure system **100** for use against unmanned aerial systems **44**. A first function of the system is locating and identifying a UAS target. The present invention provides integrated detection sections **103-105** and deterrent/countermeasure section **102** against small unmanned aerial vehicles/systems (sUAS), which are commonly referred to as drones, in the vicinity of, or approaching the vicinity of a property, place, event or very important person (VIP). All sUAS’s have a distinct set of spectral signatures (sound, heat, radar cross section, radio frequency wave pattern) detected by a spectral signal identifier processor **36**. This fact is the basis for the detection sections **103-105** of the system **100** of the present invention and sections **103-105** is the first function of the system. Using a proven high-end direction finding (DF) high fidelity RF receiver **24** coupled with omnidirectional and directional antennae **12**, **14** and unique created software of the system when the RF signature of the sUAS flying within the system’s detection boundaries is detected, for example within maximum lateral distance of about 2 kilometers (6560 feet) and within the aerial boundaries up to a maximum altitude of about 1.5 kilometers (4920 feet) above ground level (AGL). This element of the system may be augmented and is shown with additional signature detection elements consisting of acoustic and/or radar sensors **43** and electro optical sensors **16**. These elements operate with unique software translating discernable signatures into coherent data aiding in the detection and location process. All signature data is then processed to generate a reference azimuth and elevation **26**, **46** from the sensor to the subject sUAS **44**. The information generated by the systems detection section is then passed electronically to the direction and range estimation processor **32** to yield a target’s location. The system **100** of the present invention uses the hardware and software of the Radio Frequency (RF) detection section **103** to identify the type of sUAS and the associated known and observed radio frequencies signatures required for the sUAS communications and video data exchange.

A second function of the system is providing countermeasures against sUAS that is determined to be a threat in or approaching the vicinity of a property, place, event or VIP. Azimuthal data for a sUAS is determined by the detection section **103-105** of the system. The system’s control software/hardware provides this information to the integrated Electro-Optical (EO) and Infrared (IR) sensor **16** which autonomously centers the field of regard of the EO/IR sensor to the known location of the subject sUAS **44**. When the visual identification is confirmed to be a sUAS; by either video analytics or human verification, the system of invention’s software/hardware will then determine the precise x, y, z coordinates (x=longitude, y=latitude, z=altitude) of the sUAS. This precise location and range information is provided to the countermeasure and deterrent section **102** of the system **100**. Using this data the countermeasure and deterrent section **102** computes the RF spectral characteristics that will nullify signals that the sUAS expects to receive. A signal generator **34** produces a tailored signal and a variable strength amplifier **28** generates the output power required; causing the desired effect at the desired range to the subject sUAS **44**. The countermeasure and deterrent section **102** broadcasts the unique generated RF waveform using highly directional and focused antennae **10**. The system uses Blanking **30** at the time between the last radio transmitting signal and the beginning of the next radio-transmitting signal of the transmitted signal in accordance with the frequency and waveform parameters **40** to avoid negative internal effects to system **103**. The system then disables the sUAS sensors, or causes the sUAS navigation system to malfunction due to communication interference causing most sUAS to enter a “Fail Safe Mode” (either land immediately or return to the launch point). This action is sUAS specific and is based on the manufacturer design and sUAS operational capabilities.

The interdict element of a system of the present invention interdicts the operation of an sUAS initially in a non-destructive manner, increasing to a destructive manner based on the response of the target sUAS. A system of the present invention may interdict the operation of a sUAS in a non-destructive manner by transmitting a concentrated Radio Frequency (RF) emission tuned to the specific sUAS characteristics identified by the spectral analysis during the detection process. These RF waveforms are then used to disrupt the expected inputs to the onboard controller of the identified sUAS. The video downlink signal is the initial target of the interdiction process. If this interruption is not sufficient to deter the sUAS, the RF transmitter will be tuned to the appropriate control frequency to disrupt the sUAS on-board electronics. These actions will cause most sUAS to enter the Fail Safe Mode (either land immediately or return to the launch point). The present invention considers the differences based on the manufacturer design and operational capabilities of the sUAS on a case-by-case basis and tailors the inventions countermeasure/deterrent response accordingly.

The countermeasure and deterrent section **102** of the system **100** interdicts the operation of an sUAS in a non-destructive manner by using the non-destructive technology described to generate a interdict transmission signal that is significantly stronger than control signals from an operator of the sUAS. This interdict transmission will have significantly higher gain (Stronger Signal) and target both the sensor and the control electronics of the sUAS. The interdiction process may be augmented with electro-magnetic pulse technology, pulsed laser and is specifically designed to accept other current or future counter-measures used to defeat the sUAS’ electronics, motors and or navigation

systems. The effects of the higher gain radio transmission will cause amongst other effects, servo-chatter, resulting in the loss of control of the sUAS and disruption of most on-board electronic processes increasing the probability of a forced landing. In addition, a counter sUAS can be dispatched with autonomous navigation data being supplied by the system of present invention to locate and intentionally disable the opposing sUAS by flying into it, dropping a net on the threat, covering it with spray foam or liquid or capturing the opposing sUAS.

The system of the present invention will use direction finding (DF) equipment **12**, **16** to search for the radio communications link of an airborne sUAS **44**, commonly referred to as a drone. Integrating multiple Direction Finding (DF) equipment **26**, **46** to the system of the present invention will increase the precision in obtaining the azimuth that the sUAS is flying. Integrating radar equipment **43** provided with a radar clutter and target filter processor **45**, with the direction finding (DF) equipment will provide the present invention the ability to determine with greater accuracy the altitude and azimuth of the sUAS **44** at the time of discovery and during the time it remains within the systems detection boundaries.

When the DF equipment **26**, **46** has detected a communication link of a sUAS within the system boundaries, the receive host workstation **24** will analyze the radio frequency wave signature and confirm that the RF detected is from a sUAS. This process also applies when a radar unit **43** is integrated with the DF equipment.

The information obtained from DF **26**, **46** and or radar unit **43** is then sent to the direction detect and range estimation unit **32** where algorithms will be used to send sUAS location coordinates to the Automatic Antenna Alignment Assembly (A4) **22**, **18**. Put another way, using Slew To Cue, the autonomous actions of electronic, radio or optical sensors to rotate using an automatic antenna alignment assembly **18**, **22** to move and point cameras **16** and countermeasures in the direction of a suspect target **44** based on input from data processed by the azimuth and elevation unit **26** **46**, thus, keeping the "cued" targets in view at all times with or without human intervention. This information will then direct the Automatic Antenna Alignment Assembly (A4) **22** to point the Electro-Optical and Laser Range Finding unit **16** at the sUAS to allow for visual confirmation, distance and elevation of the sUAS to be known.

The information obtained by the Laser Range Finding equipment will be sent to the Azimuth and Elevation Vector Coordinate Data unit **26** which will send exact azimuth and elevation information to the A4 system **18** controlling the Matrix Directional Transmit Antenna Array **10** via the Direction Detect and Range Estimation unit **32**.

When the communications link between the subject sUAS and its' operator is detected by the Radio Frequency (RF) detection section **103** of the system the information is passed through the Multiband LNA Assembly **20** and through the Uplink Receive Host Workstation **24**. The information is then sent to the Spectral Signal Detect and Type Identification unit **36** where the type of sUAS is determined based on a known database containing Spectral Signal Wave information **36**. When the Spectral Signal Wave information is known the information is sent to the Frequency and Wave Form Parameters unit **40** where the analyzed RF data is sent to the Modulation Look Up Table **42**. When the Modulation information is known the information is then sent to the ECM Modulation Type Select unit **38**.

The selected modulation waveform is then sent to the Uplink Video Transmitter Assembly **28** that unit works in

conjunction with the Receive Blanking unit **30**. When the Uplink Video Transmitter **28** is transmitting a radio signal the Receive Blanking unit **30** will force the DF antennae **12**, **14** to stop receiving the radio frequency being transmitted by the Matrix Directional Transmit Antenna Array **10**. The radio frequency selected to disrupt the communication link of the sUAS with its' operator is then transmitted by the Transmitter Assembly **28** using the Matrix Directional Transmit Antenna Array **10** aimed at the sUAS **44** via the Automatic Antenna Alignment Assembly **18**.

While the invention has been described with reference to certain exemplary embodiments, obvious modifications and alterations are possible by those skilled in the related art. Therefore, it is intended that the invention include all such modifications and alterations to the full extent that they come within the scope of the following claims or the equivalents thereof.

The invention claimed is:

1. A method for detecting and defeating a drone comprising:
  - utilizing a detection antenna array to scan for at least one of a drone control link and a video link associated with the drone;
  - utilizing said detection antenna array to determine a source direction of the drone based on the at least one of the drone control link and the video link;
  - utilizing a neutralization system to generate an interdiction signal, said interdiction signal at least partially generated with reference to the at least one of the drone control link and the video link; and
  - utilizing a transmission antenna to transmit said interdiction signal.
2. The method of claim 1, further comprising:
  - transmitting a first interdiction signal followed by transmitting a second interdiction signal; and
  - providing a time interval between transmitting the first interdiction signal and transmitting the second interdiction signal to allow the detection antenna array to receive signals.
3. The method of claim 1, further comprising:
  - detecting at least one additional drone;
  - performing at least one of determining each drone's size, determining each drone's range, determining each drone's position, generating interdiction signals for each drone; and
  - transmitting interdiction signals to each drone.
4. The method of claim 1, further comprising:
  - comparing the video link to radio signatures stored in a library of downlink frequencies used by drones.
5. The method of claim 1, wherein the interdiction signal disrupts at least one of uplink signals and downlink signals.
6. The method of claim 1, further comprising identifying one or more drones using a transponder identification process.
7. The method of claim 1, further comprising tracking one or more drones using at least one of a radar, a laser range finder, a camera, and a radio receiver.
8. The method of claim 1, further comprising classifying one or more drones based on at least one of drone uplink signals and drone downlink signals.
9. The method of claim 1, further comprising generating a visual display of detected drone locations.
10. A system for detecting and defeating a drone comprising:
  - a detection antenna array configured to scan for at least one of a drone control link and a video link associated with the drone, said detection antenna array configured

11

to determine a source direction of the drone based on the at least one of the drone control link and the video link;

a neutralization system configured to generate an interdiction signal, said interdiction signal at least partially generated with reference to the at least one of the drone control link and the video link; and

a transmission antenna configured to transmit said interdiction signal.

11. The system of claim 10, wherein:

the transmission antenna is configured for transmitting a first interdiction signal followed by transmitting a second interdiction signal; and

the neutralization system is further configured to provide a time interval between transmitting the first interdiction signal and transmitting the second interdiction signal to allow the detection antenna array to receive signals.

12. The system of claim 10, wherein:

the detection antenna array is configured for detecting at least one additional drone; and

the system further includes a processor configured to perform at least one of determining each drone's size, determining each drone's range, and determining each drone's position.

13. The system of claim 10, further comprising a processor configured for comparing the video link to radio signatures stored in a library of downlink frequencies used by drones.

14. The system of claim 10, wherein the interdiction signal disrupts at least one of uplink signals and downlink signals.

15. The system of claim 10, wherein the detection antenna array is configured for identifying one or more drones using a transponder identification process.

16. The system of claim 10, further comprising at least one of a radar, a laser range finder, a camera, and a radio receiver configured to track one or more drones.

17. The system of claim 10, further comprising a processor configured for classifying one or more drones based on at least one of drone uplink signals and drone downlink signals.

18. The system of claim 10, further comprising a visual display configured for displaying detected drone locations.

19. An apparatus, comprising at least one processor, at least one memory in electronic communication with the at least one processor, and instructions stored in the at least one memory, the stored instructions comprising instructions executable by the at least one processor for:

utilizing a detection antenna array to scan for at least one of a drone control link and a video link associated with the drone;

12

utilizing said detection antenna array to determine a source direction of the drone based on the at least one of the drone control link and the video link;

utilizing a neutralization system to generate an interdiction signal, said interdiction signal at least partially generated with reference to the at least one of the drone control link and the video link; and

utilizing a transmission antenna to transmit said interdiction signal.

20. The apparatus of claim 19, further comprising instructions stored in the at least one memory executable by the at least one processor for controlling transmission of a first interdiction signal followed by transmission of a second interdiction signal, and providing a time interval between transmitting the first interdiction signal and transmitting the second interdiction signal to allow the detection antenna array to receive signals.

21. The apparatus of claim 19, further comprising instructions stored in the at least one memory executable by the at least one processor for:

detecting at least one additional drone;

performing at least one of determining each drone's size, determining each drone's range, determining each drone's position, generating interdiction signals for each drone; and

controlling transmission of interdiction signals to each drone.

22. The apparatus of claim 19, further comprising instructions stored in the at least one memory executable by the at least one processor for comparing the video link to radio signatures stored in a library of downlink frequencies used by drones.

23. The apparatus of claim 19, wherein the interdiction signal disrupts at least one of uplink signals and downlink signals.

24. The apparatus of claim 19, further comprising instructions stored in the at least one memory executable by the at least one processor for identifying one or more drones using a transponder identification process.

25. The apparatus of claim 19, further comprising instructions stored in the at least one memory executable by the at least one processor for tracking one or more drones using at least one of a radar, a laser range finder, a camera, and a radio receiver.

26. The apparatus of claim 19, further comprising instructions stored in the at least one memory executable by the at least one processor for classifying one or more drones based on at least one of drone uplink signals and drone downlink signals.

27. The apparatus of claim 19, further comprising instructions stored in the at least one memory executable by the at least one processor for generating a visual display of detected drone locations.

\* \* \* \* \*