



US010795010B2

(12) **United States Patent**
Parker et al.

(10) **Patent No.:** **US 10,795,010 B2**
(45) **Date of Patent:** **Oct. 6, 2020**

(54) **SYSTEMS AND METHODS FOR DETECTING, TRACKING AND IDENTIFYING SMALL UNMANNED SYSTEMS SUCH AS DRONES**

(71) Applicant: **XiDrone Systems, Inc.**, Naples, FL (US)

(72) Inventors: **Dwayne A. Parker**, Naples, FL (US); **Damon E. Stern**, Riverview, FL (US); **Lawrence S. Pierce**, Huntsville, AL (US)

(73) Assignee: **XiDrone Systems, Inc.**, Naples, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 34 days.

(21) Appl. No.: **16/362,285**

(22) Filed: **Mar. 22, 2019**

(65) **Prior Publication Data**

US 2019/0219682 A1 Jul. 18, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/967,291, filed on Apr. 30, 2018, now Pat. No. 10,281,570, which is a (Continued)

(51) **Int. Cl.**
G01S 13/06 (2006.01)
F41H 11/02 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G01S 13/06** (2013.01); **F41H 11/02** (2013.01); **F41H 13/0075** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC . G01S 7/021; G01S 7/38; G01S 7/414; G01S 13/42; G01S 13/52; G01S 13/5244;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,668,403 A 6/1972 Meilander G01S 13/9303 342/36
3,754,249 A 8/1973 Kearney, II F41G 7/007 244/3.13

(Continued)

FOREIGN PATENT DOCUMENTS

AU 2016332918 A1 4/2018
CN 105214288 A 1/2016

(Continued)

OTHER PUBLICATIONS

N9310A RF Signal Generator, 9kHz to 3 GHz, Key Features & Specifications, Keysight Technologies {1994}, retrieved Nov. 14, 2017, 2 pages.

(Continued)


Primary Examiner — Peter M Bythrow

(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye, P.C.

(57) **ABSTRACT**

A system for providing integrated detection and countermeasures against unmanned aerial vehicles include a detecting element, a location determining element and an interdiction element. The detecting element detects an unmanned aerial vehicle in flight in the region of, or approaching, a property, place, event or very important person. The location determining element determines the exact location of the unmanned aerial vehicle. The interdiction element can either direct the unmanned aerial vehicle away from the property, place, event or very important person in a non-destructive manner, or can cause disable the unmanned aerial vehicle in a destructive manner.

21 Claims, 4 Drawing Sheets



Related U.S. Application Data					
	continuation of application No. 15/598,112, filed on May 17, 2017, now Pat. No. 9,977,117, which is a continuation of application No. 14/821,907, filed on Aug. 10, 2015, now Pat. No. 9,689,976.	5,381,150 A	1/1995	Hawkins	G01R 23/165 342/13
		5,402,129 A	3/1995	Gellner	G01S 13/348 342/70
		5,442,168 A	8/1995	Gurner et al.	
		5,554,990 A	9/1996	McKinney	G01S 7/22 342/176
(60)	Provisional application No. 62/094,154, filed on Dec. 19, 2014.	5,557,278 A	9/1996	Piccirillo	G01S 7/003 342/29
		5,728,965 A	3/1998	Fesland	B64C 39/024 244/190
(51)	Int. Cl.	5,884,040 A	3/1999	Chung	
	<i>G01S 3/782</i> (2006.01)	5,930,696 A	7/1999	Tzuang	
	<i>G01S 7/41</i> (2006.01)	5,996,646 A	10/1999	Lampe et al.	
	<i>G01S 13/42</i> (2006.01)	6,081,764 A	6/2000	Varon	G01S 13/91 342/29
	<i>G01S 13/86</i> (2006.01)	6,087,974 A	7/2000	Yu	F41G 7/2226 244/3.1
	<i>G01S 7/02</i> (2006.01)	6,262,679 B1	7/2001	Tran	G01S 13/9303 342/29
	<i>G01S 7/38</i> (2006.01)	6,529,820 B2	3/2003	Tomescu	G01S 5/0063 342/36
	<i>F41H 13/00</i> (2006.01)	6,563,453 B1	5/2003	Wilson	G01S 13/782 342/29
	<i>G01S 13/88</i> (2006.01)	6,564,149 B2	5/2003	Lai	G01S 7/06 340/945
	<i>G01S 13/91</i> (2006.01)	6,608,559 B1	8/2003	Lemelson et al.	
	<i>G01S 13/933</i> (2020.01)	6,690,296 B2	2/2004	Corwin	G01S 13/782 340/945
(52)	U.S. Cl.	6,697,008 B1 *	2/2004	Sternowski	G01S 5/0284 342/14
	CPC <i>G01S 3/782</i> (2013.01); <i>G01S 7/021</i> (2013.01); <i>G01S 7/38</i> (2013.01); <i>G01S 7/414</i> (2013.01); <i>G01S 13/42</i> (2013.01); <i>G01S 13/86</i> (2013.01); <i>G01S 13/88</i> (2013.01); <i>G01S 13/883</i> (2013.01); <i>G01S 13/91</i> (2013.01); <i>G01S 13/933</i> (2020.01)	6,707,052 B1	3/2004	Wild	F41H 11/02 250/504 R
(58)	Field of Classification Search	6,868,314 B1	3/2005	Frink	
	CPC G01S 13/86; G01S 13/865; G01S 13/867; G01S 13/88; G01S 13/883; G01S 13/9303; G01S 13/91; G01S 13/93; F41H 11/00; F41H 11/02; F41H 13/0043; F41H 13/0075	6,877,691 B2	4/2005	DeFlumere	G01S 7/4802 244/3.1
	See application file for complete search history.	6,903,676 B1	6/2005	Fraday	F41H 11/00 342/52
		6,992,614 B1	1/2006	Joyce	
		7,046,841 B1	5/2006	Dow et al.	
		7,149,366 B1	12/2006	Sun	
		7,202,809 B1	4/2007	Schade	F41A 1/08 244/3.1
(56)	References Cited	7,205,932 B2	4/2007	Fiore	G01S 13/32 342/104
	U.S. PATENT DOCUMENTS	7,236,766 B2	6/2007	Freeburg	
	3,981,010 A 9/1976 Michelsen	7,248,342 B1	7/2007	Degnan	
	F41G 3/2611 342/55	7,283,840 B2	10/2007	Cho	
	4,016,565 A 4/1977 Walker	7,336,939 B2	2/2008	Gomez	
	4,160,974 A 7/1979 Stavis	7,339,981 B2	3/2008	Dogan	
	4,178,596 A * 12/1979 Rowlett	7,430,257 B1	9/2008	Shattil	
	G01S 7/38 342/187	7,437,225 B1	10/2008	Rathinam	G08G 5/0013 340/961
	4,468,656 A 8/1984 Clifford	7,492,308 B2	2/2009	Benayahu	F41H 7/00 244/3.1
	4,652,885 A 3/1987 Saffold	7,504,982 B2	3/2009	Berg	F41G 5/08 342/13
	H01Q 5/45 342/53	7,548,184 B2	6/2009	Lo	F41G 7/008 244/3.15
	4,698,638 A 10/1987 Branigan	7,551,121 B1	6/2009	O'Connell	F41G 5/08 235/400
	F41G 7/008 342/53	7,567,202 B2	7/2009	Pearson et al.	
	4,723,311 A 2/1988 Moustakas et al.	7,593,706 B2	9/2009	Bucknor et al.	
	4,727,537 A 2/1988 Nichols	7,619,555 B2	11/2009	Rolfe	H04B 7/18506 342/29
	4,746,924 A * 5/1988 Lightfoot	7,680,192 B2	3/2010	Kaplinsky	
	G01S 5/02 342/159	7,683,782 B2	3/2010	Christopher	
	4,780,719 A 10/1988 Frei	7,684,020 B1	3/2010	Marti et al.	
	G01S 13/86 342/351	7,706,979 B1	4/2010	Hervitz	
	4,825,435 A 4/1989 Amundsen et al.	7,710,463 B2	5/2010	Foote	
	4,990,814 A 2/1991 Tanski et al.	7,728,755 B1 *	6/2010	Jocic	H04K 3/45 342/13
	5,005,147 A 4/1991 Krishen	7,782,256 B2	8/2010	Smith	G01S 5/06 342/453
	G06K 9/6293 703/13	7,853,261 B1	12/2010	Lewis et al.	
	5,187,485 A * 2/1993 Tsui	7,898,454 B1	3/2011	Starkey	G01S 7/38 342/14
	G01S 5/12 342/126				
	5,268,680 A 12/1993 Zantos				
	F41G 7/008 342/53				
	5,307,077 A 4/1994 Branigan				
	G01S 13/4463 342/53				
	5,327,149 A 7/1994 Kuffer				
	G01S 13/86 342/53				
	5,341,142 A 8/1994 Reis				
	F41G 7/2226 244/3.15				

(56)	References Cited		9,715,009 B1	7/2017	Parker	
	U.S. PATENT DOCUMENTS		9,977,117 B2	5/2018	Parker	
			10,156,631 B2	5/2018	Parker	
			10,051,475 B2	8/2018	Shattil	H04L 43/18
7,961,133 B2	6/2011	Vollin	10,281,570 B2	5/2019	Parker	
			2003/0174763 A1	9/2003	Kouki	
7,969,346 B2	6/2011	Franceschini et al.	2004/0021852 A1	2/2004	DeFlumere	F41G 7/008 356/141.1
8,161,440 B2	4/2012	Lontka		3/2004	Kim	
8,204,494 B2	6/2012	Weinzieri	2004/0057537 A1	3/2004	Kim	
8,212,709 B2	7/2012	Bradley	2004/0061595 A1	4/2004	Yannone	F41H 11/00 340/425.5
			244/3.1			
8,212,995 B2	7/2012	Koehler et al.	2004/0130488 A1	7/2004	DeChamplain	
8,254,847 B2	8/2012	Sen	2004/0166878 A1	8/2004	Erskine et al.	
8,258,994 B2	9/2012	Hamilton	2004/0167667 A1	8/2004	Goncalves et al.	
			2004/0203748 A1	10/2004	Kappes et al.	
8,258,998 B2	9/2012	Factor	2004/0249519 A1	12/2004	Frink	B64F 45/0015 701/3
			342/12			
8,305,196 B2	11/2012	Kennedy et al.	2005/0040909 A1	2/2005	Waight	
8,330,641 B2	12/2012	Ryden	2005/0046703 A1	3/2005	Cutler	
			2005/0108374 A1	5/2005	Pierzga	
8,378,880 B1	2/2013	Boka	2006/0028373 A1	2/2006	Fullerton	F41H 11/00 342/67
8,378,881 B2	2/2013	LeMire	2006/0028374 A1	2/2006	Fullerton	F41G 5/08 342/67
8,464,949 B2	6/2013	Namey	2006/0063485 A1	3/2006	Gainey et al.	
			2006/0092075 A1	5/2006	Bruce	G01S 7/02 342/175
84,837,003	7/2013	Swope et al.				
8,543,053 B1	9/2013	Melamed et al.	2006/0106506 A1	5/2006	Nichols	G05D 1/101 701/3
8,543,265 B2	9/2013	Ekhaguere	2006/0164282 A1*	7/2006	Duff	G01S 7/38 342/14
8,599,367 B2	12/2013	Canham	2006/0175464 A1	8/2006	Chang	F41H 5/007 244/3.19
8,625,854 B2	1/2014	Valkenburg et al.				
8,655,348 B2	2/2014	Zha	2006/0188033 A1	8/2006	Zehavi et al.	
8,670,390 B2	3/2014	Shattil	2006/0235584 A1	10/2006	Fregene et al.	
8,750,903 B1	6/2014	Fitzsimmons et al.	2007/0052580 A1	3/2007	Fiore	G01S 13/32 342/133
8,750,934 B2	6/2014	Lucidarme				
8,761,687 B2	6/2014	Chang et al.	2007/0060055 A1	3/2007	Desai	
8,798,922 B2	8/2014	Tillotson	2007/0099667 A1	5/2007	Graham et al.	
8,811,720 B2	8/2014	Seida	2007/0226247 A1	9/2007	Ferm	
8,824,966 B2	9/2014	Boes	2007/0285280 A1	12/2007	Robinson et al.	
8,909,304 B1	12/2014	Coleman	2008/0018519 A1	1/2008	Berg	F41G 5/08 342/14
8,918,540 B2	12/2014	Carman et al.				
8,939,081 B1	1/2015	Smith et al.	2008/0088508 A1*	4/2008	Smith	H01Q 21/29 342/453
8,942,082 B2	1/2015	Shattil				
8,942,197 B2	1/2015	Rudnick et al.	2008/0095121 A1	4/2008	Shattil	
8,955,110 B1	2/2015	Twitcheil, Jr.	2008/0191924 A1*	8/2008	Duff	H04K 3/44 342/14
8,983,455 B1	3/2015	Frolov et al.				
9,041,798 B1	5/2015	Yerkes	2009/0061870 A1	3/2009	Finklestein et al.	
			2009/0098847 A1	4/2009	Noujeim	
9,042,333 B2	5/2015	Shattil	2009/0118875 A1	5/2009	Stroud	
9,048,944 B2	6/2015	Boes	2009/0174589 A1	7/2009	Moraites	
9,083,425 B1	7/2015	Frolov et al.	2009/0216757 A1	8/2009	Sen et al.	
9,108,729 B2	8/2015	Duggan	2009/0273504 A1	11/2009	Meyers	
9,170,069 B1	10/2015	Smith	2009/0292468 A1	11/2009	Wu	G01S 13/726 701/301
9,170,117 B1	10/2015	Abuelsaad et al.				
9,175,934 B1	11/2015	Kilian	2009/0326735 A1	12/2009	Wood et al.	
9,204,488 B2	12/2015	Bai	2010/0042269 A1	2/2010	Kokkeby	G01S 3/7864 701/3
9,212,869 B1	12/2015	Boardman				
9,246,629 B2	1/2016	Coleman	2010/0170383 A1*	7/2010	Willner	H04K 3/42 86/50
9,275,645 B2	3/2016	Hearing et al.				
9,302,782 B2	4/2016	Frolov et al.	2010/0174475 A1	7/2010	Estkowski	
9,337,889 B1	5/2016	Stapleford	2010/0253567 A1	10/2010	Factor	
9,354,317 B2	5/2016	Halmos	2010/0272012 A1	10/2010	Knefelkkamp	
9,356,727 B2	5/2016	Immendorf et al.	2010/0315281 A1	12/2010	Askelson	G01S 7/00 342/30
9,363,690 B1	6/2016	Singh et al.				
9,405,005 B1	8/2016	Arteaga	2011/0002687 A1	1/2011	Sabat, Jr. et al.	
9,406,237 B2	8/2016	Downey et al.	2011/0009053 A1	1/2011	Anglin, Jr. et al.	
9,412,278 B1	8/2016	Gong et al.	2011/0058036 A1	3/2011	Metzger et al.	
9,429,655 B2*	8/2016	Yun	2011/0117870 A1	5/2011	Pera	
9,432,095 B2	8/2016	Berlin et al.	2011/0292976 A1	12/2011	Sen et al.	
9,479,392 B2	10/2016	Anderson et al.	2012/0022719 A1	1/2012	Matos	
9,479,964 B2	10/2016	Jalali	2012/0092208 A1	4/2012	LeMire	
9,483,950 B2	11/2016	Wang et al.	2012/0092503 A1	4/2012	Cheng	
9,495,877 B2	11/2016	Duffy	2012/0143482 A1	6/2012	Goossen	G08G 5/0034 701/120
9,508,264 B2	11/2016	Chan				
9,529,360 B1	12/2016	Melamed et al.				
9,537,561 B1	1/2017	Kotecha et al.				
9,689,976 B2	6/2017	Parker	2012/0169842 A1	7/2012	Chuang et al.	

(56)		References Cited					
U.S. PATENT DOCUMENTS				2016/0140851	A1	5/2016	Levy et al.
				2016/0142880	A1	5/2016	Talluri et al.
				2016/0180719	A1	6/2016	Wouhaybi G08G 5/0082 701/4
2012/0217301	A1	8/2012	Namey F41H 5/007 235/411	2016/0189732	A1	6/2016	Hearing et al.
2012/0235881	A1	9/2012	Pan	2016/0219506	A1	7/2016	Pratt et al.
2012/0298748	A1	11/2012	Factor F41H 11/02 235/400	2016/0225264	A1	8/2016	Taveira
2012/0299765	A1	11/2012	Huang et al.	2016/0246297	A1	8/2016	Song
2012/0309288	A1	12/2012	Lu	2016/0300493	A1	10/2016	Ubhi et al.
2012/0322360	A1	12/2012	Sen et al.	2016/0300495	A1	10/2016	Kantor et al.
2012/0322459	A1	12/2012	Jaffri et al.	2016/0309337	A1	10/2016	Priest et al.
2013/0157599	A1*	6/2013	Ray H04B 1/16 455/130	2016/0330771	A1	11/2016	Tan
2013/0188008	A1	7/2013	Meadow et al.	2016/0335476	A1	11/2016	Renkis
2013/0244712	A1	9/2013	Kuzio et al.	2016/0337871	A1	11/2016	Wieneke et al.
2013/0316659	A1	11/2013	Ylamurto	2016/0357192	A1	12/2016	McGrew et al.
2013/0329052	A1	12/2013	Chew	2016/0358432	A1	12/2016	Branscomb et al.
2014/0022051	A1	1/2014	Levien	2016/0358483	A1*	12/2016	Park G01S 13/91
2014/0062757	A1	3/2014	Fox et al.	2017/0039413	A1*	2/2017	Nadler H04N 5/2258
2014/0098185	A1	4/2014	Davari et al.	2017/0045884	A1	2/2017	Kablaoui
2014/0102288	A1*	4/2014	Yeshurun F41H 11/00 89/36.17	2017/0094527	A1	3/2017	Shattil
2014/0111372	A1*	4/2014	Wu G01S 7/418 342/146	2017/0261613	A1	9/2017	Van Voorst
2014/0138474	A1*	5/2014	Sharpin F41G 7/00 244/3.22	2017/0261999	A1	9/2017	Van Voorst
2014/0148978	A1	5/2014	Duncan et al.	FOREIGN PATENT DOCUMENTS			
2014/0172200	A1	6/2014	Miralles	CN	108353081	A	7/2018
2014/0200875	A1*	7/2014	Yüksel Ergun F41G 9/00 703/21	EP	2 252 859	B1	12/2012
2014/0209678	A1*	7/2014	Factor G01S 7/38 235/400	EP	3357214	A1	8/2018
2014/0219124	A1	8/2014	Chang et al.	FR	2983973		6/2013
2014/0219449	A1	8/2014	Shattil	GB	2536043		9/2016
2014/0249693	A1	9/2014	Stark et al.	KR	20130009895		1/2013
2014/0251123	A1*	9/2014	Venema F41H 11/02 89/41.22	KR	20180049154	A1	5/2018
2014/0253378	A1	9/2014	Hinman	WO	WO2017058966	A1	4/2014
2014/0257692	A1	9/2014	Stefani	WO	WO2014116314	A1	7/2014
2014/0266851	A1*	9/2014	Fink G01S 19/015 342/14	WO	2017/041303	A1	3/2017
2014/0267775	A1	9/2014	Lablans	OTHER PUBLICATIONS			
2014/0269650	A1	9/2014	Sahota	Smart Sensor Radar System, Vista Radar Systems {1994}, Raven			
2014/0277854	A1	9/2014	Jones	Aerostar, Product Overview, retrieved Nov. 14, 2017, 2 pages.			
2015/0009945	A1	1/2015	Shattil	WiNRADiO MS-8118/G3 Multichannel Radio Monitoring System			
2015/0016712	A1	1/2015	Rhoads et al.	(1994), Product Overview, retrieved Nov. 14, 2017, 2 pages.			
2015/0133067	A1	5/2015	Chang et al.	RF Power Amplifiers, High Power-6GHz and below, Empower RF			
2015/0214926	A1	7/2015	Tohidian et al.	Systems, Inc. {1994}, retrieved Nov. 14, 2017, 1 page.			
2015/0226834	A1	8/2015	Floch	WiNRADiO WD-3300 High Performance Portable Direction Find-			
2015/0229434	A1*	8/2015	Shawn G01S 7/38 342/14	ing System (1994), Product Overview, retrieved Nov. 14, 2017, 2			
2015/0236778	A1	8/2015	Jalali	pages.			
2015/0249498	A1	9/2015	Minguez Rascon et al.	International Preliminary Report on Patentability and Written Opin-			
2015/0254988	A1*	9/2015	Wang G08G 5/0021 701/3	ion of the International Searching Authority dated Jun. 29, 2017,			
2015/0260824	A1	9/2015	Malveaux	issued in related International Application No. PCT/US2015/			
2015/0301529	A1	10/2015	Pillai et al.	059698.			
2015/0302858	A1*	10/2015	Hearing G01H 1/00 381/58	Kems, Andrew J., et al., "Unmanned Aircraft Capture and Control			
2015/0304783	A1	10/2015	Yang et al.	via GPS Spoofing," Journal of Robotics, vol. 31, No. 1, Jul. 2014,			
2015/0304869	A1	10/2015	Johnson	29 pages.			
2015/0312835	A1	10/2015	Subramanian	Rassler, Don, "Remotely Piloted Innovation: Terrorism, Drones and			
2015/0339912	A1	11/2015	Farrand	Supportive Technology," Combating Terrorism Center at West Point,			
2015/0370250	A1	12/2015	Bachrach	United States Military Academy, Oct. 2016, 77 pages.			
2016/0055399	A1	2/2016	Hiester	Ying, Gao, et al., "Design and Realization of Virtual Scene System			
2016/0086621	A1	3/2016	Hearing et al.	in UAV Electronic Warfare," International Conference on Informa-			
2016/0095001	A1	3/2016	Uelk et al.	tion Engineering and Computer Science, IEEE, 2009, 4 pages.			
2016/0100415	A1	4/2016	Mishra et al.	"In the battle for Mosul, grenades rain down from ISIS drones,"			
2016/0116915	A1	4/2016	Pulleti	Rudaw, Jan. 7, 2017, 3 pages.			
2016/0117931	A1	4/2016	Chan G08G 5/0043 701/120	"Liteye and Tribalco Team to Deliver Auds Counter Drone Systems			
2016/0118059	A1	4/2016	Hearing et al.	to U.S. Military Customers," PR Newswire, Jan. 12, 2017, 3 pages.			
2016/0119052	A1	4/2016	Frerking et al.	Natson, Ben, "The Drones of Isis," Defense One, Jan. 12, 2017, 10			
2016/0119938	A1	4/2016	Frerking et al.	pages.			
2016/0134358	A1	5/2016	Jalali	Office Action dated Apr. 4, 2017, issued in related U.S. Appl. No.			
2016/0135204	A1	5/2016	Mishra et al.	14/821,907.			
				Notice of Allowance and Fee(s) Due dated May 15, 2017, issued in			
				related U.S. Appl. No. 14/821,907.			
				Anderton, Donald C., "Synchronized Line-Scan LIDAR/EO Imager			
				for Creating 3D Images of Dynamic Scenes: Prototype II," Utah			
				State University, All Graduate Plan B and Other Reports, 2005, 148			
				pages.			
				Gezer, Berat Levent, "Multi-Beam Digital Antenna for Radar,			

(56)

References Cited

OTHER PUBLICATIONS

Communications, and UAV Tracking Based on Off-The-Shelf Wireless Technologies,” Thesis, Naval Postgraduate School, Sep. 2006, 127 pages.

Pham, Tien, et al., “TTCP AG-6: Acoustic Detection and Tracking of UAVs,” Proceedings of SPIE, vol. 5417, 2004, pp. 24-30.

Hang, Shuqun, “Object Tracking in Unmanned Aerial Vehicle (UAV) Videos Using a Combined Approach,” IEEE, 2005, pp. II-681-II-684.

Passary, Anu, “Drone invading your privacy? Now, there’s a warning system for that,” Tech Times, <http://www.techtimes.com/articles/8816/20140620/drone-invading-your-privacy-now-theres-a-warning-system-for-that.htm>, 3 pages.

Amirhossein Fereidounbar, Gian Carlo Cardarilli, Luca Di Nunzio, Rocco Fazzolari; “UAV Channel Estimation with STBC in MIMO Systems”, The International Conference on Advanced Wireless, Information, and Communication Technologies (AWICT 2015).

Liu Tao, Hu Yonghui, Hua Yu, Wu Meifang; “Study on Autonomous and Distributed Time Synchronization Method for formation UAVs”; 2nd International Conference on Electrical, Computer Engineering and Electronics (ICECEE 2015).

Hamed Rezaee, Farzaneh Abdollahi; “Synchronized Cross Coupled Sliding Mode Controllers for Cooperative UAVs with Communication Delays”; 51st IEEE Conference on Decision and Control; Dec. 10-13, 2012. Maui, Hawaii, USA.

S. Rayanchu, et al.; “Airshark: Detecting Non-WiFi RF Devices using Commodity WiFi Hardware,” IMC ’11 Proceedings of the 2011 ACM SIGCOMM conference on Internet measurement conference; pp. 137-154; Berlin, Germany—Nov. 2-4, 2011.

A. Patro, et al.; “AirTrack: Locating Non-WiFi interferers using Commodity WiFi Hardware,” ACM SIGMOBILE Mobile Computing and Communications Review; vol. 15 Issue 4, pp. 52-54; Oct. 2011.

K. Saylor, “A World of Proliferated Drones: A Technology Primer.” <https://www.cnas.org/publications/reports/a-world-of-proliferated-drones--a-technology-primer>; Jun. 10, 2015.

T. Goodspeed, “Packets in Packets: Orson Welles’ In-Band Signaling Attacks for Modem Radios,” WOOT’11 Proceedings of the 5th USENIX conference on Offensive technologies; San Francisco, CA; 2011.

N.O. Tippenhauer, et al.; “On the Requirements for Successful GPS Spoofing Attacks,” Conference: Proceedings of the 18th ACM Conference on Computer and Communications Security, CCS 2011, Chicago, Illinois, USA, Oct. 17-21, 2011.

N. Kothari, et al.; “Finding Protocol Manipulation Attacks,” SIGCOMM ’11 Proceedings of the ACM SIGCOMM 2011 conference pp. 26-37; Toronto, Ontario, Canada—Aug. 15-19, 2011.

J. Bellardo and S. Savage, “802.11 Denial-of-Service Attacks: Real Vulnerabilities and Practical Solutions,” SSYM’03 Proceedings of the 12th conference on USENIX Security Symposium—vol. 12; pp. 2-2; Washington, DC—Aug. 4-8, 2003.

* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4

**SYSTEMS AND METHODS FOR
DETECTING, TRACKING AND
IDENTIFYING SMALL UNMANNED
SYSTEMS SUCH AS DRONES**

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 15/967,291 filed Apr. 30, 2018; which is a continuation of U.S. patent application Ser. No. 15/598,112 filed May 17, 2017, now U.S. Pat. No. 9,977,117; which is a continuation of U.S. patent application Ser. No. 14/821,907 filed Aug. 10, 2015, now U.S. Pat. No. 9,689,976; which claims benefit of U.S. Provisional Application No. 62/094,154 filed Dec. 19, 2014. The disclosures of the prior applications are incorporated herein in their entirety by reference.

FIELD OF THE INVENTION

The present invention relates to an integrated detection and countermeasure solution against unmanned aerial systems, which are commonly referred to as drones.

BACKGROUND OF THE INVENTION

Unmanned aerial systems, which are commonly referred to as drones, have become commercially available to the general public. While there may be many safe commercial and recreational uses for unmanned aerial systems these devices may potentially pose hazards to commercial and general aviation, the public, and private and government property if improperly operated. Furthermore unmanned aerial systems may be used to violate the privacy of personal, commercial, educational, athletic, entertainment and governmental activities. Most unfortunately unmanned aerial systems may potentially be used in the furtherance of invading privacy, or carrying out terrorist and/or criminal activities. There is a need for a device and method of detecting the approach of an unmanned aerial system towards a location where personal, public, commercial, educational, athletic, entertainment and governmental activities occur and where an unmanned aerial system could potentially be used for invading privacy, or carrying out terrorist and criminal activities. The present invention provides an integrated detection and countermeasure solution against unmanned aerial systems and offers increased security, privacy, and protection from the threats of violence involving small unmanned aerial vehicles/systems (sUAS) and is applicable to governmental, commercial, private, and public concerns.

SUMMARY OF THE INVENTION

There is provided in accordance with the present invention a system that detects, identifies, tracks, deters and or interdicts small unmanned aerial vehicles/systems (sUAS) from ground level to several thousand feet above ground level. The system disclosed herein is an integrated solution comprising components using: existing technology for a new use; multiplexing hardware components designed for this application; and development of the integrating software which calculates the exact x, y, z coordinates of the subject sUAS; subject sUAS RF signal analysis to determine the most appropriate RF signal characteristics to affect the subject sUAS; precision alignment of high definition elec-

tro-optical (EO) sensors and infrared (IR) sensors and image recognition algorithms providing confirmation that the subject sUAS is in violation of airspace authorization. The integration of these components via the herein disclosed combination of software and hardware is novel, not related to existing art in purpose, is non-obvious, and provides a useful solution to uninvited, invasive and potentially hazardous sUAS operations.

The system of the present invention provides an integrated and diversified solution that can be deployed as a "permanent placement" or mobile system on land, sea, or air platform.

The system of the invention may be strategically deployed to monitor the airspace around a protected interest such as a property, place, event or very important person (VIP) offering 360 degree azimuth coverage extending from the receiving antennae of the system out to a maximum lateral distance of about 2 kilometers (6560 feet) and within the lateral boundaries up to a maximum altitude of about 1.5 kilometers (4920 feet) above ground level (AGL).

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic representation of the components and function of an integrated detection and countermeasure system for use against unmanned aerial systems.

FIG. 2 is a schematic representation of a countermeasure and interdiction to UAS system of the integrated detection and countermeasure system for use against unmanned aerial systems, 44 of FIG. 1.

FIG. 3 is a schematic representation of the Radio Frequency (RF) detection system of the integrated detection and countermeasure system for use against unmanned aerial systems, 44 of FIG. 1.

FIG. 4 is a schematic representation of the Radar detection system and Electro Optical and Infer Red (EO/IR) detection system of the integrated detection and countermeasure system for use against unmanned aerial systems, 44 of FIG. 1.

DETAILED DESCRIPTION OF THE
INVENTION

Part Numbers

- 10 Transmitting multi band high gain directional antenna array with vertical polarity
- 12 Receive directional antenna array
- 14 Receive Omni antenna array
- 16 EO/IR (Electro Optical/Infra Red) sensor
- 18 Automatic antenna alignment assembly
- 20 Multi-band LNA assembly
- 22 Automatic antenna alignment assembly
- 24 High fidelity RF receivers/host work station CPU
- 26 Azimuth and elevation vector coordinate data processor
- 28 Empower 1189-BBM3 wideband HPA assembly
- 30 Receive blanking
- 32 Direction detect and range estimation
- 34 Key sight N9310A RF signal generator with multiple modulation sources
- 36 Spectral signals detect and type identification
- 38 ECM modulation type select
- 40 Frequency and waveform parameters
- 42 Modulation database
- 43 Commercial 4k X band radar
- 44 Subject UAS (Unmanned Aerial System)

- 45 Radar clutter and target filter processor
- 46 Azimuth and elevation vector coordinate data processor
- 99 System power and status monitor
- 100 Entire system
- 102 Countermeasure and deterrent section of entire system
- 103 Radio Frequency (RF) detection section of entire system
- 104 Radar detection section of entire system
- 105 Electro Optical and Infer Red (EO/IR) detection section of entire system

Glossary

As used herein and in the claims each of the terms defined in this glossary is understood to have the meaning set forth in this glossary.

Algorithm—a process or set of rules to be followed in calculations or other problem-solving operations by a computer

Automatic Antenna Alignment Assembly—designated as **18** in FIGS. **1**, **2** and **3**, and as **22** in FIGS. **1** and **4**, is specialized electronic equipment specifically designed to automatically point the directional antennae and or camera, laser systems to the desired location, namely a small unmanned aerial vehicles/systems (sUAS) designated as a target **44** in FIG. **1**, based on longitude and or latitude information gained or received by the receiving antennae, designated as **12** and **14** in FIGS. **1** and **3**, and or radar antennae designated as **43** in FIGS. **1** and **4**; this specialized equipment can be purchased from and is proprietary to EnrGies Engineering located in Huntsville, Ala.

Azimuth and Elevation Vector Coordinate Data—designated as **26** in FIGS. **1** and **4**, is specialized algorithm software that has been developed to be used with a spherical coordinate system for three-dimensional space where three numbers specify the position of a point measured in latitude, longitude and elevation obtained from an EO/IR Sensor designated as **16** in FIGS. **1** and **4** that includes a Laser Range Finder, and/or Radar designated as **43** in FIGS. **1** and **4**

Blanking—designated as **30** in FIGS. **1**, **2** and **3** is the time between the last radio transmitting signal and the beginning of the next radio transmitting signal

C2 Communications—Command and Control Communications links

Commercial—relating to or engaged in commerce (i.e. NON-military)

Counter—to offer in response or act in opposition

CUASs2—Counter Unmanned Aerial Systems of Systems, the system of the present invention used to detect, identify and deter or interdict unmanned aerial vehicles or systems

Directional Antenna—designated as **10** in FIGS. **1** and **2**, and **12** in FIGS. **1** and **3**, a class of directional or beam antenna that radiates greater power in one or more directions allowing for increased performance on transmits and receives and reduced interference from unwanted sources

Direction Detection and Range Estimation—designated as **32** in FIGS. **1-4**, is specialized algorithm software that has been developed to detect a suspected target or signal of interest and calculated to obtain the azimuth and distance to that target or signal of interest based on data obtained by the Radio Frequency (RF) detection section **103** in FIG. **3**, the

Radar detection section **104** in FIG. **4**, and the Electro Optical and Infer Red (EO/IR) detection section **105** in FIG. **4**

DF—designated as **12** in FIGS. **1** and **3**, Direction Finding refers to the measurement of the direction from which a received signal was transmitted, this can refer to radio or other forms of wireless communication

Drone—designated as **44** in FIG. **1**, refers to an unmanned aircraft operated by remote control, allows for human correction (i.e. semi-autonomous), or autonomous, see also UAV, UAS, sUAS, RPA

EAR—Export Administration Regulations are regulations that are administered by the United States Department of Commerce and regulate the export of “dual use” items; technology designed for commercial purposes and with potential military applications, such as computers, software, aircraft, and pathogens as well the re-export of items

Electro-Optical and Infrared Sensors—designated as **16** in FIGS. **1** and **4**, is a combination of a standard high definition video camera capable of viewing in daylight conditions and an infrared video camera capable of viewing in the infrared light perspective; both camera systems can be purchased “Off-The-Shelf” as common technology, one common manufacturer of this type of camera systems is FLIR Systems

Electronic Counter Measure (ECM) Modulation Type Select—designated as **38** in FIGS. **1-3** is specialized algorithm software that has been developed to help narrow down the radio frequency identified by a modulation lookup table (defined in this glossary) of the specific unmanned aerial vehicle/system of interest, designated as a target **44** in FIG. **1**, utilizing a database library that was created and categorized with the specific radio frequencies common to all unmanned aerial vehicles/systems

Emitter—to send or give out a matter of energy

EO—Electro-Optics is a branch of electrical engineering and materials science involving components, devices and systems that operate by modification of the optical properties of a material by an electric field, thus it concerns the interaction between the electromagnetic (optical) and the electrical (electronic) states of materials

Frequency—the rate at which a vibration occurs that constitutes a wave, either in a material (as in sound waves), or in an electromagnetic field (as in radio waves and light), usually measured per second

Frequency and Waveform Parameters—designated as **40** in FIGS. **1-3**, Is specialized algorithm software that has been developed to identify unmanned aerial vehicles/systems utilizing a database library that was created and categorized with the specific radio frequency waveform common to all unmanned aerial vehicles/systems

IR—infrared is invisible (to the human eye) radiant energy, electromagnetic radiation with longer wavelengths than those of visible light, extending from the nominal red edge of the visible spectrum at 700 nanometers (frequency 430 THz) to 1 mm (300 GHz)

ISR—Intelligence, Surveillance, Reconnaissance is an activity that synchronizes and integrates the planning and operation of sensors, assets, and processing, exploitation, and dissemination systems in direct support of current and future operations

ITAR—International Traffic in Arms Regulations is a set of United States government regulations that control the export and import of defense-related articles and services on the United States Munitions List (USML)

Jam or Jammed or Jammers or Jamming—to interfere with or prevent the clear reception of broadcast signals by

electronic means to become unworkable or to make unintelligible by sending out interfering signals by any means

Laser—a device that emits light through a process of optical amplification based on the stimulated emission of electromagnetic radiation

Laser Range Finder—designated as **16** in FIGS. **1** and **4**, is a rangefinder which uses a laser beam, usually pulsed, to determine the distance to an object

LED—Light-Emitting Diode is a semiconductor device that emits visible light when an electric current passes through it

Matrix—an environment in which something develops

Matrix Directional Transmit Antenna Array—designated as **10** in FIGS. **1** and **2**, Is a signal processing technique used in sensor (Antenna) arrays for directional signal transmission; this is achieved by combining elements in a phased array in such a way that signals at particular angles experience constructive interference while others experience destructive interference; his equipment can be purchased “Off-The-Shelf” and one common manufacturer of this type of equipment is Motorola

Mobile Platform (MP)—the mobile Counter Unmanned Aerial System of Systems equipment installed on any vehicle with the intent to move from one location to another location as needed to fulfill a short-term need in the detection, identification and deterrence or interdiction of an unmanned aerial vehicle

Modulation—the process of varying one or more properties of a periodic waveform, called the carrier signal, with a modulating signal that typically contains information to be transmitted

Modulation Function Generation—designated as **34** in FIGS. **1-3**, Is specialized algorithm software that has been developed to transmit (Jam) a specific radio frequency, designated by **38** in FIG. **1-3** and **42** in FIGS. **1** and **3**, which is unique to a specific unmanned aerial vehicles/systems utilizing a database library that was created and categorized with the specific radio frequencies used on all common unmanned aerial vehicles/systems

Modulation Lookup Table—designated as **42** in FIGS. **1** and **3**, is specialized algorithm software that has been developed to identify the broad range of radio frequencies being used by a specific unmanned aerial vehicle/system of interest, designated as a target **44** in FIG. **1**, utilizing a database library that was created and categorized with the specific radio frequencies common to all unmanned aerial vehicles/systems

Multi-Band—a communication device that supports multiple radio frequency bands

Multiband Low Noise Amplifier (LNA) Assembly—designated as **20** in FIGS. **1** and **3**, is a multi-radio frequency electronic amplifier used to amplify possibly very weak signals, for example captured by an antenna

Omni-directional Antenna—designated as **14** in FIGS. **1** and **3**, a class of antenna which receives or transmits radio wave power uniformly in all directions in one plane, with the radiated power decreasing with elevation angle above or below the plane, dropping to zero on the antenna’s axis

OTS—Off The Shelf refers to materials or equipment that currently exists and is readily available for purchased or use

Permanent Platform (PP)—the installation of the Counter Unmanned Aerial System of Systems equipment at a specific location to fulfill a long-term need in the detection, identification and deterrence or interdiction of an unmanned aerial vehicle

Pulse—a single vibration or short burst of sound, electric current, light, or other wave

RPA—Remotely Piloted Aircraft, aka UAV, UAS

RF—Radio Frequency is a rate of oscillation in the range of around 3 kHz to 300 GHz, which corresponds to the frequency of radio waves, and the alternating currents that carry radio signals

Receive Blanking—designated as **30** in FIGS. **1-3**, is specialized algorithm software that has been developed to stop the receiving antennae, designated as **12** and **14** in FIGS. **1** and **3**, from receiving radio frequency signals during the time that the counter measure transmitting frequency, designated as **34** in FIGS. **1-3**, is being transmitted by directional transmitting antennae, designated as **10** in FIGS. **1** and **2**, for the purpose of deterrence or interdiction of the suspect unmanned aerial vehicle/system, designated as a target **44** in FIG. **1**, identified as a known threat

Receive Directional Antenna Array—designated as **12** in FIGS. **1** and **3**, refers to multiple receiving antennae arranged such that the superposition of the electromagnetic waves is a predictable electromagnetic field and that the currents running through them are of different amplitudes and phases; this equipment can be purchased “Off-The-Shelf” and one common manufacturer of this type of equipment is Motorola

Receive Omni Antenna Array—designated as **14** in FIGS. **1** and **3**, is a class of antenna that receives radio wave power uniformly in all directions in one plane; this equipment can be purchased “Off-The-Shelf” and one common manufacturer of this type of equipment is Motorola

STC—Slew To Cue, the autonomous actions of electronic, radio or optical sensors to rotate using an automatic antenna alignment assembly designated as **18** in FIGS. **1-3**, and **22** in FIGS. **1** and **4** to move and point cameras **16** in FIGS. **1** and **4** and countermeasures **10** in FIGS. **1** and **2** in the direction of a suspect target **44** in FIG. **1**, based on input from data processed by components **26** in FIGS. **1** and **4**, and **46** in FIGS. **1**, **3** and **4**, thus, keeping the “cued” targets in view at all times with or without human intervention

Spectral Signal—designated as **36** in FIGS. **1** and **3**, the frequency spectrum of a time-domain signal is a representation of that signal in the frequency domain

Spectral Signal Detection and Type Identification—designated as **36** in FIGS. **1** and **3**, is specialized algorithm software that has been developed to detect and identify unmanned aerial vehicles/systems utilizing a database library that was created and categorized with the spectral signatures common to all unmanned aerial vehicles/systems

sUAS—designated as **44** in FIG. **1** small Unmanned Aerial System, usually weighing less than 20 kg or 55 lbs.

Target—designated as **44** in FIG. **1**, something or someone of interest to be affected by an action or development

Target Tracking Log—a graphic or table of coordinates documenting the target’s path in space during area of concern

Technology—the application of science, especially to industrial or commercial objectives

Threat—a declaration or an act of an intention or determination to inflict the destruction of property or harm, punishment, injury or death of person(s)

UAS—designated as **44** in FIG. **1**, Unmanned Aerial System, Unmanned Aircraft System (aka UAV, RPA)

UAV—designated as **44** in FIG. **1**, Unmanned Aerial Vehicle, Unmanned Aircraft Vehicle (aka UAS, RPA)

Uplink—the part of a network connection used to send, or upload, data from one device to a remote device

Uplink Video/Radio Transmitter Assembly—designated as **28** in FIGS. **1** and **2**, is a device that will take the received radio or video frequency information from database libraries

designated as **36** in FIGS. **1** and **3**, **40** in FIGS. **1-3**, and **42** in FIGS. **1** and **3** and send it through a radio amplifier designated as **34** in FIGS. **1-3** to a transmitting directional antenna or matrix directional transmit antenna array designated as **10** in FIGS. **1** and **2**; this equipment can be purchased “Off-The-Shelf” and one common manufacturer of this type of equipment is Motorola

Uplink/Video Standard Definition (SD) Receiver & Host Workstation—designated as **24** in FIGS. **1** and **3**, is a connection from the antennae to the video encoder where the information is processed by the main computer network; the uplink equipment can be purchased “Off-The-Shelf” and one common manufacturer of this type of equipment is Cisco Systems; the video receiver and main computer is also “Off-The-Shelf” technology and are readily available from numerous manufacturers

Vector—a quantity having direction as well as magnitude, especially as determining the position of one point in space relative to another

Watt—the system unit of power, equivalent to one joule per second, corresponding to the power in an electric circuit in which the potential difference is one volt and the current one ampere

Waveform—a graphic representation of the shape of a wave that indicates its characteristics as frequency and amplitude

Referring to FIGS. **1-4** there are shown schematic representations of the components and function of an integrated detection and countermeasure system **100** for use against unmanned aerial systems **44**. A first function of the system is locating and identifying a UAS target. The present invention provides integrated detection sections **103-105** and deterrent/countermeasure section **102** against small unmanned aerial vehicles/systems (sUAS), which are commonly referred to as drones, in the vicinity of, or approaching the vicinity of a property, place, event or very important person (VIP). All sUAS’s have a distinct set of spectral signatures (sound, heat, radar cross section, radio frequency wave pattern) detected by a spectral signal identifier processor **36**. This fact is the basis for the detection sections **103-105** of the system **100** of the present invention and sections **103-105** is the first function of the system. Using a proven high-end direction finding (DF) high fidelity RF receiver **24** coupled with omnidirectional and directional antennae **12**, **14** and unique created software of the system when the RF signature of the sUAS flying within the system’s detection boundaries is detected, for example within maximum lateral distance of about 2 kilometers (6560 feet) and within the aerial boundaries up to a maximum altitude of about 1.5 kilometers (4920 feet) above ground level (AGL). This element of the system may be augmented and is shown with additional signature detection elements consisting of acoustic and/or radar sensors **43** and electro optical sensors **16**. These elements operate with unique software translating discernable signatures into coherent data aiding in the detection and location process. All signature data is then processed to generate a reference azimuth and elevation **26**, **46** from the sensor to the subject sUAS **44**. The information generated by the systems detection section is then passed electronically to the direction and range estimation processor **32** to yield a target’s location. The system **100** of the present invention uses the hardware and software of the Radio Frequency (RF) detection section **103** to identify the type of sUAS and the associated known and observed radio frequencies signatures required for the sUAS communications and video data exchange.

A second function of the system is providing countermeasures against sUAS that is determined to be a threat in or approaching the vicinity of a property, place, event or VIP. Azimuthal data for a sUAS is determined by the detection section **103-105** of the system. The system’s control software/hardware provides this information to the integrated Electro-Optical (EO) and Infrared (IR) sensor **16** which autonomously centers the field of regard of the EO/IR sensor to the known location of the subject sUAS **44**. When the visual identification is confirmed to be a sUAS; by either video analytics or human verification, the system of invention’s software/hardware will then determine the precise x, y, z coordinates (x=longitude, y=latitude, z=altitude) of the sUAS. This precise location and range information is provided to the countermeasure and deterrent section **102** of the system **100**. Using this data the countermeasure and deterrent section **102** computes the RF spectral characteristics that will nullify signals that the sUAS expects to receive. A signal generator **34** produces a tailored signal and a variable strength amplifier **28** generates the output power required; causing the desired effect at the desired range to the subject sUAS **44**. The countermeasure and deterrent section **102** broadcasts the unique generated RF waveform using highly directional and focused antennae **10**. The system uses Blanking **30** at the time between the last radio transmitting signal and the beginning of the next radio-transmitting signal of the transmitted signal in accordance with the frequency and waveform parameters **40** to avoid negative internal effects to system **103**. The system then disables the sUAS sensors, or causes the sUAS navigation system to malfunction due to communication interference causing most sUAS to enter a “Fail Safe Mode” (either land immediately or return to the launch point). This action is sUAS specific and is based on the manufacturer design and sUAS operational capabilities.

The interdict element of a system of the present invention interdicts the operation of an sUAS initially in a non-destructive manner, increasing to a destructive manner based on the response of the target sUAS. A system of the present invention may interdict the operation of a sUAS in a non-destructive manner by transmitting a concentrated Radio Frequency (RF) emission tuned to the specific sUAS characteristics identified by the spectral analysis during the detection process. These RF waveforms are then used to disrupt the expected inputs to the onboard controller of the identified sUAS. The video downlink signal is the initial target of the interdiction process. If this interruption is not sufficient to deter the sUAS, the RF transmitter will be tuned to the appropriate control frequency to disrupt the sUAS on-board electronics. These actions will cause most sUAS to enter the Fail Safe Mode (either land immediately or return to the launch point). The present invention considers the differences based on the manufacturer design and operational capabilities of the sUAS on a case-by-case basis and tailors the inventions countermeasure/deterrent response accordingly.

The countermeasure and deterrent section **102** of the system **100** interdicts the operation of an sUAS in a non-destructive manner by using the non-destructive technology described to generate a interdict transmission signal that is significantly stronger than control signals from an operator of the sUAS. This interdict transmission will have significantly higher gain (Stronger Signal) and target both the sensor and the control electronics of the sUAS. The interdiction process may be augmented with electro-magnetic pulse technology, pulsed laser and is specifically designed to accept other current or future counter-measures used to defeat the sUAS’ electronics, motors and or navigation

systems. The effects of the higher gain radio transmission will cause amongst other effects, servo-chatter, resulting in the loss of control of the sUAS and disruption of most on-board electronic processes increasing the probability of a forced landing. In addition, a counter sUAS can be dispatched with autonomous navigation data being supplied by the system of present invention to locate and intentionally disable the opposing sUAS by flying into it, dropping a net on the threat, covering it with spray foam or liquid or capturing the opposing sUAS.

The system of the present invention will use direction finding (DF) equipment **12, 16** to search for the radio communications link of an airborne sUAS **44**, commonly referred to as a drone. Integrating multiple Direction Finding (DF) equipment **26, 46** to the system of the present invention will increase the precision in obtaining the azimuth that the sUAS is flying. Integrating radar equipment **43** provided with a radar clutter and target filter processor **45**, with the direction finding (DF) equipment will provide the present invention the ability to determine with greater accuracy the altitude and azimuth of the sUAS **44** at the time of discovery and during the time it remains within the systems detection boundaries.

When the DF equipment **26, 46** has detected a communication link of a sUAS within the system boundaries, the receive host workstation **24** will analyze the radio frequency wave signature and confirm that the RF detected is from a sUAS. This process also applies when a radar unit **43** is integrated with the DF equipment.

The information obtained from DF **26, 46** and or radar unit **43** is then sent to the direction detect and range estimation unit **32** where algorithms will be used to send sUAS location coordinates to the Automatic Antenna Alignment Assembly (A4) **22, 18**. Put another way, using Slew To Cue, the autonomous actions of electronic, radio or optical sensors to rotate using an automatic antenna alignment assembly **18, 22** to move and point cameras **16** and countermeasures in the direction of a suspect target **44** based on input from data processed by the azimuth and elevation unit **26 46**, thus, keeping the "cued" targets in view at all times with or without human intervention. This information will then direct the Automatic Antenna Alignment Assembly (A4) **22** to point the Electro-Optical and Laser Range Finding unit **16** at the sUAS to allow for visual confirmation, distance and elevation of the sUAS to be known.

The information obtained by the Laser Range Finding equipment will be sent to the Azimuth and Elevation Vector Coordinate Data unit **26** which will send exact azimuth and elevation information to the A4 system **18** controlling the Matrix Directional Transmit Antenna Array **10** via the Direction Detect and Range Estimation unit **32**.

When the communications link between the subject sUAS and its' operator is detected by the Radio Frequency (RF) detection section **103** of the system the information is passed through the Multiband LNA Assembly **20** and through the Uplink Receive Host Workstation **24**. The information is then sent to the Spectral Signal Detect and Type Identification unit **36** where the type of sUAS is determined based on a known database containing Spectral Signal Wave information **36**. When the Spectral Signal Wave information is known the information is sent to the Frequency and Wave Form Parameters unit **40** where the analyzed RF data is sent to the Modulation Look Up Table **42**. When the Modulation information is known the information is then sent to the ECM Modulation Type Select unit **38**.

The selected modulation waveform is then sent to the Uplink Video Transmitter Assembly **28** that unit works in

conjunction with the Receive Blanking unit **30**. When the Uplink Video Transmitter **28** is transmitting a radio signal the Receive Blanking unit **30** will force the DF antennae **12, 14** to stop receiving the radio frequency being transmitted by the Matrix Directional Transmit Antenna Array **10**. The radio frequency selected to disrupt the communication link of the sUAS with its' operator is then transmitted by the Transmitter Assembly **28** using the Matrix Directional Transmit Antenna Array **10** aimed at the sUAS **44** via the Automatic Antenna Alignment Assembly **18**.

While the invention has been described with reference to certain exemplary embodiments, obvious modifications and alterations are possible by those skilled in the related art. Therefore, it is intended that the invention include all such modifications and alterations to the full extent that they come within the scope of the following claims or the equivalents thereof.

The invention claimed is:

1. A system, comprising:

at least one radio receiver configured to detect a radio frequency (RF) signature based on a radio signal communicated between an aerial target and a remote control device;

at least one radar configured to detect the target; and
at least one computer processor programmed to identify the target based on the detected RF signature and locate the target based on the radar detection, and based on at least one of target identification and/or target location, determine if the target is an unmanned aerial system (UAS).

2. The system recited in claim **1**, further comprising a database of RF signature data that the at least one computer processor accesses to detect the RF signature.

3. The system recited in claim **2**, wherein the RF signature data comprises modulation information, and the database comprises a modulation look-up table.

4. The system recited in claim **1**, wherein determining the UAS comprises one of target of interest or threat if its location is within a predetermined airspace boundary around a protected interest.

5. The system recited in claim **1**, further comprising an alignment assembly configured to employ UAS location information to point at least one of the radar, a laser range finder, a radio receiver antenna, and an electro-optic receiver in the direction of the UAS.

6. The system recited in claim **1**, further comprising an electronic countermeasure (ECM) signal generator configured to transmit an ECM signal to disrupt communications between the UAS and the remote control device.

7. The system recited in claim **6**, wherein the ECM signal generator employs waveform parameters of at least one of an uplink and a downlink radio signal.

8. An apparatus, comprising:

a memory; and at least one processor operatively coupled to the memory, the at least one processor configured to: detect a radio frequency (RF) signature of at least one of an uplink and a downlink radio signal communicated between an unmanned aerial system (UAS) and a remote control device;

identify the UAS based on the RF signature;

process radar data to locate the UAS; and

based on at least one of UAS identification and location, determine if the target is a UAS.

9. The apparatus recited in claim **8**, further comprising a database of RF signature data that the at least one processor accesses to identify the UAS.

11

10. The apparatus recited in claim 9, wherein the RF signature data comprises modulation information, and the database comprises a modulation look-up table.

11. The apparatus recited in claim 8, wherein determining the UAS comprises one of target of interest or threat if its location is within a predetermined airspace boundary around a protected interest.

12. The apparatus recited in claim 8, wherein the at least one processor is further configured to control an alignment assembly to point at least one of a radar, a laser range finder, a radio receiver antenna, and an electro-optic receiver in the direction of the UAS.

13. The apparatus recited in claim 8, wherein the at least one processor is further configured to control an electronic countermeasure (ECM) signal generator that generates an ECM signal for disrupting communications between the UAS and its remote-control device.

14. The apparatus recited in claim 13, wherein the ECM signal generator employs waveform parameters of at least one of the uplink and the downlink radio signal.

15. A method, comprising:
detecting a radio frequency (RF) signature of at least one of an uplink and a downlink radio signal communicated between an unmanned aerial system (UAS) and a remote control device;
identifying the UAS based on the RF signature;

12

employing a radar to locate the UAS; and based on at least one of UAS identification and location, determining if the target is a UAS.

16. The method recited in claim 15, wherein identifying the UAS comprises accessing a database of RF signature data.

17. The method recited in claim 16, wherein the RF signature data comprises modulation information, and the database comprises a modulation look-up table.

18. The method recited in claim 15, wherein determining if the UAS comprises one of target of interest or threat if the UAS's location is within a predetermined airspace boundary around a protected interest.

19. The method recited in claim 15, further comprising controlling an alignment assembly to point at least one of a radar, a laser range finder, a radio receiver antenna, and an electro-optic receiver in the direction of the UAS.

20. The method recited in claim 15, further comprising employing an electronic countermeasure (ECM) signal generator to generate an ECM signal for disrupting communications between the UAS and its remote-control device.

21. The method recited in claim 20, wherein the ECM signal generator employs waveform parameters of at least one of the uplink and the downlink radio signal.

* * * * *