



US009868524B2

(12) **United States Patent**
Welsh et al.

(10) **Patent No.:** **US 9,868,524 B2**
(45) **Date of Patent:** **Jan. 16, 2018**

(54) **UNMANNED AERIAL VEHICLE CONFIGURATION FOR EXTENDED FLIGHT**

(71) Applicant: **Amazon Technologies, Inc.**, Seattle, WA (US)
(72) Inventors: **Ricky Dean Welsh**, Bellevue, WA (US); **Daniel Buchmueller**, Seattle, WA (US); **Fabian Hensel**, Zurich (CH); **Gur Kimchi**, Bellevue, WA (US); **Louis LeRoi LeGrand, III**, Seattle, WA (US); **Brandon William Porter**, Yarrow Point, WA (US); **Walker Chamberlain Robb**, Seattle, WA (US); **Joshua White Traube**, Seattle, WA (US)

(73) Assignee: **Amazon Technologies, Inc.**, Seattle, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/538,570**

(22) Filed: **Nov. 11, 2014**

(65) **Prior Publication Data**
US 2016/0129998 A1 May 12, 2016

(51) **Int. Cl.**
B64C 27/24 (2006.01)
B64C 29/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B64C 39/024** (2013.01); **B64C 27/22** (2013.01); **B64C 27/24** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B64C 27/00; B64C 27/08; B64C 27/20; B64C 27/22; B64C 27/26;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,979,658 A * 9/1976 Foster H02J 7/0081
320/156
6,293,491 B1 * 9/2001 Wobben B64C 27/00
244/17.23

(Continued)

FOREIGN PATENT DOCUMENTS

DE 102012202698 * 8/2013 B64C 27/08
DE 102012202698 A1 8/2013

(Continued)

OTHER PUBLICATIONS

Ferrell et al. "Dynamic Flight Modeling of a Multi-Mode Flying Wing Quadrotor Aircraft", 2013.

(Continued)



Primary Examiner — Richard R Green

(74) *Attorney, Agent, or Firm* — Athorus, PLLC

(57) **ABSTRACT**

This disclosure describes a configuration of an unmanned aerial vehicle (UAV) that will facilitate extended flight duration. The UAV may have any number of lifting motors. For example, the UAV may include four lifting motors (also known as a quad-copter), eight lifting motors (octo-copter), etc. Likewise, to improve the efficiency of horizontal flight, the UAV also includes a pushing motor and propeller assembly that is oriented at approximately ninety degrees to one or more of the lifting motors. When the UAV is moving horizontally, the pushing motor may be engaged and the pushing propeller will aid in the horizontal propulsion of the UAV.

21 Claims, 10 Drawing Sheets



(51)	Int. Cl. <i>B64C 39/02</i> (2006.01) <i>B64C 27/22</i> (2006.01)	2009/0283629 A1 11/2009 Kroetsch et al. 2011/0042508 A1 2/2011 Bevirt 2012/0018571 A1 1/2012 Goelet 2012/0083945 A1 4/2012 Oakley et al. 2013/0092799 A1* 4/2013 Tian	
(52)	U.S. Cl. CPC <i>B64C 29/0025</i> (2013.01); <i>B64C 2201/027</i> (2013.01); <i>B64C 2201/108</i> (2013.01); <i>B64C</i> <i>2201/128</i> (2013.01); <i>B64C 2201/165</i> (2013.01)	2013/0134254 A1* 5/2013 Moore 2014/0032034 A1 1/2014 Raptopoulos et al. 2014/0099853 A1 4/2014 Condon et al. 2014/0103158 A1 4/2014 Berry 2014/0131510 A1 5/2014 Wang et al. 2014/0217230 A1* 8/2014 Helou, Jr.	B64C 27/26 244/7 R B64D 1/16 244/17.11 B64C 25/14 244/17.17
(58)	Field of Classification Search CPC <i>B64C 2027/8236</i> ; <i>B64C 29/0025</i> ; <i>B64C</i> <i>29/005</i> ; <i>B64C 2201/024</i> ; <i>B64C 2201/108</i> See application file for complete search history.	2014/0231582 A1 8/2014 Headrick 2015/0175258 A1* 6/2015 Lee 2016/0207625 A1* 7/2016 Judas	B64C 27/08 244/17.23 B64C 29/0025
(56)	References Cited		
	U.S. PATENT DOCUMENTS		
	7,273,195 B1 9/2007 Gollhofer 7,911,796 B2* 3/2011 Vander Ploeg H05K 7/1412 257/727		
	8,322,648 B2 12/2012 Kroetsch et al. 8,485,464 B2* 7/2013 Kroo B64C 29/0025 244/17.23		
	8,596,571 B2 12/2013 Goelet 8,964,396 B1* 2/2015 Dailey H05K 7/1492 312/223.2		
	9,061,763 B1 6/2015 Christensen et al. 9,120,560 B1* 9/2015 Armer B64C 27/08 D751,025 S 3/2016 Howell et al. D756,842 S 5/2016 Ashjaee 9,457,901 B2 10/2016 Bertrand et al. 2003/0085319 A1* 5/2003 Wagner B64C 27/20 244/12.3		
		FOREIGN PATENT DOCUMENTS	
		GB 2486448 A 6/2012 GB 2502250 A 11/2013 WO WO 2011149544 A1* 12/2011 B64C 39/028 WO 2013123944 8/2013 WO 2014080388 4/2015 WO 2015135951 A1 9/2015	
		OTHER PUBLICATIONS	
		International Search Report and Written Opinion for International Application No. PCT/US2015/060023 dated Jan. 27, 2016.	
		* cited by examiner	




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

1

UNMANNED AERIAL VEHICLE CONFIGURATION FOR EXTENDED FLIGHT

BACKGROUND

Multi-propeller aerial vehicles (e.g., quad-copters, octo-copters) are becoming more common. All such vehicles require a body configuration that will support the separation of the multiple propellers, the control components, the power supply (e.g., battery), etc. However, there is a balance between weight and duration of flight. As the weight increases, for example to support more components, the flight duration will decrease.

BRIEF DESCRIPTION OF THE DRAWINGS

The detailed description is set forth with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different figures indicates similar or identical items or features.

FIG. 1A depicts a block diagram of a top-down view of an unmanned aerial vehicle, according to an implementation.

FIG. 1B depicts a block diagram of a top-down view of an unmanned aerial vehicle, according to an implementation.

FIG. 2 depicts another view of an unmanned aerial vehicle, according to an implementation.

FIG. 3 depicts a view of a power supply container of an unmanned aerial vehicle coupled to a frame of the unmanned aerial vehicle, according to an implementation.

FIG. 4 depicts a view of a power supply container of the unmanned aerial vehicle, according to an implementation.

FIG. 5 depicts a bottom view of a frame of the unmanned aerial vehicle, according to an implementation.

FIG. 6 depicts a lifting motor and lifting motor housing of the unmanned aerial vehicle, according to an implementation.

FIG. 7 depicts a lifting motor housing of the unmanned aerial vehicle, according to an implementation.

FIG. 8 is a block diagram of an illustrative implementation of a server system that may be used with various implementations.

FIG. 9 is a block diagram of a protection circuit, according to an implementation.

While implementations are described herein by way of example, those skilled in the art will recognize that the implementations are not limited to the examples or drawings described. It should be understood that the drawings and detailed description thereto are not intended to limit implementations to the particular form disclosed but, on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope as defined by the appended claims. The headings used herein are for organizational purposes only and are not meant to be used to limit the scope of the description or the claims. As used throughout this application, the word “may” is used in a permissive sense (i.e., meaning having the potential to), rather than the mandatory sense (i.e., meaning must). Similarly, the words “include,” “including,” and “includes” mean including, but not limited to. Additionally, as used herein, the term “coupled” may refer to two or more components connected together, whether that connection is permanent (e.g., welded) or temporary (e.g., bolted), direct or indirect (i.e., through an intermediary), mechanical, chemical, opti-

2

cal, or electrical. Furthermore, as used herein, “horizontal” flight refers to flight traveling in a direction substantially parallel to the ground (i.e., sea level), and that “vertical” flight refers to flight traveling substantially radially outward from the earth’s center. It should be understood by those having ordinary skill that trajectories may include components of both “horizontal” and “vertical” flight vectors.

DETAILED DESCRIPTION

This disclosure describes a configuration of an unmanned aerial vehicle (“UAV”) that will facilitate extended flight duration. The UAV may have any number of lifting motors. For example, the UAV may include four lifting motors (also known as a quad-copter), eight lifting motors (also known as an octo-copter), etc. Likewise, to improve the efficiency of horizontal flight, the UAV also includes a pushing motor and propeller assembly that is oriented at approximately ninety degrees to one or more of the lifting motors, the frame of the UAV and/or the motor arm of the UAV. When the UAV is moving horizontally, the pushing motor may be engaged and the pushing propeller will aid in the horizontal propulsion of the UAV. In some implementations, the rotational speed of the lifting motors may be reduced when the pushing motor is engaged, thereby improving efficiency and reducing power consumption of the UAV. Likewise, in some implementations, the UAV may include a wing to aid in the vertical lift of the UAV while the UAV is moving horizontally.

To further improve the efficiency of the UAV, in some implementations, the frame, motor arms, fuselage, wing, propellers, and/or other components of the UAV may be formed of one or more lightweight materials, such as carbon fiber, graphite, machined aluminum, titanium, fiberglass, etc. As discussed below, in some implementations, the frame may be formed of a thermally conductive material to enable use of the frame for heat dissipation.

Regardless of material, each of the motor arms, motor housing, and/or fuselage may be hollow, thereby reducing weight and providing a cavity through which one or more wires and/or cables may be passed and/or in which other components may be housed. For example, wires that connect the motors (e.g., lifting motors, pushing motors) to components located in or around the frame (e.g., electronic speed control (“ESC”)) may be passed through the inner portion of one or more of the motor housings and motor arms.

In some implementations, the UAV assembly may be configured so that the wires passing through the motor housings and/or motor arms have multiple junctions to enable easy disassembly and/or part replacements. For example, the motor wires may be configured with multiple separable junctions. For example, the motor wires may extend from the motor and have a separable junction at or near the end of the motor arm near where the motor is mounted, rather than having only a single junction where the motor wires connect to the ESC. By having a separable junction for the motor wires near the motor, the motor can be easily removed and replaced without having to disassemble any other components (e.g., fuselage, motor arms) of the UAV.

In some implementations, as discussed below, the fuselage may be aerodynamically designed to mount on an underneath or bottom side of the frame and be configured to contain components and power supplies of the UAV. For example, the fuselage may be formed from carbon fiber and mount to ridges or grooves in the frame, as illustrated and discussed below with respect to FIG. 1B.

FIG. 1A illustrates a block diagram of a top-down view of a UAV **100**, according to an implementation. As illustrated, the UAV **100** includes a frame **104**. The frame **104** or body of the UAV **100** may be formed of any suitable material, such as graphite, carbon fiber, aluminum, etc., or any combination thereof. In this example, the frame **104** of the UAV **100** is formed of machined aluminum in a rectangular shape. As discussed in further detail below with respect to FIG. 5, the underneath or bottom side of the frame **104** may be machined into a grid or hash pattern to reduce the weight of the frame, provide support, and provide locations for mounting other components of the UAV **100**.

Mounted to the frame are two motor arms **105-1**, **105-2**. In this example, the motor arms **105-1**, **105-2** are approximately the same length, are arranged substantially parallel to one another and perpendicular to the frame **104**. In other implementations, the motor arms **105** may be of different lengths (e.g., the front motor arm **105-1** may be shorter than the rear motor arm **105-2** and/or arranged at different locations on the UAV **100**).

Mounted to each end of the motor arms **105** are lifting motor housings **106-1**, **106-2**, **106-3**, **106-4**. The lifting motor housings **106** may be formed of any material, such as carbon fiber, aluminum, graphite, etc. In this example, the lifting motor housings **106** are aerodynamically shaped to reduce friction of air flow during horizontal flight of the UAV. The lifting motor housings **106** are discussed further below with respect to FIGS. 6-7.

Mounted inside each lifting motor housing **106** is a lifting motor **602** (not shown in FIG. 1A, but illustrated and discussed in FIG. 6). In one implementation, the lifting motors are mounted so that propeller shaft of the lifting motor that mounts to the propeller **102** is facing downward with respect to the UAV **100**. In other implementations, the lifting motors may be mounted with the propeller shaft facing upwards with respect to the UAV **100**. In still other implementations, one or more of the lifting motors may be mounted with the propeller shaft facing downward and one or more of the lifting motors may be mounted with the propeller shaft facing upward. In other implementations, the lifting motors may be mounted at other angles with respect to the frame of the UAV **100**. The lifting motors may be any form of motor capable of generating enough rotational speed with the propellers to lift the UAV **100** and any engaged payload, thereby enabling aerial transport of the payload. For example, the lifting motors may each be a FX-4006-13 740 kv multi-rotor motor, or a Tiger U-11 motor.

Mounted to each lifting motor is a lifting propeller **102-1**, **102-2**, **102-3**, **102-4**. The lifting propellers **102** may be any form of propeller (e.g., graphite, carbon fiber) and of a size sufficient to lift the UAV **100** and any payload engaged by the UAV **100** so that the UAV **100** can navigate through the air, for example, to deliver a payload to a delivery location. For example, the lifting propellers **102** may each be carbon fiber propellers having a dimension or diameter of twenty-nine inches. While the illustration of FIG. 1 shows the lifting propellers **102** all of a same size, in some implementations, one or more of the lifting propellers **102** may be different sizes and/or dimensions. Likewise, while this example includes four lifting propellers, in other implementations, more or fewer propellers may be utilized as lifting propellers. Likewise, in some implementations, the propellers may be positioned at different locations on the UAV **100**. In addition, alternative methods of propulsion may be utilized as “motors” in implementations described herein. For example, fans, jets, turbojets, turbo fans, jet engines, internal

combustion engines, and the like may be used (either with propellers or other devices) to provide thrust for the UAV.

Mounted to a first end, or front end, of the frame **104** of the UAV **100** is one or more antennas **108**. The antennas **108** may be used to transmit and/or receive wireless communications. For example, the antennas **108** may be utilized for Wi-Fi, satellite, near field communication (“NFC”), cellular communication, or any other form of wireless communication. Other components, such as cameras, time of flight sensors, distance determining elements, gimbals, etc. may likewise be mounted to the front of the frame **104** of the UAV **100**.

Mounted to a second end, or rear end, of the frame **104** of the UAV **100** is a pushing motor housing **111**, a pushing motor **110** and a pushing propeller **112**. While the term “pushing motor” is used, those having ordinary skill will appreciate that the position of motor **110** and antennas **108** may be reversed and reconfigured such that pushing motor **110** actually “pulls” the UAV **100** in a horizontal direction rather than pushes it. As such, as used herein, the term pushing motor shall be construed to include implementations configured for either “push” horizontal thrust or “pull” horizontal thrust. The pushing motor housing **111** may be aerodynamically shaped and configured to encase the pushing motor **110**. The pushing motor **110** and the pushing propeller **112** may be the same or different than the lifting motors and lifting propellers **102**. For example, in some implementations, the pushing motor **110** may be a Tiger U-8 motor and the pushing propeller **112** may have a dimension of eighteen inches. In some implementations, the pushing propeller may have a smaller dimension than the lifting propellers.

The pushing motor **110** and pushing propeller **112** may be oriented at approximately ninety degrees with respect to the frame **104** of the UAV **100** and utilized to increase the efficiency of flight that includes a horizontal component. For example, when the UAV **100** is traveling in a direction that includes a horizontal component, the pushing motor **110** may be engaged to provide horizontal thrust force via the pushing propeller to propel the UAV **100** horizontally. As a result, the speed and power utilized by the lifting motors may be reduced. Alternatively, in selected implementations, the pushing motor **110** may be oriented at an angle greater or less than ninety degrees with respect to frame **104** to provide a combination of pushing and lifting thrust.

One or more navigation components **114**, such as a global positioning receiver/transmitter, may also be mounted to the top of the frame **104**.

FIG. 1B depicts another block diagram of a top-down view of a UAV **100**, according to an implementation. In the example illustrated in FIG. 1B, the UAV **100** includes a wing **116** coupled to the frame of the UAV **100**. The wing may be formed of any suitable material such as, but not limited to, carbon fiber, aluminum, fabric, plastic, fiberglass, etc. The wing **116** may be coupled to the top of the frame **104** and positioned between the lifting motors **102**. In other implementations, the wing **116** may be positioned above the lifting motors and/or lifting propellers.

The wing is designed to have an airfoil shape to provide lift to the UAV **100** as the UAV **100** moves horizontally. In some implementations, utilizing the pushing motor **110** and pushing propeller **112** in conjunction with the wing **116**, when the UAV **100** is moving in a direction that includes a horizontal component, the rotational speed of the lifting motors and lifting propellers **102** may be reduced or eliminated as the wing **116** may provide lift and keep the UAV **100** airborne when thrust in a horizontal direction by the

5

pushing motor **110** and pushing propeller **112** is applied. In implementations where the wing includes flaps and/or ailerons, the pitch, yaw and roll of the UAV **100** may be controlled using the flaps and/or ailerons alone or in combination with the lifting motors and lifting propellers **102**. If the wing does not include flaps and/or ailerons, the lifting motors and lifting propellers **102** may be utilized to control the pitch, yaw, and roll of the UAV **100** during flight. In some implementations, the wing **116** may be configured to rotate or pivot about the frame **104** of the UAV to reduce drag when the UAV **100** is moving a direction that includes a vertical component.

FIG. 2 depicts another view of a UAV **100**, according to an implementation. As illustrated in FIG. 2, the UAV **100** may be configured for aerodynamics. For example, a fuselage **202** may be included on the UAV **100**, mounted to the frame **104** and extending downward and around many of the components of the UAV **100**. The fuselage **202** may be made of any suitable material(s) such as graphite, carbon fiber, aluminum, fiberglass, etc.

The fuselage **202** may encompass one or more power supply containers **204** (FIG. 3), a payload (not shown), and/or the components of the UAV control system **205**. The fuselage **202** may be coupled to the sides of the frame using one or more attachment mechanisms, such as screws, rivets, latches, quarter-turn fasteners, etc. In some implementations, the attachment mechanisms may be configured to enable easy removal and reattachment of the fuselage to facilitate power supply and/or power supply container replacement and maintenance to the UAV control system.

The payload, such as a package or item to be delivered to a user, may be configured to fit within the fuselage **202**, such as between two power supply containers, and be removably coupled to the frame **104** of the UAV. In other implementations, the payload may form a portion of the fuselage. For example, the fuselage may include a gap or opening and when the payload is coupled to the frame **104** of the UAV **100** the sides of the payload may complete the fuselage **202**.

As discussed above, and further illustrated in FIG. 2, the motor housings **106-1**, **106-2**, **106-3**, **106-4**, **111** have an aerodynamic shape to improve the overall aerodynamics of the UAV when the UAV is traveling horizontally. For example, the motor housings **106-1**, **106-2**, **106-3**, **106-4** for the lifting motors may be tapered toward the rear of the UAV **100**. Likewise, the motor housing **111** may be cone shaped with the narrow end of the cone directed toward the nose of the UAV **100**. In some implementations, the motor arms **105** may also have an aerodynamic form. For example, the motor arms **105** may be tapered toward the rear (e.g., “teardrop” shaped) of the UAV **100** and/or may have an airfoil design to provide additional lift to the UAV **100** when the UAV **100** moves horizontally.

The UAV may also include a vertical stabilizer **208** extending upward from the top of the frame **104**. The vertical stabilizer **208** may also include a rudder (not shown) that can be controlled by the UAV control system to adjust the yaw of the UAV. Likewise, in some implementations, the UAV **100** may also include horizontal stabilizers (not shown) which may include elevators controlled by the UAV control system to adjust the pitch of the UAV **100**.

FIG. 3 depicts a view of the UAV **100** with the fuselage **202** removed, exposing two power supply containers **204** of the UAV **100** coupled to the frame **104** of the UAV **100**, according to an implementation. As illustrated, the frame **104** may include one or more grooves or indents into which the power supply containers **204** may be positioned and attached to the frame **104**. In some implementations, the

6

grooves of the frame **104** may be angled and designed to provide a friction fit with the power supply containers. In other implementations, the power supply containers **204** may be removably mounted to the frame **104** using screws, rivets, quarter-turn fasteners, or other attachment mechanisms. In still other implementations, the power supply containers **204** may be permanently mounted to the frame **104** and/or formed as part of the frame **104**.

The power supply containers **204** may include one or more shelves **302** that may be positioned within the power supply container **204**. Referring to FIG. 4, the shelves **302-1**, **302-3** may be removable from the power supply containers **204**. For example, the shelves **302** may be designed to mount or fit in the power supply container **204** on rails **402**. The rails **402** and shelves **302** may be movable horizontally and/or vertically to facilitate placement of different size power supplies and/or other components. For example, as illustrated in FIGS. 3-4, the shelf **302-1** is supporting four power supplies **304-1**, **304-2**, **304-3**, **304-4**. The power supplies **304** may be in the form of battery power, solar power, gas power, super capacitor, fuel cell, alternative power generation source, or a combination thereof. For example, the power supplies **304** may each be a 6000 mAh lithium-ion polymer battery, polymer lithium ion (Li-poly, Li-Pol, LiPo, LIP, PLI or Lip) battery, etc.

The power supplies **304** may be individually removed and/or the entire shelf **302** may be removed with all of the supporting power supplies, as illustrated in FIG. 4. Likewise, the power supply containers **204** may include one or more openings (e.g., holes) on the sides of the power supply container to facilitate heat dissipation from the supported power supplies and/or other components.

The shelves of the power supply containers **204** may also support other components. For example, one or more components of the UAV control system **310** may be included on the shelves **302** of the power supply containers **204**, as illustrated in FIG. 3. Likewise, a power distribution unit to which the power supplies **304** are connected may be supported by one of the shelves of the power supply container. For example, the power distribution unit may be mounted to a shelf of the power supply container **204** and all of the power supplies may be coupled to the power distribution unit. The power distribution unit may then be coupled to the UAV control system **310** and/or other components of the UAV to provide power. In some implementations, the connection between the power distribution unit and the UAV control system may be a single coupling, such as a magnetic coupling, male/female connection, etc. to facilitate complete exchange of the power supply container **204**.

Referring to FIG. 9, in some implementations, the power distribution unit may include or be coupled with a protection circuit **900** that operates as both a spark suppression circuit to protect the UAV **100** when power is applied, and a shut-off or kill-switch circuit to shut down the UAV **100** by removing power. For example, the positive lead of the power supply(s) may be coupled to the protection circuit **900** and a positive node of each ESC component **904**. The second or negative node of each ESC component **904** is coupled to the protection circuit **900** which controls power to the ESC components **904**. Specifically, each second node of each ESC component **904** may be coupled to a respective drain of a transistor **902**, such as a metal-oxide-semiconductor field-effect transistor (MOSFET) transistor, of the protection circuit **900**. The source of each of the transistors **902** is coupled to ground and each gate of the transistors **902** is coupled to a drain of a transistor **906** and a resistor **908**. The resistor **908** is used to control the time it takes for each of the

transistors **902** to transition from an off state to an on state. The gate of transistor **906** is coupled to a second resistor **910** and an optical isolator **912**. When the optical isolator is off, the transistor **910** pulls-up transistor **906** into an on state by drawing voltage from the voltage divider **914**.

When the optical isolator is in an off state, the gate of transistor **906** is high (transistor **906** is on) which causes the transistors **902** to be in an off state and no power is applied to the ESCs. When the optical isolator **912** is activated, it causes the gate of transistor **906** to go low (transistor **904** is off), which, in turn, causes the gate node of each transistor **902** to charge through resistor **908** until the transistors **902** reach a threshold voltage for the transistor **902**. By altering the size of the transistor **906** and/or the size of the resistor **908**, the speed at which the transistors **902** transition from off, through their linear states and to their on states may be controlled, thereby providing spark suppression to protect the ESCs when power is first applied to the ESCs.

To control the timing of transition for transistors **902**, the resistor **908** and resistor **910** must be sufficiently large (e.g., 100,000-500,000 ohms) so as not to affect the voltage divider **914**. The resistor **910** is also larger than resistor **908**. In one implementation, resistor **910** is three times as large as resistor **908**. Likewise, the transistor **906** is generally smaller than transistors **902**.

The protection circuit **900** also operates as a shut-off or kill switch circuit by quickly removing power from the ESCs. The kill switch may be used, for example, when an operator loses control of the UAV. To quickly remove power, the optical isolator **912** is shut off, which causes the gate on transistor **906** to go high. When the gate on transistor **906** goes high, the gates of transistors **902** go low and the transistors **902** shut off, thereby removing power from the ESCs **904**. Likewise, a diode **916** may be coupled to the drain of each transistor **902** to receive current when power is removed, thereby protecting the transistors **902**.

The protection circuit **900** is designed so that, comparatively, power is applied to the ESCs in a controlled manner, thereby providing spark suppression, but removed quickly, thereby providing a shut-off or kill switch circuit.

FIG. 5 depicts an underneath or bottom view of a frame **104** of a UAV **100**, according to an implementation. As discussed above, the frame **104** may be formed of any suitable material, including but not limited to, carbon fiber, graphite, steel, machined aluminum, titanium, fiberglass and/or any other material or combination of materials. Likewise, the frame **104** may be machined to reduce the weight of the frame **104**. For example, as illustrated in FIG. 5, the underneath side of the frame **104** may be machined into a hash pattern. The groves or open spaces **502** in the hash pattern may be formed of a size sufficient to position one or more components of the UAV and/or components of the UAV control system. For example, the electronic speed control (ESC) components **504-1**, **504-2**, **504-3**, **504-4**, **504-5** may be positioned in the open spaces **502** of the frame. In some implementations, the frame **104** may also operate as a heat sink to dissipate heat from the components mounted to the frame.

For example, components of the UAV control system **610**, such as the ESC components **504** may be thermally coupled to the frame **104** using a thermal grease. The thermal grease, also known as thermal gel, thermal compound, thermal paste, heat paste, heat sink paste, heat transfer compound, heat transfer paste (HTP) or heat sink compound, is a viscous fluid substance which improves thermal transfer between the components and the frame **104**. The thermal grease may comprise a ceramic, metal, carbon, graphite,

liquid metal, phase change metal alloy (PCMA) and other similar materials. In other implementations thermally conductive pads may be used to provide thermal coupling between the frame **104** and the components. The frame **104** may also be used to dissipate heat from other components, such as the power supply.

FIG. 6 depicts a lifting motor **602** and a motor housing **106** of a UAV, according to an implementation. As discussed above, the motor housing **106** is mounted to the end of a motor arm **105** and houses a lifting motor **602**. In some implementations, the lifting motor **602** and motor housing **106** may be secured to the motor arm using screws. For example, mounting screws for the lifting motor may be threaded through the motor housing, through the motor arm and into the lifting motor to secure each component together.

In one implementation, the lifting motors are mounted so that propeller shaft **604** of the lifting motor that mounts to the propeller **102** is facing downward with respect to the UAV. In other implementations, the lifting motor may be mounted with the propeller shaft **604** facing upwards with respect to the UAV. The lifting motors **602** may be any form of motor capable of generating enough rotational speed with the propellers to lift the UAV and any engaged payload, thereby enabling aerial transport of the payload. For example, the lifting motors **602** may each be a FX-4006-13 740 kv multi-rotor motor, or a Tiger U-11 motor.

FIG. 7 depicts a lifting motor housing **106** of a UAV with the lifting motor removed, according to an implementation. As discussed above, the lifting motor housing **106** may be positioned on an end of the motor arm **105** and secured to the motor arm **105** using screws of the lifting motor. For example, four screws may be threaded through a top side (not shown) of the motor housing **106**, through screw holes (not shown) in the motor arm **105** and through the lower screw holes **702-1**, **702-2**, **702-3**, **702-4** of the lower side of the motor housing. The screws may then be screwed into the lifting motor to secure each of the components together. The wires of the lifting motor may be routed through the opening **704** in the motor housing **106** and through the internal cavity of the motor arm **105**. Alternatively, the wires of the lifting motor may be routed through the opening **705** in the back of the motor housing **106** and through the internal cavity of the motor arm **105**. In still another implementation, the wires may be affixed to an external portion of the motor arm **105**.

FIG. 8 is a block diagram illustrating an example UAV control system **610** of the UAV **100**. In various examples, the block diagram may be illustrative of one or more aspects of the UAV control system **610** that may be used to implement the various systems and methods discussed herein and/or to control operation of the UAV **100**. In the illustrated implementation, the UAV control system **610** includes one or more processors **802**, coupled to a memory, e.g., a non-transitory computer readable storage medium **820**, via an input/output (I/O) interface **810**. The UAV control system **610** may also include electronic speed controls **804** (ESCs), power supply modules **806** and/or a navigation system **808**. The UAV control system **610** further includes a payload engagement controller **812**, a network interface **816**, and one or more input/output devices **818**.

In various implementations, the UAV control system **610** may be a uniprocessor system including one processor **802**, or a multiprocessor system including several processors **802** (e.g., two, four, eight, or another suitable number). The processor(s) **802** may be any suitable processor capable of executing instructions. For example, in various implementations, the processor(s) **802** may be general-purpose or embedded processors implementing any of a variety of

instruction set architectures (ISAs), such as the x86, PowerPC, SPARC, or MIPS ISAs, or any other suitable ISA. In multiprocessor systems, each processor(s) **802** may commonly, but not necessarily, implement the same ISA.

The non-transitory computer readable storage medium **820** may be configured to store executable instructions, data, flight paths, flight control parameters, component adjustment information, center of gravity information, and/or data items accessible by the processor(s) **802**. In various implementations, the non-transitory computer readable storage medium **820** may be implemented using any suitable memory technology, such as static random access memory (SRAM), synchronous dynamic RAM (SDRAM), nonvolatile/Flash-type memory, or any other type of memory. In the illustrated implementation, program instructions and data implementing desired functions, such as those described herein, are shown stored within the non-transitory computer readable storage medium **820** as program instructions **822**, data storage **824** and flight controls **826**, respectively. In other implementations, program instructions, data and/or flight controls may be received, sent or stored upon different types of computer-accessible media, such as non-transitory media, or on similar media separate from the non-transitory computer readable storage medium **820** or the UAV control system **610**. Generally speaking, a non-transitory, computer readable storage medium may include storage media or memory media such as magnetic or optical media, e.g., disk or CD/DVD-ROM, coupled to the UAV control system **610** via the I/O interface **810**. Program instructions and data stored via a non-transitory computer readable medium may be transmitted by transmission media or signals such as electrical, electromagnetic, or digital signals, which may be conveyed via a communication medium such as a network and/or a wireless link, such as may be implemented via the network interface **816**.

In one implementation, the I/O interface **810** may be configured to coordinate I/O traffic between the processor(s) **802**, the non-transitory computer readable storage medium **820**, and any peripheral devices, the network interface or other peripheral interfaces, such as input/output devices **818**. In some implementations, the I/O interface **810** may perform any necessary protocol, timing or other data transformations to convert data signals from one component (e.g., non-transitory computer readable storage medium **820**) into a format suitable for use by another component (e.g., processor(s) **802**). In some implementations, the I/O interface **810** may include support for devices attached through various types of peripheral buses, such as a variant of the Peripheral Component Interconnect (PCI) bus standard or the Universal Serial Bus (USB) standard, for example. In some implementations, the function of the I/O interface **810** may be split into two or more separate components, such as a north bridge and a south bridge, for example. Also, in some implementations, some or all of the functionality of the I/O interface **810**, such as an interface to the non-transitory computer readable storage medium **820**, may be incorporated directly into the processor(s) **802**.

The ESCs **804** communicate with the navigation system **808** and adjust the rotational speed of each lifting motor and/or the pushing motor to stabilize the UAV and guide the UAV along a determined flight path.

The navigation system **808** may include a global positioning system (GPS), indoor positioning system (IPS), or other similar system and/or sensors that can be used to navigate the UAV **100** to and/or from a location. The

payload engagement controller **812** communicates with the actuator(s) or motor(s) (e.g., a servo motor) used to engage and/or disengage items.

The network interface **816** may be configured to allow data to be exchanged between the UAV control system **610**, other devices attached to a network, such as other computer systems (e.g., remote computing resources), and/or with UAV control systems of other UAVs. For example, the network interface **816** may enable wireless communication between the UAV **100** and a UAV control system that is implemented on one or more remote computing resources. For wireless communication, an antenna of an UAV or other communication components may be utilized. As another example, the network interface **816** may enable wireless communication between numerous UAVs. In various implementations, the network interface **816** may support communication via wireless general data networks, such as a Wi-Fi network. For example, the network interface **816** may support communication via telecommunications networks, such as cellular communication networks, satellite networks, and the like.

Input/output devices **818** may, in some implementations, include one or more displays, imaging devices, thermal sensors, infrared sensors, time of flight sensors, accelerometers, pressure sensors, weather sensors, etc. Multiple input/output devices **818** may be present and controlled by the UAV control system **610**. One or more of these sensors may be utilized to assist in landing as well as to avoid obstacles during flight.

As shown in FIG. **8**, the memory may include program instructions **822**, which may be configured to implement the example routines and/or sub-routines described herein. The data storage **824** may include various data stores for maintaining data items that may be provided for determining flight paths, landing, identifying locations for disengaging items, etc. In various implementations, the parameter values and other data illustrated herein as being included in one or more data stores may be combined with other information not described or may be partitioned differently into more, fewer, or different data structures. In some implementations, data stores may be physically located in one memory or may be distributed among two or more memories.

Those skilled in the art will appreciate that the UAV control system **610** is merely illustrative and is not intended to limit the scope of the present disclosure. In particular, the computing system and devices may include any combination of hardware or software that can perform the indicated functions. The UAV control system **610** may also be connected to other devices that are not illustrated, or instead may operate as a stand-alone system. In addition, the functionality provided by the illustrated components may, in some implementations, be combined in fewer components or distributed in additional components. Similarly, in some implementations, the functionality of some of the illustrated components may not be provided and/or other additional functionality may be available.

Those skilled in the art will also appreciate that, while various items are illustrated as being stored in memory or storage while being used, these items or portions of them may be transferred between memory and other storage devices for purposes of memory management and data integrity. Alternatively, in other implementations, some or all of the software components may execute in memory on another device and communicate with the illustrated UAV control system **610**. Some or all of the system components or data structures may also be stored (e.g., as instructions or structured data) on a non-transitory, computer-accessible

11

medium or a portable article to be read by an appropriate drive, various examples of which are described herein. In some implementations, instructions stored on a computer-accessible medium separate from the UAV control system 610 may be transmitted to the UAV control system 610 via transmission media or signals such as electrical, electromagnetic, or digital signals, conveyed via a communication medium such as a wireless link. Various implementations may further include receiving, sending or storing instructions and/or data implemented in accordance with the foregoing description upon a computer-accessible medium. Accordingly, the techniques described herein may be practiced with other UAV control system configurations.

Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as exemplary forms of implementing the claims.

What is claimed is:

1. An unmanned aerial vehicle (UAV), comprising:

a frame;

a first lifting motor coupled to the frame;

a second lifting motor coupled to the frame;

a pushing motor coupled to the frame;

a fuselage coupled to the frame and extending downward from the frame, wherein the fuselage encompasses a plurality of components of the UAV and is configured to reduce aerodynamic resistance of the UAV when the UAV is flown in a direction including a horizontal component;

a first power supply container coupled to the frame at a first position;

a second power supply container coupled to the frame at a second position; and

an unmanned aerial vehicle control system configured to send control signals to the first lifting motor, the second lifting motor and the pushing motor in response to signals received from a remote location; and wherein:

the frame includes a payload receiving area between the first power supply container and the second power supply container that receives a payload;

the fuselage includes a downward-facing gap or opening within which the payload, when received, is at least partially contained; and

the payload includes an item to be delivered to a user.

2. The UAV of claim 1, further comprising:

a wing coupled to the frame, wherein the wing is configured to provide lift as the UAV is flown in a direction including a horizontal component.

3. The UAV of claim 1, further comprising:

a first motor housing coupled to the frame and the first lifting motor, the first motor housing having a tapered shape to reduce an aerodynamic resistance of the first lifting motor.

4. The UAV of claim 1, further comprising:

a first lifting propeller coupled to the first lifting motor; and

a first pushing propeller coupled to the pushing motor.

5. The UAV of claim 4, wherein:

the first lifting propeller has a first dimension;

the first pushing propeller has a second dimension; and the first dimension is larger than the second dimension.

6. The UAV of claim 1, wherein:

12

the pushing motor is a different motor size than at least one of the first lifting motor or the second lifting motor.

7. The UAV of claim 1, wherein:

the frame is configured to dissipate heat from the first power supply container and the second power supply container; and

at least one component of the unmanned aerial vehicle control system is thermally coupled to the frame with at least one of a thermal grease or thermal pad positioned between the at least one component and the frame such that the thermal grease or the thermal pad improves a thermal transfer between the at least one component and the frame.

8. The UAV of claim 1, wherein the unmanned aerial vehicle control system is further configured to send control signals to at least one of the first lifting motor, the second lifting motor, or the pushing motor in response to signals received from a device of the UAV.

9. An unmanned aerial vehicle (UAV), comprising:

a frame;

a first motor arm having a first end and a second end, the first motor arm coupled to the frame;

a second motor arm having a third end and a fourth end, the second motor arm coupled to the frame;

a first lifting motor coupled to the first end of the first motor arm;

a second lifting motor coupled to the second end of the first motor arm;

a third lifting motor coupled to the third end of the second motor arm;

a fourth lifting motor coupled to the fourth end of the second motor arm;

a pushing motor coupled to a fifth end of the frame and configured to provide horizontal propulsion to the UAV;

a first power supply container coupled to the frame at a first position;

a second power supply container coupled to the frame at a second position; and

an unmanned aerial vehicle control system for controlling a rotational speed of at least one of the first lifting motor, the second lifting motor, the third lifting motor, the fourth lifting motor or the pushing motor, wherein: the frame includes a payload receiving area including a downward-facing gap or opening within which a payload, when received, is at least partially contained, the payload receiving area being positioned between the first power supply container and the second power supply container; and

the payload includes an item to be delivered to a user.

10. The UAV of claim 9,

wherein the first power supply container and the second power supply container are each removably coupled to the frame and configured to house at least one power supply for providing power to the UAV.

11. The UAV of claim 10, further comprising:

a fuselage coupled to the frame and extending downward from the frame, wherein;

the fuselage encompasses at least a portion of the first power supply container and the second power supply container; and

the fuselage is configured to reduce aerodynamic resistance of the UAV when flown in a direction including a horizontal component.

12. The UAV of claim 10, wherein the first power supply container and the second power supply container each

13

includes a removable shelf configured to support at least one power supply or a component of a control system of the UAV.

13. The UAV of claim 9, further comprising:

a wing coupled to the frame, wherein the wing is configured to provide lift as the UAV is flown in a direction including a horizontal component.

14. The UAV of claim 9, further comprising:

a fuselage coupled to the frame and extending downward from the frame, wherein the fuselage encompasses a plurality of components of the UAV and is configured to reduce aerodynamic resistance of the UAV when the UAV is flown in a direction including a horizontal component; and

the fuselage includes the downward-facing gap or opening within which the payload, when received, is at least partially contained.

15. The UAV of claim 9, further comprising:

a first lifting motor housing coupled to the first end of the first motor arm and formed around the first lifting motor, the first lifting motor housing having a tapered shape to reduce an aerodynamic resistance of the first lifting motor.

16. An unmanned aerial vehicle (UAV), comprising:

a frame;

a first lifting motor coupled to the frame;

a pushing motor coupled to the frame;

a first power supply container coupled to the frame at a first position;

a second power supply container coupled to the frame at a second position;

a wing coupled to the frame and configured to provide lift when the UAV is moving in a direction that includes a horizontal component;

a fuselage coupled to the frame and extending downward from the frame, wherein the fuselage encompasses a plurality of components of the UAV and is configured

14

to reduce aerodynamic resistance of the UAV when the UAV is flown in a direction including a horizontal component; and

wherein:

the frame includes a payload receiving area between the first power supply container and the second power supply container that receives a payload;

the fuselage includes a downward-facing gap or opening within which the payload, when received, is at least partially contained; and

the payload includes an item to be delivered to a user.

17. The UAV of claim 16, wherein the wing is positioned between the first lifting motor and a second lifting motor.

18. The UAV of claim 16, further comprising:

an unmanned aerial vehicle control system; and

wherein:

at least one component of the unmanned aerial vehicle control system is thermally coupled to the frame with at least one of a thermal grease or thermal pad positioned between the at least one component and the frame such that the thermal grease or the thermal pad improves a thermal transfer between the at least one component and the frame; and

the frame dissipates heat generated by the at least one component of the unmanned aerial vehicle control system.

19. The UAV of claim 18, wherein the at least one component includes an electronic speed control component.

20. The UAV of claim 16, further comprising:

a protection circuit configured to operate as a spark suppression circuit for protecting at least a portion of the UAV when power is applied and a kill switch for removing power from at least a portion of the UAV.

21. The UAV of claim 16, further comprising:

a payload engagement controller that communicates with at least one component of the UAV to control an engagement and disengagement of the payload.

* * * * *