



US009892322B1

(12) **United States Patent**
Beard et al.

(10) **Patent No.:** **US 9,892,322 B1**
(45) **Date of Patent:** **Feb. 13, 2018**

(54) **CASCADE RECOGNITION FOR PERSONAL TRACKING VIA UNMANNED AERIAL VEHICLE (UAV)**

(2013.01); **G06K 9/4652** (2013.01); **G06K 9/6201** (2013.01); **G06T 7/20** (2013.01); **H04N 5/44** (2013.01); **H04N 7/183** (2013.01); **B64C 2201/024** (2013.01); **B64C 2201/127** (2013.01); **B64C 2201/14** (2013.01)

(71) Applicant: **Trace Live Network Inc.**, Calgary (CA)

(58) **Field of Classification Search**
None
See application file for complete search history.

(72) Inventors: **Paul Beard**, Bigfork, MT (US); **Cameron Chell**, Calgary (CA); **Jamie Clarke**, Calgary (CA); **Craig McDermott**, Cedar Rapids, IA (US); **Erika Racicot**, Calgary (CA); **Paul Readwin**, Calgary (CA)

(56) **References Cited**
U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

8,908,573 B1 * 12/2014 Wang H04L 5/26 370/280
2007/0230742 A1 * 10/2007 Burns G06T 7/207 382/103

(21) Appl. No.: **15/651,672**

(Continued)

(22) Filed: **Jul. 17, 2017**

Primary Examiner — Heather Jones
(74) *Attorney, Agent, or Firm* — Suiter Swantz pc llo

Related U.S. Application Data

(63) Continuation of application No. 14/642,370, filed on Mar. 9, 2015, now Pat. No. 9,710,709.
(Continued)

(51) **Int. Cl.**
H04N 7/18 (2006.01)
H04N 5/225 (2006.01)
G06K 9/00 (2006.01)
B64C 39/02 (2006.01)
B64D 47/08 (2006.01)
G06F 3/044 (2006.01)
G06K 9/46 (2006.01)
G06T 7/20 (2017.01)
H04N 5/44 (2011.01)


(Continued)

(52) **U.S. Cl.**
CPC **G06K 9/0063** (2013.01); **B64C 39/024** (2013.01); **B64D 47/08** (2013.01); **G06F 3/044** (2013.01); **G06F 17/3028** (2013.01); **G06K 9/00476** (2013.01); **G06K 9/46**

(57) **ABSTRACT**

Systems and methods for tracking a subject using an unmanned aerial vehicle (UAV) are disclosed. An unmanned aerial vehicle (UAV) includes an onboard camera to capture/stream multiple images. An onboard visual recognition module isolates image elements by analyzing the captured images, and determines whether the image elements correspond or do not correspond to the subject. Current image elements corresponding to a subject are stored in a positive database, and non-corresponding current image elements are stored in a negative database. An onboard subject tracking module defines the chosen subject, determines attributes of the subject based on comparisons of image elements, and follows the subject by directing the attitude control system to adjust the velocity and orientation of the UAV based on the determined attributes.

13 Claims, 9 Drawing Sheets



Related U.S. Application Data

(60) Provisional application No. 61/949,801, filed on Mar. 7, 2014.

(51) **Int. Cl.**

G06F 17/30 (2006.01)

G06K 9/62 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2008/0085048	A1 *	4/2008	Venetsky	G06K 9/00355 382/153
2009/0222149	A1 *	9/2009	Murray	A63H 30/04 701/2
2010/0084513	A1 *	4/2010	Gariepy	B64C 39/024 244/190
2017/0235308	A1 *	8/2017	Gordon	G05D 1/0088 701/2

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 6C

1

CASCADE RECOGNITION FOR PERSONAL TRACKING VIA UNMANNED AERIAL VEHICLE (UAV)

For purposes of the USPTO extra-statutory requirements, the present application constitutes a continuation of the United States patent application entitled CASCADE RECOGNITION FOR PERSONAL TRACKING VIA UNMANNED AERIAL VEHICLE (UAV), naming Paul Beard, Cameron Chell, Jamie Clarke, Craig McDermott, Erika Racicot, and Paul Readwin as inventors, filed Mar. 9, 2015, application Ser. No. 14/642,370, which application is currently co-pending.

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority under 35 U.S.C. § 119(e) to provisional patent application U.S. Ser. No. 61/949,801 filed on Mar. 7, 2014. Said application is herein incorporated by reference in its entirety.

TECHNICAL FIELD

Embodiments of the present invention relate generally to unmanned aerial vehicles (UAVs) and particularly to systems and methods for selecting and following a moving subject individual or object while photographing the subject via onboard camera.

BACKGROUND

Live broadcasting of competitions or athletic events in real time or near real time is generally accomplished with large camera crews and multiple camera operators, each having their own video/audio equipment. Stationary mounts, helicopters, blimps, and other bulky vehicles have also been used. The space and time necessary to coordinate the large crews and bulky vehicles can be economically and logistically taxing. Additionally, for individuals or small, informal groups interested in capturing video and/or images from inaccessible locations and streaming these images to one or more remote viewers in real time or near real time, professional-grade live broadcasting equipment of this nature is not feasible. Therefore, a smaller, less logistically demanding, and economically feasible alternative for live broadcasting is desirable.

SUMMARY

It is to be understood that both the foregoing general description and the following detailed description are only for illustrative and explanatory purposes, and are not necessarily restrictive of the invention as claimed. The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and together with the general description, serve to explain the principles of the invention.

One or more cascade recognition systems for acquiring and following a subject with an unmanned aerial vehicle (UAV) are disclosed. In one embodiment, the system includes one or more cameras fixed to the UAV and configured to capture one or more images. In one embodiment, the system includes an attitude control system configured to adjust one or more rotor speeds of the UAV. In one embodiment, the cascade recognition system includes a visual recognition module configured to: isolate one or more

2

current image elements by analyzing the one or more images captured; determine whether the one or more current image elements is a positive image element corresponding to the subject or a negative image element not corresponding to the subject; store the one or more positive image elements in a positive database; and store the one or more negative image elements in a negative database. In one embodiment, the cascade recognition system includes a subject tracking module coupled to the visual recognition module and to the attitude control system of the UAV and configured to: define a subject by capturing one or more reference images via at least one camera of the UAV; determine at least one attribute of the subject by performing a comparison of at least one current image element to a positive image element, a negative image element, or a reference image element; and direct the attitude control system to adjust a rotor speed of the UAV based on the at least one attribute of the subject.

One or more unmanned aerial vehicles (UAV) for acquiring and following a subject, are disclosed. In one embodiment, the UAV includes an attitude control system configured to adjust one or more rotor speeds of the UAV (thereby adjusting a velocity of the UAV, a heading of the UAV, or an orientation of the UAV). In one embodiment, the UAV includes one or more cameras configured to capture one or more images. In one embodiment, the UAV includes one or more data storage units. In one embodiment, the UAV includes one or more processors coupled to the one or more cameras, one or more data storage units, and to the attitude control system, the one or more processors are configured to: isolate one or more current image elements from the one or more captured images; designate one or more image elements as a positive image element corresponding to the subject, a negative image element not corresponding to the subject, or a reference image element corresponding to the subject; compare one or more current image elements to at least one of a positive image element stored in a first database, a negative image element stored in a negative database, and a reference image element stored in a third database; determine one or more attributes of the subject based on at least the comparisons; and direct the attitude control system to adjust at least one rotor speed of the UAV based on the one or more attributes of the subject.

One or more methods of acquiring and following a subject via an unmanned aerial vehicle (UAV) are disclosed. In one embodiment, the method includes defining a subject by capturing at least one reference image via at least one camera of the UAV. In one embodiment, the method includes extracting at least one current image element from the at least one captured image. In one embodiment, the method includes determining whether the at least one current image element is a positive image element corresponding to the subject or a negative image element not corresponding to the subject. In one embodiment, the method includes storing the at least one positive image element in a positive database. In one embodiment, the method includes storing the at least one negative image element in a negative database. In one embodiment, the method includes determining at least one attribute of the subject by performing a comparison of the at least one current image element to at least one of a positive image element, a negative image element, and a reference image element.

BRIEF DESCRIPTION OF THE FIGURES

Embodiments of the presently disclosed invention may be better understood by those skilled in the art by reference to the accompanying figures in which:

FIG. 1A illustrates a schematic diagram of a system for acquiring and following a subject with an unmanned aerial vehicle (UAV), according to embodiments of this disclosure;

FIG. 1B illustrates a schematic diagram of a system for acquiring and following a subject with one or more UAVs using multiple storage databases and a base station, according to embodiments of this disclosure;

FIG. 1C illustrates a schematic diagram of a UAV in a system for acquiring and following a subject, according to embodiments of this disclosure;

FIG. 2 is a process flow diagram of a method of acquiring and following a subject with an UAV, according to embodiments of this disclosure;

FIGS. 3A-3B illustrate respective views of an image tracking/analysis process of the UAV utilizing macro-scaled visual recognition techniques to acquire and center one or more images of a subject to track the subject, according to embodiments of this disclosure;

FIGS. 4A-4B illustrate respective views of an image tracking/analysis process of an UAV utilizing medium-scaled visual recognition techniques to acquire one or more images of a subject to track the subject, according to embodiments of this disclosure;

FIGS. 5A-5C illustrate respective views of an image tracking/analysis process of an UAV utilizing Haar-like features, Viola-Jones facial recognition, and infrared/color pattern detection techniques to acquire one or more images of a subject to track the subject, according to embodiments of this disclosure; and

FIGS. 6A-6C illustrate respective side views of an UAV adjusting one or more rotor speeds of the UAV due to one or more command gestures given by a subject, according to embodiments of this disclosure.

DETAILED DESCRIPTION

Features of the invention in its various embodiments are exemplified by the following descriptions with reference to the accompanying drawings, which describe the invention with further detail. These drawings depict only selected embodiments of the invention, and should not be considered to limit its scope in any way.

Embodiments of this disclosure generally relate to personal, visual recognition and tracking and more particularly to a system, apparatus, and method for tracking with an Unmanned Aerial Vehicle (UAV). In operation, embodiments of this disclosure form an integrated system utilizing a UAV, a camera, a visual recognition module, and a subject tracking module, to select and follow a selected subject (ex.—targeted individual). In this regard, the UAV captures a series of pictures of multiple subjects, any of which may be tracked. The series of pictures are separated into images with distinct image elements utilizing cascading visual recognition techniques and/or Haar-like features, Viola-Jones facial recognition and infrared, color pattern detection. The UAV stores the images and distinct image elements in one or more databases. A comparison is made between distinct image elements and one or more stored/known image elements. Based on the comparison the UAV may be directed to alter its position or heading to follow an identified subject (e.g., keep the subject centrally framed).

Referring generally to FIG. 1A, a cascade recognition system **100** for acquiring and following a subject with an unmanned aerial vehicle (UAV) comprises the UAV **102** and one or more cameras **106**. Applicant notes that for purposes of simplicity the camera **106**, the UAV **102**, and the other components of the system **100** have been generally depicted

in a simplified schematic diagram. This depiction, including the components and geometrical configuration, is not limiting and is provided for illustrative purposes only. Applicant further notes that the UAV **102**, the camera **106**, and the other components of the system **100** may include any number of elements to carry out the image capturing and tracking processes contemplated in this disclosure. For example, the camera **106** may include, but is not limited to, one or more optics, one or more apertures, one or more image sensors, and one or more adjustable mounts. By way of another example, the UAV **102** may include, but is not limited to, a different rotor configuration (e.g., three, six, or eight rotors instead of the four depicted in FIGS. 6A-6C), an audio tracking system, and one or more processors.

In one embodiment, the system **100** includes one or more processors (not shown). In one embodiment, the one or more processors are configured to execute and implement one or more instructions or sets of instructions. In one embodiment, the one or more instructions executed and implemented are stored in one or more memories (e.g., non-transitory memory) (not shown).

In one embodiment, referring generally to FIG. 1A, the one or more memories are separated into one or more databases. For example, the one or more memories may be separated into a positive database **136** for storing one or more positive image elements associated with a first subject to be tracked, a negative database **138a** for storing one or more negative image elements that are not associated with a subject to be tracked, and a third database **138b** for storing one or more reference image elements.

In one embodiment, the one or more memories are separated according to their content. For example, the one or more memories may be separated into a positive database **136** for storing one or more image elements associated with a subject to be tracked, and a negative database **138a** for storing one or more image elements that are not associated with the subject being tracked. Applicant notes that the general configuration and geometrical orientation of the one or more memories or the one or more databases is not limiting. Applicant further notes that other configurations will be apparent to those skilled in the art.

In one embodiment, the system **100** includes one or more cameras **106** fixed to the UAV **102** and operably/communicatively coupled to the one or more processors. In one embodiment, the one or more cameras **106** are configured to capture one or more images for visual recognition and analysis processes executed by the one or more processors. In one embodiment the images captured correspond to one or more subjects to be tracked. In one embodiment, the one or more subjects to be tracked (e.g., subject **122**) is a human, such as a skier. In this regard, the subject is referred to as a subject (e.g., subject **122**).

In one embodiment, referring to FIG. 1A, the one or more instructions executed and implemented by the one or more processors of system **100** are separated into multiple processes or sets of instructions, and further separated into multiple sub-process or sub-sets of instructions. For example, the one or more instructions when executed and implemented by the one or more processors may cause the one or more processors to: execute the capturing of one or more images using camera **106**; execute an image compression and storage process **110**; execute an image analysis process and a subject acquisition sub-process; execute a subject profile matching process, an image element classification sub-process, and a subject and environment distinguishing sub-process; execute a subject tracking process **124**; determine an attitude of the UAV and an orientation

5

(e.g., direction of travel **128**) of the subject **122**; and adjust the attitude control system **126** such that one or more of the orientation and the direction of travel **132** of the UAV matches the orientation or direction of travel **128** of the subject **122**.

In one embodiment, the cascade recognition system **100** includes a visual recognition module **108**. In one embodiment, the visual recognition module **108** is operably/communicatively coupled to one or more cameras **106**. In one embodiment, the visual recognition module **108** further comprises the image analysis process, the subject acquisition sub-process, the subject profile matching process, and the image element classification sub-process. For example, referring to FIG. 1A, the visual recognition module **108** may be configured to: isolate one or more current image elements of a subject by analyzing the one or more images; determine **140** whether the one or more current image elements is a positive current image element corresponding to a subject, or determine **142** whether the one or more current image elements is a negative current image element not corresponding to the subject; store the one or more positive current image elements in a positive database **136**; and store the one or more negative current image elements in a negative database **138a**.

In one embodiment, the cascade recognition system **100** includes a subject tracking module **124** operably/communicatively coupled to the visual recognition module **108** and to the attitude control system **126** of the UAV **102**. In one embodiment, such an operative/communicative coupling configures the UAV **102** to: define a subject (e.g., subject **122**) by capturing at least one reference image via at least one camera **106** of the UAV; designate one or more first images as a reference image, and the associated image elements as reference image elements; determine **146** at least one attribute of the subject by performing a comparison of at least one current image element to at least one of a positive image element, a negative image element, and a reference image element; and adjust a rotor speed of at least one rotor of the UAV (e.g., direct the attitude control system **126** and coupled motor drivers **170**/UAV rotors **172**) based on the at least one attribute of the subject.

In one embodiment, the visual recognition module **108** comprises a subject acquisition module, or a subject acquisition process. In this regard, the visual recognition module **108** utilizes both macro-scaled and micro-scaled visual recognition techniques/algorithms to determine whether one or more reference image elements is a positive reference image element corresponding to the subject **122** or a negative reference image element not corresponding to the subject, populating negative database **138b** accordingly.

In one embodiment, referring to FIG. 1B, the system **100** includes a base station **150** configured to receive and process image data from multiple UAVs. For example, UAV **102**, UAV **154**, UAV **156**, and UAV **158** may capture images through onboard cameras and perform some image processing functions or associated subprocesses (e.g., at least one of: selecting a subject (e.g., potential subject **122**); visual recognition **108**; image compression and storage **110**; and subject tracking **124**). In this regard, each individual UAV may be further configured to transmit streaming images, processed images, and/or image elements via wireless device **152** to the base station **150**.

In one embodiment, the base station **150** conducts the image processing functions and associated subprocesses for each UAV (e.g., at least one of: selecting a subject (e.g., potential subject **122**); visual recognition **108**; image compression and storage **110**; and subject tracking **124**). The

6

base station **150** may be further configured to communicate with the individual attitude systems **126** of multiple UAVs, issuing commands to one or more UAVs to acquire or track either a single subject **122** or multiple subjects.

In one embodiment, referring to FIGS. 1A and 1C, the UAV **102** of system **100** includes an airframe **104**. In one embodiment, the system **100** includes a UAV with one or more rotors **172** with one or more motor drivers **170** (ex.—electronic speed controls) fixed to the airframe **104**, the one or more rotors **172** configured to rotate at one or more rotor speeds. For example, the UAV **102** may be a rotorcraft incorporating any appropriate number of rotors (e.g., a tri-copter, quadcopter, hexacopter, or octocopter).

In one embodiment, the UAV **102** of system **100** includes a power source. For example, the power source may be battery **160**. In one embodiment, the UAV **102** includes a power controller **162**. In one embodiment, the UAV **102** includes one or more sensors for tracking the position of the UAV **102**. For example, the one or more sensors may include attitude sensors **164**. In one embodiment, the UAV includes one or more sensors for tracking the position of a subject. For example, the one or more sensors may include CMOS image sensor **166**.

In one embodiment, the UAV **102** includes one or more cameras **106** operably connected to one or more processors, which are configured to move according to one or more executed instructions or sets of executed instructions. For example, the one or more cameras **106** may include one or more camera mounts that move in multiple directions upon receiving one or more signals. In one embodiment, one or more components of the one or more cameras **106** are configured to move according to one or more executed instructions or sets of executed instructions. For example, one or more apertures may increase or decrease in size upon receiving one or more signals.

In one embodiment, the one or more cameras **106** further comprise an image stabilization module (e.g., set of programmed instructions to conduct image stabilization); one or more memory controllers; a high-speed memory (e.g., partitioned into separate databases); a graphics engine; one or more outputs, including, but not limited to, a display output and an audio output; an image/video DSP; one or more devices configured to execute wireless transmission, including, but not limited to, an Ethernet device; and one or more devices for receiving and executing general purpose input and output (I/O) commands. In one embodiment, the one or more cameras **106** may be configured to receive and/or communicate with one or more external memory devices. For example, the one or more cameras **106** may include a slot for receiving and/or communicating with an external SDXC card **174** or other external flash memory devices.

In one embodiment, the high-speed memory includes one or more types of memory **168**. For example, the one or more types of memory may include one or more solid state drives (SSD) (e.g., one or more stacked NAND flash chips), and one or more random access memories (RAM) (e.g., DDR3 SDRAM).

In one embodiment, the UAV **102** of system **100** includes a wireless transceiver for sending and receiving one or more wireless signals. For example, UAV **102** may include Wi-Fi transceiver **152**.

The embodiments of system **100** and UAV **102** (e.g., illustrated in FIGS. 1A-1C) may be further configured as described herein. In addition, system **100** and UAV **102** may be configured to perform any other step(s) of any of the method embodiment(s) described herein. The following method embodiments relate to visual recognition and subject

tracking using one or more UAVs. It is generally recognized that system **100** and UAV **102** are suitable for implementing the visual recognition and subject tracking steps of the following embodiments. It is noted, however, the methods described below are not limited to the architectures of system **100** or UAV **102**.

FIG. 2 illustrates a flow diagram depicting a method **200** of acquiring and following a subject with an unmanned aerial vehicle (UAV), in accordance with one or more embodiments of the present disclosure.

In one embodiment, the cascade recognition system **100** conducts a preparatory step of generating one or more subject profiles, each profile corresponding to a subject **122**. In one embodiment, the preparatory step comprises gathering characteristic information for each of a group of potential subjects. In this regard, the characteristic information will be used by the visual recognition module **108** to identify positive image elements corresponding to the subject **122**. For example, one or more cameras, including, but not limited to camera **106**, may be used to create one or more subject profiles, which may include one or more subject characteristic image elements specific to each of a group of potential subjects (e.g., including subject **122**) and extracted from captured images featuring the potential subjects. Camera **106** may capture one or more images featuring a subject or potential subject, which the subject tracking module may designate as reference images. Reference image elements may then be isolated from the reference images. Reference image elements may be reference image elements corresponding to a subject or potential subject (e.g., a face or facial feature, a Haar-like feature, a hue or color scheme, a pattern or texture, a shape corresponding to a body or body part of the subject) or reference image elements not directly corresponding to the subject (e.g., the background and environment in which the subject is pictured). In this regard, the one or more subject characteristic image elements may be stored in one or more databases (e.g., in negative database **138b**) for a comparison with one or more real-time image elements (e.g., positive or negative image elements extracted from images captured in real time or near real time).

In one embodiment, the preparatory step of system **100** also includes gathering non-subject characteristic information for a group of reference objects. For example, one or more natural features, manmade structures, or landmarks (e.g., tree **408**, tower **412**, or mountain **414**, FIGS. 4A-4B) may exist along or in the path of a ski course. In this regard, one or more cameras including, but not limited to, camera **106**, may be used to create one or more subject profiles, which may include one or more reference object characteristic image elements specific to a group of potential subjects (e.g., tree **408**, tower **412**, or mountain **414**). In one embodiment, the one or more reference object characteristic image elements are stored in one or more databases (e.g., as reference images in negative database **138b**) for a comparison with one or more real-time image elements (e.g., negative image elements extracted from images captured in real time or near real time). In one embodiment, the subject tracking module **124** further analyzes subject characteristic and subject noncharacteristic reference image elements to determine reference relationships (e.g., a relative height of the subject compared to a natural feature, a hue associated with the subject compared to the hue of a natural feature such as the sky, the absolute location of a background element identified as a known natural feature or landmark). In one embodiment, reference relationships are stored in the

one or more databases (e.g., negative database **138b**) for comparison with current image elements.

In one embodiment, the UAV **102** of system **100** also includes one or more transmitters for transmitting one or more images. In one embodiment the UAV **102** of system **100** includes one or more receivers for receiving data associated with one or more subjects (e.g., subject **122**) or one or more command gestures. In one embodiment, the UAV of system **100** includes one or more transceivers (e.g., Wi-Fi transceiver **152**) capable of transmitting and receiving data.

In some embodiments, a user may receive image data captured by the onboard camera of a UAV, or processed by the cascade recognition system **100**, through a pair of goggles **182** or a similar linked device **180** enabling remote viewing. Such a remote viewing system may additionally allow the user to select (e.g., via a user interface of the smartphone **180** or similar handheld device) an image element or a subject to acquire or track, or receive information associated with the position of the UAV or a subject. The remote viewing system may also incorporate an image intensifier or similar device to assist in low-light image recognition (ex.—night vision).

In step **210**, the method of acquiring and following a subject with an UAV includes defining a subject by capturing at least one reference image via one or more cameras of the UAV. In one embodiment, the subject is defined by a remote user, communicatively coupled to the system **100** (e.g., via Wi-Fi), who selects a subject to follow or track. For example, a particular person or persons may be designated by a remote user as a subject **122**. For instance, referring to FIG. 1B, a remote user using a smartphone **180**, interactive goggles **182**, tablet, or other media device may indicate a particular competitor or competitors they wish to follow.

In one embodiment, the UAV may remotely or autonomously designate a person as a subject for the UAV to track or follow in motion. For example, at a cross-country ski race the UAV may be assigned (e.g., by a remote user, by a base station, or by an operator/programmer of the UAV) to track a particular skier **122** along the course and relay information about his or her progress (e.g., still images, video feed, position, etc.) to coaches or viewers stationed elsewhere. In one embodiment, the UAV defines as its subject **122** an individual with various distinguishing features, including, but not limited to, features such as height and weight, hair color and texture, facial composition, clothing color and texture, facial hair or the lack thereof.

In one embodiment, the UAV **102** switches subjects between various members of a team. In one embodiment, the UAV **102** tracks the lead skier **122** whoever he or she may be. For example, the UAV **102** may be configured to select one subject **122** from a finite set of potential subjects for which associated subject profiles have been uploaded, swapping the appropriate image elements between one or more databases as a new subject is selected. In this regard, if multiple persons (subjects, potential subjects, and non-subjects) or potential subjects are in the field of view of the UAV **102**, then the UAV **102** may use cascade recognition techniques to distinguish subjects from non-subjects on a continual basis.

In step **220**, the UAV **102** captures one or more first images via the one or more cameras **106**. In one embodiment, capturing one or more first images includes utilizing one or more data compression algorithms **110** to efficiently transmit, store, and/or analyze the one or more images captured.

In one embodiment, the one or more instructions executed by the one or more processors of system 100 comprise an image compression and storage process 110. In one embodiment, the system 100 may initiate one or more algorithms to compress the one or more images being captured by the one or more cameras 106. For example, the one or more algorithms initiated by system 100 may assign a gray-scale value to each pixel of the one or more images captured. In this regard, the one or more algorithms initiated may recognize a series of repeating gray-scale values and assign to a portion of the one or more images captured at least one of a compression label, a compression position/coordinate, or a compression gray-scale-repeat number (e.g., indicating the number of repeating pixels associated with the compression value). In one embodiment, the system 100 or a base station (not shown) includes a codebook for decompressing the one or more images using one or more of the compression label, the compression position/coordinate, or the compression gray-scale repeat number. Applicant notes that the algorithms for image compression initiated by the image compression/storage module 110 may vary according to image compression processes known in the art. In this regard, the examples for the compression algorithms given herein are merely for illustrative and explanatory purposes, and are not limiting.

In one embodiment, referring to FIGS. 1A-1B, a UAV (e.g., UAV 102) includes an onboard cascade visual recognition system 100 according to the present disclosure, the system operably/communicatively coupled to the one or more cameras 106. The one or more cameras 106 are configured to capture a stream of images, either as a video feed or as periodic still images. In one embodiment, a user may preprogram or adjust the rate at which images are captured, increasing the capture rate for greater precision or reducing the capture rate for greater efficiency of operation or longer battery life. For example, captured images may include real-time (or near real-time) images of human beings who may or may not be designated as subjects (e.g., defined in step 210 as subject 122). In one embodiment, referring to FIG. 4A-4B, the captured images include additional background elements capable of conveying information, such as man-made structures or landmarks (buildings/towers) and natural features (terrain, vegetation, mountains, bodies of water). For example, the information conveyed by background (negative) image elements may establish reference relationships between one or more reference image elements. In this regard, the information conveyed includes, but is not limited to, time of day, weather, and medium-scale positioning. For example, an additional background image element may include the sky 410. Reference relationships involving the sky 410 may indicate time of day (darker but non-black sky may indicate evening or early morning), approximate position (the location of the sun may indicate a westerly or easterly direction, or stellar patterns may indicate an approximate latitude), or weather conditions (cloud cover or overcast skies may indicate imminent precipitation).

In one embodiment of step 220, capturing one or more positive image elements includes utilizing macro-scaled visual recognition techniques/algorithms to distinguish subjects (and their corresponding image elements) from non-subjects (and their corresponding image elements). For example, the macro-scaled techniques/algorithms include, but are not limited to, motion sensing capabilities, color and shape discernment, and other broad-level visual recognition techniques/algorithms. For example, while tracking a subject 304 at speed (e.g., at faster velocities while following

the subject from behind, as depicted in FIGS. 3A-3B), the visual recognition module 108 may not be able to identify positive image elements corresponding to the subject 304 based on identification of facial features or other micro-scale characteristics. Therefore, at speed the visual recognition module 108 may instead verify the subject 304 (and corresponding positive image elements) via less precise but more efficient macro-scaled or medium-scaled techniques. For example, the visual recognition module 108 may identify the subject 304 based on a known hue or color scheme corresponding to the subject's clothing, based on whether the general shape of the subject corresponds to reference images of the subject in motion (e.g., in various positions associated with skiing), or based on identification of a specific pattern (e.g., a QR code) affixed to the clothing of the subject 122.

In step 230, the visual recognition module 108 extracts one or more current image elements from the one or more first images (e.g., real-time images) captured in step 220. In one embodiment, extracting the one or more current image elements includes analyzing the one or more real-time images to determine whether the current image elements are positive image elements or negative image elements.

In one embodiment, referring to FIGS. 1A and 4A, the cascade recognition system 100 of the UAV 102 may initially separate a captured and compressed image 400 into a group of individual elements (402, 404, 406, 408, 410, 412, 414) using medium-scale visual recognition techniques and/or algorithms. For example, the visual recognition module 108 of UAV 102 may identify one or more current image elements, including three human beings 402, 404, and 406, a tree in the foreground 408, the sky 410, a tower 412, and a mountain 414 in the background, then extract the one or more current image elements for analysis and storage.

In one embodiment, the medium-scale visual recognition techniques and/or algorithms include identifying, analyzing, and determining medium-scaled characteristics. For example, in one embodiment, medium-scaled characteristics may include shape, texture, color schemes, and components of an object (e.g., distinguishing human arms/legs from arboreal trunks/branches).

In one embodiment, referring to FIGS. 1A and 3A-4B, system 100 utilizes a combination of macro-scaled techniques/algorithms and medium-scaled techniques/algorithms of the visual recognition module 108 to identify and extract positive current image elements corresponding to one or more subjects 122. For example, the system 100 may use camera 106 to make broad scans to identify a group of image elements corresponding to subjects, potential subjects, or non-subjects. When capturing images in step 220, the visual recognition module 108 may separate images (e.g., image 400) into small chunks (image elements 402, 404, 406, 408, 410, 412, and 414), divide them into sortable objects (e.g., subjects, non-subjects, and/or landmarks), and analyze (e.g., 140, 142, or 144) the specifics of the resulting image elements.

In step 240, cascade recognition system 100 determines whether the one or more current image elements are positive image elements or negative image elements. In this regard, the visual recognition module 108 determines 140 whether the one or more current image elements are one or more positive image elements corresponding to the subject, or determines 142 whether the one or more current image elements are negative image elements not corresponding to the subject.

In one embodiment of step 240, referring generally to FIGS. 1A and 5A-5C, the cascade recognition system 100 of UAV 102 further identifies and extracts one or more image

elements corresponding to specific human beings (e.g., subject persons **122** vs. non-subject persons) utilizing micro-scaled visual recognition techniques/algorithms. In one embodiment, the micro-scaled visual recognition techniques/algorithms include, but are not limited to, using Haar-like features, Viola-Jones facial recognition, and infrared/color pattern detection techniques. In one embodiment, micro-scaled visual recognition techniques are more efficiently employed when assembling subject profiles associated with one or more subjects **122** in advance, while medium-scale or macro-scale techniques are more efficiently employed for real-time or near real-time image analysis. For example, the UAV **102** may be able to acquire multiple, detailed reference images of the subjects **122** from multiple distances and perspectives, assembling an individual profile for each subject **122** based on a detailed analysis of the subject's facial features as in FIGS. 5A-5C. Once the subject's facial features have been analyzed, and the associated reference image elements added to the subject profile and stored in database **138b**, the cascade recognition system **100** may augment these micro-scale reference image elements with medium-scale and macro-scale information, e.g., about the clothing or dimensions of each individual subject. The visual recognition module **108** may then use medium-scale or macro-scale data to differentiate positive image elements from negative image elements if micro-scale visual recognition techniques cannot be employed with sufficient confidence.

In one embodiment, the determination (e.g., **140**, **142**, or **144**) is made using micro-scaled visual recognition techniques/algorithms including, but not limited to, using Haar-like features, Viola-Jones facial recognition, and infrared/color pattern detection techniques. In this regard, the one or more processors of UAV **102** utilize the identified and extracted positive image elements of step **230** to determine whether the positive image elements correspond to the subject defined in step **210**. The determination of negative image elements (e.g., elements not corresponding to a subject) also occurs at this step. For example, referring to FIGS. 5A-5C, visual recognition module **108** may have identified an image element (e.g., **402**, **404**, or **406**) as corresponding to a human being. In this regard, the visual recognition module **108** may further analyze the element (e.g., **402**) on a micro-scale to identify and extract the facial region **502** or individual facial features **504**, **506**, **508**, or **510** within region **502**, which may or may not correspond to the subject (e.g., subject defined in step **210**).

Applicant notes the horizontal, medium-scaled facial feature recognition algorithms and/or Haar-like features depicted in FIGS. 5A and 5B are merely for illustrative and explanatory purposes, as other algorithms are encompassed by the visual recognition methods of this disclosure. For example, referring to FIG. 5C, a vertical, medium-scaled facial feature recognition algorithm may be used to determine one or more features of a specific human being.

In step **250**, cascade recognition system **100** stores in a positive database **136** the current positive image elements determined in step **240** to correspond to the subject **122**. For example, the visual recognition module **108** may determine in step **240** that one or more current image elements correspond to a subject (e.g., subject **122** or **304**—defined in step **210**). In this regard, the one or more current image elements are determined to be positive image elements and are stored in the positive database **136**, indicating a correspondence to the current subject **122**.

In step **260**, cascade recognition system **100** stores in a negative database **138a** the current image elements deter-

mined in step **240** not to correspond to the subject. For example, the visual recognition module **108** may determine in step **240** that one or more current image elements do not correspond to the subject (e.g., they correspond to non-subjects: tree **306**, tree **408**, tower **412**, mountain **414**; or they correspond to other (ex.—potential) persons who are not the defined subject, such as subjects **402**, **404**, and **406**). In one embodiment, the positive database **136** and negative database **138a** are populated with image elements that establish foreground and background position, hue and color scheme, patterns, or other distinguishing features to precisely determine what aspects of the current image correspond (or do not correspond) to the subject **122**.

In step **270**, the subject tracking module **124** determines one or more attributes of a subject **122** by performing a comparison of one or more image elements. In this regard, the comparison may be between the one or more current image elements and a positive image element, a negative image element, or a reference image element. For example, the subject tracking module **124** may compare a current positive image element (i.e., extracted from the most recent image captured by camera **106** and analyzed by visual recognition module **108**) corresponding to the subject **122** with one or more prior positive image elements stored in positive database **136** and corresponding to earlier representations of the subject **122**. Referring to FIG. 3A, the subject tracking module may compare current and prior positive image elements corresponding to skier **304** (a selected subject currently being tracked by UAV **102**) and determine that (e.g., over the course of multiple frames) that skier **304** has moved slightly to the left relative to his/her position in the frame **302a**. Accordingly, the subject tracking module **124** may direct the attitude control system **126** of UAV **102** to keep skier **304** centrally framed by rotating UAV **102** slightly to the left (resulting in frame **302b**). Referring to FIG. 3B, the subject tracking module **124** may instead determine that skier **304**, while still centrally framed, is transitioning to a crouching position. In this instance, the subject tracking module **124** may instead instruct the attitude control system to adjust the pitch angle of UAV **102** downward in anticipation of an approaching down-sloping portion of the course.

In one embodiment, referring to FIGS. 4A and 4B, at step **270** the subject tracking module **124** may instead compare a current negative image element with a prior negative image element stored in negative database **138a**, or a second reference image element stored in negative database **138b**, to determine one or more attributes of subject **124** by deriving information about the environment through which subject **122** is passing. For example, the visual recognition module **108** may have previously determined that tree **408**, tower **412**, and mountain **414** do not correspond to the subject, or to a human being, and stored any image elements associated with these objects in negative database **138a** (or as reference image elements in negative database **138b**). As additional image elements corresponding to tree **408**, tower **412**, or mountain **414** accumulate in negative database **138a**, however, the subject tracking module **128** may compare sequential image elements to determine to what extent, if any, the subject **122** is approaching each of tree **408**, tower **412**, and mountain **414**. This way the subject tracking module **124** may estimate a relative distance between the subject **122** and tree **408**, tower **412**, and mountain **414**, or estimate a position of the subject **122** relative to tree **408**, tower **412**, or mountain **414**, depending on the available information.

In one embodiment, the subject tracking module **124** may compare current or prior negative image elements with

13

reference image elements stored in negative database 138b to determine one or more attributes of subject 122. For example, tower 412 may be a known landmark of known height and location. The subject tracking module may be tracking subject 122 at a predetermined distance, and may have estimated the height of subject 122 from reference image elements in the subject profile of subject 122. Therefore if the current image displays a positive image element corresponding to subject 122 and a negative image element corresponding to tower 412 (the negative image element indicating a height of tower 412 relative both to subject 122 and to the frame), the negative image element can be compared to a reference image element of tower 412 if such a reference image element is stored in negative database 138b. If a reference image element corresponding to tower 412 exists in negative database 138b, the reference image element may be associated with metadata associated with a reference relationship between one or more reference image elements, e.g., an actual height or other dimension of tower 412, or a relative height of tower 412 as seen by a subject from one or more distances or perspectives. In one embodiment, metadata associated with a reference image element is associated with a reference relationship between one or more reference image elements, e.g., The subject tracking module 124 may then compare one or more negative image elements corresponding to tower 412 to the reference image element in negative database 138b, thus making inferences about the relative distance between subject 122 and tower 412 or a position of subject 122 relative to tower 412.

In one embodiment, successive captured images may thus allow the subject tracking module 124 to determine a heading of the subject (e.g., subject 122) based on changes in relative position to fixed landmarks such as tower 412. In one embodiment, the UAV 102 incorporates a GPS receiver or other position sensor connected to the cascade recognition system 100 and capable of determining an absolute position or absolute heading of the subject 122.

In one embodiment, referring to FIGS. 1A and 6A-6C, the cascade recognition system 100 determines one or more attributes of the subject including one or more command gestures. In one embodiment, the cascade recognition system 100 records one or more command gestures, each command gesture associated with one or more command functions (e.g., increase distance, change position, or abandon subject). For example, UAV 102 may be communicatively coupled with one or more cameras, including, but not limited to, camera 106. In this regard, the subject 122 may direct the UAV 102 to record a sequence of images depicting the performance of distinctive gestures. Referring to FIG. 6A, a distinctive command gesture may include a subject 122 briefly raising the left arm at a 90° angle to the torso. A sequence of reference image elements corresponding to this sequence of images (and thus to the command gesture) may then be stored in the negative database 138b. The sequence of images or image elements may be further associated with a particular confidence level and/or a counter.

In one embodiment, a UAV (e.g., UAV 102) tracking a subject (e.g., subject 122), having identified at least one positive image element corresponding to the subject via the visual recognition module 108, compares the at least one positive image element to one or more reference image elements corresponding to a command gesture and stored in negative database 138b via the subject tracking system 124. For example, a current positive image element may correspond to one or more reference image elements associated with a particular command gesture (and related command function, e.g., "reduce tracking distance by half") to a

14

predetermined confidence level. The subject tracking system 124 may then increment a counter associated with the command gesture and continue to compare incoming positive image elements to the reference image element/s associated with the particular command gesture. Should the counter reach a predetermined threshold (i.e., a predetermined number of sequential positive image elements correspond to the command gesture), the cascade recognition system 100 may determine that the associated command gesture has been identified to a sufficient confidence level and direct the attitude control system 126 to execute any procedures or functions associated with the command gesture (i.e., close to half the current tracking distance). In one embodiment, the subject tracking module 124 will only initiate the command gesture detection process if the gesture is performed by an identified subject 122, ignoring any gestures performed by non-subjects.

In step 280, the attitude control system 126 adjusts at least one at least one rotor speed of the UAV 102 based on the one or more determined attributes of the subject (e.g., subject 122), as directed by the subject tracking module 124. For example, referring to FIGS. 1A-1B, having determined one or more attributes of subject 122, which may include at least an orientation (e.g., direction of travel 128 in FIG. 1B), the subject tracking module 124 directs the attitude system 126 of UAV 102 to adjust at least one rotor speed (thereby adjusting the position, orientation, velocity, and/or direction of the UAV 102) to match at least the orientation or direction of travel 132 of the UAV 102 to the orientation or direction of travel 128 of the subject 122.

In one embodiment the attitude control system 126 adjusts at least one rotor speed of the UAV 102 based on one or more determined command gestures (e.g., attributes) of subject 122. For example, the visual recognition module 108 may identify and extract image elements from a current image and determine those identified image elements correspond to the subject 122. The subject tracking module 124 may then determine that one or more positive image elements correspond to one or more distinctive command gestures. The subject tracking module 124 may then direct the attitude control system 126 of UAV 102 to perform any procedures or functions associated with the command gestures. In one embodiment, referring to FIG. 1B, the subject tracking station 124 of base station 150 signals the attitude control systems 126 of (ex.—transmits attitude signals to) one or more UAVs 102, 154, 156, 158 to execute procedures or functions associated with identified command gestures.

In one embodiment, the one or more attitude signals cause UAV 102 to adjust one or more rotor speeds, such that the UAV tracks the subject 122 from a different or new position. For example, referring to FIG. 6B, if a command gesture includes subject 122 holding the left arm at a 90° angle to the torso and the left forearm at a 90° angle to the left bicep, the UAV 102 may then assume a new position more distant from the subject 122.

Applicant notes that the command gestures given above are merely for illustrative and explanatory purposes. In one embodiment, the UAV 102, camera 106, visual recognition module 108, and subject tracking module 124 are further configured to recognize multiple distinctive command gestures, each of which may stop or adjust a one or more rotor speeds of the UAV 102. For example, referring to FIG. 6C, a distinctive command gesture of the left arm held out straight away from the torso may be associated with stopping the tracking of the subject 122. By way of another example, a distinctive command gesture of the right arm being held out straight away from the torso may be associ-

15

ated with changing a tracking angle of the UAV 102. Applicant notes that additional distinctive command gestures associated with additional command procedures or functions will be recognized by those skilled in the art, and are encompassed in embodiments of this disclosure.

Those having skill in the art will appreciate that there are various vehicles by which processes and/or systems and/or other technologies described herein can be effected (e.g., hardware, software, and/or firmware), and that the preferred vehicle will vary with the context in which the processes and/or systems and/or other technologies are deployed. For example, if an implementer determines that speed and accuracy are paramount, the implementer may opt for a mainly hardware and/or firmware vehicle; alternatively, if flexibility is paramount, the implementer may opt for a mainly software implementation; or, yet again alternatively, the implementer may opt for some combination of hardware, software, and/or firmware. Hence, there are several possible vehicles by which the processes and/or devices and/or other technologies described herein may be effected, none of which is inherently superior to the other in that any vehicle to be utilized is a choice dependent upon the context in which the vehicle will be deployed and the specific concerns (e.g., speed, flexibility, or predictability) of the implementer, any of which may vary. Those skilled in the art will recognize that optical aspects of implementations will typically employ optically-oriented hardware, software, and or firmware.

The herein described subject matter sometimes illustrates different components contained within, or connected with, different other components. It is to be understood that such depicted architectures are merely exemplary, and that in fact many other architectures can be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively “associated” such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as “associated with” each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “connected”, or “coupled”, to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being “couplable”, to each other to achieve the desired functionality. Specific examples of couplable include but are not limited to physically mateable and/or physically interacting components and/or wirelessly interactable and/or wirelessly interacting components and/or logically interacting and/or logically interactable components.

While particular aspects of the subject matter described herein have been shown and described, it will be apparent to those skilled in the art that, based upon the teachings herein, changes and modifications may be made without departing from the subject matter described herein and its broader aspects and, therefore, the appended claims are to encompass within their scope all such changes and modifications as are within the true spirit and scope of the subject matter described herein.

We claim:

1. An unmanned aerial vehicle (UAV), comprising:
an airframe;

at least one attitude control system coupled to the airframe and configured to adjust one or more of a position of the UAV, a velocity of the UAV, a heading of the UAV, and a first orientation of the UAV;

16

at least one camera pivotably attached to the airframe by a mount and configured to capture one or more images; one or more processors coupled to the camera and configured to:

determine at least one subject for tracking via the UAV; extract at least one current image element from the one or more captured images;

designate the at least one current image element as one of a subject image element corresponding to the subject, a non-subject image element not corresponding to the subject;

store the at least one subject image element to a subject database, and the at least one non-subject image element to a non-subject database, the subject database and the non-subject database associated with a memory coupled to the one or more processors;

determine at least one subject attribute based on the at least one subject image element, the at least one non-subject image element, and at least one reference image element stored to a reference database associated with the memory;

determine at least one command gesture based on the at least one subject image element, the at least one command gesture associated with one or more of the subject and a command procedure;

and

execute the at least one command procedure based on one or more of the at least one subject attribute and the at least one command gesture, the command procedure comprising one or more of:

adjusting one or more of the position of the UAV, the velocity of the UAV, the heading of the UAV, and the first orientation of the UAV;

and

adjusting a second orientation of the camera relative to the UAV by articulating the at least one mount.

2. The UAV of claim 1, wherein:

the one or more processors are configured to identify at least one non-subject element based on one or more of the at least one non-subject image element and the at least one reference image element.

3. The UAV of claim 1, further comprising:

at least one image stabilizer coupled to the camera and compared to articulate the at least one mount based on the orientation of the UAV.

4. The UAV of claim 1, wherein:

the one or more processors are configured to determine the subject by selecting the subject from a plurality of potential subjects based on the at least one reference image.

5. The UAV of claim 1, wherein the one or more processors are configured to determine at least one reference relationship based on the at least one subject image element, the at least one non-subject image element, and the at least one reference image element.

6. The UAV of claim 5, wherein the at least one reference relationship includes at least one of a relative position of the subject relative to a non-subject element and a relative distance of the subject from the non-subject element.

7. The UAV of claim 6, further comprising:

at least one satellite-based position sensor configured to determine at least one of:

a first absolute position of the UAV; and

a second absolute position of the subject based on at least one of the relative position, the first absolute position, and a third absolute position of the non-subject element.

17

8. The UAV of claim 5, wherein the at least one reference relationship includes at least one orientation of the subject.

9. The UAV of claim 5, wherein the one or more processors are configured to execute the at least one command procedure based on the at least one reference relationship.

10. The UAV of claim 1, further comprising:

at least one transceiver coupled to the one or more processors, the at least one transceiver configured to: transmit at least one of:

1) the one or more images; and

2) at least one reference relationship based on the at least one subject image element, the at least one non-subject image element, and the at least one reference image element;

to at least one remote display device wirelessly coupled to the at least one transceiver, the remote display device configured to display at least one of the one

18

or more images and the at least one reference relationship to at least one user;

and

receive at least one attitude signal from the at least one remote display device.

11. The UAV of claim 10, wherein the at least one remote display device includes at least one of a head-worn display (HWD), a smartphone, a portable computing device, and a base station.

12. The UAV of claim 10, wherein the one or more processors are configured to execute the at least one command procedure based on the at least one received attitude signal.

13. The UAV of claim 10, wherein the at least one remote display device is configured to allow the user to select the at least one subject.

* * * * *