



US010198953B2

(12) **United States Patent**  
**Priest**

(10) **Patent No.:** **US 10,198,953 B2**

(45) **Date of Patent:** **Feb. 5, 2019**

(54) **OBSTRUCTION DETECTION IN AIR TRAFFIC CONTROL SYSTEMS FOR UNMANNED AERIAL VEHICLES**

*5/0069* (2013.01); *B64C 2201/12* (2013.01); *H04B 7/18506* (2013.01)

(71) Applicant: **Lee Priest**, Charlotte, NC (US)

(58) **Field of Classification Search**

CPC ..... *B64C 2201/12*; *B64C 39/024*; *G08G 5/0008*; *G08G 5/0039*; *G08G 5/0069*; *H04B 7/18506*

(72) Inventor: **Lee Priest**, Charlotte, NC (US)

See application file for complete search history.

(73) Assignee: **ETAK Systems, LLC**, Huntersville, NC (US)

(56) **References Cited**

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 281 days.

U.S. PATENT DOCUMENTS

9,488,979 B1 \* 11/2016 Chambers ..... *G05D 1/0088*  
9,997,080 B1 \* 6/2018 Chambers ..... *G08G 5/045*  
(Continued)

(21) Appl. No.: **15/255,672**

(22) Filed: **Sep. 2, 2016**

OTHER PUBLICATIONS

Technology and the Future Evolution of the ATC System, Chapter 5, Airport and Air Traffic Control System, pp. 67-98.  
(Continued)

(65) **Prior Publication Data**

US 2017/0358213 A1 Dec. 14, 2017

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 15/244,023, filed on Aug. 23, 2016, now Pat. No. 10,109,205, and a continuation-in-part of application No. 15/217,135, filed on Jul. 22, 2016, now Pat. No. 9,959,772, and a continuation-in-part of application No. 15/193,488, filed on Jun. 27, 2016, and a continuation-in-part of application No. 15/185,598, filed on Jun. 17, 2016,  
(Continued)

*Primary Examiner* — Harry Y Oh

(74) *Attorney, Agent, or Firm* — Clements Bernard Walker PLLC; Lawrence A. Baratta, Jr.

(57) **ABSTRACT**

Obstruction detection and management systems and methods are performed through an Air Traffic Control (ATC) system for Unmanned Aerial Vehicles (UAVs). The obstruction detection and management method includes receiving UAV data from a plurality of UAVs, wherein the UAV data includes operational data for the plurality of UAVs and obstruction data from one or more UAVs; updating an obstruction database based on the obstruction data; monitoring a flight plan for the plurality of UAVs based on the operational data; and transmitting obstruction instructions to the plurality of UAVs based on analyzing the obstruction database with their flight plan.


(51) **Int. Cl.**

*G05B 19/04* (2006.01)  
*G05B 19/18* (2006.01)  
*G08G 5/00* (2006.01)  
*B64C 39/02* (2006.01)  
*H04B 7/185* (2006.01)

(52) **U.S. Cl.**

CPC ..... *G08G 5/0008* (2013.01); *B64C 39/024* (2013.01); *G08G 5/0039* (2013.01); *G08G*

**18 Claims, 17 Drawing Sheets**



**Related U.S. Application Data**

now Pat. No. 10,019,906, and a continuation-in-part of application No. 15/179,188, filed on Jun. 10, 2016, now Pat. No. 9,928,750.

(56) **References Cited**


U.S. PATENT DOCUMENTS

2016/0253908 A1\* 9/2016 Chambers ..... B64C 39/024  
701/2  
2016/0275801 A1\* 9/2016 Kopardekar ..... G08G 5/0043


OTHER PUBLICATIONS

Operator Benefits of Future Air Navigation System, The Boeing Company, pp. 1-4.  
What are the essential elements of a control tower?, Aviation Stack Exchange is a question and answer site for aircraft pilots, mechanics, and enthusiasts, pp. 1-2.


\* cited by examiner




**FIG. 1**




**FIG. 2**




**FIG. 3**




**FIG. 4**



**FIG. 5**




**FIG. 6**




**FIG. 7**







**FIG. 8**




**FIG. 9**




**FIG. 10**




**FIG. 11**



**FIG. 12**




**FIG. 13**



**FIG. 14**




**FIG. 15**




**FIG. 16**






**FIG. 17**



**FIG. 18**



**FIG. 19**

**OBSTRUCTION DETECTION IN AIR TRAFFIC CONTROL SYSTEMS FOR UNMANNED AERIAL VEHICLES**

CROSS-REFERENCE TO RELATED APPLICATION(S)

The present patent/application is continuation-in-part of, and the content of each is incorporated by reference herein

Filing Date	Serial No.	Title
Aug. 23, 2016	15/244,023	AIR TRAFFIC CONTROL MONITORING SYSTEMS AND METHODS FOR UNMANNED AERIAL VEHICLES
Jul. 22, 2016	15/217,135	FLYING LANE MANAGEMENT SYSTEMS AND METHODS FOR UNMANNED AERIAL VEHICLES
Jun. 27, 2016	15/193,488	AIR TRAFFIC CONTROL OF UNMANNED AERIAL VEHICLES FOR DELIVERY APPLICATIONS
Jun. 17, 2016	15/185,598	AIR TRAFFIC CONTROL OF UNMANNED AERIAL VEHICLES CONCURRENTLY USING A PLURALITY OF WIRELESS NETWORKS
Jun. 10, 2016	15/179,188	AIR TRAFFIC CONTROL OF UNMANNED AERIAL VEHICLES VIA WIRELESS NETWORKS

FIELD OF THE DISCLOSURE

The present disclosure relates generally to systems and methods to control Unmanned Aerial Vehicles (UAVs or “drones”). More particularly, the present disclosure relates to obstruction detection systems and methods with air traffic control systems for UAVs.

BACKGROUND OF THE DISCLOSURE

Use of Unmanned Aerial Vehicles (UAVs or “drones”) is proliferating. UAVs are used for a variety of applications such as search and rescue, inspections, security, surveillance, scientific research, aerial photography and video, surveying, cargo delivery, and the like. With the proliferation, the Federal Aviation Administration (FAA) is providing regulations associated with the use of UAVs. Existing air traffic control in the United States is performed through a dedicated air traffic control network, i.e., the National Airspace System (NAS). However, it is impractical to use the existing air traffic control network for UAVs because of the sheer quantity of UAVs. Also, it is expected that UAVs will be autonomous, requiring communication for flight control as well. There will be a need for systems and methods to provide air traffic control and communication to UAVs.

There is a great deal of discussion and anticipation for using drones for applications such as package delivery. For example, online stores, brick & mortar stores, restaurants, etc. can use drones to provide delivery to end consumers. As the number of applications increase and the number of UAVs concurrently in flight also increase, there are various issues that have to be addressed relative to air traffic control.

As UAV use proliferates, there is a need to coordinate flying lanes to avoid collisions, obstructions, etc. Of course, with UAV use as a hobby, collision avoidance is not a major concern. However, once UAVs begin widespread delivery applications, collisions will be a major problem due to the

potential damage to deliveries as well as threats to people and property on the ground. Thus, there is a need for flying lane management systems and methods.

Further, it is expected that there will be orders of magnitude more UAVs in flight in any geographic region, zone, coverage area, etc. than regular aircraft. Accordingly, conventional monitoring systems and methods are inadequate to support UAV monitoring. Thus, there is a need for optimized UAV monitoring systems and methods.

Further, obstructions on or near the ground pose a significant risk to UAVs as most UAVs fly only several hundred feet above the ground, unlike airplanes which fly at thousands of feet above the ground. Stated differently, air traffic control for airplanes focuses on other airplanes primarily whereas air traffic control for UAVs must deal with other UAVs and with near ground obstructions.

BRIEF SUMMARY OF THE DISCLOSURE

In an exemplary embodiment, an obstruction detection and management method implemented through the UAV air traffic control system for the UAVs includes receiving UAV data from a plurality of UAVs, wherein the UAV data includes operational data for the plurality of UAVs and obstruction data from one or more UAVs; updating an obstruction database based on the obstruction data; monitoring a flight plan for the plurality of UAVs based on the operational data; and transmitting obstruction instructions to the plurality of UAVs based on analyzing the obstruction database with their flight plan.

In another exemplary embodiment, an Unmanned Aerial Vehicle (UAV) air traffic control and monitoring system for obstruction detection and management includes a network interface and one or more processors communicatively coupled to one another; and memory storing instructions that, when executed, cause the one or more processors to receive UAV data from a plurality of UAVs, wherein the UAV data includes operational data for the plurality of UAVs and obstruction data from one or more UAVs; update an obstruction database based on the obstruction data; monitor a flight plan for the plurality of UAVs based on the operational data; and transmit obstruction instructions to the plurality of UAVs based on analyzing the obstruction database with their flight plan.

A non-transitory computer-readable medium comprising instructions that, when executed, cause one or more processors to perform steps of: receiving Unmanned Aerial Vehicle (UAV) data from a plurality of UAVs, wherein the UAV data includes operational data for the plurality of UAVs and obstruction data from one or more UAVs; updating an obstruction database based on the obstruction data; monitoring a flight plan for the plurality of UAVs based on the operational data; and transmitting obstruction instructions to the plurality of UAVs based on analyzing the obstruction database with their flight plan.

In an exemplary embodiment, an Unmanned Aerial Vehicle (UAV) air traffic control and monitoring method implemented by a consolidated system includes communicating with a plurality of servers each configured to communicate with a plurality of UAVs in a geographic or zone coverage; consolidating data from the plurality of servers to provide a visualization of a larger geography comprising a plurality of geographic or zone coverages; providing the visualization via a Graphical User Interface (GUI); and performing one or more functions via the GUI for air traffic control and monitoring at any of a high-level and an individual UAV level.

Further, in an exemplary embodiment, a flying lane management method implemented in an air traffic control system communicatively coupled to one or more Unmanned Aerial Vehicles (UAVs) via one or more wireless networks includes: initiating communication to the one or more UAVs at a preflight stage for each, wherein the communication is via one or more cell towers associated with the one or more wireless networks, wherein the plurality of UAVs each include hardware and antennas adapted to communicate to the plurality of cell towers; determining a flying lane for the one or more UAVs based on a destination, current air traffic in a region under management of the air traffic control system, and based on detected obstructions in the region; and providing the flying lane to the one or more UAVs are an approval to takeoff and fly along the flying lane.

In another exemplary embodiment, an air traffic control system communicatively coupled to one or more Unmanned Aerial Vehicles (UAVs) via one or more wireless networks adapted to perform flying lane management includes a network interface and one or more processors communicatively coupled to one another; and memory storing instructions that, when executed, cause the one or more processors to: initiate communication to the one or more UAVs at a preflight stage for each, wherein the communication is via one or more cell towers associated with the one or more wireless networks, wherein the plurality of UAVs each include hardware and antennas adapted to communicate to the plurality of cell towers; determine a flying lane for the one or more UAVs based on a destination, current air traffic in a region under management of the air traffic control system, and based on detected obstructions in the region; and provide the flying lane to the one or more UAVs are an approval to takeoff and fly along the flying lane.

In an exemplary embodiment, an Unmanned Aerial Vehicle (UAV) air traffic control method utilizing wireless networks and concurrently supporting delivery application authorization and management includes communicating with a plurality of UAVs via a plurality of cell towers associated with the wireless networks, wherein the plurality of UAVs each comprise hardware and antennas adapted to communicate to the plurality of cell towers; maintaining data associated with flight of each of the plurality of UAVs based on the communicating; processing the maintained data to perform a plurality of functions associated with air traffic control of the plurality of UAVs; and processing the maintained data to perform a plurality of functions for the delivery application authorization and management for each of the plurality of UAVs.

In an exemplary embodiment, an Unmanned Aerial Vehicle (UAV) air traffic control method is implemented in a UAV during a flight, for concurrently utilizing a plurality of wireless networks for air traffic control. The UAV air traffic control method includes maintaining communication with a first wireless network and a second wireless network of the plurality of wireless networks; communicating first data with the first wireless network and second data with the second wireless network throughout the flight, wherein one or more of the first data and the second data is provided to an air traffic control system configured to maintain status of a plurality of UAVs in flight and perform control thereof; and adjusting the flight based on one or more of the first data and the second data and control from the air traffic control system.

In an exemplary embodiment, an Unmanned Aerial Vehicle (UAV) air traffic control method utilizing wireless networks includes communicating with a plurality of UAVs via a plurality of cell towers associated with the wireless

networks, wherein the plurality of UAVs each include hardware and antennas adapted to communicate to the plurality of cell towers, and wherein each of the plurality of UAVs include a unique identifier; maintaining data associated with flight of each of the plurality of UAVs based on the communicating; and processing the maintained data to perform a plurality of functions associated with air traffic control of the plurality of UAVs. The UAV-based method can further include transmitting data based on the processing to one or more of the plurality of UAVs to perform the plurality of functions.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure is illustrated and described herein with reference to the various drawings, in which like reference numbers are used to denote like system components/method steps, as appropriate, and in which:

FIG. 1 is a diagram of a side view of an exemplary cell site;

FIG. 2 is a perspective view of an exemplary UAV for use with the systems and methods described herein;

FIG. 3 is a block diagram of a mobile device, which may be embedded or associated with the UAV of FIG. 1;

FIG. 4 is a network diagram of various cell sites deployed in a geographic region;

FIG. 5 is a block diagram of functional components of a UAV air traffic control system;

FIG. 6 is a diagram of various cell sites deployed in a geographic region;

FIG. 7 is a map of three cell towers and associated coverage areas for describing location determination of the UAV;

FIG. 8 is a flowchart of a UAV air traffic control method utilizing wireless networks;

FIG. 9 is a flowchart of a UAV air traffic control method concurrently utilizing a plurality of wireless networks;

FIG. 10 is a flowchart of a packet delivery authorization and management method utilizing the UAV air traffic control system of FIG. 5;

FIG. 11 is a diagram of a flight path of an associated flying lane of a UAV from takeoff to landing;

FIG. 12 is a diagram of obstruction detection by the UAV and associated changes to the flying lane;

FIG. 13 is a flowchart of a flying lane management method via an air traffic control system communicatively coupled to a UAV via one or more wireless networks;

FIG. 14 is a block diagram of functional components of a consolidated UAV air traffic control monitoring system;

FIG. 15 is a screen shot of a Graphical User Interface (GUI) providing a view of the consolidated UAV air traffic control monitoring system;

FIG. 16 is a flowchart of a UAV air traffic control and monitor method;

FIGS. 17 and 18 are block diagrams of the UAV air traffic control system describing functionality associated with obstruction detection, identification, and management with FIG. 17 describing data transfer from the UAVs to the servers and FIG. 18 describing data transfer to the UAVs from the servers; and

FIG. 19 is a flowchart of an obstruction detection and management method implemented through the UAV air traffic control system for the UAVs.

#### DETAILED DESCRIPTION OF THE DISCLOSURE

Again, in various exemplary embodiments, the present disclosure relates to obstruction detection systems and meth-

ods with air traffic control systems for UAVs. Specifically, the systems and methods use a framework of an air traffic control system which uses wireless (cell) networks to communicate with various UAVs. Through such communication, the air traffic control system receives continuous updates related to existing obstructions whether temporary or permanent, maintains a database of present obstructions, and updates the various UAVs with associated obstructions in their flight plan. The systems and methods can further direct UAVs to investigate, capture data, and provide such data for analysis to detect and identify obstructions for addition in the database. The systems and methods can make use of the vast data collection equipment on UAVs, such as cameras, radar, etc. to properly identify and classify obstructions.

Further, in various exemplary embodiments, the present disclosure relates to air traffic control monitoring systems and methods for UAVs. Conventional FAA Air Traffic Control monitoring approaches are able to track and monitor all airplanes flying in the U.S. concurrently. Such approaches do not scale with UAVs which can exceed airplanes in numbers by several orders of magnitude. The systems and methods provide a hierarchical monitoring approach where zones or geographic regions of coverage are aggregated into a consolidated view for monitoring and control. The zones or geographic regions can provide local monitoring and control while the consolidated view can provide national monitoring and control in addition to local monitoring and control through a drill-down process. A consolidated server can aggregate data from various sources of control for zones or geographic regions. From this consolidated server, monitoring and control can be performed for any UAV communicatively coupled to a wireless network.

Further, in various exemplary embodiments, flying lane management systems and methods are described for UAVs such as through an air traffic control system that uses one or more wireless networks. As described herein, a flying lane for a UAV represents its path from takeoff to landing at a certain time. The objective of flying lane management is to prevent collisions, congestion, etc. with UAVs in flight. A flying lane can be modeled as a vector which includes coordinates and altitude (i.e., x, y, and z coordinates) at a specified time. The flying lane also can include speed and heading such that the future location can be determined. The flying lane management systems utilize one or more wireless networks to manage UAVs in various applications.

Note, flying lanes for UAVs have significant differences from conventional air traffic control flying lanes for aircraft (i.e., commercial airliners). First, there will be orders of magnitude more UAVs in flight than aircraft. This creates a management and scale issue. Second, air traffic control for UAVs is slightly different than aircraft in that collision avoidance is paramount in aircraft; while still important for UAVs, the objective does not have to be collision avoidance at all costs. It is further noted that this ties into the scale issue where the system for managing UAVs will have to manage so many more UAVs. Collision avoidance in UAVs is about avoiding property damage in the air (deliveries and the UAVs) and on the ground; collision avoidance in commercial aircraft is about safety. Third, UAVs are flying at different altitudes, much closer to the ground, i.e., there may be many more ground-based obstructions. Fourth, UAVs do not have designated takeoff/landing spots, i.e., airports, causing the different flight phases to be intertwined more, again adding to more management complexity.

To address these differences, the flying lane management systems and methods provide an autonomous/semi-autonomous management system, using one or more wireless

networks, to control and manage UAVs in flight, in all phases of a flying plane and adaptable based on continuous feedback and ever changing conditions.

Also, in various exemplary embodiments, the present disclosure relates to air traffic control of UAVs in delivery applications, i.e., using the drones to deliver packages, etc. to end users. Specifically, an air traffic control system utilizes existing wireless networks, such as wireless networks including wireless provider networks, i.e., cell networks, using Long Term Evolution (LTE) or the like, to provide air traffic control of UAVs. Also, the cell networks can be used in combination with other networks such as the NAS network or the like. Advantageously, cell networks provide high-bandwidth connectivity, low-cost connectivity, and broad geographic coverage. The air traffic control of the UAVs can include, for example, separation assurance between UAVs; navigation assistance; weather and obstacle reporting; monitoring of speed, altitude, location, direction, etc.; traffic management; landing services; and real-time control. The UAV is equipped with a mobile device, such as an embedded mobile device or physical hardware emulating a mobile device. In an exemplary embodiment, the UAV can be equipped with hardware to support plural cell networks, to allow for broad coverage support. In another exemplary embodiment, UAV flight plans can be constrained based on the availability of wireless cell coverage. In a further exemplary embodiment, the air traffic control can use plural wireless networks for different purposes such as using the NAS network for location and traffic management and using the cell network for the other functions.

The present disclosure leverages the existing wireless networks to address various issues associated with specific UAV applications such as delivery and to address the vast number of UAVs concurrently expected in flight relative to air traffic control. In an exemplary embodiment, in addition to air traffic control, the air traffic control system also supports package delivery authorization and management, landing authorization and management, separation assurance through altitude and flying lane coordination, and the like. Thus, the air traffic control system, leveraging existing wireless networks, can also provide application specific support.

#### § 1.0 Exemplary Cell Site

Referring to FIG. 1, in an exemplary embodiment, a diagram illustrates a side view of an exemplary cell site 10. The cell site 10 includes a cell tower 12. The cell tower 12 can be any type of elevated structure, such as 100-200 feet/30-60 meters tall. Generally, the cell tower 12 is an elevated structure for holding cell site components 14. The cell tower 12 may also include a lighting rod 16 and a warning light 18. Of course, there may various additional components associated with the cell tower 12 and the cell site 10 which are omitted for illustration purposes. In this exemplary embodiment, there are four sets 20, 22, 24, 26 of cell site components 14, such as for four different wireless service providers. In this example, the sets 20, 22, 24 include various antennas 30 for cellular service. The sets 20, 22, 24 are deployed in sectors, e.g. there can be three sectors for the cell site components—alpha, beta, and gamma. The antennas 30 are used to both transmit a radio signal to a mobile device and receive the signal from the mobile device. The antennas 30 are usually deployed as a single, groups of two, three or even four per sector. The higher the frequency of spectrum supported by the antenna 30, the shorter the antenna 30. For example, the antennas 30 may operate around 850 MHz, 1.9 GHz, and the like. The set 26 includes a microwave dish 32 which can be used to provide other

types of wireless connectivity, besides cellular service. There may be other embodiments where the cell tower **12** is omitted and replaced with other types of elevated structures such as roofs, water tanks, etc.

#### § 1.1 FAA Regulations

The FAA is overwhelmed with applications from companies interested in flying drones, but the FAA is intent on keeping the skies safe. Currently, approved exemptions for flying drones include tight rules. Once approved, there is some level of certification for drone operators along with specific rules such as speed limit of 100 mph, height limitations such as 400 ft, no-fly zones, only day operation, documentation, and restrictions on aerial filming. It is expected that these regulations will loosen as UAV deployments evolve. However, it is expected that the UAV regulations will require flight which would accommodate wireless connectivity to cell towers **12**, e.g., less than a few hundred feet.

#### § 2.0 Exemplary Hardware

Referring to FIG. **2**, in an exemplary embodiment, a perspective view illustrates an exemplary UAV **50** for use with the systems and methods described herein. Again, the UAV **50** may be referred to as a drone or the like. The UAV **50** may be a commercially available UAV platform that has been modified to carry specific electronic components as described herein to implement the various systems and methods. The UAV **50** includes rotors **80** attached to a body **82**. A lower frame **84** is located on a bottom portion of the body **82**, for landing the UAV **50** to rest on a flat surface and absorb impact during landing. The UAV **50** also includes a camera **86** which is used to take still photographs, video, and the like. Specifically, the camera **86** is used to provide the real-time display on the screen **62**. The UAV **50** includes various electronic components inside the body **82** and/or the camera **86** such as, without limitation, a processor, a data store, memory, a wireless interface, and the like. Also, the UAV **50** can include additional hardware, such as robotic arms or the like that allow the UAV **50** to attach/detach components for the cell site components **14**. Specifically, it is expected that the UAV **50** will get bigger and more advanced, capable of carrying significant loads, and not just a wireless camera.

These various components are now described with reference to a mobile device **100**. Those of ordinary skill in the art will recognize the UAV **50** can include similar components to the mobile device **100**. In an exemplary embodiment, the UAV **50** can include one or more mobile devices **100** embedded therein, such as for different cell networks. In another exemplary embodiment, the UAV **50** can include hardware which emulates the mobile device **100** including support for multiple different cell networks. For example, the hardware can include multiple different antennas and unique identifier configurations (e.g., Subscriber Identification Module (SIM) cards). For example, the UAV **50** can include circuitry to communicate with one or more LTE networks with an associated unique identifier, e.g., serial number.

Referring to FIG. **3**, in an exemplary embodiment, a block diagram illustrates a mobile device **100** hardware, which may be embedded or associated with the UAV **50**. The mobile device **100** can be a digital device that, in terms of hardware architecture, generally includes a processor **102**, input/output (I/O) interfaces **104**, wireless interfaces **106**, a data store **108**, and memory **110**. It should be appreciated by those of ordinary skill in the art that FIG. **3** depicts the mobile device **100** in an oversimplified manner, and a practical embodiment may include additional components

and suitably configured processing logic to support known or conventional operating features that are not described in detail herein. The components (**102**, **104**, **106**, **108**, and **102**) are communicatively coupled via a local interface **112**. The local interface **112** can be, for example, but not limited to, one or more buses or other wired or wireless connections, as is known in the art. The local interface **112** can have additional elements, which are omitted for simplicity, such as controllers, buffers (caches), drivers, repeaters, and receivers, among many others, to enable communications. Further, the local interface **112** may include address, control, and/or data connections to enable appropriate communications among the aforementioned components.

The processor **102** is a hardware device for executing software instructions. The processor **102** can be any custom made or commercially available processor, a central processing unit (CPU), an auxiliary processor among several processors associated with the mobile device **100**, a semiconductor-based microprocessor (in the form of a microchip or chip set), or generally any device for executing software instructions. When the mobile device **100** is in operation, the processor **102** is configured to execute software stored within the memory **110**, to communicate data to and from the memory **110**, and to generally control operations of the mobile device **100** pursuant to the software instructions. In an exemplary embodiment, the processor **102** may include a mobile-optimized processor such as optimized for power consumption and mobile applications. The I/O interfaces **104** can be used to receive user input from and/or for providing system output. User input can be provided via, for example, a keypad, a touch screen, a scroll ball, a scroll bar, buttons, barcode scanner, and the like. System output can be provided via a display device such as a liquid crystal display (LCD), touch screen, and the like. The I/O interfaces **104** can also include, for example, a serial port, a parallel port, a small computer system interface (SCSI), an infrared (IR) interface, a radio frequency (RF) interface, a universal serial bus (USB) interface, and the like. The I/O interfaces **104** can include a graphical user interface (GUI) that enables a user to interact with the mobile device **100**. Additionally, the I/O interfaces **104** may further include an imaging device, i.e. camera, video camera, etc.

The wireless interfaces **106** enable wireless communication to an external access device or network. Any number of suitable wireless data communication protocols, techniques, or methodologies can be supported by the wireless interfaces **106**, including, without limitation: RF; IrDA (infrared); Bluetooth; ZigBee (and other variants of the IEEE 802.15 protocol); IEEE 802.11 (any variation); IEEE 802.16 (WiMAX or any other variation); Direct Sequence Spread Spectrum; Frequency Hopping Spread Spectrum; Long Term Evolution (LTE); cellular/wireless/cordless telecommunication protocols (e.g. 3G/4G, etc.); wireless home network communication protocols; paging network protocols; magnetic induction; satellite data communication protocols; wireless hospital or health care facility network protocols such as those operating in the WMTS bands; GPRS; proprietary wireless data communication protocols such as variants of Wireless USB; and any other protocols for wireless communication. The wireless interfaces **106** can be used to communicate with the UAV **50** for command and control as well as to relay data. Again, the wireless interfaces **106** can be configured to communicate on a specific cell network or on a plurality of cell networks. The wireless interfaces **106** include hardware, wireless antennas, etc. enabling the UAV **50** to communicate concurrently with a

plurality of wireless networks, such as cellular networks, GPS, GLONASS, WLAN, WiMAX, or the like.

The data store **108** may be used to store data. The data store **108** may include any of volatile memory elements (e.g., random access memory (RAM, such as DRAM, SRAM, SDRAM, and the like)), nonvolatile memory elements (e.g., ROM, hard drive, tape, CDROM, and the like), and combinations thereof. Moreover, the data store **108** may incorporate electronic, magnetic, optical, and/or other types of storage media. The memory **110** may include any of volatile memory elements (e.g., random access memory (RAM, such as DRAM, SRAM, SDRAM, etc.)), nonvolatile memory elements (e.g., ROM, hard drive, etc.), and combinations thereof. Moreover, the memory **110** may incorporate electronic, magnetic, optical, and/or other types of storage media. Note that the memory **110** may have a distributed architecture, where various components are situated remotely from one another, but can be accessed by the processor **102**. The software in memory **110** can include one or more software programs, each of which includes an ordered listing of executable instructions for implementing logical functions. In the example of FIG. 3, the software in the memory **110** includes a suitable operating system (O/S) **114** and programs **116**. The operating system **114** essentially controls the execution of other computer programs and provides scheduling, input-output control, file and data management, memory management, and communication control and related services. The programs **116** may include various applications, add-ons, etc. configured to provide end user functionality with the mobile device **100**, including performing various aspects of the systems and methods described herein.

It will be appreciated that some exemplary embodiments described herein may include one or more generic or specialized processors (“one or more processors”) such as microprocessors; Central Processing Units (CPUs); Digital Signal Processors (DSPs); customized processors such as Network Processors (NPs) or Network Processing Units (NPs), Graphics Processing Units (GPUs), or the like; Field Programmable Gate Arrays (FPGAs); and the like along with unique stored program instructions (including both software and firmware) for control thereof to implement, in conjunction with certain non-processor circuits, some, most, or all of the functions of the methods and/or systems described herein. Alternatively, some or all functions may be implemented by a state machine that has no stored program instructions, or in one or more Application Specific Integrated Circuits (ASICs), in which each function or some combinations of certain of the functions are implemented as custom logic or circuitry. Of course, a combination of the aforementioned approaches may be used. For some of the exemplary embodiments described herein, a corresponding device in hardware and optionally with software, firmware, and a combination thereof can be referred to as “circuitry configured or adapted to,” “logic configured or adapted to,” etc. perform a set of operations, steps, methods, processes, algorithms, functions, techniques, etc. on digital and/or analog signals as described herein for the various exemplary embodiments.

Moreover, some exemplary embodiments may include a non-transitory computer-readable storage medium having computer readable code stored thereon for programming a computer, server, appliance, device, processor, circuit, etc. each of which may include a processor to perform functions as described and claimed herein. Examples of such computer-readable storage mediums include, but are not limited to, a hard disk, an optical storage device, a magnetic storage

device, a ROM (Read Only Memory), a PROM (Programmable Read Only Memory), an EPROM (Erasable Programmable Read Only Memory), an EEPROM (Electrically Erasable Programmable Read Only Memory), Flash memory, and the like. When stored in the non-transitory computer readable medium, software can include instructions executable by a processor or device (e.g., any type of programmable circuitry or logic) that, in response to such execution, cause a processor or the device to perform a set of operations, steps, methods, processes, algorithms, functions, techniques, etc. as described herein for the various exemplary embodiments.

### § 3.0 Exemplary Server

Referring to FIG. 4, in an exemplary embodiment, a block diagram illustrates a server **200** which may be used for air traffic control of the UAVs **50**. The server **200** may be a digital computer that, in terms of hardware architecture, generally includes a processor **202**, input/output (I/O) interfaces **204**, a network interface **206**, a data store **208**, and memory **210**. It should be appreciated by those of ordinary skill in the art that FIG. 4 depicts the server **200** in an oversimplified manner, and a practical embodiment may include additional components and suitably configured processing logic to support known or conventional operating features that are not described in detail herein. The components (**202**, **204**, **206**, **208**, and **210**) are communicatively coupled via a local interface **212**. The local interface **212** may be, for example, but not limited to, one or more buses or other wired or wireless connections, as is known in the art. The local interface **212** may have additional elements, which are omitted for simplicity, such as controllers, buffers (caches), drivers, repeaters, and receivers, among many others, to enable communications. Further, the local interface **212** may include address, control, and/or data connections to enable appropriate communications among the aforementioned components.

The processor **202** is a hardware device for executing software instructions. The processor **202** may be any custom made or commercially available processor, a central processing unit (CPU), an auxiliary processor among several processors associated with the server **200**, a semiconductor-based microprocessor (in the form of a microchip or chip set), or generally any device for executing software instructions. When the server **200** is in operation, the processor **202** is configured to execute software stored within the memory **210**, to communicate data to and from the memory **210**, and to generally control operations of the server **200** pursuant to the software instructions. The I/O interfaces **204** may be used to receive user input from and/or for providing system output to one or more devices or components. User input may be provided via, for example, a keyboard, touchpad, and/or a mouse. System output may be provided via a display device and a printer (not shown). I/O interfaces **204** may include, for example, a serial port, a parallel port, a small computer system interface (SCSI), a serial ATA (SATA), a fibre channel, Infiniband, iSCSI, a PCI Express interface (PCI-x), an infrared (IR) interface, a radio frequency (RF) interface, and/or a universal serial bus (USB) interface.

The network interface **306** may be used to enable the server **200** to communicate over a network, such as to a plurality of UAVs **50** over a cell network or the like. The network interface **206** may include, for example, an Ethernet card or adapter (e.g., 10BaseT, Fast Ethernet, Gigabit Ethernet, 10 GbE) or a wireless local area network (WLAN) card or adapter (e.g., 802.11a/b/g/n). The network interface **206** may include address, control, and/or data connections to



enable appropriate communications on the network. A data store **208** may be used to store data. The data store **208** may include any of volatile memory elements (e.g., random access memory (RAM, such as DRAM, SRAM, SDRAM, and the like)), nonvolatile memory elements (e.g., ROM, hard drive, tape, CDROM, and the like), and combinations thereof. Moreover, the data store **208** may incorporate electronic, magnetic, optical, and/or other types of storage media. In one example, the data store **208** may be located internal to the server **200** such as, for example, an internal hard drive connected to the local interface **212** in the server **200**. Additionally, in another embodiment, the data store **208** may be located external to the server **200** such as, for example, an external hard drive connected to the I/O interfaces **204** (e.g., SCSI or USB connection). In a further embodiment, the data store **208** may be connected to the server **200** through a network, such as, for example, a network attached file server.

The memory **210** may include any of volatile memory elements (e.g., random access memory (RAM, such as DRAM, SRAM, SDRAM, etc.)), nonvolatile memory elements (e.g., ROM, hard drive, tape, CDROM, etc.), and combinations thereof. Moreover, the memory **210** may incorporate electronic, magnetic, optical, and/or other types of storage media. Note that the memory **210** may have a distributed architecture, where various components are situated remotely from one another, but can be accessed by the processor **202**. The software in memory **210** may include one or more software programs, each of which includes an ordered listing of executable instructions for implementing logical functions. The software in the memory **210** includes a suitable operating system (O/S) **214** and one or more programs **216**. The operating system **214** essentially controls the execution of other computer programs, such as the one or more programs **216**, and provides scheduling, input-output control, file and data management, memory management, and communication control and related services. The one or more programs **216** may be configured to implement the various processes, algorithms, methods, techniques, etc. described herein.

#### § 4.0 UAV Air Traffic Control System

Referring to FIG. 5, in an exemplary embodiment, a block diagram illustrates functional components of a UAV air traffic control system **300**. The UAV air traffic control system **300** includes a cell network **302** and optionally other wireless networks **304** communicatively coupled to one of more servers **200** and to a plurality of UAVs **50**. The cell network **302** can actually include a plurality of different provider networks, such as AT&T, Verizon, Sprint, etc. The cell network **302** is formed in part with a plurality of cell towers **12**, geographically dispersed and covering the vast majority of the United States. The cell towers **12** are configured to backhaul communications from subscribers. In the UAV air traffic control system **300**, the subscribers are the UAVs **50** (in addition to conventional mobile devices) and the communications is between the UAVs **50** and the servers **200**. The other wireless networks **304** can include, for example, the NAS network, GPS and/or GLONASS, WLAN networks, private wireless networks, or any other wireless networks.

The servers **200** are configured to provide air traffic control and can be deployed in a control center, at a customer premises, in the cloud, or the like. Generally, the servers **200** are configured to receive communications from the UAVs **50** such as for continuous monitoring and of relevant details of each UAV **50** such as location, altitude, speed, direction, function, etc. The servers **200** are further

configured to transmit communications to the UAVs **50** such as for control based on the details, such as to prevent collisions, to enforce policies, to provide navigational control, to actually fly the UAVs **50**, to land the UAVs **50**, and the like. That is, generally, communications from the UAV **50** to the server **200** are for detailed monitoring and communications to the UAV **50** from the server **200** are for control thereof.

#### § 4.1 Data Management

Each UAV **50** is configured with a unique identifier, such as a SIM card or the like. Similar to standard mobile devices **100**, each UAV **50** is configured to maintain an association with a plurality of cell towers **12** based on a current geographic location. Using triangulation or other location identification techniques (GPS, GLONASS, etc.), the location, altitude, speed, and direction of each UAV **50** can be continuously monitored and reported back to the servers **200**. The servers **200** can implement techniques to manage this data in real-time in an automated fashion to track and control all UAVs **50** in a geographic region. For example, the servers **200** can manage and store the data in the data store **208**.

#### § 4.2 Air Traffic Control Functions

The servers **200** are configured to perform air traffic control functionality of the UAV air traffic control system **300**. Specifically, the servers **200** are configured to perform separation assurance, navigation, traffic management, landing, and general control of the UAVs **50**. The separation assurance includes tracking all of the UAVs **50** in flight, based on the monitored data, to ensure adequate separation. The navigation includes maintaining defined airways. The traffic management includes comparing flights planes of UAVs **50** to avoid conflicts and to ensure the smooth and efficient flow of UAVs **50** in flight. The landing includes assisting and control of UAVs **50** at the end of their flight. The general control includes providing real-time data including video and other monitored data and allowing control of the UAV **50** in flight. The general control can also include automated flight of the UAVs **50** through the UAV air traffic control system **300**, such as for autonomous UAVs. Generally, the UAV air traffic control system **300** can include routing and algorithms for autonomous operation of the UAVs **50** based on initial flight parameters. The UAV air traffic control system **300** can control speed, flight path, and altitude for a vast number of UAVs **50** simultaneously.

#### § 5.0 UAV Flight Plans

Referring to FIG. 6, in an exemplary embodiment, a network diagram illustrates various cell sites **10a-10e** deployed in a geographic region **400**. In an exemplary embodiment, the UAV **50** is configured to fly a flight plan **402** in the geographic region **400** while maintaining associations with multiple cell sites **10a-10e** during the flight plan **402**. In an exemplary embodiment, the UAV **50** is constrained only to fly in the geographic region **400** where it has cell coverage. This constraint can be preprogrammed based on predetermining cell coverage. Alternatively, the constraint can be dynamically managed by the UAV **50** based on monitoring its cell signal level in the mobile device **100** hardware. Here, the UAV **50** will alter its path whenever it loses or detects signal degradation to ensure it is always active on the cell network **302**. During the flight plan **402**, the cell sites **10a-10e** are configured to report monitored data to the servers **200** periodically to enable real-time air traffic control. Thus, the communication between the UAVs **50** is bi-directional with the servers **200**, through the associated cell sites **10**.

In an exemplary embodiment, the UAV **50** maintains an association with at least three of the cell sites **10** which perform triangulation to determine the location of the UAV **50**. In addition to the cell sites **10** on the cell network **302**, the UAV **50** can also communicate to the other wireless networks **304**. In an exemplary embodiment, the UAV **50** can maintain its GPS and/or GLONASS location and report that over the cell network **302**. In another exemplary embodiment, the other wireless networks **304** can include satellite networks or the like.

#### § 5.1 Triangulation

Referring to FIG. **7**, in an exemplary embodiment, a map illustrates three cell towers **12** and associated coverage areas **410**, **412**, **414** for describing location determination of the UAV **50**. Typically, for a cell site **10**, in rural locations, the coverage areas **410**, **412**, **414** can be about 5 miles in radius whereas, in urban locations, the coverage areas **410**, **412**, **414** can be about 0.5 to 2 miles in radius. One aspect of the UAV air traffic control system **300** is to maintain a precise location at all time of the UAVs **50**. This can be accomplished in a plurality of ways, including a combination. The UAV air traffic control system **300** can use triangulation based on the multiple cell towers **12**, location identifiers from GPS/GLONASS transmitted over the cell network **402** by the UAVs **50**, sensors in the UAV **50** for determining altitude, speed, etc., and the like.

#### § 6.0 UAV Air Traffic Control Method Utilizing Wireless Networks

Referring to FIG. **8**, in an exemplary embodiment, a flowchart illustrates a UAV air traffic control method **450** utilizing wireless networks. The UAV air traffic control method **450** includes communicating with a plurality of UAVs via a plurality of cell towers associated with the wireless networks, wherein the plurality of UAVs each include hardware and antennas adapted to communicate to the plurality of cell towers, and wherein each of the plurality of UAVs include a unique identifier (step **452**); maintaining data associated with flight of each of the plurality of UAVs based on the communicating (step **454**); and processing the maintained data to perform a plurality of functions associated with air traffic control of the plurality of UAVs (step **456**). The UAV-based method **450** can further include transmitting data based on the processing to one or more of the plurality of UAVs to perform the plurality of functions (step **458**). The plurality of UAVs can be configured to constrain flight based on coverage of the plurality of cell towers. The constrained flight can include one or more of pre-configuring the plurality of UAVs to operate only where the coverage exists, monitoring cell signal strength by the plurality of UAVs and adjusting flight based therein, and a combination thereof.

The maintaining data can include the plurality of UAVs and/or the plurality of cell towers providing location, speed, direction, and altitude. The location can be determined based on a combination of triangulation by the plurality of cell towers and a determination by the UAV based on a location identification network. The plurality of function can include one or more of separation assurance between UAVs; navigation assistance; weather and obstacle reporting; monitoring of speed, altitude, location, and direction; traffic management; landing services; and real-time control. One or more of the plurality of UAVs can be configured for autonomous operation through the air traffic control. The plurality of UAVs can be configured with mobile device hardware configured to operate on a plurality of different cell networks.

#### § 7.0 UAV Air Traffic Control Method Concurrently Utilizing a Plurality of Wireless Networks

Referring to FIG. **9**, in an exemplary embodiment, a flowchart illustrates an Unmanned Aerial Vehicle (UAV) air traffic control method **500** implemented in the UAV **50** during a flight, for concurrently utilizing a plurality wireless networks for air traffic control. The UAV air traffic control method **500** includes maintaining communication with a first wireless network and a second wireless network of the plurality of wireless networks (step **502**); communicating first data with the first wireless network and second data with the second wireless network throughout the flight, wherein one or more of the first data and the second data is provided to an air traffic control system configured to maintain status of a plurality of UAVs in flight and perform control thereof (step **504**); and adjusting the flight based on one or more of the first data and the second data and control from the air traffic control system (step **506**). The first wireless network can provide bidirectional communication between the UAV and the air traffic control system and the second wireless network can support unidirectional communication to the UAV for status indications. The first wireless network can include one or more cellular networks and the second wireless network can include a location identification network. Both the first wireless network and the second wireless network can provide bidirectional communication between the UAV and the air traffic control system for redundancy with one of the first wireless network and the second wireless network operating as primary and another as backup. The first wireless network can provide bidirectional communication between the UAV and the air traffic control system and the second wireless network can support unidirectional communication from the UAV for status indications.

The UAV air traffic control method can further include constraining the flight based on coverage of one or more of the first wireless network and the second wireless network (step **508**). The constrained flight can include one or more of pre-configuring the UAV to operate only where the coverage exists, monitoring cell signal strength by the UAV and adjusting flight based therein, and a combination thereof. The first data can include location, speed, direction, and altitude for reporting to the air traffic control system. The control from the air traffic control system can include a plurality of functions comprising one or more of separation assurance between UAVs; navigation assistance; weather and obstacle reporting; monitoring of speed, altitude, location, and direction; traffic management; landing services; and real-time control. The UAV can be configured for autonomous operation through the air traffic control system.

In another exemplary embodiment, an Unmanned Aerial Vehicle (UAV) adapted for air traffic control via an air traffic control system and via communication to a plurality of wireless networks includes one or more rotors disposed to a body; wireless interfaces including hardware and antennas adapted to communicate with a first wireless network and a second wireless network of the plurality of wireless networks, and wherein the UAV comprises a unique identifier; a processor coupled to the wireless interfaces and the one or more rotors; and memory storing instructions that, when executed, cause the processor to: maintain communication with the first wireless network and the second wireless network via the wireless interfaces; communicate first data with the first wireless network and second data with the second wireless network throughout the flight, wherein one or more of the first data and the second data is provided to an air traffic control system configured to maintain status of

a plurality of UAVs in flight and perform control thereof; and adjust the flight based on one or more of the first data and the second data and control from the air traffic control system. The first wireless network can provide bidirectional communication between the UAV and the air traffic control system and the second wireless network can support unidirectional communication to the UAV for status indications. The first wireless network can include one or more cellular networks and the second wireless network can include a location identification network. Both the first wireless network and the second wireless network can provide bidirectional communication between the UAV and the air traffic control system for redundancy with one of the first wireless network and the second wireless network operating as primary and another as backup.

The first wireless network can provide bidirectional communication between the UAV and the air traffic control system and the second wireless network can support unidirectional communication from the UAV for status indications. The UAV can be configured to constrain the flight based on coverage of one or more of the first wireless network and the second wireless network. The constrained flight can include one or more of pre-configuring the UAV to operate only where the coverage exists, monitoring cell signal strength by the UAV and adjusting flight based therein, and a combination thereof. The first data can include location, speed, direction, and altitude for reporting to the air traffic control system. The control from the air traffic control system can include a plurality of functions comprising one or more of separation assurance between UAVs; navigation assistance; weather and obstacle reporting; monitoring of speed, altitude, location, and direction; traffic management; landing services; and real-time control. The UAV can be configured for autonomous operation through the air traffic control system.

#### § 8.0 Package Delivery Authorization and Management

Referring to FIG. 10, in an exemplary embodiment, a flowchart illustrates a packet delivery authorization and management method 600 utilizing the UAV air traffic control system 300. The method 600 includes communicating with a plurality of UAVs via a plurality of cell towers associated with the wireless networks, wherein the plurality of UAVs each comprise hardware and antennas adapted to communicate to the plurality of cell towers (step 602); maintaining data associated with flight of each of the plurality of UAVs based on the communicating (step 604); processing the maintained data to perform a plurality of functions associated with air traffic control of the plurality of UAVs (step 606); and processing the maintained data to perform a plurality of functions for the delivery application authorization and management for each of the plurality of UAVs (step 608). The maintained data can include location information received and updated periodically from each of the plurality of UAVs, and wherein the location information is correlated to coordinates and altitude. The location information can be determined based on a combination of triangulation by the plurality of cell towers and a determination by the UAV based on a location identification network. The processing for the delivery application authorization and management can include checking the coordinates and the altitude based on a flight plan, for each of the plurality of UAVs. The checking the coordinates and the altitude can further include assuring each of the plurality of UAVs is in a specified flying lane.

The maintained data can include current battery and/or fuel status for each of the plurality of UAVs, and wherein the processing for the delivery application authorization and

management can include checking the current battery and/or fuel status to ensure sufficiency to provide a current delivery, for each of the plurality of UAVs. The maintained data can include photographs and/or video of a delivery location, and wherein the processing for the delivery application authorization and management can include checking the delivery location is clear for landing and/or dropping a package, for each of the plurality of UAVs. The maintained data can include photographs and/or video of a delivery location, and wherein the processing for the delivery application authorization and management comprises, for each of the plurality of UAVs, checking the delivery location for a delivery technique including one of landing, dropping via a tether, dropping to a doorstep, dropping to a mailbox, dropping to a porch, and dropping to a garage. The plurality of UAVs can be configured to constrain flight based on coverage of the plurality of cell towers. The constrained flight can include one or more of pre-configuring the plurality of UAVs to operate only where the coverage exists, monitoring cell signal strength by the plurality of UAVs and adjusting flight based therein, and a combination thereof.

#### § 8.1 Package Delivery Authorization and Management Via the Air Traffic Control System

In another exemplary embodiment, the air traffic control system 300 utilizing wireless networks and concurrently supporting delivery application authorization and management includes the processor and the network interface communicatively coupled to one another; and the memory storing instructions that, when executed, cause the processor to: communicate, via the network interface, with a plurality of UAVs via a plurality of cell towers associated with the wireless networks, wherein the plurality of UAVs each include hardware and antennas adapted to communicate to the plurality of cell towers; maintain data associated with flight of each of the plurality of UAVs based on the communicating; process the maintained data to perform a plurality of functions associated with air traffic control of the plurality of UAVs; and process the maintained data to perform a plurality of functions for the delivery application authorization and management for each of the plurality of UAVs.

#### § 8.2 Landing Authorization and Management

In another exemplary aspect, the air traffic control system 300 can be configured to provide landing authorization and management in addition to the aforementioned air traffic control functions and package delivery authorization and management. The landing authorization and management can be at the home base of the UAV, at a delivery location, and/or at a pickup location. The air traffic control system 300 can control and approve the landing. For example, the air traffic control system 300 can receive photographs and/or video from the UAV 50 of the location (home base, delivery location, pickup location). The air traffic control system 300 can make a determination based on the photographs and/or video, as well as other parameters such as wind speed, temperature, etc. to approve the landing.

#### § 9.0 Separation Assurance Via the Air Traffic Control System

In another exemplary aspect, the air traffic control system 300 can be used to for separation assurance through altitude and flying lane coordination in addition to the aforementioned air traffic control functions, package delivery authorization and management, landing authorization and management, etc. As the air traffic control system 300 has monitored data from various UAVs 50, the air traffic control system 300 can keep track of specific flight plans as well as cause changes in real time to ensure specific altitude and

vector headings, i.e., a flight lane. For example, the air traffic control system 300 can include a specific geography of interest and there can be adjacent air traffic control systems 300 that communicate to one another and share some overlap in the geography for handoffs. The air traffic control systems 300 can make assumptions on future flight behavior based on the current data and then direct UAVs 50 based thereon. The air traffic control system 300 can also communicate with commercial aviation air traffic control systems for limited data exchange to ensure the UAVs 50 do not interfere with commercial aircraft or fly in no-fly zones.

#### § 10.0 Flying Lane Management

Referring to FIG. 11, in an exemplary embodiment, a diagram illustrates a flight path of an associated flying lane 700 of a UAV 50 from takeoff to landing. The flying lane 700 covers all flight phases which include preflight, takeoff, en route, descent, and landing. Again, the flying lane 700 includes coordinates (e.g., GPS, etc.), altitude, speed, and heading at a specified time. As described herein, the UAV 50 is configured to communicate to the air traffic control system 300, during all of the flight phases, such as via the networks 302, 304. The air traffic control system 300 is configured to monitor and manage/control the flying lane 700 as described herein. The objective of this management is to avoid collisions, avoid obstructions, avoid flight in restricted areas or areas with no network 302, 304 coverage, etc.

During preflight, the UAV 50 is configured to communicate with the air traffic control system 300 for approvals (e.g., flight plan, destination, the flying lane 700, etc.) and notification thereof, for verification (e.g., weather, delivery authorization, etc.), and the like. The key aspect of the communication during the preflight is for the air traffic control system 300 to become aware of the flying lane 700, to ensure it is open, and to approve the UAV 50 for takeoff. Other aspects of the preflight can include the air traffic control system 300 coordinating the delivery, coordinating with other systems, etc. Based on the communication from the UAV 50 (as well as an operator, scheduler, etc.), the air traffic control system 300 can perform processing to make sure the flying lane 700 is available and if not, to adjust accordingly.

During takeoff, the UAV 50 is configured to communicate with the air traffic control system 300 for providing feedback from the UAV 50 to the air traffic control system 300. Here, the air traffic control system 300 can store and process the feedback to keep up to date with the current situation in airspace under control, for planning other flying lanes 700, etc. The feedback can include speed, altitude, heading, etc. as well as other pertinent data such as location (e.g., GPS, etc.), temperature, humidity, the wind, and any detected obstructions during takeoff. The detected obstructions can be managed by the air traffic control system 300 as described herein, i.e., temporary obstructions, permanent obstructions, etc.

Once airborne, the UAV is en route to the destination and the air traffic control system 300 is configured to communicate with the air traffic control system 300 for providing feedback from the UAV 50 to the air traffic control system 300. Similar to takeoff, the communication can include the same feedback. Also, the communication can include an update to the flying lane 700 based on current conditions, changes, etc. A key aspect is the UAV 50 is continually in data communication with the air traffic control system 300 via the networks 302, 304.

As the destination is approached, the air traffic control system 300 can authorize/instruct the UAV 50 to begin the descent. Alternatively, the air traffic control system 300 can

pre-authorize based on reaching a set point. Similar to takeoff and en route, the communication in the descent can include the same feedback. The feedback can also include information about the landing spot as well as processing by the air traffic control system 300 to change any aspects of the landing based on the feedback. Note, the landing can include a physical landing or hovering and releasing cargo.

In various embodiments, the air traffic control system 300 is expected to operate autonomously or semi-autonomously, i.e., there is not a live human operator monitoring each UAV 50 flight. This is an important distinction between conventional air traffic control for aircraft and the air traffic control system 300 for UAVs 50. Specifically, it would not be feasible to manage UAVs 50 with live operators. Accordingly, the air traffic control system 300 is configured to communicate and manage during all flight phases with a large quantity of UAVs 50 concurrently in an automated manner.

In an exemplary embodiment, the objective of the flying lane management through the air traffic control system 300 is to manage deliveries efficiently while secondarily to ensure collision avoidance. Again, this aspect is different from conventional air traffic control which focuses first and foremost of collision avoidance. This is not to say that collision avoidance is minimized, but rather it is less important since the UAVs 50 can themselves maintain a buffer from one another based on the in-flight detection. To achieve the management, the air traffic control system 300 can implement various routing techniques to allow the UAVs 50 to use associated flying lanes 700 to arrive and deliver packages. Thus, one aspect of flying lane management, especially for delivery applications, is efficiency since efficient routing can save time, fuel, etc. which is key for deliveries.

Referring to FIG. 12, in an exemplary embodiment, a diagram illustrates obstruction detection by the UAV 50 and associated changes to the flying lane 700. One aspect of flying lane management is detected obstruction management. Here, the UAV 50 has taken off, have the flying lane 700, and is in communication with the air traffic control system 300. During the flight, either the UAV 50 detects an obstacle 710 or the air traffic control system 300 is notified from another source of the obstacle 710 and alerts the UAV 50. Again, the UAVs 50 are flying at lower altitudes, and the obstacle 710 can be virtually anything that is temporary such as a crane, a vehicle, etc. or that is permanent such as a building, tree, etc. The UAV 50 is configured, with assistance and control from the air traffic control system 300 to adjust the flying lane 700 to overcome the obstacle 710 as well as add a buffer amount, such as 35 feet or any other amount for safety.

Referring to FIG. 13, in an exemplary embodiment, a flowchart illustrates a flying lane management method 750 via an air traffic control system communicatively coupled to a UAV via one or more wireless networks. In an exemplary embodiment, the flying lane management method 750 includes initiating communication to the one or more UAVs at a preflight stage for each, wherein the communication is via one or more cell towers associated with the one or more wireless networks, wherein the plurality of UAVs each include hardware and antennas adapted to communicate to the plurality of cell towers (step 752); determining a flying lane for the one or more UAVs based on a destination, current air traffic in a region under management of the air traffic control system, and based on detected obstructions in the region (step 754); and providing the flying lane to the one or more UAVs are an approval to takeoff and fly along

the flying lane (step 756). The flying lane management method 750 can further include continuing the communication during flight on the flying lane and receiving data from the one or more UAVs, wherein the data includes feedback during the flight (step 758); and utilizing the feedback to

update the flying lane, to update other flying lanes, and to manage air traffic in the region (step 760). During the flight, the feedback includes speed, altitude, and heading, and the feedback can further include one or more of temperature, humidity, wind, and detected obstructions.

The flying lane management method 750 can further include providing updates to the flying lane based on the feedback and based on feedback from other devices. The flying lane management method 750 can further include, based on the feedback, determining the one or more UAVs at ready to descend or fly to the destination and providing authorization to the one or more UAVs for a descent. The flying lane management method 750 can further include, based on the feedback, detecting a new obstruction; and one of updating the flying lane based on adjustments made by the one or more UAVs due to the new obstruction and providing an updated flying lane due to the new obstruction. The adjustments and/or the updated flying lane can include a buffer distance from the new obstruction. The new obstruction can be detected by the one or more UAVs based on hardware thereon and communicated to the air traffic control system. The air traffic control system can be adapted to operate autonomously.

In another exemplary embodiment, an air traffic control system communicatively coupled to one or more Unmanned Aerial Vehicles (UAVs) via one or more wireless networks adapted to perform flying lane management includes a network interface and one or more processors communicatively coupled to one another; and memory storing instructions that, when executed, cause the one or more processors to: initiate communication to the one or more UAVs at a preflight stage for each, wherein the communication is via one or more cell towers associated with the one or more wireless networks, wherein the plurality of UAVs each include hardware and antennas adapted to communicate to the plurality of cell towers; determine a flying lane for the one or more UAVs based on a destination, current air traffic in a region under management of the air traffic control system, and based on detected obstructions in the region; and provide the flying lane to the one or more UAVs are an approval to take off and fly along the flying lane. The instructions, when executed, can further cause the one or more processors to: continue the communication during flight on the flying lane and receiving data from the one or more UAVs, wherein the data include feedback during the flight; and utilize the feedback to update the flying lane, to update other flying lanes, and to manage air traffic in the region.

During the flight, the feedback includes speed, altitude, and heading, and the feedback can further include one or more of temperature, humidity, wind, and detected obstructions. The instructions, when executed, can further cause the one or more processors to: provide updates to the flying lane based on the feedback and based on feedback from other devices. The instructions, when executed, can further cause the one or more processors to: based on the feedback, determine the one or more UAVs at ready to descend or fly to the destination and providing authorization to the one or more UAVs for a descent. The instructions, when executed, can further cause the one or more processors to: based on the feedback, detect a new obstruction; and one of update the flying lane based on adjustments made by the one or more

UAVs due to the new obstruction and provide an updated flying lane due to the new obstruction. The adjustments and/or the updated flying lane can include a buffer distance from the new obstruction. The new obstruction can be detected by the one or more UAVs based on hardware thereon and communicated to the air traffic control system. The air traffic control system can be adapted to operate autonomously.

§ 11.0 Air Traffic Control Monitoring Systems and Methods

Referring to FIG. 14, in an exemplary embodiment, a block diagram illustrates functional components of a consolidated UAV air traffic control monitoring system 300A. The monitoring system 300A is similar to the UAV air traffic control system 300 described herein. Specifically, the monitoring system 300A includes the cell network 302 (or multiple cell networks 302) as well as the other wireless networks 304. The one or more servers 200 are communicatively coupled to the networks 302, 304 in a similar manner as in the UAV air traffic control system 300 as well as the UAVs 50 communication with the servers 200. Additionally, the monitoring system 300A includes one or more consolidated servers 200A which are communicatively coupled to the servers 200.

The consolidated servers 200A are configured to obtain a consolidated view of all of the UAVs 50. Specifically, the UAVs 50 are geographically distributed as are the networks 302, 304. The servers 200 provide geographic or zone coverage. For example, the servers 200 may be segmented along geographic boundaries, such as different cities, states, etc. The consolidated servers 200A are configured to provide a view of all of the servers 200 and their associated geographic or zone coverage. Specifically, the consolidated servers 200A can be located in a national Air Traffic Control center. From the consolidated servers 200A, any air traffic control functions can be accomplished for the UAVs 50. The consolidated servers 200A can aggregate data on all of the UAVs 50 based on multiple sources, i.e., the servers 200, and from multiple networks 302, 304.

Thus, from the consolidated servers 200A, UAV traffic can be managed from a single point. The consolidated servers 200A can perform any of the air traffic control functions that the servers 200 can perform. For example, the consolidated servers 200A can be used to eliminate accidents, minimize delay and congestion, etc. The consolidated servers 200A can handle connectivity with hundreds or thousands of the servers 200 to manage millions or multiple millions of UAVs 50. Additionally, the consolidated servers 200A can provide an efficient Graphical User Interface (GUI) for air traffic control.

Referring to FIG. 15, in an exemplary embodiment, a screen shot illustrates a Graphical User Interface (GUI) providing a view of the consolidated UAV air traffic control monitoring system. Specifically, the GUI can be provided by the consolidated servers 200A to provide visualization, monitoring, and control of the UAVs 50 across a wide geography, e.g., state, region, or national. In FIG. 15, the GUI provides a map visualization at the national level, consolidating views from multiple servers 200. Various circles are illustrated with shading, gradients, etc. to convey information such as congestion in a local region.

A user can drill-down such as by clicking any of the circles or selecting any geographic region to zoom in. The present disclosure contemplates zooming between the national level down to local or even street levels to view individual UAVs 50. The key aspect of the GUI is the information display is catered to the level of UAV 50 traffic. For example, at the national level, it is not possible to

display every UAV **50** since there are orders of magnitude more UAVs **50** than airplanes. Thus, at higher geographic levels, the GUI can provide a heat map or the like to convey levels of UAV **50** congestion. As the user drills-down to local geographies, individual UAVs **50** can be displayed.

Using the GUI, the consolidated servers **200A**, and the servers **200**, various air traffic control functions can be performed. One aspect is that control can be high-level (coarse) through individual-level (fine) as well as in-between. That is, control can be at a large geographic level (e.g., city or state), at a local level (city or smaller), and at an individual UAV **50** level. The high-level control can be performed via single commands through the consolidated server **200A** that are propagated down to the servers **200** and to the UAVs **50**. Examples of high-level control include no-fly zones, congestion control, traffic management, hold patterns, and the like. Examples of individual-level control include flight plan management; separation assurance; real-time control; monitoring of speed, altitude, location, and direction; weather and obstacle reporting; landing services; and the like.

In addition to the communication from the consolidated servers **200A** to the UAVs **50**, such as through the servers **200**, for air traffic control functions, there can be two-way communication as well. In an exemplary embodiment, the UAVs **50** are configured to provide a first set of data to the servers **200**, such as speed, altitude, location, direction, weather and obstacle reporting. The servers **200** are configured to provide a second set of data to the consolidated servers **200A**, such as a summary or digest of the first data. This hierarchical data handling enables the consolidated servers **200A** to handle nationwide control of millions of UAVs **50**.

For example, when there is a view at the national level, the consolidated servers **200A** can provide summary information for regions, such as illustrated in FIG. **15**. This is based on the second set of data which can provide a summary view of the GUI, such as how many UAVs **50** are in a region. When there is a drill-down to a local level, the consolidated servers **200A** can obtain more information from the servers, i.e., the first set of data, allowing the consolidated servers **200A** to act in a similar manner as the servers **200** for local control.

Referring to FIG. **16**, in an exemplary embodiment, a flowchart illustrates a UAV air traffic control and monitor method **800**. The method **800** includes communicating with a plurality of servers each configured to communicate with a plurality of UAVs in a geographic or zone coverage (step **802**); consolidating data from the plurality of servers to provide a visualization of a larger geography comprising a plurality of geographic or zone coverages (step **804**); providing the visualization via a Graphical User Interface (GUI) (step **806**); and performing one or more functions via the GUI for air traffic control and monitoring at any of a high-level and an individual UAV level (step **808**). The visualization can include a heat map of congestion at the larger geography and a view of individual UAVs via a drill-down. For the individual UAV level, the consolidating the data can include obtaining a first set of data and, for the high-level, the consolidating the data can include obtaining a second set of data which is a summary or digest of the first set of data. The first set of data can include speed, altitude, location, direction, weather and obstacle reporting from individual UAVs.

For the individual UAV level, the air traffic control and monitoring can include any of flight plan management; separation assurance; real-time control; monitoring of speed,

altitude, location, and direction; weather and obstacle reporting; landing services, and wherein, for the high-level, the air traffic control and monitoring can include any of no-fly zones, congestion control, traffic management, and hold patterns. The plurality of UAVs can be configured to constrain flight based on coverage of a plurality of cell towers, wherein the constrained flight can include one or more of pre-configuring the plurality of UAVs to operate only where the coverage exists, monitoring cell signal strength by the plurality of UAVs and adjusting flight based therein, and a combination thereof. One or more of the plurality of UAVs are configured for autonomous operation through the air traffic control. The plurality of UAVs each can include circuitry adapted to communicate via a plurality of cell networks to the plurality of servers. The plurality of cell networks can include a first wireless network and a second wireless network each provide bidirectional communication between the UAV and the plurality of servers for redundancy with one of the first wireless network and the second wireless network operating as primary and another as a backup.

In another exemplary embodiment, an Unmanned Aerial Vehicle (UAV) air traffic control and monitoring system includes a network interface and one or more processors communicatively coupled to one another; and memory storing instructions that, when executed, cause the one or more processors to: communicate with a plurality of servers each configured to communicate with a plurality of UAVs in a geographic or zone coverage; consolidate data from the plurality of servers to provide a visualization of a larger geography comprising a plurality of geographic or zone coverages; provide the visualization via a Graphical User Interface (GUI); and perform one or more functions via the GUI for air traffic control and monitoring at any of a high-level and an individual UAV level.

In a further exemplary embodiment, a non-transitory computer-readable medium includes instructions that, when executed, cause one or more processors to perform steps of: communicating with a plurality of servers each configured to communicate with a plurality of UAVs in a geographic or zone coverage; consolidating data from the plurality of servers to provide a visualization of a larger geography comprising a plurality of geographic or zone coverages; providing the visualization via a Graphical User Interface (GUI); and performing one or more functions via the GUI for air traffic control and monitoring at any of a high-level and an individual UAV level.

#### § 12.0 Obstruction Detection, Identification, and Management Systems and Methods

Referring to FIGS. **17** and **18**, in an exemplary embodiment, block diagrams illustrate the UAV air traffic control system **300** describing functionality associated with obstruction detection, identification, and management with FIG. **17** describing data transfer from the UAVs **50** to the servers **200** and FIG. **18** describing data transfer to the UAVs **50** from the servers **200**. As described herein, obstructions include, without limitation, other UAVs **50** based on their flight plan and objects at or near the ground at height above ground of several hundred feet. Again, the UAVs **50** typically fly at low altitudes such as 100'-500' and obstruction management is important based on this low level of flight.

The obstructions can be stored and managed in an obstruction database (DB) **820** communicatively coupled to the servers **200** and part of the UAV air traffic control system **300**. Obstructions can be temporary or permanent and managed accordingly. Thus, the DB **820** can include an entry for each obstruction with location (e.g., GPS coordinates), size

(height), and permanence. Temporary obstructions can be ones that are transient in nature, such as a scaffold, construction equipment, other UAVs 50 in flight, etc. Permanent obstructions can be buildings, power lines, cell towers, geographic (mountains), etc. For the permanence, each entry in the DB 820 can either be marked as permanent or temporary with a Time to Remove (TTR). The TTR can be how long the entry remains in the DB 820. The permanence is determined by the servers 200 as described herein.

The obstruction detection, identification, and management is performed in the context of the UAV air traffic control system 300 described herein with communication between the UAVs 50 and the servers 200 via the wireless networks 302, 304. FIGS. 17 and 18 illustrate functionality in the UAV air traffic control system 300 with FIGS. 17 and 18 separate to show different data flow and processing.

In FIG. 17, the UAVs 50 communicates to the servers 200 through the wireless networks 302, 304. Again, as described herein, the UAVs 50 have advanced data capture capabilities, such as video, photos, location coordinates, altitude, speed, wind, temperature, etc. Additionally, some UAVs 50 can be equipped with radar to provide radar data surveying proximate landscape. Collectively, the data capture is performed by data capture equipment associated with the UAVs 50.

Through the data capture equipment, the UAVs 50 are adapted to detect potential obstructions and detect operational data (speed, direction, altitude, heading, location, etc.). Based on one or more connections to the wireless networks 302, 304, the UAVs 50 are adapted to transfer the operational data to the servers 200. Note, the UAV 50 can be configured to do some local processing and transmit summaries of the operational data to reduce the transmission load on the wireless networks 302, 304. For example, for speed, heading, etc., the UAVs 50 can transmit delta information such that the servers 200 can track the flight plan. Note, the transmission of the operational data is performed throughout the flight such that the servers 200 can manage and control the UAVs 50.

For obstructions, the UAVs 50 can capture identification data, photos, video, etc. In an exemplary embodiment, the UAVs 50 are provided advanced notification of obstructions (in FIG. 18) and capable of local data processing of the identification data to verify the obstructions. If the local data processing determines an obstruction is already known, i.e., provided in a notification from the servers 200, the UAV 50 does not require any further processing or data transfer of the identification data, i.e., this obstruction is already detected. On the other hand, if the UAV 50 detects a potential obstruction, i.e., one that it has not been notified of, based on the local data processing, the UAV 50 can perform data transfer of the identification data to the servers 200.

The servers 200 are configured to manage the obstruction DB 820, namely to update the entries therein. The servers 200 are configured to receive operational data from the UAVs 50 under control for management thereof. Specifically, the servers 200 are configured to manage the flight plans of the UAVs 200, and, in particular with respect to obstructions, for advanced notification of future obstructions in the flight plan.

The servers 200 are configured to receive the detection of potential obstructions. The UAVs 200 can either simply notify the servers 200 of a potential obstruction as well as provide the identification data for the servers 200 to perform identification and analysis. Upon receipt of any data from the UAVs 200 related to obstructions (a mere notification, actual photos, etc.), the servers 200 are configured to cor-

relate this data with the DB 820. If the data correlates to an entry that exists in the DB 820, the servers 200 can update the entry if necessary, e.g., update any information related to the obstruction such as last seen date.

If the servers 200 detect the potential obstruction does not exist in the DB 820, the servers 200 are configured to add an entry in the DB 820, perform identification if possible from the identification data, and potentially instruct a UAV 50 to identify in the future. For example, if the servers 200 can identify the potential obstruction from the identification data, the servers 200 can create the DB 820 entry and populate it with the identified data. The servers 200 can analyze the identification data, as well as request human review, using pattern recognition to identify what the obstruction is, what its characteristics are (height, size, permanency, etc.).

If the servers 200 do not have enough identification data, the servers 200 can instruct the identifying UAV 50 or another UAV 50 in proximity in the future to obtain specific identification data for the purposes of identification.

In FIG. 18, the servers 200 continue to manage the DB 820, both for populating/managing entries as well as to provide notifications of obstructions in the flight plans of each of the UAVs 50. Specifically, the servers 200 are configured to keep track of the flight plans of all of the UAVs 50 under its control. As part of this tracking, the servers 200 are configured to correlate the operational data to derive the flight plan and to determine any obstructions from the DB 820 in the flight plan. The servers 200 are configured to provide notifications and/or instructions to the UAVs 50 based on upcoming obstructions.

Additionally, the servers 200 are configured to provide instructions to UAVs 50 to capture identification data for potential obstructions that are not yet identified. Specifically, the servers 200 can instruct the UAVs 50 on what exact data to obtain, e.g., pictures, video, etc., and from what angle, elevation, direction, location, etc. With the identification data, the servers 200 can perform various processes to pattern match the pictures with known objects for identification. In case an obstruction is not matched, it can be flagged for human review. Also, human review can be performed based on successful matches to grade the performance and to further improve pattern matching techniques. Identification of the obstruction is important for permanency determinations. For example, a new high-rise building is permanent whereas a construction crane is temporary.

For the TTR, temporary obstructions are automatically removed in the DB 820 based on this entry. In an exemplary embodiment, the TTR can be a flag with a specified time. In another exemplary embodiment, the TTR can be a flag which requires removal if the next UAV 50 passing near the obstruction fails to detect and report it.

Referring to FIG. 19, in an exemplary embodiment, a flowchart illustrates an obstruction detection and management method 900 implemented through the UAV air traffic control system 300 for the UAVs 50. The obstruction detection and management method 900 includes receiving UAV data from a plurality of UAVs, wherein the UAV data comprises operational data for the plurality of UAVs and obstruction data from one or more UAVs (step 902); updating an obstruction database based on the obstruction data (step 904); monitoring a flight plan for the plurality of UAVs based on the operational data (step 906); and transmitting obstruction instructions to the plurality of UAVs based on analyzing the obstruction database with their flight plan (step 908).

The obstruction data can include an indication of a potential obstruction which was not provided to a UAV in the obstruction instructions. The obstruction data can include a confirmation of an obstruction based on the obstruction instructions, and wherein the updating can include noting any changes in the obstruction based on the confirmation. The obstruction instructions can include a request to a UAV to perform data capture of a potential obstruction, wherein the obstruction data can include photos and/or video of the potential obstruction, and wherein the updating can include identifying the potential obstruction based on the obstruction data.

The obstruction database can include entries of obstructions with their height, size, location, and a permanency flag comprising either a temporary obstruction or a permanent obstruction. The permanency flag can include a Time To Remove (TTR) for the temporary obstruction which is a flag with a specified time or a flag which requires removal if the next UAV passing near the temporary obstruction fails to detect and report it. The operational data can include a plurality of speed, location, heading, and altitude, and wherein the flight plan is determined from the operational data. The plurality of UAVs fly under about 1000'.

In another exemplary embodiment, an Unmanned Aerial Vehicle (UAV) air traffic control and monitoring system for obstruction detection and management includes a network interface and one or more processors communicatively coupled to one another; and memory storing instructions that, when executed, cause the one or more processors to receive UAV data from a plurality of UAVs, wherein the UAV data includes operational data for the plurality of UAVs and obstruction data from one or more UAVs; update an obstruction database based on the obstruction data; monitor a flight plan for the plurality of UAVs based on the operational data; and transmit obstruction instructions to the plurality of UAVs based on analyzing the obstruction database with their flight plan.

A non-transitory computer-readable medium comprising instructions that, when executed, cause one or more processors to perform steps of: receiving Unmanned Aerial Vehicle (UAV) data from a plurality of UAVs, wherein the UAV data includes operational data for the plurality of UAVs and obstruction data from one or more UAVs; updating an obstruction database based on the obstruction data; monitoring a flight plan for the plurality of UAVs based on the operational data; and transmitting obstruction instructions to the plurality of UAVs based on analyzing the obstruction database with their flight plan.

Although the present disclosure has been illustrated and described herein with reference to preferred embodiments and specific examples thereof, it will be readily apparent to those of ordinary skill in the art that other embodiments and examples may perform similar functions and/or achieve like results. All such equivalent embodiments and examples are within the spirit and scope of the present disclosure, are contemplated thereby, and are intended to be covered by the following claims.

What is claimed is:

1. An obstruction detection and management method comprising:

in an Air Traffic Control (ATC) system comprising one or more servers communicatively coupled to a plurality of Unmanned Aerial Vehicles (UAVs) via one or more wireless networks, receiving UAV data from a plurality of UAVs, wherein the UAV data comprises operational data for the plurality of UAVs and obstruction data from one or more UAVs;

updating an obstruction database based on the obstruction data, wherein the obstruction database comprises entries of obstructions with their height, size, location, and a permanency flag comprising either a temporary obstruction or a permanent obstruction;

monitoring a flight plan for the plurality of UAVs based on the operational data; and

transmitting obstruction instructions to the plurality of UAVs based on analyzing the obstruction database with their flight plan.

2. The obstruction detection and management method of claim 1, wherein the obstruction data comprises an indication of a potential obstruction which was not provided to a UAV in the obstruction instructions.

3. The obstruction detection and management method of claim 1, wherein the obstruction data comprises a confirmation of an obstruction based on the obstruction instructions, and wherein the updating comprises noting any changes in the obstruction based on the confirmation.

4. The obstruction detection and management method of claim 1, wherein the obstruction instructions comprise a request to a UAV to perform data capture of a potential obstruction, wherein the obstruction data comprises photos and/or video of the potential obstruction, and wherein the updating comprises identifying the potential obstruction based on the obstruction data.

5. The obstruction detection and management method of claim 1, wherein the permanency flag comprises a Time To Remove (TTR) for the temporary obstruction which is a flag with a specified time or a flag which requires removal if the next UAV passing near the temporary obstruction fails to detect and report it.

6. The obstruction detection and management method of claim 1, wherein the operational data comprises a plurality of speed, location, heading, and altitude, and wherein the flight plan is determined from the operational data.

7. The obstruction detection and management method of claim 1, wherein the plurality of UAVs fly under about 1000'.

8. An Unmanned Aerial Vehicle (UAV) air traffic control and monitoring system for obstruction detection and management, the system comprising:

a network interface and one or more processors communicatively coupled to one another, wherein the network interface is communicatively coupled to one or more wireless networks for communication with a plurality of UAVs; and

memory storing instructions that, when executed, cause the one or more processors to:

receive UAV data from the plurality of UAVs, wherein the UAV data comprises operational data for the plurality of UAVs and obstruction data from one or more UAVs;

update an obstruction database based on the obstruction data, wherein the obstruction database comprises entries of obstructions with their height, size, location, and a permanency flag comprising either a temporary obstruction or a permanent obstruction;

monitor a flight plan for the plurality of UAVs based on the operational data; and

transmit obstruction instructions to the plurality of UAVs based on analyzing the obstruction database with their flight plan.

9. The system of claim 8, wherein the obstruction data comprises an indication of a potential obstruction which was not provided to a UAV in the obstruction instructions.



27

10. The system of claim 8, wherein the obstruction data comprises a confirmation of an obstruction based on the obstruction instructions, and wherein updates to the obstruction database comprise noting any changes in the obstruction based on the confirmation.

11. The system of claim 8, wherein the obstruction instructions comprise a request to a UAV to perform data capture of a potential obstruction, wherein the obstruction data comprises photos and/or video of the potential obstruction, and wherein updates to the obstruction database comprise identifying the potential obstruction based on the obstruction data.

12. The system of claim 8, wherein the permanency flag comprises a Time To Remove (TTR) for the temporary obstruction which is a flag with a specified time or a flag which requires removal if the next UAV passing near the temporary obstruction fails to detect and report it.

13. The system of claim 8, wherein the operational data comprises a plurality of speed, location, heading, and altitude, and wherein the flight plan is determined from the operational data.

14. The system of claim 8, wherein the plurality of UAVs fly under about 1000'.

15. A non-transitory computer-readable medium comprising instructions that, when executed, cause one or more processors, in an Air Traffic Control (ATC) system comprising one or more servers communicatively coupled to a plurality of Unmanned Aerial Vehicles (UAVs) via one or more wireless networks, to perform steps of:

receiving Unmanned Aerial Vehicle (UAV) data from a plurality of UAVs, wherein the UAV data comprises

28

operational data for the plurality of UAVs and obstruction data from one or more UAVs;

updating an obstruction database based on the obstruction data, wherein the obstruction database comprises entries of obstructions with their height, size, location, and a permanency flag comprising either a temporary obstruction or a permanent obstruction;

monitoring a flight plan for the plurality of UAVs based on the operational data; and

transmitting obstruction instructions to the plurality of UAVs based on analyzing the obstruction database with their flight plan.

16. The non-transitory computer-readable medium of claim 15, wherein the obstruction data comprises an indication of a potential obstruction which was not provided to a UAV in the obstruction instructions.

17. The non-transitory computer-readable medium of claim 15, wherein the obstruction data comprises a confirmation of an obstruction based on the obstruction instructions, and wherein the updating comprises noting any changes in the obstruction based on the confirmation.

18. The non-transitory computer-readable medium of claim 15, wherein the obstruction instructions comprise a request to a UAV to perform data capture of a potential obstruction, wherein the obstruction data comprises photos and/or video of the potential obstruction, and wherein the updating comprises identifying the potential obstruction based on the obstruction data.

\* \* \* \* \*