



US006502787B1

(12) **United States Patent**
Barrett

(10) **Patent No.:** **US 6,502,787 B1**
(45) **Date of Patent:** **Jan. 7, 2003**

(54) **CONVERTIBLE VERTICAL TAKE-OFF AND LANDING MINIATURE AERIAL VEHICLE**

(75) Inventor: **Ronald Martin Barrett**, Auburn, AL (US)

(73) Assignees: **Micro Autonomous Systems LLC**, Del Mar, CA (US); **Singapore Technologies Dynamics PTE LTD**, Singapore (SG)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/082,814**

(22) Filed: **Feb. 22, 2002**

(51) **Int. Cl.**⁷ **B64C 27/20**

(52) **U.S. Cl.** **244/23 A; 244/7 B; 244/73 R**

(58) **Field of Search** **244/7 B, 23 A, 244/23 D, 34 A, 73 R**

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,065,932 A * 11/1962 Herrmann 244/15

3,138,349 A * 6/1964 Piasecki 224/230
5,295,643 A * 3/1994 Ebbert et al. 244/12.2
5,516,060 A * 5/1996 McDonnell 244/207
6,082,675 A * 7/2000 Woodall et al. 244/120

* cited by examiner

Primary Examiner—Robert P. Swiatek

(74) *Attorney, Agent, or Firm*—John L. Rogitz

(57) **ABSTRACT**

A vertical take-off and landing miniature aerial vehicle includes an upper fuselage segment and a lower fuselage segment that extend in opposite directions from a rotor guard assembly. A rotor rotates within the rotor guard assembly between the fuselage segments. Plural turning vanes extend from the rotor guard assembly beneath the rotor. Moreover, plural grid fins extend radially from the lower fuselage segment below the turning vanes. The aerial vehicle is capable of taking off and landing vertically. During flight, the aerial vehicle can hover and transition between a horizontal flight mode and a vertical flight mode using the grid fins.

30 Claims, 5 Drawing Sheets




Fig. 1




Fig. 2




Fig. 3




Fig. 4





Fig. 5






Fig. 6

CONVERTIBLE VERTICAL TAKE-OFF AND LANDING MINIATURE AERIAL VEHICLE

TECHNICAL FIELD OF THE INVENTION

The present invention relates generally to aircraft.

BACKGROUND OF THE INVENTION

In the past, attempts have been made to combine fixed wing airplanes with helicopters to achieve vertical take-off and landing (VTOL) capabilities. Examples include the Lockheed XFV-1 and the Convair XFY-1 Pogo.

The Pogo, for example, was thirty-one feet (31') long with a twenty-six (26') wide delta wing. A large vertical stabilizer above the wing was matched by an equally sized ventral fin below which could be jettisoned for an emergency horizontal landing. The first double transition from vertical flight to horizontal flight and back to a vertical landing by the Pogo was made on Nov. 2, 1954. The Pogo was flown until November 1956. The Lockheed XFV-1 never made a vertical takeoff and landing. The world's first operational vertical/short take-off and landing (VSTOL), the Harrier jump jet, was introduced in the 1960's and was used successfully in several military campaigns.

Fixed wing airplanes and helicopters have completely permeated worldwide commerce and warfare. Presently, they are used to move civilians, soldiers, goods, supplies, etc. to nearly any place in the world. Moreover, fixed wing airplanes and helicopters are used to quickly transport injured persons or organs to and from hospitals. Militaries, law enforcement agencies, and intelligence agencies also use them to chase criminals, target, spy, and gather any other type of information. VTOL and VSTOL aircrafts have been used infrequently for specific military missions, but these types of aircrafts have never achieved the widespread success of conventional fixed wing airplanes and helicopters due in part to the difficulty in powering and controlling them.

Smaller unmanned fixed wing airplanes and helicopters have proved useful for surveillance, lethal and non-lethal ordinance delivery, crowd control, targeting, etc. However, a relatively small, unmanned aircraft that can transition between vertical flight (like a helicopter) and horizontal flight (like a fixed wing airplane), has not been provided. Thus, the present invention recognizes that there is a need for a relatively small, unmanned aerial vehicle that can transition between a vertical flight mode and a horizontal flight mode and sustain either mode of flight.

SUMMARY OF THE INVENTION

An aerial vehicle includes a rotor guard assembly. An upper fuselage segment extends upwardly from the rotor guard assembly and a lower fuselage segment extends downwardly from the rotor guard assembly. Moreover, a rotor rotates within the rotor guard assembly between the upper fuselage segment and the lower fuselage segment. A turning vane flap extends from the rotor guard assembly below the rotor and a grid fin extends radially from the lower fuselage segment below the turning vane flap. The grid fin allows the aerial vehicle to transition between a vertical flight mode and a horizontal flight mode.

In a preferred embodiment, the aerial vehicle further includes an undercarriage that extends downwardly from the outer periphery of the rotor guard assembly. Also, a powerplant is installed in the lower fuselage segment adjacent to

the rotor guard assembly. The power plant has a shaft that extends between the lower fuselage segment and the upper fuselage segment and the rotor is rigidly attached to the shaft.

Preferably, a fuel tank is installed in the upper fuselage segment adjacent to the rotor guard assembly. The fuel tank includes a bladder installed therein. The bladder is inflatable to pressurize fuel in the fuel tank. In a preferred embodiment, a fuel line leads from the fuel tank to the powerplant and is routed partially external to the rotor guard assembly. Also, a high pressure line leads from the powerplant to the bladder within the fuel tank and is routed partially external to the rotor guard assembly.

In a preferred embodiment, an upper cap is installed on the upper fuselage segment. One or more sensors are disposed within the upper cap. The sensor can be an optical sensor, an infrared (IR) sensor, a radio frequency (RF) sensor, a magnetic field sensor, a chemical sensor, an acoustic sensor, a motion sensor, etc. Additionally, one or more cameras can be disposed within the upper cap. The camera can be a video camera, a still camera, a digital video camera, a digital still camera, a color video camera, a black-and-white video camera, a thermal imaging camera, an infrared video camera, a night vision camera, etc.

Preferably, the aerial vehicle also includes a microprocessor within the upper fuselage segment. A transceiver is connected to the microprocessor and extends through the upper cap. In a preferred embodiment, the aerial vehicle further includes a global positioning satellite (G.P.S.) system within the upper fuselage segment. The G.P.S. system is also connected to the microprocessor.

In another aspect of the present invention, an aerial vehicle includes means for launching the vehicle vertically and means for flying the vehicle vertically. In this aspect, the aerial vehicle includes means for transitioning the vehicle from vertical flight to horizontal flight.

In still another aspect of the present invention, an aerial vehicle includes a fuselage that defines a longitudinal axis. A rotor guard assembly surrounds a portion of the fuselage in a plane perpendicular to the longitudinal axis. Moreover, a rotor rotates within the rotor guard assembly in a plane perpendicular to the longitudinal axis. In this aspect, a turning vane flap extends downwardly from the rotor guard. The turning vane flap has one end hingedly attached to the rotor guard and the turning vane flap rotates about a radial axis that extends radially from the longitudinal axis. Also in this aspect, a grid fin extends radially from the fuselage below the turning vane flap. The grid fin rotates about a central axis that extends radially from the longitudinal axis.

The present invention will now be described, by way of example, with reference to the accompanying drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side plan view of the aerial vehicle of the present invention;

FIG. 2 is a cross-section view of the aerial vehicle taken along line 2—2 in FIG. 1;

FIG. 3 is a cross-section view of the aerial vehicle taken along line 3—3 in FIG. 1;

FIG. 4 is a cross-section view of the aerial vehicle taken along line 4—4 in FIG. 1;

FIG. 5 is a block diagram of a fuel system; and

FIG. 6 is a block diagram of a control system.

DESCRIPTION OF AN EMBODIMENT OF THE INVENTION

Referring initially to FIG. 1, an aerial vehicle is shown and generally designated **10**. FIG. 1 shows that the aerial

vehicle **10** includes an upper fuselage segment **12** and a lower fuselage segment **14** that are connected by a rotor guard assembly **16**. In a preferred embodiment, the fuselage segments **12, 14** are hollow tubular members which are open at each end. Preferably, the fuselage segments **12, 14** are made from a graphite epoxy composite, but can be made from any other suitable material well known in the art.

As mentioned above, the lower end of the upper fuselage segment **12** and the upper end of the lower fuselage segment **14** are engaged with the rotor guard assembly **16**. FIG. **1** further shows that the aerial vehicle **10** includes an undercarriage that, in this non-limiting, exemplary embodiment, comprises six legs **18** that extend downwardly from the outer periphery of the rotor guard assembly **16**. The legs **18** are equally spaced around the outer periphery of the rotor guard assembly **16** and are angled with respect to a longitudinal axis **20** defined by the aerial vehicle **10**.

It is to be understood that the undercarriage can be fixed or retractable and can be configured to allow the aerial vehicle **10** to alight on surfaces of varying contour. As described above, the undercarriage is mounted on the outer periphery of the rotor guard assembly **16** and is structurally coupled to the turning vanes, described below, to allow loads on the undercarriage to be transferred to the upper fuselage segment **12** and the lower fuselage segment **14**. Preferably, the undercarriage is made from a graphite epoxy composite, but can be made from any other suitable material well known in the art. The undercarriage can also include a quick release mechanism to allow it to drop-off after the aerial vehicle **10** is launched, e.g., for a one-way mission. Moreover, the undercarriage can be designed to absorb impacts caused by landing, e.g., using elastomeric polymers, shock-absorbing foam hinges, shock absorbing feet, etc.

As shown in FIG. **1**, an upper cap **22** is installed on the upper end of the upper fuselage segment **12**. A sensor bay, described in detail below, is established within the upper cap **22**. A lower cap **24** is disposed on the lower end of the lower fuselage segment **14**. As shown the upper cap **22** and the lower cap **24** are hemispherically shaped, but they can be any aerodynamically appropriate shape. It is to be understood that the lower cap **24** provides a smooth fairing off which boattail drag can be significantly reduced when the aerial vehicle is in airplane flight mode, e.g., like a conventional fixed-wing airplane. The lower cap **24** also protects the empennage **26**, described in detail below, the lower fuselage segment **14**, and the components within the lower fuselage segment **14** and empennage **26** from damage caused by dirt, debris, exhaust gases, impact, etc. The lower cap **24** is preferably made from an energy absorbing material. Thus, if any of the legs **18** are damaged during landing, the lower cap **20** can absorb the impact.

In a preferred embodiment, the aerial vehicle **10** includes plural, preferably six, turning vane flaps **28**. The turning vane flaps **28** are equally spaced around the rotor guard assembly **16** and are placed beneath the rotor, described below. As described in detail below, each turning vane flap **28** is hinged attached to a turning vane within the rotor guard assembly **16**. Also, each turning vane flap **28** is aligned with a respective leg **18** extending from the rotor guard assembly **16**. Moreover, a respective roll control servo **30**, e.g., a rotary electro-mechanical servo-actuator, is connected to each turning vane flap **28** and controls the rotation thereof. Each roll control servo **30** is rigidly attached to the outer periphery of the rotor guard assembly **16** and includes a shaft **32** that is attached to a respective turning vane flap **28**. It is to be understood that the roll control servos **30** are issued identical commands so as to roll the aerial vehicle **10**.

Specifically, each turning vane flap **28** is rotated about its hinged end, through an axis extending radially from the longitudinal axis **20**, in order to generate rolling moments around the longitudinal axis **20**. Accordingly, the turning vane flaps **28** are designed to counter atmospheric effects and changes in rolling moments due to inertial loading or unloading.

In a preferred embodiment, the turning vane flaps **28** are fabricated from a structurally stiff material which is strong and light, e.g., a graphite epoxy composite, to allow for rapid transitions and increase the speed and responsiveness of the aerial vehicle **10** during rolling maneuvers. Preferably, the width of each turning vane flap **28** is such that the inner edge of each flap **28** is a greater distance from the central longitudinal axis **20** of the aerial vehicle **10** than the outer periphery of the empennage **26**. Otherwise, the below-described grid fins that comprise the empennage **26** might counteract the motion of the aerial vehicle caused by the turning vane flaps **28**.

FIG. **1** further shows that the aerial vehicle **10** can include a remote control unit **34**. As shown, the remote control unit **34** can include plural control buttons **36** and a joy stick **38**. Thus, the buttons **36** and the joy stick **28** can be used to control the flight of the aerial vehicle **10**.

Referring to FIG. **2**, the aerial vehicle **10** is shown with the fuselage segments **12, 14**, the caps **22, 24**, and the rotor guard assembly **16** cross-sectioned to reveal the interior components of the aerial vehicle **10**. FIG. **2** shows that the rotor guard assembly **16** includes plural upper turning vanes **40** and plural lower turning vanes **42** that extend radially from a generally cylindrical rotor guard hub **44** to a generally cylindrical rotor guard wall **46**. As shown, the vanes **40, 42** are integrally formed with the rotor guard hub **44** and the rotor guard wall **46**, but it can be appreciated that the vanes **40, 42**, the hub **44**, and the wall **46** can be formed separately and then attached to each other by a means well known in the art such as chemical welding. The lower end of the upper fuselage segment **12** and the upper end of the lower fuselage segment **14** are disposed within the rotor guard hub **44**. Thus, the fuselage segments **12, 14** are supported by the rotor guard assembly **16**.

It is to be understood that the rotor guard assembly **16** lends safety to the aerial vehicle and observers or objects in close proximity to the aerial vehicle **10**. The rotor guard assembly **16** is designed so that lateral strike loads can be absorbed thereby during close-quarters hovering maneuvers. The rotor guard assembly **16** also increases the efficiency of the aerial vehicle **10** in that tip-effects of the rotor, described below, are reduced. It can be appreciated that the rotor guard assembly **16** can be lined with a rub strip to further reduce tip losses and it can be lined with anechoic materials to absorb acoustic energy. Further, the rotor guard assembly **16** can be penetrated and/or perforated for acoustic signature amelioration and accommodation of subsystem components. The rotor guard assembly **16** can also be fabricated from foil-thickness materials or it can have a thickness that is substantial enough to allow the rotor guard assembly **16** to house ancillary payloads.

FIG. **2** shows a powerplant **48** installed within the lower fuselage segment **14**. It is to be understood that the powerplant **48** can be a micro turbine, a rotary engine, any type of internal combustion engine, or any type of electric motor. In this non-limiting, exemplary embodiment the powerplant **48** is an internal combustion engine. As shown, the powerplant **48** includes a shaft **50** that extends perpendicularly into the rotor guard assembly **16** within the space established

between the ends of the fuselage segments **12**, **14**. A rotor **52** is rigidly attached to the shaft **50** and rotates perpendicularly to the longitudinal axis **20** within the rotor guard assembly **16**. It is to be understood that the rotor **52** can have any number of blades and blade chords. Moreover the rotor **52** can be made of any suitable structural material well known in the art. Preferably, the rotor **52** extends from the center of the shaft **50** outward to the inner periphery of the rotor guard wall **46** in order to reduce tip losses which are normally encountered by free rotors. In a preferred embodiment the rotor **52** has a diameter from four inches to ten inches (4"-10"), but it can be as large as six feet (6') in diameter.

A preferably cylindrical fuel tank **54** is disposed in the upper fuselage segment **12** above the rotor **46**. A fuel line **56** leads from the fuel tank **54**, through the upper fuselage segment **12**, through the rotor guard hub **44**, along an upper turning vane **40**, along the rotor guard wall **46**, along a lower turning vane **42**, through the rotor guard hub **44**, through the lower fuselage segment **14**, and into the powerplant **48**.

In a preferred embodiment, the fuel tank **54** includes a sealed bladder **58** that is pressurized by an external gas source, e.g., the exhaust manifold of the powerplant **48**, described below. It is to be appreciated that the bladder **58** ensures consistent flow of pressurized fuel to the powerplant **48**. As shown, a pressure line **60** extends from the powerplant **48** to the bladder **58** and is routed thereto much like the fuel line **56** is routed from the fuel tank **54** to the powerplant **48**. Preferably, the fuel tank **54** is located as close to the center of gravity of the aerial vehicle **10** as possible. Thus, as the fuel level within the fuel tank **54** changes during flight, the location of the center of gravity of the aerial vehicle will not significantly change.

As shown in FIG. 2, a sensor bay **62** is established within the upper cap **22** and an avionics bay **64** is established within the upper end of the upper fuselage segment **12** beneath the sensor bay **62**. FIG. 2 shows that a microprocessor **66** is disposed within the avionics bay **64**. Moreover, at least one sensor **68** and at least one camera **70** are disposed within the sensor bay **62**. A transceiver **72** extends through the upper cap **22**. The sensor **68** can be any type of sensor, e.g., an optical sensor, an infrared (IR) sensor, a radio frequency (RF) sensor, a magnetic field sensor, a chemical sensor, an acoustic sensor, a motion sensor, etc. Also, the camera **70** can be any type of camera, e.g., a video camera, a still camera, a digital video camera, a digital still camera, a color video camera, a black-and-white video camera, a thermal imaging camera, an infrared video camera, a night vision camera, etc.

Referring now to FIG. 3, in a preferred embodiment the rotor guard assembly **16** includes six upper turning vanes **40**. It is to be understood that the preferred rotor guard assembly **16** also includes six lower turning vanes **42** (FIG. 2). Each lower turning vane **42** is aligned with a respective upper turning vane **40**.

FIG. 4 shows details of the empennage **26**. As shown, in this non-limiting, exemplary embodiment, the empennage **26** includes four identical grid fins **74** radially spaced around the lower end of the lower fuselage segment **14**. In a preferred embodiment, each grid fin **74** includes plural hollow cells **76** through which air flows during flight of the aerial vehicle **10**. As shown, a single respective rotary electromechanical servo-actuator **78** is connected to each grid fin **74** via a shaft **80**. Opposite servos **78** receive identical signals so that the grid fins **74** are actuated in unified pairs. Each grid fin **74** rotates through an axis that extends radially from the longitudinal axis **20**.

It is to be understood that the powerplant **48** rotates the rotor **52** which provides lift for the aerial vehicle **10**. With the grid fins **74** aligned with the air flow caused by the rotor **52**, the aerial vehicle **10** can take-off vertically and land vertically. During flight, the turning vanes **28** can be rotated in unison about their hinged ends, e.g., in response to a signal from the remote control unit **34**, in order to change the direction of air flowing across the turning vanes **28** and thus, rotate the aerial vehicle **10** about its longitudinal axis **20**. If the aerial vehicle **10** is vertically oriented, this motion is considered yaw. On the other hand, if the aerial vehicle **10** is horizontal, this motion is considered roll.

The grid fins **74** can be used to alter the direction of air flowing therethrough and alter the direction in which the aerial vehicle **10** is traveling. Thus, the grid fins **74** can be used to redirect the aerial vehicle **10** during vertical flight or horizontal flight or completely transition the aerial vehicle **10** between a vertical flight mode and a horizontal flight mode.

Referring to FIG. 5, one non-limiting exemplary fuel system is shown and generally designated **100**. FIG. 5 shows that the fuel system **100** includes the fuel tank **54** (FIG. 2) and bladder **58** (FIG. 2) that are connected to the powerplant **48** (FIG. 2) via the fuel line **56** (FIG. 2) and the pressure line **60** (FIG. 2).

As shown in FIG. 5, the bladder **58** is preferably connected to an exhaust manifold **102** by the pressure line **60**. However, it is to be understood that the bladder **58** can be connected to a crankcase **104** as indicated by dashed line **106**. FIG. 5 shows that the fuel system **100** can include a fuel filter **108** and a fuel regulator **110** installed along the fuel line **56** between the fuel tank **54** and the engine **48**. Preferably, the fuel filter **108** is installed between the fuel tank **54** and the fuel regulator **110**. The fuel regulator **110** is used to prevent excessive fuel pressure during start-up, idle, or shut-down, and thus, to prevent engine flooding or hydro-lock. Moreover, the fuel filter **108** is used to ensure that the fuel delivered to the powerplant **48** is clean and free of debris that can adversely affect the performance and life span of the powerplant **48** and the fuel regulator **110**.

In general, the fuel filter **108** is situated so that it can be removed, inspected, and, if necessary, replaced during routine maintenance of the aerial vehicle **10**. On the other hand, the fuel regulator **110** is not typically replaced on a regular basis and accordingly, is mounted in a location within the upper fuselage segment **12** that is not as easily accessible as the fuel filter **108**.

Referring now to FIG. 6, one exemplary, non-limiting control system is shown and generally designated **150**. FIG. 6 shows that the control system **150** includes a microprocessor **122** to which the subcomponents, described below, are attached. As shown, the microprocessor **122** is connected to the grid fin servos **78** (FIG. 4) via electrical lines **124** and **126**. The grid fin servos **78** are connected in pairs so that opposite pairs of grid fin servos **78** receive the same signals. The microprocessor **122** is also connected to the roll control servos **30** (FIG. 1) via electrical line **128**. The roll control servos **30** are connected so that all six roll control servos **30** receive identical signals simultaneously.

As shown in FIG. 6, the microprocessor **122** is connected to the powerplant **48**, e.g., the accelerator **130** and ignition system **132**, via electrical lines **134** and **136** in order to control the operation thereof. The microprocessor **122** is also connected to the sensor **68** (FIG. 2), the camera **70** (FIG. 2), and the transceiver **72** by electrical lines **138**, **140** and **142**. As shown, the microprocessor **122** can also be connected to a global positioning satellite (G.P.S.) system **144** by electrical line **146**.

Accordingly, with the above described control system **120** the microprocessor **122** can be used to control the flight of the aerial vehicle **10** by controlling the operation of the grid fin servos **78**, the roll control servos **30**, the engine accelerator **130** and ignition system **132** in response to remote control signals from the remote **34**. Or, the microprocessor **122** can control the flight of the aerial vehicle **10** in response to a pre-programmed flight plan. The microprocessor **122** can also send and receive information via the transceiver **72**. This information can be control signals from the remote control unit **34**, sensor signals, video or stills from the camera **70**, or any other information relevant to the flight of the aerial vehicle **10**.

With the configuration of structure and method described above, it can be appreciated that the aerial vehicle **10** can take off and land vertically. Moreover, during flight the aerial vehicle **10** can hover while vertical and transition between a vertical flight mode and a horizontal flight mode.

While the particular CONVERTIBLE VERTICAL TAKE-OFF AND LANDING MINIATURE AERIAL VEHICLE as herein shown and described in detail is fully capable of attaining the above-described objects of the invention, it is to be understood that it is the presently preferred embodiment of the present invention and thus, is representative of the subject matter which is broadly contemplated by the present invention, that the scope of the present invention fully encompasses other embodiments which may become obvious to those skilled in the art, and that the scope of the present invention is accordingly to be limited by nothing other than the appended claims, in which reference to an element in the singular is not intended to mean "one and only one" unless explicitly so stated, but rather "one or more." All structural and functional equivalents to the elements of the above-described preferred embodiment that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the present claims. Moreover, it is not necessary for a device or method to address each and every problem sought to be solved by the present invention, for it is to be encompassed by the present claims. Furthermore, no element, component, or method step in the present disclosure is intended to be dedicated to the public regardless of whether the element, component, or method step is explicitly recited in the claims. No claim element herein is to be construed under the provisions of 35 U.S.C. section 112, sixth paragraph, unless the element is expressly recited using the phrase "means for."

What is claimed is:

- 1.** An aerial vehicle, comprising:
 - a rotor guard assembly;
 - an upper fuselage segment extending upwardly from the rotor guard assembly;
 - a lower fuselage segment extending downwardly from the rotor guard assembly;
 - at least one rotor rotating within the rotor guard assembly between the upper fuselage segment and the lower fuselage segment;
 - at least one turning vane flap extending from the rotor guard assembly below the rotor; and
 - at least one grid fin extending radially from the lower fuselage segment below the turning vane flap, the grid fin allowing the aerial vehicle to transition between a vertical flight mode and a horizontal flight mode.
- 2.** The aerial vehicle of claim **1**, further comprising:
 - an undercarriage extending downwardly from the outer periphery of the rotor guard assembly.

- 3.** The aerial vehicle of claim **2**, further comprising:
 - a powerplant installed in the lower fuselage segment adjacent to the rotor guard assembly, the power plant having a shaft extending between the lower fuselage segment and the upper fuselage segment, the rotor being rigidly attached to the shaft.
- 4.** The aerial vehicle of claim **3**, further comprising:
 - a fuel tank installed in the upper fuselage segment adjacent to the rotor guard assembly.
- 5.** The aerial vehicle of claim **4**, wherein the fuel tank includes a bladder installed therein, the bladder being inflatable to pressurize fuel in the fuel tank.
- 6.** The aerial vehicle of claim **5**, further comprising:
 - a fuel line leading from the fuel tank to the powerplant, the fuel line being routed at least partially external to the rotor guard assembly.
- 7.** The aerial vehicle of claim **6**, further comprising:
 - a high pressure line leading from the powerplant to the bladder within the fuel tank, the high pressure line being routed at least partially external to the rotor guard assembly.
- 8.** The aerial vehicle of claim **7**, further comprising:
 - an upper cap installed on the upper fuselage segment.
- 9.** The aerial vehicle of claim **8**, further comprising:
 - at least one sensor disposed within the upper cap.
- 10.** The aerial vehicle of claim **9**, wherein the sensor is at least one of the following: an optical sensor, an infrared (IR) sensor, a radio frequency (RF) sensor, a magnetic field sensor, a chemical sensor, an acoustic sensor, and a motion sensor.
- 11.** The aerial vehicle of claim **10**, further comprising:
 - at least one camera disposed within the upper cap.
- 12.** The aerial vehicle of claim **11**, wherein the camera is at least one of the following: a video camera, a still camera, a digital video camera, a digital still camera, a color video camera, a black-and-white video camera, a thermal imaging camera, an infrared video camera, and a night vision camera.
- 13.** The aerial vehicle of claim **12**, further comprising:
 - at least one microprocessor within the upper fuselage segment.
- 14.** The aerial vehicle of claim **13**, further comprising:
 - at least one transceiver connected to the microprocessor and extending through the upper cap.
- 15.** The aerial vehicle of claim **14**, further comprising:
 - at least one global positioning satellite system within the upper fuselage segment and connected to the microprocessor.
- 16.** An aerial vehicle, comprising:
 - a fuselage defining a longitudinal axis;
 - a rotor guard assembly surrounding at least a portion of the fuselage in a plane perpendicular to the longitudinal axis;
 - at least one rotor rotating within the rotor guard assembly in a plane perpendicular to the longitudinal axis;
 - at least one turning vane flap extending downwardly from the rotor guard, the turning vane flap having one end hingedly attached to the rotor guard, the turning vane flap rotating about a radial axis extending radially from the longitudinal axis; and
 - at least one grid fin extending radially from the fuselage below the, turning vane flap, the grid fin rotating about a central axis extending radially from the longitudinal axis.

9

- 17. The aerial vehicle of claim 16, further comprising:
an undercarriage extending downwardly from the outer
periphery of the rotor guard assembly.
- 18. The aerial vehicle of claim 17, further comprising:
a powerplant installed in the fuselage adjacent to the rotor
guard assembly, the power plant having a shaft extend-
ing into the rotor guard assembly, the rotor being
rigidly attached to the shaft.
- 19. The aerial vehicle of claim 18, further comprising:
a fuel tank installed in the fuselage adjacent to the rotor
guard assembly opposite the power plant.
- 20. The aerial vehicle of claim 19, wherein the fuel tank
includes a bladder installed therein, the bladder being inflat-
able to pressurize fuel in the fuel tank.
- 21. The aerial vehicle of claim 20, further comprising:
a fuel line leading from the fuel tank to the powerplant,
the fuel line being routed at least partially external to
the rotor guard assembly.
- 22. The aerial vehicle of claim 21, further comprising:
a high pressure line leading from the powerplant to the
bladder within the fuel tank, the high pressure line
being routed at least partially external to the rotor guard
assembly.

10

- 23. The aerial vehicle of claim 22, further comprising:
an upper cap installed on an upper end defined by the
fuselage.
- 24. The aerial vehicle of claim 23, further comprising:
at least one sensor disposed within the upper cap.
- 25. The aerial vehicle of claim 24, wherein the sensor is
at least one of the following: an optical sensor, an infrared
(IR) sensor, a radio frequency (RF) sensor, a magnetic field
sensor, a chemical sensor, and an acoustic sensor.
- 26. The aerial vehicle of claim 25, further comprising:
at least one camera disposed within the upper cap.
- 27. The aerial vehicle of claim 26, wherein the camera is
at least one of the following: a video camera, a still camera,
a digital video camera, a digital still camera, a color video
camera, a black-and-white video camera, a thermal imaging
camera, an infrared video camera, and a night vision camera.
- 28. The aerial vehicle of claim 27, further comprising:
at least one microprocessor within the fuselage.
- 29. The aerial vehicle of claim 28, further comprising:
at least one transceiver connected to the microprocessor
and extending through the upper cap.
- 30. The aerial vehicle of claim 29, further comprising:
at least one global positioning satellite system within the
fuselage segment and connected to the microprocessor.

* * * * *