



US006576880B2

(12) **United States Patent**
Martorana et al.

(10) **Patent No.:** **US 6,576,880 B2**
(45) **Date of Patent:** ***Jun. 10, 2003**

(54) **FLYER ASSEMBLY**

(75) Inventors: **Richard T. Martorana**, Andover, MA (US); **Jamie Anderson**, Watertown, MA (US); **Simon Mark Spearing**, Newton, MA (US); **Seth Kessler**, Cambridge, MA (US); **Brent Appleby**, Holliston, MA (US); **Edward Bergmann**, Hopkinton, MA (US); **Sean George**, Boston, MA (US); **Steven Jacobson**, Shrewsbury, MA (US); **Donald Fyler**, Needham, MA (US); **Mark Drela**, Cambridge, MA (US); **Gregory Kirkos**, Somerville, MA (US); **William McFarland, Jr.**, Watertown, MA (US)

(73) Assignee: **The Charles Stark Draper Laboratory, Inc.**, Cambridge, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/150,726**

(22) Filed: **May 17, 2002**

(65) **Prior Publication Data**

US 2003/0089820 A1 May 15, 2003

Related U.S. Application Data

(62) Division of application No. 09/690,000, filed on Oct. 12, 2000, now Pat. No. 6,392,213.

(51) **Int. Cl.**⁷ **B64C 3/51**

(52) **U.S. Cl.** **244/3.1; 244/3.24; 244/13; 244/49; 89/1.816**

(58) **Field of Search** 244/3.1, 3.11, 244/3.15, 3.21, 3.24-3.3, 36, 49, 13; 102/348, 501, 503, 380, 206; 89/1.809, 1.81, 1.815, 1.816, 1.819

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,695,555 A * 10/1972 Chadwick 244/3.14
4,240,601 A * 12/1980 Reed 244/160

(List continued on next page.)

OTHER PUBLICATIONS

Carl Dietrich, On line Resume, Feb. 5, 1997 (WASP II Project summer 1998).*



Primary Examiner—Galen L. Barefoot

(74) *Attorney, Agent, or Firm*—McDermott, Will & Emery

(57) **ABSTRACT**

A flyer assembly is adapted for launching with, transit in, and deployment from an artillery shell having a central void region extending along a ballistic shell axis. The flyer assembly includes a jettisonable shroud and a flyer. The shroud extends along a shroud axis, and is positionable within the central void region with the shroud axis substantially parallel to the shell axis. The flyer is adapted to withstand a launch acceleration force along a flyer axis when in a first state, and to effect aerodynamic flight when in a second state. When in the first state, the flyer is positionable within the shroud with the flyer axis parallel to the shroud axis and the shell axis. The flyer includes a body member disposed about the flyer axis, and a foldable wing assembly mounted to the body member. The wing assembly is configurable in a folded state characterized by a plurality of nested wing segments when the flyer is in the first state. The wing assembly is configurable in an unfolded state characterized by a substantially uninterrupted aerodynamic surface when the flyer is in the second state. The flyer assembly is adapted to be launched from a ballistic delivery system such as an artillery cannon, and can thus reach a target quickly, without expending system energy stored within the flyer. During launch, the flyer is coupled to the shroud so as to maintain a portion of the flyer in tension during an acceleration of the flyer along the flyer axis resulting from the launch. The flyer assembly is adapted to withstand the high g-load and high temperature environments of a cannon launch, and can tolerate a set-back g load of about 16,000 g.

46 Claims, 13 Drawing Sheets



U.S. PATENT DOCUMENTS

4,296,894 A	10/1981	Schnabele et al.	244/3.27	6,000,340 A	* 12/1999	Small	102/380
4,410,151 A	10/1983	Hoppner et al.	244/63	6,119,976 A	* 9/2000	Rogers	244/13
4,752,052 A	6/1988	Galvin	244/3.29	6,144,899 A	* 11/2000	Babb et al.	701/3
5,456,427 A	* 10/1995	Greenhalgh	244/138 R	6,179,248 B1	* 1/2001	Putman et al.	244/36
5,467,681 A	* 11/1995	Lieberman	244/301	6,260,797 B1	* 7/2001	Palmer	244/49

* cited by examiner




FIG. 1A




FIG. 1B






FIG. 2




FIG. 3B




FIG. 3A




FIG. 4




FIG. 5







FIG. 6




FIG. 7




FIG. 8(b)




FIG. 8(a)





FIG. 9(a)




FIG. 9(b)




FIG. 10B




FIG. 10D




FIG. 10A




FIG. 10C




FIG. 11

FLYER ASSEMBLY**RELATED APPLICATIONS**

The following application is a divisional application of U.S. patent application Ser. No. 09/690,000, filed Oct. 12, 2000, now U.S. Pat. No. 6,392,213.

CROSS-REFERENCE TO RELATED APPLICATIONS

Not Applicable

REFERENCE TO MICROFICHE APPENDIX

Not Applicable

FIELD OF THE INVENTION

The present invention relates generally to flyer assemblies, and more particularly to flyer assemblies adapted to be launched from artillery cannons for surveillance and other time-critical missions.

BACKGROUND OF THE INVENTION

Reconnaissance and surveillance missions are used in military as well as civilian operations in order to identify and evaluate potential targets, and to provide target information as needed. For example, in a military operation, surveillance missions can provide timely information about moving military targets in air, land or sea, or can provide battle damage assessment, following a sortie. They can also identify non-targets such as refugees.

For time-critical moving targets, it is necessary that tactical observational tools be able to provide identification and/or imaging of the targets within the fastest response time possible. Prior art unmanned air vehicles (UAVs) suffer, however, from a slow response time and in many cases are not able to reach areas of interest as fast as required by the mission.

It is time consuming and difficult to launch, operate and transport prior art UAVs. Special troops and facilities are needed to launch, transport, and in some situations recover prior art UAVs. Generally, a specialized platoon is required in order to launch prior art UAVs. Most prior art UAVs are launched like traditional aircraft from the ground, either with runways or with variants such as rails, sling-shots or similar devices. This requires flat land in a safe terrain, as well as significant set-up and support time. The UAV must also be fueled, which takes up additional time. There is considerable risk involved in transporting observational tools such as UAVs to locations that will provide the most valuable observational information, because of the probability that the tool will be detected, intercepted and/or destroyed by hostile forces.

Prior art UAVs require special storage, shipping, and handling, since prior art UAVs are stored as aircraft, requiring maintenance after use. Often a vehicle, such as a HUMVEE, is required for launch, flight support, or both. Finally, prior art UAVs are expensive to build and maintain, which constrains their numbers. Cost is not limited to the hardware of the UAVs, but additional cost is involved in training and maintaining the support troops.

Prior art UAVs use their own fuel or some other type of own system energy to fly to the area of interest. Using system energy for travel reduces the energy available for endurance or functionality when the UAV is in an overhead position with respect to the target. The sizes and locations of

the areas to which UAVs can be sent are limited by such a reduction in available energy.

Ballistically launching the UAV to the desired location would avoid the problems described above. Ballistic launching would greatly improve response time. Ballistic launching would also obviate the need to expend system energy of the UAV until the UAV is near the target, thereby maximizing the energy available to the UAV for endurance or functionality. Greater flexibility would be available for the sizes and locations of the areas to which the UAVs can be sent. Existing tactical UAVs are not, however, constructed to survive the high g-forces that develop during a ballistic launch.

It is an object of this invention to overcome the above described disadvantages of prior art flyers.

SUMMARY OF THE INVENTION

The present invention features a flyer assembly adapted for launching with, transit in, and deployment from an artillery shell having a central void region extending along a ballistic shell axis. The flyer assembly includes a jettisonable shroud, and a flyer. The shroud extends along a shroud axis, and is positionable within the central void region of the artillery shell, with the shroud axis substantially parallel to the shell axis. The flyer is adapted, when in a first state, to withstand a launch acceleration force along a flyer axis. In the first state, the flyer is positionable within the shroud with the flyer axis parallel to the shroud axis and the shell axis. The flyer is adapted, when in a second state, to effect aerodynamic flight. The flyer may be an unmanned air vehicle.

The flyer includes a body member disposed about the flyer axis, and a foldable wing assembly mounted to the body member. The wing assembly is configurable in a folded state characterized by a plurality of nested wing segments when the flyer is in the first state. The wing assembly is configurable in an unfolded state characterized by a substantially uninterrupted aerodynamic surface when the flyer is in the second state. When the wing assembly is in the folded state, a span-wise axis of each wing segment is substantially parallel to the flyer axis. When the wing assembly is in the unfolded state, the span-wise axis of each wing segment is substantially transverse to the flyer axis. In one embodiment, the flyer further includes a foldable tail assembly mounted to the body member.

The flyer is adapted to be coupled to the shroud so as to maintain a portion of the flyer in tension during an acceleration of the flyer along the flyer axis resulting from the launch acceleration force. In one embodiment, the shroud includes a support mechanism disposed at an interior surface of the shroud. The flyer includes a bulkhead for coupling to the support mechanism of the shroud. The flyer can be hung by the bulkhead on the support mechanism of the shroud, thereby maintaining a portion of the flyer in tension and preventing buckling. In one embodiment, the support mechanism is a hanger. In one embodiment, the body member of the flyer includes a nose section, a mid-body section, and a tail section. Bulkheads are disposed at the junctions between the nose section and the mid-body section, and between the mid-body and the tail section. The mid-body section and the tail section of the flyer are maintained in tension during an acceleration of the flyer along the axis resulting from the launch.

The flyer is adapted to survive the high-g and high temperature environments of a cannon launch. In a preferred form, the flyer is adapted to withstand a set-back accelera-

tion of about 16,000 g along the flyer axis. In one embodiment, the flyer is constructed from a composite material. Because the flyer is launched by a ballistic delivery system, the flyer is operable to reach a predetermined ballistic range at a predetermined average ground speed without expending system energy stored within the flyer. In one embodiment, the predetermined ballistic range is about 22 km, and the predetermined average ground speed is about 22 km/min.

In one embodiment, the body member of the flyer includes a central void region, and the wing assembly is mounted on an outer surface of the body member exterior to the central void region. The central void region is adapted to store system energy to be dispensed during an aerodynamic flight of the flyer.

In one embodiment, the flyer assembly is adapted for expulsion from the artillery shell after reaching a predetermined ballistic range. The weight of the shroud adds to a weight of the flyer so as to provide an optimal ballistic range for the flyer assembly. In one embodiment, the optimal ballistic range is about 22 km. In one embodiment, the flyer assembly comprises a mechanism for decelerating and de-spinning the flyer assembly subsequent to an expulsion of the flyer assembly from the shell. In one embodiment, the deceleration mechanism includes a parachute. The deceleration mechanism may include a two-stage parachute.

The shroud protects the flyer during the gun launch, and during the expulsion from the shell. The shroud also protects the flyer during spinning of the flyer assembly after the expulsion. In one embodiment, during an acceleration of the flyer along the flyer axis resulting from the launch, an outermost one of the plurality of wing segments is placed under compression, and all but the outermost one of the plurality of wing segments is placed under tension. An inner surface of the shroud abuts an outermost one of the plurality of wing segments of the foldable wing assembly, and provides a radial restraining force that counters a centrifugal force arising from a spinning of the flyer assembly, thereby preventing a buckling of one or more of the plurality of wing segments.

The shroud includes a separation mechanism for jettisoning the shroud subsequent to the expulsion of the flyer assembly from the shell and upon a reaching of the expelled flyer assembly of a predetermined altitude. In one embodiment, the separation mechanism includes charges embedded within the shroud. The shroud may be substantially cylindrical.

The present invention also features a method for deploying a flyer. The method includes positioning the flyer within a jettisonable shroud so that an axis of the flyer is parallel to an axis of the shroud. The method includes positioning the shroud within a central void region in an artillery shell so that the shroud axis is parallel to a ballistic shell axis. The method includes launching the shell from a ballistic delivery assembly. The method includes expelling the shroud and the flyer from the shell. The method further includes deploying the flyer so as to configure in an unfolded state a foldable wing assembly mounted to a body member of the flyer. The step of deploying the flyer may include the step of configuring in an unfolded state a foldable tail assembly mounted to a body member of the flyer.

The method further includes the steps of decelerating and de-spinning the shroud and the flyer after expelling the shroud and the enclosed flyer from the shell. The steps of decelerating and de-spinning the shroud and the flyer may include the step of deploying a parachute. The method may

include the step of separating the shroud from the flyer after expelling the shroud and the flyer from the shell.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1(a) illustrates a flyer assembly, including a shroud and a flyer enclosed within the shroud.

FIG. 1(b) illustrates an artillery shell into which a flyer assembly according to the present invention can be loaded for launching by a ballistic launch assembly.

FIG. 2 illustrates a bulkhead disposed on the body member of the flyer for coupling the flyer to the shroud.

FIG. 3(a) illustrates one embodiment of a foldable wing assembly for a flyer constructed according to the present invention.

FIG. 3(b) illustrates a wing assembly configured in a folded state characterized by a plurality of nested wing segments.

FIG. 4 illustrates a fully deployed flyer, in which the wing assembly is configured in an unfolded state.

FIG. 5 illustrates a nose section, and a portion of the mid-body section of the flyer.

FIG. 6 illustrates an integrated imager for a flyer of the present invention.

FIG. 7 illustrates a mid-body section, and part of the tail section of the flyer.

FIGS. 8(a) and 8(b) illustrates a tail section of the flyer, which can be configured in a folded state and in an unfolded, deployed state.

FIGS. 9(a) and 9(b) illustrate a multi-stage transformation from a flyer packaged within the shroud into a fully deployed flyer capable of sustaining aerodynamic flight.

FIG. 10 illustrates a progressive deployment of the wing assembly of the flyer.

FIG. 11 illustrates possible deployments of the flyer assembly from diverse platforms.

DETAILED DESCRIPTION

FIG. 1(a) illustrates one embodiment of a flyer assembly 10 constructed according to the present invention. In overview, the flyer assembly 10 includes a jettisonable shroud 12 and a flyer 14. The flyer 14 is designed to withstand an acceleration force along a flyer axis 18 when in a first, undeployed state, and to effect aerodynamic flight when in a second, deployed state. The flyer 14 includes a body member 16 disposed about the flyer axis 18, and a foldable wing assembly 20 mounted to the body member 16. When the flyer 14 is in the first state, the wing assembly 20 is in a folded state. When the wing assembly 20 is in the folded state, the flyer 14 can be positioned within the shroud 12 with the flyer axis 18 parallel to a shroud axis 19, as shown in FIG. 1(a). In one embodiment, the flyer 14 is a Wide Area Surveillance Projectile (WASP), namely a small UAV used for reconnaissance, surveillance, or other sensing missions.

The flyer assembly 10 can be loaded as a cargo in a standard 155 artillery shell 22, such as the Army M-483 cargo round shown in FIG. 1(b). The flyer assembly is adapted for launching with, transit in, and deployment from the artillery shell 22, which has a central void region extending along a ballistic shell axis 100. The flyer assembly 10 may be stowed in the cargo bay of the M-483, and can be loaded in artillery cannons just like a normal round of cargo. The jettisonable shroud 12 extends along the shroud axis 19, and is positionable within the central void region with the

shroud axis **19** substantially parallel to the shell axis **100**. The flyer assembly **10** can be launched from ballistic launch systems such as artillery cannons, and can thus reach an area of interest very quickly without using its own stored fuel. The flyer assembly **10** can be launched by unspecialized 155-mm artillery troops. After reaching a predetermined ballistic range, the flyer assembly **10** is expelled from the artillery shell **22**. The shroud **12** is then jettisoned, and the flyer **14** unfolds from the shroud **12** into a fully deployed UAV that can carry out reconnaissance or similar sensing missions. The flyer **14** is designed with a stress mitigation approach and a g-hardening strategy that enable the flyer **14** to withstand severe gun-launch, expulsion, and deployment environments.

The shroud **12** is a rugged, multi-functional canister. In one embodiment, the shroud **12** has a substantially cylindrical shape, so as to be positionable within a central void region of the artillery shell **22**. The shroud **12** must be heavy, if used in an application where the flyer **14** is launched from a gun. The shroud **12** is designed to protect the flyer **14** during gun launch from the harsh gun environments that includes high temperatures and high g-loads. The shroud **12** also protects the flyer **14** during expulsion from the artillery shell **22**. The shroud **12** is preferably made of high-strength steel, in order to avoid buckling during set-back acceleration, and to endure high temperatures. In one embodiment, the shroud **12** is preferably made of steel having a hardness of about 4140 H, and capable of enduring a temperature of 500° F.

The present invention implements a g-hardening strategy for the flyer **14**, by hanging the flyer **14** inside the shroud **12** so as to maintain most of the flyer **14** in tension during set-back acceleration. For this purpose, a support mechanism **24** is disposed at an interior surface of the shroud **12**. In one embodiment, the support mechanism **24** is a hanger, such as a supporting ring or shelf. The body member **16** of the flyer **14** includes a load-bearing bulkhead **26**, such as an attachment ring. In one embodiment, the bulkhead **26** is disposed near the center of gravity of the flyer **14**. A substantial portion of the flyer **14** of the present invention is maintained in tension, by hanging the flyer **14** by its bulkhead **26** on the support mechanism **24** of the shroud **12**. The structures of the flyer **14** located aft of the bulkhead **26** are thereby maintained in tension. Because the flyer **14** is hung within the shroud **12**, there are gaps **25** between the outer end surfaces of the flyer **14** and the inner end surfaces of the shroud **12**, as shown in FIG. 1(a). During set-back acceleration the front end of the flyer assembly **10**, as well as the outer wall of the shroud **12**, are in compression, while the flyer **14** is in tension aft of its center of gravity. In this way, the flyer **14** is protected from buckling under the compression created by the set-back acceleration.

The flyer **14** is preferably constructed from light weight composite materials, which are well adapted to withstand tension, but not necessarily well adapted to withstand compression. Composite materials have a high strength-to-weight ratio, which helps maintain the tensile strength of the flyer **14**. The carbon fibers within the composite materials are oriented so that structures of the flyer **14** in the load path are made strong in the loaded direction. Many carbon-based composites known in the art may be used, including but not limited to unidirectional, woven-conformable and chopped mixture approaches. For a given propulsion system, the lighter the flyer **14**, the easier it is for the flyer **14** to fly, since less propulsive power is needed in order for the flyer **14** to remain airborne. The use of light weight composite materials advantageously reduces the weight of the flyer **14**. In the

illustrated embodiment, the maximum flyer weight is 8.6 lbs. Also, reducing the weight of the flyer **14** reduces the g-load on the flyer **14**, since each pound of weight of the flyer **14** bears a pound force equal in numerical value to the g-load on the flyer **14**. In one form, the flyer **14** is designed to endure a temperature of 300° F.

FIG. 2 illustrates one embodiment of a bulkhead **26** that provides a load path into the shroud **12**. The shroud **12** provides an ultimate load path for the acceleration force, by coupling to the flyer **14** through the bulkhead **26**. With this configuration, the shroud **12** mitigates the g-load on the flyer **14** during the launch. The shroud **12** thus functions as a sabot to support the flyer **14** in the high-g environment created during a gun launch. In the illustrated embodiment, the weight during peak acceleration of the aft sections of the flyer **14** is about 65,000 lb. As shown in FIG. 2, the flyer assembly **10** is adapted to survive a g-load of up to about 16,000 g. The flyer assembly **10** is unique among existing flyers and UAVs in its capability to survive such a high g-load.

The shroud **12** also serves as a convenient container for transporting and handling the flyer **14**. One advantage of the flyer assembly **10** over prior art UAVs is ease of handling and transportation. Prior art UAVs are inherently unwieldy and cumbersome to transport, and require that the wings first be removed, and subsequently reattached at the launch site. In contrast, the flyer **14** of the present invention can be easily stowed inside and packaged within the shroud **12** for transportation and handling.

In a preferred embodiment, the body member **16** includes a central void region **28** within the body member **16**. The wing assembly **20** is mounted exclusively on the outer surface of the body member **16**, exterior to the central void region **28**. This configuration permits use of the space within the body member **16**, in contrast to prior art flyers in which the wing assembly **20** when in the folded state uses up all available space in the body member **16** of the flyer **14**, severely reducing any storage space within the body member **16**. In one embodiment, the void region **28** may be used for storage of system energy, i.e. fuel or battery, that is dispensed during an aerodynamic flight of the flyer **14**.

FIG. 3(a) illustrates one embodiment of a foldable wing assembly **20** for the flyer **14**. The wing assembly **20** is designed to be part of the stress mitigation strategy for the flyer assembly **10**. The wing assembly **20** includes at least two wing segments **32**. The illustrated embodiment includes three wing segments. Each wing segment **32** has a span-wise axis **34**. The wing segments **32** are disposed mutually adjacent and end to end.

In the illustrated embodiment, a pivot assembly **36** is attached to each pair of adjacent wing segments **32** and at an end of each adjacent wing segment along the span-wise axis **34**. The pivot assemblies **36** may include hinges **38** provided at the junction between each pair of wing segments **32**. The hinges **38** may include torsion springs **42** which provide a torque that causes an angular rotation of each pair of adjacent wing segments **32** with respect to one another about an articulation axis **33**, so that the wing assembly **20** converts from a folded configuration to an unfolded or deployed configuration. Torsion springs **42** may act in combination with gravity to effect wing deployment.

FIG. 3(b) illustrates a wing assembly **20** configured in a folded state characterized by a plurality of nested wing segments **32**. The wing segments **32** are designed to withstand a stress along the flyer axis of the flyer **14**. When the wing assembly **20** is in a folded state and the flyer **14** is

enclosed within the shroud **12**, the planar surfaces of the wing segments **32** are substantially parallel to the flyer axis **18** of the flyer **14**. In the embodiment illustrated in FIG. 3(b), the wing segments **32** are folded so that the middle wing segment **32(b)** abuts an inner surface of the shroud **12**, thereby becoming the outermost wing segment. During setback acceleration, the outermost one **32(b)** of the wing segments are under compression, while the other wing segments **32(a)** and **32(c)** are under tension. Any buckling of one or more of the wing segments **32** is supported by the shroud **12**, which provides a radial restraining force against the wing segments **32** so as to counter the centrifugal force arising from a spinning of the flyer assembly **10** after expulsion from the artillery shell **22**.

FIG. 4 illustrates a fully deployed flyer **14** in which the wing assembly **20** is configured in an unfolded state characterized by a substantially uninterrupted aerodynamic surface. The fully deployed flyer **14** is capable of sustaining aerodynamic flight. The flyer **14** of the present invention uses the energy of an existing external delivery system in order to reach an area of interest very quickly without expending its own fuel. The flyer **14** of the present invention thus provides an important tactical advantage over prior art UAVs, by maximizing the energy available over the target, and thereby improving endurance and functionality. In one embodiment, flyer endurance is at minimum 30 minutes of continuous flight after full deployment of the flyer **14**. Prior art UAVs that are launched in a traditional way must expend their own stored energy, whether in the form of gasoline or battery, in order to reach the target. Prior art UAVs must thus give up a substantial portion of their stored energy before reaching the target, and therefore cannot maximize use of the energy available over the target. In contrast, the flyer **14** according to the present invention uses its stored energy only after reaching the target area of interest and while carrying out its surveillance or other mission. The flyer **14** thereby significantly increases flight endurance, and reduces time of flight to the target.

In the embodiment illustrated in FIG. 4, the body member **16** of the flyer **14** comprises a nose section **44**, a mid-body section **46**, and a tail section **48**. In this embodiment, the forward bulkhead **26** is disposed at a junction between the nose section **44** and the mid-body section **46**. In one embodiment, the body member **16** has a length of about 19.5 inches, and has a diameter of about 4.6 inches at the nose section **44**.

FIG. 5 presents a more detailed illustration of the nose section **44** and part of the mid-body section **46** of one embodiment of a flyer **14** constructed according to the present invention. An electric propulsion system, including a folding propeller **52** and a brushless DC motor **54**, are located at the forward portion of the nose section **44**. The electric propulsion system is preferably constructed to be highly reliable and to survive g-loads, so that the system can start up while the flyer is in motion, and while the flyer **14** is at an altitude with low ambient temperature and reduced oxygen. The cruise speed of the flyer **14** is about 65 mph. In one embodiment, the propeller **52** rotates at about 5000 RPM, during a level flight of the flyer at 60 mph. In one embodiment, the propeller **52** has a diameter of 11 inches, and a pitch of 15 inches. The motor **54** has a maximum power of 0.5 HP.

An analog and digital Global Positioning System (GPS) **41** is stored in the forward portion of the mid-body section **46** of the flyer, adjacent the bulkhead **26** and above the foldable wing assembly **20**. An Inertial Navigation System (INS) **57** and a flight computer **59** are stored adjacent the bulkhead **26** and under the wing assembly **20**.

An integrated imager **62**, including imager electronics **63** and imager optics **64**, is located behind the motor **54**. The imager optics **64** preferably includes four imaging sensors, of which three sensors **68** are electro/optic (E/O), and one sensor is infrared (IR). The three E/O imaging sensor heads **68** are positioned side by side in front of the imager electronics **63**, while the fourth IR imaging sensor head is located near the battery. The imager electronics **63** include an image processor and an image transmitter. The imaging distance required for identification of moving targets is about 4000 ft. The image resolution required for identification of moving targets is about 1 ft.

FIG. 6 presents a more detailed illustration of one embodiment of the integrated imager **62**, including imaging electronics **63** and the three imaging sensor heads **68**. The centerline of the imaging head cluster is coincident with the centerline of the flyer **14**. As shown in FIG. 6, the focal length of each imaging sensor head is 33 mm, and the field of vision (FOV) of each imaging sensor head **68** is 19 degrees. The imager charge coupled device (CCD) has 1280x1024 active pixels. Images are captured by taking a series of stills. In one embodiment, the snapshot ground coverage from the flyer **14** is 1024 ft downrange and 3840 ft crossrange, for identification of targets, and 2048 ft downrange and 7880 ft crossrange, for recognition of targets. The flyer **14** takes one still photo from directly above the target position, and at least two snapshots from 30 degrees off vertical. In one embodiment, the identification range does not exceed 4000 ft.

FIG. 7 illustrates one embodiment of the mid-body section **46** and part of the tail section **48** of a flyer constructed according to the present invention. The battery **49** is shown located within the central void region **28** of the mid-body section. The battery **49** is preferably a Lithium oxyhalide (Li/SOCl₂) reserve battery, which has a long storage life due to separate storage of the electrolyte. The battery electrolyte is stored independent of the electrodes for long life, eliminating fueling requirements for the flyer **14**. The electrolyte is forced into the cells upon high-g projectile firing. The total voltage in the battery is about 32+/-4 volts. The maximum current is about 1 A, and the storage loss is about 3% per year. An aft bulkhead is located between the mid-body section **46** and the tail section **48**. Tail servos **80** are located near the aft bulkhead behind the battery.

FIGS. 8(a) and 8(b) provide a more detailed illustration of one embodiment of the tail section **48**. The tail section includes a plurality of single fin tails **90**, each single fin tail having a tail surface **92**. In one embodiment, the plurality of single fin tails **90** form a foldable tail assembly, configurable in a folded state and in an unfolded state. FIG. 8(a) shows the single fin tails **90** configured in a folded state, while FIG. 8(b) shows the tails in an unfolded, fully deployed state. The tail section has a conventional, inverted tail surface arrangement. The tail surfaces **92** can rotate and lock to effect servo drive. All tail surfaces **92** fold externally.

While the flyer assembly **10** can be used for any operation that utilizes a ballistically launched flyer-in-a-shell, a fundamental application for the flyer assembly **10** of the present invention is visual imaging and identification of moving land targets. Moving target identification was needed in order to avoid civilian casualties in recent conflicts such as the conflict in Kosovo. In the air wars in Kosovo, where ground forces were avoided and targets were too far inland for naval gunfire, the air spotters needed video images of ground target areas. The flyer assembly **10** may also be used for Battle Damage Assessment (BDA), when it is prudent to use UAVs rather than to put airmen at risk.

In the operation of one possible application scenario, a high-altitude, long-endurance system, such as JSTARS, surveys a large conflict area. JSTARS locates potential targets, and reports its data through the JSTARS Common Ground Station. Typical JSTARS data include potential target location, speed, and heading. Once an operational decision is made that target identification is required prior to further action, a command is issued to an artillery battery to load a flyer assembly **10** (i.e. WASP) to the directed coordinates.

Upon loading, the shell **22** containing the flyer assembly **10** is fired to the area of interest. In one embodiment, the artillery launch delivers the shell-and-flyer projectile about 22 km in approximately 1 minute. Typically the apogee of the projectile trajectory is about 50,000 ft. The heavy shroud **12** provides the necessary mass for an optimal ballistic range. While the light weight of the flyer **14** increases the flight endurance of the flyer **14** for a given propulsion system, if the flyer assembly **10** is too light, air resistance slows down the flyer assembly, decreasing the ballistic range of the projectile. On the other hand, if the flyer assembly **10** is too heavy, its weight shortens the ballistic range. By implementing a flyer-in-a-shroud design, the weight of the shroud **12** can be added to the light weight of the flyer **14**, in order to optimize the ballistic range. In one embodiment, the unloaded shell weighs about 54.9 lb, while the weight of the shell **22** loaded with the flyer assembly **10** is about 102.6 lb. In one embodiment, the muzzle velocity, i.e. the velocity of the flyer assembly **10** when just coming out of the gun is 2,624 ft/sec. As mentioned earlier, the setback acceleration is approximately 16,000 g.

After reaching a desired ballistic range, the flyer assembly **10** is expelled from the rear of the M-483 by an expulsion charge in the projectile nose. The shroud **12** is designed to bear a 60,000 lbf force of expulsion charge. After expulsion, a two-stage parachute system is used to decelerate the flyer **14**, and to fully deploy the flyer **14** by converting the wing assembly **20** from a folded state to an unfolded state.

FIGS. **9(a)** and **9(b)** illustrate a multi-stage metamorphosis from a flyer **14** packaged within the shroud **12** into a fully deployed flyer **14**. Step **1** in FIG. **9(a)** shows the flyer assembly **10**, just after being expelled from the artillery shell by expulsion charges. At this point, the spin rate of the flyer assembly **10** is about 270 Hz, and the speed of the flyer assembly **10** is about 600 mph. The shroud **12** protects the flyer **14** during spinning, preventing the flyer **14** from being torn apart by the high-g rebound loads, and by the high spin. In step **2** shown in FIG. **9(a)**, a first stage drogue parachute **91** deploys from the shroud **12**, to slow and de-spin the flyer **14**. The first stage parachute is a high velocity parachute or ballute, and is deployed at a speed of about 900 ft/sec and a rotation rate of about 250–270 Hz. The first stage parachute **91** may be the first stage of a Ram Air Insertion Device (RAID). The spin rate of the flyer assembly **10** is decreased from about 270 Hz to about 10 Hz. The speed of the flyer assembly **10** is reduced from about 600 mph to about 80 mph.

When the flyer assembly **10** reaches a speed of about 80 mph, and a spin rate of about 10 Hz, the shroud **12** is destroyed, as illustrated in step **3** in FIG. **9(b)**. The shroud **12** is jettisoned by means of small charges embedded within the shroud **12**. After the shroud **12** is broken away, a second stage parachute **100** deploys from the flyer **14**. The second stage parachute **100** further slows the descent of the flyer **14**, and further de-spins the flyer **14**. The second stage parachute **100** is a low velocity parachute. The speed of descent of the flyer is reduced from about 80 mph to about 40 mph. The spin rate decreases from about 10 Hz to about 0 Hz. The tail fin surfaces **92** of the flyer **14** are then deployed.

In the fourth and final step, the wing assembly fully deploys, converting from a folded state characterized by a plurality of nested wing segments into an unfolded state characterized by a substantially uninterrupted aerodynamic surface. FIGS. **10(a)** to **10(d)** illustrate a deployment sequence for the wing assembly **20** of the present invention. As seen from the illustrated sequence, the wing segments **32** make a 90° arcuate trajectory from FIG. **10(a)** to FIG. **10(d)**, while sequentially converting from the folded state illustrated in FIG. **10(a)**, to an unfolded state illustrated in FIG. **10(d)**. When the wing assembly is in the folded state, the span-wise axis **34** of each wing segment **32** is substantially parallel to the flyer axis **18** of the flyer **14**, whereas in the unfolded and fully deployed state, the span-wise axis **34** of each wing segment **32** is substantially transverse to the flyer axis **18**.

Once the wing assembly **20** is in the unfolded state, the electric motor starts, the flyer **14** stabilizes, and aerodynamic flight of the flyer **14** begins. As described earlier, the flyer **14** can perform at least 30 minutes of continuous flight after deployment. The loiter range of the flyer **14** is typically about 48 km, since the flyer **14** travels for about 0.5 hour at a target land speed of about 60 mph. The loiter altitude is about 4,000 ft. The flight of the flyer **14** is may be controlled by a mission plan that is prepared in the UAV Ground Control Station (GCS). The UAV GCS receives down-linked information from the flyer **14**, and serves as the up-link node to the flyer **14**. Typically, the range from the artillery unit to the GCS is about 40 km. The communication range from the flyer **14** to the GCS can therefore be up to 88 km. During the initial stage of the controlled flight, the flyer **14** receives the mission plan through a ground communication link. The flyer **14** then executes the mission plan flying between designated points. The mission plan may be updated continuously, as JSTARS supplies updates on target location, speed, and heading. The E/O imaging sensors **68** send video images to the ground. The video images may be sent directly to JSTARS, to the ground operations centers, or to all of these nodes, as required.

Because of its high-g capability, and because of its capacity to tolerate extreme environments, the flyer assembly **10** of the present invention can be launched from other launch platforms such as Naval guns. The flyer assembly **10** of the present invention can be thus used in the Army, Navy, or the Air Forces, for time-critical missions involving moving targets. For alternate launch platforms, the flyer assembly **10** of the present invention may be substituted, for example, for the munition in the munitions compartments of projectile/missile hybrids such as the Extended Range Guided Munition (ERGM). FIG. **11** illustrates a notional application of the flyer assembly **10** for deployment from diverse air, land, and undersea platforms.

The flyer assembly **10** may also be air-dropped or launched from aircraft weapon pods to extend the vision of, e.g., Forward Air Controllers (FACs). FACs are close enough to see, sense and report ground information, but could be in a danger zone, and would therefore benefit from the WASP capabilities disclosed in the present invention. The FACs could drop the flyer assembly **10** of the present invention and have it fly to an area of interest, while remaining at a safe distance or above cloud cover. The flyer assembly **10** may even be used for civilian purposes, such as disseminating leaflets over selected target areas.

By implementing flyers that can survive cannon launches, the present invention greatly improves the availability of flyers for time-critical missions. In a battlefield environment, situations change extremely quickly so that very fast

response with very little planning is an advantage. In order to engage in time-critical missions involving moving ground targets, availability of the assets, including cost, planning time, and maintenance of the assets, and the time it takes to reach the target, are important.

The flyer assembly **10** disclosed in the present invention significantly improves the availability of flyers for time-critical missions. As described earlier, the flyer assembly can be packaged in a standard artillery shell which is distributed to guns in the same manner as existing kill rounds in the inventory. As soon as a decision to deploy a WASP is made, the battery can be notified, and a shell containing a flyer assembly **10** can be loaded and fired to the area of interest. The flyer assembly **10** is thus available when needed, at the point of fire. Time need not be wasted for fueling the flyer **14**, since the flyer **14** constructed according to the present invention uses electric propulsion with a g-activated long-storage life battery, as described earlier. The actual flight of the shell takes only one minute for 22 km. The mission plan can be downloaded by the UAV controller while the flyer **14** is in flight. No special takeoff or landing facilities are required. Finally, the target cost for the flyer assembly **10** is only \$10,000 in lots of 1000. With such low production costs, the flyer assembly **10** of the present invention can be considered expendable, thus avoiding additional costs of recovering and refurbishing UAVs. Expendability is a logistical advantage for UAVs intended to sense chemical or biological agents, since it makes it unnecessary to return and thus decontaminate the UAVs.

While the invention has been particularly shown and described with reference to specific preferred embodiments, it should be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. A flyer assembly adapted for launching with, transit in, and deployment from an artillery shell having a central void region extending along a ballistic shell axis, comprising:

A) a jettisonable shroud extending along a shroud axis and positionable within said central void region with said shroud axis substantially parallel to said shell axis;

B) a flyer adapted when in a first state to withstand a launch acceleration force along a flyer axis and adapted when in a second state to effect aerodynamic flight, the flyer in said first state being positionable within said shroud with said flyer axis parallel to said shroud axis and said shell axis, the flyer including:

- a) a body member disposed about said flyer axis; and
- b) a wing assembly mounted to the body member;

wherein the flyer is adapted for coupling to the shroud so as to maintain a portion of the flyer in tension during an acceleration of the flyer along the flyer axis resulting from the launching of said artillery shell.

2. A flyer assembly according to claim **1**, wherein said wing assembly is foldable.

3. A flyer assembly according to claim **2**, wherein said wing assembly is configurable in a folded state when the flyer is in said first state; and

wherein said wing assembly is configurable in an unfolded state when the flyer is in said second state.

4. A flyer assembly according to claim **1**, wherein said wing assembly comprises at least one wing segment.

5. A flyer assembly according to claim **2**, wherein said wing assembly further comprises a pivot assembly attached to an end of each wing segment for enabling the angular

rotation of said wing segment about an articulation axis, so that said wing assembly can be converted from a folded configuration to an unfolded configuration.

6. A flyer assembly according to claim **5**, wherein said pivot assembly comprises a hinge.

7. A flyer assembly according to claim **6**, wherein said hinge comprises a torsion spring.

8. A flyer assembly according to claim **4**, wherein each wing segment comprises a span-wise axis.

9. A flyer assembly according to claim **8**, wherein when the wing assembly is in the folded state said span-wise axis of each wing segment is substantially parallel to the flyer axis, and

wherein when the wing assembly is in the unfolded state said span-wise axis of each wing segment is substantially transverse to said flyer axis.

10. A flyer assembly according to claim **1**, wherein the shroud comprises a support mechanism disposed at an interior surface of the shroud; and

wherein the flyer comprises a bulkhead for coupling to said support mechanism of said shroud.

11. A flyer according to claim **10**, wherein said support mechanism comprises a hanger.

12. A flyer assembly according to claim **10**, wherein the body member comprises a nose section, a mid-body section, and a tail section;

wherein the bulkhead is disposed at a junction between the nose section and the mid-body section; and

whereby the mid-body section and the tail section of the flyer are maintained in tension during an acceleration of the flyer along the axis resulting from the launching of the artillery shell.

13. A flyer assembly according to claim **12**, wherein at least a portion of at least one of said mid-body section and said tail section is made of a composite material.

14. A flyer assembly according to claim **1**, wherein the body member comprises a central void region, and further wherein the wing assembly is mounted on an outer surface of the body member exterior to said central void region.

15. A flyer assembly according to claim **14**, further comprising an energy storage system for storing system energy to be dispensed during aerodynamic flight of the flyer, said energy storage system being disposed within said central void region.

16. A flyer assembly according to claim **15**, wherein said energy storage system comprises a battery.

17. A flyer assembly according to claim **16**, wherein said battery comprises a Lithium battery.

18. A flyer assembly according to claim **1**, further comprising a deceleration mechanism adapted to decelerate the flyer assembly subsequent to an expulsion of the flyer assembly from the artillery shell.

19. A flyer assembly according to claim **18**, wherein said deceleration mechanism comprises a parachute.

20. A flyer assembly according to claim **1**, wherein the shroud comprises a separation mechanism for jettisoning the shroud subsequent to the expulsion of the flyer assembly from the shell.

21. A flyer assembly according to claim **1**, wherein the flyer assembly is adapted to be launched from a ballistic delivery system.

22. A flyer assembly according to claim **21**, wherein the ballistic delivery system is selected from the group consisting of a cannon, an aircraft, a rocket, and a submarine.

23. A flyer assembly according to claim **1**, further comprising an electric motor for sustaining said aerodynamic flight of said flyer when said flyer is in said second state.

24. A flyer assembly according to claim 1, wherein the body member comprises a nose section, a mid-body section, and a tail section.

25. A flyer assembly according to claim 24, further comprising an electric propulsion system disposed in said nose section of said body member.

26. A flyer assembly according to claim 25, wherein said electric propulsion system includes a folding propeller and a motor.

27. A flyer assembly according to claim 26, wherein the RPM of said folding propeller during a sustained flight of said flyer is about 5000.

28. A flyer assembly according to claim 24, further comprising a Global Positioning System disposed within said mid-body section of said flyer.

29. A flyer assembly according to claim 24, further comprising an Inertial Navigation System disposed within said mid-body section of said flyer.

30. A flyer assembly according to claim 24, further comprising an integrated imager disposed within said nose section.

31. A flyer assembly according to claim 30, wherein said integrated imager comprises:

- a. at least one electro/optic sensor; and
- b. an image processor.

32. A flyer assembly according to claim 31, wherein said integrated imager further comprises an image transmitter.

33. A flyer assembly according to claim 31, wherein said integrated imager further comprises an infrared sensor.

34. A flyer assembly adapted for launching with, transit in, and deployment from an artillery shell having a central void region, comprising:

- A) a launch canister positionable within said central void region; and
- B) a flyer adapted when in a first state to withstand a launch acceleration force along a flyer axis and adapted when in a second state to effect aerodynamic flight, the flyer in said first state being positionable within said launch canister, the flyer including:
 - a) a body member disposed about said flyer axis; and
 - b) a foldable wing assembly mounted to the body member;

wherein the flyer is adapted to be coupled to said launch canister so as to maintain at least a portion of the flyer in tension during acceleration of the flyer along said flyer axis resulting from the launching of said artillery shell.

35. A flyer assembly according to claim 34, wherein the launch canister comprises a support mechanism disposed at an interior surface of the shroud; and

wherein the flyer comprises a bulkhead for coupling to said support mechanism of said shroud.

36. A flyer according to claim 35, wherein said support mechanism comprises a hanger.

37. A flyer assembly according to claim 35, wherein the body member comprises a nose section, a mid-body section, and a tail section;

wherein the bulkhead is disposed at a junction between the nose section and the mid-body section; and

whereby the mid-body section and the tail section of the flyer are maintained in tension during an acceleration of the flyer along the axis resulting from the launching of the artillery shell.

38. A flyer assembly according to claim 37, wherein at least a portion of said mid-body section and said tail section is made of a composite material.

39. A flyer assembly according to claim 34, wherein the body member comprises a central void region, and further wherein the wing assembly is mounted on an outer surface of the body member exterior to said central void region.

40. A flyer assembly according to claim 39, further comprising an energy storage system for storing system energy to be dispensed during aerodynamic flight of the flyer, said energy storage system being disposed within said central void region.

41. A flyer assembly according to claim 40, wherein said energy storage system comprises a battery.

42. A flyer assembly according to claim 34, further comprising a deceleration mechanism adapted to decelerate the flyer assembly subsequent to an expulsion of the flyer assembly from the artillery shell.

43. A flyer assembly according to claim 42, wherein said deceleration mechanism comprises a parachute.

44. A flyer assembly according to claim 34, further comprising an electric motor for sustaining said aerodynamic flight of said flyer when said flyer is in said second state.

45. A flyer assembly adapted for launching with, transit in, and deployment from an artillery shell having a central void region, comprising:

- A) a launch canister positionable within said central void region; and
- B) a flyer positionable within the canister and adapted to be releasably coupled thereto, and adapted when in a first state when coupled to said canister to withstand a launch acceleration force along a flyer axis, and adapted when in a second state when decoupled from said canister to effect aerodynamic flight, the flyer including:
 - a) a body member disposed about said flyer axis; and
 - b) a foldable wing assembly mounted to the body member.

46. A flyer assembly according to claim 45, wherein the flyer is adapted to be coupled to said canister so as to maintain at least a portion of the flyer in tension during acceleration of the flyer

along said flyer axis resulting from the launching of said artillery shell.

* * * * *