



US006845942B2

(12) **United States Patent**  
**Paul**

(10) **Patent No.:** **US 6,845,942 B2**  
(45) **Date of Patent:** **Jan. 25, 2005**

(54) **OMNI-DIRECTIONAL AIR VEHICLE  
PERSONAL TRANSPORTATION SYSTEM**

(76) Inventor: **Marius A. Paul**, 1120 E. Elm Ave.,  
Fullerton, CA (US) 92631

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/371,680**

(22) Filed: **Feb. 20, 2003**

(65) **Prior Publication Data**

US 2004/0061022 A1 Apr. 1, 2004

**Related U.S. Application Data**

(60) Provisional application No. 60/361,544, filed on Mar. 4,  
2002, and provisional application No. 60/358,825, filed on  
Feb. 21, 2002.

(51) **Int. Cl.**<sup>7</sup> ..... **B64C 15/00**

(52) **U.S. Cl.** ..... **244/12.2; 244/17.11; 244/21**

(58) **Field of Search** ..... **244/12.2, 17.11,  
244/21, 23 C, 12.4, 23 B, 72**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,745,498 A	*	5/1956	Nagler	416/21
2,952,422 A	*	9/1960	Fletcher et al.	244/12.2
3,082,977 A	*	3/1963	Max	244/17.23
3,181,811 A	*	5/1965	Maksim, Jr.	244/12.2
3,276,723 A	*	10/1966	Miller et al.	244/12.2
3,606,570 A	*	9/1971	Haggerty	416/2

4,537,372 A	*	8/1985	Forizs	244/12.4
4,653,705 A	*	3/1987	Bensen	244/17.11
4,941,628 A	*	7/1990	Sakamoto et al.	244/12.2
5,178,344 A	*	1/1993	Dlouhy	244/12.2
5,190,242 A	*	3/1993	Nichols	244/12.2
5,226,350 A	*	7/1993	Cycon et al.	74/665 F
5,295,643 A	*	3/1994	Ebbert et al.	244/7 B
5,351,913 A	*	10/1994	Cycon et al.	244/60
5,419,513 A	*	5/1995	Flemming et al.	244/12.2
5,419,514 A	*	5/1995	Ducan	244/12.4
5,653,404 A	*	8/1997	Ploshkin	244/12.2
5,765,776 A	*	6/1998	Rogers et al.	244/12.2
6,179,247 B1	*	1/2001	Milde, Jr.	244/23 A
6,270,038 B1	*	8/2001	Cycon et al.	244/12.3
6,343,768 B1	*	2/2002	Muldoon	244/7 R
6,450,445 B1	*	9/2002	Moller	244/23 A
6,691,949 B2	*	2/2004	Plump et al.	244/12.2
6,719,244 B1	*	4/2004	Gress	244/7 R


\* cited by examiner

*Primary Examiner*—Teri P. Luu  
*Assistant Examiner*—Stephen A. Holzen  
(74) *Attorney, Agent, or Firm*—Richard Esty Peterson

(57) **ABSTRACT**

An omni-directional air vehicle having a pod with a connected turbofan system, the pod has a body that contains a power source for generating electrical power and a ducted fan with spherical articulation mechanism having a projecting arm with counter-rotating propellers and a ducted shroud around the periphery of the counter rotating propellers and containing drive motors for electrically driving the propellers.

**11 Claims, 6 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B

1

## OMNI-DIRECTIONAL AIR VEHICLE PERSONAL TRANSPORTATION SYSTEM

### RELATED APPLICATIONS

This application claims the benefit of provisional application Ser. No. 60/361,544, filed on Mar. 4, 2002 and Ser. No. 60/358,825, filed on Feb. 21, 2002.

### BACKGROUND AND SUMMARY OF THE INVENTION

This invention relates to a new air vehicle having omni-directional flying capabilities. The vehicle can sit motionless in air or on land, and, depart to and land from all positions and directions, including vertical take-off and landing (VTOL). The invented vehicle is a universal mobility air vehicle.

The PTS can replace any and all cars, vans, motorcycles, helicopters, business airplanes, or any vehicles military and commercial. The omni-directional vehicle is an absolute revolutionary, universal transportation system for solving our modern, vehicle-congested urban environment.

The modular association of multiple omni-directional vehicles in an integrated structural apparatus provides a universal propulsion system for flying platforms, air lift vehicles, combined multi-functional operations, individual flying vehicles, and unlimited applications which need flexible capabilities for emergency and special forces.

For military use in the rapid deploying of forces, fuel and all other the logistic supplies for armored vehicles isolated in places without lines of communication, the modularized air lift system can be invaluable.

A first characteristic of the novel omni-directional air vehicle is a thermal-electric, hybrid propulsion system using the power source technology of our U.S. Pat. No. 6,282,897, issued Sep. 4, 2001, entitled Advanced Thermo-Electronic Systems For Hybrid Electric Vehicles, and incorporated herein by reference.

A second characteristic is the use of a counter-rotating, counter-electric, turbofan system, driven by the thermal electric power source with double ring permanent magnets in hollow concentric motors.

A third characteristic is an omni-directional articulation between the turbo-electric, counter-rotating fan and the main body of the vehicle, permitting a universal adjustment of the relative direction of the turbofan, and thereby providing the vehicle with universal mobility.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic view of the omni-directional air vehicle of this invention.

FIG. 2 is a schematic view of the omni-directional air vehicle adapted for personal transport.

FIG. 3 is a schematic view of an alternate omni-directional air vehicle.

FIG. 4A is a schematic view of a further alternate omni-directional air vehicle.

FIG. 4B is a further schematic view of the alternate omni-directional air vehicle of FIG. 4a.

FIG. 5A is a schematic view of a further alternate omni-directional air vehicle.

FIG. 5B is a further schematic view of the alternate omni-directional air vehicle of FIG. 5a.

FIG. 6A is a schematic view of a further alternate omni-directional air vehicle.

2

FIG. 6B is a further schematic view of the alternate omni-directional air vehicle of FIG. 6a.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In FIG. 1, the omni-directional air vehicle, depicted generally by the number **10**, comprises a pod **11** with pod supports **12**, and a connected turbofan system **16** having a turbo-electric, counter-rotating ducted fan **20** provided with two counter-rotating propellers **21** and **22**, peripherally driven by counter-rotating, permanent magnet, electric motors **23** and **24**, integrated in a ducted shroud **25**, supported by struts **26** connected to a projecting arm **27** of a spherical articulation mechanism **28** seated in the main body **30** of the pod **11** of the vehicle **10**. The spherical articulatory mechanism **28** changes the angular position of the projecting arm **27** to the angle "a" as limited by stop **13** at the top of main body **30**.

In the main body **30**, is located a combination thermal electric engine and gas turbine **31**, of the type described in the referenced U.S. Pat. No. 6,282,897. The combination thermal electric engine and gas turbine **31** is provided with air intake ports **32** and exhaust ports **33** and in out put generator **16** supplies the electric power through an electronic control module **34** to the counter-rotating electric motors **23** and **24** through electric circuit line **34a**.

The ability to change the relative angular position (a) between the turboelectric counter-rotating ducted fan **20** and the main body **30** allows the vehicle to perform all flying missions from all positions in all directions, including ground and air, from on-board control systems, wherein the vehicle has a universal mobility.

The ultra high efficiency of the engines and gas turbines, as described in the referenced U.S. patent, provides the absolute best performance for military applications, such as unmanned aerial vehicles (UAV) and commercial applications for better cargo and personnel transports than actual helicopters or business airplanes.

In FIG. 2 there is depicted a configuration of the same omni-directional vehicle used as a personal transportation system (PTS) which is designed to accommodate a person or multiple persons. Manual control of the spherical articulation mechanism is accomplished by control arm **28a**.

FIG. 3 depicts a special configuration of the omni-directional air vehicle **10** with the ability to fly horizontally at high speed facilitated by the addition of a cruciform **14** having wings **35** which have directional guides **36** that are active only in horizontal high speed operation.

FIGS. 4A and 4B depict the omni-directional air vehicle **10** with a discoid shape vehicle body **40** attached to a round fixed wing **41** connected with the dome **42** and at least two electric ducted fans **20a** (push) and **20b** (pull) with counter-rotating propellers **21** and **22**, each fan being attached with a projecting arm **27**. Once the vehicle is converted to horizontal flight, both turbo-electric, counter-rotating ducted fans **20a** and **20b** are horizontally arranged in the same push-pull actions per the direction of flight. The omni-directional air vehicle flight capability is improved by the round discoid wing **41** which uses less energy and has less drag at high speed in the horizontal mode. Additionally, the round discoid wing **41** can be used on gliding flight.

FIGS. 5A and 5B depict the omni-directional air vehicle **10** having an elongated fuselage **50** attached to an adjustable elongated wing **51** able to be rotary arranged always perpendicular to the direction of flight. The same turbo-electric, counter-rotating ducted fans **20a** and **20b** with counter-



rotating propellers 21 and 22 in a push-pull arrangement form the omni-directional air vehicle propulsion system.

FIGS. 6A and 6B depict the omni-directional air vehicle 10 having an adjustable (rotary) platform body 60 associated with platform wing 61 articulated by pivot dome 63 and the shaft 62. The axial position x-x will always be perpendicular with the axial y-y of the body 60 per flight direction. The same turbo-electric, counter-rotating ducted fans 20a, 20b and 20c with counter-rotating propellers 21 and 22 will cooperate in a combined push-pull action for the omni-directional air vehicle direction of flight. The omni-directional air vehicle is designed to accommodate a person or multiple persons.

While, in the foregoing, embodiments of the present invention have been set forth in considerable detail for the purposes of making a complete disclosure of the invention, it may be apparent to those of skill in the art that numerous changes may be made in such detail without departing from the spirit and principles of the invention.

What is claimed is:

1. An omni-directional air vehicle comprising:

a pod;

a turbofan system having an articulated connection to the pod, the turbofan system having a ducted fan with counter rotating propellers, a spherical articulation mechanism with a projecting arm on which the propellers are mounted, and a shroud with struts connected to the projecting arm, wherein the pod has a body with the spherical articulation mechanism begin seated in the body of the pod, with the projecting arm projecting from the pod and with the spherical articulation mechanism having means for limited articulation of the projecting arm relative to the pod wherein the angular position of the turbofan system relative to the pod is changeable, and the ducted fan has counter-rotating electric motors driving the counter-rotating propellers; and,

a power source connected to the counter-rotating electric motors.

2. The omni-directional air vehicle of claim 1 wherein the means for limited articulation of the projecting arm of the

spherical articulation mechanism comprises a control arm in the pod that is connected to the spherical articulation mechanism for manual operation.

3. The omni-directional air vehicle of claim 1 wherein the pod has supports for supporting the pod.

4. The omni-directional air vehicle of claim 1 wherein the pod has wings with directional guides for horizontal operation.

5. The omni-directional air vehicle of claim 1 has multiple ducted fans with counter-rotating propellers.

6. The omni-directional air vehicle of claim 1 wherein the pod has a vehicle body with a round discoid wings.

7. The omni-directional air vehicle of claim 1 wherein the pod has an elongated fuselage and an elongated discoid wing arrangeable perpendicular to the direction of travel.

8. The omni-directional air vehicle of claim 1 having a platform body and articulated wing.

9. The omni-directional air vehicle of claim 1, wherein the counter-rotating propellers are mounted on the projecting arm one above the other.

10. An omni-directional air vehicle of claim 9, wherein the turbofan system is mounted over the pod.

11. An omni-directional air vehicle comprising:

a pod;

a turbofan system connected to the pod the turbofan system having a ducted fan with counter-rotating propellers, a spherical articulation mechanism with a projecting arm on which the propellers are mounted, and a shroud with struts connected to the projecting arm, wherein the pod has a body for seating the spherical articulation mechanism and the ducted fan has counter-rotating electric motors driving the counter-rotating propellers wherein the counter-rotating electric motors are integrated in the shroud around the periphery of the propellers; and,

a power source connected to the counter-rotating electric motors.

\* \* \* \* \*