



US009114871B2

(12) **United States Patent**
Woodworth et al.

(10) **Patent No.:** **US 9,114,871 B2**

(45) **Date of Patent:** **Aug. 25, 2015**

(54) **MODULAR MINIATURE UNMANNED AIRCRAFT WITH VECTORED-THRUST CONTROL**

USPC 244/7 R, 7 A, 7 C, 12.4, 17.23, 17.25, 49, 244/51, 56, 108, 110 H, 120, 137.4, 138, 244/140, 190, 53 R, 54; 446/6, 30-45, 446/55-61, 63-66, 68; 16/320
See application file for complete search history.

(71) Applicant: **Aurora Flight Sciences Corporation**, Manassas, VA (US)

(72) Inventors: **Adam John Woodworth**, Melrose, MA (US); **James Peverill**, Canton, MA (US); **Greg Vulikh**, Manassas, VA (US); **Jeremy Scott Hollman**, Manassas, VA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,791,867 A 5/1957 Dasher
3,177,612 A 4/1965 Gioffi

(Continued)

(73) Assignee: **Aurora Flight Sciences Corporation**, Manassas, VA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 110 days.

FOREIGN PATENT DOCUMENTS

DE 102008023194 A1 * 12/2009
DE 102008061752 A1 * 6/2010

(Continued)

(21) Appl. No.: **13/954,362**

(22) Filed: **Jul. 30, 2013**

OTHER PUBLICATIONS

Welcome to Paparazzi, retrieved from <http://paparazzi.enac.fr/wiki/Main_Page> on May 31, 2012.

(Continued)

(65) **Prior Publication Data**

US 2014/0061390 A1 Mar. 6, 2014

Related U.S. Application Data

(60) Division of application No. 13/567,015, filed on Aug. 4, 2012, now Pat. No. 8,500,067, which is a continuation-in-part of application No. 12/556,225, filed on Sep. 9, 2009, now Pat. No. 8,721,383.

Primary Examiner — Philip J Bonzell

Assistant Examiner — Michael Kreiner

(74) *Attorney, Agent, or Firm* — Katten Muchin Rosenman LLP

(51) **Int. Cl.**

B64D 27/00 (2006.01)
B64C 1/30 (2006.01)

(Continued)

(57) **ABSTRACT**

An aircraft for unmanned aviation is described. The aircraft includes an airframe, a pair of fins attached to a rear portion of the airframe, a pair of dihedral braces attached to a bottom portion of the airframe, a first thrust-vectoring (“T/V”) module and a second T/V module, and an electronics module. The electronics module provides commands to the two T/V modules. The two T/V modules are configured to provide lateral and longitudinal control to the aircraft by directly controlling a thrust vector for each of the pitch, the roll, and the yaw of the aircraft. The use of directly articulated electrical motors as T/V modules enables the aircraft to execute tight-radius turns over a wide range of airspeeds.

(52) **U.S. Cl.**



CPC **B64C 1/30** (2013.01); **A63H 27/001** (2013.01); **A63H 27/02** (2013.01); **B64C 15/00** (2013.01);

(Continued)

21 Claims, 31 Drawing Sheets

(58) **Field of Classification Search**

CPC ... A63H 17/02; A63H 27/001; A63H 27/002; A63H 27/004; A63H 27/007; A63H 27/02; B64C 2201/18; B64C 2201/187; B64C 2201/20; B64C 2201/201; B64C 2201/203; B64D 1/14; B64D 2027/262; B64D 27/26



(51)	<p>Int. Cl. <i>B64D 27/26</i> (2006.01) <i>B64D 9/00</i> (2006.01) <i>B64C 19/00</i> (2006.01) <i>B64D 1/14</i> (2006.01) <i>B64C 15/00</i> (2006.01) <i>B64C 39/02</i> (2006.01) <i>A63H 27/00</i> (2006.01)</p>	<p>5,087,000 A * 2/1992 Suto 244/189 5,100,357 A 3/1992 MacCready et al. 5,568,903 A 10/1996 Pena et al. 5,947,785 A 9/1999 Bausch 6,425,794 B1 7/2002 Levy et al. 6,612,893 B2 * 9/2003 Rehkemper et al. 446/34 6,682,017 B1 1/2004 Giannakopoulos 6,719,224 B2 4/2004 Enomoto et al. 6,719,244 B1 4/2004 Gress 6,776,373 B1 8/2004 Talmage, Jr. 6,840,480 B2 1/2005 Carroll 7,089,627 B2 8/2006 Seidler 7,237,750 B2 7/2007 Chiu et al. 7,262,395 B2 8/2007 Bilyk et al. 7,318,565 B2 1/2008 Page 7,997,526 B2 * 8/2011 Greenley 244/7 B 8,136,766 B2 3/2012 Dennis 8,162,263 B2 4/2012 Wong et al. 8,328,130 B2 12/2012 Goossen 2006/0091258 A1 5/2006 Chiu et al. 2006/0192047 A1 8/2006 Goossen 2008/0223994 A1 9/2008 Greenley 2011/0057074 A1 3/2011 Woodworth et al.</p>
(52)	<p>U.S. Cl. CPC <i>B64C 19/00</i> (2013.01); <i>B64C 39/028</i> (2013.01); <i>B64D 1/14</i> (2013.01); <i>B64D 9/00</i> (2013.01); <i>B64D 27/26</i> (2013.01); <i>B64C</i> <i>2201/028</i> (2013.01); <i>B64C 2201/042</i> (2013.01); <i>B64C 2201/104</i> (2013.01); <i>B64C 2201/127</i> (2013.01); <i>B64C 2201/165</i> (2013.01); <i>B64C</i> <i>2201/18</i> (2013.01); <i>B64C 2201/187</i> (2013.01); <i>B64C 2201/201</i> (2013.01)</p>	
(56)	<p>References Cited</p>	

U.S. PATENT DOCUMENTS

3,777,395 A	12/1973	Chang	
3,908,305 A	9/1975	Schroeder	
3,999,328 A	12/1976	Schroeder	
4,027,422 A	6/1977	Schroeder	
4,143,841 A	3/1979	Roeder	
4,358,072 A	11/1982	Williamson	
4,496,120 A	1/1985	Eickmann	
4,591,114 A	5/1986	Block	
4,714,444 A	12/1987	Rendel	
4,736,910 A	4/1988	O'Quinn et al.	
4,746,082 A	5/1988	Syms et al.	
4,759,736 A	7/1988	Carlson	
4,891,029 A *	1/1990	Hutchinson 446/58	
4,957,465 A	9/1990	dasa	
5,035,382 A	7/1991	Lissaman et al.	

FOREIGN PATENT DOCUMENTS

GB	2446589 A	8/2008
WO	WO 2009071755 A1 *	6/2009

OTHER PUBLICATIONS

Transmittal; International Search Report; and Written Opinion of the International Searching Authority for International Application No. PCT/US2013/053271 with a mailing date of Nov. 26, 2013.
"Paparazzi User's Manual." Ecole Nationale de l'Aviation Civile. Toulouse, France, Feb. 3, 2008. Accessed online from <http://wiki.paparazziuav.org/w/images/O/Oa/Users_manual.pdf> on Sep. 29, 2014.

* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4b

Figure 4a




Figure 5b




Figure 5c




Figure 5a




Figure 6a




Figure 6b




Figure 6c




Figure 6d




Figure 7





Figure 8a



102

Figure 8b

102




Figure 8c




Figure 8d

102




Figure 9a




Figure 9b




Figure 9c




Figure 9d

1000




Figure 10




Figure 11

1102




Figure 12a




Figure 12b




Figure 12c




Figure 12d




Figure 12e




Figure 13a




Figure 13b




Figure 13c




Figure 14




Figure 15a




Figure 15b




Figure 15c




Figure 15d

1

**MODULAR MINIATURE UNMANNED
AIRCRAFT WITH VECTORED-THRUST
CONTROL**

CROSS REFERENCE TO RELATED
APPLICATIONS

This application is a divisional of U.S. patent application Ser. No. 13/567,015, filed Aug. 4, 2012 (now U.S. Pat. No. 8,500,067, issued Aug. 6, 2013), which is a continuation-in-part of commonly owned U.S. patent application Ser. No. 12/556,225, filed on Sep. 9, 2009, by Adam Woodworth and Brandon Suarez, both of which are incorporated herein by reference.

TECHNICAL FIELD

The present invention relates to miniature unmanned aircraft. More particularly, the present invention relates to aircraft that use thrust-vectoring (“T/V”) modules to enable the aircraft to execute tight-radius turns at high angular rates over a wide range of speeds.

BACKGROUND INFORMATION

The use of unmanned aerial vehicles (“UAVs”) has become important in recent years for a wide variety of applications, including military uses. In some applications, a UAV may be required to be capable of maneuvering quickly or in tight spaces. Further, the UAV may be required to have this capability over a wide range of speeds.

Conventional, fixed-wing, small UAVs generally lack the maneuverability and speed range that would be necessary for operating in an urban canyon. Generally, this is due to a reliance upon airflow over control surfaces derived from the forward airspeed of the vehicle. Therefore, vertical-takeoff-and-landing (“VTOL”) aircraft have been used to address this maneuvering challenge at low speeds. For example, in U.S. Pat. No. 6,719,244, a VTOL aircraft uses lateral tilting of the propellers to induce unbalanced torque-induced and gyroscopic moments which act on the aircraft about an axis essentially perpendicular to the tilt axis. Similarly, U.S. Patent Application Publication No. 2006/0192047 discloses a hovering aerial vehicle that uses two ducted fans attached to a common drive housing. In operation, the vanes below each fan body may be tilted differentially or in unison to generate control forces. In certain aspects, fixed wings may be attached to the ducts for forward flight capability.

Despite the foregoing advancements, a need still exists for an aircraft capable of executing tight-radius turns at high angular rates over a wide range of speeds. Moreover, a need exists for a low-cost and/or durable aircraft capable of executing tight-radius turns at high angular rates over a wide range of speeds. Finally, a need exists for an aircraft that may be organically deployed and that involves only nominal assembly.

Accordingly, the subject disclosure provides durable aircraft that use thrust-vectoring modules to enable the aircraft to execute tight-radius turns at high angular rates over a wide range of speeds. The subject disclosure also describes aircraft that employ frangible aircraft components to mitigate or eliminate damage by transferring landing energy into kinetic energy operating on the frangible components upon impact.

SUMMARY

The present disclosure endeavors to provide an aircraft that uses thrust vectoring (T/V) modules to enable the aircraft to execute tight-radius turns at high angular rates over a wide range of speeds.

2

According to a first aspect of the present invention, a T/V module for providing propulsion forces in an aerial vehicle comprises a propeller; an electric motor, wherein the electric motor is configured to rotate the propeller; a rigid link having a first end and a second end, wherein the first end is coupled with the electric motor; a positioning device coupled with the second end of the rigid link, wherein the positioning device is configured to position the electric motor by rotating the rigid link; and a retention mechanism for passively securing the T/V module to the aerial vehicle.

According to a second aspect of the present invention, an aerial vehicle for reducing impact loads comprises an airframe; a payload module coupled to the airframe via one or more passive engagement tabs; and a battery module configured to interface with the airframe and the payload module, wherein the payload module and the battery module are configured to eject from the airframe during impact.

According to a third aspect of the present invention, a folding airframe comprises: a plurality of integrated hinges, each integrated hinge defining a fold line; a locking mechanism, wherein the locking mechanism is used to lock the folding airframe in a deployed position; and at least one passive retention device for securing one or more flight components to the folding airframe, wherein said one or more flight components are configured to eject upon sudden impact.

According to a fourth aspect of the present invention, an aircraft for unmanned aviation comprises an airframe having two or more shallow pockets, each shallow pocket comprising an electrical interface; a payload module coupled to the airframe; a battery module configured to interface with the airframe and the payload module; two or more thrust vectoring modules configured to interface with the payload module via the electrical interface, each of said two or more T/V modules being configured to reside within one of the shallow pockets; wherein said two or more T/V modules provide lateral and longitudinal control to the aircraft by directly controlling a thrust vector; and an electronics module configured to provide commands to the at least two T/V modules.

According to certain aspects, the locking mechanism may comprise one or more rods fixed to an edge of the folding airframe. The one or more rods may be fixed to the folding airframe using at least one clip or a magnet. Alternatively, the locking mechanism may comprise one or more magnets at each fold line.

According to certain aspects, the electric motor’s rotational speed may be controlled to produce a desired amount of thrust.

According to certain aspects, the positioning device may comprise an electric servo.

According to certain aspects, the retention mechanism may comprise a high-strength permanent magnet.

According to certain aspects, the positioning device may be configured to position the electric motor by rotating the rigid link about at least one degree of freedom.

According to certain aspects, the thrust vectoring module may be configured to passively break away from the aerial vehicle upon sudden impact.

According to certain aspects, the thrust vectoring module may be electrically interfaced with the aerial vehicle.

According to certain aspects, the battery module may be configured to eject from the airframe along an ejection path that does not intersect with any other aircraft component.

According to certain aspects, the aerial vehicle may comprise a ramp interface between the airframe and the payload module.

According to certain aspects, the payload module may comprise avionics and sensor payloads.

According to certain aspects, each thrust vectoring module may comprise a propeller, an electric motor and a positioning device configured to position the electric motor.

According to certain aspects, the thrust vectoring modules may be configured to independently control a pitch, a roll, and a yaw of the aircraft.

According to certain aspects, the airframe may be foldable into a compact, stowable configuration.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other advantages of the present invention will be readily understood with reference to the following specifications and attached drawings, wherein:

FIG. 1 illustrates a first modular miniature unmanned aircraft with vectored-thrust control in a deployed configuration;

FIG. 2 illustrates the major components of a disassembled first modular miniature unmanned aircraft with vectored-thrust control;

FIG. 3 illustrates an electronics module and two T/V modules for a modular miniature unmanned aircraft;

FIG. 4a illustrates a portion of an airframe configured to receive a T/V module;

FIG. 4b illustrates the portion of FIG. 4a with a T/V module configured thereon;

FIGS. 5a through 5c illustrate a T/V module for use with a modular miniature unmanned aircraft;

FIGS. 6a through 6d illustrate four directional motions based on action by the T/V modules of a modular miniature unmanned aircraft with vectored-thrust control;

FIG. 7 illustrates the modular miniature unmanned aircraft with vectored-thrust control of FIG. 1 in a stowed configuration;

FIGS. 8a through 8d illustrate a folding process for compactly packing a modular miniature unmanned aircraft;

FIGS. 9a through 9d illustrate a dihedral brace for use as a landing skid and locking element on a modular miniature unmanned aircraft;

FIG. 10 illustrates a flow chart for a method of controlling a flight path of a modular miniature unmanned aircraft with vectored-thrust control;

FIG. 11 illustrates a second modular miniature unmanned aircraft with vectored-thrust control in a deployed configuration;

FIGS. 12a and 12b illustrate an airframe for a modular miniature unmanned aircraft;

FIG. 12c illustrates the underside of a T/V module for use with the airframe component of FIGS. 12a and 12b;

FIG. 12d illustrates a rear prospective view of the T/V module of FIG. 12c;

FIG. 12e illustrates an enlarged view of the shallow pocket of FIGS. 12a and 12b;

FIGS. 13a, 13b, and 13c illustrate a first folding airframe configuration of the airframe component of FIGS. 12a and 12b;

FIG. 14 illustrates a second folding airframe configuration of the airframe component of FIGS. 12a and 12b; and

FIGS. 15a through 15d illustrate a modular miniature unmanned aircraft having frangible aircraft components ejected during four phases of ground impact.

DETAILED DESCRIPTION

Embodiments of the present invention will be described hereinbelow with reference to the accompanying drawings.

In the following description, well-known functions or constructions are not described in detail because they would obscure the invention in unnecessary detail.

The present disclosure endeavors to provide a modular miniature unmanned aircraft with vectored-thrust control enabled to synergistically mesh sensor and aircraft capabilities into a system capable of navigating through highly cluttered urban environments. Whereas traditional force production techniques rely on airflow over control surfaces, a modular miniature unmanned aircraft with vectored-thrust control may employ articulated electric motors to directly change the thrust vector. Directly changing both the magnitude and the direction of the thrust vector allows the modular miniature unmanned aircraft to execute tight-radius high-angular-rate turns, over a wide speed range and in the post-stall regime.

Moreover, the modular miniature unmanned aircraft airframe may feature a low aspect ratio (i.e., the ratio of a wing's length to its breadth) planform, which permits rapid deceleration/perch maneuvers, and permits benign controlled flight at large angles of attack. Such features provide the additional advantages of reduced system complexity and increased durability. Further, all of the moving parts of the modular miniature unmanned aircraft are preferably co-located in ruggedized modules or "pods", while making the actual airframe a fairly low-cost, disposable and/or interchangeable element of the modular miniature unmanned aircraft system.

The modular miniature unmanned aircraft of the present disclosure may be configured to execute a turn having a radius of less than or equal to one wing span. Moreover, the modular miniature unmanned aircraft may be further configured to operate with an airspeed of zero with its nose pointing vertically, thereby operating in a hover mode. While in a hover mode, the aircraft may rotate about a vertical axis. Finally, the modular miniature unmanned aircraft can perform a pirouette maneuver at a rate of more than one rotation per second.

The maximum angular rate of the modular miniature unmanned aircraft is generally a function of the forward airspeed, with the only limitation being equivalent to the physical limits associated with centrifugal forces at the given forward airspeed. Therefore, turning and rotating maneuvers of the modular miniature unmanned aircraft may be executed at virtually any forward airspeed between zero and the maximum forward airspeed of the modular miniature unmanned aircraft itself.

As will be discussed in greater detail below, T/V modules serve as a propulsion means for the aircraft, while allowing for quick aircraft assembly time and yielding a vehicle configuration that is more robust to landing impact loads. Each T/V module generally comprises a thrust-generating propeller that produces varying amounts of thrust at varying rotational speeds, an electric motor that spins the propeller at the varying speeds, a rigid link that the electric motor mounts to a positioning device that rotates the rigid link, and a retention device that passively retains the motor module against the aircraft's structure. Each T/V module may be configured to electrically couple with the aircraft (e.g., an electronics module) via a cable or directly via an electrical interface through the base of the T/V module.

As disclosed herein, a modular miniature unmanned aircraft configuration may be developed into a scalable series of vehicles, ranging from, for example, 6 inches to 100 inches in length. However, the modular miniature unmanned aircraft illustrated in the figures is illustrated as having a full length of approximately 24 inches.

The modular miniature unmanned aircraft vehicle may be equipped with an autopilot such as, for example, Paparazzi autopilot, which is used for flight tests in support of the Micro Air Vehicle Small Business Innovative Research grant. Paparazzi autopilot is an open-source hardware and software project intended to create an exceptionally powerful and versatile autopilot system by allowing and encouraging input from the community. Features of the Paparazzi autopilot include its combination of infrared thermopiles and inertial measurement for attitude sensing, providing a robust and accurate attitude estimate that requires no ground calibration and can recover from any launch attitude. For additional information on the Paparazzi autopilot, see, for example, Paparazzi's website.

Alternatively, the modular miniature unmanned aircraft vehicle may be controlled using conventional wireless remote control technologies. For example, flight may be controlled using a handheld remote control, portable computer (e.g., laptop or smart phone), vehicle or command station via a network (e.g., the Internet). Finally, the aircraft may follow a predetermined flight path using autopilot stored to the vehicles on-board memory (e.g., a computer readable medium).

Referring to FIG. 1, a first modular miniature unmanned aircraft 100 with vectored-thrust control is depicted in a fully deployed configuration. The modular miniature unmanned aircraft 100 generally comprises an airframe 102, two or more fins 108, an electronics module 104, two or more skids 110, and two or more T/V modules 106. As illustrated, the airframe 102 forms a wing planform having a low aspect ratio (i.e., short and stubby wings).

Adjusting the aspect ratio and planform (e.g., the shape and layout of a fixed-wing aircraft's fuselage and wing) can be used to predict the aerodynamic performance of a wing. As exemplified in Equation 1, the aspect ratio (AR) is defined as the square of the wingspan b divided by the area S of the wing planform—this is equal to the length-to-breadth ratio for constant breadth. Accordingly, it may be preferable to employ a wing having a low AR value. The AR value of an aircraft as illustrated in the figures may be, for example, 1.26. However, the AR value may be readily adjusted by the designer to achieve a particular purpose.

$$AR = \left(\frac{b^2}{S} \right) \quad \text{Equation 1}$$

Low-aspect-ratio wing planforms encourage more efficient structures and higher instantaneous roll rate. Accordingly, such planforms tend to be used by fighter aircraft and by very high-speed aircraft where maneuverability and speed are important.

Each T/V module 106 comprises a directly articulated electric motor for providing lateral and longitudinal control. Specifically, as will be disclosed below, the directly articulated electric motor may be accomplished using a DC electric motor coupled with an articulating arm, which may be controlled by an electric servo. The two T/V modules 106 may be deflected in unison for pitch control and differentially for yaw control. Low mass propellers 114 may be used to mitigate unwanted force coupling with motor deflection. The propellers may be either 2 or 3 blade configuration and may comprise a fiber reinforced polymer material. The propellers 114 may operate in a counter-rotational mode to cancel or offset gyroscopic effects and improve cruise efficiency due to a reduction in induced drag by spinning in a direction such that

the propeller wake opposes the spin direction of the normal tip vortex. In order to operate in a counter-rotational mode, the left and right propellers may be mirror images of each other. While only two T/V modules 106 are illustrated, additional T/V modules 106 may be integrated as desired for a particular use. For example, to enhance VTOL operation, a tri-motor or quad-motor configuration may be used. Specifically, additional T/V modules 106 may be provided at the aft end of the airframe 102.

As illustrated, a modular miniature unmanned aircraft 100 features a modular vehicle architecture. A modular vehicle architecture facilitates airframe 102 interchangeability, including, for example, disposable airframes, folding airframes, and/or the use of mission-specific airframes (e.g., a smaller planform, which could be employed in gusty environments). For example, as will be discussed in greater detail below, FIG. 11 illustrates a second modular miniature unmanned aircraft 1100 employing similar techniques, but having a different airframe 1102. Accordingly, each component, or module, should be easily detached from the aircraft 100 and substantially self-contained in a module or "pod."

Referring to FIG. 2, a modular miniature unmanned aircraft 100 with vectored-thrust control generally comprises eight major components or modules: the airframe 102, two fins 108, two combination landing skids 110 (e.g., dihedral braces), an electronics module 108, and T/V modules 106. In certain situations, it may be preferable to construct the airframe 102, fins 108, and skids 110 from a low cost disposable material (e.g., expanded polypropylene foam (EPP)). Therefore, in the event of a crash, the airframe 102, fins 108, and skids 110 may be readily and relatively inexpensively replaced, while the more costly components, such as the electronics module 108 and T/V modules 106, are reused.

FIG. 3 illustrates an electronics module 104 and two T/V modules 106, which may serve as the primary flight components for a modular miniature unmanned aircraft 100. The electronics module 108, or centerline avionics/payload "pod," houses the vehicle's avionics, propulsion battery, and sensor payload while providing rigidity to the airframe 102 when assembled. While the electronics module 108 is depicted as being a single module, as will be discussed in greater detail below, the electronics module 108 may comprise multiple modules or "sub-modules." For example, the electronics module 108 may be divided into two modules, a first module for housing heavier components, such as the battery, and a second module for housing the more delicate components, such as the avionics, surveillance payload, sensor payload and any other electronic equipment. More specifically, the aircraft 100 may further include one or more sensors used to facilitate autonomous flight. Such sensors may include, but are not limited to, ultrasonic sensor, infrared sensors, radar and the like. The electronics module 108 pod, or housing, may be fabricated from, for example, a plastic polymer such as acrylonitrile butadiene styrene, ABS. The packaging volume of the electronics module may be approximately 1.5×1.5×1.0 inch.

The T/V modules 106 provide propulsive power and control forces for the aircraft 100 during operation. Each T/V module 106 is electronically coupled with the electronics module 108 via a cable 112 or, as will be described below, through an integrated electrical interface. The cable 112 may be a bundle of conductors and configured to transmit both power and/or data signals between the electronics module 108 and the T/V modules 106. To facilitate quick detachment of a T/V module 106 from the electronics module 108, each cable 112 may comprise an electrical connector 122, such as a plug and socket connector. In embodiments where the cable

112 is configured to transmit both data signals and power, the data signal conductors may be shielded from the power conductors to reduce or eliminate interference or noise. The electronics module **108** and T/V modules **106** may be used to provide all of the necessary elements for controlled flight (i.e., the equipment to power and control the aerial vehicle).

The electronics module **108** and T/V modules **106** are preferably configured to be easily installed on and/or removed from the airframe **102** to facilitate stowage or permit use of other airframes (e.g., replacement or mission-specific). Thus, each T/V module **106** and/or electronics module **108** is preferably coupled with the airframe **102** via an integrated breakaway mount. The integrated breakaway mount should be sufficiently strong to keep the components secured in place during operation, but capable of giving way (e.g., detaching) upon sudden impact (e.g., ground impact, in-air impact or any other unexpected impact or collision) or intentional disassembly by the operator. For example, as illustrated in FIG. **4a**, the airframe **102** may be provided with a retention device that passively retains each T/V module **106** to the aircraft's structure (e.g., airframe **102**). The retention device for attaching the T/V modules **106** to the airframe **102** may comprise, for example, magnets **116** and/or one or more anti-rotation brackets **118**. The magnets **116** may be mounted on a surface of the airframe **102** or embedded within the airframe **102**. The magnets **116** are preferably configured to engage with corresponding magnets positioned on the underside of the T/V modules **106**. Similar techniques may be used to attach the electronics module **108** to the airframe **102**. For example, a series of magnets and clips may be provided on the airframe **102** and configured to engage with corresponding magnets and clips on the electronics module **108**.

To avoid a reduction in aircraft performance, the magnets **116**, brackets **118**, and clips are preferable light in weight and high in strength. For example, the magnets **116** may be high-strength neodymium magnets. Neodymium magnets are permanent magnets made from an alloy of neodymium, iron, and boron to form the Nd₂Fe₁₄B tetragonal crystalline structure. The anti-rotation brackets **118** and clips, on the other hand, may be constructed from, for example, lightweight plastics, metals or metal alloys. The anti-rotation brackets **118** are used to resist thrust and torque loads generated by the T/V module **106** by securing two or more sides of the T/V module's **106** base, yet allowing for the T/V modules **106** to detach in the event of impact. FIG. **4b** illustrates the same view as FIG. **4a**, but with a T/V module **106** secured in place.

Detailed side views of a T/V module **106** are provided in FIGS. **5a** through **5c**. As illustrated in FIG. **5a**, the T/V module **106** comprises an electric motor **106a**, a positioning device **106b**, a propeller **114**, and a rigid link **106c**. The electric motor **106a** is preferably a brushless electric motor, while the positioning device **106b** may comprise an electric servo, which is a type of actuator often used for radio control and small robotics. The electric motor **106a** and positioning device **106b** may each be powered by direct electric current supplied by the electronics module **104**.

A typical servo comprises a small electric motor driving a train of reduction gears and a potentiometer connected to the output shaft. In operation, the position of the output shaft, measured by the potentiometer, can be continually compared to the commanded position from the control (e.g., the radio control). Any difference gives rise to an error signal in the appropriate direction, which drives the electric motor either forward or backward and moves the output shaft to the commanded position. When the servo reaches this position, the error signal reduces and then becomes zero, at which point the servo stops moving.

As illustrated, a rigid link **106c** attaches the electric motor **106a** to the positioning device's **106b** output shaft. Although other types are available, the positioning device **106b** is preferably a rotary actuator and operates by rotating the rigid link **106c** about one degree of freedom while consuming minimal power and precisely controlling the position of the rigid link **106c**. As the output shaft rotates, the rigid link **106c** is rotated such that the electric motor **106a** may be pointed forward (FIG. **5a**), upward (FIG. **5b**), downward (FIG. **5c**), or at any point therebetween. However, for additional control, the positioning device **106b** may be configured to direct the rigid link **106c** in two or more degrees of freedom.

Thus, the thrust **T** generated by a propeller **114** mounted on the electric motor's **106a** shaft can be directed to facilitate controlled flight. The amount of thrust **T** may be controlled by adjusting the speed of the electric motor **106a**. All data and power required to operate the electric motor **106a** and positioning device **106b** may be delivered through the conductive cable **112**. Thus, the electric motor **106a** and positioning device **106b** may each receive electric current and electric signals through the conductive cable **112** or other equivalent. Specifically, a conductive cable **112** may be exposed as illustrated in FIG. **1** or integrated with an airframe **1102** as discussed below with regard to FIG. **11**.

As illustrated in FIGS. **6a** through **6d**, the T/V modules **106** may be used to provide fully controlled flight. Specifically, lateral and longitudinal control may be achieved solely through the use of the two or more T/V modules **106** whereby the T/V modules **106** may move in unison for pitch control or move differentially for roll control. For example, two T/V modules **106** may be used to control the aircraft's **100** pitch, yielding an up-down movement of the aircraft nose measured by the angle of attack. When both T/V modules **106** are pointed upward (FIG. **6a**), the resulting thrust **T** is directed downward, thus resulting in a nose-up pitch. Conversely, when both T/V modules **106** are pointed downward (FIG. **6b**), the resulting thrust **T** is directed upward, thereby resulting in a nose-down pitch.

The two T/V modules **106** may also be used to control the aircraft's **100** roll, resulting in an up-down movement of the wing tips measured by the roll or bank angle. For example, when the port side T/V module **106** is pointed upward and the starboard side T/V module **106** is pointed downward (FIG. **6c**), the resulting thrust **T** on each side of the aircraft **100** is directed in an opposite direction, thus resulting in right roll. Conversely, when the port side T/V module **106** is pointed downward and the starboard side T/V module **106** is pointed upward (FIG. **6d**), the resulting thrust **T** on each side of the aircraft **100** is directed in an opposite direction, thus resulting in left roll. Finally, yaw control may be achieved through differential thrust commands to the T/V modules **106**. Specifically, each T/V module **106** may be separately controlled, thus the aircraft's **100** yaw may be controlled by adjusting the speed of a T/V module **106**.

The fully articulated movement of each T/V module **106** also enables VTOL operation. During takeoff, for example, both T/V modules **106** may be initially pointed upward. As the electric motor **106a** speed is increased with the T/V modules **106** in the upward configuration, the resulting thrust causes the nose end of the aircraft **100** to lift off the ground, while the tail end initially remains on or near the ground. Then, the motor **106a** thrust continues to increase and the T/V modules **106** begin to transition from the upward configuration to the forward configuration (e.g., as illustrated in FIG. **5a**) until the aircraft **100** has achieved a hover mode.

When two T/V modules **106** are used, the aircraft platform is typically substantially perpendicular to the ground with the

T/V module **106** in the forward direction during hover mode. However, additional T/V modules **106** may be integrated (e.g., at the aft end of the airframe **102**) to enable a more traditional VTOL liftoff, whereby the aircraft is substantially parallel to the ground during liftoff and hover, wherein the T/V module **106** in an upward direction. Once in hover mode, the aircraft **100** may transition to a forward-flight mode.

Referring to FIG. 7, the modular miniature unmanned aircraft **100** is shown in a stowed configuration. As a result of its modular architecture, the modular miniature unmanned aircraft **100** may be readily disassembled and transported in, for example, a carrying case **700**. To prevent damage to the various modules or components, the case **700** may provide padded compartments configured to receive each module or component. To facilitate portability, the case **700** may be provided with a carrying handle **702**. The portability of the modular miniature unmanned aircraft **100** encourages quick organic deployment of the aircraft **100**.

A folding wing configuration may be employed to reduce the stowed footprint of the aircraft **100**, while minimizing the reduced structural strength inherent to adding fold lines to an aircraft wing. Referring to FIGS. **8a** through **8d**, because the airframe **102** does not require control surfaces or other integrated systems, the airframe **102** can be folded to significantly reduce the packed size of the aerial vehicle (i.e., when stowed). The folding scheme may include four integrated hinges, as illustrated in FIG. **8b**. Two dihedral hinges A and a chord-wise hinge B may be located on the upper surface of the aircraft, and a centerline hinge C may be located on the lower surface. When deflected, the tip dihedral hinge locks the chord-wise hinge, thereby minimizing the amount of hardware needed to rigidize the airframe **102**. As illustrated in FIG. **8d**, the area of the airframe **102** may be reduced by approximately 75%, thereby facilitating stowage within, for example, a carrying case **700**.

Referring to FIGS. **9a** through **9d**, the landing skids **110**, also referred to as dihedral braces, may engage a pair of skid clips **120**. As illustrated in FIG. **9b**, the landing skids **110** may lock the dihedral hinges A at a predetermined angle when assembled. To lock the dihedral hinges A at a predetermined angle, one skid clip **120** is preferably positioned on each side of the dihedral hinge A as illustrated in FIGS. **9c** and **9d**. The upper end of the portion, which connects to the airframe **102**, is preferably rigidly formed at the desired dihedral hinge angle. Thus, coupled with the electronics module **104**, which locks the centerline hinge C, the airframe **102** is fully rigidized when assembled in a deployed configuration. As a result, the landing skids **110** and electronics module **104** may be the only fasteners needed to hold the airframe **102** in the deployed configuration.

Referring to FIG. **10**, a flowchart **1000** illustrates a method for controlling a flight path of a UAV, such as a modular miniature unmanned aircraft with vectored-thrust control, according to a preferred embodiment of the invention. In the first step **1005**, instructions for controlling the speed and direction of the modular miniature unmanned aircraft are transmitted by a user to the electronics module. In the second step **1010**, the electronics module converts these instructions into commands which are sent to the two or more T/V modules. Finally, in the third step **1015**, the T/V modules provide thrust in the appropriate directions and magnitudes to cause the modular miniature unmanned aircraft to change direction, thereby controlling the flight path of the modular miniature unmanned aircraft both laterally and longitudinally.

FIG. **11** illustrates a second modular miniature unmanned aircraft **1100** that operates in substantially the same manner as the miniature unmanned aircraft **100** and uses substantially

identical T/V modules **106**. As illustrated, the aircraft **1100** may utilize a blended wing-body configuration. Specifically, the removable electronics module **1104**, which is akin to a fuselage, provides a smooth transition between the wing portion of the airframe **1102** and electronics module **1104**.

Unlike the miniature unmanned aircraft **100**, the second modular miniature unmanned aircraft **1100** employs an airframe **1102** having shallow pockets **1112**, **1124**, each providing an interface point for engagement with the T/V modules **106** and/or electronics module **1104**. When assembled, the airframe **1102** and various interface points are configured to facilitate communication between the various modules, such as the T/V modules **106** and electronics module **1104**. For example, an integrated wiring harness may be used. When an integrated wiring harness is desired, conductors for carrying data and power may be embedded, or run, within the airframe **1102** and configured to communicatively connect the interface points. The conductors may be run within hollow portions of the airframe **102** or embedded within the actual airframe material. For example, carbon nanotubes (“CNT”) may be embedded within the airframe **102** material. Commonly owned U.S. patent application Ser. No. 13/561,598, filed Jul. 30, 2012, (incorporated herein by reference) discloses a suitable embedded CNT harness and method of doing the same.

Therefore, rather than employing exposed conductive cables **112** to send and receive electric current and electric signals as illustrated in FIG. **1**, the T/V modules **106** may interface directly to the aerial vehicle **1100**, whereby conductive cabling is integrated within the body of the airframe.

Accordingly, in addition to a physical interface for physically securing each module with the airframe **1102**, each shallow pocket interface point **1112**, **1124** may comprise an electrical interface for communicating signals or power between modules via the integrated wiring harness. According to this aspect, the aerial vehicle **1100** is more streamlined, thereby reducing drag and eliminating risk of having an exposed conductive cable **112** becoming entangled during operation.

To enable electrical interface functionality, each interface location **1112**, **1126** of FIG. **12** may comprise one or more electrical contact pads **1130** and electrical contact pins **1128**. The pins **1128** may reside on the aircraft’s side (e.g., on the airframe **1102**) and may be spring loaded to ensure contact. For example, the spring loaded pins **1128** may be located on the aircraft side. However, the spring loaded pins **1128** may also be located on the T/V module **106**, or a combination thereof. Similarly, the pins **1128** located at the interface between wing and payload module **106** may be on the aircraft and/or payload pod side. Suitable spring loaded pins include Mill-Max Spring-Loaded (“Pogo Pin”) Contacts. Mill-Max Spring Loaded Contacts are button type contacts interconnecting two parallel conductive surfaces inside an electronic device or instrument (e.g., between an aircraft surface and motor/payload module). The stroking movement of the spring pin piston accommodates uneven non-parallel conditions due to mechanical tolerances in the assembly. The contacts may be constructed out of gold-plated brass alloy components and a gold-plated spring.

The pads **1130** and contact pins **1128** allow for electrical power and signal transfer, while also allowing for easy attachment and removal of the T/V modules **106**. In further embodiments, the electric power and signal transfer may be achieved using common electrical connectors, but may not preferred as it requires the end user to physically disconnect/connect the connector, resulting in an additional step by the operator to attach and remove the T/V modules **106**.

11

As illustrated, when assembled, each T/V module **106** resides within a shallow pocket **1112** that provides anti-rotation bracket functionality, thus eliminating the need for a separate anti-rotational bracket. Specifically, the shallow pocket **1112** is used to resist thrust and torque loads, yet allows easy removal of the T/V modules **106** from the aerial vehicle. More specifically, the walls of the shallow pocket **1112** may secure the T/V modules **106** in two translational directions and one rotational direction. A passive retention device **1114** secures the T/V modules **106** in the other three degrees of freedom. In a preferred embodiment, the passive retention device **1114** comprises high-strength permanent magnets, such as high-strength neodymium magnets. The electronics module **1004** may be similarly attached to the airframe **1002** and resides within the shallow pocket **1124**. Akin to the T/V module **106**, the electronics module **1004** electrically couples with the airframe **1002** via interface location **1126**.

FIG. **12c** provides an underside view of a T/V module **106** configured for attachment to the airframe **1102** and FIG. **12e** illustrates a corresponding shallow pocket **1112**. As illustrated, the underside of the servo mechanism **106b**, which serves as the T/V module's **106** base portion, may be equipped with one or more magnets **1114** for coupling with magnets positioned in the shallow pocket **1112** of the airframe **1102** and connection pads **1130**. The connection pads **1130** enabled the T/V module **106** to electrically interface with other modules via the integrated wiring harness running throughout the airframe **1102** and pins **1128**.

Like the magnets on the airframe **1102**, the magnets **1114** on the servo mechanism **106b** may also be high-strength neodymium magnets. Specifically, as illustrated, the magnets may be positioned within two corners of the shallow pocket **1112** while two additional magnets **1114**, of opposite polarity, are positioned in the respective corners of the T/V module **106**. The retention force of the mated magnets secures the T/V module **106** in the remaining two rotational directions and the one translational direction. This retention configuration allows for passive retention, wherein the end user is not required to activate, deactivate, or otherwise disable any mechanism to remove the T/V module **106** from the airframe **1002**.

When magnets are used, removal of the T/V module **106** only requires that the end user apply a reasonable force to pull or rock the T/V module **106** from its shallow pocket **1112**. This same force acts upon the T/V module **106** during impact, whereby the T/V module **106** passively ejects from the airframe **1102** during impact. Without ejecting, a significant portion of the entire vehicle's landing loads would have to travel through the T/V module **106**, resulting in undesirable damage to the T/V module **106**. As such, ejection serves to protect the mechanical components of the T/V module **106** from damage.

All components of the T/V module **106** (with the possible exception of the propeller **114**, motor **106a**, and rigid link **106c**) may be secured and housed together in a chassis or "pod." The T/V module **106** propellers **114** may be easily attached and removed from the motor **106c** for ground transportation or storage. Finally, FIG. **12d** provides a rear perspective view of the T/V module **106**.

As illustrated in FIGS. **13a** through **13c**, a folding airframe configuration may be employed to reduce the stowed footprint of the aircraft **1100** while minimizing the reduced structural strength inherent to adding fold lines to an airframe **1102**. Accordingly, as illustrated in FIG. **13a**, the airframe **1102** may be provided with three different fold lines **1116** that split the airframe's **1102** chord into four substantially equal-

12

length sections. The last of the sections **1102a**, the section most aft, may be utilized as a trim tab that trims the pitching moment of the aircraft **1100**. This section **1102a** should have a desired reflection angle, which may be retained by installing fins **1108**, and does not change during the flight duration. However, in certain aspects, the angle may be actively controlled during flight with, for example, an adjustment mechanism within airframe **1102**, such as a servo or piezoelectric element.

The airframe **1102** in its deployed configuration is ideally substantially rigid, with minimal mechanical compliance. Such rigidity may be accomplished by having two rods **1118** fixed to the edges of the airframe **1102** (e.g., one on each side). The rods **1118** may clip into the edge of the airframe **1102**. When not in use, the rods **1118** may be stored within the airframe **1102** itself. The clips **1120** are passive and provide a connection that has sufficient levels of compliance when the airframe **1102** is loaded in flight. In lieu of physical clips, the rods **1118** may be secured to the airframe **1102** via one or more magnets. In certain aspects, the two rods **1118** may be attached to each other by an elastic cord that runs through the inner diameter of the rods **1118** and through the airframe **1102** itself. The elastic cord may serve two purposes, to provide a tether between the rods **1118** and airframe **1102**, and to prevent the rods **1118** from moving forward or aft in their deployed configuration.

With respect to FIG. **13c**, in addition to, or in lieu of the rods **1118**, one or more magnets **1302** may be provided at each fold line **1116** (e.g., magnets of opposite polarity may be positioned on each side of the hinge) such that the magnets **1302** engaged with one another when the airframe **1102** sections are secured in a deployed position. To fold the airframe **1102** (e.g., for stowage), the operator may simply fold the aircraft at each fold line **1116** with sufficient force to overcome the magnet's **1302** strength. The magnets **1302** may be the same as, or similar to, the high power magnets used to secure the T/V modules **106** to the airframe **1102**.

Depending on the stowage needs, the airframe **1102** may be configured to fold into quarters as illustrated in FIG. **14**, rather than lengthwise. The folding scheme may include two integrated hinges: a chord-wise hinge and a centerline hinge. Rigidity of the airframe **1102** in the deployed position may be accomplished using the rods **1118** or magnets, as discussed above, and/or the electronics module **1108**.

In operation, the modular miniature unmanned aircraft **1100** may employ a deep-stall, high-glide angle approach for landing. A benefit of which over a conventional landing approach is a reduced runway length requirement, the disadvantage of which is a relatively high-landing impact load. However, two approaches may be taken to avoid damage to the aircraft's structure during a deep-stall landing.

The first approach is to increase the strength of the structure, typically achieved by increasing the size of the structure and strength of material. The other approach is to reduce the peak impact load. The former solution is generally undesirable because it requires substantial weight and cost to be added to the aircraft. Like any aircraft, the modular miniature unmanned aircraft's **1100** performance may be significantly hindered by the addition of weight. The aircraft weight can range from about 800 g to 1100 g with various sized payloads. Fortunately, as will be discussed below, the latter solution may be achieved through several means.

For example, peak impact loads may be reduced by designing the major components of the aircraft to be frangible. In other words, the major components may be configured to eject from the main aircraft structure during an impact. Accordingly, instead of being absorbed as strain energy by

13

the aircraft's structure, the landing or impact energy is transferred into kinetic energy of the frangible components. For example, as noted above and illustrated in FIGS. 15a through 15d, the T/V module 106 and electronics module 1104 may detach and eject from the main aircraft structure (e.g., the airframe 1102) during an impact, thereby mitigating potential damage to the components. Moreover, as illustrated in FIG. 15c, the electronics module 1004 may comprise two sub-modules, such as a payload sub-module 1104a and a battery sub-module 1104b. The highly dense, heavy components of the aircraft 1100 (e.g. the battery 1104b) may be designed to eject in a direction that minimizes contact with the less dense, more frangible components (e.g., the payload 1104a).

The controlled ejection of the frangible components may be accomplished by designing the manner in which the components mechanically interface with each other and with the aircraft structure (e.g., the airframe 1102). For example, the ejection of the payload 1104a and battery module 1104b may be controlled. More specifically, the payload 1104a may make use of a plurality of passive engagement tabs (e.g., four, two on each side of the payload 1104a) and a ramp interface between the airframe 1102 and the payload 1104a. The ramp interface may be approximately 45 degrees to the typical impact load direction. As such, the impact load when transferred from the payload board to the aircraft frame is results in a portion of that load separating the payload pod from the aircraft frame. The passive engagement tabs provide the retention force. By simply overcoming this retention force, which is accomplished by an impact, the engagement tabs disengage.

In a typical ground impact position, the payload module's 1104a nose is the first component to touch the ground 1110. This introduces a force at the ramp interface between the payload 1104a and the airframe 1102. This force pushes the payload module 1104a away from the airframe 1102 in direction A, ultimately disengaging the passive retention tabs. With the payload module 1104a removed, the aircraft 1100 and remaining battery 1104b have only lost a portion of their forward velocity. Soon after hitting the ground 1110, the aircraft structure, as well as the battery module 1104b, continues forward and hits the ground 1110 with no portion of the aircraft 1100 between the ground 1110 and the battery module 1104b, thus avoiding damage to the payload module 1104a by the heavy battery module 1104b. Similarly, the T/V modules detach and eject from the airframe 1102 upon impact with the ground 1110, thus mitigating damage to both the payload 1104a and T/V modules 106.

Although the present invention has been described with respect to what are currently considered to be the preferred embodiments, the invention is not limited to the disclosed embodiments. To the contrary, the invention is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

All U.S. and foreign patent documents, all articles, all brochures, and all other published documents discussed above are hereby incorporated by reference into the Detailed Description of the Preferred Embodiment.

What is claimed is:

1. An aircraft for unmanned aviation, comprising:

an airframe having two or more recessed regions, each recessed region comprising an electrical interface and a passive retention mechanism;
a payload module coupled to the airframe;

14

a battery module configured to interface with the airframe and the payload module;

two or more thrusters configured to interface with the payload module via the electrical interface, each of said two or more thrust vectoring modules being configured to passively couple to one of said two or more recessed regions via the passive retention mechanism;

wherein said two or more thrust vectoring modules provide lateral and longitudinal control to the aircraft by directly controlling a thrust vector; and

an electronics module configured to provide commands to the two or more thrust vectoring modules.

2. The aircraft of claim 1, wherein each of the two or more thrusters is configured to passively break away from the airframe during impact.

3. The aircraft of claim 1, wherein each of said two or more thrusters comprises an electric servo.

4. The aircraft of claim 1, wherein the passive retention mechanism is a high strength permanent magnet.

5. The aircraft of claim 1, wherein the two or more thrusters are further configured to independently control a pitch, a roll, and a yaw of the aircraft.

6. The aircraft of claim 1, wherein each of the two or more thrusters comprises a directly articulated electrical motor.

7. The aircraft of claim 1, wherein the airframe is foldable into a compact, stowable configuration.

8. The aircraft of claim 1, wherein the aircraft is configured for executing a turn having a radius of less than or equal to one wing span over a range of airspeeds from zero to a maximum speed of the aircraft.

9. The aircraft of claim 8, wherein the aircraft is further configured for executing a turn having a radius of less than or equal to one wing span while in a post-stall condition.

10. The aircraft of claim 1, wherein the airframe does not comprise a control surface.

11. The aircraft of claim 1, wherein the airframe is a folding airframe and comprises a plurality of integrated hinges, each integrated hinge defining a fold line and a locking mechanism for locking the airframe in a deployed position.

12. The aircraft of claim 1, wherein the passive retention mechanism is a magnetic retention mechanism.

13. The aircraft of claim 1, wherein the airframe is a foldable into a compact, stowable configuration.

14. The aircraft of claim 1, wherein the airframe is a folding airframe and comprises a plurality of integrated hinges, each integrated hinge defining a fold line and a locking mechanism for locking the airframe in a deployed position.

15. An aircraft for unmanned aviation, comprising:

an airframe having (1) a first recessed region comprising a first electrical interface and a first integrated non-destructive retention mechanism, and (2) a second recessed region comprising a second electrical interface and a second integrated non-destructive retention mechanism;

an electronics module operatively coupled to the airframe; a first thrust vectoring module coupled to said first recessed region via said first integrated non-destructive retention mechanism, and configured to interface with the electronics module via said first electrical interface; and

a second thrusters coupled to said second recessed region via said second integrated non-destructive retention mechanism, and configured to interface with the electronics module via said second electrical interface;

wherein each of said first thrust vectoring module and said second thrust vectoring module is configured to (i) provide lateral and longitudinal control to the aircraft by

15

directly controlling a thrust vector, and (ii) to independently control pitch, roll, and yaw of the aircraft, wherein each of said first thrust vectoring module and said second thrust vectoring module is independently articulable with respect to a portion of the fixed wing to which it is attached.

16. The aircraft of claim 15, wherein each of said first thrusters and said second thrust vectoring module is configured to passively break away from the airframe during impact.

17. The aircraft of claim 15, wherein each of said first thrusters and said second thrust vectoring module comprise an electric servo.

18. The aircraft of claim 15, wherein each of said first integrated non-destructive retention mechanism and said second integrated non-destructive retention mechanism comprises a magnet.

19. An aircraft for unmanned aviation, comprising: an airframe having (1) a first recessed region comprising a first electrical interface and a first integrated non-destructive retention mechanism, and (2) a second recessed region comprising a second electrical interface and a second integrated non-destructive retention mechanism,

16

wherein each of said first integrated non-destructive retention mechanism and said second integrated non-destructive retention mechanism comprises a magnet;

an electronics module operatively coupled to the airframe; a first thrusters coupled to said first recessed region via said first integrated non-destructive retention mechanism, and configured to interface with the electronics module via said first electrical interface; and

a second thrust vectoring module coupled to said second recessed region via said second integrated non-destructive retention mechanism, and configured to interface with the electronics module via said second electrical interface,

wherein said first thrust vectoring module and said second thrust vectoring module provide lateral and longitudinal control to the aircraft by directly controlling a thrust vector.

20. The aircraft of claim 19, wherein the magnet is a permanent magnet.

21. The aircraft of claim 19, wherein each of said first thrusters and said second thrust vectoring module is configured to passively break away from the airframe during impact.

* * * * *