



US006707419B2

(12) **United States Patent**
Woodington et al.

(10) **Patent No.:** **US 6,707,419 B2**
(45) **Date of Patent:** **Mar. 16, 2004**

(54) **RADAR TRANSMITTER CIRCUITRY AND TECHNIQUES**

3,974,501 A * 8/1976 Ritzie 342/128

(List continued on next page.)

(75) Inventors: **Walter Gordon Woodington**, Lincoln, MA (US); **Michael Joseph Delcheccolo**, Westford, MA (US); **Joseph S. Pleva**, Londonderry, NH (US); **Mark E. Russell**, Westford, MA (US); **H. Barteld Van Rees**, Needham, MA (US); **James T. Hanson**, Maynard, MA (US)

FOREIGN PATENT DOCUMENTS

DE	19632889	2/1998
DE	196 32 889 A1	2/1998
DE	195 23 693 A1	5/1998
DE	198 55 400	12/1998

(List continued on next page.)

OTHER PUBLICATIONS

International Search Report of PCT Application No. PCT/US01/25638 dated May 7, 2002.

Barnett, Roy I. et al. "A Feasibility Study of Stripline-Fed Slots Arranged as a Planar Array with Circular Grid and Circular Boundary", IEEE, 1989, pp. 1510-1515.

(List continued on next page.)

(73) Assignee: **Raytheon Company**, Waltham, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/931,636**

(22) Filed: **Aug. 16, 2001**

(65) **Prior Publication Data**

US 2002/0075178 A1 Jun. 20, 2002

Related U.S. Application Data

(60) Provisional application No. 60/226,160, filed on Aug. 16, 2000.

(51) **Int. Cl.**⁷ **G01S 7/35**; G01S 7/40; G01S 13/32; G01S 13/93

(52) **U.S. Cl.** **342/200**; 342/52; 342/53; 342/70; 342/82; 342/118; 342/128; 342/165; 342/173; 342/175; 342/195; 342/196

(58) **Field of Search** 342/120-125, 342/128-133, 165-175, 192-197, 52-55, 70, 71, 72, 82-88, 200-205, 118

(56) **References Cited**

U.S. PATENT DOCUMENTS


3,697,985 A	10/1972	Faris et al.
3,935,559 A	1/1976	Straffon et al.
3,940,696 A	2/1976	Nagy

Primary Examiner—Bernarr E. Gregory
(74) *Attorney, Agent, or Firm*—Daly, Crowley & Mofford, LLP

(57) **ABSTRACT**

A radar transmitter includes a digital ramp generator circuit for generating a VCO control signal. The ramp generator includes a digital signal processor and a digital-to-analog converter. In one embodiment, the VCO output signal is up-converted to provide the transmit signal and in another embodiment, the VCO operates over the transmit frequency. Also described is a VCO comprising a DR and a phase shifter. A temperature compensation feature includes detecting the transmit frequency and comparing the DSP output generating the detected frequency to a DSP output stored in association with the detected frequency. Also described is a technique for compensating for non-linear VCO operation in which the DSP output words are adjusted to provide a waveform complementary in shape to the non-linear VCO characteristic. Susceptibility of the radar to interference is reduced by randomly varying at least one parameter of the ramp signal, such as offset interval or voltage range, in at least one ramp signal cycle.

18 Claims, 16 Drawing Sheets



U.S. PATENT DOCUMENTS					
3,978,481 A	8/1976	Angwin et al.	5,495,252 A	2/1996	Adler
4,003,049 A	1/1977	Sterzer et al.	5,508,706 A	4/1996	Tsou et al.
4,008,473 A	2/1977	Hinachi et al.	5,517,196 A	5/1996	Pakett et al.
4,008,475 A	2/1977	Johnson	5,517,197 A	5/1996	Algeo et al.
4,035,797 A	7/1977	Nagy	5,521,579 A	5/1996	Bernhard
4,063,243 A	12/1977	Anderson et al.	5,525,995 A	6/1996	Benner
4,079,377 A	3/1978	zur Heiden et al.	5,530,447 A	6/1996	Henderson et al.
4,143,370 A	3/1979	Yamanaka et al.	5,572,428 A	11/1996	Ishida et al.
4,203,113 A	5/1980	Baghdady	5,583,495 A	12/1996	Ben Lu lu
4,209,791 A	6/1980	Gerst et al.	5,587,908 A	12/1996	Kajiwarra
4,217,582 A	8/1980	Endo et al.	5,613,039 A	3/1997	Wang et al.
4,246,585 A	1/1981	Mailloux	5,619,208 A	4/1997	Tamatsu et al.
4,308,536 A	12/1981	Sims, Jr. et al.	5,625,362 A	4/1997	Richardson
4,348,675 A	9/1982	Senzaki et al.	5,627,510 A	5/1997	Yuan
4,349,823 A	9/1982	Tagami et al.	5,633,642 A	5/1997	Hoss et al.
4,409,899 A	* 10/1983	Owen et al. 102/211	5,654,715 A	8/1997	Hayashikura et al.
4,414,550 A	11/1983	Tresselt	5,670,963 A	9/1997	Kubota et al.
4,507,662 A	3/1985	Rothenberg et al.	5,675,345 A	10/1997	Pozgay et al.
4,543,577 A	9/1985	Tachibana et al.	5,678,650 A	10/1997	Ishihara et al.
4,549,181 A	10/1985	Tachibana et al.	5,689,264 A	11/1997	Ishikawa et al.
4,622,636 A	11/1986	Tachibana	5,712,640 A	1/1998	Andou et al.
4,673,937 A	6/1987	Davis	5,715,044 A	* 2/1998	Hayes 356/5.09
4,703,429 A	10/1987	Sakata	5,717,399 A	2/1998	Urabe et al.
4,718,558 A	* 1/1988	Castaneda 209/546	5,731,778 A	3/1998	Nakatani et al.
4,901,083 A	2/1990	May et al.	5,734,344 A	3/1998	Yamada
4,962,383 A	10/1990	Tresselt	5,757,074 A	5/1998	Matloubian et al.
4,970,653 A	11/1990	Kenue	5,757,307 A	5/1998	Nakatani et al.
4,994,809 A	2/1991	Yung et al.	5,767,793 A	6/1998	Agravante et al.
5,008,678 A	4/1991	Herman	5,771,007 A	6/1998	Arai et al.
5,014,200 A	5/1991	Chundrlik et al.	5,777,563 A	7/1998	Minissale et al.
5,023,617 A	6/1991	Deering	5,805,103 A	9/1998	Doi et al.
5,045,856 A	9/1991	Paoletti	5,808,561 A	9/1998	Kinoshita et al.
5,115,245 A	5/1992	Wen et al.	5,808,728 A	9/1998	Uehara
5,134,411 A	7/1992	Adler	5,818,355 A	10/1998	Shirai et al.
5,138,321 A	* 8/1992	Hammer 342/36	5,839,534 A	11/1998	Chakraborty et al.
5,173,859 A	12/1992	Deering	5,905,472 A	5/1999	Wolfson et al.
5,189,426 A	2/1993	Asbury et al.	5,923,280 A	7/1999	Farmer
5,235,316 A	8/1993	Qualizza	5,926,126 A	7/1999	Engelman
5,249,027 A	9/1993	Mathur et al.	5,929,802 A	7/1999	Russell et al.
5,249,157 A	9/1993	Taylor	5,938,714 A	8/1999	Satonaka
5,252,981 A	* 10/1993	Grein et al. 342/200	5,940,011 A	8/1999	Agravante et al.
5,268,692 A	12/1993	Grosch et al.	5,949,366 A	9/1999	Herrmann
5,280,288 A	1/1994	Sherry et al.	5,959,570 A	9/1999	Russell
5,285,207 A	2/1994	Asbury et al.	5,977,904 A	11/1999	Mizuno et al.
5,302,956 A	4/1994	Asbury et al.	5,978,736 A	11/1999	Greendale
5,315,303 A	5/1994	Tsou et al.	5,999,092 A	12/1999	Smith et al.
5,325,096 A	6/1994	Pakett	5,999,119 A	12/1999	Carnes et al.
5,325,097 A	6/1994	Zhang et al.	5,999,874 A	12/1999	Winner et al.
5,339,075 A	8/1994	Abst et al.	6,011,507 A	1/2000	Curran et al.
5,341,144 A	8/1994	Stove	6,018,308 A	1/2000	Shirai
5,351,044 A	9/1994	Mathur et al.	6,026,347 A	2/2000	Schuster
RE34,773 E	11/1994	Dombrowski	6,026,353 A	2/2000	Winner
5,390,118 A	2/1995	Margolis et al.	6,028,548 A	2/2000	Farmer
5,394,292 A	2/1995	Hayashida	6,037,860 A	3/2000	Zander et al.
5,396,252 A	3/1995	Kelly	6,037,894 A	3/2000	Pfizenmaier et al.
5,400,864 A	3/1995	Winner et al.	6,040,796 A	3/2000	Matsugatani et al.
5,410,745 A	4/1995	Friesen et al.	6,043,772 A	3/2000	Voigtlaender et al.
5,414,643 A	* 5/1995	Blackman et al. 342/95	6,049,257 A	4/2000	Hauk
5,451,960 A	9/1995	Kastella et al.	6,052,080 A	* 4/2000	Magori 342/118
5,454,442 A	10/1995	Labuhn et al.	6,057,797 A	5/2000	Wagner
5,467,072 A	11/1995	Michael	6,069,581 A	5/2000	Bell et al.
5,467,283 A	11/1995	Butsuen et al.	6,070,682 A	6/2000	Isogai et al.
5,471,214 A	11/1995	Faibish et al.	6,075,492 A	6/2000	Schmidt et al.
5,479,173 A	12/1995	Yoshioka et al.	6,076,622 A	6/2000	Chakraborty et al.
5,481,268 A	1/1996	Higgins	6,085,151 A	7/2000	Farmer et al.
5,483,453 A	1/1996	Uemura et al.	6,087,975 A	7/2000	Sugimoto et al.
5,485,155 A	1/1996	Hibino	6,091,355 A	7/2000	Cadotte, Jr. et al.
5,485,159 A	1/1996	Zhang et al.	6,097,331 A	8/2000	Matsugatani et al.
5,486,832 A	1/1996	Hulderman	6,097,931 A	8/2000	Weiss et al.
5,493,302 A	2/1996	Woll et al.	6,104,336 A	8/2000	Curran et al.
			6,107,956 A	8/2000	Russell et al.

6,114,985	A	9/2000	Russell et al.	
6,127,965	A	10/2000	McDade et al.	
6,130,607	A	10/2000	McClanahan et al.	
6,147,637	A	11/2000	Morikawa et al.	
6,147,638	A	11/2000	Rohling et al.	
6,154,168	A	11/2000	Egawa et al.	
6,161,073	A	12/2000	Tange et al.	
6,163,252	A	12/2000	Nishiwaki	
6,184,819	B1	2/2001	Adomat et al.	
6,188,950	B1	2/2001	Tsutsumi et al.	
6,198,426	B1	3/2001	Tamatsu et al.	
6,198,434	B1	3/2001	Martek et al.	
6,215,438	B1	4/2001	Oswald et al.	
6,225,918	B1	5/2001	Kam	
6,232,910	B1	5/2001	Bell et al.	
6,233,516	B1	5/2001	Egawa	
6,252,560	B1	6/2001	Tanaka et al.	
6,255,984	B1	7/2001	Kreppold et al.	
6,256,573	B1	7/2001	Higashimata	
6,259,395	B1	7/2001	Adachi et al.	
6,265,990	B1	7/2001	Isogai et al.	
6,268,803	B1	7/2001	Gunderson et al.	
6,269,298	B1	7/2001	Seto	
6,278,400	B1	8/2001	Cassen et al.	
6,307,622	B1 *	10/2001	Lewis	356/4.01
6,317,073	B1	11/2001	Tamatsu et al.	
6,317,075	B1	11/2001	Heide et al.	
6,317,090	B1	11/2001	Nagy et al.	
6,320,547	B1	11/2001	Fathy et al.	
6,327,530	B1	12/2001	Nishimura et al.	
6,329,952	B1	12/2001	Grace	
6,330,507	B1	12/2001	Adachi et al.	
6,335,705	B1	1/2002	Grace et al.	
6,345,227	B1	2/2002	Egawa et al.	
6,351,702	B1	2/2002	Tange et al.	
6,366,235	B1	4/2002	Mayer et al.	
6,384,770	B1	5/2002	de Gouy et al.	

FOREIGN PATENT DOCUMENTS

DE	198 50 128	5/1999	
EP	0 398 712	5/1990	
EP	0 484 995	5/1992	
EP	0 642 190 A1	12/1993	
EP	0 784 213	1/1996	
EP	0 887 658 A1	12/1998	
EP	0 932 052	7/1999	
EP	0 978 729 A2	2/2000	
EP	0 982 173	3/2000	
EP	1 020 989	7/2000	
FR	2 709 834	9/1993	
FR	2754-604 A *	4/1998	G01S/13/88
GB	2267401 A *	12/1993	H03L/7/18

OTHER PUBLICATIONS

Bhattacharyya, Arum, et al. "Analysis of Stripline-Fed Slot-Coupled Patch Antennas with Vias for Parallel-Plate Mode Suppression", IEEE Transactions on Antennas and Propagation, vol. 46, No. 4, Apr. 1998, pp. 538-545.

Clouston E.N. et al. "A Triplate Stripline Slot Antenna Developed for Time-Domain Measurements on Phased Arrays", 1998, pp. 312-315.

Das, Nirod K. et al. "Multiport Scattering Analysis of General Multilayered Printed Antennas Fed by Multiple Feed Ports: Part II-Applications", IEEE, 1992, pp. 482-491.

Katehi, Pisti B. et al. "Design of a Low Sidelobe Level Stripline Fed Slot Array Covered by a Dielectric Layer", 1989, pp. 978-981.

Kimura, Yuichi et al. "Alternating Phase Single-Layer Slotted Waveguide Arrays at 25GHz Band", IEEE, 1999, pp. 142-145.

Muir, A., "Analysis of Stripline/Slot Transition", Electronics Letter, vol. 26 No. 15, pp. 1160-1161.

Sakaibara, Kunio et al. "A Single Slotted Waveguide Array for 22GHz Band Radio System Between Mobile Base Station", IEEE, 1994, pp. 356-359.

Sangster, Alan et al. "A Moment Method Analysis of a Transverse Slot Fed by a Boxed Stripline", (No Date) pp. 146-149.

Schaubert, Daniel H. et al. "Moment Method Analysis of Infinite Stripline-Fed Tapered Slot Antenna Arrays with a Ground Plane", IEEE Transactions on Antennas and Propagation, vol. 42, No. 8, Aug. 1994, pp. 1161.

Smith, Peter "Transverse Slot Radiator in the Ground-Plane of Enclosed Stripline", 10th International Conference on Antennas and Propagation 14.17, Apr. 1997, 5 pages.

Theron, Isak Petrus et al. "On Slotted Waveguide Antenna Design at Ka-Band", IEEE Trans. vol. 32, Oct. 1984, pp. 1425-1426.

International Search Report of PCT Application No. PCT/US01/25594 dated May 7, 2002.

G.S. Dow, et al. "Monolithic Receivers with Integrated Temperature Compensation Function", IEEE GaAs IC Symposium, 1991, pp. 267-269.

International Search Report of PCT Application No. PCT/US01/25682 dated May 14, 2002.

Ferryman, et al.; "Visual Surveillance for Moving Vehicles"; 1198; Proceedings 1998 IEEE Workshop on 1997; pp. 73-80.

Woodington, et al.; U.S. Patent Application Publication No. US 2002/0044082; Publication Date Apr. 18, 2002.

Russell, et al.; U.S. Patent Application Publication No. US 2002/0049539; Publication Date Apr. 25, 2002.

Delcheccolo, et al.; U.S. Patent Application Publication No. US 2002/0067287; Publication Date Jun. 6, 2002.

* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5






Figure 5A

**Figure 6****Figure 6A**







Figure 7



**Figure 9**

*Figure 10*




Figure 11A





Figure 11B






Figure 14A





Figure 14B







Figure 15

*Figure 16*

1

RADAR TRANSMITTER CIRCUITRY AND TECHNIQUES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 60/226,160, filed on Aug. 16, 2000 which application is hereby incorporated herein by reference in its entirety.

STATEMENTS REGARDING FEDERALLY SPONSORED RESEARCH

Not applicable.

FIELD OF THE INVENTION

This invention relates generally to radar transmitters and more particularly to a radar transmitter having a digital ramp signal generator and temperature compensation, non-linear VCO compensation, and reduced interference features.

BACKGROUND OF THE INVENTION

As is known in the art, there are many types of radar transmission techniques, one of which is Frequency Modulated Continuous Wave (FMCW) transmission, in which the frequency of the transmitted signal increases linearly from a first predetermined frequency to a second predetermined frequency. FMCW radar has the advantages of high sensitivity, relatively low transmitter power and good range resolution.

Various circuitry and techniques can be used to generate an FMCW transmit signal. One technique is to feed a signal voltage having a ramp characteristic (referred to herein as a

Various circuitry and techniques can be used to generate an FMCW transmit signal. One technique is to feed a signal voltage having a ramp characteristic (referred to herein as a "ramp signal" or ramp voltage") to a voltage controlled oscillator (VCO) to generate the frequency modulated transmit signal commonly referred to as a chirp signal. Typically, the ramp signal is generated by an analog circuit which may include timing pulse generation circuits, integrators and amplifiers. Components of such an analog circuit are fixed at the design stage and thus, such a circuit does not afford much, if any versatility.

Ideally, the frequency of the VCO output signal varies linearly with respect to the ramp voltage. When there is non-linearity in the ramp signal and/or in the operation of the VCO, the frequency of the RF return signal can be spread across an RF frequency range or "smeared", thereby degrading target detection, resolution and range accuracy performance of the radar system.

Another technique for generating an FMCW transmit signal is to use direct-digital synthesis (DDS) in which the transmit signal itself is digitally synthesized. Typical DDS systems include a phase accumulator and a digital-to-analog (D/A) converter. However, the transmit signal rate is limited by the Nyquist theory to less than one-half of the maximum clock rate of the D/A converter. Other disadvantages of DDS systems include complexity and cost plus an increase in supporting hardware requirements because of limitations in operating frequency and tuning range of currently available DDS synthesizers.

As is also known, some relatively complex radar systems include multiple transmit and receive circuits (TRCs) each of which operate independently of one another. When such

2

transmit and receive circuits are placed in proximity to one another and operate at the same or overlapping frequencies, the multiple TRCs can interfere with one another, preventing the accurate detection of targets. Other problems can also arise by simultaneous operation of multiple TRCs.

Radar systems provide several design challenges. As one example, when radar systems operating at the same or overlapping frequencies are used in proximity to one another, the two systems can interfere with one another, preventing the accurate detection of targets. For example, circuit performance variations attributable to temperature changes can result in interference between multiple TRCs. It would, therefore, be desirable to provide a radar transmitter circuit which permits adjustment of transmit signal characteristics in a relatively simple manner. It would also be desirable to provide a radar transmitter which compensates for variations in transit signal characteristics caused by variations in temperature in the environment in which the radar transmitter is disposed. It would be still further desirable to provide an FMCW radar system which compensates for non-linear VCO operation. It would be still further desirable to provide a technique which allows simultaneous operation of multiple TRCs in overlapping frequency ranges. It would be still further desirable to provide a system and technique which allows simultaneous operation of multiple FMCW TRCs.

SUMMARY OF THE INVENTION

In accordance with the present invention, a radar transmitter includes a DSP, a D/A converter having an input terminal coupled to the output terminal of the DSP and an output terminal at which an analog ramp signal is provided, and a VCO having an input terminal responsive to the analog ramp signal and an output terminal at which a frequency modulated signal is provided.

With this arrangement, simple and relatively inexpensive circuitry is used to generate an analog ramp signal for controlling the VCO. Several advantageous features can be readily implemented by appropriate adjustment of the DSP output words, which results in concomitant adjustment of the chirp signal. These features include VCO and drive circuit temperature compensation, compensation for non-linear VCO operation, and interference reduction techniques. An analog smoothing circuit may be coupled between the output terminal of the D/A converter and the input terminal of the VCO in order to smooth the stepped D/A converter output.

In one embodiment, the output of the VCO is up-converted to provide the transmit signal and in another embodiment, the VCO operates over the transmit signal frequency range, thereby eliminating the need for the up-converter.

Also described is a VCO which consists of a dielectric resonator oscillator (DRO) to generate the chirp signal. The VCO includes an amplifier, a dielectric resonator (DR) for controlling the center frequency of the VCO and a phase shifter for providing a frequency tuning capability to the VCO. The phase shifter is a three terminal device which has an input terminal coupled to the amplifier, and an output terminal connected to the dielectric resonator. The dielectric resonator is connected back to the input of the amplifier to provide positive feedback and thus create an oscillator. In addition, the phase shifter has a control terminal to control the frequency of the VCO by providing a phase shift proportional to the control voltage. The frequency modulating signal or "ramp signal" is connected to the control terminal which is responsive to the ramp signal.

3

A temperature compensation feature is described including the steps of generating, from a predetermined sequence of digital words, a transmit signal having a frequency associated with a respective one of the sequence of words, and storing each of the digital words in association with an expected transmit signal frequency. The actual frequency of the transmit signal is detected and the digital word used to generate the detected frequency is compared to the digital word stored in association with the actual transmit signal frequency. The result of the comparison is an error value which is used to adjust each of the digital words. In one embodiment, the actual transmit signal frequency is detected with a circuit which is responsive to a narrow band of frequencies and the digital words are adjusted by introducing an offset equal to the error value. In one embodiment the circuit is provided as a DRO which is responsive to signals having the transmit signal frequency.

According to a method for compensating for non-linear VCO operation, the VCO is characterized during manufacture by feeding a predetermined sequence of digital words to the D/A converter and detecting the resulting transmit signal frequency for each word. This process yields a so-called VCO curve which relates VCO output frequency to VCO input voltage. A curve having a shape which is complementary to the shape of the VCO curve is determined and the DSP output words are adjusted to provide the complementary waveform to the VCO. By controlling the VCO with a waveform complementary with respect to its characteristic curve, frequency smear caused by such non-linear operation is reduced.

A method for reducing interference between radar systems includes the steps of generating a ramp signal for controlling a VCO and randomly varying at least one parameter of the ramp signal. The ramp signal includes a plurality of cycles, each having an offset portion, a ramp portion, and a CW portion. The parameter of the ramp signal may be randomly varied in one or more of the cycles. Illustrative ramp signal parameters which may be randomly varied include, the starting ramp signal voltage, the duration of the offset portion and the voltage range of the ramp portion.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing features of this invention, as well as the invention itself, may be more fully understood from the following description of the drawings in which:

FIG. 1 is a block diagram of a radar system;

FIG. 2 is a block diagram of an automotive near object detection (NOD) system including a plurality of radar systems of the type shown in FIG. 1;

FIG. 3 is a detailed block diagram of a side object detection (SOD) system suitable for use in the NOD system of FIG. 2;

FIG. 4 is a plot of VCO control signal voltage vs. time which illustrates VCO control signal waveforms provided by the ramp generator of FIG. 3 for implementing a temperature compensation feature;

FIG. 5 is a plot of VCO control signal voltage vs. time which further illustrates VCO control signal waveforms provided by the ramp generator of FIG. 3 for implementing an interference reduction feature;

FIG. 5A is plot of VCO control signal voltage vs. time which illustrates yet another VCO control signal waveform provided by the ramp generator of FIG. 3 for implementing an alternative interference reduction feature;

4

FIG. 6 is a plot of VCO control signal voltage vs. time which illustrates a non-linear relationship between a frequency of the VCO output signal of FIG. 3 and a voltage of the VCO control signal of FIG. 3;

FIG. 6A is a plot of VCO control signal voltage vs. time which illustrates a relationship between the VCO control signal and the output of the DSP of FIG. 3 used to compensate for the non-linear VCO characteristic of FIG. 6;

FIG. 7 is detailed a block diagram of an alternate SOD system embodiment;

FIG. 8 is a detailed block diagram of a further alternate SOD system embodiment;

FIG. 9 is a block diagram of an illustrative architecture for the DSP of FIGS. 3, 7, and 8;

FIG. 10 is a diagrammatic view of an exemplary detection zone provided by a SOD system disposed on a vehicle;

FIGS. 11A and 11B are diagrammatic views of alternative detection zones which can be provided by the SOD system;

FIG. 13 is a timing chart of a minor cycle detection process included in the process of FIG. 12;

FIG. 14A is a plot of signal return fast Fourier transform (FFT) magnitude vs. FFT frequency bin which illustrates output generated at an intermediate stage of the detection process of FIG. 12;

FIG. 14B is a plot of FFT derivative magnitude vs. FFT frequency bin which illustrates first and second derivatives of the FFT output of FIG. 14A computed at another intermediate stage of the detection process of FIG. 12;

FIG. 15 is a plot of signal return FFT magnitude vs. FFT frequency bin which illustrates an exemplary FFT output resulting from detection of a geometrically extended target and an illustrative FFT output resulting from detection of a non-extended target at the same range; and

FIG. 16 is a plot of signal return FFT magnitude vs. FFT frequency bin which illustrates exemplary FFT outputs associated with detections of two proximate targets.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIG. 1, a radar system 10 includes an antenna portion 14, a microwave portion 20 having both a transmitter 22 and a receiver 24, and an electronics portion 28 containing a digital signal processor (DSP) 30, a power supply 32, control circuits 34 and a digital interface unit (DIU) 36. The transmitter 22 includes a digital ramp signal generator for generating a control signal for a voltage controlled oscillator (VCO), as will be described.

The radar system 10 utilizes radar technology to detect one or more objects, or targets in the field of view of the system 10 and may be used in various applications. In the illustrative embodiment, the radar system 10 is a module of an automotive radar system (FIG. 2) and, in particular, is a side object detection (SOD) module or system adapted for mounting on an automobile or other vehicle 40 for the purpose of detecting objects, including but not limited to other vehicles, trees, signs, pedestrians, and other objects which can be located proximate a path on which the vehicle is located. As will be apparent to those of ordinary skill in the art, the radar system 10 is also suitable for use in many different types of applications including but not limited to marine applications in which radar system 10 can be disposed on a boat, ship or other sea vessel.

The transmitter 22 operates as a Frequency Modulated Continuous Wave (FMCW) radar, in which the frequency of

the transmitted signal linearly increases from a first predetermined frequency to a second predetermined frequency. FMCW radar has the advantages of high sensitivity, relatively low transmitter power and good range resolution. However, it will be appreciated that other types of transmitters may be used.

Control signals are provided by the vehicle **40** to the radar system **10** via a control signal bus **42**. The DSP **30** processes these control signals and radar return signals received by the radar system **10** in order to detect objects within the field of view of the radar system, as will be described in conjunction with FIGS. **10–16**. The radar system **10** provides to the vehicle one or more output signals characterizing an object within its field of view via an output signal bus **46**. These output signals may include a target detection signal when a target exceeds the system preset thresholds. The output signals may be coupled to a control unit of the vehicle **40** for various uses such as blind spot and near object detection.

The antenna assembly **14** includes a receive antenna **16** for receiving RF signals and a transmit antenna **18** for transmitting RF signals. The radar system **10** may be characterized as a bistatic radar system since it includes separate transmit and receive antennas positioned proximate one another. The antennas **16, 18** provide multiple beams at steering angles that are controlled in parallel as to point a transmit and a receive beam in the same direction. Various circuitry for selecting the angle of the respective antennas **16, 18** is suitable, including multi-position transmit and receive antenna switches.

Referring also to FIG. **2**, an illustrative application for the radar system **10** of FIG. **1** is shown in the form of an automotive near object detection (NOD) system **100**. The NOD system **100** is disposed on a vehicle **120** which may be provided for example, as an automotive vehicle such as car, motorcycle, or truck, or a marine vehicle such as a boat or an underwater vehicle or as an agricultural vehicle such as a harvester. In this particular embodiment, the NOD system **100** includes a forward-looking sensor (FLS) system **122**, an electro optic sensor (EOS) system **124**, a plurality of side-looking sensor (SLS) systems **128** or equivalently side object detection (SOD) systems **128** and a plurality of rear-looking sensor (RLS) systems **130**. In the illustrative embodiment, the radar system **10** of FIG. **1** which is shown in greater detail in FIG. **3** is a SOD system **128**.

Each of the FLS, EOS, SLS, and RLS systems is coupled to a sensor processor **134**. In this particular embodiment, the sensor processor **134** is shown as a central processor to which each of the FLS, EOS, SLS, and RLS systems is coupled via a bus or other means. It should be appreciated that in an alternate embodiment, one or more of the FLS, EOS, SLS, and RLS systems may include its own processors, such as the DSP **30** of FIG. **1**, to perform the processing described below. In this case, the NOD system **100** would be provided as a distributed processor system.

Regardless of whether the NOD system **100** includes a single or multiple processors, the information collected by each of the sensor systems **122, 124, 128, 130** is shared and the processor **134** (or processors in the case of a distributed system) implements a decision or rule tree. The NOD system **100** may be used for a number of functions including but not limited to blind spot detection, lane change detection, pre-arming of vehicle air bags and to perform a lane stay function. For example, the sensor processor **134** may be coupled to the airbag system of the vehicle **132**. In response to signals from one or more of the FLS, EOS, SLS, and RLS systems, the sensor processor may determine that it is

appropriate to “pre-arm” the airbag of the vehicle. Other examples are also possible.

The EOS system **124** includes an optical or IR sensor or any other sensor which provides relatively high resolution in the azimuth plane of the sensor. The pair of RLS systems **130** can utilize a triangulation scheme to detect objects in the rear portion of the vehicle. The FLS system **122** is described in U.S. Pat. No. 5,929,802 entitled Automotive Forward Looking Sensor Architecture, issued Jul. 27, 1999, assigned to the assignee of the present invention, and incorporated herein by reference. It should be appreciated that each of the SLS and RLS sensors may be provided having the same antenna system.

Each of the sensor systems is disposed on the vehicle **120** such that a plurality of coverage zones exist around the vehicle. Thus, the vehicle is enclosed in a cocoon-like web or wrap of sensor zones. With the particular configuration shown in FIG. **2**, four coverage zones **68a–68d** are used. Each of the coverage zones **68a–68d** utilizes one or more RF detection systems. The RF detection system utilizes an antenna system which provides multiple beams in each of the coverage zones **68a–68d**. In this manner, the particular direction from which another object approaches the vehicle or vice-versa can be found. One particular antenna which can be used is described in U.S. Patent Application entitled “Slot Antenna for an Array Antenna,” filed on Aug. 16, 2001, and assigned application Ser. No. 09/931,633, now U.S. Pat. No. 6,492,949, and U.S. Patent Application entitled “Switched Beam Antenna Architecture,” filed on Aug. 16, 2001, and assigned application Ser. No. 09/932,574, each of which are assigned to the assignee of the present invention and incorporated herein by reference.

It should be appreciated that the SLS, RLS, and the FLS systems may be removably deployed on the vehicle. That is, in some embodiments the SLS, RLS, and FLS sensors may be disposed external to the body of the vehicle (i.e. on an exposed surface of the vehicle body), while in other systems the SLS, RLS, and FLS systems may be embedded into bumpers or other portions of vehicle (e.g. doors, panels, quarter panels, vehicle front ends, and vehicle rear ends). It is also possible to provide a system which is both mounted inside the vehicle (e.g., in the bumper or other location) and which is also removable. The system for mounting can be of a type described in U.S. Patent Application entitled “System and Technique for Mounting a Radar System on a Vehicle,” filed on Aug. 16, 2001, and assigned application Ser. No. 09/930,868, now U.S. Pat. No. 6,489,927, and U.S. Patent Application entitled “Portable Object Detection System,” filed on Aug. 16, 2001, and assigned application Ser. No. 09/931,276, each of which are assigned to the assignee of the present invention and incorporated herein by reference.

Referring also to FIG. **3**, the radar system **10** of FIG. **1** for use as a SOD system **128** (FIG. **2**) is shown in greater detail. In general overview of the operation of the transmitter **22**, the FMCW radar transmits a signal **50** having a frequency which changes in a predetermined manner over time. The transmit signal **50** is generally provided by feeding a VCO control or ramp signal **86** to a voltage controlled oscillator (VCO) **92**. In response to the ramp signal **86**, the VCO **92** generates a chirp signal **88**.

A measure of transmit time of the RF signal can be determined by comparing the frequency of a received signal **54** with the frequency of a sample **58** of the transmit signal. The range determination is thus provided by measuring the beat frequency between the frequencies of the sample **58** of the transmit signal and the return signal **54**, with the beat

frequency being equal to the slope of the ramp signal **86** multiplied by the time delay of the return signal. The measured frequency further contains the Doppler frequency due to the relative velocity between the target and the radar system. In order to permit the two contributions to the measured frequency shift to be separated and identified, the time-varying frequency of the transmit signal **50** is achieved by providing a control signal **86** to the VCO **92** in the form of a linear ramp signal followed by either a CW signal or a ramp with the opposite slope.

According to one aspect of the invention, the VCO control signal **86** is generated with digital circuitry and techniques. In a preferred embodiment, the ramp signal **86** is generated by the DSP **30** and a digital-to-analog converter (DAC) **70**. Use of the DSP **30** and DAC **70** to generate the ramp signal **86** is possible in the SOD system **10** since, it has been determined in accordance with the present invention, that by proper selection of the detection zone characteristics including but not limited to detection zone size, shape and resolution, precise linearity of the chirp signal **88** is not necessary. This is a result of the correlation that exists between the nonlinearities in the transmit and receive waveforms at close ranges. With this arrangement, the frequency of the transmit signal **50** is accurately and easily controllable which facilitates implementation of several advantageous and further inventive features. As one example, one or more characteristics of successive ramps in the ramp signal **86** are randomly varied in order to reduce interference between similar, proximate radar systems, as illustrated by FIGS. **5** and **5A**. As another example, temperature compensation is implemented by appropriately adjusting the ramp signal **86**, as will be described in conjunction with FIG. **4**. Yet another example is compensation for non-linearity in the VCO operation, as illustrated by FIGS. **6** and **6A**. Further, changes to the SOD system **10** which would otherwise require hardware changes or adjustments can be made easily, by simply downloading software to the DSP **30**. For example, the frequency band of operation of the SOD system **10** can be readily varied, as may be desirable when the SOD is used in different countries with different operating frequency requirements.

The electronics portion **28** of the SOD system **10** in FIG. **3** includes the DSP **30**, the power supply **32**, and a connector **154** through which signal buses **42**, **46** (FIG. **1**) are coupled between the SOD system **10** and the vehicle **40** (FIG. **1**). The digital interface **36** is provided in the form of a controller area network (CAN) transceiver (XCVR) **150** in FIG. **3** which is coupled to the DSP **30** via a CAN microcontroller **80**. The CAN controller **80** has a system clock coupled thereto to provide frequency stability. In one embodiment, the system clock is provided as a crystal controlled oscillator. An analog-to-digital (A/D) converter **68** receives the output of a video amplifier **64** and converts the signal to digital form for coupling to the DSP **30** for detection processing. In one embodiment, the A/D converter **68** is provided as a twelve bit A/D converter. Those of ordinary skill in the art will appreciate, however, that any A/D converter having sufficient resolution for the particular application may be used. A digital signal bus **158** is coupled to antenna switch driver circuits **103** which in turn control microwave switches **99**, **101** in order to provide control signals to drive the microwave switches which in turn control antenna steering. Also provided in the electronics portion **28** of the SOD system **10** is a memory **156** in which software instructions, or code and data are stored. In the illustrative embodiment of FIGS. **3** and **7**, the memory is provided as a flash memory **156**.

The DSP **30** provides the digital ramp output signals, or words to the DAC **70** which converts the ramp words into respective analog signals. An analog smoothing circuit **76** is coupled to the output of the DAC **70** in order to smooth the stepped DAC output to provide the ramp control signal **86** to the VCO **92**. The DSP **30** includes a volatile memory device **304** (FIG. **9**) in which is stored a look-up table containing a set of DSP output signals, or words in association with the frequency of the transmit signal **50** generated by the respective DSP output signal. This data is transferred to data RAM **304** from Flash memory **156** during initial boot up of the system. This data may be corrected from time to time as a result of temperature effects as described herein. In the illustrative embodiment, the VCO **92** is an SMV2488 device provided by Z Communications, Inc. of San Diego, Calif. and the VCO output signal **88** has a frequency in the range of 2.31 to 2.54 GHz. The SOD embodiments of FIGS. **7** and **8** illustrate alternative VCO arrangements for generating the transmit signal.

An up-converter circuit **90** up-converts the VCO output signal **88** to a higher frequency as is desired for transmission in the illustrative automotive NOD system **100**. In particular, the signal **88** is up-converted to a frequency of between 24.01 to 24.24 GHz. The up-converter **90** includes a 50 ohm load **136**, an amplifier **138**, a dielectric resonator (DR) **140**, and a mixer **142**. The amplifier **138**, the dielectric resonator (DR) and the transmission lines **144**, **146** form an oscillator circuit in which the DR **140** couples energy at its fundamental frequency and within its passband from transmission line **144** to transmission line **146** in order to generate an oscillator signal for coupling to mixer **142**. In the illustrative embodiment, the oscillator signal on transmission line **144** has a nominal frequency of 21.7 GHz. The output of the mixer **142** is filtered by a bandpass filter **96** and is amplified by an amplifier **94**. A portion of the output signal from amplifier **94**, is coupled via coupler **95** to provide the transmit signal **50** for further amplification by amplifier **78** and transmission by transmitter antenna **18**. Another portion of the output signal from amplifier **94** corresponds to a local oscillator (LO) signal **58** fed to an LO input port of a mixer **60** in the receive signal path.

The switch circuits **99**, **101** are coupled to the transmit and receive antenna **16**, **18** through a Butler matrix. The antennas **18**, **16** and switch circuits **99**, **101**, and Butler matrix can be of the type described in U.S. patent application entitled "Switched Beam Antenna Architecture," filed on Aug. 16, 2001, and assigned application Ser. No. 09/932,574, assigned to the assignee of the present invention, and incorporated herein by reference. Suffice it here to say that the switch circuits **99**, **101** and Butler matrix operate to provide the antenna having a switched antenna beam with antenna beam characteristics which enhance the ability of the SOD system **10** to detect targets.

The received signal **54** is processed by an RF low noise amplifier (LNA) **52**, a bandpass filter **56**, and another LNA **62**, as shown. The output signal of the RF amplifier **62** is down-converted by a mixer **60**, which receives a local oscillator signal **58**, coupled from the transmitter, as shown. Illustrative frequencies for the RF signals from the amplifier **62** and the local oscillator signal **58** are on the order of 24 GHz. Although the illustrated receiver **24** is a direct conversion, homodyne receiver, other receiver topologies may be used in the SOD radar system **10**.

A video amplifier **64** amplifies and filters the down-converted signals, which, in the illustrative embodiment have a frequency between 1 KHz and 40 KHz. The video amplifier **64** may incorporate features, including tempera-

ture compensation, filtering of leakage signals, and sensitivity control based on frequency, as described in a co-pending U.S. Patent Application entitled "Video Amplifier for a Radar Receiver," and assigned application Ser. No. 09/931,593, filed on Aug. 16, 2001, assigned to the assignee of the present invention, and incorporated herein by reference.

The A/D converter **68** converts the analog output of the video amplifier **64** into digital signal samples for further processing. In particular, the digital signal samples are processed by a fast Fourier transform (FFT) within the DSP **30** in order to determine the content of the return signal within various frequency ranges (i.e., frequency bins). The FFT outputs serve as data for the rest of the signal processor **30** in which one or more algorithms are implemented to detect objects within the field of view, as will be described in conjunction with FIGS. **10–16**.

The radar system **10** includes a temperature compensation feature with which temperature induced variations in the frequency of the transmit signal are compensated by adjusting the ramp signal **86** accordingly. For this purpose, the transmitter **22** includes a dielectric resonator (DR) **72** coupled to a microwave signal detector **74**. The output of the microwave detector **74** is coupled to an analog-to-digital converter which is included in the CAN controller **80** (FIG. **9**) for processing by the DSP **30**.

In operation, the DR **72** couples energy to the detector **74** only when the transmit signal **50** has a frequency within a range around the fundamental resonant frequency of the DR (i.e., within the passband of the DR). In the illustrative embodiment, the DR **72** has a fundamental frequency within the transmit frequency range and a passband which is relatively narrow compared with the transmit frequency range. In this illustrative embodiment the DR is provided having a passband on the order of 10 MHz centered in the middle of the band of operation of the system in order to provide sufficient frequency detection resolution as will become apparent. The detector **74** detects output power from the DR **72** and provides an electrical signal indicative of a predetermined level of output power from the DR.

Detection of output power from the DR **72** indicates transmission of the DR's fundamental predetermined frequency. Further, transmission of the predetermined frequency corresponds to a predetermined DSP output word which, in turn, corresponds to "an expected" transmission frequency as specified in the look-up table.

In operation, when the DSP **30** receives an output signal via the CAN controller **80** from the frequency detector **72** and **74** indicating transmission of the predetermined frequency, the expected frequency associated with the DSP output is compared to the predetermined frequency by a software comparator **82** within the DSP. The measured time of detection and the commanded frequency is correlated in order to make an accurate frequency measurement. Any discrepancy between the expected frequency and the measured frequency indicates that an adjustment to the DSP output is necessary. Stated differently, a difference between the two frequencies indicates that the look-up table data needs to be corrected, since the expected frequency is not being transmitted in response to the corresponding DSP output.

By way of a simple example, consider the case where the look-up table indicates that a DSP output of 11110000 corresponds to a transmit frequency of 24.20 GHz and the DR **72** has a fundamental frequency of 24.20 GHz. Thus, detection of output power from the DR **72** indicates that

24.20 GHz is being transmitted. However, assume further that the detection occurs when the DSP output is given by 11110001. This scenario indicates that the DSP output words need to be adjusted and, specifically, need to be shifted down by one, in order to transmit the desired, expected frequency.

Various techniques may be used to compensate for the error between the transmitted frequency and the expected frequency. As one example, an offset equal to the amount of the error (i.e., the difference between the transmitted frequency and the DSP output word that is stored in the look-up table in association with the DRO's fundamental frequency) may be added or subtracted, depending on the direction of the offset, each time a new DSP output word is provided and until a new error is detected. Stated differently, each subsequent DSP output is simply shifted by the amount of the detected error. Since temperature generally does not change quickly, this error detection and correction may be performed relatively infrequently, such as once every 50 ms or 100 ms. It will be appreciated by those of ordinary skill in the art that other structures and techniques may be used for detecting the frequency of the transmit signal **50** to feedback to the DSP **30** for the purpose of adjusting the DSP output words in order to thereby adjust the frequency of the transmit signal.

Referring also to FIG. **4**, a single cycle of an illustrative ramp signal **220** as provided at the output of the DAC **70** (FIG. **3**) is shown. In operation according to the above-described temperature compensation feature, detection of an error between the predetermined transmit signal frequency (i.e., the DRO fundamental frequency) and the expected transmit frequency associated with the DSP output word generating the predetermined frequency results in modification of the DSP output words as described above. The effect of shifting the DSP output words up or down is a shift of the ramp signal up or down, accordingly. For example, following correction of the DSP output, the nominal ramp signal **220** is shifted down in voltage to provide temperature compensated ramp signal **224**, as shown.

An interference reduction feature of the SOD **10** according to a further aspect of the invention is implemented with a random, or pseudo-random number generator **84**, (FIG. **3**), as may be provided by software within the DSP **30**. The random number generator **84** is used to randomly vary at least one aspect, and parameter of the ramp signal **86**. Examples of such parameters are the offset interval of each chirp cycle as illustrated in FIG. **5** and the voltage (and thus frequency) range generated in each chirp cycle as illustrated in FIG. **5A**.

Referring to FIG. **5**, a plurality of cycles of an illustrative ramp signal **230**, corresponding to ramp signal **86** (FIG. **3**), for coupling to the VCO **92** are shown. Each ramp cycle starts at a time T1, T2, T3, . . . and has a ramp portion R1, R2, R3, . . . commencing at an offset time t1, t2, t3, . . . following the respective cycle start time T1, T2, T3, . . . , as shown. According to the invention, the duration of the offset interval of each cycle (i.e., intervals t1—T1, t2—T2, t3—T3, . . .) is randomly selected by the DSP **30**. This is achieved by introducing a random delay corresponding to the offset interval into a recursive process by which the ramp signal is generated. In the illustrative embodiment, each ramp cycle is on the order of 1.1 msec and the offset interval of each cycle is randomly selected from one of sixteen possible intervals between 0 and 0.1 msec. As a result, at any given time, the frequency of the resulting transmit signal **50** will be different than the frequency of transmit signals from like radar systems, although the transmission frequency range of the radars will be the same.

With this arrangement, two identical SOD radar systems **10** operating proximate to each other over the same frequency range will not interfere with one another since, at any given time, the frequency of the transmit signals provided by the systems will vary randomly with respect to each other. This feature advantageously permits two or more identical SODs to be used on a vehicle, as is desirable to reduce the parts count of the NOD system and simplify replacement of one or more modules within the NOD system. A less desirable approach to reduce interference between proximate SODs would be to manually manipulate or program each SOD to ensure different transmit signals.

An alternative technique for reducing interference illustrated by the ramp signal **234** of FIG. **5A** entails randomly varying the frequency range of the transmit signal **50** during each ramp cycle while still staying within the specified frequency range for the SOD system **10**. This is achieved by introducing a random offset voltage to the ramp signal during each cycle while keeping the peak-to-peak ramp signal voltage constant (i.e., moving the ramp up or down while keeping peak-to-peak ramp voltage constant). For example, during the cycle commencing at time T1, the ramp R1 increases from 1 volt to 2.5 volts, thus corresponding to a first frequency range. During the next cycle, the ramp R2 increases from 1.25 volts to 2.75 volts, corresponding to a second different frequency range. In the illustrative embodiment, the frequency range of the transmit signal **50** is randomly selected from twenty-four different frequency ranges.

Various techniques in either the analog or digital portions of the circuitry, are possible for introducing an offset voltage to the ramp signal in order to randomly vary the voltage range. As one example, the offset voltage is introduced by the smoothing circuit **76** (FIG. **3**).

It will be appreciated that although the ramps R1, R2, R3, . . . of the ramp signal **234** of FIG. **5A** have random offset intervals (i.e., offset intervals computed as t1-T1, t2-T2, t3-T3, . . .) as described above in conjunction with FIG. **5**, the transmit frequency range can be randomly varied without also varying the offset interval. Stated differently, the technique of randomly varying the offset interval of each ramp cycle and randomly varying the frequency range of each ramp cycle can be implemented separately or in combination. It will also be appreciated that although the offset interval of each ramp cycle is randomly varied in FIGS. **5** and **5A** and the voltage range is randomly varied in each ramp cycle in FIG. **5A**, the selected parameter(s) may be randomly varied in one or more of the ramp cycles and need not be randomly varied in every ramp cycle.

Another feature of the SOD system **10** is compensation for non-linear operation of the VCO **92** (FIG. **3**). FIG. **6** shows a curve **238** representing the relationship between the frequency of the VCO output signal **88** (FIG. **3**) versus the VCO control signal voltage **86**, (FIG. **3**). The illustrative curve **238** has a typical frequency range on the order of 180 MHz and a typical voltage range on the order of 1.25 volts. Although in an ideal VCO the relationship is linear as illustrated by curve **236**, typically there is some non-linearity, as shown in the curve **238**. This non-linearity is compensated, or nulled by adjusting the DSP output words accordingly. More particularly, the DSP output words are adjusted in order to provide ramp voltage (i.e., DAC output voltage) that is substantially complementary with respect to the actual curve **238**. Such a complementary curve **240** is shown in FIG. **6A**.

The operation of VCO **92** is characterized (i.e., a curve like FIG. **6** is generated) by feeding a sequence of DSP

output words to the DAC **70** and measuring the transmit frequency with a test receiver (not shown). Such VCO characterization can be done at manufacture or prior to or after insertion of the VCO in the SOD system **10** or prior to or after placing a SOD system on a vehicle. Having characterized the VCO, the complementary curve of FIG. **6A** is simply determined by taking the complement of the curve with respect to the ideal characteristic (labeled **236** in FIG. **6**). A sequence of DSP output words necessary to generate the VCO control signal **240** of FIG. **6A** can then be determined. By way of a simple example, where prior to characterization of the VCO, a DSP output sequence of 00000000, 00000001, 00000010, 00000011, . . . might be used to generate a linear ramp, in order to compensate for the VCO non-linearity, the sequence might be adjusted to 00000000, 00000000, 00000001, 00000010, . . . The process of determining the necessary sequence of DSP output words to generate the control signal **240** can be performed manually or can be automated and preferably is repeatable from system to system. Typically, the correction to the DSP output words is made in software and stored in memory.

With knowledge of the way in which VCO output frequency varies with input voltage, the VCO control voltage **86** can be adjusted in order to force the output frequency of the VCO to be swept in a desired manner. Although the relationship between VCO output and VCO input is non-linear, the relationship between VCO output and DSP output is substantially linear.

Also, it will be appreciated that, given knowledge of the FIG. **6** characteristic curve **238** of the VCO **92**, the system may be optimized to operate over a particular input voltage range to the VCO. Specifically, the most linear region of operation of the VCO (as labeled **242** in FIG. **6**) can be selected as the DAC output voltage range simply by selecting a range of DSP output words necessary to generate the desired DAC output voltage range.

Referring also to FIG. **7**, an alternate SOD system **250** differs from the SOD system **10** of FIG. **3** in the VCO portion of the transmitter **22** which processes the ramp signal **86** to generate the transmit signal **50**. Portions of the SOD system **250** which are identical to the SOD system **10** of FIG. **3** have like reference numbers. Like the VCO **92** of FIG. **3**, the VCO **254** is responsive to the ramp signal **86** and provides an output signal to a bandpass filter **96** which, in turn, provides an output signal having the desired transmit frequency in the range of 24.01 to 24.24 GHz.

The SOD system **250** includes a VCO **254** in the form of a voltage controlled DRO **254**. The VCO **254** further includes a 50 ohm load **258** coupled to an amplifier **270** which, in turn, is coupled to a diode phase shifter **262**. The phase shifter **262**, signal coupling paths **268**, **272**, amplifier **270** and dielectric resonator **266**, form an oscillation loop.

In operation, the DR **266** transfers signals within its passband from transmission line **268** to transmission line **272**. The signal is amplified by amplifier **270** until the amplifier saturates. The passband of the DR **266** is selected to cover the desired frequency range of transmission which, in the illustrative embodiment is a range of 24.01–24.24 GHz. The final frequency of the signal on transmission line **268** is controlled by adjusting the phase shift introduced by the phase shifter **262**. In this way, the diode phase shifter **262** provides phase reinforcement on the oscillation loop so that the oscillation loop seeks out the frequency determined by the feedback loop which includes the phase shifter and the DR. In general, a feedback loop will oscillate at a frequency whereby a feedback signal, for example a signal on signal

path 272, achieves zero degrees phase (or any multiple of three hundred sixty degree phase) as it travels around the loop back to its starting point, with a loop gain, or gain around the loop, greater than one. Thus, by altering phase shifter 262, the frequency at which the feedback signal will achieve zero degrees will be similarly altered, and, so long as the loop gain remains greater than one, the loop will oscillate at the altered frequency. With the arrangement of FIG. 7, up converting of the signal provided by the VCO 254 is not necessary since the VCO operates within the desired transmit frequency range to generate the transmit signal 50.

Referring also to FIG. 8, another alternate SOD system 280 differs from the SOD system 10 of FIG. 3 in the VCO portion of the transmitter and the antenna arrangement. Portions of the SOD system 280 which are identical to the SOD system 10 of FIG. 3 have like reference numbers.

The SOD 280 includes a VCO 284 receiving ramp signal 86 from the analog smoothing circuit 76. The VCO 284 operates in the transmit frequency range of between 24.01 to 24.24 GHz and provides an output signal to bandpass filter 96, as shown. Since the VCO 284 operates in the transmit frequency range, the need for up-converting of the VCO output signal (FIG. 3) is eliminated.

It will be appreciated by those of ordinary skill in the art that features, components, elements and other portions of the SOD system 10 of FIG. 3, the SOD system 250 of FIG. 7, and the SOD system 280 of FIG. 8 may be mixed and matched. As one example, it will be appreciated that the antenna arrangement of FIG. 3 may be used with the VCO 254 of FIG. 7 or the VCO 284 of FIG. 8.

Referring to FIG. 9, a block diagram of the SOD electronics 28 (FIGS. 1, 3, 7, and 8) is shown in greater detail to include the DSP 30, the CAN microprocessor 80, the CAN transceiver 150, power supply 32, and the memory 156. The memory 156 provides non-volatile storage of data and program information. Also shown is the video amplifier 64 providing an output signal to the A/D converter 68 which is coupled to port 312 of the DSP 30. In one embodiment, the memory 156 is provided as a 128 kx8 flash memory and the port 312 is provided as a serial port of the DSP 30. The D/A converter 70 receives the digitized ramp signal in the form of a sequence of digital words from the DSP through the port 312, as shown, and is further coupled to the smoothing circuit 76.

The DSP 30 includes RAM 304 in which data is stored, such as the look-up table of VCO control signal voltage 86 versus transmit frequency, and a program RAM 306 in which process instructions are stored, such as software code used to implement the detection algorithm described below. Program and data information stored in memory 156 are transferred to program RAM 306 and data RAM 304, respectively, upon application of power. The illustrative DSP 30 is an ADSP2186M microprocessor manufactured by Analog Devices, Inc. and includes an oscillator 308 operating at 33 MHz which is doubled internally to 66 MHz which is the clock rate of the DSP.

The DSP 30 further includes digital input/output (I/O) port 314 at which the antenna control signals are provided on bus 158. The DSP 30 communicates with the CAN microprocessor 80 via the digital I/O 314 and a serial port 316 which is further coupled to a serial EEPROM 340. The serial EEPROM 340 is used to hold data such as calibration constants and diagnostic test results and trouble codes.

In the illustrative embodiment, the random number generator 84 (FIG. 3) used to implement temperature compensation and the comparator 82 (FIG. 3) used to compensate

for non-linear VCO operation are implemented by the DSP as a series of software instructions stored in the program RAM 306 and executed by the microprocessor. It will be appreciated by those of ordinary skill in the art however that these functional blocks as well as others may be implemented in hardware, firmware, software or a combination of hardware, firmware or software.

The illustrative CAN microprocessor 80 is a TMS470R1F316, a member of the TMS470 family from Texas Instruments and includes RAM 320, flash memory 322, an A/D converter 328, serial ports 330, digital I/O ports 332, a CAN interface 334, and an oscillator 324, here operating at 4.915 MHz. The CAN microprocessor 80 is coupled to the DSP 30 through serial port 330 and digital I/O 332 and is coupled to the CAN transceiver 150 through digital I/O 332 and the interface 334, as shown.

The CAN A/D converter 328 has a plurality of multiplexed inputs adapted for receiving various monitoring signals. As examples, the output of frequency detector 74 (FIG. 3) is coupled to the CAN A/D converter 328. Another optional input to the CAN A/D converter 328 is provided by a temperature sensor 98 (FIG. 3). The temperature sensor provides an output signal indicative of the temperature of the receiver 22 and may be used separately or in conjunction with features of the oscillator 90 (FIG. 3) to compensate for temperature induced frequency variations in the RF VCO 90. Optional detectors for detecting power supply faults may also be coupled to the A/D converter 328. The CAN A/D converter 328 converts the received signals to digital form for further processing, generally by the DSP 30.

Referring now to FIG. 10, an exemplary detection zone 500, shown in top view, is an azimuthal region in which a SOD system 504 (also referred to as a SOD sensor 504) which may be of the type described above in FIGS. 1-9 is specified to detect objects. Only objects within a specific detection zone 500 in proximity to an automobile 508 on which the SOD system 504 is mounted are included in a detection, and objects outside of the detection zone 500 are excluded.

The detection zone shape, of which the indicated zone 500 is only one example, depends upon the application in which the radar system is used. For example, an automobile SOD system is designed to detect objects in the adjacent lane of traffic including objects within the blind spot of the vehicle. Detection of objects in lanes of traffic beyond the adjacent traffic lane and outside of the blind would be undesirable. As another example, an automobile FLS system 122 (FIG. 2) used for purposes including but not limited to collision avoidance is designed to detect objects generally in front of the vehicle. Thus, each application requires a different shape of detection zone 500.

The sideward detection zone 500 includes a maximum detection zone boundary 512, a minimum detection zone boundary 520, and a nominal detection zone boundary 516 between the maximum and minimum detection zone boundaries. In a preferred embodiment, the SOD system 504 does not detect objects outside of the maximum detection zone boundary 512 and always detects objects within the minimum detection zone boundary 520. A probability region 524 exists between the maximum detection zone boundary 512 and the minimum detection zone boundary 520. The SOD system may or may not detect an object in the region 524. Probability region 524 exists due to imperfections and tolerances of practical circuit components which make up the SOD system 524. Ideally, the region 524 would have a width of 0 meters. Thus, the probability of detection in the

probability zone is between zero and one hundred percent. An exemplary probability region **524** has a maximum width of 0.6 meters. The detection zone **500** further includes a minimum range **528** which is the distance from the SOD system to the closest object that will be detected. In the illustrative SOD system **504**, the nominal detection zone boundary has an average width on the order of ten meters and an average length on the order of four meters. The minimum range **528** is on the order of 0.25 meters.

The size and shape specifications of the detection zone **500** and probability region **524** dictate many design parameters associated with the SOD system architecture. For example, in order to provide a SOD system performance that can transition from no detections to certain detections within a given probability region **524**, the SOD system **504** can determine the range to an object with a measurement accuracy which is relatively high compared with the width of the probability region **524**. For example, in the case where the probability region has a width of 0.6 meters, the measurement accuracy of the SOD system should be on the order of 0.06 meters.

As another example of a system parameter determined by the detection zone **500**, the specification of a wide detection zone boundary **512–520** in azimuth relative to the SOD system **504**, requires a wide radar coverage in azimuth. Furthermore, a detection zone boundary **512–520** with a complex contour requires that multiple beams be used in the detection algorithm, each with a different detection range. The beams related to the detection zone will be shown in greater detail in association with FIGS. **11A** and **11B**.

For another example, the specified minimum range **528** of the detection zone **500**, can preferably be achieved with a system architecture that uses a chirp signal, like the FMCW chirp signal described above in conjunction with FIG. **3**. In particular, the Federal Communications Commission (FCC) has specified that low power radar, at power of six decibels (6 dB) effective isotropic radiated power (6 dB_{eirp}) such as that used by the SOD systems discussed above, can have a frequency bandwidth no greater than 200 MHz. As will become apparent from the following description, the short range requirement **528** and the FCC bandwidth requirement together preclude the use of conventional pulsed radar.

The FCC 200 MHz bandwidth requirement is met by the SOD system being an FMCW system since a slowly varying FMCW signal can be generated with a narrow bandwidth of 200 MHz. For example, the SOD system **504** generates a transmit signal having a frequency which increases from approximately 24.000 GHz to 24.200 GHz in approximately 1 ms and has a bandwidth of 200 MHz. In contrast, conventional pulsed radar in a short range application cannot meet the 200 MHz FCC bandwidth requirement. A pulsed radar is also limited in its ability to detect objects at short ranges. This is because, in order to operate at the short ranges required of the SOD system, a pulsed radar system would require a very short radar pulse. Not only is such a short pulse technically difficult to achieve, but also, as the pulse width becomes narrower, the bandwidth of the transmitted signal becomes wider. A pulsed radar with pulse widths sufficiently short to enable operation at a minimum range **528** on the order of 0.25 meters fundamentally requires a frequency bandwidth in excess of 200 MHz. Thus, the characteristics of the detection zone **500** impact the system design in many ways. The detection algorithm processing that operates upon the received echoes, or signals, is also selected to operate with detection zones having particular characteristics. The detection algorithm is described below in conjunction with FIG. **12**.

While a detection zone **500** to the side of the automobile is indicated, it should be recognized that other detection zones of specified sizes and shapes can be equivalently specified around the automobile **508**, such as those shown in FIG. **2**. For example, frontal zones and rearward zones can be specified without departing from this invention. Typically, an automobile manufacturer specifies one or more detection zones, including zone size, shape and position relative to the automobile. The SOD system **504** can be configured so as to provide the appropriate side detection zone **500** regardless of where it is mounted on the side of the automobile. Other probability zones **524** and other minimum detection ranges **528** are also possible with this invention.

Also, while the SOD system **504** is shown at a position to the rear of the outside rear view mirror **532**, the detection zone **500** and the resulting SLS sensor **504** location can be located anywhere along the perimeter of the automobile **508**.

Referring now to FIGS. **11A** and **11B**, two different examples of side detection zones **536**, **548** are shown. In FIG. **11A**, the maximum detection zone boundary **536** is provided having a trapezoidal shape. An exemplary SOD system provides eight azimuthal beams **540a–540h** each with a different maximum detection range, as indicated in shading, and as determined by the detection algorithm that operates upon the beam echoes. The algorithmic control of the maximum detection range of each of the eight beams defines the shape of an actual maximum detection zone boundary **538** versus the specified maximum detection zone boundary **536**.

The exemplary SOD system of FIGS. **11A**, **11B** has eight beams, each with a beam width of approximately fifteen degrees and with a total azimuth scan of in excess of one hundred fifty degrees. It will be recognized by one of ordinary skill in the art that other numbers of beams (e.g. fewer than eight or more than eight) and scan angles are possible without departing from the present invention. The particular number of antenna beams to use in a particular application is selected in accordance with a variety of factors including but not limited to the desired detection zone **500** and the width of the probability region **524**.

FIG. **11B** shows a detection zone **548** having a substantially rectangular shape of the maximum boundary. Again, an exemplary system provides eight azimuthal beams **552a–552h** each with a different maximum detection range as indicated in shading, the ranges **552a–552h** being different from beams **540a–540h** so as to form a different actual maximum detection zone **550**, indicated again by shading.

Referring now to FIG. **12**, a flow diagram illustrates a process **556** performed by the SOD processor, such as DSP **30** of FIG. **3**. The process contains major cycles and minor cycles. A minor cycle includes all detection operations that are performed utilizing a particular beam of the SOD antenna system. A major cycle includes operations that are performed utilizing the full group of beams provided by the SOD antenna system. In step **560** a major cycle is initiated and in step **564** a minor cycle is initiated. Initiating the major cycle **560** involves resetting the beam to the first beam. Initiating the minor cycle **564** involves resetting the beam to the next adjacent beam.

A chirp signal is initiated in step **570**. During a chirp, a number n of digital samples of the received signal are processed by the A/D converter **68** (FIG. **3**), previously described, at a rate of f_s KHz, in a time period t . In the illustrative embodiment of FIG. **3**, $n=256$, $f_s=256$ KHz, and $t=1$ msec.

While it will be recognized by those of ordinary skill in the art that other numbers of samples at other rates are

possible with this invention, selection of n and f_s determine the eventual frequency and range resolution and thus must be selected to meet all system detection requirements.

In step 574, range thresholds are established at each beam pointing angle in order to define the detection zone. Thus, at a given beam pointing angle, range detections that are either too far or too near to the SOD system to fall within the detection zone are excluded by way of pre-established range thresholds. Echo magnitude window thresholds are also established in step 574. Only object detections that produce echoes above a lower threshold and below an upper threshold, i.e. within the magnitude window, are considered valid. An echo that is below the lower threshold could be caused by system noise rather than an object or target. An echo that is above the upper threshold could be caused by an interfering radar source, such as a radar transmission from another vehicle. Thus, both range and amplitude thresholds are established at step 574. It should be recognized that by altering the range thresholds, other specified detection zone shapes and sizes can be obtained.

In step 578, the data samples are truncated, whereby a small number of samples at the beginning of the data set and at the end of the data set are removed. The removed samples may contain unwanted artifacts due to hardware limitations such as amplifier settling which can occur after switching from one antenna beam to another, etc. In the illustrative embodiment, approximately two hundred fifty six data samples remain after truncation.

Also in step 578, the remaining input samples are amplitude weighted, or windowed. Recall from the discussion of FIG. 3 that the data samples output of the A/D converter 68 are processed by an FFT within the DSP 30. Amplitude weighting of the data samples that are input to an FFT can provide beneficial effects with regard to the minimum width of a spectral peak in the resulting frequency domain, and the sidelobe magnitude associated with each FFT frequency bin. Essentially, with a spectrally pure frequency input to an FFT, input weighting can make the resulting FFT output appear in a smaller number of frequency bins than would occur with no input weighting. Since the frequency difference between the received echo and the transmitted signal relates directly to range, then the accuracy with which the received echo frequency is detected relates directly to range accuracy. Resolving a frequency to a single FFT bin or better is desirable.

In the exemplary SOD system a Chebyshev weighting function is applied to the input samples. This weighting function provides a good compromise between spreading of a narrowband signal into multiple FFT bins and a good sidelobe suppression. It will also be recognized by those of ordinary skill in the art that various amplitude weighting functions could be applied to the input data samples, and that the weighting may be applied with a variety of techniques including both hardware and software multiplication's.

It will be recognized by those of ordinary skill in the art that an FFT output is a frequency domain spectral representation of digital input samples to the FFT, where the digital input samples are samples of a time domain analog signal. It will also be recognized that the parameters, including number of samples, n , and sample rate, f_s , determine the frequency resolution, or bin width, f_r , of the FFT output by the relation $f_r = f_s/n$. Since the range of a target is associated with the frequency of the received signal, the frequency resolution correlates to a range resolution. As has been described above, a range resolution better than 0.6 meters is required in order to achieve the specified detection zone 500 (FIG. 10).

The exemplary SOD system provides two hundred fifty six data samples, n , taken at a 256 KHz sample rate, f_s . Thus, the resulting FFT frequency resolution, f_r , is 1 KHz. The corresponding range resolution can be derived as follows. As mentioned earlier, in the illustrative SOD system 504 (FIG. 10), the frequency chirp is swept in frequency through 200 MHz in approximately 1 msec. One KHz thus represents a time period of approximately 5 nsec. In 5 nsec, radar energy can propagate a distance of approximately 1.5 meters. Since the energy propagates both to the target and back, the range to the target represented by a 1 KHz signal from the A/D converter 68 (FIG. 3) is approximately 0.75 meters. A 2 KHz signal represents a target at 1.5 meters, etc. Thus, an FFT bin width of 1 KHz corresponds to a target range resolution of 0.75 meters. This measurement accuracy does not meet the desired range resolution of less than 0.6 meters. Additional processing is thus necessary.

In the exemplary embodiment at step 578, a zero padding technique, recognized by those of ordinary skill in the art, is applied to the input samples to the FFT in order to reduce the resulting FFT bin width. It will also be recognized by those of ordinary skill in the art that other techniques may be used to reduce the FFT bin width. For example, various interpolation techniques can be applied.

The windowed and zero padded input samples are operated on with an FFT operation in step 582. Time domain data samples are collected from a chirp echo and a complex FFT is performed on the data samples. Subsequent processing can improve the measurement accuracy still further as described starting at process step 606.

In step 586, a magnitude calculation is performed on the complex FFT data, whereby the FFT real and imaginary parts of the complex FFT data are used to calculate an FFT magnitude, hereafter called FFT output data, or an FFT output signal.

As the data samples associated with a particular beam steering angle in azimuth can vary from one such data set to another, averaging of either time domain data samples or FFT output data associated with a particular beam steer angle can reduce the rate of false detections, or improve the false alarm rate. For example, where system noise or other artifacts cause variation in the detected frequency and amplitude, averaging can reduce the impact of such artifacts and thus improve system performance.

In step 590, it is determined whether four chirps have been processed, to be used in the aforementioned averaging. If four chirps have not been processed, then processing returns to step 570 where another chirp is initiated. If four chirps have been processed, then processing proceeds to step 602 in which the FFT output data from the four chirps are averaged. Whereas the exemplary SOD system uses four averaged chirps for each beam within the minor cycle timing, it will be recognized by those of ordinary skill in the art that other numbers of chirps can also be averaged.

In step 602, the resulting FFT output data is also range normalized. Whereas a radar return echo signal generally loses amplitude proportional to range, and whereas increasing FFT bins are proportional to increasing range, the FFT output data without range normalization would indicate an amplitude reduction across the FFT bins. Range normalization is provided to adjust the FFT bin amplitudes by scale factors to minimize the amplitude range dependency of the FFT output data.

In step 606, the minimum and maximum range thresholds, frequencies R_{min} and $T_{BeamRange}$ respectively, and minimum magnitude threshold, T_{object} are applied to the averaged

FFT output data. The thresholds will be described more fully in conjunction with FIGS. 14A and 14B. Let it suffice to say here that the range thresholds limit detections to those objects that are not too close and not too far from the SOD system, specific to the particular beam pointing angle, so as to detect objects as required within a specified detection zone, for example detection zone 500 (FIG. 10).

Additional processing is required in order to achieve range accuracy much better than the 0.6 meters as required by the exemplary detection region 500. To this end, in step 606, first and second derivatives of the FFT output data are computed by the DSP, as discussed further in conjunction with FIGS. 13A and 13B. As will be explained below, range accuracy is significantly improved by use of the first and second derivatives of the FFT output data. In step 610, the negative going zero crossing of the first derivative and second derivative are computed as will be described.

The first and second derivatives of the FFT output data provide an indication of whether a detection has or has not occurred. In the case where a detection has occurred, the first and second derivatives also provide a range to the detected object. Only those objects with a range within the range thresholds, and with sufficient magnitude are considered as valid targets by the SOD system in step 612, thereby setting a minor cycle detection flag. Step 612 concludes a minor cycle of processing in which detections associated with a single beam steering angle are made.

In step 616, the minor cycle detection flag is stored in a detection table, or target detection report matrix. The table is shown in block 616 and includes columns corresponding to antenna beams and rows corresponding to major cycles. Each entry in the table is a minor cycle detection flag. A "T" (true) indicates a minor cycle detection in the associated beam detected during the minor cycle and F (false) indicates no minor cycle detection. Thus, the entry labeled 620, indicates detection in the first radar beam during a minor cycle. A complete row is obtained during each major cycle and each column of the detection table 616 comprises successive minor cycle detection flags for a given beam steering angle.

After a minor cycle detection flag is stored in the table, it is determined in step 636 whether a major cycle has ended, i.e., whether a minor cycle detection flag has been provided for the last beam. If the major cycle has not ended, then processing returns to step 564 on the next beam and steps 564-616 are repeated for that beam. Alternatively, if the major cycle has ended, thus completing a row of the detection table, then the table is analyzed in step 644.

In step 644, minor cycle detection flags stored in the detection table are logically combined to provide an alert condition message with a reduced false alarm rate. An alert condition message 644 indicates either the presence or absence of a target within the detection zone. For example, groups of four minor cycle detection flags such as those groups labeled 628 and 632 in the table may be logically combined to reduce the false alarm rate. The logically combined groups 628, 632 can span both minor and major cycles, i.e. can span more than one column or more than one row. In the illustrative embodiment, each group (e.g. group 628, 632) is a 2x2 matrix of detection flags. It will be recognized that group 632 is analyzed only at the completion of the major cycle represented by the third row of the detection table, whereas group 628 is analyzed at the completion of the major cycle represented by the second row of the table.

Each combined group 628, 632 is processed to determine if at least two detection flags within the group are true. In

particular, two or more true minor cycle detection flags in a 2x2 group of minor cycle detection flags yields an alert condition message that indicates a target detection. Thus, processing of group 628 yields an alert condition message resulting from consecutive detections in beam 1 during consecutive minor cycles. Processing of group 632 likewise yields an alert condition message caused by detections in beams four and five during one major cycle. Although a particular logical combination of minor cycle detection flags has been described, it will be recognized by those of ordinary skill in the art that other logical combinations of minor cycle detection flags from one or multiple beams and from one or more major cycles are possible with this invention. Upon completion of major cycle processing in step 644, a new major cycle is initiated in step 560.

An alert condition message that indicates the presence of a target in the detection zone can cause a system action appropriate for the application. For example, a visual indication or audible alarm may be provided to alert the driver that an object is within the detection zone of a SOD system.

FIG. 13 shows minor cycle timing in relation to the chirp signal and processing steps. A minor cycle 648 is completed on each beam steering angle in a predetermined period of time (e.g. 5.5 ms). Within that time period, four radar chirps 652a-652d are transmitted, the chirp echo returns are differenced from the transmission and the difference is sampled during intervals 656a-656d, the differences are FFT analyzed during intervals 660a-660d, the FFT magnitudes are calculated during intervals 664a-664d, and the four FFT output data are averaged at interval 668. First and second derivatives are computed and analyzed during interval 672, and a minor cycle detection flag is generated at interval 676. The minor cycle 648 is then repeated for the next beam. Note that the processing associated with intervals 668, 672, and 676 is performed coincidentally with sampling of the first chirp 680 in the next minor cycle.

Randomly variable chirp offset intervals 680a-680d as described above in conjunction with FIGS. 5 and 5A provide a reduction in false detections caused by receptions from other radars including other SOD systems.

The overall minor and major cycle timing is selected in order to detect objects within a specified time period so that system actions can be taken in an appropriate amount of time. For the illustrative SOD system 504 (FIG. 10), an alert condition message is generated at the completion of each major cycle, i.e. at the completion of seven minor cycles. Thus, an alert condition message is generated in approximately once every 50 msec. The CAN microprocessor 80 (FIG. 9) has an asynchronous update rate for the overall vehicle of approximately 300 msec. Thus, several major cycles and associated alert condition messages are generated during each CAN cycle. While specific timing selections have been described for the illustrative embodiment, it should be recognized that other timing selections are possible. For example, averaging of other than four FFTs, and use of other than seven beams are possible. One of ordinary skill in the art, after reading this description would clearly understand how to implement any necessary modification to the timing structure of FIG. 13.

Referring now to FIGS. 14A and 14B an illustrative FFT output data curve 682 as may be generated in step 602 of FIG. 12 contains a magnitude detection peak 686 at a detection frequency 690 that corresponds to a particular detection range and one or more FFT bins. It should be recognized that the detection peak 686 from a single target may be broader than a single FFT bin. As mentioned above,

the broadening of the detected echo in the frequency domain is related to aspects of the particular FFT, in particular the weighting function that may be applied the input data samples to the FFT. Broadening can also be related to physical aspects of the echoing target, such as the dimension of the target along the axis of the particular radar beam. An extended target has an extended range and thus may appear as a broadened frequency corresponding to the range.

In general, the peak **686** of the FFT output data curve **682** for a single target is a frequency **690** that corresponds to the range to the target. However, in association with FIGS. **15** and **16**, it will be seen that the peak can give a false impression of the range to the target in some cases. For now, let us assume that the peak of the FFT output data curve indicates the range to the target.

As has been discussed in association with the detection algorithm **556** of FIG. **12**, the FFT frequency bins may not be sufficiently narrow to provide the required accuracy required for a particular detection zone. Where the detected signal from a single target is spread between several FFT bins, additional processing must be done on the FFT output data in order to provide sufficient range resolution.

Consideration of the first derivative **694** of the FFT output data curve **682** reveals that the peak **686** of the FFT output data curve **682** is coincident with the negative going zero crossing **698**. Thus, the negative going zero crossing **698** of the first derivative **694**, provides the frequency **690** of the FFT peak **686**, and thus, the corresponding range to the target. Range detection in this manner provides greater accuracy than simply determining the range by determining the fractional frequency bin of the FFT output data curve **682** in which the peak occurs since the peak may occur in multiple FFT bins.

It should be recognized that although FIGS. **14A** and **14B** show the FFT output data curve **682** and FFT first derivative **694** as smooth continuous waveforms, the FFT output data, represented by FFT output data curve **682**, and first derivative **694** are comprised of discontinuous digital samples. As a result, finding the zero crossing of the first derivative **694** requires additional processing. If the spacing of the points of the first derivative **694** are sufficiently close, then adjacent first derivative data points lie approximately on a straight line. With this approximation, the zero crossing **698** can be found by a conventional similar triangles technique. In the illustrative embodiment, spacing between data points on the order of 500 Hz has been found to be sufficient. However, it will be recognized by those of ordinary skill in the art that other data point frequency spacings can be used with this invention. It should be noted that the zero crossing **698** of the first derivative so determined can be at any frequency and need not be at the center of an FFT bin, thus the resolution in frequency and associated range resolution is greatly improved as compared to the conventional technique of determining the frequency bin in which the FFT peak **686** occurs.

For complex echo returns, for example from multiple targets or from a target that is extended along the beam axis, the negative going zero crossing **702** of the second derivative **706** is determined and provides greater range discrimination than the use of the first derivative in the above manner. The negative zero crossing **702** of the second derivative **706** of the FFT output data curve **682** corresponds to a negative inflection point **710** of the FFT output data curve **682**. A negative inflection point **710**, is a point where the slope of the FFT output data curve **682** changes from curving upward to curving downward.

It will be recognized that the rising portion of an FFT output data feature, for example **714**, has a discrete negative inflection point **710**, whereas the peak **686** of the feature can be extended along the frequency axis. Although the broadening of an FFT output data feature is related to both to mathematical characteristics of the FFT, such as the input sample weighting, and to dimensional characteristics of the target, the shape of the rising portion of the FFT output data feature **714** is, to a first order, related only to the FFT mathematical characteristics. The negative inflection point **710** on the rising portion of the FFT output data feature **714** can be used to predict the frequency of the FFT peak **686** as may be desirable where the peak **686** is not otherwise distinct. In essence, for a relatively broad range of target dimensional characteristics, the distance **716** between the negative inflection point **710** and the FFT peak **686**, is known and constant, determined only by the mathematics of the FFT. Thus, by finding the first negative inflection point **710** of the rising portion of an FFT output data feature **714**, and by using the negative inflection point **710** to predict the position of the peak **686**, the range to the target can be found even for more complex FFT output data curve spectral shapes.

As noted in conjunction with step **606** in FIG. **12**, thresholds R_{min} **717** and $T_{BeamRange}$ **718**, specific to the particular beam pointing angle, are applied to the calculated frequency of an object range as calculated by either first derivative or second derivative test. In particular, those peaks within the thresholds will be considered valid. Similarly, only those peaks that are above a magnitude threshold T_{Object} **719** are considered valid.

Referring now to FIG. **15** an example curve **728** corresponding to FFT output data as may be caused by a target that is extended along the beam axis so as to result in a nearly flat top FFT output data curve for which a peak would be indeterminate or result in multiple peak detections **724**, **732** is shown. Also shown is curve **736** which corresponds to FFT output data resulting from a non-extended target. Comparison of the FFT output data curve **728** with the FFT output data curve **736** reveals coincident negative inflection points **720**, **740**. Thus, computation of the second derivative of the FFT output data curve **728** and use of the resulting negative zero crossing to determine peak **724** by adding the known distance, i.e. frequency, between negative inflection point **720** and peak **724** as described above, results in an accurate range determination.

Referring now to FIG. **16**, another curve **744** corresponding to an example of FFT output data as may be caused by simultaneous receipt of echoes from two targets, of which one is weaker than the other is shown. Note that a strong echo can cause the curve portion **748** of the composite FFT output data curve **744** associated with the weaker echo to have no peak at all, while the curve portion **752** from the stronger target has a distinct peak **756**. Still, the negative inflection points **760**, **764** found by computing the second derivative of the composite FFT output data curve **744** can be used to predict the range of both targets. Detection of the two negative zero crossings of the second derivative of FFT output data curve **744** and use of the known distance, like distance **716** of FIG. **14A**, results in detection of peak frequency points **768** and **756**. A first negative inflection point **760** is used to find the peak **768** corresponding to the first target range, though a peak **768** does not in fact exist. A second negative inflection point **764** is used to similarly find the peak **756** corresponding to the second target range. Since the frequency peaks correspond to target range, the range to both the strong and weak target can be discrimi-

nated. Thus, use of the second derivative of the FFT output data provides range discrimination for targets represented by more complex FFT output data curves.

Having described the preferred embodiments of the invention, it will now become apparent to one of ordinary skill in the art that other embodiments incorporating their concepts may be used.

It will be appreciated by those of ordinary skill in the art that the particular boundaries between portions of the radar system **10** can be varied from that described herein above. As examples, the receiver **24** may include parts of the electronic control circuits **34** or parts of the receiver, such as an A/D converter (FIG. **2**), may be provided in the electronics portion **28** of the system. Depending upon the selected implementation of the various components, one or more portions of the radar system may be integrated onto one or more hybrid circuits, modules, or subassemblies.

It is felt therefore that these embodiments should not be limited to disclosed embodiments but rather should be limited only by the spirit and scope of the appended claims. All publications and references cited herein are expressly incorporated herein by reference in their entirety.

What is claimed is:

1. A radar transmitter comprising:

a DSP having an output terminal at which a digital output word is provided;

a D/A converter having an input terminal coupled to the output terminal of the DSP and an output terminal at which an analog ramp signal is provided; and

a VCO having an input terminal responsive to the analog ramp signal and an output terminal at which a frequency modulated signal is provided.

2. The radar transmitter of claim **1** further comprising a smoothing circuit having an input terminal coupled to the output terminal of the D/A converter and an output terminal coupled to the input terminal of the VCO.

3. The radar transmitter of claim **1** further comprising an up-converter having an input terminal coupled to the output terminal of the VCO and an output terminal at which a transmit signal is provided.

4. The radar transmitter of claim **3** wherein said up-converter comprises a DRO.

5. The radar transmitter of claim **1** wherein said VCO comprises:

an amplifier having an input terminal to which a terminator is coupled and an output terminal;

a phase shifter having an input terminal coupled to the output terminal of the amplifier, an output terminal at which a frequency modulated signal is provided, and a control terminal; and

a DR positioned to couple energy from the output terminal of the phase shifter to the input terminal of the amplifier.

6. The radar transmitter of claim **1** further comprising:

a memory in which is stored a look-up table containing a plurality of DSP output words in association with an expected transmit frequency;

a frequency detection circuit for detecting the frequency of a transmit signal generated by the frequency modulated signal; and

a comparator for comparing a DSP output word from which the detected frequency is generated with a DSP output word stored in the look-up table in association with the detected frequency to provide an error value.

7. The radar transmitter of claim **6** wherein said frequency detection circuit comprises a DR having a fundamental frequency substantially equal to the detected frequency.

8. The radar transmitter of claim **6** further comprising an offset generator for adjusting the output word of the DSP in response to the error value.

9. The radar transmitter of claim **1** further comprising a random number generator for varying at least one parameter of the analog ramp signal.

10. The radar transmitter of claim **9** wherein the at least one parameter is selected from an offset interval and a voltage range.

11. The radar transmitter of claim **1** wherein said transmitter comprises a side object detection module of a near object detection system.

12. A method for compensating for temperature induced variations in a radar system comprising the steps of:

generating, from a predetermined sequence of digital words, a transmit signal having a frequency associated with a respective word of the predetermined sequence of digital words;

storing each word of the predetermined sequence of digital words in association with an expected transmit signal frequency;

detecting the actual frequency of the transmit signal;

comparing the digital word from which the actual frequency is generated to a digital word stored in association with the actual frequency to provide an error value; and

adjusting each word of the predetermined sequence of digital words in response to the error value.

13. The method of claim **12** wherein said adjusting step includes offsetting each word of the predetermined sequence of digital words by the error value.

14. The method of claim **12** wherein said detecting step includes detecting the actual frequency of the transmit signal with a DR having a fundamental frequency substantially equal to the actual frequency.

15. A method for reducing interference between radar systems comprising the steps of:

generating a ramp signal for controlling to a VCO; and randomly varying at least one parameter of said ramp signal.

16. The method of claim **15** wherein said ramp signal comprises a plurality of cycles, each comprising an offset portion, a ramp portion, and a CW portion and wherein said at least one parameter is randomly varied in at least one of said plurality of cycles.

17. The method of claim **16** wherein the at least one parameter is selected from the duration of said offset portion and a voltage range of said ramp portion.

18. A method for compensating for non-linear operation of a VCO in a radar transmitter, comprising the steps of:

measuring the output frequency of the VCO in response to a plurality of input voltage levels to the VCO to provide a characteristic curve of the VCO;

determining a complementary waveform with respect to the characteristic curve; and

providing a sequence of output words of a DSP operable to generate a transmit signal for generating the complementary waveform.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,707,419 B2
DATED : March 16, 2004
INVENTOR(S) : Woodington et al.

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 1,

Lines 32-34, delete "Various circuitry and techniques can be used to generate and FMCW transmit signal. One technique is to feed a signal voltage having a ramp characteristic (referred to herein as a".

Column 3,

Line 64, delete "FIG. 5A is plot" and replace with -- FIG. 5A is a plot --.

Column 4,

Line 9, delete "FIG. 7 is detailed" and replace with -- FIG. 7 is a detailed --.

Column 5,

Line 34, delete "Such as car," and replace with -- Such as a car, --.

Column 6,

Line 39, delete "of vehicle" and replace with -- of the vehicle --.

Column 9,

Line 34, delete "embodiment the" and replace with -- embodiment, the --.

Column 16,

Line 53, delete "major cycles" and replace with -- major cycle --.

Line 55, delete "step 560 a" and replace with -- step 560, a --.

Line 56, delete "step 564 a" and replace with -- step 564, a --.

Column 17,

Line 46, delete "SOD system a" and replace with -- SOD system, a --.

Line 54, delete "multiplication's." and replace with -- multiplications. --

Column 18,

Line 16, delete "less that 0.6" and replace with -- less than 0.6 --.

Line 18, delete "an zero" and replace with -- a zero --.

Column 20,

Line 61, delete "14A and 14B an" and replace with -- 14A and 14B, an --.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,707,419 B2
DATED : March 16, 2004
INVENTOR(S) : Woodington et al.

Page 2 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 21,


Line 2, delete ", in particular the" and replace with -- , in particular, --.
Line 3, delete "applied the input" and replace with -- applied to the input --.
Line 56, delete ", for example" and replace with -- , for example, --.
Line 61, delete "that the use" and replace with -- than the use --.

Column 22,

Line 5, delete "to both to" and replace with -- both to --.
Line 27, delete "either first" and replace with -- either the first --.
Line 32, delete "FIG. 15 an" and replace with -- FIG. 15, an --.

Signed and Sealed this

Third Day of May, 2005

A handwritten signature in black ink on a light gray dotted background. The signature is written in a cursive style and appears to read "Jon W. Dudas".

JON W. DUDAS

Director of the United States Patent and Trademark Office