



US010032319B2

(12) **United States Patent**
Ricci

(10) **Patent No.:** **US 10,032,319 B2**
(45) **Date of Patent:** **Jul. 24, 2018**

(54) **BIFURCATED COMMUNICATIONS TO A
THIRD PARTY THROUGH A VEHICLE**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **NIO USA, Inc.**, San Jose, CA (US)

4,361,202 A 11/1982 Minovitch
4,476,954 A 10/1984 Johnson et al.
(Continued)

(72) Inventor: **Christopher P. Ricci**, Saratoga, CA
(US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **NIO USA, Inc.**, San Jose, CA (US)

CN 1417755 5/2003
CN 1847817 10/2006
(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

OTHER PUBLICATIONS

(21) Appl. No.: **15/396,620**

Liu et al., A Survey of Payment Card Industry Data Security
Standard, 2010, IEEE, p. 287-303 (Year: 2010).
(Continued)

(22) Filed: **Dec. 31, 2016**

Primary Examiner — McDieunel Marc
(74) *Attorney, Agent, or Firm* — Sheridan Ross P.C.

(65) **Prior Publication Data**

US 2018/0012427 A1 Jan. 11, 2018

Related U.S. Application Data

(60) Provisional application No. 62/359,563, filed on Jul.
7, 2016, provisional application No. 62/378,348, filed
on Aug. 23, 2016.

(51) **Int. Cl.**
G07C 5/00 (2006.01)
G07B 15/06 (2011.01)
(Continued)


(52) **U.S. Cl.**
CPC **G07C 5/008** (2013.01); **B60W 40/08**
(2013.01); **B60W 50/08** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC .. G07C 2/008; G07B 15/063; G01C 21/3617;
G08G 1/017; G08G 1/096838;
(Continued)

(57) **ABSTRACT**

A vehicle is provided that determines a need for communi-
cation with a third party vendor, retrieves a user rule from
the memory (the user rule defines to which third party
vendor the vehicle can send a first communication to address
the need and defines a geographic location of the third party
vendor relative to a current location of the vehicle, a
monetary amount the vehicle can pay to a third party vendor
for a product or service to address the need, and a time limit
for the third party vendor to provide the product or service
to address the need), based on the user rule, selects a third
party vendor from among multiple possible third party
vendors, and when determined by the user rule, automati-
cally sends the first communication to the selected third
party vendor to address the need. The first communication is
associated with an order for the product or service, and the
processor provides an authorization to the selected third
party vendor to complete the order. The vehicle uses differ-
ent antennas positioned at different physical locations on an
exterior of the vehicle to provide the first communication
and authorization to the selected third party vendor.

21 Claims, 59 Drawing Sheets



- (51) **Int. Cl.**
G01C 21/36 (2006.01)
B60W 50/08 (2012.01)
B60W 40/08 (2012.01)
G08G 1/017 (2006.01)
G08G 1/0968 (2006.01)
G01S 13/93 (2006.01)
- (52) **U.S. Cl.**
CPC **G01C 21/3617** (2013.01); **G07B 15/063**
(2013.01); **G08G 1/017** (2013.01); **G08G**
1/096838 (2013.01); **B60W 2540/00** (2013.01);
G01S 2013/936 (2013.01)
- (58) **Field of Classification Search**
CPC . G01S 2013/936; B60W 40/08; B60W 50/08;
B60W 2540/00
See application file for complete search history.
- (56) **References Cited**
U.S. PATENT DOCUMENTS
- | | | | | | | | |
|-----------|----|---------|---------------------|-----------|----|---------|----------------------|
| 4,754,255 | A | 6/1988 | Sanders et al. | 6,662,077 | B2 | 12/2003 | Haag |
| 4,875,391 | A | 10/1989 | Leising et al. | 6,675,081 | B2 | 1/2004 | Shuman et al. |
| 5,136,498 | A | 8/1992 | McLaughlin et al. | 6,678,747 | B2 | 1/2004 | Goossen et al. |
| 5,204,817 | A | 4/1993 | Yoshida | 6,681,176 | B2 | 1/2004 | Funk et al. |
| 5,363,306 | A | 11/1994 | Kuwahara et al. | 6,690,260 | B1 | 2/2004 | Ashihara |
| 5,508,689 | A | 4/1996 | Rado et al. | 6,690,940 | B1 | 2/2004 | Brown et al. |
| 5,521,815 | A | 5/1996 | Rose | 6,724,920 | B1 | 4/2004 | Berenz et al. |
| 5,529,138 | A | 6/1996 | Shaw et al. | 6,754,580 | B1 | 6/2004 | Ask et al. |
| 5,531,122 | A | 7/1996 | Chatham et al. | 6,757,593 | B2 | 6/2004 | Mori et al. |
| 5,572,201 | A | 11/1996 | Graham et al. | 6,762,684 | B1 | 7/2004 | Camhi |
| 5,572,450 | A | 11/1996 | Worthy | 6,765,495 | B1 | 7/2004 | Dunning et al. |
| 5,610,821 | A | 3/1997 | Gazis et al. | 6,778,888 | B2 | 8/2004 | Cataldo et al. |
| 5,648,769 | A | 7/1997 | Sato et al. | 6,782,240 | B1 | 8/2004 | Tabe |
| 5,710,702 | A | 1/1998 | Hayashi et al. | 6,785,531 | B2 | 8/2004 | Lepley et al. |
| 5,794,164 | A | 8/1998 | Heckert et al. | 6,816,783 | B2 | 11/2004 | Hashima et al. |
| 5,797,134 | A | 8/1998 | McMillan et al. | 6,820,259 | B1 | 11/2004 | Kawamata et al. |
| 5,812,067 | A | 9/1998 | Bergholz et al. | 6,944,533 | B2 | 9/2005 | Obradovich et al. |
| 5,825,283 | A | 10/1998 | Camhi | 6,950,022 | B2 | 9/2005 | Breed |
| 5,838,251 | A | 11/1998 | Brinkmeyer et al. | 6,958,707 | B1 | 10/2005 | Siegel |
| 5,847,661 | A | 12/1998 | Ricci | 6,992,580 | B2 | 1/2006 | Kotzin et al. |
| 5,890,080 | A | 3/1999 | Coverdill et al. | 7,019,641 | B1 | 3/2006 | Lakshmanan et al. |
| 5,928,294 | A | 7/1999 | Zelinkovsky | 7,020,544 | B2 | 3/2006 | Shinada et al. |
| 5,949,345 | A | 9/1999 | Beckert et al. | 7,021,691 | B1 | 4/2006 | Schmidt et al. |
| 5,983,161 | A | 11/1999 | Lemelson et al. | 7,042,345 | B2 | 5/2006 | Ellis |
| 5,986,575 | A | 11/1999 | Jones et al. | 7,047,129 | B2 | 5/2006 | Uotani |
| 6,038,426 | A | 3/2000 | Williams, Jr. | 7,058,898 | B2 | 6/2006 | McWalter et al. |
| 6,081,756 | A | 6/2000 | Mio et al. | 7,096,431 | B2 | 8/2006 | Tambata et al. |
| D429,684 | S | 8/2000 | Johnson | 7,142,696 | B1 | 11/2006 | Engelsberg et al. |
| 6,128,003 | A | 10/2000 | Smith et al. | 7,164,117 | B2 | 1/2007 | Breed et al. |
| 6,141,620 | A | 10/2000 | Zyburt et al. | 7,187,947 | B1 | 3/2007 | White et al. |
| 6,148,261 | A | 11/2000 | Obradovich et al. | 7,203,598 | B1 | 4/2007 | Whitsell |
| 6,152,514 | A | 11/2000 | McLellen | 7,233,861 | B2 | 6/2007 | Van Buer et al. |
| 6,157,321 | A | 12/2000 | Ricci | 7,239,960 | B2 | 7/2007 | Yokota et al. |
| 6,198,996 | B1 | 3/2001 | Berstis | 7,277,454 | B2 | 10/2007 | Mocek et al. |
| 6,199,001 | B1 | 3/2001 | Ohta et al. | 7,284,769 | B2 | 10/2007 | Breed |
| 6,202,008 | B1 | 3/2001 | Beckert et al. | 7,289,645 | B2 | 10/2007 | Yamamoto et al. |
| 6,252,544 | B1 | 6/2001 | Hoffberg | 7,295,921 | B2 | 11/2007 | Spencer et al. |
| 6,267,428 | B1 | 7/2001 | Baldas et al. | 7,313,547 | B2 | 12/2007 | Mocek et al. |
| 6,302,438 | B1 | 10/2001 | Stopper, Jr. et al. | 7,333,012 | B1 | 2/2008 | Nguyen |
| 6,310,542 | B1 | 10/2001 | Gehlot | 7,343,148 | B1 | 3/2008 | O'Neil |
| 6,317,058 | B1 | 11/2001 | Lemelson et al. | 7,386,376 | B2 | 6/2008 | Basir et al. |
| 6,339,826 | B2 | 1/2002 | Hayes, Jr. et al. | 7,386,799 | B1 | 6/2008 | Clanton et al. |
| 6,356,838 | B1 | 3/2002 | Paul | 7,432,829 | B2 | 10/2008 | Poltorak |
| 6,388,579 | B1 | 5/2002 | Adcox et al. | 7,474,264 | B2 | 1/2009 | Bolduc et al. |
| 6,480,224 | B1 | 11/2002 | Brown | 7,493,140 | B2 | 2/2009 | Michmerhuizen et al. |
| 6,502,022 | B1 | 12/2002 | Chastain et al. | 7,526,539 | B1 | 4/2009 | Hsu |
| 6,519,519 | B1 | 2/2003 | Stopczynski | 7,548,815 | B2 | 6/2009 | Watkins et al. |
| 6,526,335 | B1 | 2/2003 | Treyz et al. | 7,566,083 | B2 | 7/2009 | Vitito |
| 6,557,752 | B1 | 5/2003 | Yacoob | 7,606,660 | B2 | 10/2009 | Diaz et al. |
| 6,563,910 | B2 | 5/2003 | Menard et al. | 7,606,867 | B1 | 10/2009 | Singhal et al. |
| 6,587,739 | B1 | 7/2003 | Abrams et al. | 7,643,913 | B2 | 1/2010 | Taki et al. |
| 6,598,227 | B1 | 7/2003 | Berry et al. | 7,650,234 | B2 | 1/2010 | Obradovich et al. |
| 6,607,212 | B1 | 8/2003 | Reimer et al. | 7,671,764 | B2 | 3/2010 | Uyeki et al. |
| 6,617,981 | B2 | 9/2003 | Basinger | 7,680,596 | B2 | 3/2010 | Uyeki et al. |
| | | | | 7,683,771 | B1 | 3/2010 | Loeb |
| | | | | 7,711,468 | B1 | 5/2010 | Levy |
| | | | | 7,734,315 | B2 | 6/2010 | Rathus et al. |
| | | | | 7,748,021 | B2 | 6/2010 | Obradovich et al. |
| | | | | RE41,449 | E | 7/2010 | Krahnstoever et al. |
| | | | | 7,791,499 | B2 | 9/2010 | Mohan et al. |
| | | | | 7,796,190 | B2 | 9/2010 | Basso et al. |
| | | | | 7,802,832 | B2 | 9/2010 | Carnevali |
| | | | | 7,821,421 | B2 | 10/2010 | Tamir et al. |
| | | | | 7,832,762 | B2 | 11/2010 | Breed |
| | | | | 7,864,073 | B2 | 1/2011 | Lee et al. |
| | | | | 7,872,591 | B2 | 1/2011 | Kane et al. |
| | | | | 7,873,471 | B2 | 1/2011 | Gieseke |
| | | | | 7,881,703 | B2 | 2/2011 | Roundtree et al. |
| | | | | 7,891,004 | B1 | 2/2011 | Gelvin et al. |
| | | | | 7,891,719 | B2 | 2/2011 | Carnevali |
| | | | | 7,899,610 | B2 | 3/2011 | McClellan |
| | | | | 7,966,678 | B2 | 6/2011 | Ten Eyck et al. |
| | | | | 7,969,290 | B2 | 6/2011 | Waeiler et al. |
| | | | | 7,969,324 | B2 | 6/2011 | Chevion et al. |
| | | | | 8,060,631 | B2 | 11/2011 | Collart et al. |
| | | | | 8,064,925 | B1 | 11/2011 | Sun et al. |
| | | | | 8,066,313 | B2 | 11/2011 | Carnevali |
| | | | | 8,098,170 | B1 | 1/2012 | Szczerba et al. |
| | | | | 8,113,564 | B2 | 2/2012 | Carnevali |

(56)

References Cited

U.S. PATENT DOCUMENTS

8,131,419 B2	3/2012	Ampunan et al.	2002/0095249 A1	7/2002	Lang
8,157,310 B2	4/2012	Carnevali	2002/0097145 A1	7/2002	Tumey et al.
8,162,368 B2	4/2012	Carnevali	2002/0103622 A1	8/2002	Burge
8,175,802 B2	5/2012	Forstall et al.	2002/0105968 A1	8/2002	Pruzan et al.
8,233,919 B2	7/2012	Haag et al.	2002/0110146 A1	8/2002	Thayer et al.
8,245,609 B1	8/2012	Greenwald et al.	2002/0126876 A1	9/2002	Paul et al.
8,306,514 B1	11/2012	Nunally	2002/0128774 A1	9/2002	Takezaki et al.
8,334,847 B2	12/2012	Tomkins	2002/0143461 A1	10/2002	Burns et al.
8,346,233 B2	1/2013	Aaron et al.	2002/0143643 A1	10/2002	Catan
8,346,432 B2	1/2013	Van Wiemeersch et al.	2002/0152010 A1	10/2002	Colmenarez et al.
8,350,721 B2	1/2013	Can	2002/0154217 A1	10/2002	Ikeda
8,352,282 B2	1/2013	Jensen et al.	2002/0169551 A1	11/2002	Inoue et al.
8,369,263 B2	2/2013	Dowling et al.	2002/0174021 A1	11/2002	Chu et al.
8,417,449 B1	4/2013	Denise	2003/0004624 A1	1/2003	Wilson et al.
8,432,260 B2	4/2013	Talty et al.	2003/0007227 A1	1/2003	Ogino
8,442,389 B2	5/2013	Kashima et al.	2003/0055557 A1	3/2003	Dutta et al.
8,442,758 B1	5/2013	Rovik et al.	2003/0060937 A1	3/2003	Shinada et al.
8,467,965 B2	6/2013	Chang	2003/0065432 A1	4/2003	Shuman et al.
8,497,842 B2	7/2013	Tomkins et al.	2003/0101451 A1	5/2003	Bentolila et al.
8,498,809 B2	7/2013	Bill	2003/0109972 A1	6/2003	Tak
8,509,982 B2	8/2013	Montemerlo et al.	2003/0125846 A1	7/2003	Yu et al.
8,521,410 B2	8/2013	Mizuno et al.	2003/0132666 A1	7/2003	Bond et al.
8,527,143 B2	9/2013	Tan	2003/0149530 A1	8/2003	Stopczynski
8,527,146 B1	9/2013	Jackson et al.	2003/0158638 A1	8/2003	Yakes et al.
8,532,574 B2	9/2013	Kirsch	2003/0182435 A1	9/2003	Redlich et al.
8,543,330 B2	9/2013	Taylor et al.	2003/0202683 A1	10/2003	Ma et al.
8,547,340 B2	10/2013	Sizelove et al.	2003/0204290 A1	10/2003	Sadler et al.
8,548,669 B2	10/2013	Naylor	2003/0230443 A1	12/2003	Cramer et al.
8,559,183 B1	10/2013	Davis	2004/0017292 A1	1/2004	Reese et al.
8,577,600 B1	11/2013	Pierfelice	2004/0024502 A1	2/2004	Squires et al.
8,578,279 B2	11/2013	Chen et al.	2004/0036622 A1	2/2004	Dukach et al.
8,583,292 B2	11/2013	Preston et al.	2004/0039500 A1	2/2004	Amendola et al.
8,589,073 B2	11/2013	Guha et al.	2004/0039504 A1	2/2004	Coffee et al.
8,600,611 B2	12/2013	Seize	2004/0068364 A1	4/2004	Zhao et al.
8,613,385 B1	12/2013	Hulet et al.	2004/0070920 A1	4/2004	Flueli
8,621,645 B1	12/2013	Spackman	2004/0093155 A1	5/2004	Simonds et al.
8,624,727 B2	1/2014	Saigh et al.	2004/0117494 A1	6/2004	Mitchell et al.
8,634,984 B2	1/2014	Sumizawa	2004/0128062 A1	7/2004	Ogino et al.
8,644,165 B2	2/2014	Saaimaki et al.	2004/0153356 A1	8/2004	Lockwood et al.
8,660,735 B2	2/2014	Tengler et al.	2004/0162019 A1	8/2004	Horita et al.
8,671,068 B2	3/2014	Harber et al.	2004/0180653 A1	9/2004	Royalty
8,688,372 B2	4/2014	Bhagal et al.	2004/0182574 A1	9/2004	Adnan et al.
8,705,527 B1	4/2014	Addepalli et al.	2004/0193347 A1	9/2004	Harumoto et al.
8,706,143 B1	4/2014	Elias	2004/0203974 A1	10/2004	Seibel
8,718,797 B1	5/2014	Addepalli et al.	2004/0204837 A1	10/2004	Singleton
8,725,311 B1	5/2014	Breed	2004/0209594 A1	10/2004	Naboulsi
8,730,033 B2	5/2014	Yarnold et al.	2004/0217850 A1	11/2004	Perttunen et al.
8,737,986 B2	5/2014	Rhoads et al.	2004/0225557 A1	11/2004	Phelan et al.
8,761,673 B2	6/2014	Sakata	2004/0255123 A1	12/2004	Noyama et al.
8,774,842 B2	7/2014	Jones et al.	2004/0257208 A1	12/2004	Huang et al.
8,779,947 B2	7/2014	Tengler et al.	2004/0260470 A1	12/2004	Rast
8,782,262 B2	7/2014	Collart et al.	2005/0012599 A1	1/2005	DeMatteo
8,793,065 B2	7/2014	Seltzer et al.	2005/0031100 A1	2/2005	Iggulden et al.
8,798,918 B2	8/2014	Onishi et al.	2005/0038598 A1	2/2005	Oesterling et al.
8,805,110 B2	8/2014	Rhoads et al.	2005/0042999 A1	2/2005	Rappaport
8,812,171 B2	8/2014	Fillev et al.	2005/0065678 A1	3/2005	Smith et al.
8,817,761 B2	8/2014	Gruberman et al.	2005/0065711 A1	3/2005	Dahlgren et al.
8,825,031 B2	9/2014	Aaron et al.	2005/0086051 A1	4/2005	Brulle-Drews
8,825,277 B2	9/2014	McClellan et al.	2005/0093717 A1	5/2005	Lilja
8,825,382 B2	9/2014	Liu	2005/0097541 A1	5/2005	Holland
8,826,261 B1	9/2014	Anand Ag et al.	2005/0114864 A1	5/2005	Surace
8,838,088 B1	9/2014	Henn et al.	2005/0122235 A1	6/2005	Teffer et al.
8,862,317 B2	10/2014	Shin et al.	2005/0124211 A1	6/2005	Diessner et al.
8,977,408 B1	3/2015	Cazanas et al.	2005/0130744 A1	6/2005	Eck et al.
9,043,016 B2	5/2015	Filippov et al.	2005/0144156 A1	6/2005	Barber
9,229,905 B1	1/2016	Penilla et al.	2005/0149752 A1	7/2005	Johnson et al.
9,694,685 B2 *	7/2017	Ricci B60L 3/0015	2005/0153760 A1	7/2005	Varley
2001/0010516 A1	8/2001	Roh et al.	2005/0159853 A1	7/2005	Takahashi et al.
2001/0015888 A1	8/2001	Shaler et al.	2005/0159892 A1	7/2005	Chung
2002/0009978 A1	1/2002	Dukach et al.	2005/0192727 A1	9/2005	Shostak et al.
2002/0023010 A1	2/2002	Rittmaster et al.	2005/0197748 A1	9/2005	Holst et al.
2002/0026278 A1	2/2002	Feldman et al.	2005/0197767 A1	9/2005	Nortrup
2002/0045484 A1	4/2002	Eck et al.	2005/0251324 A1	11/2005	Wiener et al.
2002/0065046 A1	5/2002	Mankins et al.	2005/0261815 A1	11/2005	Cowelchuk et al.
2002/0077985 A1	6/2002	Kobata et al.	2005/0278093 A1	12/2005	Kameyama
			2005/0283284 A1	12/2005	Grenier et al.
			2006/0015819 A1	1/2006	Hawkins et al.
			2006/0036358 A1	2/2006	Hale et al.
			2006/0044119 A1	3/2006	Egelhaaf

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0047386	A1	3/2006	Kanevsky et al.	2008/0164985	A1	7/2008	Iketani et al.
2006/0058948	A1	3/2006	Blass et al.	2008/0169940	A1	7/2008	Lee et al.
2006/0059229	A1	3/2006	Bain et al.	2008/0174451	A1	7/2008	Harrington et al.
2006/0125631	A1	6/2006	Sharony	2008/0212215	A1	9/2008	Schofield et al.
2006/0130033	A1	6/2006	Stoffels et al.	2008/0216067	A1	9/2008	Villing
2006/0142933	A1	6/2006	Feng	2008/0228358	A1	9/2008	Wang et al.
2006/0173841	A1	8/2006	Bill	2008/0234919	A1	9/2008	Ritter et al.
2006/0175403	A1	8/2006	McConnell et al.	2008/0252487	A1	10/2008	McClellan et al.
2006/0184319	A1	8/2006	Seick et al.	2008/0253613	A1	10/2008	Jones et al.
2006/0212909	A1	9/2006	Girard et al.	2008/0255721	A1	10/2008	Yamada
2006/0241836	A1	10/2006	Kachouh et al.	2008/0255722	A1	10/2008	McClellan et al.
2006/0243056	A1	11/2006	Sundermeyer et al.	2008/0269958	A1	10/2008	Filev et al.
2006/0250272	A1	11/2006	Puamau	2008/0281508	A1	11/2008	Fu
2006/0253307	A1	11/2006	Warren et al.	2008/0300778	A1	12/2008	Kuznetsov
2006/0259210	A1	11/2006	Tanaka et al.	2008/0305780	A1	12/2008	Williams et al.
2006/0274829	A1	12/2006	Siemens et al.	2008/0319602	A1	12/2008	McClellan et al.
2006/0282204	A1	12/2006	Breed	2009/0006525	A1	1/2009	Moore
2006/0287807	A1	12/2006	Teffler	2009/0024419	A1	1/2009	McClellan et al.
2006/0287865	A1	12/2006	Cross et al.	2009/0037719	A1	2/2009	Sakthikumar et al.
2006/0288382	A1	12/2006	Vitito	2009/0040026	A1	2/2009	Tanaka
2006/0290516	A1	12/2006	Muehlsteff et al.	2009/0055178	A1	2/2009	Coon
2007/0001831	A1	1/2007	Raz et al.	2009/0082951	A1	3/2009	Graessley
2007/0002032	A1	1/2007	Powers et al.	2009/0099720	A1	4/2009	Elgali
2007/0010942	A1	1/2007	Bill	2009/0112393	A1	4/2009	Maten et al.
2007/0015485	A1	1/2007	DeBiasio et al.	2009/0112452	A1	4/2009	Buck et al.
2007/0028370	A1	2/2007	Seng	2009/0119657	A1	5/2009	Link, II
2007/0032225	A1	2/2007	Konicek et al.	2009/0125174	A1	5/2009	Delean
2007/0057781	A1	3/2007	Breed	2009/0132294	A1	5/2009	Haines
2007/0061057	A1	3/2007	Huang et al.	2009/0138336	A1	5/2009	Ashley et al.
2007/0067614	A1	3/2007	Berry et al.	2009/0144622	A1	6/2009	Evans et al.
2007/0069880	A1	3/2007	Best et al.	2009/0157312	A1	6/2009	Black et al.
2007/0083298	A1	4/2007	Pierce et al.	2009/0158200	A1	6/2009	Palahnuk et al.
2007/0088488	A1	4/2007	Reeves et al.	2009/0180668	A1	7/2009	Jones et al.
2007/0103328	A1	5/2007	Lakshmanan et al.	2009/0189373	A1	7/2009	Schramm et al.
2007/0115101	A1	5/2007	Creekbaum et al.	2009/0189979	A1	7/2009	Smyth
2007/0118301	A1	5/2007	Andarawis et al.	2009/0195370	A1	8/2009	Huffman et al.
2007/0120697	A1	5/2007	Ayoub et al.	2009/0210257	A1	8/2009	Chalfant et al.
2007/0135995	A1	6/2007	Kikuchi et al.	2009/0216935	A1	8/2009	Flick
2007/0156317	A1	7/2007	Breed	2009/0222200	A1	9/2009	Link et al.
2007/0182625	A1	8/2007	Kerai et al.	2009/0224931	A1	9/2009	Dietz et al.
2007/0182816	A1	8/2007	Fox	2009/0224942	A1	9/2009	Goudy et al.
2007/0185969	A1	8/2007	Davis	2009/0234578	A1	9/2009	Newby et al.
2007/0192486	A1	8/2007	Wilson et al.	2009/0241883	A1	10/2009	Nagoshi et al.
2007/0194902	A1	8/2007	Blanco et al.	2009/0254446	A1	10/2009	Chernyak
2007/0194944	A1	8/2007	Galera et al.	2009/0264849	A1	10/2009	La Croix
2007/0195997	A1	8/2007	Paul et al.	2009/0275321	A1	11/2009	Crowe
2007/0200663	A1	8/2007	White et al.	2009/0278750	A1	11/2009	Man et al.
2007/0208860	A1	9/2007	Zellner et al.	2009/0278915	A1	11/2009	Kramer et al.
2007/0213090	A1	9/2007	Holmberg	2009/0279839	A1	11/2009	Nakamura et al.
2007/0228826	A1	10/2007	Jordan et al.	2009/0284359	A1	11/2009	Huang et al.
2007/0233341	A1	10/2007	Logsdon	2009/0287405	A1	11/2009	Liu et al.
2007/0250228	A1	10/2007	Reddy et al.	2009/0299572	A1	12/2009	Fujikawa et al.
2007/0257815	A1	11/2007	Gunderson et al.	2009/0312998	A1	12/2009	Berckmans et al.
2007/0276596	A1	11/2007	Solomon et al.	2009/0319181	A1	12/2009	Khosravy et al.
2007/0280505	A1	12/2007	Breed	2010/0008053	A1	1/2010	Osternack et al.
2008/0005974	A1	1/2008	Delgado Vazquez et al.	2010/0023204	A1	1/2010	Basir et al.
2008/0023253	A1	1/2008	Prost-Fin et al.	2010/0035620	A1	2/2010	Naden et al.
2008/0027337	A1	1/2008	Dugan et al.	2010/0036560	A1	2/2010	Wright et al.
2008/0033635	A1	2/2008	Obradovich et al.	2010/0042498	A1	2/2010	Schalk
2008/0042824	A1	2/2008	Kates	2010/0052945	A1	3/2010	Breed
2008/0051957	A1	2/2008	Breed et al.	2010/0057337	A1	3/2010	Fuchs
2008/0052627	A1	2/2008	Oguchi	2010/0066498	A1	3/2010	Fenton
2008/0071465	A1	3/2008	Chapman et al.	2010/0069115	A1	3/2010	Liu
2008/0082237	A1	4/2008	Breed	2010/0070338	A1	3/2010	Siotia et al.
2008/0086455	A1	4/2008	Meisels et al.	2010/0077094	A1	3/2010	Howarter et al.
2008/0090522	A1	4/2008	Oyama	2010/0085213	A1	4/2010	Turnock et al.
2008/0104227	A1	5/2008	Birnie et al.	2010/0087987	A1	4/2010	Huang et al.
2008/0119994	A1	5/2008	Kameyama	2010/0090817	A1	4/2010	Yamaguchi et al.
2008/0129475	A1	6/2008	Breed et al.	2010/0097178	A1	4/2010	Pisz et al.
2008/0143085	A1	6/2008	Breed et al.	2010/0097239	A1	4/2010	Campbell et al.
2008/0147280	A1	6/2008	Breed	2010/0097458	A1	4/2010	Zhang et al.
2008/0148374	A1	6/2008	Spaur et al.	2010/0106344	A1	4/2010	Edwards et al.
2008/0154712	A1	6/2008	Wellman	2010/0106418	A1	4/2010	Kindo et al.
2008/0154957	A1	6/2008	Taylor et al.	2010/0118025	A1	5/2010	Smith et al.
2008/0161986	A1	7/2008	Breed	2010/0121570	A1	5/2010	Tokue et al.
				2010/0121645	A1	5/2010	Seitz et al.
				2010/0125387	A1	5/2010	Sehyun et al.
				2010/0125405	A1	5/2010	Chae et al.
				2010/0125811	A1	5/2010	Moore et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0127847 A1	5/2010	Evans et al.	2011/0119344 A1	5/2011	Eustis
2010/0131300 A1	5/2010	Collopy et al.	2011/0130915 A1	6/2011	Wright et al.
2010/0134958 A1	6/2010	Disaverio et al.	2011/0134749 A1	6/2011	Speks et al.
2010/0136944 A1	6/2010	Taylor et al.	2011/0137520 A1	6/2011	Rector et al.
2010/0137037 A1	6/2010	Basir	2011/0145331 A1	6/2011	Christie et al.
2010/0144284 A1	6/2010	Chutorash et al.	2011/0172873 A1	7/2011	Szwabowski et al.
2010/0145700 A1	6/2010	Kennewick et al.	2011/0175754 A1	7/2011	Karpinsky
2010/0145987 A1	6/2010	Harper et al.	2011/0183658 A1	7/2011	Zellner
2010/0152976 A1	6/2010	White et al.	2011/0187520 A1	8/2011	Filev et al.
2010/0169432 A1	7/2010	Santori et al.	2011/0193707 A1	8/2011	Ngo
2010/0174474 A1	7/2010	Nagase	2011/0193726 A1	8/2011	Szwabowski et al.
2010/0179712 A1	7/2010	Pepitone et al.	2011/0195699 A1	8/2011	Tadayon et al.
2010/0185341 A1	7/2010	Wilson et al.	2011/0197187 A1	8/2011	Roh
2010/0188831 A1	7/2010	Ortel	2011/0205047 A1	8/2011	Patel et al.
2010/0197359 A1	8/2010	Harris	2011/0209079 A1	8/2011	Tarte et al.
2010/0202346 A1	8/2010	Sitzes et al.	2011/0210867 A1	9/2011	Benedikt
2010/0211259 A1	8/2010	McClellan	2011/0212717 A1	9/2011	Rhoads et al.
2010/0211282 A1	8/2010	Nakata et al.	2011/0221656 A1	9/2011	Haddick et al.
2010/0211300 A1	8/2010	Jaffe et al.	2011/0224865 A1	9/2011	Gordon et al.
2010/0211304 A1	8/2010	Hwang et al.	2011/0224898 A1	9/2011	Scofield et al.
2010/0211441 A1	8/2010	Sprigg et al.	2011/0225527 A1	9/2011	Law et al.
2010/0217458 A1	8/2010	Schweiger et al.	2011/0227757 A1	9/2011	Chen et al.
2010/0222939 A1	9/2010	Namburu et al.	2011/0231091 A1	9/2011	Gourlay et al.
2010/0228404 A1	9/2010	Link et al.	2011/0234369 A1	9/2011	Cai et al.
2010/0234071 A1	9/2010	Shabtay et al.	2011/0245999 A1	10/2011	Kordonowy
2010/0235042 A1	9/2010	Ying	2011/0246210 A1	10/2011	Matsur
2010/0235744 A1	9/2010	Schultz	2011/0247013 A1	10/2011	Feller et al.
2010/0235891 A1	9/2010	Oglesbee et al.	2011/0251734 A1	10/2011	Schepp et al.
2010/0250071 A1	9/2010	Pala et al.	2011/0257973 A1	10/2011	Chutorash et al.
2010/0253493 A1	10/2010	Szczerba et al.	2011/0267204 A1	11/2011	Chuang et al.
2010/0256836 A1	10/2010	Mudalige	2011/0267205 A1	11/2011	McClellan et al.
2010/0265104 A1	10/2010	Zlojutro	2011/0286676 A1	11/2011	El Dokor
2010/0268426 A1	10/2010	Pathak et al.	2011/0291886 A1	12/2011	Krieter
2010/0274410 A1	10/2010	Tsien et al.	2011/0291926 A1	12/2011	Gokturk et al.
2010/0280751 A1	11/2010	Breed	2011/0298808 A1	12/2011	Rovik
2010/0287303 A1	11/2010	Smith et al.	2011/0301844 A1	12/2011	Aono
2010/0289632 A1	11/2010	Seder et al.	2011/0307354 A1	12/2011	Erman et al.
2010/0289643 A1	11/2010	Trundle et al.	2011/0307570 A1	12/2011	Speks
2010/0291427 A1	11/2010	Zhou	2011/0309926 A1	12/2011	Eikelenberg et al.
2010/0295676 A1	11/2010	Khachaturov et al.	2011/0309953 A1	12/2011	Petite et al.
2010/0304640 A1	12/2010	Sofman et al.	2011/0313653 A1	12/2011	Lindner
2010/0305807 A1	12/2010	Basir et al.	2011/0320089 A1	12/2011	Lewis
2010/0306080 A1	12/2010	Trandal et al.	2012/0006610 A1	1/2012	Wallace et al.
2010/0306309 A1	12/2010	Santori et al.	2012/0010807 A1	1/2012	Zhou
2010/0306435 A1	12/2010	Nigoghosian et al.	2012/0016581 A1	1/2012	Mochizuki et al.
2010/0315218 A1	12/2010	Cades et al.	2012/0029852 A1	2/2012	Goff et al.
2010/0321151 A1	12/2010	Matsuura et al.	2012/0030002 A1	2/2012	Bous et al.
2010/0325626 A1	12/2010	Greschler et al.	2012/0030512 A1	2/2012	Wadhwa et al.
2010/0332130 A1	12/2010	Shimizu et al.	2012/0038489 A1	2/2012	Goldshmidt
2011/0015853 A1	1/2011	DeKock et al.	2012/0046822 A1	2/2012	Anderson
2011/0018736 A1	1/2011	Carr	2012/0047530 A1	2/2012	Shkedi
2011/0021213 A1	1/2011	Carr	2012/0053793 A1	3/2012	Sala et al.
2011/0021234 A1	1/2011	Tibbits et al.	2012/0053888 A1	3/2012	Stahlin et al.
2011/0028138 A1	2/2011	Davies-Moore et al.	2012/0059789 A1	3/2012	Sakai et al.
2011/0035098 A1	2/2011	Goto et al.	2012/0065815 A1	3/2012	Hess
2011/0035141 A1	2/2011	Barker et al.	2012/0065834 A1	3/2012	Senart
2011/0040438 A1	2/2011	Kluge et al.	2012/0068956 A1	3/2012	Jira et al.
2011/0050589 A1	3/2011	Yan et al.	2012/0071097 A1	3/2012	Matsushita et al.
2011/0053506 A1	3/2011	Lemke et al.	2012/0072244 A1	3/2012	Collins et al.
2011/0077808 A1	3/2011	Hyde et al.	2012/0074770 A1	3/2012	Lee
2011/0078024 A1	3/2011	Messier et al.	2012/0083960 A1	4/2012	Zhu et al.
2011/0080282 A1	4/2011	Kleve et al.	2012/0083971 A1	4/2012	Preston
2011/0082615 A1	4/2011	Small et al.	2012/0084773 A1	4/2012	Lee et al.
2011/0084824 A1	4/2011	Tewari et al.	2012/0089299 A1	4/2012	Breed
2011/0090078 A1	4/2011	Kim et al.	2012/0092251 A1	4/2012	Hashimoto et al.
2011/0092159 A1	4/2011	Park et al.	2012/0101876 A1	4/2012	Turvey et al.
2011/0093154 A1	4/2011	Moinzadeh et al.	2012/0101914 A1	4/2012	Kumar et al.
2011/0093158 A1	4/2011	Theisen et al.	2012/0105613 A1	5/2012	Weng et al.
2011/0093438 A1	4/2011	Poulsen	2012/0106114 A1	5/2012	Caron et al.
2011/0093846 A1	4/2011	Moinzadeh et al.	2012/0109446 A1	5/2012	Yousefi et al.
2011/0105097 A1	5/2011	Tadayon et al.	2012/0109451 A1	5/2012	Tan
2011/0106375 A1	5/2011	Sundaram et al.	2012/0110356 A1	5/2012	Yousefi et al.
2011/0112717 A1	5/2011	Resner	2012/0113822 A1	5/2012	Letner
2011/0112969 A1	5/2011	Zaid et al.	2012/0115446 A1	5/2012	Guatama et al.
2011/0117933 A1	5/2011	Andersson	2012/0116609 A1	5/2012	Jung et al.
			2012/0116678 A1	5/2012	Witmer
			2012/0116696 A1	5/2012	Wank
			2012/0146766 A1	6/2012	Geisler et al.
			2012/0146809 A1	6/2012	Oh et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0149341	A1	6/2012	Tadayon et al.	2013/0144462	A1	6/2013	Ricci
2012/0150651	A1	6/2012	Hoffberg et al.	2013/0144463	A1	6/2013	Ricci et al.
2012/0155636	A1	6/2012	Muthaiah	2013/0144469	A1	6/2013	Ricci
2012/0158436	A1	6/2012	Bauer et al.	2013/0144470	A1	6/2013	Ricci
2012/0173900	A1	7/2012	Diab et al.	2013/0144474	A1	6/2013	Ricci
2012/0173905	A1	7/2012	Diab et al.	2013/0144486	A1	6/2013	Ricci
2012/0179325	A1	7/2012	Faenger	2013/0144520	A1	6/2013	Ricci
2012/0179547	A1	7/2012	Besore et al.	2013/0144657	A1	6/2013	Ricci
2012/0188876	A1	7/2012	Chow et al.	2013/0145065	A1	6/2013	Ricci
2012/0197523	A1	8/2012	Kirsch	2013/0145279	A1	6/2013	Ricci
2012/0197669	A1	8/2012	Kote et al.	2013/0145297	A1	6/2013	Ricci et al.
2012/0204166	A1	8/2012	Ichihara	2013/0145360	A1	6/2013	Ricci
2012/0210160	A1	8/2012	Fuhrman	2013/0145401	A1	6/2013	Ricci
2012/0215375	A1	8/2012	Chang	2013/0145482	A1	6/2013	Ricci et al.
2012/0217928	A1	8/2012	Kulidjian	2013/0147638	A1	6/2013	Ricci
2012/0218125	A1	8/2012	Demirdjian et al.	2013/0151031	A1	6/2013	Ricci
2012/0226413	A1	9/2012	Chen et al.	2013/0151065	A1	6/2013	Ricci
2012/0238286	A1	9/2012	Mallavarapu et al.	2013/0151088	A1	6/2013	Ricci
2012/0239242	A1	9/2012	Uehara	2013/0151288	A1	6/2013	Bowne et al.
2012/0242510	A1	9/2012	Choi et al.	2013/0152003	A1	6/2013	Ricci et al.
2012/0254763	A1	10/2012	Protopapas et al.	2013/0154298	A1	6/2013	Ricci
2012/0254804	A1	10/2012	Shema et al.	2013/0157640	A1	6/2013	Aycock
2012/0259951	A1	10/2012	Schalk et al.	2013/0157647	A1	6/2013	Kolodziej
2012/0265359	A1	10/2012	Das	2013/0158778	A1	6/2013	Tengler et al.
2012/0274459	A1	11/2012	Jaisimha et al.	2013/0158821	A1	6/2013	Ricci
2012/0274481	A1	11/2012	Ginsberg et al.	2013/0166096	A1	6/2013	Jotanovic
2012/0284292	A1	11/2012	Rechsteiner et al.	2013/0166097	A1	6/2013	Ricci
2012/0289217	A1	11/2012	Reimer et al.	2013/0166098	A1	6/2013	Lavie et al.
2012/0289253	A1	11/2012	Haag et al.	2013/0166152	A1	6/2013	Butterworth
2012/0296567	A1	11/2012	Breed	2013/0166208	A1	6/2013	Forstall et al.
2012/0313771	A1	12/2012	Wotliff, III	2013/0167159	A1	6/2013	Ricci et al.
2012/0316720	A1	12/2012	Hyde et al.	2013/0173531	A1	7/2013	Rinearson et al.
2012/0317561	A1	12/2012	Aslam et al.	2013/0179689	A1	7/2013	Matsumoto et al.
2012/0323413	A1	12/2012	Kedar-Dongarkar et al.	2013/0181847	A1	7/2013	Willig et al.
2012/0327231	A1	12/2012	Cochran et al.	2013/0190978	A1	7/2013	Kato et al.
2013/0005263	A1	1/2013	Sakata	2013/0194108	A1	8/2013	Lapiotis et al.
2013/0005414	A1	1/2013	Bindra et al.	2013/0197796	A1	8/2013	Obradovich et al.
2013/0013157	A1	1/2013	Kim et al.	2013/0198031	A1	8/2013	Mitchell et al.
2013/0019252	A1	1/2013	Haase et al.	2013/0198737	A1	8/2013	Ricci
2013/0024060	A1	1/2013	Sukkarie et al.	2013/0198802	A1	8/2013	Ricci
2013/0030645	A1	1/2013	Divine et al.	2013/0200991	A1	8/2013	Ricci et al.
2013/0030811	A1	1/2013	Olleon et al.	2013/0203400	A1	8/2013	Ricci
2013/0031540	A1	1/2013	Throop et al.	2013/0204455	A1	8/2013	Chia et al.
2013/0031541	A1	1/2013	Wilks et al.	2013/0204457	A1	8/2013	King
2013/0035063	A1	2/2013	Fisk et al.	2013/0204466	A1	8/2013	Ricci
2013/0046624	A1	2/2013	Calman	2013/0204484	A1	8/2013	Ricci
2013/0050069	A1	2/2013	Ota	2013/0204493	A1	8/2013	Ricci et al.
2013/0055096	A1	2/2013	Kim et al.	2013/0204943	A1	8/2013	Ricci
2013/0059607	A1	3/2013	Herz et al.	2013/0205026	A1	8/2013	Ricci
2013/0063336	A1	3/2013	Sugimoto et al.	2013/0205412	A1	8/2013	Ricci
2013/0066512	A1	3/2013	Willard et al.	2013/0207794	A1	8/2013	Patel et al.
2013/0067599	A1	3/2013	Raje et al.	2013/0212065	A1	8/2013	Rahnama
2013/0075530	A1	3/2013	Shander et al.	2013/0212659	A1	8/2013	Maher et al.
2013/0079964	A1	3/2013	Sukkarie et al.	2013/0215116	A1	8/2013	Siddique et al.
2013/0083805	A1	4/2013	Lu et al.	2013/0218412	A1	8/2013	Ricci
2013/0085787	A1	4/2013	Gore et al.	2013/0218445	A1	8/2013	Basir
2013/0086164	A1	4/2013	Wheeler et al.	2013/0219039	A1	8/2013	Ricci
2013/0099915	A1	4/2013	Prasad et al.	2013/0226365	A1	8/2013	Brozovich
2013/0103196	A1	4/2013	Monceaux et al.	2013/0226371	A1	8/2013	Rovik et al.
2013/0105264	A1	5/2013	Ruth et al.	2013/0226392	A1	8/2013	Schneider et al.
2013/0116882	A1	5/2013	Link et al.	2013/0226449	A1	8/2013	Rovik et al.
2013/0116915	A1	5/2013	Ferreira et al.	2013/0226622	A1	8/2013	Adamson et al.
2013/0134730	A1	5/2013	Ricci	2013/0227648	A1	8/2013	Ricci
2013/0135118	A1	5/2013	Ricci	2013/0231784	A1	9/2013	Rovik et al.
2013/0138591	A1	5/2013	Ricci	2013/0231800	A1	9/2013	Ricci
2013/0138714	A1	5/2013	Ricci	2013/0232142	A1	9/2013	Nielsen et al.
2013/0139140	A1	5/2013	Rao et al.	2013/0238165	A1	9/2013	Garrett et al.
2013/0141247	A1	6/2013	Ricci	2013/0241720	A1	9/2013	Ricci et al.
2013/0141252	A1	6/2013	Ricci	2013/0245882	A1	9/2013	Ricci
2013/0143495	A1	6/2013	Ricci	2013/0250933	A1	9/2013	Yousefi et al.
2013/0143546	A1	6/2013	Ricci	2013/0261871	A1	10/2013	Hobbs et al.
2013/0143601	A1	6/2013	Ricci	2013/0261966	A1	10/2013	Wang et al.
2013/0144459	A1	6/2013	Ricci	2013/0265178	A1	10/2013	Tengler et al.
2013/0144460	A1	6/2013	Ricci	2013/0274997	A1	10/2013	Chien
2013/0144461	A1	6/2013	Ricci	2013/0279111	A1	10/2013	Lee
				2013/0279491	A1	10/2013	Rubin et al.
				2013/0282238	A1	10/2013	Ricci et al.
				2013/0282357	A1	10/2013	Rubin et al.
				2013/0282946	A1	10/2013	Ricci

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0288606	A1	10/2013	Kirsch	2014/0306814	A1	10/2014	Ricci
2013/0293364	A1	11/2013	Ricci et al.	2014/0306817	A1	10/2014	Ricci
2013/0293452	A1	11/2013	Ricci et al.	2014/0306826	A1	10/2014	Ricci
2013/0293480	A1	11/2013	Kritt et al.	2014/0306833	A1	10/2014	Ricci
2013/0295901	A1	11/2013	Abramson et al.	2014/0306834	A1	10/2014	Ricci
2013/0295908	A1	11/2013	Zeinstra et al.	2014/0306835	A1	10/2014	Ricci
2013/0295913	A1	11/2013	Matthews et al.	2014/0307655	A1	10/2014	Ricci
2013/0300554	A1	11/2013	Braden	2014/0307724	A1	10/2014	Ricci
2013/0301584	A1	11/2013	Addepalli et al.	2014/0308902	A1	10/2014	Ricci
2013/0304371	A1	11/2013	Kitatani et al.	2014/0309789	A1	10/2014	Ricci
2013/0308265	A1	11/2013	Arnouse	2014/0309790	A1	10/2014	Ricci
2013/0309977	A1	11/2013	Heines et al.	2014/0309804	A1	10/2014	Ricci
2013/0311038	A1	11/2013	Kim et al.	2014/0309805	A1	10/2014	Ricci
2013/0325453	A1	12/2013	Levien et al.	2014/0309806	A1	10/2014	Ricci
2013/0325568	A1	12/2013	Mangalvedkar et al.	2014/0309813	A1	10/2014	Ricci
2013/0329372	A1	12/2013	Wilkins	2014/0309814	A1	10/2014	Ricci et al.
2013/0332023	A1	12/2013	Bertosa et al.	2014/0309815	A1	10/2014	Ricci et al.
2013/0338914	A1	12/2013	Weiss	2014/0309838	A1	10/2014	Ricci
2013/0339027	A1	12/2013	Dokor et al.	2014/0309839	A1	10/2014	Ricci et al.
2013/0344856	A1	12/2013	Silver et al.	2014/0309842	A1	10/2014	Jefferies et al.
2013/0345929	A1	12/2013	Bowden et al.	2014/0309847	A1	10/2014	Ricci
2014/0028542	A1	1/2014	Lovitt et al.	2014/0309849	A1	10/2014	Ricci
2014/0032014	A1	1/2014	DeBiasio et al.	2014/0309852	A1	10/2014	Ricci
2014/0054957	A1	2/2014	Bellis	2014/0309853	A1	10/2014	Ricci
2014/0058672	A1	2/2014	Wansley et al.	2014/0309862	A1	10/2014	Ricci
2014/0066014	A1	3/2014	Nicholson et al.	2014/0309863	A1	10/2014	Ricci
2014/0067201	A1	3/2014	Visintainer et al.	2014/0309864	A1	10/2014	Ricci
2014/0067564	A1	3/2014	Yuan	2014/0309865	A1	10/2014	Ricci
2014/0070917	A1	3/2014	Protopapas	2014/0309866	A1	10/2014	Ricci
2014/0081544	A1	3/2014	Fry	2014/0309867	A1	10/2014	Ricci
2014/0088798	A1	3/2014	Himmelstein	2014/0309868	A1	10/2014	Ricci
2014/0096068	A1	4/2014	Dewan et al.	2014/0309869	A1	10/2014	Ricci
2014/0097955	A1	4/2014	Lovitt et al.	2014/0309870	A1	10/2014	Ricci et al.
2014/0109075	A1	4/2014	Hoffman et al.	2014/0309871	A1	10/2014	Ricci
2014/0109080	A1	4/2014	Ricci	2014/0309872	A1	10/2014	Ricci
2014/0120829	A1	5/2014	Bhamidipati et al.	2014/0309873	A1	10/2014	Ricci
2014/0121862	A1	5/2014	Zarella et al.	2014/0309874	A1	10/2014	Ricci
2014/0125802	A1	5/2014	Beckert et al.	2014/0309875	A1	10/2014	Ricci
2014/0143839	A1	5/2014	Ricci	2014/0309876	A1	10/2014	Ricci
2014/0164611	A1	6/2014	Molettiere et al.	2014/0309877	A1	10/2014	Ricci
2014/0168062	A1	6/2014	Katz et al.	2014/0309878	A1	10/2014	Ricci
2014/0168436	A1	6/2014	Pedicino	2014/0309879	A1	10/2014	Ricci
2014/0169621	A1	6/2014	Burr	2014/0309880	A1	10/2014	Ricci
2014/0171752	A1	6/2014	Park et al.	2014/0309885	A1	10/2014	Ricci
2014/0172727	A1	6/2014	Abhyanker et al.	2014/0309886	A1	10/2014	Ricci
2014/0188533	A1	7/2014	Davidson	2014/0309891	A1	10/2014	Ricci
2014/0195272	A1	7/2014	Sadiq et al.	2014/0309892	A1	10/2014	Ricci
2014/0198216	A1	7/2014	Zhai et al.	2014/0309893	A1	10/2014	Ricci
2014/0200737	A1	7/2014	Lortz et al.	2014/0309913	A1	10/2014	Ricci et al.
2014/0207328	A1	7/2014	Wolf et al.	2014/0309919	A1	10/2014	Ricci
2014/0220966	A1	8/2014	Muetzel et al.	2014/0309920	A1	10/2014	Ricci
2014/0222298	A1	8/2014	Gurin	2014/0309921	A1	10/2014	Ricci et al.
2014/0223384	A1	8/2014	Graumann	2014/0309922	A1	10/2014	Ricci
2014/0240089	A1	8/2014	Chang	2014/0309923	A1	10/2014	Ricci
2014/0244078	A1	8/2014	Downey et al.	2014/0309927	A1	10/2014	Ricci
2014/0244111	A1	8/2014	Gross et al.	2014/0309929	A1	10/2014	Ricci
2014/0244156	A1	8/2014	Magnusson et al.	2014/0309930	A1	10/2014	Ricci
2014/0245277	A1	8/2014	Petro et al.	2014/0309934	A1	10/2014	Ricci
2014/0245278	A1	8/2014	Zellen	2014/0309935	A1	10/2014	Ricci
2014/0245284	A1	8/2014	Alrabady et al.	2014/0309982	A1	10/2014	Ricci
2014/0252091	A1	9/2014	Morse et al.	2014/0310031	A1	10/2014	Ricci
2014/0257627	A1	9/2014	Hagan, Jr.	2014/0310075	A1	10/2014	Ricci
2014/0267035	A1	9/2014	Schalk et al.	2014/0310103	A1	10/2014	Ricci
2014/0277936	A1	9/2014	El Dokor et al.	2014/0310186	A1	10/2014	Ricci
2014/0278070	A1	9/2014	McGavran et al.	2014/0310277	A1	10/2014	Ricci
2014/0278071	A1	9/2014	San Filippo et al.	2014/0310379	A1	10/2014	Ricci et al.
2014/0281971	A1	9/2014	Isbell, III et al.	2014/0310594	A1	10/2014	Ricci et al.
2014/0282161	A1	9/2014	Cash	2014/0310610	A1	10/2014	Ricci
2014/0282278	A1	9/2014	Anderson et al.	2014/0310702	A1	10/2014	Ricci et al.
2014/0282470	A1	9/2014	Buga et al.	2014/0310739	A1	10/2014	Ricci et al.
2014/0282931	A1	9/2014	Protopapas	2014/0310788	A1	10/2014	Ricci
2014/0292545	A1	10/2014	Nemoto	2014/0322676	A1	10/2014	Raman
2014/0292665	A1	10/2014	Lathrop et al.	2014/0347207	A1	11/2014	Zeng et al.
2014/0303899	A1	10/2014	Fung	2014/0347265	A1	11/2014	Allen et al.
2014/0306799	A1	10/2014	Ricci	2015/0007155	A1	1/2015	Hoffman et al.
				2015/0012186	A1	1/2015	Horseman
				2015/0032366	A1	1/2015	Man et al.
				2015/0032670	A1	1/2015	Brazell
				2015/0057839	A1	2/2015	Chang et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

2015/0061895	A1	3/2015	Ricci	
2015/0081133	A1	3/2015	Schulz	
2015/0081167	A1	3/2015	Pisz et al.	
2015/0088423	A1	3/2015	Tuukkanen	
2015/0088515	A1	3/2015	Beaumont et al.	
2015/0116200	A1	4/2015	Kurosawa et al.	
2015/0146605	A1	5/2015	Rubin et al.	
2015/0158499	A1	6/2015	Koravadi	
2015/0178034	A1	6/2015	Penilla et al.	
2015/0363986	A1	12/2015	Hoyos et al.	
2016/0008985	A1	1/2016	Kim et al.	
2016/0070527	A1	3/2016	Ricci	
2016/0086391	A1	3/2016	Ricci	
2016/0269456	A1	9/2016	Ricci	
2016/0269469	A1	9/2016	Ricci	
2017/0136880	A1*	5/2017	Ricci	B60L 3/0015
2017/0136887	A1*	5/2017	Ricci	B60L 11/182
2017/0136902	A1*	5/2017	Ricci	B60L 11/1825
2017/0136903	A1*	5/2017	Ricci	B60L 11/1827
2017/0136904	A1*	5/2017	Ricci	B60L 11/1827
2017/0136905	A1*	5/2017	Ricci	B60L 11/1829
2017/0136907	A1*	5/2017	Ricci	B60L 3/0015
2017/0136910	A1*	5/2017	Ricci	B60L 11/1844
2018/0012279	A1*	1/2018	Ricci	G06Q 30/0625

FOREIGN PATENT DOCUMENTS

CN	101303878	11/2008
CN	102467827	5/2012
EP	1223567	7/2002
EP	1484729	12/2004
EP	2192015	6/2010
JP	2004-284450	10/2004
KR	2006-0128484	12/2006
WO	WO 2007/126204	11/2007
WO	WO 2012/102879	8/2012
WO	WO 2013/074866	5/2013
WO	WO 2013/074867	5/2013
WO	WO 2013/074868	5/2013
WO	WO 2013/074897	5/2013
WO	WO 2013/074899	5/2013
WO	WO 2013/074901	5/2013
WO	WO 2013/074919	5/2013
WO	WO 2013/074981	5/2013
WO	WO 2013/074983	5/2013
WO	WO 2013/075005	5/2013
WO	WO 2013/181310	12/2013
WO	WO 2014/014862	1/2014
WO	WO 2014/143563	9/2014
WO	WO 2014/158667	10/2014
WO	WO 2014/158672	10/2014
WO	WO 2014/158766	10/2014
WO	WO 2014/172312	10/2014
WO	WO 2014/172313	10/2014
WO	WO 2014/172316	10/2014
WO	WO 2014/172320	10/2014
WO	WO 2014/172322	10/2014
WO	WO 2014/172323	10/2014
WO	WO 2014/172327	10/2014
WO	WO 2016/145073	9/2016
WO	WO 2016/145100	9/2016

OTHER PUBLICATIONS

U.S. Appl. No. 15/396,591, filed Dec. 31, 2016, Ricci.
U.S. Appl. No. 15/396,592, filed Dec. 31, 2016, Ricci.
U.S. Appl. No. 15/396,595, filed Dec. 31, 2016, Ricci.
U.S. Appl. No. 15/396,597, filed Dec. 31, 2016, Ricci.
U.S. Appl. No. 15/396,601, filed Dec. 31, 2016, Ricci.
U.S. Appl. No. 15/396,604, filed Dec. 31, 2016, Ricci.
U.S. Appl. No. 15/396,607, filed Dec. 31, 2016, Ricci.
U.S. Appl. No. 15/396,610, filed Dec. 31, 2016, Ricci.
U.S. Appl. No. 15/396,613, filed Dec. 31, 2016, Ricci.

U.S. Appl. No. 15/396,616, filed Dec. 31, 2016, Ricci.

"How NFC Works," Near Field Communication, retrieved from <http://nearfieldcommunication.org/how-it-works.html>, retrieved on Sep. 27, 2016, 1 page.

"Near Field Communication Technology Standards," Near Field Communication, retrieved from <http://nearfieldcommunication.org/technology.html>, retrieved on Sep. 27, 2016, 1 page.

"Near Field Communication versus Bluetooth," Near Field Communication, retrieved from <http://nearfieldcommunication.org/bluetooth.html>, retrieved on Sep. 27, 2016, 1 page.

"Near Field versus Far Field," Near Field Communication, retrieved from <http://nearfieldcommunication.org/far-field.html>, retrieved on Sep. 27, 2016, 1 page.

"NFC SD and SIM Cards," Near Field Communication, retrieved from <http://nearfieldcommunication.org/sd-sim-cards.html>, retrieved on Sep. 27, 2016, 1 page.

Profiis, "Everything you need to know about NFC and mobile payments," CNET, 2014, retrieved from <https://www.cnet.com/how-to/how-nfc-works-and-mobile-payments/>, 8 pages.

Strickland, "How Near Field Communication Works," Near Field Communication, retrieved from <http://electronics.howstuffworks.com/near-field-communication.htm>, retrieved on Sep. 27, 2016, 11 pages.

U.S. Appl. No. 61/567,962, filed Dec. 7, 2011, Baarman et al.

"Nexus 10 Guidebook for Android," Google Inc., © 2012, Edition 1.2, 166 pages.

"Self-Driving: Self-Driving Autonomous Cars," available at <http://www.automotivetechologies.com/autonomous-self-driving-cars>, accessed Dec. 2016, 9 pages.

Amor-Segan et al., "Towards the Self Healing Vehicle," Automotive Electronics, Jun. 2007, 2007 3rd Institution of Engineering and Technology Conference, 7 pages.

Bennett, "Meet Samsung's Version of Apple AirPlay," CNET.com, Oct. 10, 2012, 11 pages.

Cairnie et al., "Using Finger-Pointing to Operate Secondary Controls in Automobiles," Proceedings of the IEEE Intelligent Vehicles Symposium 2000, Oct. 3-5, 2000, 6 pages.

Clark, "How Self-Driving Cars Work: The Nuts and Bolts Behind Google's Autonomous Car Program," Feb. 21, 2015, available at <http://www.makeuseof.com/tag/how-self-driving-cars-work-the-nuts-and-bolts-behind-googles-autonomous-car-program/>, 9 pages.

Deaton et al., "How Driverless Cars Will Work," Jul. 1, 2008, HowStuffWorks.com. <<http://auto.howstuffworks.com/under-the-hood/trends-innovations/driverless-car.htm>> Sep. 18, 2017, 10 pages.

Dumbaugh, "Safe Streets, Livable Streets: A Positive Approach to urban Roadside Design," Ph.D. dissertation for School of Civil & Environ. Engr., Georgia Inst. of Technology, Dec. 2005, 235 pages.

Fei et al., "A QoS-aware Dynamic Bandwidth Allocation Algorithm for Relay Stations in IEEE 802.16j-based Vehicular Networks," Proceedings of the 2010 IEEE Global Telecommunications Conference, Dec. 10, 2010, 10 pages.

Ge et al., "Optimal Relay Selection in IEEE 802.16j Multihop Relay Vehicular Networks," IEEE Transactions on Vehicular Technology, 2010, vol. 59(5), pp. 2198-2206.

Guizzo, Erico, "How Google's Self-Driving Car Works," Oct. 18, 2011, available at <https://spectrum.ieee.org/automaton/robotics/artificial-intelligence/how-google-self-driving-car-works>, 5 pages.

Heer et al., "ALPHA: An Adaptive and Lightweight Protocol for Hop-by-hop Authentication," Proceedings of CoNEXT 2008, Dec. 2008, pp. 1-12.

Jainich et al., "Towards a Middleware Approach for a Self-Configurable Automotive Embedded System," International Federation for Information Processing, 2008, pp. 55-65.

Persson "Adaptive Middleware for Self-Configurable Embedded Real-Time Systems," KTH Industrial Engineering and Management, 2009, pp. iii-71 and references.

Raychaudhuri et al., "Emerging Wireless Technologies and the Future Mobile Internet," p. 48, Cambridge Press, 2011, 3 pages.

Stephens, Leah, "How Driverless Cars Work," Interesting Engineering, Apr. 28, 2016, available at <https://interestingengineering.com/driverless-cars-work/>, 7 pages.

(56)

References Cited

OTHER PUBLICATIONS

Stoller, "Leader Election in Distributed Systems with Crash Failures," Indiana University, 1997, pp. 1-15.

Strunk et al., "The Elements of Style," 3d ed., Macmillan Publishing Co., 1979, 3 pages.

Suwatthikul, "Fault detection and diagnosis for in-vehicle networks," Intech, 2010, pp. 283-286 [retrieved from: www.intechopen.com/books/fault-detection-and-diagnosis-for-in-vehicle-networks].

Walter et al., "The smart car seat: personalized monitoring of vital signs in automotive applications." Personal and Ubiquitous Computing, Oct. 2011, vol. 15, No. 7, pp. 707-715.

Wolf et al., "Design, Implementation, and Evaluation of a Vehicular Hardware Security Module," ICISC'11 Proceedings of the 14th Int'l Conf. Information Security & Cryptology, Springer-Verlag Berlin, Heidelberg, 2011, pp. 302-318.

International Search Report and Written Opinion for PCT Application No. PCT/US2017/041061, dated Sep. 14, 2017, 8 pages.

Official Action for U.S. Appl. No. 15/396,616, dated Aug. 24, 2017, 8 pages.

Notice of Allowance for U.S. Appl. No. 15/396,616, dated Jan. 24, 2018, 9 pages.

* cited by examiner




Fig. 1




Fig. 2

300	310A	310B	310C	310D	310E	310F	310G	310H	310I
	Charging Type	Compatible Vehicle Charging Panel Types	Compatible Vehicle Storage Units	Available Automation Level	Charging Service Status	Charge Rate	Cost	Other	Shielding
310J	Station: manual	Roof, Side	x, z	Low	Up	Low	\$100	A, B, C	On
310K	Station: manual	Roof, Side	x, z	Low	Up	Medium	\$150	A, C	On
310L	Station: manual	Roof, Side	x, z	Low	Up	High	\$400	A, B, C	On
310M	Station: robotic	Roof, Side	x, z	Medium	Down	Medium	\$150	A, B, D	On
310N	Station: robotic	Roof, Side	x, z	High	Down	High	\$500	B, D	On
310O	Station: robotic	Roof, Side	x, z	High	Down	High	\$500	B, C	On
310P	Roadway	Side, Lower	x, z	Low	Up	Low	\$50	A, C, E	Off
310Q	Roadway	Side, Lower	x, z	Medium	Up	Low	\$100	A, C, E	Off
310R	Roadway	Side, Lower	x, z	Medium	Up	Low	\$100	A, C, E	Off
310S	Emergency: truck	Roof, Side, Lower	x, y	Low	Up	Low	\$150	A, B	Off
310T	Emergency: truck	Roof, Side, Lower	x, y	Medium	Up	Medium	\$200	A, B	Off
310U	Emergency: truck	Roof, Side, Lower	x, y	Medium	Up	High	\$500	A, D	Off
310V	Emergency: UAV	Roof	x	Medium	Down	Medium	\$500	A, B, C	Off
310W	Emergency: UAV	Roof	x	High	Down	High	\$800	B	Off
310X	Emergency: UAV	Roof	x	High	Down	High	\$800	B	Off
310Y	Overhead	Roof	x, y	Low	Up	Low	\$150	B, D	Off
310Z	Overhead	Roof	x, y	Medium	Up	Low	\$200	B, C	Off
310AA	Overhead	Roof	x, y	Medium	Up	Low	\$200	B, C	Off

Fig. 3




Fig. 4A




Fig. 4B




Fig. 4C




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19








Fig. 20





**Fig. 23**




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28

2900

2912a

2912b

2912c

2912d

2904

2908

Financial Information

Passenger Financial Information

User Preferences

Event Preferences

Enter Financial Information: ☐ Yes ☒ No

2920

2928a

2928b

2928c

2928d

2928e

2928f

2928g

2928h

2928i

2928j

2928k

2928l

2928m

2928n

2928o

2928p

2928q

2928r

2928s

2928t

2928u

2928v

2928w

2928x

2928y

2928z

2929a

2929b

2929c

2929d

2929e

2929f

2929g

2929h

2929i

2929j

2929k

2929l

2929m

2929n

2929o

2929p

2929q

2929r

2929s

2929t

2929u

2929v

2929w

2929x

2929y

2929z

2930a

2930b

2930c

2930d

2930e

2930f

2930g

2930h

2930i

2930j

2930k

2930l

2930m

2930n

2930o

2930p

2930q

2930r

2930s

2930t

2930u

2930v

2930w

2930x

2930y

2930z

2931a

2931b

2931c

2931d

2931e

2931f

2931g

2931h

2931i

2931j

2931k

2931l

2931m

2931n

2931o

2931p

2931q

2931r

2931s

2931t

2931u

2931v

2931w

2931x

2931y

2931z

2932a

2932b

2932c

2932d

2932e

2932f

2932g

2932h

2932i

2932j

2932k

2932l

2932m

2932n

2932o

2932p

2932q

2932r

2932s

2932t

2932u

2932v

2932w

2932x

2932y

2932z

2933a

2933b

2933c

2933d

2933e

2933f

2933g

2933h

2933i

2933j

2933k

2933l

2933m

2933n

2933o

2933p

2933q

2933r

2933s

2933t

2933u

2933v

2933w

2933x

2933y

2933z

2934a

2934b

2934c

2934d

2934e

2934f

2934g

2934h

2934i

2934j

2934k

2934l

2934m

2934n

2934o

2934p

2934q

2934r

2934s

2934t

2934u

2934v

2934w

2934x

2934y

2934z

2935a

2935b

2935c

2935d

2935e

2935f

2935g

2935h

2935i

2935j

2935k

2935l

2935m

2935n

2935o

2935p

2935q

2935r

2935s

2935t

2935u

2935v

2935w

2935x

2935y

2935z

2936a

2936b

2936c

2936d

2936e

2936f

2936g

2936h

2936i

2936j

2936k

2936l

2936m

2936n

2936o

2936p

2936q

2936r

2936s

2936t

2936u

2936v

2936w

2936x

2936y

2936z

2937a

2937b

2937c

2937d

2937e

2937f

2937g

2937h

2937i

2937j

2937k

2937l

2937m

2937n

2937o

2937p

2937q

2937r

2937s

2937t

2937u

2937v

2937w

2937x

2937y

2937z

2938a

2938b

2938c

2938d

2938e

2938f

2938g

2938h

2938i

2938j

2938k

2938l

2938m

2938n

2938o

2938p

2938q

2938r

2938s

2938t

2938u

2938v

2938w

2938x

2938y

2938z

2939a

2939b

2939c

2939d

2939e

2939f

2939g

2939h

2939i

2939j

2939k

2939l

2939m

2939n

2939o

2939p

2939q

2939r

2939s

2939t

2939u

2939v

2939w

2939x

2939y

2939z

2940a

2940b

2940c

2940d

2940e

2940f

2940g

2940h

2940i

2940j

2940k

2940l

2940m

2940n

2940o

2940p

2940q

2940r

2940s

2940t

2940u

2940v

2940w

2940x

2940y

2940z

2941a

2941b

2941c

2941d

2941e

2941f

2941g

2941h

2941i

2941j

2941k

2941l

2941m

2941n

2941o

2941p

2941q

2941r

2941s

2941t

2941u

2941v

2941w

2941x

2941y

2941z

2942a

2942b

2942c

2942d

2942e

2942f

2942g

2942h

2942i

2942j

2942k

2942l

2942m

2942n

2942o

2942p

2942q

2942r

2942s

2942t

2942u

2942v

2942w

2942x

2942y

2942z

2943a

2943b

2943c

2943d

2943e

2943f

2943g

2943h

2943i

2943j

2943k

2943l

2943m

2943n

2943o

2943p

2943q

2943r

2943s

2943t

2943u

2943v

2943w

2943x

2943y

2943z

2944a

2944b

2944c

2944d

2944e

2944f

2944g

2944h

2944i

2944j

2944k

2944l

2944m

2944n

2944o

2944p

2944q

2944r

2944s

2944t

2944u

2944v

2944w

2944x

2944y

2944z

2945a

2945b

2945c

2945d

2945e

2945f

2945g

2945h

2945i

2945j

2945k

2945l

2945m

2945n

2945o

2945p

2945q

2945r

2945s

2945t

2945u

2945v

2945w

2945x

2945y

2945z

2946a

2946b

2946c

2946d

2946e

2946f

2946g

2946h

2946i

2946j

2946k

2946l

2946m

2946n

2946o

2946p

2946q

2946r

2946s

2946t

2946u

2946v

2946w

2946x

2946y

2946z

2947a

2947b

2947c

2947d

2947e

2947f

2947g

2947h

2947i

2947j

2947k

2947l

2947m

2947n

2947o

2947p

2947q

2947r

2947s

2947t

2947u

2947v

2947w

2947x

2947y

2947z

2948a

2948b

2948c

2948d

2948e

2948f

2948g

2948h

2948i

2948j

2948k

2948l

2948m

2948n

2948o

2948p

2948q

2948r

2948s

2948t

2948u

2948v

2948w

2948x

2948y

2948z

2949a

2949b

2949c

2949d

2949e

2949f

2949g

2949h

2949i

2949j

2949k

2949l

2949m

2949n

2949o

2949p

2949q

2949r

2949s

2949t

2949u

2949v

2949w

2949x

2949y

2949z

2950a

2950b

2950c

2950d

2950e

2950f

2950g

2950h

2950i

2950j

2950k

2950l

2950m

2950n

2950o

2950p

2950q

2950r

2950s

2950t

2950u

2950v

2950w

2950x

2950y

2950z

2951a

2951b

2951c

2951d

2951e

2951f

2951g

2951h

2951i

2951j

2951k

2951l

2951m

2951n

2951o

2951p

2951q

2951r

2951s

2951t

2951u

2951v

2951w

2951x

2951y

2951z

2952a

2952b

2952c

2952d

2952e

2952f

2952g

2952h

2952i

2952j

2952k

2952l

2952m

2952n

2952o

2952p

2952q

2952r

2952s

2952t

2952u

2952v

2952w

2952x

2952y

2952z

2953a

2953b

2953c

2953d

2953e

2953f

2953g

2953h

2953i

2953j

2953k

2953l

2953m

2953n

2953o

2953p

2953q

2953r

2953s

2953t

2953u

2953v

2953w

2953x

2953y

2953z

2954a

2954b

2954c

2954d

2954e

2954f

2954g

2954h

2954i

2954j

2954k

2954l

2954m

2954n

2954o

2954p

2954q

2954r

2954s

2954t

2954u

2954v

2954w

2954x

2954y

2954z

2955a

2955b

2955c

2955d

2955e

2955f

2955g

2955h

2955i

2955j

2955k

2955l

2955m

2955n

2955o

2955p

2955q

2955r

2955s

2955t

2955u

2955v

2955w

2955x

2955y

2955z

2956a

2956b

2956c

2956d

2956e

2956f

2956g

2956h

2956i

2956j

2956k

2956l

2956m

2956n

2956o

2956p

2956q

2956r

2956s

2956t

2956u

2956v

2956w

2956x

2956y

2956z

2957a

2957b

2957c

2957d

2957e

2957f

2957g

2957h

2957i

2957j

2957k

2957l

2957m

2957n

2957o

2957p

2957q

2957r

2957s

2957t

2957u

2957v

2957w

2957x

2957y

2957z

2958a

2958b

2958c

2958d

2958e

2958f

2958g

2958h

2958i

2958j

2958k

2958l

2958m

2958n

2958o

2958p

2958q

2958r

2958s

2958t

2958u

2958v

2958w

2958x

2958y

2958z

2959a

2959b

2959c

2959d

2959e

2959f

2959g

2959h

2959i

2959j

2959k

2959l

2959m

2959n

2959o

2959p

2959q

2959r

2959s

2959t

2959u

2959v

2959w

2959x

2959y

2959z

2960a

2960b

2960c

2960d

2960e

2960f

2960g

2960h

2960i

2960j

2960k

2960l

2960m

2960n

2960o

2960p

2960q

2960r

2960s

2960t

2960u

2960v

2960w

2960x

2960y

2960z

2961a

2961b

2961c

2961d

2961e

2961f

2961g

2961h

2961i

2961j

2961k

2961l

2961m

2961n

2961o

2961p

2961q

2961r

2961s

2961t

2961u

2961v

2961w

2961x

2961y

2961z

2962a

2962b

2962c

2962d

2962e

2962f

2962g

2962h

2962i

2962j

2962k

2962l

2962m

2962n

2962o

2962p

2962q

2962r

2962s

2962t

2962u

2962v

2962w

2962x

2962y

2962z

2963a

2963b

2963c

2963d

2963e

2963f

2963g

2963h

2963i

2963j

2963k

2963l

2963m

2963n

2963o

2963p

2963q

2963r

2963s

2963t

2963u

2963v

2963w

2963x

2963y

2963z

2964a

2964b

2964c

2964d

2964e

2964f

2964g

2964h

2964i

2964j

2964k

2964l

2964m

2964n

2964o

2964p

2964q

2964r

2964s

2964t

2964u

2964v

2964w

2964x

2964y

2964z

2965a

2965b

2965c

2965d

2965e

2965f

2965g

2965h

2965i

2965j

2965k

2965l

2965m

2965n

2965o

2965p

2965q

2965r

2965s

2965t

2965u

2965v

2965w

2965x

2965y

2965z

2966a

2966b

2966c

2966d

2966e

2966f

2966g

2966h

2966i

2966j

2966k

2966l

2966m

2966n

2966o

2966p

2966q

2966r

2966s

2966t

2966u

2966v

2966w

2966x

2966y

2966z

2967a

2967b

2967c

2967d

2967e

2967f

2967g

2967h

2967i

2967j

2967k

2967l

2967m

2967n

2967o

2967p

2967q

2967r

2967s

2967t

2967u

2967v

2967w

2967x

2967y

2967z

2968a

2968b

2968c

2968d

2968e

2968f

2968g

2968h

2968i

2968j

2968k

2968l

2968m

2968n

2968o

2968p

2968q

2968r

2968s

2968t

2968u

2968v

2968w

2968x

2968y

2968z

2969a

2969b

2969c

2969d

2969e

2969f

2969g

2969h

2969i

2969j

2969k

2969l

2969m

2969n

2969o

2969p

2969q




Fig. 30A




Fig. 30B




Fig. 31




Fig. 32




Fig. 33




Fig. 34




Fig. 35




Fig. 36A




Fig. 36B




Fig. 37





Fig. 38






Fig. 40









Fig. 41


**Fig. 42**


**Fig. 43**


**Fig. 44**


**Fig. 45**


**Fig. 46**


**Fig. 47**


**Fig. 48**

**Fig. 49**

**Fig. 50**

**Fig. 51**

**Fig. 52**

**Fig. 53**




Fig. 54A




Fig. 54B




Fig. 54C




Fig. 55




Fig. 56

1

BIFURCATED COMMUNICATIONS TO A THIRD PARTY THROUGH A VEHICLE

CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims the benefits of and priority, under 35 U.S.C. § 119(e), to U.S. Provisional Application Ser. No. 62/359,563, filed on Jul. 7, 2016 and U.S. Provisional Application Ser. No. 62/378,348, filed on Aug. 23, 2016, both entitled "Next Generation Vehicle." The entire disclosures of the applications listed above are hereby incorporated by reference, in their entirety, for all that they teach and for all purposes.

FIELD

The present disclosure is generally directed to vehicle systems, in particular, toward semi-autonomous or fully autonomous vehicles.

BACKGROUND

In recent years, transportation methods have changed substantially. This change is due in part to a concern over the limited availability of natural resources, a proliferation in personal technology, and a societal shift to adopt more environmentally and user-friendly transportation solutions. These considerations have encouraged the development of a number of new features on vehicles that allow the user to concentrate on other tasks or on driving.

While these vehicles appear to be new they are generally implemented as a number of traditional subsystems that are executed with a communication system. In fact, the design and construction of the vehicles is limited to operations that can be completed by drivers. Among other things, these limitations fail to take advantage of the autonomous nature of vehicles.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a vehicle in accordance with embodiments of the present disclosure;

FIG. 2 shows a vehicle in an environment in accordance with embodiments of the present disclosure;

FIG. 3 is a diagram of an embodiment of a data structure for storing information about a vehicle in an environment;

FIG. 4A shows a vehicle in a user environment in accordance with embodiments of the present disclosure;

FIG. 4B shows a vehicle in a fleet management and automated operation environment in accordance with embodiments of the present disclosure;

FIG. 4C shows an embodiment of the instrument panel of the vehicle according to one embodiment of the present disclosure;

FIG. 5 shows charging areas associated with an environment in accordance with embodiments of the present disclosure;

FIG. 6 shows a vehicle in a roadway charging environment in accordance with embodiments of the present disclosure;

FIG. 7 shows a vehicle in a robotic charging station environment in accordance with another embodiment of the present disclosure;

FIG. 8 shows a vehicle in an overhead charging environment in accordance with another embodiment of the present disclosure;

2

FIG. 9 shows a vehicle in a roadway environment comprising roadway vehicles in accordance with another embodiment of the present disclosure;

FIG. 10 shows a vehicle in an aerial vehicle charging environment in accordance with another embodiment of the present disclosure;

FIG. 11 shows a vehicle in an emergency charging environment in accordance with embodiments of the present disclosure;

FIG. 12 is a perspective view of a vehicle in accordance with embodiments of the present disclosure;

FIG. 13 is a plan view of a vehicle in accordance with at least some embodiments of the present disclosure;

FIG. 14 is a plan view of a vehicle in accordance with embodiments of the present disclosure;

FIG. 15 is a block diagram of an embodiment of an electrical system of the vehicle;

FIG. 16 is a block diagram of an embodiment of a power generation unit associated with the electrical system of the vehicle;

FIG. 17 is a block diagram of an embodiment of power storage associated with the electrical system of the vehicle;

FIG. 18 is a block diagram of an embodiment of loads associated with the electrical system of the vehicle;

FIG. 19 is a block diagram of an exemplary embodiment of a communications subsystem of the vehicle;

FIG. 20 is another view of a vehicle including communication interfaces positioned on the vehicle;

FIG. 21 is a block diagram of a communication interface for conducting secure communications with the vehicle;

FIG. 22A is a two-dimensional diagram of a physical interconnection between the vehicle and a receiving port;

FIG. 22B is another two-dimensional diagram of a physical interconnection between the vehicle and a receiving port;

FIG. 23 is a block diagram of hardware and/or software components that may interface a restored in memory for conducting secure communications with the vehicle;

FIG. 24 is a block diagram of data that may be stored in the vehicle;

FIG. 25 is a block diagram of data that may be communicated between the vehicle and a third party;

FIG. 26 is a block diagram of data used to do automatic communications between the vehicle and a third party;

FIG. 27 is a communication diagram between a user in a vehicle including a dongle;

FIG. 28 is a communication diagram between a vehicle and a second party;

FIG. 29 is a user interface provided within the vehicle;

FIG. 30A is another user interface provided within the vehicle;

FIG. 30B is another user interface provided within the vehicle;

FIG. 31 is another user interface provided within the vehicle;

FIG. 32 is another user interface provided within the vehicle;

FIG. 33 is another user interface provided within the vehicle;

FIG. 34 is another user interface provided within the vehicle;

FIG. 35 is another user interface provided within the vehicle;

FIG. 36A is another user interface provided within the vehicle;

FIG. 36B is another user interface provided within the vehicle;

FIG. 37 is another user interface provided within the vehicle;

FIG. 38 is another user interface provided within the vehicle;

FIG. 39 is another user interface provided within the vehicle;

FIG. 40 is another user interface provided within the vehicle;

FIG. 41 is another user interface provided within the vehicle;

FIG. 42 is another user interface provided within the vehicle;

FIG. 43 is a flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 44 is another flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 45 is another flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 46 is another flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 47 is another flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 48 is another flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 49 is another flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 50 is another flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 51 is another flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 52 is another flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 53 is another flow diagram of an embodiment of a method for providing secure communications with a vehicle;

FIG. 54A is a block diagram of vehicle systems;

FIG. 54B is a block diagram of a vehicle sensor system;

FIG. 54C is a block diagram of a navigation system;

FIG. 55 is a diagram of a computing environment for the vehicle; and

FIG. 56 is a block diagram of a computing system of the vehicle.

DETAILED DESCRIPTION

Embodiments of the present disclosure will be described in connection with a vehicle, and in accordance with one exemplary embodiment an electric vehicle and/or hybrid-electric vehicle and associated systems.

With attention to FIGS. 1-11, embodiments of the electric vehicle system 10 and method of use are depicted.

Referring to FIG. 1, the electric vehicle system comprises electric vehicle 100. The electric vehicle 100 comprises vehicle front 110, vehicle aft 120, vehicle roof 130, vehicle side 160, vehicle undercarriage 140 and vehicle interior 150.

Referring to FIG. 2, the vehicle 100 is depicted in a plurality of exemplary environments. The vehicle 100 may operate in any one or more of the depicted environments in any combination. Other embodiments are possible but are not depicted in FIG. 2. Generally, the vehicle 100 may operate in environments which enable charging of the vehicle 100 and/or operation of the vehicle 100. More specifically, the vehicle 100 may receive a charge via one or more means comprising emergency charging vehicle system 270, aerial vehicle charging system 280, roadway system 250, robotic charging system 254 and overhead charging system 258. The vehicle 100 may interact and/or operate in an environment comprising one or more other roadway

vehicles 260. The vehicle 100 may engage with elements within the vehicle 100 comprising vehicle driver 220, vehicle passengers 220 and vehicle database 210. In one embodiment, vehicle database 210 does not physically reside in the vehicle 100 but is instead accessed remotely, e.g. by wireless communication, and resides in another location such as a residence or business location. Vehicle 100 may operate autonomously and/or semi-autonomously in an autonomous environment 290 (here, depicted as a roadway environment presenting a roadway obstacle of which the vehicle 100 autonomously identifies and steers the vehicle 100 clear of the obstacle). Furthermore, the vehicle 100 may engage with a remote operator system 240, which may provide fleet management instructions or control.

FIG. 3 is a diagram of an embodiment of a data structure 300 for storing information about a vehicle 100 in an environment. The data structure may be stored in vehicle database 210. Generally, data structure 300 identifies operational data associated with charging types 310A. The data structures 300 may be accessible by a vehicle controller. The data contained in data structure 300 enables, among other things, for the vehicle 100 to receive a charge from a given charging type.

Exemplar data comprises charging type 310A comprising a manual charging station 310J, robotic charging station 310K such as robotic charging system 254, a roadway charging system 310L such as those of roadway system 250, an emergency charging system 310M such as that of emergency charging vehicle system 270, an emergency charging system 310N such as that of aerial vehicle charging system 280, and overhead charging type 310O such as that of overhead charging system 258.

Compatible vehicle charging panel types 310B comprise locations on vehicle 100 wherein charging may be received, such as vehicle roof 130, vehicle side 160 and vehicle lower or undercarriage 140. Compatible vehicle storage units 310C data indicates storage units types that may receive power from a given charging type 310A. Available automation level 310D data indicates the degree of automation available for a given charging type; a high level may indicate full automation, allowing the vehicle driver 220 and/or vehicle passengers 230 to not involve themselves in charging operations, while a low level of automation may require the driver 220 and/or occupant 230 to manipulate/position a vehicle charging device to engage with a particular charging type 310A to receive charging. Charging status 310E indicates whether a charging type 310A is available for charging (i.e. is “up”) or is unavailable for charging (i.e. is “down”). Charge rate 310F provides a relative value for time to charge, while Cost 310G indicates the cost to vehicle 100 to receive a given charge. The Other data element 310H may provide additional data relevant to a given charging type 310A, such as a recommended separation distance between a vehicle charging plate and the charging source. The Shielding data element 310I indicates if electromagnetic shielding is recommended for a given charging type 310A and/or charging configuration. Further data fields 310P, 310Q are possible.

FIG. 4A depicts the vehicle 100 in a user environment comprising vehicle database 210, vehicle driver 220 and vehicle passengers 230. Vehicle 100 further comprises vehicle instrument panel 400 to facilitate or enable interactions with one or more of vehicle database 210, vehicle driver 220 and vehicle passengers 230. In one embodiment, driver 210 interacts with instrument panel 400 to query database 210 so as to locate available charging options and to consider or weigh associated terms and conditions of the

5

charging options. Once a charging option is selected, driver **210** may engage or operate a manual control device (e.g., a joystick) to position a vehicle charging receiver panel so as to receive a charge.

FIG. 4B depicts the vehicle **100** in a user environment comprising a remote operator system **240** and an autonomous driving environment **290**. In the remote operator system **240** environment, a fleet of electric vehicles **100** (or mixture of electric and non-electric vehicles) is managed and/or controlled remotely. For example, a human operator may dictate that only certain types of charging types are to be used, or only those charging types below a certain price point are to be used. The remote operator system **240** may comprise a database comprising operational data, such as fleet-wide operational data. In another example, the vehicle **100** may operate in an autonomous driving environment **290** wherein the vehicle **100** is operated with some degree of autonomy, ranging from complete autonomous operation to semi-automation wherein only specific driving parameters (e.g., speed control or obstacle avoidance) are maintained or controlled autonomously. In FIG. 4B, autonomous driving environment **290** depicts an oil slick roadway hazard that triggers that triggers the vehicle **100**, while in an automated obstacle avoidance mode, to automatically steer around the roadway hazard.

FIG. 4C shows one embodiment of the vehicle instrument panel **400** of vehicle **100**. Instrument panel **400** of vehicle **100** comprises steering wheel **410**, vehicle operational display **420** (which would provide basic driving data such as speed), one or more auxiliary displays **424** (which may display, e.g., entertainment applications such as music or radio selections), heads-up display **434** (which may provide, e.g., guidance information such as route to destination, or obstacle warning information to warn of a potential collision, or some or all primary vehicle operational data such as speed), power management display **428** (which may provide, e.g., data as to electric power levels of vehicle **100**), and charging manual controller **432** (which provides a physical input, e.g. a joystick, to manual maneuver, e.g., a vehicle charging plate to a desired separation distance). One or more of displays of instrument panel **400** may be touch-screen displays. One or more displays of instrument panel **400** may be mobile devices and/or applications residing on a mobile device such as a smart phone.

FIG. 5 depicts a charging environment of a roadway charging system **250**. The charging area may be in the roadway **504**, on the roadway **504**, or otherwise adjacent to the roadway **504**, and/or combinations thereof. This static charging area **520B** may allow a charge to be transferred even while the electrical vehicle **100** is moving. For example, the static charging area **520B** may include a charging transmitter (e.g., conductor, etc.) that provides a transfer of energy when in a suitable range of a receiving unit (e.g., an inductor pick up, etc.). In this example, the receiving unit may be a part of the charging panel associated with the electrical vehicle **100**.

The static charging areas **520A**, **520B** may be positioned a static area such as a designated spot, pad, parking space **540A**, **540B**, traffic controlled space (e.g., an area adjacent to a stop sign, traffic light, gate, etc.), portion of a building, portion of a structure, etc., and/or combinations thereof. Some static charging areas may require that the electric vehicle **100** is stationary before a charge, or electrical energy transfer, is initiated. The charging of vehicle **100** may occur by any of several means comprising a plug or other protruding feature. The power source **516A**, **516B** may include a receptacle or other receiving feature, and/or vice versa.

6

The charging area may be a moving charging area **520C**. Moving charging areas **520C** may include charging areas associated with one or more portions of a vehicle, a robotic charging device, a tracked charging device, a rail charging device, etc., and/or combinations thereof. In a moving charging area **520C**, the electrical vehicle **100** may be configured to receive a charge, via a charging panel, while the vehicle **100** is moving and/or while the vehicle **100** is stationary. In some embodiments, the electrical vehicle **100** may synchronize to move at the same speed, acceleration, and/or path as the moving charging area **520C**. In one embodiment, the moving charging area **520C** may synchronize to move at the same speed, acceleration, and/or path as the electrical vehicle **100**. In any event, the synchronization may be based on an exchange of information communicated across a communications channel between the electric vehicle **100** and the charging area **520C**. Additionally or alternatively, the synchronization may be based on information associated with a movement of the electric vehicle **100** and/or the moving charging area **520C**. In some embodiments, the moving charging area **520C** may be configured to move along a direction or path **532** from an origin position to a destination position **520C'**.

In some embodiments, a transformer may be included to convert a power setting associated with a main power supply to a power supply used by the charging areas **520A-C**. For example, the transformer may increase or decrease a voltage associated with power supplied via one or more power transmission lines.

Referring to FIG. 6, a vehicle **100** is shown in a charging environment in accordance with embodiments of the present disclosure. The system **10** comprises a vehicle **100**, an electrical storage unit **612**, an external power source **516** able to provide a charge to the vehicle **100**, a charging panel **608** mounted on the vehicle **100** and in electrical communication with the electrical storage unit **612**, and a vehicle charging panel controller **610**. The charging panel controller **610** may determine if the electrical storage unit requires charging and if conditions allow for deployment of a charging panel. The vehicle charging panel **608** may operate in at least a retracted state and a deployed state (**608** and **608'** as shown in FIG. 6), and is movable by way of an armature.

The charging panel controller **610** may receive signals from vehicle sensors **626** to determine, for example, if a hazard is present in the path of the vehicle **100** such that deployment of the vehicle charging panel **608** is inadvisable. The charging panel controller **610** may also query vehicle database **210** comprising data structures **300** to establish other required conditions for deployment. For example, the database may provide that a particular roadway does not provide a charging service or the charging service is inactive, wherein the charging panel **108** would not be deployed.

The power source **516** may include at least one electrical transmission line **624** and at least one power transmitter or charging area **520**. During a charge, the charging panel **608** may serve to transfer energy from the power source **516** to at least one energy storage unit **612** (e.g., battery, capacitor, power cell, etc.) of the electric vehicle **100**.

FIG. 7 shows a vehicle **100** in a charging station environment **254** in accordance with another embodiment of the present disclosure. Generally, in this embodiment of the invention, charging occurs from a robotic unit **700**.

Robotic charging unit **700** comprises one or more robotic unit arms **704**, at least one robotic unit arm **704** interconnected with charging plate **520**. The one or more robotic unit arms **704** maneuver charging plate **520** relative to charging panel **608** of vehicle **100**. Charging plate **520** is positioned

to a desired or selectable separation distance, as assisted by a separation distance sensor disposed on charging plate **520**. Charging plate **520** may remain at a finite separation distance from charging panel **608**, or may directly contact charging panel (i.e. such that separation distance is zero). Charging may be by induction. In alternative embodiments, separation distance sensor is alternatively or additionally disposed on robotic arm **704**. Vehicle **100** receives charging via charging panel **608** which in turn charges energy storage unit **612**. Charging panel controller **610** is in communication with energy storage unit **612**, charging panel **608**, vehicle database **300**, charge provider controller **622**, and/or any one of elements of instrument panel **400**.

Robotic unit further comprises, is in communication with and/or is interconnected with charge provider controller **622**, power source **516** and a robotic unit database. Power source **516** supplies power, such as electrical power, to charge plate **520** to enable charging of vehicle **100** via charging panel **608**. Controller **622** maneuvers or operates robotic unit **704**, either directly and/or completely or with assistance from a remote user, such as a driver or passenger in vehicle **100** by way of, in one embodiment, charging manual controller **432**.

FIG. **8** shows a vehicle **100** in an overhead charging environment in accordance with another embodiment of the present disclosure. Generally, in this embodiment of the invention, charging occurs from an overhead towered charging system **258**, similar to existing commuter rail systems. Such an overhead towered system **258** may be easier to build and repair compared to in-roadway systems. Generally, the invention includes a specially-designed overhead roadway charging system comprising an overhead charging cable or first wire **814** that is configured to engage an overhead contact **824** which provides charge to charging panel **608** which provides charge to vehicle energy storage unit **612**. The overhead towered charging system **258** may further comprise second wire **818** to provide stability and structural strength to the roadway charging system **800**. The first wire **814** and second wire **818** are strung between towers **810**.

The overhead charging cable or first wire **814** is analogous to a contact wire used to provide charging to electric trains or other vehicles. An external source provides or supplies electrical power to the first wire **814**. The charge provider comprises an energy source i.e. a provider battery and a provider charge circuit or controller in communication with the provider battery. The overhead charging cable or first wire **814** engages the overhead contact **824** which is in electrical communication with charge receiver panel **108**. The overhead contact **824** may comprise any known means to connect to overhead electrical power cables, such as a pantograph **820**, a bow collector, a trolley pole or any means known to those skilled in the art. Further disclosure regarding electrical power or energy transfer via overhead systems is found in US Pat. Publ. No. 2013/0105264 to Ruth entitled "Pantograph Assembly," the entire contents of which are incorporated by reference for all purposes. In one embodiment, the charging of vehicle **100** by overhead charging system **800** via overhead contact **824** is by any means known to those skilled in the art, to include those described in the above-referenced US Pat. Publ. No. 2013/0105264 to Ruth.

The overhead contact **824** presses against the underside of the lowest overhead wire of the overhead charging system, i.e. the overhead charging cable or first wire **814**, aka the contact wire. The overhead contact **824** may be electrically conductive. Alternatively or additionally, the overhead contact **824** may be adapted to receive electrical power from overhead charging cable or first wire **814** by inductive charging.

In one embodiment, the receipt and/or control of the energy provided via overhead contact **824** (as connected to the energy storage unit **612**) is provided by receiver charge circuit or charging panel controller **110**.

Overhead contact **824** and/or charging panel **608** may be located anywhere on vehicle **100**, to include, for example, the roof, side panel, trunk, hood, front or rear bumper of the charge receiver **100** vehicle, as long as the overhead contact **824** may engage the overhead charging cable or first wire **814**. Charging panel **108** may be stationary (e.g. disposed on the roof of vehicle **100**) or may be moveable, e.g. moveable with the pantograph **820**. Pantograph **820** may be positioned in at least two states comprising retracted and extended. In the extended state pantograph **820** engages first wire **814** by way of the overhead contact **824**. In the retracted state, pantograph **820** may typically reside flush with the roof of vehicle **100** and extend only when required for charging. Control of the charging and/or positioning of the charging plate **608**, pantograph **820** and/or overhead contact **824** may be manual, automatic or semi-automatic (such as via controller **610**); said control may be performed through a GUI engaged by driver or occupant of receiving vehicle **100** and/or driver or occupant of charging vehicle.

FIG. **9** shows a vehicle in a roadway environment comprising roadway vehicles **260** in accordance with another embodiment of the present disclosure. Roadway vehicles **260** comprise roadway passive vehicles **910** and roadway active vehicles **920**. Roadway passive vehicles **910** comprise vehicles that are operating on the roadway of vehicle **100** but do not cooperatively or actively engage with vehicle **100**. Stated another way, roadway passive vehicles **910** are simply other vehicles operating on the roadway with the vehicle **100** and must be, among other things, avoided (e.g., to include when vehicle **100** is operating in an autonomous or semi-autonomous manner). In contrast, roadway active vehicles **920** comprise vehicles that are operating on the roadway of vehicle **100** and have the capability to, or actually are, actively engaging with vehicle **100**. For example, the emergency charging vehicle system **270** is a roadway active vehicle **920** in that it may cooperate or engage with vehicle **100** to provide charging. In some embodiments, vehicle **100** may exchange data with a roadway active vehicle **920** such as, for example, data regarding charging types available to the roadway active vehicle **920**.

FIG. **10** shows a vehicle in an aerial vehicle charging environment in accordance with another embodiment of the present disclosure. Generally, this embodiment involves an aerial vehicle ("AV"), such as an Unmanned Aerial Vehicle (UAV), flying over or near a vehicle to provide a charge. The UAV may also land on the car to provide an emergency (or routine) charge. Such a charging scheme may be particularly suited for operations in remote areas, in high traffic situations, and/or when the car is moving. The AV may be a specially-designed UAV, aka RPV or drone, with a charging panel that can extend from the AV to provide a charge. The AV may include a battery pack and a charging circuit to deliver a charge to the vehicle. The AV may be a manned aerial vehicle, such as a piloted general aviation aircraft, such as a Cessna 172.

With reference to FIG. **10**, an exemplar embodiment of a vehicle charging system **100** comprising a charge provider configured as an aerial vehicle **280**, the aerial vehicle **280** comprising a power source **516** and charge provider controller **622**. The AV may be semi-autonomous or fully autonomous. The AV may have a remote pilot/operator providing control inputs. The power source **516** is configured to provide a charge to a charging panel **608** of vehicle

100. The power source 516 is in communication with the charge provider controller 622. The aerial vehicle 280 provides a tether 1010 to deploy or extend charging plate 520 near to charging panel 608. The tether 1010 may comprise a chain, rope, rigid or semi-rigid tow bar or any means to position charging plate 520 near charging panel 608. For example, tether 1010 may be similar to a refueling probe used by airborne tanker aircraft when refueling another aircraft.

In one embodiment, the charging plate 520 is not in physical interconnection to AV 280, that is, there is no tether 1010. In this embodiment, the charging plate 520 is positioned and controlled by AV 280 by way of a controller on AV 280 or in communication with AV 280.

In one embodiment, the charging plate 520 position and/or characteristics (e.g. charging power level, flying separation distance, physical engagement on/off) are controlled by vehicle 100 and/or a user in or driver of vehicle 100.

Charge or power output of power source 516 is provided or transmitted to charger plate 620 by way of a charging cable or wire, which may be integral to tether 1010. In one embodiment, the charging cable is non-structural, that is, it provides zero or little structural support to the connection between AV 280 and charger plate 520.

Charging panel 608 of vehicle 100 receives power from charger plate 520. Charging panel 608 and charger plate 520 may be in direct physical contact (termed a “contact” charger configuration) or not in direct physical contact (termed a “flyer” charger configuration), but must be at or below a threshold (separation) distance to enable charging, such as by induction. Energy transfer or charging from the charger plate 520 to the charging panel 608 is inductive charging (i.e. use of an EM field to transfer energy between two objects). The charging panel 608 provides received power to energy storage unit 612 by way of charging panel controller 610. Charging panel controller 610 is in communication with vehicle database 210, vehicle database 210 comprising an AV charging data structure.

Charging panel 508 may be located anywhere on vehicle 100, to include, for example, the roof, side panel, trunk, hood, front or rear bumper and wheel hub of vehicle 100. Charging panel 608 is mounted on the roof of vehicle 100 in the embodiment of FIG. 10. In some embodiments, charging panel 608 may be deployable, i.e. may extend or deploy only when charging is needed. For example, charging panel 608 may typically reside flush with the roof of vehicle 100 and extend when required for charging. Similarly, charger plate 520 may, in one embodiment, not be connected to AV 280 by way of tether 1010 and may instead be mounted directly on the AV 280, to include, for example, the wing, empennage, undercarriage to include landing gear, and may be deployable or extendable when required. Tether 1010 may be configured to maneuver charging plate 520 to any position on vehicle 100 so as to enable charging. In one embodiment, the AV 280 may land on the vehicle 100 so as to enable charging through direct contact (i.e. the aforementioned contact charging configuration) between the charging plate 520 and the charging panel 608 of vehicle 100. Charging may occur while both AV 280 and vehicle 100 are moving, while both vehicle 100 and AV 280 are not moving (i.e., vehicle 100 is parked and AV 280 lands on top of vehicle 100), or while vehicle 100 is parked and AV 280 is hovering or circling above. Control of the charging and/or positioning of the charging plate 520 may be manual, automatic or semi-automatic; said control may be performed through a

GUI engaged by driver or occupant of receiving vehicle 100 and/or driver or occupant of charging AV 280.

FIG. 11 is an exemplar embodiment of a vehicle emergency charging system comprising an emergency charging vehicle 270 and charge receiver vehicle 100 is disclosed. The emergency charging vehicle 270 is a road vehicle, such as a pick-up truck, as shown in FIG. 11. The emergency charging vehicle 270 is configured to provide a charge to a charge receiver vehicle 100, such as an automobile. The emergency charging vehicle 270 comprises an energy source i.e. a charging power source 516 and a charge provider controller 622 in communication with the charging power source 516. The emergency charging vehicle 270 provides a towed and/or articulated charger plate 520, as connected to the emergency charging vehicle 270 by connector 1150. The connector 1150 may comprise a chain, rope, rigid or semi-rigid tow bar or any means to position charger plate 520 near the charging panel 608 of vehicle 100. Charge or power output of charging power source 516 is provided or transmitted to charger plate 520 by way of charging cable or wire 1140. In one embodiment, the charging cable 1140 is non-structural, that is, it provides little or no structural support to the connection between emergency charging vehicle 270 and charging panel 608. Charging panel 608 (of vehicle 100) receives power from charger plate 520. Charger plate 520 and charging panel 608 may be in direct physical contact or not in direct physical contact, but must be at or below a threshold separation distance to enable charging, such as by induction. Charger plate 520 may comprise wheels or rollers so as to roll along roadway surface. Charger plate 520 may also not contact the ground surface and instead be suspended above the ground; such a configuration may be termed a “flying” configuration. In the flying configuration, charger plate may form an aerodynamic surface to, for example, facilitate stability and control of the positioning of the charging plate 520. Energy transfer or charging from the charger plate 520 to the charge receiver panel 608 is through inductive charging (i.e. use of an EM field to transfer energy between two objects). The charging panel 608 provides received power to energy storage unit 612 directly or by way of charging panel controller 610. In one embodiment, the receipt and/or control of the energy provided via the charging panel 608 is provided by charging panel controller 610.

Charging panel controller 610 may be located anywhere on charge receiver vehicle 100, to include, for example, the roof, side panel, trunk, hood, front or rear bumper and wheel hub of charge receiver 100 vehicle. In some embodiments, charging panel 608 may be deployable, i.e. may extend or deploy only when charging is needed. For example, charging panel 608 may typically stow flush with the lower plane of vehicle 100 and extend when required for charging. Similarly, charger plate 520 may, in one embodiment, not be connected to the lower rear of the emergency charging vehicle 270 by way of connector 1150 and may instead be mounted on the emergency charging vehicle 270, to include, for example, the roof, side panel, trunk, hood, front or rear bumper and wheel hub of emergency charging vehicle 270. Connector 1150 may be configured to maneuver connector plate 520 to any position on emergency charging vehicle 270 so as to enable charging. Control of the charging and/or positioning of the charging plate may be manual, automatic or semi-automatic; said control may be performed through a GUI engaged by driver or occupant of receiving vehicle and/or driver or occupant of charging vehicle.

FIG. 12 shows a perspective view of a vehicle 100 in accordance with embodiments of the present disclosure. Although shown in the form of a car, it should be appreci-

ated that the vehicle **100** described herein may include any conveyance or model of a conveyance, where the conveyance was designed for the purpose of moving one or more tangible objects, such as people, animals, cargo, and the like. The term “vehicle” does not require that a conveyance moves or is capable of movement. Typical vehicles may include but are in no way limited to cars, trucks, motorcycles, busses, automobiles, trains, railed conveyances, boats, ships, marine conveyances, submarine conveyances, airplanes, space craft, flying machines, human-powered conveyances, and the like. In any event, the vehicle **100** may include a frame **1204** and one or more body panels **1208** mounted or affixed thereto. The vehicle **100** may include one or more interior components (e.g., components inside an interior space **150**, or user space, of a vehicle **100**, etc.), exterior components (e.g., components outside of the interior space **150**, or user space, of a vehicle **100**, etc.), drive systems, controls systems, structural components.

Referring now to FIG. 13, a plan view of a vehicle **100** will be described in accordance with embodiments of the present disclosure. As provided above, the vehicle **100** may comprise a number of electrical and/or mechanical systems, subsystems, etc. The mechanical systems of the vehicle **100** can include structural, power, safety, and communications subsystems, to name a few. While each subsystem may be described separately, it should be appreciated that the components of a particular subsystem may be shared between one or more other subsystems of the vehicle **100**.

The structural subsystem includes the frame **1204** of the vehicle **100**. The frame **1204** may comprise a separate frame and body construction (i.e., body-on-frame construction), a unitary frame and body construction (i.e., a unibody construction), or any other construction defining the structure of the vehicle **100**. The frame **1204** may be made from one or more materials including, but in no way limited to steel, titanium, aluminum, carbon fiber, plastic, polymers, etc., and/or combinations thereof. In some embodiments, the frame **1204** may be formed, welded, fused, fastened, pressed, etc., combinations thereof, or otherwise shaped to define a physical structure and strength of the vehicle **100**. In any event, the frame **1204** may comprise one or more surfaces, connections, protrusions, cavities, mounting points, tabs, slots, or other features that are configured to receive other components that make up the vehicle **100**. For example, the body panels, powertrain subsystem, controls systems, interior components, communications subsystem, and safety subsystem may interconnect with, or attach to, the frame **1204** of the vehicle **100**.

The frame **1204** may include one or more modular system and/or subsystem connection mechanisms. These mechanisms may include features that are configured to provide a selectively interchangeable interface for one or more of the systems and/or subsystems described herein. The mechanisms may provide for a quick exchange, or swapping, of components while providing enhanced security and adaptability over conventional manufacturing or attachment. For instance, the ability to selectively interchange systems and/or subsystems in the vehicle **100** allow the vehicle **100** to adapt to the ever-changing technological demands of society and advances in safety. Among other things, the mechanisms may provide for the quick exchange of batteries, capacitors, power sources **1308A**, **1308B**, motors **1312**, engines, safety equipment, controllers, user interfaces, interiors exterior components, body panels **1208**, bumpers **1316**, sensors, etc., and/or combinations thereof. Additionally or alternatively, the mechanisms may provide unique security hardware and/or software embedded therein that, among other things,

can prevent fraudulent or low quality construction replacements from being used in the vehicle **100**. Similarly, the mechanisms, subsystems, and/or receiving features in the vehicle **100** may employ poka-yoke, or mistake-proofing, features that ensure a particular mechanism is always interconnected with the vehicle **100** in a correct position, function, etc.

By way of example, complete systems or subsystems may be removed and/or replaced from a vehicle **100** utilizing a single minute exchange principle. In some embodiments, the frame **1204** may include slides, receptacles, cavities, protrusions, and/or a number of other features that allow for quick exchange of system components. In one embodiment, the frame **1204** may include tray or ledge features, mechanical interconnection features, locking mechanisms, retaining mechanisms, etc., and/or combinations thereof. In some embodiments, it may be beneficial to quickly remove a used power source **1308A**, **1308B** (e.g., battery unit, capacitor unit, etc.) from the vehicle **100** and replace the used power source **1308A**, **1308B** with a charged power source. Continuing this example, the power source **1308A**, **1308B** may include selectively interchangeable features that interconnect with the frame **1204** or other portion of the vehicle **100**. For instance, in a power source **1308A**, **1308B** replacement, the quick release features may be configured to release the power source **1308A**, **1308B** from an engaged position and slide or move away from the frame **1204** of a vehicle **100**. Once removed, the power source **1308A**, **1308B** may be replaced (e.g., with a new power source, a charged power source, etc.) by engaging the replacement power source into a system receiving position adjacent to the vehicle **100**. In some embodiments, the vehicle **100** may include one or more actuators configured to position, lift, slide, or otherwise engage the replacement power source with the vehicle **100**. In one embodiment, the replacement power source may be inserted into the vehicle **100** or vehicle frame **1204** with mechanisms and/or machines that are external or separate from the vehicle **100**.

In some embodiments, the frame **1204** may include one or more features configured to selectively interconnect with other vehicles and/or portions of vehicles. These selectively interconnecting features can allow for one or more vehicles to selectively couple together and decouple for a variety of purposes. For example, it is an aspect of the present disclosure that a number of vehicles may be selectively coupled together to share energy, increase power output, provide security, decrease power consumption, provide towing services, and/or provide a range of other benefits. Continuing this example, the vehicles may be coupled together based on travel route, destination, preferences, settings, sensor information, and/or some other data. The coupling may be initiated by at least one controller of the vehicle and/or traffic control system upon determining that a coupling is beneficial to one or more vehicles in a group of vehicles or a traffic system. As can be appreciated, the power consumption for a group of vehicles traveling in a same direction may be reduced or decreased by removing any aerodynamic separation between vehicles. In this case, the vehicles may be coupled together to subject only the foremost vehicle in the coupling to air and/or wind resistance during travel. In one embodiment, the power output by the group of vehicles may be proportionally or selectively controlled to provide a specific output from each of the one or more of the vehicles in the group.

The interconnecting, or coupling, features may be configured as electromagnetic mechanisms, mechanical couplings, electromechanical coupling mechanisms, etc., and/or

13

combinations thereof. The features may be selectively deployed from a portion of the frame **1204** and/or body of the vehicle **100**. In some cases, the features may be built into the frame **1204** and/or body of the vehicle **100**. In any event, the features may deploy from an unexposed position to an exposed position or may be configured to selectively engage/disengage without requiring an exposure or deployment of the mechanism from the frame **1204** and/or body. In some embodiments, the interconnecting features may be configured to interconnect one or more of power, communications, electrical energy, fuel, and/or the like. One or more of the power, mechanical, and/or communications connections between vehicles may be part of a single interconnection mechanism. In some embodiments, the interconnection mechanism may include multiple connection mechanisms. In any event, the single interconnection mechanism or the interconnection mechanism may employ the poka-yoke features as described above.

The power system of the vehicle **100** may include the powertrain, power distribution system, accessory power system, and/or any other components that store power, provide power, convert power, and/or distribute power to one or more portions of the vehicle **100**. The powertrain may include the one or more electric motors **1312** of the vehicle **100**. The electric motors **1312** are configured to convert electrical energy provided by a power source into mechanical energy. This mechanical energy may be in the form of a rotational or other output force that is configured to propel or otherwise provide a motive force for the vehicle **100**.

In some embodiments, the vehicle **100** may include one or more drive wheels **1320** that are driven by the one or more electric motors **1312** and motor controllers **1314**. In some cases, the vehicle **100** may include an electric motor **1312** configured to provide a driving force for each drive wheel **1320**. In other cases, a single electric motor **1312** may be configured to share an output force between two or more drive wheels **1320** via one or more power transmission components. It is an aspect of the present disclosure that the powertrain include one or more power transmission components, motor controllers **1314**, and/or power controllers that can provide a controlled output of power to one or more of the drive wheels **1320** of the vehicle **100**. The power transmission components, power controllers, or motor controllers **1314** may be controlled by at least one other vehicle controller described herein.

As provided above, the powertrain of the vehicle **100** may include one or more power sources **1308A**, **1308B**. These one or more power sources **1308A**, **1308B** may be configured to provide drive power, system and/or subsystem power, accessory power, etc. While described herein as a single power source **1308** for sake of clarity, embodiments of the present disclosure are not so limited. For example, it should be appreciated that independent, different, or separate power sources **1308A**, **1308B** may provide power to various systems of the vehicle **100**. For instance, a drive power source may be configured to provide the power for the one or more electric motors **1312** of the vehicle **100**, while a system power source may be configured to provide the power for one or more other systems and/or subsystems of the vehicle **100**. Other power sources may include an accessory power source, a backup power source, a critical system power source, and/or other separate power sources. Separating the power sources **1308A**, **1308B** in this manner may provide a number of benefits over conventional vehicle systems. For example, separating the power sources **1308A**, **1308B** allow one power source **1308** to be removed and/or replaced independently without requiring that power be

14

removed from all systems and/or subsystems of the vehicle **100** during a power source **1308** removal/replacement. For instance, one or more of the accessories, communications, safety equipment, and/or backup power systems, etc., may be maintained even when a particular power source **1308A**, **1308B** is depleted, removed, or becomes otherwise inoperable.

In some embodiments, the drive power source may be separated into two or more cells, units, sources, and/or systems. By way of example, a vehicle **100** may include a first drive power source **1308A** and a second drive power source **1308B**. The first drive power source **1308A** may be operated independently from or in conjunction with the second drive power source **1308B** and vice versa. Continuing this example, the first drive power source **1308A** may be removed from a vehicle while a second drive power source **1308B** can be maintained in the vehicle **100** to provide drive power. This approach allows the vehicle **100** to significantly reduce weight (e.g., of the first drive power source **1308A**, etc.) and improve power consumption, even if only for a temporary period of time. In some cases, a vehicle **100** running low on power may automatically determine that pulling over to a rest area, emergency lane, and removing, or “dropping off,” at least one power source **1308A**, **1308B** may reduce enough weight of the vehicle **100** to allow the vehicle **100** to navigate to the closest power source replacement and/or charging area. In some embodiments, the removed, or “dropped off,” power source **1308A** may be collected by a collection service, vehicle mechanic, tow truck, or even another vehicle or individual.

The power source **1308** may include a GPS or other geographical location system that may be configured to emit a location signal to one or more receiving entities. For instance, the signal may be broadcast or targeted to a specific receiving party. Additionally or alternatively, the power source **1308** may include a unique identifier that may be used to associate the power source **1308** with a particular vehicle **100** or vehicle user. This unique identifier may allow an efficient recovery of the power source **1308** dropped off. In some embodiments, the unique identifier may provide information for the particular vehicle **100** or vehicle user to be billed or charged with a cost of recovery for the power source **1308**.

The power source **1308** may include a charge controller **1324** that may be configured to determine charge levels of the power source **1308**, control a rate at which charge is drawn from the power source **1308**, control a rate at which charge is added to the power source **1308**, and/or monitor a health of the power source **1308** (e.g., one or more cells, portions, etc.). In some embodiments, the charge controller **1324** or the power source **1308** may include a communication interface. The communication interface can allow the charge controller **1324** to report a state of the power source **1308** to one or more other controllers of the vehicle **100** or even communicate with a communication device separate and/or apart from the vehicle **100**. Additionally or alternatively, the communication interface may be configured to receive instructions (e.g., control instructions, charge instructions, communication instructions, etc.) from one or more other controllers of the vehicle **100** or a communication device that is separate and/or apart from the vehicle **100**.

The powertrain includes one or more power distribution systems configured to transmit power from the power source **1308** to one or more electric motors **1312** in the vehicle **100**. The power distribution system may include electrical interconnections **1328** in the form of cables, wires, traces, wireless power transmission systems, etc., and/or combina-

15

tions thereof. It is an aspect of the present disclosure that the vehicle **100** include one or more redundant electrical interconnections **1332** of the power distribution system. The redundant electrical interconnections **1332** can allow power to be distributed to one or more systems and/or subsystems of the vehicle **100** even in the event of a failure of an electrical interconnection portion of the vehicle **100** (e.g., due to an accident, mishap, tampering, or other harm to a particular electrical interconnection, etc.). In some embodiments, a user of a vehicle **100** may be alerted via a user interface associated with the vehicle **100** that a redundant electrical interconnection **1332** is being used and/or damage has occurred to a particular area of the vehicle electrical system. In any event, the one or more redundant electrical interconnections **1332** may be configured along completely different routes than the electrical interconnections **1328** and/or include different modes of failure than the electrical interconnections **1328** to, among other things, prevent a total interruption power distribution in the event of a failure.

In some embodiments, the power distribution system may include an energy recovery system **1336**. This energy recovery system **1336**, or kinetic energy recovery system, may be configured to recover energy produced by the movement of a vehicle **100**. The recovered energy may be stored as electrical and/or mechanical energy. For instance, as a vehicle **100** travels or moves, a certain amount of energy is required to accelerate, maintain a speed, stop, or slow the vehicle **100**. In any event, a moving vehicle has a certain amount of kinetic energy. When brakes are applied in a typical moving vehicle, most of the kinetic energy of the vehicle is lost as the generation of heat in the braking mechanism. In an energy recovery system **1336**, when a vehicle **100** brakes, at least a portion of the kinetic energy is converted into electrical and/or mechanical energy for storage. Mechanical energy may be stored as mechanical movement (e.g., in a flywheel, etc.) and electrical energy may be stored in batteries, capacitors, and/or some other electrical storage system. In some embodiments, electrical energy recovered may be stored in the power source **1308**. For example, the recovered electrical energy may be used to charge the power source **1308** of the vehicle **100**.

The vehicle **100** may include one or more safety systems. Vehicle safety systems can include a variety of mechanical and/or electrical components including, but in no way limited to, low impact or energy-absorbing bumpers **1316A**, **1316B**, crumple zones, reinforced body panels, reinforced frame components, impact bars, power source containment zones, safety glass, seatbelts, supplemental restraint systems, air bags, escape hatches, removable access panels, impact sensors, accelerometers, vision systems, radar systems, etc., and/or the like. In some embodiments, the one or more of the safety components may include a safety sensor or group of safety sensors associated with the one or more of the safety components. For example, a crumple zone may include one or more strain gages, impact sensors, pressure transducers, etc. These sensors may be configured to detect or determine whether a portion of the vehicle **100** has been subjected to a particular force, deformation, or other impact. Once detected, the information collected by the sensors may be transmitted or sent to one or more of a controller of the vehicle **100** (e.g., a safety controller, vehicle controller, etc.) or a communication device associated with the vehicle **100** (e.g., across a communication network, etc.).

FIG. **14** shows a plan view of the vehicle **100** in accordance with embodiments of the present disclosure. In particular, FIG. **14** shows a broken section **1402** of a charging system for the vehicle **100**. The charging system may

16

include a plug or receptacle **1404** configured to receive power from an external power source (e.g., a source of power that is external to and/or separate from the vehicle **100**, etc.). An example of an external power source may include the standard industrial, commercial, or residential power that is provided across power lines. Another example of an external power source may include a proprietary power system configured to provide power to the vehicle **100**. In any event, power received at the plug/receptacle **1404** may be transferred via at least one power transmission interconnection **1408**. Similar, if not identical, to the electrical interconnections **1328** described above, the at least one power transmission interconnection **1408** may be one or more cables, wires, traces, wireless power transmission systems, etc., and/or combinations thereof. Electrical energy in the form of charge can be transferred from the external power source to the charge controller **1324**. As provided above, the charge controller **1324** may regulate the addition of charge to the power source **1308** of the vehicle **100** (e.g., until the power source **1308** is full or at a capacity, etc.).

In some embodiments, the vehicle **100** may include an inductive charging system and inductive charger **1412**. The inductive charger **1412** may be configured to receive electrical energy from an inductive power source external to the vehicle **100**. In one embodiment, when the vehicle **100** and/or the inductive charger **1412** is positioned over an inductive power source external to the vehicle **100**, electrical energy can be transferred from the inductive power source to the vehicle **100**. For example, the inductive charger **1412** may receive the charge and transfer the charge via at least one power transmission interconnection **1408** to the charge controller **1324** and/or the power source **1308** of the vehicle **100**. The inductive charger **1412** may be concealed in a portion of the vehicle **100** (e.g., at least partially protected by the frame **1204**, one or more body panels **1208**, a shroud, a shield, a protective cover, etc., and/or combinations thereof) and/or may be deployed from the vehicle **100**. In some embodiments, the inductive charger **1412** may be configured to receive charge only when the inductive charger **1412** is deployed from the vehicle **100**. In other embodiments, the inductive charger **1412** may be configured to receive charge while concealed in the portion of the vehicle **100**.

In addition to the mechanical components described herein, the vehicle **100** may include a number of user interface devices. The user interface devices receive and translate human input into a mechanical movement or electrical signal or stimulus. The human input may be one or more of motion (e.g., body movement, body part movement, in two-dimensional or three-dimensional space, etc.), voice, touch, and/or physical interaction with the components of the vehicle **100**. In some embodiments, the human input may be configured to control one or more functions of the vehicle **100** and/or systems of the vehicle **100** described herein. User interfaces may include, but are in no way limited to, at least one graphical user interface of a display device, steering wheel or mechanism, transmission lever or button (e.g., including park, neutral, reverse, and/or drive positions, etc.), throttle control pedal or mechanism, brake control pedal or mechanism, power control switch, communications equipment, etc.

An embodiment of the electrical system **1500** associated with the vehicle **100** may be as shown in FIG. **15**. The electrical system **1500** can include power source(s) that generate power, power storage that stores power, and/or load(s) that consume power. Power sources may be associated with a power generation unit **1504**. Power storage may be associated with a power storage system **612**. Loads may

17

be associated with loads **1508**. The electrical system **1500** may be managed by a power management controller **1324**. Further, the electrical system **1500** can include one or more other interfaces or controllers, which can include the billing and cost control unit **1512**.

The power generation unit **1504** may be as described in conjunction with FIG. **16**. The power storage component **612** may be as described in conjunction with FIG. **17**. The loads **1508** may be as described in conjunction with FIG. **18**.

The billing and cost control unit **1512** may interface with the power management controller **1324** to determine the amount of charge or power provided to the power storage **612** through the power generation unit **1504**. The billing and cost control unit **1512** can then provide information for billing the vehicle owner. Thus, the billing and cost control unit **1512** can receive and/or send power information to third party system(s) regarding the received charge from an external source. The information provided can help determine an amount of money required, from the owner of the vehicle, as payment for the provided power. Alternatively, or in addition, if the owner of the vehicle provided power to another vehicle (or another device/system), that owner may be owed compensation for the provided power or energy, e.g., a credit.

The power management controller **1324** can be a computer or computing system(s) and/or electrical system with associated components, as described herein, capable of managing the power generation unit **1504** to receive power, routing the power to the power storage **612**, and then providing the power from either the power generation unit **1504** and/or the power storage **612** to the loads **1508**. Thus, the power management controller **1324** may execute programming that controls switches, devices, components, etc. involved in the reception, storage, and provision of the power in the electrical system **1500**.

An embodiment of the power generation unit **1504** may be as shown in FIG. **16**. Generally, the power generation unit **1504** may be electrically coupled to one or more power sources **1308**. The power sources **1308** can include power sources internal and/or associated with the vehicle **100** and/or power sources external to the vehicle **100** to which the vehicle **100** electrically connects. One of the internal power sources can include an on board generator **1604**. The generator **1604** may be an alternating current (AC) generator, a direct current (DC) generator or a self-excited generator. The AC generators can include induction generators, linear electric generators, and/or other types of generators. The DC generators can include homopolar generators and/or other types of generators. The generator **1604** can be brushless or include brush contacts and generate the electric field with permanent magnets or through induction. The generator **1604** may be mechanically coupled to a source of kinetic energy, such as an axle or some other power take-off. The generator **1604** may also have another mechanical coupling to an exterior source of kinetic energy, for example, a wind turbine.

Another power source **1308** may include wired or wireless charging **1608**. The wireless charging system **1608** may include inductive and/or resonant frequency inductive charging systems that can include coils, frequency generators, controllers, etc. Wired charging may be any kind of grid-connected charging that has a physical connection, although, the wireless charging may be grid connected through a wireless interface. The wired charging system can include connectors, wired interconnections, the controllers,

18

etc. The wired and wireless charging systems **1608** can provide power to the power generation unit **1504** from external power sources **1308**.

Internal sources for power may include a regenerative braking system **1612**. The regenerative braking system **1612** can convert the kinetic energy of the moving car into electrical energy through a generation system mounted within the wheels, axle, and/or braking system of the vehicle **100**. The regenerative braking system **1612** can include any coils, magnets, electrical interconnections, converters, controllers, etc. required to convert the kinetic energy into electrical energy.

Another source of power **1308**, internal to or associated with the vehicle **100**, may be a solar array **1616**. The solar array **1616** may include any system or device of one or more solar cells mounted on the exterior of the vehicle **100** or integrated within the body panels of the vehicle **100** that provides or converts solar energy into electrical energy to provide to the power generation unit **1504**.

The power sources **1308** may be connected to the power generation unit **1504** through an electrical interconnection **1618**. The electrical interconnection **1618** can include any wire, interface, bus, etc. between the one or more power sources **1308** and the power generation unit **1504**.

The power generation unit **1504** can also include a power source interface **1620**. The power source interface **1620** can be any type of physical and/or electrical interface used to receive the electrical energy from the one or more power sources **1308**; thus, the power source interface **1620** can include an electrical interface **1624** that receives the electrical energy and a mechanical interface **1628** which may include wires, connectors, or other types of devices or physical connections. The mechanical interface **1608** can also include a physical/electrical connection **1634** to the power generation unit **1504**.

The electrical energy from the power source **1308** can be processed through the power source interface **1624** to an electric converter **1632**. The electric converter **1632** may convert the characteristics of the power from one of the power sources into a useable form that may be used either by the power storage **612** or one or more loads **1508** within the vehicle **100**. The electrical converter **1624** may include any electronics or electrical devices and/or component that can change electrical characteristics, e.g., AC frequency, amplitude, phase, etc. associated with the electrical energy provided by the power source **1308**. The converted electrical energy may then be provided to an optional conditioner **1638**. The conditioner **1638** may include any electronics or electrical devices and/or component that may further condition the converted electrical energy by removing harmonics, noise, etc. from the electrical energy to provide a more stable and effective form of power to the vehicle **100**.

An embodiment of the power storage **1612** may be as shown in FIG. **17**. The power storage unit can include an electrical converter **1632b**, one or more batteries, one or more rechargeable batteries, one or more capacitors, one or more accumulators, one or more supercapacitors, one or more ultrabatteries, and/or superconducting magnetics **1704**, and/or a charge management unit **1708**. The converter **1632b** may be the same or similar to the electrical converter **1632a** shown in FIG. **16**. The converter **1632b** may be a replacement for the electric converter **1632a** shown in FIG. **16** and thus eliminate the need for the electrical converter **1632a** as shown in FIG. **16**. However, if the electrical converter **1632a** is provided in the power generation unit **1504**, the converter **1632b**, as shown in the power storage unit **612**, may be eliminated. The converter **1632b** can also be redundant or

19

different from the electrical converter **1632a** shown in FIG. **16** and may provide a different form of energy to the battery and/or capacitors **1704**. Thus, the converter **1632b** can change the energy characteristics specifically for the battery/capacitor **1704**.

The battery **1704** can be any type of battery for storing electrical energy, for example, a lithium ion battery, a lead acid battery, a nickel cadmium battery, etc. Further, the battery **1704** may include different types of power storage systems, such as, ionic fluids or other types of fuel cell systems. The energy storage **1704** may also include one or more high-capacity capacitors **1704**. The capacitors **1704** may be used for long-term or short-term storage of electrical energy. The input into the battery or capacitor **1704** may be different from the output, and thus, the capacitor **1704** may be charged quickly but drain slowly. The functioning of the converter **1632** and battery capacitor **1704** may be monitored or managed by a charge management unit **1708**.

The charge management unit **1708** can include any hardware (e.g., any electronics or electrical devices and/or components), software, or firmware operable to adjust the operations of the converter **1632** or batteries/capacitors **1704**. The charge management unit **1708** can receive inputs or periodically monitor the converter **1632** and/or battery/capacitor **1704** from this information; the charge management unit **1708** may then adjust settings or inputs into the converter **1632** or battery/capacitor **1704** to control the operation of the power storage system **612**.

An embodiment of one or more loads **1508** associated with the vehicle **100** may be as shown in FIG. **18**. The loads **1508** may include a bus or electrical interconnection system **1802**, which provides electrical energy to one or more different loads within the vehicle **100**. The bus **1802** can be any number of wires or interfaces used to connect the power generation unit **1504** and/or power storage **1612** to the one or more loads **1508**. The converter **1632c** may be an interface from the power generation unit **1504** or the power storage **612** into the loads **1508**. The converter **1632c** may be the same or similar to electric converter **1632a** as shown in FIG. **16**. Similar to the discussion of the converter **1632b** in FIG. **17**, the converter **1632c** may be eliminated, if the electric converter **1632a**, shown in FIG. **16**, is present. However, the converter **1632c** may further condition or change the energy characteristics for the bus **1802** for use by the loads **1508**. The converter **1632c** may also provide electrical energy to electric motor **1804**, which may power the vehicle **100**.

The electric motor **1804** can be any type of DC or AC electric motor. The electric motor may be a direct drive or induction motor using permanent magnets and/or winding either on the stator or rotor. The electric motor **1804** may also be wireless or include brush contacts. The electric motor **1804** may be capable of providing a torque and enough kinetic energy to move the vehicle **100** in traffic.

The different loads **1508** may also include environmental loads **1812**, sensor loads **1816**, safety loads **1820**, user interaction loads **1808**, etc. User interaction loads **1808** can be any energy used by user interfaces or systems that interact with the driver and/or passenger(s). These loads **1808** may include, for example, the heads up display, the dash display, the radio, user interfaces on the head unit, lights, radio, and/or other types of loads that provide or receive information from the occupants of the vehicle **100**. The environmental loads **1812** can be any loads used to control the environment within the vehicle **100**. For example, the air conditioning or heating unit of the vehicle **100** can be environmental loads **1812**. Other environmental loads can

20

include lights, fans, and/or defrosting units, etc. that may control the environment within the vehicle **100**. The sensor loads **1816** can be any loads used by sensors, for example, air bag sensors, GPS, and other such sensors used to either manage or control the vehicle **100** and/or provide information or feedback to the vehicle occupants. The safety loads **1820** can include any safety equipment, for example, seat belt alarms, airbags, headlights, blinkers, etc. that may be used to manage the safety of the occupants. There may be more or fewer loads than those described herein, although they may not be shown in FIG. **18**.

FIG. **19** illustrates an exemplary hardware diagram of communications componentry that can be optionally associated with the vehicle.

The communications componentry can include one or more wired or wireless devices such as a transceiver(s) and/or modem that allows communications not only between the various systems disclosed herein but also with other devices, such as devices on a network, and/or on a distributed network such as the Internet and/or in the cloud.

The communications subsystem can also include inter- and intra-vehicle communications capabilities such as hotspot and/or access point connectivity for any one or more of the vehicle occupants and/or vehicle-to-vehicle communications.

Additionally, and while not specifically illustrated, the communications subsystem can include one or more communications links (that can be wired or wireless) and/or communications busses (managed by the bus manager), including one or more of CANbus, OBD-II, ARCINC 429, Byteflight, CAN (Controller Area Network), D2B (Domestic Digital Bus), FlexRay, DC-BUS, IDB-1394, IEBus, I²C, ISO 9141-1/-2, J1708, J1587, J1850, J1939, ISO 11783, Keyword Protocol 2000, LIN (Local Interconnect Network), MOST (Media Oriented Systems Transport), Multifunction Vehicle Bus, SMARTwireX, SPI, VAN (Vehicle Area Network), and the like or in general any communications protocol and/or standard.

The various protocols and communications can be communicated one or more of wirelessly and/or over transmission media such as single wire, twisted pair, fibre optic, IEEE 1394, MIL-STD-1553, MIL-STD-1773, power-line communication, or the like. (All of the above standards and protocols are incorporated herein by reference in their entirety)

As discussed, the communications subsystem enables communications between any if the inter-vehicle systems and subsystems as well as communications with non-located resources, such as those reachable over a network such as the Internet.

The communications subsystem, in addition to well-known componentry (which has been omitted for clarity), the device communications subsystem **1900** includes interconnected elements including one or more of: one or more antennas **1904**, an interleaver/deinterleaver **1908**, an analog front end (AFE) **1912**, memory/storage/cache **1916**, controller/microprocessor **1920**, MAC circuitry **1922**, modulator/demodulator **1924**, encoder/decoder **1928**, a plurality of connectivity managers **1934-1966**, GPU **1942**, accelerator **1944**, a multiplexer/demultiplexer **1954**, transmitter **1970**, receiver **1972** and wireless radio **310** components such as a Wi-Fi PHY/Bluetooth® module **1980**, a Wi-Fi/BT MAC module **1984**, transmitter **1988** and receiver **1992**. The various elements in the device **1900** are connected by one or more links/busses **5** (not shown, again for sake of clarity).

The device **400** can have one more antennas **1904**, for use in wireless communications such as multi-input multi-out-

put (MIMO) communications, multi-user multi-input multi-output (MU-MIMO) communications Bluetooth®, LTE, 4G, 5G, Near-Field Communication (NFC), etc. The antenna(s) **1904** can include, but are not limited to one or more of directional antennas, omnidirectional antennas, monopoles, patch antennas, loop antennas, microstrip antennas, dipoles, and any other antenna(s) suitable for communication transmission/reception. In an exemplary embodiment, transmission/reception using MIMO may require particular antenna spacing. In another exemplary embodiment, MIMO transmission/reception can enable spatial diversity allowing for different channel characteristics at each of the antennas. In yet another embodiment, MIMO transmission/reception can be used to distribute resources to multiple users for example within the vehicle and/or in another vehicle.

Antenna(s) **1904** generally interact with the Analog Front End (AFE) **1912**, which is needed to enable the correct processing of the received modulated signal and signal conditioning for a transmitted signal. The AFE **1912** can be functionally located between the antenna and a digital baseband system in order to convert the analog signal into a digital signal for processing and vice-versa.

The subsystem **1900** can also include a controller/microprocessor **1920** and a memory/storage/cache **1916**. The subsystem **1900** can interact with the memory/storage/cache **1916** which may store information and operations necessary for configuring and transmitting or receiving the information described herein. The memory/storage/cache **1916** may also be used in connection with the execution of application programming or instructions by the controller/microprocessor **1920**, and for temporary or long term storage of program instructions and/or data. As examples, the memory/storage/cache **1920** may comprise a computer-readable device, RAM, ROM, DRAM, SDRAM, and/or other storage device(s) and media.

The controller/microprocessor **1920** may comprise a general purpose programmable processor or controller for executing application programming or instructions related to the subsystem **1900**. Furthermore, the controller/microprocessor **1920** can perform operations for configuring and transmitting/receiving information as described herein. The controller/microprocessor **1920** may include multiple processor cores, and/or implement multiple virtual processors. Optionally, the controller/microprocessor **1920** may include multiple physical processors. By way of example, the controller/microprocessor **1920** may comprise a specially configured Application Specific Integrated Circuit (ASIC) or other integrated circuit, a digital signal processor(s), a controller, a hardwired electronic or logic circuit, a programmable logic device or gate array, a special purpose computer, or the like.

The subsystem **1900** can further include a transmitter **1970** and receiver **1972** which can transmit and receive signals, respectively, to and from other devices, subsystems and/or other destinations using the one or more antennas **1904** and/or links/busses. Included in the subsystem **1900** circuitry is the medium access control or MAC Circuitry **1922**. MAC circuitry **1922** provides for controlling access to the wireless medium. In an exemplary embodiment, the MAC circuitry **1922** may be arranged to contend for the wireless medium and configure frames or packets for communicating over the wireless medium.

The subsystem **1900** can also optionally contain a security module (not shown). This security module can contain information regarding but not limited to, security parameters required to connect the device to one or more other devices or other available network(s), and can include WEP or

WPA/WPA-2 (optionally+AES and/or TKIP) security access keys, network keys, etc. The WEP security access key is a security password used by Wi-Fi networks. Knowledge of this code can enable a wireless device to exchange information with an access point and/or another device. The information exchange can occur through encoded messages with the WEP access code often being chosen by the network administrator. WPA is an added security standard that is also used in conjunction with network connectivity with stronger encryption than WEP.

The exemplary subsystem **1900** also includes a GPU **1942**, an accelerator **1944**, a Wi-Fi/BT/BLE PHY module **1980** and a Wi-Fi/BT/BLE MAC module **1984** and wireless transmitter **1988** and receiver **1992**.

The various connectivity managers **1934-1966** manage and/or coordinate communications between the subsystem **1900** and one or more of the systems disclosed herein and one or more other devices/systems. The connectivity managers include an emergency charging connectivity manager **1934**, an aerial charging connectivity manager **1938**, a roadway charging connectivity manager **1942**, an overhead charging connectivity manager **1946**, a robotic charging connectivity manager **1950**, a static charging connectivity manager **1954**, a vehicle database connectivity manager **1958**, a remote operating system connectivity manager **1962** and a sensor connectivity manager **1966**.

The emergency charging connectivity manager **1934** can coordinate not only the physical connectivity between the vehicle and the emergency charging device/vehicle, but can also communicate with one or more of the power management controller, one or more third parties and optionally a billing system(s). As an example, the vehicle can establish communications with the emergency charging device/vehicle to one or more of coordinate interconnectivity between the two (e.g., by spatially aligning the charging receptacle on the vehicle with the charger on the emergency charging vehicle) and optionally share navigation information. Once charging is complete, the amount of charge provided can be tracked and optionally forwarded to, for example, a third party for billing. In addition to being able to manage connectivity for the exchange of power, the emergency charging connectivity manager **1934** can also communicate information, such as billing information to the emergency charging vehicle and/or a third party. This billing information could be, for example, the owner of the vehicle, the driver of the vehicle, company information, or in general any information usable to charge the appropriate entity for the power received.

The aerial charging connectivity manager **1938** can coordinate not only the physical connectivity between the vehicle and the aerial charging device/vehicle, but can also communicate with one or more of the power management controller, one or more third parties and optionally a billing system(s). As an example, the vehicle can establish communications with the aerial charging device/vehicle to one or more of coordinate interconnectivity between the two (e.g., by spatially aligning the charging receptacle on the vehicle with the charger on the emergency charging vehicle) and optionally share navigation information. Once charging is complete, the amount of charge provided can be tracked and optionally forwarded to, for example, a third party for billing. In addition to being able to manage connectivity for the exchange of power, the aerial charging connectivity manager **1938** can similarly communicate information, such as billing information to the aerial charging vehicle and/or a third party. This billing information could be, for example, the owner of the vehicle, the driver of the vehicle, company

information, or in general any information usable to charge the appropriate entity for the power received etc., as discussed.

The roadway charging connectivity manager **1942** and overhead charging connectivity manager **1946** can coordinate not only the physical connectivity between the vehicle and the charging device/system, but can also communicate with one or more of the power management controller, one or more third parties and optionally a billing system(s). As one example, the vehicle can request a charge from the charging system when, for example, the vehicle needs or is predicted to need power. As an example, the vehicle can establish communications with the charging device/vehicle to one or more of coordinate interconnectivity between the two for charging and share information for billing. Once charging is complete, the amount of charge provided can be tracked and optionally forwarded to, for example, a third party for billing. This billing information could be, for example, the owner of the vehicle, the driver of the vehicle, company information, or in general any information usable to charge the appropriate entity for the power received etc., as discussed. The person responsible for paying for the charge could also receive a copy of the billing information as is customary. The robotic charging connectivity manager **1950** and static charging connectivity manager **1954** can operate in a similar manner to that described herein.

The vehicle database connectivity manager **1958** allows the subsystem to receive and/or share information stored in the vehicle database. This information can be shared with other vehicle components/subsystems and/or other entities, such as third parties and/or charging systems. The information can also be shared with one or more vehicle occupant devices, such as an app on a mobile device the driver uses to track information about the vehicle and/or a dealer or service/maintenance provider. In general, any information stored in the vehicle database can optionally be shared with any one or more other devices optionally subject to any privacy or confidentiality restrictions.

The remote operating system connectivity manager **1962** facilitates communications between the vehicle **100** and any one or more autonomous vehicle systems. These communications can include one or more of navigation information, vehicle information, occupant information, or in general any information related to the remote operation of the vehicle.

The sensor connectivity manager **1966** facilitates communications between any one or more of the vehicle sensors and any one or more of the other vehicle systems. The sensor connectivity manager **1966** can also facilitate communications between any one or more of the sensors and/or vehicle systems and any other destination, such as a service company, app, or in general to any destination where sensor data is needed.

In accordance with one exemplary embodiment, any of the communications discussed herein can be communicated via the conductor(s) used for charging. One exemplary protocol usable for these communications is Power-line communication (PLC). PLC is a communication protocol that uses electrical wiring to simultaneously carry both data, and Alternating Current (AC) electric power transmission or electric power distribution. It is also known as power-line carrier, power-line digital subscriber line (PDSL), mains communication, power-line telecommunications, or power-line networking (PLN). For DC environments in vehicles PLC can be used in conjunction with CAN-bus, LIN-bus over power line (DC-LIN) and DC-BUS.

The communications subsystem can also optionally manage one or more identifiers, such as an IP (internet protocol)

address(es), associated with the vehicle and one or other system or subsystems or components therein. These identifiers can be used in conjunction with any one or more of the connectivity managers as discussed herein.

An alternative or additional embodiment of vehicle **100** may be as shown in FIG. **20**. The vehicle **100** may have one or more areas for communicating with the near field communication interface. The areas may include antennas **2004a**, **2004b**, and **2004c**. Antennas can include any type of near field communication (NFC) antenna including loop antennas and other antennas that may be embedded in the panels of the vehicle **100**. NFC may employ electromagnetic induction between two loop antennae when NFC devices, antennas **2004a**, **2004b**, and **2004c** exchange information, operating within the globally available unlicensed radio frequency ISM band of 13.56 MHz on ISO/IEC 18000-3 air interface at rates ranging from 106 to 424 Kbit/s. As such, the antennas **2004a**, **2004b**, and **2004c** can also include any transceiver circuitry that completes the electromagnetic induction connection. In some configurations, the antennas **2004** may only include the loop antenna and the antennas **2004** may share a common circuitry to enable NFC communications.

The antennas **2004a**, **2004b**, and **2004c** can communicate using one or more NFC standards. NFC standards cover communications protocols and data exchange formats and are based on existing radio-frequency identification (RFID) standards including ISO/IEC 14443 and Felicity Card (FeliCa). The standards include ISO/IEC 18092 and those defined by the NFC Forum. In addition to the NFC Forum, the GSM Association (GSMA) group defined a platform for the deployment of GSMA NFC Standards within mobile handsets. GSMA's efforts include Trusted Services Manager, Single Wire Protocol, testing/certification and secure element. NFC components incorporated into the antennas **2004a**, **2004b**, and **2004c** can include, for example, the iClass®, veriClass®, and other NFC devices developed by HID®.

The antennas **2004a**, **2004b**, and **2004c** can be placed in locations on the vehicle **100** to allow easier connection with other devices. For example, antenna **2004a** may be placed on the roof **130** of the vehicle **100** to allow for connection with overhead NFC devices, such as may be found in parking garages. Antenna **2004c** may be positioned outboard on a mirror **2016** or side panel of the vehicle **100** to better connect with devices on walls or other vertical structures, such as may be found at drive through restaurants and establishments. Another antenna **2004c** may be within physical proximity to a charging port **2012** or gas tank door to facilitate communications with a charging device or a gas pump. Other antennas **2004** may be positioned in other parts of the vehicle **100** to facilitate other communications with other entities or facilities.

The vehicle **100** may also communicate with a dongle **2008**. A dongle **2008** may be another hardware/software component that can communicate wirelessly with the vehicle **100**. The dongle **2008** may communicate using an NFC connection or may employ another wireless technology, such as Bluetooth or WLAN technology. A common example of the dongle **2008** is the keyless entry system of many vehicles. Unlike the simple keyless entry system, the dongle **2008** may provide biometric data associated with the user of the dongle **2008**. For example, the dongle **2008** may be associated with a single user, which may need to provide a biometric characteristic (e.g., a fingerprint, a voice signature, etc.) to employ the dongle **2008**. This biometric signature may be exchanged between the dongle **2008** and the

25

vehicle **100**. Further, the presence of the dongle **2008**, determined by a continuous connection between the dongle **2008** and the vehicle **100**, can indicate the presence of the associated user holding the dongle **2008**.

An embodiment of the hardware/software configuration associated with the antennas **2004** may be as shown in FIG. **21**. The hardware software configuration of the antennas **2004** can include a near field communication chipset **2104** a vehicle interface **2108** and/or a soft touch interface **2116**. Each of these different components **2104** through **2116** can include hardware software operable to receive and/or transmit near field communication or other types of communications to and from the vehicle **100**.

The near field communication chipset **2104** can include any hardware and software associated with the execution of near field communication communications. As explained previously, loop antenna **2004** of the NFC device can be embedded within the vehicle. However, the other circuitry and components of the near field communication devices may be incorporated into a single NFC chipset **2104**. Thus, the NFC chipset **2104** can include the components that receive data from the loop antenna, decode and/or encode information from or onto the transmission, or conduct other functions that allow for communications over the NFC connection. For example, the NFC chipset can include, for example, the iClass®, veriClass®, and other NFC devices developed by HID® or similar hardware and/or software.

The soft touch interface **2116** may include a physical interconnection abilities described in conjunction with FIGS. **22A** and **22B**. Vehicle interface **2108** can include any hardware and/or software to exchange communications between the NSC chipset **2104** and or the soft touch interface **2116** and the vehicle processor as described in conjunction with FIG. **19**. As such, the vehicle interface **2108** can include the application programming interface (API) or other communications capability that can translate, reconfigure, or manage the data from the NFC antenna **2004** to the vehicle communication system described FIG. **19**.

An embodiment of a soft touch interface navies described in FIGS. **22A** and **22B**. The soft touch interface may be mounted on an exterior mirror **2016**. Soft touch interface can include an area **2116**. The area **2116** may be a cavity or other mounting structure for the soft touch interface. The soft touch interface can include a rotating cylinder **2204**. The rotating Senate cylinder may be connected to the mounting structure **2116** such that the rotating cylinder **2204** can rotate through a range of movement. Physically attached to the rotating cylinder **2204** may be armature **2208**. Two or more armatures **2208** cab extend from the rotating cylinder **2204**. The two or more armatures **2208** may be stored inboard of the area **2116** in a first position. In a second position, as shown in FIG. **22B**, the armatures **2208** may extend outboard of the mirror **2016**. Amateurs **2208** may connect to or contact a pad **2212**. Both the armatures **2208** the pad **2212** may provide for an electric connection. Signals may be passed between the armatures **2208** and the pad **2212** in the configuration shown in FIG. **22B**. Other configurations for the soft touch interface are possible. These other configurations may include any type of physical electrical connection that may be optionally made by moving an electrical conduit in contact with another electrically conductive surface.

An embodiment of software **2300** that may be stored within the memory **1916** may be as shown in FIG. **23**. Software **2300** can include one or more of an interaction application **2304**, an event handling application **2316**, a browser **2320**, a geolocation application **2224**, a mapping

26

application **2328**, a vehicle identity application **2332**, a motor control application **2336**, and/or a voice input/output application **2344**. The interaction application **2304** can include a contactless payment component **2308** and/or half token application **2312**.

The contactless payment application **2308** can conducts financial transactions using the vehicle. Contactless payment application **2308** may conduct the financial transactions with or without user input with third parties. The half token application **2312** can provide half tokens or pre-authorizations to third parties when interacting with those third parties. As such, the half token application **2312** is capable of authenticating or verifying the identity and veracity of the third party or providing that information for the user to the third party. In some configurations, the half token application **2312** is capable of sending authorizations for secure information in two or more packet communications that may be conducted over different communication media such that a higher-level security is achieved for the vehicle **100**.

Event handling application **2316** is capable of receiving events associated with the vehicle **100** or the user. Events can include such items as need for charging of the electric vehicle, purchase requests by the user, service needs of the vehicle **100**, communication requests by the user, or other types of events. Event handler **2316** can receive the event notifications and instruct other parts or components of the vehicle **100** to respond to the events as received. A browser **2320** can the Internet interface for the vehicle **100** and/or user. Thus, the browser can be any type of Internet interface, for example, Internet Explorer, Safari, Mozilla, etc. The browser **2320** may also provide Internet access to the vehicle **100**.

Geolocation application **2324** can provide location information to the vehicle **100**. The geolocation information may be provided from a GPS antenna, through triangulation of cellular towers or other known landmarks, or by some other type of location information. Geolocation information may be provided to the mapping application **2228**. The mapping application **2228** can provide a coordinated location for the vehicle **100** based on the geolocation information provided by the geolocation application **2324** and one or more maps stored within the vehicle **100**. Thus, the mapping application **2328** can resolve the physical locations of vehicle **100** based on the geolocation information.

The vehicle identity application **2332** can determine the identity of one or more occupants of the vehicle **100**. Thus, the vehicle identity application **2332** can use one or more characteristics of biometric information to identify users within the vehicle **100**. The identity of the users may then be used by other components of the vehicle **100**.

The motor control application can control the motor function of the electric vehicle **100**. Thus, the motor control application **2336** can accelerate or decelerate the electric motor based on user input or input from an automated driving function. The motor control function **2236** may also include the ability to send information using the motor. As such, the motor control application **2336** can include a data over field application **2340** which can encode data onto the electric field generated by the motor. In another configuration, the motor control application **2336** can cycle the motor in a pattern to convey information to a device that can receive or interpret the electric field of the motor.

The voice input output application **2344** can receive voice input from a user within the vehicle **100**. Further, the voice input output can provide sound output to the speakers of the vehicle **100**. Sound output can be synthesized voice to convey information to the user. In other configurations, the

voice input output application **2344** can provide for the exchange of audio and/or video in a communication between a user of the vehicle **100** and another party. If synthesized voice output is provided, the voice input output application **2344** can include a synthesis module **2348**. The synthesis module **2248** can translate written or other signals into voice output that can be sent to the speakers of the vehicle **100**. As such, the driver of the vehicle **100** may not read the information but can listen to the information conveyed by the voice input/output application **2344**.

An embodiment of data system **2400** that may be stored, retrieved, sent, managed etc. with the vehicle **100** and associated with a user may be as shown in FIG. **24**. The data structure **2400** can be stored, received, managed, sent by one or more of the systems in one or more of the processes described herein. The data structure **2404** can represent secure information associated with a user and/or the vehicle **100**. This information data structure **2404** can have one or more data fields including, but not limited to: biometrics **2408**, username **2412**, password **2416**, mobile device information **2420**, dongle code **2424**, encryption key **2428**, credentials **2432**, vehicle identification number (VIN) **2436**, and electronic serial number (ESN) **2440**, and/or an engine code **2444**. There may be more or fewer fields than those shown in data structure **2404**, as represented by ellipses **2452**. Further, each user of the vehicle **100** may have their own data structure, as represented by ellipses **2448**.

The biometrics field **2408** can include biometric information for the user. This information **2408** can include one of more of, but is not limited to: facial structure, facial recognition information, voiceprint, voice recognition information, eye color, DNA information, fingerprint information, or other types of biometric information that could be used to identify the user. This information **2408** may be gathered by sensors and stored in data structure **2408**.

A username **2412** and password **2416** can be identifying information created by a user. The username **2412** can be any type of identifying information that the user can enter to access vehicle systems, and the password **2416** can be another form of data known to the user, used with the username **2414**, to authenticate the user. The username **2412** and password **2416** may be created by the user in another computer and downloaded into the vehicle **100** or may be created in the vehicle **100**.

The mobile device information **2420** can include any information about one or more mobile devices or other types of devices that may be associated with the user and linked with the vehicle **100**. Mobile device information **2420** can include the mobile device number, the media access control (MAC) address, a uniform resource locator (URL), or other types of information that might be associated with a mobile device. Further, mobile device information **2420** can include any kind of Bluetooth link, passcode, or information about a wearable that might provide information about a user.

The dongle code **2420** can be the code or frequency of the dongle **2008**. Thus, this information may be associated with the user rather than with the vehicle **100** because the dongle **2008** is more user-specific than vehicle-specific because the user carries the dongle **2008**. Information from that dongle **2008** can be associated with any kind of specific information about the user. The encryption key **2428** can be any type of known secret that is common between the vehicle **100** and the user. This encryption key **2428** can include some type of pretty good privacy (PGP) key or other types of encryption information used to encrypt the information in the data structure **2404** or other information described herein.

The credentials **2432** can include any type of other credentials or information that might be used to access the encryption key **2428** or other information described herein. These credentials can be other types of information that may be different than that described previously, such as a barcode or other type of information that might be provided from another device or memory or may have been provided by the user through a user interface.

The VIN **2436** and ESN **2440** can be information about the vehicle **100**. This information **2436**, **2440** may be provided automatically when the data structure **2404** is created by the processor **5608** of the vehicle **100**. The VIN may be stored not only as plates or information physically connected to the vehicle but may also be electronic information stored securely within the vehicle **100**. The ESN **2440** may be an identification number for the communication system **1900** of the vehicle **100**.

The engine code **2448** can be any type of code related to the electric or gasoline engine. This code **2444** can be provided by the engine through some type of communication with the magnetic or electric field of the engine. This engine code **2448** can be an alphanumeric code, a numeric code, a globally-unique identifier (GUID), or some other type of code. Thus, similar to the VIN **2436** or the ESN **2440**, the engine code **2444** can provide an identification of the engine.

Another data system **2500** may be as shown in FIG. **25**. Here, the data system **2500** can include one or more other types of secure information associated with the user. The data system **2500** can include one or more data structures **2504**, each related to a user, as represented by ellipses **2536**. The data structure **2504** can include information that is stored, managed, sent, received, retrieved by the systems described herein. The data structure **2504** can include one or more of, but is not limited to: payment information **2508**, a personal identification number (PIN) **2512**, identifiers **2516**, addresses **2520**, limits **2524**, preferences **2528**, and/or rules **2532**. There may be more or fewer fields, associated with data structure **2504**, than those shown in FIG. **25**, as represented by the ellipses **2540**.

Payment information **2508** can be any type of credit card, bank account, or other financial information that might be used in a secure communication payment through or with the vehicle **100**. Similarly, the PIN **2512** can be any type of PIN associated with one or more of the financial instruments provided in the payment information **2508**. These PINs may be created by the third-party financial institutions and given to the user. The user may enter the PIN **2512** into the vehicle **100** through a user interface, and the vehicle can store the PIN **2512** in data structure **2504**.

The IDs **2516** may be any type of information used with the payment information **2508**. Thus, the IDs **2516** can include the name on a credit card, an alias, or some other information associated with the payment information **2508**. The address **2520**, similar to the IDs **2516**, can be the address for the user of the payment information **2508**. As such, the address **2520** can be the home address, business address, or some other type of address associated with the user having payment information stored in field **2508**.

Limits **2524**, preferences **2528**, and rules **2532** can be user-created fields, may be automatically set, or learned, by machine-learning, based on repetitive processes of the user while in the vehicle **100**. Limits **2524** can be any limit on any type of secure communication or secure transaction used with the vehicle **100**. These limits **2524** can be in dollars, in a number of transactions, or some other type of limit. Limits **2524** can be associated with the vehicle **100** or may be

associated with two or more vehicles and thus may limit transactions across all types of vehicles the user may be associated therewith. Preferences **2528** can be any type of financial or behavior preference of the user. Behavior preference **2528** can be a determination of the desires or wants of a user based on their behavior. For example, if a user buys coffee every morning at a certain Starbucks, that coffee-buying event at the Starbucks can be a preference of the user stored in field **2528**. The rules **2532** can be any type of information dictated by the user to control secure communications or transactions with the vehicle **100**. For example, the user may preauthorize certain types of transactions or communications with the vehicle **100**, or others may not be preauthorized. As such, this preauthorization may be included in the rules field **2532**.

Data system **2600** can include one or more types of information regarding a user's behavior or information about the vehicle **100** associated with the user may be as shown in FIG. **26**. Each user may have their own type of information stored in the data system **2600**, as represented by ellipses **2628**. The information may be stored in the data structure **2604** that includes one or more of, but is not limited to: a product services field **2608**, a route field **2612**, a triggering events field **2616**, and/or battery rules field **2620**. There may be more or fewer fields than those shown in data structure **2604**, as represented by ellipses **2624**.

The product services field **2608** can include any type of product or service bought by the user while operating the vehicle **100**. For example, the products or services **2608** can represent such things as food purchases, gasoline purchases, car wash purchases, toll purchases, parking purchases, or other types of events that occur with and/or are associated with the vehicle **100**. The lists of products and services **2608** may also include a context about when or where things were bought, what time the user bought them, how often they bought them, and other types of information. As such, this information of products and/service purchases **2608** can be generated and developed into preferences **2528**, as explained previously with FIG. **25**.

An embodiment of one or more routes taken by the user may be stored in route field **2612**. These routes **2612** may be the consistent or common routes taken by the user and may also include information about what types of products or services may be offered along those routes. This information **2612** can allow the vehicle **100** to present options to the user or conduct automatic communications or transactions along such routes **2612**.

Triggering events **2616** may be predetermined events that may cause certain purchases or communications to be conducted automatically by the vehicle **100**. For example, a triggering event **2616** of inclement weather may cause the user to automatically purchase heightened map and weather data for the vehicle display. In other events, triggering events **2616** may be set once the user enters the vehicle **100** before conducting a drive. For example, a user can establish what communications or transactions are preauthorized for that drive when the triggering event **2616** of starting the vehicle occurs.

Battery rules **2620** can be what type of actions may be allowed for charging, discharging, changing, or managing the battery charge. These battery rules **2620** can include one or more of, but are not limited to: where batteries may be charged or replaced, where a vehicle **100** is allowed to get a charge without authorization, and other types of information. As such, the battery rules **2620** can manage the financial transactions conducted and associated with the battery.

An embodiment of a signaling diagram between the vehicle **100** and a user **220** may be as shown in FIG. **27**. This signaling arrangement shown in FIG. **27** may occur when the user enters the vehicle **100** and then begins to drive the vehicle **100**. Upon entering the vehicle **100**, the user **220** may start the vehicle **100** or generate an event with the vehicle **100** that indicates a drive is about to begin.

The vehicle **100** may then request the user's username **2412** and password **2416**, in signal **2704**. The username and password request may be sent to a user interface displayed on a display associated with the vehicle **100**. In other configurations, the username **2412** and/or password **2416** may be requested and provided to the vehicle **100** with a user interface event and an audio or other type of response or gesture, in signal **2708**. The response from the user **220** can provide the credentials for the vehicle **100** to authenticate the user. In some configurations, the dongle **2008** may send a code **2712** to the vehicle **100**. As the dongle **2008** is associated with the user **220**, this code **2712** can identify the user to the vehicle **100**. Along with the code **2712**, the dongle **2008** may send a function or a request for an operation, optionally in step **2716**. A function can be some type of request for the vehicle to perform an operation such as starting the vehicle **100**, opening doors, opening windows, or doing some other kind of task. This function **2716** can also be a request to conduct a secure communication or transaction that may be authorized only with the dongle **2008**. As such, even if the user's vehicle **100** is stolen, without the dongle **2008**, financial transactions may not be conducted.

Biometrics may also be collected by vehicle **100**, in signal **2720**. Sensors **5437**, within the vehicle **100**, may obtain biometric information from the user **220**. This biometric information can be a visual recordings of the user's face, may be a voice recording, may be some other physical characteristics recorded by the sensors **5437** within the vehicle **100**. This biometric information can be compared to biometrics information **2408**. If there is a positive comparison with the biometric information **2408** and the user is identified, the vehicle **100** may send an identity verification signal **2724** back to the user **220**. The vehicle **100** may present some identity verification to the user interface to allow the user to understand that they have been identified. The user **220** may respond by providing an okay signal **2728** back to the vehicle **100**. The okay signal **2728** may be given in a user interface or may be a voice or a hand gesture within the vehicle **100** and recorded by the vehicle sensors **5437**.

In some configurations, the vehicle **100** may ask for a preauthorization or a half-token provided by the user, in signal **2732**. Here, the vehicle **100** may present a user interface or an audio request to the user **220** requesting whether the user wishes to authorize certain automatic communications or automatic transactions before the drive begins. If the user does desire such type of automation, the user **220** may send an ack or acknowledge signal **2736** back to the vehicle **100**. The ack signal **2736** can again be a user interface input, may be a voice command, some type of gesture or other type of response between the user **220** and the vehicle **100**.

The vehicle **100** may then send a second token, e.g., an order, **2740** to a user **220**. The order **2740** may be an automated request to a third party for some type of product or service. This order **2740** may be presented to the user interface to allow the user to acknowledge whether the order should be made in signal **2744**. If acknowledged, the vehicle **100** can confirm the purchase to the user, in signal **2748**, after making the proper purchase, transaction and/or com-

31

munication with the third party. This confirmed purchase then may be acknowledged by the user 220, in signal 2752.

Another embodiment of a signaling process between a vehicle 100 and a second party, such as a retailer 2804, may be as shown in FIG. 28. An initial signaling 2808 for establishing communications between the vehicle 100 and the second party 2804 may involve nearfield communications, such as through an RFID device, wireless communications either through a cellular or 802.11 link. Regardless of the format, the vehicle 100 and the second party 2804 can establish some communication connection through signal(s) 2808.

The vehicle 100 may then send a half-token or preauthorization for some type of good or service or other type of secure communication to the second party, in signal 2812. The half-token signal 2812 may include some secure communication data, but may not be a complete set of data for the second party to conduct an activity without a second set or portion of information. Thereinafter, the vehicle 100 may send a preorder or other type of secure communication 2816 to the second party 2804; the half-token 2812 may authenticate or authorize a transaction, the order may be the next step in identifying what is desired by the user of the vehicle 100. The vehicle 100 may then send an identifier 2820 for identifying the user and/or vehicle. This information 2820 can be sent in a long-distance communication without the vehicle/user in the physical proximity of the second party 2804. As such, the identifying information 2820 can later be used to identify that vehicle/user when the vehicle 100 does arrive within physical proximity of the second party 2804.

Sometime thereinafter, after vehicle 100 drives to second party 2804 and a second communication establishment may be conducted with signals 2824. The vehicle 100 can establish communications that require physical proximity, for example, nearfield communications or some other type of communication connection. Thereinafter, the second party 2804 may send a request to identify or verify the identity of the vehicle 100 and/or user 220, in signal 2828. This signal 2828 may be a request for more information to complete the token. The vehicle 100 can send an acknowledgement signal 2832 to the second party 2804.

The second party may then send a confirm order signal 2836, which may be acknowledged by the vehicle 100 in signal 2840. The confirm order 2836 may cause the vehicle 100 to present information to the user interface for the user 220 to confirm the order and/or information previously sent by the vehicle 100. Upon acknowledging the order, the user 220 can authorize the vehicle 100 to send billing information, in signal 2844. Billing information 2844 may be the second, matching half-token sent to the second party 2804. Billing information thus may complete the information needed by the second party 2804 to conduct or provide the service or good ordered in signal 2816. The second party 2804 may acknowledge the billing information in signal 2848.

FIGS. 28 through 41 provide user interfaces that may be presented on the display 5472 within the vehicle 100. These user interfaces may be provided in a heads-up display, in a display in the head unit, or some other type of display. The user interfaces can include both dynamic and static components. The dynamic components can receive user input and be user-selectable devices. The dynamic components can include tabs at the top of the user interface 2912, which, when selected, provide for different types of user interfaces. Further, they may include menus, dropdown menus, text-

32

boxes, radio buttons, or other types of selectable devices that provide user input into the vehicle's processing system 5608.

FIG. 29 provides a first user interface 2900 to allow the user to enter financial information into the vehicle 100 to be securely stored therein. The display 2904 can include a frame and a display portion 2908 to a window or other type of user interface (while a window is generally use in a desktop environment, the term "window" here can describe a portion of content displayed together where the content is generally interrelated). The window or user interface may be associated with one of two or more tabs 2912. In FIG. 29, window 2908 can be associated with financial information tab 2912a, which has different visual indicia, for example a shading or different color for tab 2912a compared to the other tabs 2912b through 2912d.

To enter financial information, the user may be provided with an indication 2916 that the user can select a radio button 2920 to enter financial information. If selected, the user can then enter information under different categories indicated by static information displays. For example, the name on the credit card may be presented in indication 2924 where the user could enter their name in fields 2928a and 2928b. A credit card number indication 2932 provides for a text box 2936 that allows the user to enter their credit card number into text box 2936. The billing address field 2940 allows for the user to enter their street, city, state, and ZIP code in fields 2944, 2948, 2952, and 2956, respectively. A security code field 2960 allows the user to enter their security code (CVV) from the back of their credit card in field 2964, or their PIN for the credit card in field 2968. Through the user interface 2908, the user can enter all their financial information which then may be used automatically by the vehicle 100 in secure communications.

Another user interface 3000 is shown in FIG. 30A. This user interface embodiment 3000 includes an information box 3004. The box or window 3004 includes a banner 3008 indicating that the user can use this interface to approve contactless payments or authorize those contactless payments. An icon 3012 indicates that the user interface 3004 provides for information or input and requires user attention.

A dropdown menu or selection menu, having banner 3016, allows a user to approve transactions for different types of events. For example, the user may, according to the banners 3020, 3028, and 3036, approve transactions for a particular route, time period, or per transaction by selecting one of the radio buttons 3024, 3032, or 3040, respectively. For any one of the items—for instance, the time period selection 3028, 3032—a dropdown menu 3044, with the banner 3044 for time limit, may be presented. Thus, for the time period selection 3028, the user may have different types of time periods from which to select. For example, the selections 3048, 3056, and 3064 indicate that the user can select approval of transactions or payment authorizations for a one-hour time period, a two-hour time period, or for a particular commute, by selecting radio buttons 3052, 3060, 3068, respectively.

Another embodiment of a window user interface 3072 may be as shown in FIG. 30B. Another popup window 3072 for contactless payment authorization having icon 3012 may also be presented. Here, the user may have a user-selectable device, for example, a button 3076, that allows the user to approve all contactless payments rather than enter in the information shown in FIG. 30A.

Another user interface 3100 for authorizing a particular transaction may be as shown in FIG. 31. A window 3104 that provides an alert may be shown in the user interface 2908.

33

The alert **3104** can include an information box **3108** that describes some transaction or pre-order. This pre-order may be for a vendor provided in banner **3112**. The pre-order items may be listed in section **3116** with a cost or price for the order in portion **3120**. This information may be indicative of a pre-order or an order made automatically by the vehicle **100**. The user may then approve this preauthorization or pre-order by selecting a user-selectable device, for example, the button **3124**.

Another embodiment of a user interface **3200** that provides for placing ads within the user interface **2908** of the vehicle **100** may be as shown in FIG. **32**. In this configuration, a popup window **3204** containing an advertisement **3208** may be shown in the user interface **2908**. This advertisement **3208** may be associated with a specific product commonly used by the user or may be a product available on the route currently being taken. The user may pre-order that item by selecting user-selectable device **3212** to order the product or service provided in the advertisement **3208**.

Another approval or authorization user interface **3300** to conduct a transaction may be shown in FIG. **33**. The user interface **2908** includes another window **3304** to conduct an order. A typical or usual order may be listed in section **3308**. For example, the current order is for a coffee from a particular vendor. This order may be a preference gleaned from the preferences information **2528**. By presenting this order and selecting user-selectable device **3312** through user input, the user can authorize the vehicle **100** to automatically purchase such item.

Further authorization information that may be used for conducting transactions through the vehicle **100** may be as shown in FIG. **34**. The user interface **3300** can include another window **3304** in interface **2908**. The user interface window **3304** can include further information required by a user to complete a transaction. In this case, PIN information that may be the same or similar to PIN **2512** may be provided by the user. The field **3308** allows the user to enter the PIN through input through a keyboard presented on the user interface or through a phone or other device. This PIN **2512** may then be used to present the second half-token to the vendor for completing a transaction. It may also be possible for the user to select some other type of identifier by selecting user interface device **3312**. Other identifiers can include such things as a biometric identifier, username and password, or some other type of identifier explained previously.

Another user interface **3500** for approving an order that was already preordered may be as shown in FIG. **35**. Here, user interface **2908** includes the window **3504** for allowing approval of payment. The window **3504** includes a box **3508** that provides the information about the order that is to be completed. This box **3508** may include a banner **3112** and a portion **3116** for including the items ordered and a portion **3120** including the cost or price of the order. This order may be finally approved by the user by selecting the user interface device **3512** through touch input or some other type of input.

Another user interface **3600** for approving transactions for a particular type of event may be as shown in FIG. **36A**. A window **3604** may be presented in user interface **2908**. The window **3604** can include a dropdown menu **3608** with user-selectable device **3616** to select the type of event for which to approve transactions. The banner **3612** can list what type of approval is being given. Selecting the user-selectable device **3616** can cause a dropdown menu to provide further granularity in the selection. For example, a time limit may be selected by selecting radio buttons **3620**,

34

3624, and/or radio button **3628**. As such, the user can provide for authorization of secure communications and payments for a particular time period using user interface **3604**.

Another embodiment of a user interface **3632** that includes a popup information box **3636** may be as shown in FIG. **36B**. Here, the user may have already-completed or automatic orders completed. Box **3636** provide the user information about how much time is left for transaction approval in countdown clock **3640**. This clock **3640** counts down from some certain amount of time (e.g., five (5) minutes) until the pre-order is canceled, and the transaction is left unapproved.

A user interface **3700** for allowing a user to approve transactions or communications along a particular route may be as shown in FIG. **37**. Here, the user interface **2908** may include a window **3704** that is associated with a map **3708**. This map **3708** may include a projected route **3712**. The window **3704** may also include a popup box **3716** with banner **3720** that indicates that by selecting button **3724**, the user can approve any transaction along the route **3712**. In this way, the user is allowed to complete secure communications or transactions along route **3712** through the vehicle **100** without requiring further user input during this travel.

Another user interface **3800** similar to user interface **3704** shown in FIG. **37** is provided in FIG. **38**. Here, further information is provided about the route **3712**, such as weather data **3804**. A user may preapprove for enhanced navigation or enhanced data. This approval allows the user interface **3704** to provide weather information **3804** or other types of data for which the user must pay. Thus, if inclement weather is imminent, the vehicle **100** may make an automatic transaction to provide this further information and pay for that information. These types of transactions may be pre-authorized by the user.

An embodiment of a user interface **3900** for receiving and/or providing financial information about a passenger in the vehicle **100** may be as shown in FIG. **39**. The fields **2916-2968** are the same or similar to those fields **2916** through **2968** as shown in FIG. **29**. As such, these fields **2916-2968** will not be explained further except that the fields **2916-2968** are used to enter information for a passenger rather than a driver, as represented by tab **2912b** having different visual indicia than tabs **2912a**, **2912c**, or **2912d**.

Two additional fields **3972**, **3976**, in user interface **3900**, allow the passenger to enter their mobile device information. This mobile device information **3972** and **3976** allows the vehicle **100** to identify the user and communicate the passenger's financial information when being identified within the vehicle **100**. Also, having the mobile device information **3972**, **3976** allows the vehicle **100** to conduct transactions through the mobile device rather than through the vehicle **100**, if desired.

Another user interface **4000**, within display **2908**, related to user preferences, as represented by different visual indicia on tab **2912c**, may be as shown in FIG. **40**. User preferences may include a window **4004** that includes various fields **4008** through **4052** for specifying different preferences for how secure communications or financial transactions may be conducted by the user. Each field **4008**, **4016**, **4024**, **4032**, **4040**, and **4048** may have an associated radio button **4012**, **4020**, **4028**, **4036**, **4044**, and **4052** to receive user input that indicates preferences for secure communications.

The fields **4008-4052** may include selections for automatic payments (allows the vehicle **100** conduct payments without user input), pre-authorizations (requires the vehicle

35

100 to get authorization for orders), approve payment (requires the vehicle 100 to get approval for payments), use of PIN (requires the vehicle 100 to obtain a PIN for payments), store usual orders (requires the vehicle 100 to store common or recurring orders), allow passenger payment (allows a passenger to associated payment information with the vehicle 100 and make payments). Any one of these preferences may be provided or selected by selecting radio buttons 4012, 4020, 4028, 4036, 4044, and 4052.

An embodiment of a user interface 4100 associated with event preferences, as represented by tab 2912d having different visual indicia, may be as shown in FIG. 41. Window 4104 may be provided that provides for the vehicle 100 to conduct particular procedures if certain, future events occur. These events may include weather alerts 4108, emergency battery alerts 4116, police action alerts 4124, or enable internet orders 4132. Any of these different selections 4108, 4116, 4124 may be completed by selecting one or more of the radio buttons 4112, 4120, 4128, 4136. Weather alerts 4108 allow the user to automatically purchase further information about weather if necessary. Emergency battery events 4116 can allow for purchasing or pre-purchasing battery charging if necessary. Police action event 4124 can allow for communications of routes or information on the route display when there is a police action. Finally, internet orders 4132 may allow the vehicle 100 to purchase services or goods through the Internet if radio button 3146 is selected.

An embodiment of a method 4200 for receiving and storing user secure information may be as shown in FIG. 42. Generally, the method 4200 starts with a start operation 4204 and ends with operation 4240. The method 4200 can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. 42. The method 4200 can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method 4200 may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/or a Field Programmable Gate Array (FPGA). Hereinafter, the method 4200 shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. 1-41 and 54A-56.

A processor or CPU 5608 can receive an event, in step 4208. The event can be the starting of the vehicle 100, a connection made by a user with the dongle 2008, or another event. This event can cause the CPU 5608 to present a user interface 2900 on a display 5616.

In step 4212, the CPU 5608 renders the user interface 2900 for displaying on the output device 5616. The output device 5616 can include the screen 2904 provided in the head unit, a heads-up display, or some other type of display within the vehicle 100. From the user interface 2900, the CPU 5608 can receive input into the user interface 2908, in step 4216. The input can be the entry or determination of whether or not the user desires to enter financial information to be associated with the vehicle 100.

In step 4220, the CPU 5608 determines whether the user desires to enter secure information. For example, the user may select radio button 2920 to alert the CPU 5608 that the user desires to enter secure information. If secure information is desired to be entered, the method 4200 proceeds "YES" to step 4224. However, if no information is desired to be entered, method 4200 proceeds "NO" to step 4240.

36

In step 4224, the CPU 5608 receives secure input through the user interface 2900. Here, the user may enter information about their finances or financial information in fields 2924 through 2968. This information may be provided to the CPU 5608, or the information may then be buffered in memory 5636. In step 4228, the CPU 5608 can encrypt the information and store it within memory 5636. The encryption key may be some secret shared between the user and the vehicle 100. This encryption information may be provided in another user interface, through voice input, or through some other input. Further, there may be other types of encryption keys that may be associated with biometrics or other information.

In step 4232, the CPU 5608 stores the encrypted information in secure storage within the vehicle 100. Secure storage can be a separate secure area of storage 5636. In some configurations, this secure storage may be accessed differently and may be physically separated from working memory 5636. In other configurations, the secure storage may be a separate part of the working memory 5636 that may be accessed with different protocols. Upon storing this information, the CPU 5608 associates the user of the vehicle 100 with the encrypted information, in step 4236. Here, the user's biometrics 2408, username 2412, password 2416 etc. may be stored with data structure 2504 or other information to associate the user with the information.

A method 4300 for encrypting the sensitive information, as described in conjunction with FIG. 42, may be as shown in FIG. 43. The method 4300 can be conducted by the CPU 5608 for encrypting the sensitive information in the memory 5636 of the vehicle 100. Generally, the method 4300 starts with a start operation 4304 and ends with operation 4324. The method 4300 can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. 43. The method 4300 can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method 4300 may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/or a Field Programmable Gate Array (FPGA). Hereinafter, the method 4300 shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. 1-42 and 54A-56.

In step 4308, the CPU 5608 can receive sensitive information, as described in conjunction with FIG. 42. In step 4312, the CPU 5608 can determine an encryption key based on the user and/or vehicle information. As such, the CPU 5608 can associate the VIN 2436, the ESN 2440, the engine code 2444, or other information associated with the vehicle 100 with the user and the user information, for example, biometrics 2408, username 2412, password 2416, mobile device information 2420, dongle code 2424, etc. This user and vehicle information may be associated together to create the encryption key.

In step 4316, the CPU 5608 can encrypt the sensitive information received in step 4308 with the key. This key would be associated with both the vehicle and the user and may not be accessed without the presence of the user within the vehicle 100 or if the user is not associated with the vehicle 100. As such, if the vehicle 100 is stolen, the information cannot be accessed. Further, another user cannot enter the vehicle 100 and use the information, and the user may not use some other vehicle for secure communications

with the information. The encrypted information may then be stored in working memory **5636** or in storage **5620**, **5624**, in step **4320**. As such, the CPU **5608** can permanently store the information in secure storage as encrypted information that becomes difficult to use except when the user is associated with the vehicle **100**.

Thus, operator or owner financial information and user biometric data can be stored in an encrypted memory **5624**, **5636** on the vehicle **100**, such as in encrypted RANI or other storage medium. If RAM were to be encrypted, it must be decrypted automatically for usage by the CPU **5608**. In some configurations, the CPU **5608** does not operate on the RANI directly. The CPU **5608** loads code and data from the RAM into the CPU's internal caches. The loading/unloading process is transparent for both the applications **5644** and the operating system **5640**.

An automatic RAM encryption system can be embodied in hardware, for example, in the CPU **5608**. If encryption were to be done in the RAM, an attacker may be able to freeze the RANI and then plug the RANI into a different machine to extract the information. In a similar manner, decryption in an external RAM controller may not prevent active attacks. The automatic RAM encryption system could also defeat a cold boot attack or a platform reset attack in which an attacker, with physical access to a computer, is able to retrieve encryption keys from a running operating system after using a cold reboot to restart the machine. This type of attack relies on the data remanence property of DRAM and SRAM to retrieve memory contents that remain readable in the seconds to minutes after power has been removed.

In additional or alternative configurations, disk encryption techniques can also be employed. When a user first powers on the vehicle and before the operating system **5640** can boot up, the user must unlock his or her disk by supplying the correct encryption key. The files that make up the operating system are on the encrypted disk, so there is no way for the computer **5608** to work with the operating system **5640** until the disk is unlocked.

In some configurations, inputting a security credential, like a passphrase or biometric identifier, does not unlock the whole disk but unlocks an encryption key, which in turn unlocks everything on the disk. This indirection allows a user to change his or her passphrase (if a passphrase is used) without having to re-encrypt the disk with a new key and also makes it possible to have multiple passphrases, other security credentials, or combinations thereof that can unlock the disk, for example, if the operator or owner were to add another user account to the on board computer.

Other configurations may defeat a cold boot attack; encryption software periodically flushes the encryption key every few minutes when not in use. The user would be required to re-authenticate himself or herself to the on board computer system **5608**, after expiration of a selected period of time. A user-friendly transparent proximity solution can exist where the vehicle remote keyless system (the dongle **2008**) acts as a type of wireless device to transmit a unique code or signal that can cause the controller **5608** to securely access the encryption key whenever needed or otherwise cause the encryption key to be refreshed periodically.

As will be appreciated, keyless remotes **2008** contain a short-range radio transmitter, and must be within a certain range, usually 5-20 meters, of the vehicle **100** to work. It sends a coded signal by radio waves to a receiver unit in the vehicle **100**, which performs a selected function, such as locking or unlocking the door. Alternatively, the secure key can be derived from the coded signal itself by a known key generation algorithm (e.g., in which the seed is the coded

signal or the coded signal along with another identifier, for example, a biometric indicator of a user or all or part of the VIN **2436** of the associated vehicle **100**.

An embodiment of a method **4400** for a driver and/or passenger to enter secure information into the vehicle **100** may be as shown in FIG. **44**. Generally, the method **4400** starts with a start operation **4404** and ends with operation **4440**. The method **4400** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **44**. The method **4400** can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method **4400** may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/or a Field Programmable Gate Array (FPGA). Hereinafter, the method **4400** shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. **1-43** and **54A-56**.

In steps **4408**, **4424**, the vehicle **100** can sense the presence of a driver or passenger, respectively. The internal sensors **5437** may sense the presence of a person within the vehicle **100**. This person may be a driver or a passenger. The information gleaned from the sensors within the vehicle **100** may then be provided to the CPU **5608**. In steps **4412**, **4428**, the CPU **5608** can receive the biometric information associated with the driver/passenger. This information may then be used to determine whether or not the passenger or driver is previously associated with the vehicle **100**. The biometric information may be as stored in data structure **2404** in field **2408**.

With the biometric information, the CPU **5608** can compare the received information with the information in field **2408** to determine if the driver or passenger is authenticated, in steps **4416**, **4432**. If the received biometric information from internal sensors **5437** is the same or similar to stored biometric information **2408**, the driver/passenger is authenticated. As such, the CPU **5608** can determine if the driver/passenger is authenticated in steps **4420** or **4436**. If the information does compare, then the driver/passenger is authenticated and the method **4400** proceeds "YES" to step **4448**. However, if the driver or passenger is not authenticated, the method **4400** proceeds "NO" to step **4440**, where the CPU **5608** determines if other information is available.

Other information may include a username **2412**, a password **2416**, mobile device information **2420**, etc. that may be used to authenticate the user. If there is other information, the CPU **5608** can gather or obtain that information, in step **4444**. Thus, the CPU **5608** may request the username or password from the user, connect or couple with the mobile device or the dongle, or may conduct other operations to gain that information. If the other information is valid and compares to the information stored in data structure **2404**, the user may be authenticated again. However, if no other information is available, the operation may end without the user being authenticated or allowed to do secure communications. If the user finally is authenticated, then in step **4448**, the vehicle processor **5608** can allow secure interactions between the vehicle **100** and third parties.

Based on a driver's preferences (e.g., user goes to Starbucks every morning, etc.), the onboard computer automatically pre-authorizes a transaction at a particular time and/or in response to a particular detected location of the vehicle **100**. This pre-authorization can be done by observation and

based on historic user behavior or spatial proximity of the vehicle **100** to the vendor (e.g., range of a transceiver on the vehicle **100** to a transceiver at the vendor or GPS-based locations of the vehicle **100** and vendor).

In this example, the vehicle **100** can gate release information to avoid unintended purchases. This gate-release of information can be done by an interactive user interface (UI) on the vehicle **100**. Presumably, the vehicle **100** may identify a potential purchase by the driver, such as by receiving and pre-filtering purchase options before presenting, to the operator, the option. Otherwise, the operator could be swamped by options while he or she is driving through an area loaded with retail stores. The trigger could be based on prior driver behavior, proximity of the vehicle **100** to a vendor, a state of the vehicle **100** (e.g., stopped, in motion, velocity of vehicle **100**, etc.), and the like. There may also be operator authentication prior to the function of pre-purchase being activated. This approval can prevent a thief or family member from using the function without authorization.

In some configurations, the vehicle **100** may anticipate payments to be made, or opportunities to pay, based on a number of factors associated with the vehicle **100** or vehicle state, such as speed, turn signal activation, road or lane change, and the like. In response to detecting one or more of these factors, the vehicle **100** may present the user with a context-sensitive prompt designed to provide an advanced authorization for payment for a good or service. This advanced authorization for payment can save authentication time, processing time, and/or waiting time associated with payment stations, providing a quick transactional exchange.

By way of example, a user may be approaching a gas station and a drive-through coffee shop in a vehicle **100**. Upon reducing speed, directing, and/or positioning the vehicle **100** into proximity with the coffee shop, the vehicle **100** may prompt the user for advanced authorization for the coffee shop (e.g., rather than the gas station or any other service). The user may accept the advanced authorization (e.g., for an open-amount, particular amount, etc.). Additionally or alternatively, the vehicle **100** may prompt the user for authorization for a particular drink and/or group of drinks, food, etc. The user may accept a "usual" order (e.g., based on historical data, preferences, and/or voice command), and as the user drives up to the "ordering" window/kiosk, the user may be directed to the "pickup" window where the drink and/or food is waiting for the user and has already been paid for by the vehicle authorization made.

In some configurations, payments made by a vehicle **100** may be conditionally authorized ahead of a transaction time for a limited period of time. This pre-transaction authorization may be restricted and/or only active for a particular time surrounding a determined movement of the vehicle **100**. In one example, a user may enter a destination into a driving-navigation program (e.g., GPS navigation system associated with the vehicle **100**, etc.). The vehicle **100** may determine a particular path of travel for the vehicle **100** and determine that specific routes require payment (e.g., toll roads, parking garages, congestion tax fees, etc.) or requires charging to be performed. In response to determining that the specific routes require some type of payment, the vehicle **100** may determine to authorize the predicted payments required on the specific routes. This authorization may be valid only for a limited time, while the vehicle **100** is traveling along the route, and/or as long as the vehicle **100** has power, etc. For instance, if the user deviates from the path, the pre-transaction authorization is revoked, preventing any accidental or unintended payments.

A driver may generally associate their payment information with a vehicle **100**. Yet, sometimes, the vehicle **100** may transport multiple parties, for example, in a car pool. If a person other than the driver desires to pay for a good or service, the person may not be able to utilize the vehicle's payment system. Thus, the vehicle **100** may be capable of adding multiple buyers/payers to the payment system by associating those other people with the vehicle **100**.

A passenger may enter the vehicle **100**. The vehicle **100** may sense the presence of the passenger by receiving a phone signal, by receiving sensor data from sensors associated with the passenger (e.g., activation of the airbag, heat, weight, etc.), etc. A user interface presented on the head unit or in a screen of the entertainment system may be prompt the passenger with the option to associate financial information with the vehicle **100**. If the passenger participates, the passenger can utilize the payment system. Further, the vehicle **100** may use that person's cell or phone for transactions when the passenger is paying. Any stored data may be erased when the passenger leaves the vehicle **100**, which prevents reuse of the payment information. Or, in the alternative, the payment information may be dormant until the user is identified in the vehicle **100** again or their mobile device enters the vehicle **100** again. In some situations, the passenger and driver can use the vehicle payment system to split payments, for example, for battery charging, food, hotel, etc.

An embodiment of a method **4500** for allowing contactless secure communications may be as shown in FIG. **45**. Generally, the method **4500** starts with a start operation **4504** and ends with operation **4532**. The method **4500** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **45**. The method **4500** can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method **4500** may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/or a Field Programmable Gate Array (FPGA). Hereinafter, the method **4500** shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. **1-44** and **54A-56**.

The CPU **5608** can receive information from internal sensors **5437** that indicate the presence of a user within the vehicle, in step **4508**. As described in conjunction with FIG. **44**, the internal sensors **5437** can send information to the CPU **5608** indicating that a person is within the vehicle **100**. In step **4512**, the CPU **5608** can identify the person by comparing the biometric information received from the internal sensors **5437** with biometric information **2408** in data structure **2404**. In other configurations, the user may be identified by the dongle **2008**, mobile device, the username **2412** and password **2416**, or some other information.

Based on the identity of the person, the CPU **5608** can retrieve a profile for the person, in step **4516**. The profile may include data structure **2504** or data structure **2604**, as described in conjunction with FIGS. **25** and **26**. The profile of the person may include preferences **2528** or rules **2532**. The CPU **5608** can determine if a user authorizes contactless communications, in step **4520**. Here, the CPU **5608** may check the preferences **2528** or rules **2532** to determine if the user has authorized contactless communications. In other situations, a user interface may be provided to the user to allow for contactless communications, such as window

41

3004, window 3012, etc. If the user does desire to allow contactless communications with the vehicle 100 and a third party, the method 4500 proceeds “YES” to step 4524. If the user does not desire contactless communication, the method 4500 proceeds “NO” to step 4532.

In step 4524, the vehicle 100 may enter a geographic location. The geographic location can be a route commonly taken by a user of the vehicle 100. This geographical location or route may be as described in conjunction with FIG. 37. Upon entering this location, the CPU 5608 can send contactless communications automatically, in step 4528. For example, the vehicle 100 can use preferences 2528, rules 2532, or other information in data structure 2604 to send automated purchases or other types of secure communications while in the geographic location.

An embodiment of a method 4600 for a vehicle to make secure communications may be as shown in FIG. 46. Generally, the method 4600 starts with a start operation 4604 and ends with operation 4628. The method 4600 can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. 46. The method 4600 can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method 4600 may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/or a Field Programmable Gate Array (FPGA). Hereinafter, the method 4600 shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. 1-45 and 54A-56.

A vehicle 100 may enter a location, in step 4608. For example, the vehicle 100 can enter a drive-through, a toll lane, or some other type of location. The vehicle 100 may then determine if a radio frequency (RF) field is detected at one of the two or more RF devices 2004, as described in conjunction with FIG. 20, in step 4612. The CPU 5608 may be provided signals from the RF devices 2004 to determine if an RF field is detected. In step 4616, the CPU 5608 can determine which of the RF devices 2004 has the best connection or the highest field strength. For example, if the user is at a gas station and device 2004b is nearest, to a gas pump with an RF transceiver, device 2004b may have the best connection, as the field strength there may be higher than at device 2004c or 2004a. If device 2004b has the best connection, then that device 2004b may couple with the RF transceiver at the third party.

The CPU 5608 can then determine if the user authorizes contactless communication, in step 4620. As such, the CPU 5608 can access preferences 2528, rules 2532, or other information in data structure(s) 2504, 2604, etc. to determine if contactless communications are allowed. Further, the user interface 3072 or 3004 may be presented to the user and a determination made if the user provides an authorization of contactless communications. If contactless communications are not authorized, the method 4600 proceeds “NO” to step 4628. However, if contactless communications are authorized, method 4600 proceeds “YES” to step 4624. In step 4624, the CPU 5608 can automatically send contactless communications through the RF device 2004 to the third party. These communications can include financial information or other secure information from the vehicle 100. As such, the vehicle 100 can be an extension of the user in delivering information to a third party.

42

The method 4600 provides for devices at different location that allow for information exchange using various communication standards (e.g., near field communications (NFC), BLUETOOTH™ Low Energy (BLE), radio frequency identification (RFID)). The devices can be mounted or incorporated into the vehicle 100 in various locations, e.g., a wing mirror, a windshield, a roof, etc. A vehicle 100 may have a communication device, e.g., an NFC or RFID device, installed in such a way that the device 2004 may communicate with external devices to conduct transactions including contactless payments.

The devices 2004 may be passive or active. For example, the communication device 2004 may be installed on or near the outer surface of the vehicle 100. The device 2004 may be placed in many areas of the vehicle 100 to communicate with external devices in a number of situations. A driver side device 2004c may be used to communicate and conduct contactless payment transactions in drive-thru situations. An overhead or under-carriage device 2004a may be utilized in situations such as toll-lanes or parking garages to similarly conduct payment transactions while the vehicle 100 may be moving. A communication device 2004c may be placed on or near the gas tank such that the device 2004c may conduct a payment transaction with a gas tank nozzle or gas pump. The device 2004 may be in communication with an onboard computer 5608 placed inside the vehicle 100. The device 2004 may be used to store and share any amount of information.

An embodiment of a method 4700 for conducting secure communications with the third party may be as shown in FIG. 47. Generally, the method 4700 starts with a start operation 4704 and ends with operation 4728. The method 4700 can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. 47. The method 4700 can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method 4700 may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/or a Field Programmable Gate Array (FPGA). Hereinafter, the method 4700 shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. 1-46 and 54A-56.

The vehicle 100 begins secure communications with another party, in step 4708. Here, the processor 5608 may communicate through the communications system 1900 to another entity. The communication may be a remote communication used through a wireless or cellular system. In other embodiments, it may be a nearfield communication. The third party may send a request for authorization for some type of communication. In such a case, the vehicle 100 receives a requirement for authorization by the user, in step 4712. In other situations, an internal rule 2532 or some other event may cause the processor 5608 to require authorization by the user.

In step 4716, the processor 5608 may display a user interface (e.g., user interface 2904) to provide authorization to the vehicle 100. This user interface may be user interface 3000 shown in FIG. 30A, window 3072 in FIG. 30B, or some other window as described herein. The processor 5608 can then determine if the user authorizes the contactless communication, in step 4720. For example, if the user provides input into button 3076, then the processor 5608 can

determine that contactless communication is authorized. If such authorization is given, the method **4700** proceeds “YES” to step **4724**. However, if no authorization is given, method **4700** proceeds “NO” to end operation **4728**.

In step **4724**, the processor **5608** can create an authorization based on the authorization given by the user and send such authorization through the communications system **1900** to the other entity. As such, the processor **5608** can provide authorizations for secure communications or other events, such as financial transactions, through a display and/or user interfaces on the vehicle **100** rather than through a mobile device or a device (e.g., a credit card terminal) associated with the other party.

User interfaces for authorization of transaction may be provided in a head unit or other display (e.g., dash, heads-up display (HUD), etc.). An in-vehicle display and input device may be provided to conduct contactless payment transactions with external devices. When an external device initiates a payment transaction with a communication device of the vehicle **100**, a user inside the vehicle **100** may be presented with a means for authorizing the payment, for example, a user interface that accepts a PIN entry, a signature, fingerprint ID, retina scanner, etc. or another interface that provides a different type of authorization (e.g., voice authorization, gesture authorization, etc.). The means for authorization may be dependent on the amount or type of transaction involved. Authorization may take place prior to, during, or following the transaction. For example, in the case of toll-lanes, the payment may be authorized following the use of the toll-lane. For drive-thru restaurant transactions, the authorization may take place prior to the sale. For the authorization of the sale of gas, the authorization may take place immediately following the pumping of the gas and prior to sale.

In some embodiments, payments made by a vehicle **100** may be authorized ahead of a transaction time and/or for a limited period of time. This pre-transaction authorization may be restricted and/or only active for a particular time surrounding a determined movement of the vehicle **100**. In one example, a user may enter a destination into a driving-navigation program **5402** (e.g., GPS navigation system associated with the vehicle, etc.). The vehicle **100** may determine a particular path of travel for the vehicle **100** and determine that specific routes require payment (e.g., toll roads, parking garages, congestion tax fees, etc.). In response to determining that the specific routes require some type of payment, the vehicle **100** may determine to authorize the predicted payments required on the specific routes. This authorization may be valid only for a limited time, while the vehicle **100** is traveling along the route, and/or as long as the vehicle **100** has power, etc. For instance, if the user deviates from the path, the pre-transaction authorization is revoked, preventing any accidental or unintended payments.

Payment may be later authorized based on vehicle identification and later acceptance. When a vehicle **100** conducts a payment transaction, the transaction may be authorized based on a unique identifier associated with the vehicle **100** and/or geolocation information associated with the vehicle **100** and/or the driver. During the initial part of the transaction, the vehicle’s contactless payment system may deliver the payment information and information regarding the vehicle **100** and/or driver of the vehicle **100** (e.g., a half token). This information may be collected in other ways by the external payment device to support the authorization. For example, the external device may photograph the vehicle **100**, license plate, and/or driver. This information may be used to support the authorization for the transaction.

Such pre-transaction authorization may be useful in situations requiring the driver to manually enter an authorization, such as by PIN code, signature, etc., which may be inconvenient or impossible when driving. For example, the system may be used for payments made while the vehicle **100** is in motion, e.g., for paying while entering/exiting parking garages and/or for paying for toll-lanes.

In some embodiments, the vehicle **100** may anticipate payments to be made, or opportunities to pay, based on a number of factors associated with the vehicle **100**. These factors can include location, speed, proximity to a location, preference data, and/or historical information. In response to detecting one or more of these factors, the vehicle **100** may present the user with a context-sensitive prompt designed to provide an advanced authorization for payment for a good or service. This advanced authorization for payment can save authentication time, processing time, and/or waiting time associated with payment stations, providing a quick transactional exchange.

By way of example, a user may be approaching a gas station and a drive-through coffee shop in a vehicle **100**, upon reducing speed and/or positioning the vehicle **100** into proximity with the coffee shop, the vehicle **100** may prompt the user for advanced authorization for the coffee shop (e.g., rather than the gas station, or any other service). The user may accept the advanced authorization (e.g., for an open-amount, particular amount, etc.). Additionally or alternatively, the vehicle **100** may prompt the user for authorization for a particular drink and/or group of drinks, food, etc. The user may accept a “usual” order (e.g., based on historical data, preferences, and/or voice command), and as the user drives up to the “ordering” window/kiosk, the user may be directed to the “pickup” window where the drink and/or food is waiting for the user and has already been paid for by the vehicle authorization made in advance.

Multiple communications for authorization, based on geolocation, proximity, etc. may be prompted by a user interface, for example “Are you going to buy a burger?”, “Are you filling up for gas?”, and so on. The user interface may be set for certain speeds of vehicle, based on preferences, etc. An initial step is the communications could be the “advertisement” (e.g., “Would you like a Starbucks?”). This advertisement could appear in the display of the vehicle **100**. If the answer is “Yes”, a second step of authenticating the vehicle/driver/passenger(s) to Starbucks could occur to allow the transaction to proceed. Otherwise, the question could time out.

An embodiment of a method **4800** for sending secure information or completing a communication through a deployable antenna **2208** may be as shown in FIG. **48**. Generally, the method **4800** starts with a start operation **4804** and ends with operation **4828**. The method **4800** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **48**. The method **4800** can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method **4800** may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/or a Field Programmable Gate Array (FPGA). Hereinafter, the method **4800** shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. **1-47** and **54A-56**.

The vehicle **100** may enter a location, in step **4808**. Here, the vehicle **100** may maneuver within physical proximity of a third-party location. The third-party location may have a receiving pad **2212**. In step **4812**, the processor **5608** may receive an instruction to deploy antenna **2208** to touch the pad **2212**. In response, the processor **5608** may operate the deploying device **2204** to deploy the antenna **2208** to physically contact the pad **2212**.

Upon making an electrical connection through the contact surface(s), the CPU **5608** can establish a communication/electrical connection through the deployable antenna **2208**, in step **4816**. For example, authentication or authorization information may be exchanged between the vehicle **100** and the third party through antenna **2208**. At this point, the CPU **5608** may provide a user interface, such as user interface **3000** or user interface **3012**, to determine if the user authorizes the communication, in step **4820**. If the user provides input that communications are authorized, the method **4800** proceeds “YES” to step **4824**, where the processor **5608** automatically sends the communication or financial information. If no authorization is given, the method proceeds “NO” to end operation **4828**.

The soft contact reader for payment, similar to the close proximity (e.g., NFC, close range, etc.) readers **2004** can be deployed in different locations for different functions (e.g., side of vehicle for coffee or food at drive through; top of vehicle for tolls, parking, etc., or other locations). Most forms of contactless payment utilize NFC protocol antennae. Such communication devices require very near proximity to transfer information. To utilize this technology with the vehicle **100**, when conducting contactless payment transactions with external devices, a specially designed scanner device is needed. An NFC antennae device may be installed in a type of “brush” or “arm” wherein the external device **2208** may come in contact with the NFC antennae of the vehicle without damaging the vehicle **100** in any way. For example, when conducting a contactless payment transaction while driving into or out of a parking garage, a vehicle **100** may drive over a brush or arm equipped with an NFC reading device. This reading device may come in contact with an NFC antennae placed on the undercarriage of the vehicle. In other situations, for example a drive-thru restaurant, the vehicle **100** may drive alongside an NFC reader equipped brush or arm, wherein the NFC reader is enabled to accept payment information from an NFC antennae device placed on the driver side of the vehicle **100**.

An embodiment of sending authentication information in a method **4900** may be as shown in FIG. **49**. Generally, the method **4900** starts with a start operation **4904** and ends with operation **4932**. The method **4900** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **49**. The method **4900** can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method **4900** may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/or a Field Programmable Gate Array (FPGA). Hereinafter, the method **4900** shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. **1-48** and **54A-56**.

In step **4908**, the communications system **1900** can establish a connection or communication link between the vehicle **100** and a third party. This connection may be a nearfield

communication, wireless communication, cellular communication, etc. Any of the preceding or following descriptions of communication connections may be made. In step **4912**, the CPU **5608** can then receive a request for a secure communication. This secure communication may be authorized or secured using authenticating information. This authenticating information may be information identifying a user. As such, the CPU **5608** can retrieve identifying information associated with the user, in step **4916**. Here, the CPU may extract or create a half-token **2312** or information shown in data structure **2404**.

In step **4920**, the CPU **5608** may retrieve from memory the information associated with the vehicle **100**, for example, a VIN **2436**, an ESN **2440**, an engine code **2444**. The vehicle’s information may be combined with the user information into a new grouping of identifying information from both the user and vehicle **100**, in step **4924**. This combined information may then be sent by the processor **5608** to the communications system **1900** and sent on to another party, in step **4928**.

Thus, the vehicle **100** can employ a vehicle VIN **2436**, an ESN **2440** for the vehicle **100**, an ESN of a mobile device, etc. for communication/purchase authentication. Only if a third party receives both sets of information is there an authentication for a communication/purchase. Another individual cannot purchase anything if the vehicle **100** is car-jacked or stolen. Further, in some configurations, a user could provide the VIN **2436** and/or ESN **2440** as an ignition key for vehicle **100**. An additional level of authentication may require a PIN **2512**, or additional biometrics **2408**, for the authorization.

An embodiment of a method **5000** for determining whether a communication may be limited by predetermined limits may be as shown in FIG. **50**. Generally, the method **5000** starts with a start operation **5004** and ends with operation **5032**. The method **5000** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **50**. The method **5000** can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method **5000** may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/or a Field Programmable Gate Array (FPGA). Hereinafter, the method **5000** shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. **1-49** and **54A-56**.

The communications system **1900** may establish a communications connection with a third party, in step **5008**. In step **5012**, the processor **5608** may receive a request for secure communication from the third party. Upon receiving and in response to receiving such request, the processor **5608** may access limits field **2524**, in data structure **2504**, to retrieve limits on such secure communications, in step **5016**. The processor **5608** may then determine whether the communications are prohibited by these limits, in step **5020**. Here, limits can include limits on the number of communications provided, can include monetary limits on transactions that may be conducted, etc. These limits on financial transactions may be cover two or more vehicles or just for the single vehicle **100**. The limits may also be associated with a particular financial account or across family members.

Depending on the limit, the processor **5608** can determine whether a communication is authorized, in step **5020**. If the communication is prohibited, the method **5000** proceeds “YES” to step **5024**, where the communication is ended. However, if the communication is not prohibited, the method **5000** proceeds “NO” to step **5028**, where the communications are sent. For example, without prohibitions, the financial information of the user may be sent to conduct a financial transaction.

The limits placed on transaction amounts can be based on an individual or on a collection of people, on a transaction, or over a specified period of time. The transaction history could be synchronized among multiple vehicles to provide a collective limit for all vehicles or may be based on a limit per-vehicle, per location, etc. Limits on types of transactions or products being purchased could also be imposed on another entity, for example, a parent can set transaction limits on driving teenagers.

Method **5100** may be similar to method **5000**. Generally, the method **5100** starts with a start operation **5104** and ends with operation **5132**. The method **5100** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **51**. The method **5100** can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method **5100** may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/r a Field Programmable Gate Array (FPGA). Hereinafter, the method **5100** shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. **1-50** and **54A-56**.

The method **5100**, shown in FIG. **51**, may also set limits on communications, similar to method **5000**, but, in this situation, based on third-party limits. Thus, the communication can be established with a third party, in step **5108**, and a request for secure communication can be received, in step **5112**. Rather than retrieving limits made by a user, the limits may be applied from a third party. As such, the third party may retrieve limits, in step **5116**, to determine whether the communication is prohibited by those limits, in step **5120**. For example, if the third party is a bank, the bank may limit the amount of a transaction or a communication based on limits set by the bank for the vehicle **100**. If the limits prohibit the communication, the method **5100** proceeds “YES” to step **5124**, where the communication is ended. However, if the communication is not prohibited, the method **5100** proceeds “NO” to step **5128**, where the communication is sent.

Method **5100** is directed to the other side of the transaction in method **5000**. A provider/seller can also have business rules that are applied to the supplier side. The supplier sets a different notional set of purchase rules, i.e. business operational minimums or maximums, to facilitate selection or negotiation of battery exchange/repair/charging terms. Such rules are applied when the user seeks such services, as enabled by a searching algorithm querying a database of available service stations. Automated negotiation between user and service provider may occur. The business/user is able to adjust selectable parameters, e.g., the user may be in a particular hurry and increase his/her maximum fee for a certain service, e.g., charging prices. Thus, the business and user may conduct negotiations or bargain within the limits of pre-defined limits or parameters.

Method **5200** provides for conducting secure communications based on a set of preauthorization rules as shown in FIG. **52**. Generally, the method **5200** starts with a start operation **5204** and ends with operation **5240**. The method **5200** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **52**. The method **5200** can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method **5200** may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/r a Field Programmable Gate Array (FPGA). Hereinafter, the method **5200** shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. **1-51** and **54A-56**.

In step **5208**, the vehicle **100** establishes a connection with a third party through the communications system **1900**. Again, the processor **5608** receives a request for a secure communication, in step **5212**. Rather than obtaining preferences, the CPU **5608** can retrieve pre-authorization rules from field **2532** of data structure **2504**, in step **5216**. These pre-authorization rules **2532** may be similar to those that are set in user interface **4000** or **4100**. The pre-authorization rules may determine whether a processor **5608** can conduct pre-orders or other communications without user input, at least for a portion of the communications.

If the communication is allowed by the rules **2532**, in step **5220**, the method **5200** proceeds “YES” to step **5228**, where the communication is sent through the communication system **1900**. However, if the communication is not allowed by the rules **2532**, the method **5200** proceeds “NO” to step **5224**, where the CPU **5608** determines whether the user authorizes the communication. If the communication is authorized based on input received in a user interface, such as interface **3000**, the method **5200** proceeds “YES” to step **5228**, again to send the communication. However, if the communications are not authorized or pre-authorized, the method **5200** proceeds “NO” to step **5232**, where the communication is ended.

The user establishes a set of rules triggering automatic authorization for or purchasing of services. For example, the user may establish that when visibility conditions along a route are predicted to drop below certain minimum, a moving map display **3800** with overlaid weather is provided on a vehicle display. Such a display would aid the driver in considering alternative routes or increasing the driver’s situational awareness as to the severity, duration, and direction of the cause of the visibility drop (e.g., is it ground fog over a wide area expected to linger or a result of a fast-moving thunderstorm). The real-time moving map overlaid weather display **3800** may require a costly live feed from a weather satellite, and, as such, the feed is not provided unless the triggering event is satisfied. In another example, the user may establish that if his programmed driving route requires in route charging, a purchase of a reserved charging spot at a charging station along the route is automatically made so as to reserve the spot.

An embodiment of a bifurcated communication between the vehicle **100** and a third party may be as shown in FIG. **5300**. Generally, the method **5300** starts with a start operation **5304** and ends with operation **5340**. The method **5300** can include more or fewer steps or can arrange the order of the steps differently than those shown in FIG. **53**. The

method **5300** can be executed as a set of computer-executable instructions executed by a computer system or processor and encoded or stored on a computer readable medium. In other configurations, the method **5300** may be executed by a series of components, circuits, gates, etc. created in a hardware device, such as a System of Chip (SOC), Application Specific Integrated Circuit (ASIC), and/or a Field Programmable Gate Array (FPGA). Hereinafter, the method **5300** shall be explained with reference to the systems, components, circuits, modules, software, data structures, signaling processes, models, environments, vehicles, etc. described in conjunction with FIGS. 1-52 and 54A-56.

Here, a first event may be received, in step **5308**. This event may be the user driving to a certain location, taking a route, or some other type of event that occurs that causes the vehicle **100** to decide to send a first portion of a secure communication to a third party, in step **5312**. For example, the processor **5608** may provide a pre-order for some good or service typically purchased by the user at that time of day at that route. This pre-authorization may be sent to the third party to prepare an order. At some point thereafter, in step **5316**, the processor **5608** can receive a second event associated with that first event. The second event may be the vehicle **100** driving to the physical location of the third party. As such, the second event may be the navigation system **302** identifying that the vehicle **100** is at the third party's location.

In step **5320**, the processor **5608** can determine whether the user then authorizes the complete communication/transaction. Here, the user may be presented with a user interface **3300**, **3500** associated with the preauthorization. If the communication/transaction is authorized, in step **5320**, by selecting, for example, button **3512**, the method proceeds "YES" to step **5328**, where a second portion of the secure communication may be sent to a third party. The second communication can be a second half-token. As such, a half-token **2312** can be sent, in step **5312** while further information—such as financial information **2508**, a PIN **2512**, or some other type of information to complete the transaction—may be sent as the related second half token, in step **5328**. If the user does not authorize the communication, the method **5300** can proceed "NO" to step **5336**.

Utilizing the vehicle as a mobile wallet can pose some issues. One issue is the problem with ensuring that the vehicle **100** pays the right merchant, at the right time, in the right location. To ensure accuracy in payment, the vehicle **100** may break the payment procedure into two or more phases. A first phase may order goods or services and may provide some or all of the payment information. A second phase may send the total payment information or confirm the information in the first phase, such as by user input in response to a query (e.g., providing a PIN). Thus, the vehicle **100** can pre-authorize charges.

The vehicle **100** may also use different communication media (e.g., cellular communication, Bluetooth, NFC, etc.) to conduct the two or more phases. Using different communication media can enhance security as merchants or other nefarious individuals may not use the payment information without both phases of the communication and one of the phases may be conducted with a communication media that requires physical proximity of the vehicle **100**. Moreover, having a second phase requiring operator input can prevent a first vehicle from purchasing goods or services for another second vehicle waiting in line with the first vehicle **100**.

As an example, the vehicle **100** may be driving toward a pay-point and pre-order a good. The vehicle **100** may understand that the driver is heading towards Starbucks

(through past behavior), and the vehicle **100** can communicate with the Starbucks that payment will be authorized and desires their beverage hot, sweet, etc. (based on driver behavior and location). The pre-authorization may be sent over a cellular network. When the vehicle **100** arrives at the Starbucks, the final authorization may be sent over a local proximity-based payment system, e.g. NFC.

Payment can be authorized based on vehicle identification and later acceptance. When a vehicle **100** conducts a payment transaction, the transaction may be authorized based on a unique identifier associated with the vehicle and/or a geolocation information associated with the vehicle **100** and/or the driver. During the transaction, the vehicle's contactless payment system may deliver the payment information as well as information regarding the vehicle **100** and/or driver of the vehicle. This information may be collected in other ways by the external payment device to support the authorization. For example, the external device may photograph the vehicle **100**, license plate, and/or driver. This information may be used to support the authorization for the transaction. Such pre-transaction authorization may be useful in situations where requiring the driver to manually enter an authorization, such as by PIN code, signature, etc., may be inconvenient or impossible because the driver is driving the vehicle **100**. For example, the system may be used for payments made while the vehicle **100** is in motion, e.g., for paying while entering/exiting parking garages and/or for paying for toll-lanes.

FIG. 54A is a block diagram of an embodiment of a communication environment **5400** of the vehicle **100** in accordance with embodiments of the present disclosure. The communication system **5400** may include one or more vehicle driving vehicle sensors and systems **5404**, sensor processors **5440**, sensor data memory **5444**, vehicle control system **5448**, communications subsystem **5450**, control data **5464**, computing devices **5468**, display devices **5472**, and other components **5474** that may be associated with a vehicle **100**. These associated components may be electrically and/or communicatively coupled to one another via at least one bus **5460**. In some embodiments, the one or more associated components may send and/or receive signals across a communication network **5452** to at least one of a navigation source **5455A**, a control source **5455B**, or some other entity **5455N**.

In accordance with at least some embodiments of the present disclosure, the communication network **5452** may comprise any type of known communication medium or collection of communication media and may use any type of protocols, such as SIP, TCP/IP, SNA, IPX, AppleTalk, and the like, to transport messages between endpoints. The communication network **5452** may include wired and/or wireless communication technologies. The Internet is an example of the communication network **5452** that constitutes an Internet Protocol (IP) network consisting of many computers, computing networks, and other communication devices located all over the world, which are connected through many telephone systems and other means. Other examples of the communication network **104** include, without limitation, a standard Plain Old Telephone System (POTS), an Integrated Services Digital Network (ISDN), the Public Switched Telephone Network (PSTN), a Local Area Network (LAN), such as an Ethernet network, a Token-Ring network and/or the like, a Wide Area Network (WAN), a virtual network, including without limitation a virtual private network ("VPN"); the Internet, an intranet, an extranet, a cellular network, an infra-red network; a wireless network (e.g., a network operating under any of the IEEE 802.9 suite

51

of protocols, the Bluetooth® protocol known in the art, and/or any other wireless protocol), and any other type of packet-switched or circuit-switched network known in the art and/or any combination of these and/or other networks. In addition, it can be appreciated that the communication network **5452** need not be limited to any one network type, and instead may be comprised of a number of different networks and/or network types. The communication network **5452** may comprise a number of different communication media such as coaxial cable, copper cable/wire, fiber-optic cable, antennas for transmitting/receiving wireless messages, and combinations thereof.

The driving vehicle sensors and systems **5404** may include at least one navigation **5408** (e.g., global positioning system (GPS), etc.), orientation **5412**, odometry **5416**, LIDAR **5420**, RADAR **5424**, ultrasonic **5428**, camera **5432**, infrared (IR) **5436**, and/or other sensor or system **5438**. These driving vehicle sensors and systems **5404** may be similar, if not identical, to the sensors and systems **116A-K**, **112** described in conjunction with FIGS. **1** and **2**.

The navigation sensor **5408** may include one or more sensors having receivers and antennas that are configured to utilize a satellite-based navigation system including a network of navigation satellites capable of providing geolocation and time information to at least one component of the vehicle **100**. Examples of the navigation sensor **5408** as described herein may include, but are not limited to, at least one of Garmin® GLO™ family of GPS and GLONASS combination sensors, Garmin® GPS 15x™ family of sensors, Garmin® GPS 16x™ family of sensors with high-sensitivity receiver and antenna, Garmin® GPS 18x OEM family of high-sensitivity GPS sensors, Dewetron DEWE-VGPS series of GPS sensors, GlobalSat 1-Hz series of GPS sensors, other industry-equivalent navigation sensors and/or systems, and may perform navigational and/or geolocation functions using any known or future-developed standard and/or architecture.

The orientation sensor **5412** may include one or more sensors configured to determine an orientation of the vehicle **100** relative to at least one reference point. In some embodiments, the orientation sensor **5412** may include at least one pressure transducer, stress/strain gauge, accelerometer, gyroscope, and/or geomagnetic sensor. Examples of the navigation sensor **5408** as described herein may include, but are not limited to, at least one of Bosch Sensortec BMX 160 series low-power absolute orientation sensors, Bosch Sensortec BMX054 9-axis sensors, Bosch Sensortec BMI054 6-axis inertial sensors, Bosch Sensortec BMI160 6-axis inertial sensors, Bosch Sensortec BMF054 9-axis inertial sensors (accelerometer, gyroscope, and magnetometer) with integrated Cortex M0+ microcontroller, Bosch Sensortec BMP280 absolute barometric pressure sensors, Infineon TLV493D-A1B6 3D magnetic sensors, Infineon TLI493D-W1B6 3D magnetic sensors, Infineon TL family of 3D magnetic sensors, Murata Electronics SCC2000 series combined gyro sensor and accelerometer, Murata Electronics SCC1300 series combined gyro sensor and accelerometer, other industry-equivalent orientation sensors and/or systems, and may perform orientation detection and/or determination functions using any known or future-developed standard and/or architecture.

The odometry sensor and/or system **5416** may include one or more components that is configured to determine a change in position of the vehicle **100** over time. In some embodiments, the odometry system **5416** may utilize data from one or more other sensors and/or systems **5404** in determining a position (e.g., distance, location, etc.) of the

52

vehicle **100** relative to a previously measured position for the vehicle **100**. Additionally or alternatively, the odometry sensors **5416** may include one or more encoders, Hall speed sensors, and/or other measurement sensors/devices configured to measure a wheel speed, rotation, and/or number of revolutions made over time. Examples of the odometry sensor/system **5416** as described herein may include, but are not limited to, at least one of Infineon TLE4924/26/27/28C high-performance speed sensors, Infineon TL4941plusC(B) single chip differential Hall wheel-speed sensors, Infineon TL5041plusC Giant Magnetoresistance (GMR) effect sensors, Infineon TL family of magnetic sensors, EPC Model 25SP Accu-CoderPro™ incremental shaft encoders, EPC Model 30M compact incremental encoders with advanced magnetic sensing and signal processing technology, EPC Model 925 absolute shaft encoders, EPC Model 958 absolute shaft encoders, EPC Model MA36S/MA63S/SA36S absolute shaft encoders, Dynapar™ F18 commutating optical encoder, Dynapar™ HS35R family of phased array encoder sensors, other industry-equivalent odometry sensors and/or systems, and may perform change in position detection and/or determination functions using any known or future-developed standard and/or architecture.

The LIDAR sensor/system **5420** may include one or more components configured to measure distances to targets using laser illumination. In some embodiments, the LIDAR sensor/system **5420** may provide 3D imaging data of an environment around the vehicle **100**. The imaging data may be processed to generate a full 360-degree view of the environment around the vehicle **100**. The LIDAR sensor/system **5420** may include a laser light generator configured to generate a plurality of target illumination laser beams (e.g., laser light channels). In some embodiments, this plurality of laser beams may be aimed at, or directed to, a rotating reflective surface (e.g., a mirror) and guided outwardly from the LIDAR sensor/system **5420** into a measurement environment. The rotating reflective surface may be configured to continually rotate 360 degrees about an axis, such that the plurality of laser beams is directed in a full 360-degree range around the vehicle **100**. A photodiode receiver of the LIDAR sensor/system **5420** may detect when light from the plurality of laser beams emitted into the measurement environment returns (e.g., reflected echo) to the LIDAR sensor/system **5420**. The LIDAR sensor/system **5420** may calculate, based on a time associated with the emission of light to the detected return of light, a distance from the vehicle **100** to the illuminated target. In some embodiments, the LIDAR sensor/system **5420** may generate over 2.0 million points per second and have an effective operational range of at least 100 meters. Examples of the LIDAR sensor/system **5420** as described herein may include, but are not limited to, at least one of Velodyne® LiDAR™ HDL-64E 64-channel LIDAR sensors, Velodyne® LiDAR™ HDL-32E 32-channel LIDAR sensors, Velodyne® LiDAR™ PUCK™ VLP-16 16-channel LIDAR sensors, Leica Geosystems Pegasus: Two mobile sensor platform, Garmin® LIDAR-Lite v3 measurement sensor, Quanergy M8 LiDAR sensors, Quanergy S3 solid state LiDAR sensor, LeddarTech® LeddarVU compact solid state fixed-beam LIDAR sensors, other industry-equivalent LIDAR sensors and/or systems, and may perform illuminated target and/or obstacle detection in an environment around the vehicle **100** using any known or future-developed standard and/or architecture.

The RADAR sensors **5424** may include one or more radio components that are configured to detect objects/targets in an environment of the vehicle **100**. In some embodiments, the RADAR sensors **5424** may determine a distance, posi-

53

tion, and/or movement vector (e.g., angle, speed, etc.) associated with a target over time. The RADAR sensors **5424** may include a transmitter configured to generate and emit electromagnetic waves (e.g., radio, microwaves, etc.) and a receiver configured to detect returned electromagnetic waves. In some embodiments, the RADAR sensors **5424** may include at least one processor configured to interpret the returned electromagnetic waves and determine locational properties of targets. Examples of the RADAR sensors **5424** as described herein may include, but are not limited to, at least one of Infineon RASIC™ RTN7735PL transmitter and RRN7745PL/46PL receiver sensors, Autoliv ASP Vehicle RADAR sensors, Delphi L2C0051TR 77 GHz ESR Electronically Scanning Radar sensors, Fujitsu Ten Ltd. Automotive Compact 77 GHz 3D Electronic Scan Millimeter Wave Radar sensors, other industry-equivalent RADAR sensors and/or systems, and may perform radio target and/or obstacle detection in an environment around the vehicle **100** using any known or future-developed standard and/or architecture.

The ultrasonic sensors **5428** may include one or more components that are configured to detect objects/targets in an environment of the vehicle **100**. In some embodiments, the ultrasonic sensors **5428** may determine a distance, position, and/or movement vector (e.g., angle, speed, etc.) associated with a target over time. The ultrasonic sensors **5428** may include an ultrasonic transmitter and receiver, or transceiver, configured to generate and emit ultrasound waves and interpret returned echoes of those waves. In some embodiments, the ultrasonic sensors **5428** may include at least one processor configured to interpret the returned ultrasonic waves and determine locational properties of targets. Examples of the ultrasonic sensors **5428** as described herein may include, but are not limited to, at least one of Texas Instruments TIDA-00151 automotive ultrasonic sensor interface IC sensors, MaxBotix® MB8450 ultrasonic proximity sensor, MaxBotix® ParkSonar™-EZ ultrasonic proximity sensors, Murata Electronics MA40H1S-R open-structure ultrasonic sensors, Murata Electronics MA40S4R/S open-structure ultrasonic sensors, Murata Electronics MA58MF14-7N waterproof ultrasonic sensors, other industry-equivalent ultrasonic sensors and/or systems, and may perform ultrasonic target and/or obstacle detection in an environment around the vehicle **100** using any known or future-developed standard and/or architecture.

The camera sensors **5432** may include one or more components configured to detect image information associated with an environment of the vehicle **100**. In some embodiments, the camera sensors **5432** may include a lens, filter, image sensor, and/or a digital image processor. It is an aspect of the present disclosure that multiple camera sensors **5432** may be used together to generate stereo images providing depth measurements. Examples of the camera sensors **5432** as described herein may include, but are not limited to, at least one of ON Semiconductor® MT9V024 Global Shutter VGA GS CMOS image sensors, Teledyne DALSA Falcon2 camera sensors, CMOSIS CMV50000 high-speed CMOS image sensors, other industry-equivalent camera sensors and/or systems, and may perform visual target and/or obstacle detection in an environment around the vehicle **100** using any known or future-developed standard and/or architecture.

The infrared (IR) sensors **5436** may include one or more components configured to detect image information associated with an environment of the vehicle **100**. The IR sensors **5436** may be configured to detect targets in low-light, dark, or poorly-lit environments. The IR sensors **5436** may

54

include an IR light emitting element (e.g., IR light emitting diode (LED), etc.) and an IR photodiode. In some embodiments, the IR photodiode may be configured to detect returned IR light at or about the same wavelength to that emitted by the IR light emitting element. In some embodiments, the IR sensors **5436** may include at least one processor configured to interpret the returned IR light and determine locational properties of targets. The IR sensors **5436** may be configured to detect and/or measure a temperature associated with a target (e.g., an object, pedestrian, other vehicle, etc.). Examples of IR sensors **5436** as described herein may include, but are not limited to, at least one of Opto Diode lead-salt IR array sensors, Opto Diode OD-850 Near-IR LED sensors, Opto Diode SA/SHA727 steady state IR emitters and IR detectors, FUR® LS microbolometer sensors, FUR® TacFLIR 380-HD InSb MWIR FPA and HD MWIR thermal sensors, FLIR® VOx 640×480 pixel detector sensors, Delphi IR sensors, other industry-equivalent IR sensors and/or systems, and may perform IR visual target and/or obstacle detection in an environment around the vehicle **100** using any known or future-developed standard and/or architecture.

The vehicle **100** can also include one or more interior sensors **5437**. Interior sensors **5437** can measure characteristics of the inside environment of the vehicle **100**. The interior sensors **5437** may be as described in conjunction with FIG. **54B**.

A navigation system **5402** can include any hardware and/or software used to navigate the vehicle either manually or autonomously. The navigation system **5402** may be as described in conjunction with FIG. **54C**.

In some embodiments, the driving vehicle sensors and systems **5404** may include other sensors **5438** and/or combinations of the sensors **5406-5437** described above. Additionally or alternatively, one or more of the sensors **5406-5437** described above may include one or more processors configured to process and/or interpret signals detected by the one or more sensors **5406-5437**. In some embodiments, the processing of at least some sensor information provided by the vehicle sensors and systems **5404** may be processed by at least one sensor processor **5440**. Raw and/or processed sensor data may be stored in a sensor data memory **5444** storage medium. In some embodiments, the sensor data memory **5444** may store instructions used by the sensor processor **5440** for processing sensor information provided by the sensors and systems **5404**. In any event, the sensor data memory **5444** may be a disk drive, optical storage device, solid-state storage device such as a random access memory ("RAM") and/or a read-only memory ("ROM"), which can be programmable, flash-updateable, and/or the like.

The vehicle control system **5448** may receive processed sensor information from the sensor processor **5440** and determine to control an aspect of the vehicle **100**. Controlling an aspect of the vehicle **100** may include presenting information via one or more display devices **5472** associated with the vehicle, sending commands to one or more computing devices **5468** associated with the vehicle, and/or controlling a driving operation of the vehicle. In some embodiments, the vehicle control system **5448** may correspond to one or more computing systems that control driving operations of the vehicle **100** in accordance with the Levels of driving autonomy described above. In one embodiment, the vehicle control system **5448** may operate a speed of the vehicle **100** by controlling an output signal to the accelerator and/or braking system of the vehicle. In this example, the vehicle control system **5448** may receive sensor data

describing an environment surrounding the vehicle **100** and, based on the sensor data received, determine to adjust the acceleration, power output, and/or braking of the vehicle **100**. The vehicle control system **5448** may additionally control steering and/or other driving functions of the vehicle **100**.

The vehicle control system **5448** may communicate, in real-time, with the driving sensors and systems **5404** forming a feedback loop. In particular, upon receiving sensor information describing a condition of targets in the environment surrounding the vehicle **100**, the vehicle control system **5448** may autonomously make changes to a driving operation of the vehicle **100**. The vehicle control system **5448** may then receive subsequent sensor information describing any change to the condition of the targets detected in the environment as a result of the changes made to the driving operation. This continual cycle of observation (e.g., via the sensors, etc.) and action (e.g., selected control or non-control of vehicle operations, etc.) allows the vehicle **100** to operate autonomously in the environment.

In some embodiments, the one or more components of the vehicle **100** (e.g., the driving vehicle sensors **5404**, vehicle control system **5448**, display devices **5472**, etc.) may communicate across the communication network **5452** to one or more entities **5455A-N** via a communications subsystem **5450** of the vehicle **100**. Embodiments of the communications subsystem **5450** are described in greater detail in conjunction with FIG. 5. For instance, the navigation sensors **5408** may receive global positioning, location, and/or navigational information from a navigation source **5455A**. In some embodiments, the navigation source **5455A** may be a global navigation satellite system (GNSS) similar, if not identical, to NAVSTAR GPS, GLONASS, EU Galileo, and/or the BeiDou Navigation Satellite System (BDS) to name a few.

In some embodiments, the vehicle control system **5448** may receive control information from one or more control sources **5455B**. The control source **5455** may provide vehicle control information including autonomous driving control commands, vehicle operation override control commands, and the like. The control source **5455** may correspond to an autonomous vehicle control system, a traffic control system, an administrative control entity, and/or some other controlling server. It is an aspect of the present disclosure that the vehicle control system **5448** and/or other components of the vehicle **100** may exchange communications with the control source **5455** across the communication network **5452** and via the communications subsystem **5450**.

Information associated with controlling driving operations of the vehicle **100** may be stored in a control data memory **5464** storage medium. The control data memory **5464** may store instructions used by the vehicle control system **5448** for controlling driving operations of the vehicle **100**, historical control information, autonomous driving control rules, and the like. In some embodiments, the control data memory **5464** may be a disk drive, optical storage device, solid-state storage device such as a random access memory ("RAM") and/or a read-only memory ("ROM"), which can be programmable, flash-updateable, and/or the like.

In addition to the mechanical components described herein, the vehicle **100** may include a number of user interface devices. The user interface devices receive and translate human input into a mechanical movement or electrical signal or stimulus. The human input may be one or more of motion (e.g., body movement, body part movement, in two-dimensional or three-dimensional space, etc.), voice,

touch, and/or physical interaction with the components of the vehicle **100**. In some embodiments, the human input may be configured to control one or more functions of the vehicle **100** and/or systems of the vehicle **100** described herein. User interfaces may include, but are in no way limited to, at least one graphical user interface of a display device, steering wheel or mechanism, transmission lever or button (e.g., including park, neutral, reverse, and/or drive positions, etc.), throttle control pedal or mechanism, brake control pedal or mechanism, power control switch, communications equipment, etc.

FIG. 54B shows a block diagram of an embodiment of interior sensors **5437** for a vehicle **100**. The interior sensors **5437** may be arranged into one or more groups, based at least partially on the function of the interior sensors **5437**. For example, the interior space of a vehicle **100** may include environmental sensors, user interface sensors, and/or safety sensors. Additionally or alternatively, there may be sensors associated with various devices inside the vehicle (e.g., smart phones, tablets, mobile computers, wearables, etc.)

Environmental sensors may comprise sensors configured to collect data relating to the internal environment of a vehicle **100**. Examples of environmental sensors may include one or more of, but are not limited to: oxygen/air sensors **5401**, temperature sensors **5403**, humidity sensors **5405**, light/photo sensors **5407**, and more. The oxygen/air sensors **5401** may be configured to detect a quality or characteristic of the air in the interior space **108** of the vehicle **100** (e.g., ratios and/or types of gasses comprising the air inside the vehicle **100**, dangerous gas levels, safe gas levels, etc.). Temperature sensors **5403** may be configured to detect temperature readings of one or more objects, users **216**, and/or areas of a vehicle **100**. Humidity sensors **5405** may detect an amount of water vapor present in the air inside the vehicle **100**. The light/photo sensors **5407** can detect an amount of light present in the vehicle **100**. Further, the light/photo sensors **5407** may be configured to detect various levels of light intensity associated with light in the vehicle **100**.

User interface sensors may comprise sensors configured to collect data relating to one or more users (e.g., a driver and/or passenger(s)) in a vehicle **100**. As can be appreciated, the user interface sensors may include sensors that are configured to collect data from users **216** in one or more areas of the vehicle **100**. Examples of user interface sensors may include one or more of, but are not limited to: infrared sensors **5409**, motion sensors **5411**, weight sensors **5413**, wireless network sensors **5415**, biometric sensors **5417**, camera (or image) sensors **5419**, audio sensors **5421**, and more.

Infrared sensors **5409** may be used to measure IR light irradiating from at least one surface, user, or another object in the vehicle **100**. Among other things, the Infrared sensors **5409** may be used to measure temperatures, form images (especially in low light conditions), identify users **216**, and even detect motion in the vehicle **100**.

The motion sensors **5411** may detect motion and/or movement of objects inside the vehicle **100**. Optionally, the motion sensors **5411** may be used alone or in combination to detect movement. For example, a user may be operating a vehicle **100** (e.g., while driving, etc.) when a passenger in the rear of the vehicle **100** unbuckles a safety belt and proceeds to move about the vehicle **100**. In this example, the movement of the passenger could be detected by the motion sensors **5411**. In response to detecting the movement and/or the direction associated with the movement, the passenger may be prevented from interfacing with and/or accessing at

least some of the vehicle control features. As can be appreciated, the user may be alerted of the movement/motion such that the user can act to prevent the passenger from interfering with the vehicle controls. Optionally, the number of motion sensors in a vehicle may be increased to increase an accuracy associated with motion detected in the vehicle 100.

Weight sensors 5413 may be employed to collect data relating to objects and/or users in various areas of the vehicle 100. In some cases, the weight sensors 5413 may be included in the seats and/or floor of a vehicle 100. Optionally, the vehicle 100 may include a wireless network sensor 5415. This sensor 5415 may be configured to detect one or more wireless network(s) inside the vehicle 100. Examples of wireless networks may include, but are not limited to, wireless communications utilizing Bluetooth®, Wi-Fi™, ZigBee, IEEE 802.11, and other wireless technology standards. For example, a mobile hotspot may be detected inside the vehicle 100 via the wireless network sensor 5415. In this case, the vehicle 100 may determine to utilize and/or share the mobile hotspot detected via/with one or more other devices associated with the vehicle 100.

Biometric sensors 5417 may be employed to identify and/or record characteristics associated with a user. It is anticipated that biometric sensors 5417 can include at least one of image sensors, IR sensors, fingerprint readers, weight sensors, load cells, force transducers, heart rate monitors, blood pressure monitors, and the like as provided herein.

The camera sensors 5419 may record still images, video, and/or combinations thereof. Camera sensors 5419 may be used alone or in combination to identify objects, users, and/or other features, inside the vehicle 100. Two or more camera sensors 5419 may be used in combination to form, among other things, stereo and/or three-dimensional (3D) images. The stereo images can be recorded and/or used to determine depth associated with objects and/or users in a vehicle 100. Further, the camera sensors 5419 used in combination may determine the complex geometry associated with identifying characteristics of a user. For example, the camera sensors 5419 may be used to determine dimensions between various features of a user's face (e.g., the depth/distance from a user's nose to a user's cheeks, a linear distance between the center of a user's eyes, and more). These dimensions may be used to verify, record, and even modify characteristics that serve to identify a user. The camera sensors 5419 may also be used to determine movement associated with objects and/or users within the vehicle 100. It should be appreciated that the number of image sensors used in a vehicle 100 may be increased to provide greater dimensional accuracy and/or views of a detected image in the vehicle 100.

The audio sensors 5421 may be configured to receive audio input from a user of the vehicle 100. The audio input from a user may correspond to voice commands, conversations detected in the vehicle 100, phone calls made in the vehicle 100, and/or other audible expressions made in the vehicle 100. Audio sensors 5421 may include, but are not limited to, microphones and other types of acoustic-to-electric transducers or sensors. Optionally, the interior audio sensors 5421 may be configured to receive and convert sound waves into an equivalent analog or digital signal. The interior audio sensors 5421 may serve to determine one or more locations associated with various sounds in the vehicle 100. The location of the sounds may be determined based on a comparison of volume levels, intensity, and the like, between sounds detected by two or more interior audio sensors 5421. For instance, a first audio sensor 5421 may be located in a first area of the vehicle 100 and a second audio

sensor 5421 may be located in a second area of the vehicle 100. If a sound is detected at a first volume level by the first audio sensors 5421 A and a second, higher, volume level by the second audio sensors 5421 in the second area of the vehicle 100, the sound may be determined to be closer to the second area of the vehicle 100. As can be appreciated, the number of sound receivers used in a vehicle 100 may be increased (e.g., more than two, etc.) to increase measurement accuracy surrounding sound detection and location, or source, of the sound (e.g., via triangulation, etc.).

The safety sensors may comprise sensors configured to collect data relating to the safety of a user and/or one or more components of a vehicle 100. Examples of safety sensors may include one or more of, but are not limited to: force sensors 5425, mechanical motion sensors 5427, orientation sensors 5429, restraint sensors 5431, and more.

The force sensors 5425 may include one or more sensors inside the vehicle 100 configured to detect a force observed in the vehicle 100. One example of a force sensor 5425 may include a force transducer that converts measured forces (e.g., force, weight, pressure, etc.) into output signals. Mechanical motion sensors 5427 may correspond to encoders, accelerometers, damped masses, and the like. Optionally, the mechanical motion sensors 5427 may be adapted to measure the force of gravity (i.e., G-force) as observed inside the vehicle 100. Measuring the G-force observed inside a vehicle 100 can provide valuable information related to a vehicle's acceleration, deceleration, collisions, and/or forces that may have been suffered by one or more users in the vehicle 100. Orientation sensors 5429 can include accelerometers, gyroscopes, magnetic sensors, and the like that are configured to detect an orientation associated with the vehicle 100.

The restraint sensors 5431 may correspond to sensors associated with one or more restraint devices and/or systems in a vehicle 100. Seatbelts and airbags are examples of restraint devices and/or systems. As can be appreciated, the restraint devices and/or systems may be associated with one or more sensors that are configured to detect a state of the device/system. The state may include extension, engagement, retraction, disengagement, deployment, and/or other electrical or mechanical conditions associated with the device/system.

The associated device sensors 5423 can include any sensors that are associated with a device in the vehicle 100. As previously stated, typical devices may include smart phones, tablets, laptops, mobile computers, and the like. It is anticipated that the various sensors associated with these devices can be employed by the vehicle control system 5448. For example, a typical smart phone can include, an image sensor, an IR sensor, audio sensor, gyroscope, accelerometer, wireless network sensor, fingerprint reader, and more. It is an aspect of the present disclosure that one or more of these associated device sensors 5423 may be used by one or more subsystems of the vehicle 100.

FIG. 54C illustrates a GPS/Navigation subsystem(s) 5402. The navigation subsystem(s) 5402 can be any present or future-built navigation system that may use location data, for example, from the Global Positioning System (GPS), to provide navigation information or control the vehicle 100. The navigation subsystem(s) 5402 can include several components, such as, one or more of, but not limited to: a GPS Antenna/receiver 5431, a location module 5433, a maps database 5435, etc. Generally, the several components or modules 5431-5435 may be hardware, software, firmware, computer readable media, or combinations thereof.

A GPS Antenna/receiver **5431** can be any antenna, GPS puck, and/or receiver capable of receiving signals from a GPS satellite or other navigation system. The signals may be demodulated, converted, interpreted, etc. by the GPS Antenna/receiver **5431** and provided to the location module **5433**. Thus, the GPS Antenna/receiver **5431** may convert the time signals from the GPS system and provide a location (e.g., coordinates on a map) to the location module **5433**. Alternatively, the location module **5433** can interpret the time signals into coordinates or other location information.

The location module **5433** can be the controller of the satellite navigation system designed for use in the vehicle **100**. The location module **5433** can acquire position data, as from the GPS Antenna/receiver **5431**, to locate the user or vehicle **100** on a road in the unit's map database **5435**. Using the road database **5435**, the location module **5433** can give directions to other locations along roads also in the database **5435**. When a GPS signal is not available, the location module **5433** may apply dead reckoning to estimate distance data from sensors **5404** including one or more of, but not limited to, a speed sensor attached to the drive train of the vehicle **100**, a gyroscope, an accelerometer, etc. Additionally or alternatively, the location module **5433** may use known locations of Wi-Fi hotspots, cell tower data, etc. to determine the position of the vehicle **100**, such as by using time difference of arrival (TDOA) and/or frequency difference of arrival (FDOA) techniques.

The maps database **5435** can include any hardware and/or software to store information about maps, geographical information system (GIS) information, location information, etc. The maps database **5435** can include any data definition or other structure to store the information. Generally, the maps database **5435** can include a road database that may include one or more vector maps of areas of interest. Street names, street numbers, house numbers, and other information can be encoded as geographic coordinates so that the user can find some desired destination by street address. Points of interest (waypoints) can also be stored with their geographic coordinates. For example, a point of interest may include speed cameras, fuel stations, public parking, and "parked here" (or "you parked here") information. The maps database **5435** may also include road or street characteristics, for example, speed limits, location of stop lights/stop signs, lane divisions, school locations, etc. The map database contents can be produced or updated by a server connected through a wireless system in communication with the Internet, even as the vehicle **100** is driven along existing streets, yielding an up-to-date map.

FIG. **55** illustrates a block diagram of a computing environment **5500** that may function as the servers, user computers, or other systems provided and described herein. The computing environment **5500** includes one or more user computers, or computing devices, such as a vehicle computing device **5504**, a communication device **5508**, and/or more **5512**. The computing devices **5504**, **5508**, **5512** may include general purpose personal computers (including, merely by way of example, personal computers, and/or laptop computers running various versions of Microsoft Corp.'s Windows® and/or Apple Corp.'s Macintosh® operating systems) and/or workstation computers running any of a variety of commercially-available UNIX® or UNIX-like operating systems. These computing devices **5504**, **5508**, **5512** may also have any of a variety of applications, including for example, database client and/or server applications, and web browser applications. Alternatively, the computing devices **5504**, **5508**, **5512** may be any other electronic device, such as a thin-client computer, Internet-

enabled mobile telephone, and/or personal digital assistant, capable of communicating via a network **352** and/or displaying and navigating web pages or other types of electronic documents. Although the exemplary computing environment **5500** is shown with two computing devices, any number of user computers or computing devices may be supported.

The computing environment **5500** may also include one or more servers **5514**, **5516**. In this example, server **5514** is shown as a web server and server **5516** is shown as an application server. The web server **5514**, which may be used to process requests for web pages or other electronic documents from computing devices **5504**, **5508**, **5512**. The web server **5514** can be running an operating system including any of those discussed above, as well as any commercially-available server operating systems. The web server **5514** can also run a variety of server applications, including SIP (Session Initiation Protocol) servers, HTTP(s) servers, FTP servers, CGI servers, database servers, Java servers, and the like. In some instances, the web server **5514** may publish operations available operations as one or more web services.

The computing environment **5500** may also include one or more file and/or application servers **5516**, which can, in addition to an operating system, include one or more applications accessible by a client running on one or more of the computing devices **5504**, **5508**, **5512**. The server(s) **5516** and/or **5514** may be one or more general purpose computers capable of executing programs or scripts in response to the computing devices **5504**, **5508**, **5512**. As one example, the server **5516**, **5514** may execute one or more web applications. The web application may be implemented as one or more scripts or programs written in any programming language, such as Java™, C, C#®, or C++, and/or any scripting language, such as Perl, Python, or TCL, as well as combinations of any programming/scripting languages. The application server(s) **5516** may also include database servers, including without limitation those commercially available from Oracle®, Microsoft®, Sybase®, IBM® and the like, which can process requests from database clients running on a computing device **5504**, **5508**, **5512**.

The web pages created by the server **5514** and/or **5516** may be forwarded to a computing device **5504**, **5508**, **5512** via a web (file) server **5514**, **5516**. Similarly, the web server **5514** may be able to receive web page requests, web services invocations, and/or input data from a computing device **5504**, **5508**, **5512** (e.g., a user computer, etc.) and can forward the web page requests and/or input data to the web (application) server **5516**. In further embodiments, the server **5516** may function as a file server. Although for ease of description, FIG. **55** illustrates a separate web server **5514** and file/application server **5516**, those skilled in the art will recognize that the functions described with respect to servers **5514**, **5516** may be performed by a single server and/or a plurality of specialized servers, depending on implementation-specific needs and parameters. The computer systems **5504**, **5508**, **5512**, web (file) server **5514** and/or web (application) server **5516** may function as the system, devices, or components described in FIGS. **1-54**.

The computing environment **5500** may also include a database **5518**. The database **5518** may reside in a variety of locations. By way of example, database **5518** may reside on a storage medium local to (and/or resident in) one or more of the computers **5504**, **5508**, **5512**, **5514**, **5516**. Alternatively, it may be remote from any or all of the computers **5504**, **5508**, **5512**, **5514**, **5516**, and in communication (e.g., via the network **5510**) with one or more of these. The database **5518** may reside in a storage-area network

61

("SAN") familiar to those skilled in the art. Similarly, any necessary files for performing the functions attributed to the computers **5504**, **5508**, **5512**, **5514**, **5516** may be stored locally on the respective computer and/or remotely, as appropriate. The database **5518** may be a relational database, such as Oracle 20i®, that is adapted to store, update, and retrieve data in response to SQL-formatted commands.

FIG. **56** illustrates one embodiment of a computer system **5600** upon which the servers, user computers, computing devices, or other systems or components described above may be deployed or executed. The computer system **5600** is shown comprising hardware elements that may be electrically coupled via a bus **5604**. The hardware elements may include one or more central processing units (CPUs) **5608**; one or more input devices **5612** (e.g., a mouse, a keyboard, etc.); and one or more output devices **5616** (e.g., a display device, a printer, etc.). The computer system **5600** may also include one or more storage devices **5620**. By way of example, storage device(s) **5620** may be disk drives, optical storage devices, solid-state storage devices such as a random access memory ("RAM") and/or a read-only memory ("ROM"), which can be programmable, flash-updateable and/or the like.

The computer system **5600** may additionally include a computer-readable storage media reader **5624**; a communications system **5628** (e.g., a modem, a network card (wireless or wired), an infra-red communication device, etc.); and working memory **5636**, which may include RAM and ROM devices as described above. The computer system **5600** may also include a processing acceleration unit **5632**, which can include a DSP, a special-purpose processor, and/or the like.

The computer-readable storage media reader **5624** can further be connected to a computer-readable storage medium, together (and, optionally, in combination with storage device(s) **5620**) comprehensively representing remote, local, fixed, and/or removable storage devices plus storage media for temporarily and/or more permanently containing computer-readable information. The communications system **5628** may permit data to be exchanged with a network and/or any other computer described above with respect to the computer environments described herein. Moreover, as disclosed herein, the term "storage medium" may represent one or more devices for storing data, including read only memory (ROM), random access memory (RAM), magnetic RAM, core memory, magnetic disk storage mediums, optical storage mediums, flash memory devices and/or other machine readable mediums for storing information.

The computer system **5600** may also comprise software elements, shown as being currently located within a working memory **5636**, including an operating system **5640** and/or other code **5644**. It should be appreciated that alternate embodiments of a computer system **5600** may have numerous variations from that described above. For example, customized hardware might also be used and/or particular elements might be implemented in hardware, software (including portable software, such as applets), or both. Further, connection to other computing devices such as network input/output devices may be employed.

Examples of the processors **340**, **5608** as described herein may include, but are not limited to, at least one of Qualcomm® Snapdragon® 800 and 801, Qualcomm® Snapdragon® 620 and 615 with 4G LTE Integration and 64-bit computing, Apple® A7 processor with 64-bit architecture, Apple® M7 motion coprocessors, Samsung® Exynos® series, the Intel® Core™ family of processors, the Intel® Xeon® family of processors, the Intel® Atom™ family of

62

processors, the Intel Itanium® family of processors, Intel® Core® i5-4670K and i7-4770K 22 nm Haswell, Intel® Core® i5-3560K 22 nm Ivy Bridge, the AMD® FX™ family of processors, AMD® FX-4300, FX-6300, and FX-8350 32 nm Vishera, AMD® Kaveri processors, Texas Instruments® Jacinto C6000™ automotive infotainment processors, Texas Instruments® OMAP™ automotive-grade mobile processors, ARM® Cortex™-M processors, ARM® Cortex-A and ARM926EJ-S™ processors, other industry-equivalent processors, and may perform computational functions using any known or future-developed standard, instruction set, libraries, and/or architecture.

Any of the steps, functions, and operations discussed herein can be performed continuously and automatically.

Aspects of the embodiments can include: A vehicle, comprising: a sensor to: detect a first presence of a driver in a vehicle; detect a second presence of a passenger in the vehicle a memory to: store first sensitive information for the driver of the vehicle; store second sensitive information for a passenger in the vehicle; a processor in communication with the sensor and the memory, the processor to: receive the first presence and second presence; provide a user interface for the passenger to enter the sensitive information; receive the second sensitive information for the passenger; associate the second sensitive information with the vehicle; and send the second sensitive information to the memory for storage.

Any of the one or more above aspects, wherein the sensor receives biometric information associated with the passenger.

Any of the one or more above aspects, wherein the biometric information is also stored with the second sensitive information.

Any of the one or more above aspects, wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the second sensitive information is encrypted in the memory.

Any of the one or more above aspects, wherein the second sensitive information comprises one or more of a biometric, a username, a password, mobile device information, payment information, a personal identification number, identifiers, an address, limits, preferences, and/or rules.

Any of the one or more above aspects, wherein the second sensitive information comprises one or more of a desired product, a desired service, and/or a triggering event.

Any of the one or more above aspects, wherein the processor presents a user interface to a head unit display to receive the second sensitive information.

Any of the one or more above aspects, wherein the user interface receives input from the passenger in the user interface.

Any of the one or more above aspects, wherein the input includes financial information.

A method for associated passenger information with a vehicle, comprising: detecting a first presence of a driver in a vehicle; detecting a second presence of a passenger in the vehicle receiving the first presence and second presence; providing a user interface for the passenger to enter the sensitive information; receiving the second sensitive information for the passenger; associating the second sensitive information with the vehicle; and storing second sensitive information for a passenger in the vehicle.

Any of the one or more above aspects, wherein the sensor receives biometric information associated with the passenger, wherein the biometric information is also stored with the second sensitive information, and wherein, when the pas-

63

senger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the second sensitive information is encrypted in the memory, wherein the second sensitive information comprises one or more of a biometric, a username, a password, mobile device information, payment information, a personal identification number, identifiers, an address, limits, preferences, and/or rules.

Any of the one or more above aspects, wherein the second sensitive information comprises one or more of a desired product, a desired service, and/or a triggering event.

Any of the one or more above aspects, wherein the processor presents a user interface to receive the second sensitive information, wherein the user interface receives input from the passenger, and wherein the input includes financial information.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one or more processors, cause a vehicle to perform a method, the method comprising: detecting a first presence of a driver in a vehicle; detecting a second presence of a passenger in the vehicle receiving the first presence and second presence; providing a user interface for the passenger to enter the sensitive information; receiving the second sensitive information for the passenger; associating the second sensitive information with the vehicle; and storing second sensitive information for a passenger in the vehicle.

Any of the one or more above aspects, wherein the sensor receives biometric information associated with the passenger, wherein the biometric information is also stored with the second sensitive information, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the second sensitive information is encrypted in the memory, wherein the second sensitive information comprises one or more of a biometric, a username, a password, mobile device information, payment information, a personal identification number, identifiers, an address, limits, preferences, and/or rules.

Any of the one or more above aspects, wherein the second sensitive information comprises one or more of a desired product, a desired service, and/or a triggering event.

Any of the one or more above aspects, wherein the processor presents a user interface to receive the second sensitive information, wherein the user interface receives input from the passenger, and wherein the input includes financial information.

A vehicle, comprising: two or more radio frequency (RF) antennas to communicate wirelessly sensitive information associated with a user of the vehicle; two or more RF transceivers, each RF transceiver associated with one of the two or more RF antennas, the two or more RF transceivers to communicate wirelessly sensitive information associated with a user of the vehicle; a processor in communication with the two or more RF transceivers, the processor to: determine which one of the two or more RF antennas is receiving a strongest signal; select a first RF transceiver associated with the RF antenna with the strongest signal to send the sensitive information; and send the sensitive information to the first RF transceiver.

Any of the one or more above aspects, wherein the RF transceiver and RF antenna are a radio frequency identification device.

Any of the one or more above aspects, wherein the RFID device is an active RFID device.

Any of the one or more above aspects, wherein the first RF antenna is located near a side mirror of the vehicle.

64

Any of the one or more above aspects, wherein the first RF antenna communicates with a second RF antenna in physical proximity of a drive through window of a drive through restaurant.

Any of the one or more above aspects, wherein the first RF antenna is located on a roof of the vehicle.

Any of the one or more above aspects, wherein the first RF antenna communicates with a second RF antenna in above the vehicle in a toll lane.

Any of the one or more above aspects, wherein the first RF antenna is located near a charging port or a gas refill door.

Any of the one or more above aspects, wherein the first RF antenna communicates with a second RF antenna on a charging station or gas pump.

Any of the one or more above aspects, wherein the vehicle contemporaneously communicates through two or more RF antennas.

A method for communicating information with a vehicle, comprising: receiving a signal at one of two or more radio frequency (RF) antennas and one of two or more RF transceivers, wherein each RF transceiver is associated with one of the two or more RF antennas, to communicate wirelessly sensitive information associated with a user of the vehicle; determining which one of the two or more RF antennas is receiving a strongest signal; selecting a first RF transceiver associated with the RF antenna with the strongest signal to send the sensitive information; and sending the sensitive information through the first RF transceiver.

Any of the one or more above aspects, wherein the RF transceiver and RF antenna are a radio frequency identification device, and wherein the RFID device is an active RFID device.

Any of the one or more above aspects, wherein the first RF antenna is located near a side mirror of the vehicle, wherein the first RF antenna communicates with a second RF antenna in physical proximity of a drive through window of a drive through restaurant.

Any of the one or more above aspects, wherein the first RF antenna is located on a roof of the vehicle, and wherein the first RF antenna communicates with a second RF antenna in above the vehicle in a toll lane.

Any of the one or more above aspects, wherein the first RF antenna is located near a charging port or a gas refill door, and wherein the first RF antenna communicates with a second RF antenna on a charging station or gas pump.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one or more processors, cause a vehicle to perform a method, the method comprising: receiving a signal at one of two or more radio frequency (RF) antennas and one of two or more RF transceivers, wherein each RF transceiver is associated with one of the two or more RF antennas, to communicate wirelessly sensitive information associated with a user of the vehicle; determining which one of the two or more RF antennas is receiving a strongest signal; selecting a first RF transceiver associated with the RF antenna with the strongest signal to send the sensitive information; and sending the sensitive information through the first RF transceiver.

Any of the one or more above aspects, wherein the RF transceiver and RF antenna are a radio frequency identification device, and wherein the RFID device is an active RFID device.

Any of the one or more above aspects, wherein the first RF antenna is located near a side mirror of the vehicle,

65

wherein the first RF antenna communicates with a second RF antenna in physical proximity of a drive through window of a drive through restaurant.

Any of the one or more above aspects, wherein the first RF antenna is located on a roof of the vehicle, and wherein the first RF antenna communicates with a second RF antenna in above the vehicle in a toll lane.

Any of the one or more above aspects, wherein the first RF antenna is located near a charging port or a gas refill door, and wherein the first RF antenna communicates with a second RF antenna on a charging station or gas pump.

A vehicle, comprising: a sensor to: detect a presence of a driver in a vehicle; a memory to: store sensitive information for the driver of the vehicle; a processor in communication with the sensor and the memory, the processor to: receive the presence; based upon receiving the presence, provide a user interface for the passenger to enter user information; receive vehicle information associated with the vehicle; combine the user information and the vehicle information to generate sensitive information; and send the sensitive information to the memory for storage.

Any of the one or more above aspects, wherein the sensor receives biometric information associated with the passenger.

Any of the one or more above aspects, wherein the biometric information is also stored with the sensitive information.

Any of the one or more above aspects, wherein the sensitive information is sent to a third party to authenticate the user.

Any of the one or more above aspects, wherein the sensitive information is encrypted in the memory.

Any of the one or more above aspects, wherein the user information comprises one or more of a biometric, a user-name, a password, mobile device information, payment information, a personal identification number, identifiers, an address, limits, preferences, and/or rules.

Any of the one or more above aspects, wherein the user information comprises one or more of a desired product, a desired service, and/or a triggering event.

Any of the one or more above aspects, wherein the processor presents a user interface to a head unit display to receive the second sensitive information.

Any of the one or more above aspects, wherein the user interface receives input from the passenger in the user interface, wherein the input includes financial information.

Any of the one or more above aspects, wherein the vehicle information comprises a vehicle identification number (VIN), an electronic serial number (ESN), and/or an engine code.

A method for communicating information with a vehicle, comprising: detecting a presence of a driver in a vehicle; based upon receiving the presence, providing a user interface for the passenger to enter user information; receiving vehicle information associated with the vehicle; combining the user information and the vehicle information to generate sensitive information; and sending the sensitive information to the memory for storage.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein the biometric information is also stored with the sensitive information.

Any of the one or more above aspects, wherein the sensitive information is sent to a third party to authenticate the user.

Any of the one or more above aspects, wherein the user information comprises one or more of a biometric, a user-

66

name, a password, mobile device information, payment information, a personal identification number, identifiers, an address, limits, preferences, rules, a desired product, a desired service, and/or a triggering event.

Any of the one or more above aspects, wherein the vehicle information comprises a vehicle identification number (VIN), an electronic serial number (ESN), and/or an engine code.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one or more processors, cause a vehicle to perform a method, the method comprising: detecting a presence of a driver in a vehicle; based upon receiving the presence, providing a user interface for the passenger to enter user information; receiving vehicle information associated with the vehicle; combining the user information and the vehicle information to generate sensitive information; and sending the sensitive information to the memory for storage.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein the biometric information is also stored with the sensitive information.

Any of the one or more above aspects, wherein the sensitive information is sent to a third party to authenticate the user.

Any of the one or more above aspects, wherein the user information comprises one or more of a biometric, a user-name, a password, mobile device information, payment information, a personal identification number, identifiers, an address, limits, preferences, rules, a desired product, a desired service, and/or a triggering event.

Any of the one or more above aspects, wherein the vehicle information comprises a vehicle identification number (VIN), an electronic serial number (ESN), and/or an engine code.

A vehicle, comprising: a navigation system to provide a location and/or a route of the vehicle; a memory to: store user preferences associated with a user in the vehicle; a processor in communication with the navigation system and the memory, the processor to: determine a third party resident in the location and/or on the route of the vehicle; retrieve user preferences from the memory; determine, based on the user preferences, whether the user would desire to communicate with the third party; and automatically send a first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger.

Any of the one or more above aspects, wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service.

Any of the one or more above aspects, wherein user preference is a usual order based on historical information from a user's past behavior.

Any of the one or more above aspects, wherein the user is prompted to approve the first communication with a user interface displayed in a display in the vehicle.

Any of the one or more above aspects, wherein the vehicle sends a second communication to complete an interaction with the third party.

Any of the one or more above aspects, wherein the second communication is sent when the vehicle is in physical proximity to the third party.

Any of the one or more above aspects, wherein the second communication is a final authorization for a transaction.

67

Any of the one or more above aspects, wherein the final authorization includes a PIN entered by the user in a display of the vehicle.

A method for communicating information with a vehicle, comprising: determining a location and/or a route of the vehicle; determining a third party resident in the location and/or on the route of the vehicle; retrieving user preferences associated with a user in the vehicle from a memory; determining, based on the user preferences, whether the user would desire to communicate with the third party; and automatically sending a first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service, wherein user preference is a usual order based on historical information from a user's past behavior, and wherein the user is prompted to approve the first communication with a user interface displayed in a display in the vehicle.

Any of the one or more above aspects, wherein the vehicle sends a second communication to complete an interaction with the third party, and wherein the second communication is sent when the vehicle is in physical proximity to the third party.

Any of the one or more above aspects, wherein the second communication is a final authorization for a transaction, and wherein the final authorization includes a PIN entered by the user in a display of the vehicle.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one or more processors, cause a vehicle to perform a method, the method comprising: determining a location and/or a route of the vehicle; determining a third party resident in the location and/or on the route of the vehicle; retrieving user preferences associated with a user in the vehicle from a memory; determining, based on the user preferences, whether the user would desire to communicate with the third party; and automatically sending a first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service, wherein user preference is a usual order based on historical information from a user's past behavior, and wherein the user is prompted to approve the first communication with a user interface displayed in a display in the vehicle.

Any of the one or more above aspects, wherein the vehicle sends a second communication to complete an interaction with the third party, and wherein the second communication is sent when the vehicle is in physical proximity to the third party.

Any of the one or more above aspects, wherein the second communication is a final authorization for a transaction, and wherein the final authorization includes a PIN entered by the user in a display of the vehicle.

A vehicle, comprising: a display in the vehicle to display a user interface; a processor in communication with the display, the processor to: determine a user in the vehicle desires to interact with a third party; render the user interface

68

for the display to request authorization from the user to allow a communication to the third party; receive user input associated with the request for authorization; and based on the user input, automatically send a first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger.

Any of the one or more above aspects, wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service.

Any of the one or more above aspects, wherein the user interface is an authorization for the vehicle to pre-order the good or service.

Any of the one or more above aspects, wherein the vehicle sends a second communication to complete an interaction with the third party.

Any of the one or more above aspects, wherein the second communication is sent when the vehicle is in physical proximity to the third party.

Any of the one or more above aspects, wherein the second communication is a final authorization for a transaction.

Any of the one or more above aspects, wherein the user interface is presented to authorize finally the second communication.

Any of the one or more above aspects, wherein the final authorization includes a PIN entered by the user in the user interface.

A method for communicating information with a vehicle, comprising: determining a user in the vehicle desires to interact with a third party; displaying a user interface to request authorization from the user to allow a communication to the third party; receiving user input associated with the request for authorization; and based on the user input, automatically sending a first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service, and wherein the user interface is an authorization for the vehicle to pre-order the good or service.

Any of the one or more above aspects, wherein the vehicle sends a second communication to complete an interaction with the third party, and wherein the second communication is sent when the vehicle is in physical proximity to the third party.

Any of the one or more above aspects, wherein the second communication is a final authorization for a transaction, wherein the user interface is presented to authorize finally the second communication, and wherein the final authorization includes a PIN entered by the user in the user interface.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one or more processors, cause a vehicle to perform a method, the method comprising: determining a user in the vehicle desires to interact with a third party; displaying a user interface to request authorization from the user to allow a communication to the third party; receiving user input associated with

the request for authorization; and based on the user input, automatically sending a first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service, and wherein the user interface is an authorization for the vehicle to pre-order the good or service.

Any of the one or more above aspects, wherein the vehicle sends a second communication to complete an interaction with the third party, and wherein the second communication is sent when the vehicle is in physical proximity to the third party.

Any of the one or more above aspects, wherein the second communication is a final authorization for a transaction, wherein the user interface is presented to authorize finally the second communication, and wherein the final authorization includes a PIN entered by the user in the user interface.

A vehicle, comprising: a memory to: store user information associated with a user in the vehicle; store vehicle information associated with the vehicle; a processor in communication with the memory, the processor to: determine the user desires to interact with a third party; retrieve user information from the memory; retrieve vehicle information from the memory; combine the user information and the vehicle information into a first communication for the third party; and automatically send the first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger.

Any of the one or more above aspects, wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service and the user information and vehicle information authenticate the user for the order.

Any of the one or more above aspects, wherein the user information comprises financial information, biometric information, and/or a PIN.

Any of the one or more above aspects, wherein the vehicle information comprises a vehicle identification number, an electronic serial number, and/or an engine code.

Any of the one or more above aspects, wherein the vehicle sends a second communication to complete an interaction with the third party, and wherein the second communication is sent when the vehicle is in physical proximity to the third party.

Any of the one or more above aspects, wherein the second communication is a final authorization for a transaction.

Any of the one or more above aspects, wherein the second communication includes user information or vehicle information not in the first communication.

Any of the one or more above aspects, wherein the final authorization includes a PIN entered by the user in a user interface in the vehicle.

A method for communicating information with a vehicle, comprising: storing user information associated with a user in the vehicle; storing vehicle information associated with the vehicle determining the user desires to interact with a third party; combining the user information and the vehicle

information into a first communication for the third party; and automatically send the first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service and the user information and vehicle information authenticate the user for the order.

Any of the one or more above aspects, wherein the user information comprises financial information, biometric information, and/or a PIN, and wherein the vehicle information comprises a vehicle identification number, an electronic serial number, and/or an engine code.

Any of the one or more above aspects, wherein the vehicle sends a second communication to complete an interaction with the third party, and wherein the second communication is sent when the vehicle is in physical proximity to the third party, wherein the second communication is a final authorization for a transaction, wherein the second communication includes user information or vehicle information not in the first communication, and wherein the final authorization includes a PIN entered by the user in a user interface in the vehicle.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one or more processors, cause a vehicle to perform a method, the method comprising: storing user information associated with a user in the vehicle; storing vehicle information associated with the vehicle determining the user desires to interact with a third party; combining the user information and the vehicle information into a first communication for the third party; and automatically send the first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service and the user information and vehicle information authenticate the user for the order.

Any of the one or more above aspects, wherein the user information comprises financial information, biometric information, and/or a PIN, and wherein the vehicle information comprises a vehicle identification number, an electronic serial number, and/or an engine code.

Any of the one or more above aspects, wherein the vehicle sends a second communication to complete an interaction with the third party, and wherein the second communication is sent when the vehicle is in physical proximity to the third party, wherein the second communication is a final authorization for a transaction, wherein the second communication includes user information or vehicle information not in the first communication, and wherein the final authorization includes a PIN entered by the user in a user interface in the vehicle.

A vehicle, comprising: a memory to store limits on communications associated with a user in the vehicle; a processor in communication with the memory, the processor to: determine the user desires to interact with a third party; retrieve the limits from the memory; based on the limits, determine if the vehicle can send a first communication for

the third party; and when allowed by the limits, automatically send the first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information 5 associated with the passenger.

Any of the one or more above aspects, wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service and the limits are a monetary limit applied to the order.

Any of the one or more above aspects, wherein the limit applies only to the user and the vehicle.

Any of the one or more above aspects, wherein the limit applies only to the user and to two or more vehicles.

Any of the one or more above aspects, wherein the limit applies only to two or more users and the vehicle.

Any of the one or more above aspects, wherein the limit is set on the user by a second user.

Any of the one or more above aspects, wherein the limit is on a number of communications that may be completed between the vehicle and third party.

Any of the one or more above aspects, wherein the limit only applies for a predetermined time period or route.

A method for communicating information with a vehicle, comprising: a memory storing limits on communications associated with a user in the vehicle; a processor determining the user desires to interact with a third party; retrieving the limits from the memory; based on the limits, determining if the vehicle can send a first communication for the third party; and when allowed by the limits, automatically sending the first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service and the limits are a monetary limit applied to the order.

Any of the one or more above aspects, wherein one or more of: the limit applies only to the user and the vehicle, the limit applies only to the user and to two or more vehicles, the limit applies only to two or more users and the vehicle, and/or the limit is set on the user by a second user.

Any of the one or more above aspects, wherein the limit only applies for a predetermined time period or route.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one or more processors, cause a vehicle to perform a method, the method comprising: storing limits on communications associated with a user in the vehicle; determining the user desires to interact with a third party; retrieving the limits from the memory; based on the limits, determining if the vehicle can send a first communication for the third party; and when allowed by the limits, automatically sending the first communication to the third party for the user.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service and the limits are a monetary limit applied to the order.

Any of the one or more above aspects, wherein one or more of: the limit applies only to the user and the vehicle, the limit applies only to the user and to two or more vehicles,

the limit applies only to two or more users and the vehicle, and/or the limit is set on the user by a second user.

Any of the one or more above aspects, wherein the limit only applies for a predetermined time period or route.

A vehicle, comprising: a memory to store a user rule applicable to communications associated with a user in the vehicle; a processor in communication with the memory, the processor to: determine a need for communication with a third party; retrieve the user rule from the memory; based on the user rule, determine to which third party the vehicle can send a first communication to address the need; select the third party; and when determined by the user rule, automatically send the first communication to the selected third party to address the need.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger.

Any of the one or more above aspects, wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service.

Any of the one or more above aspects, wherein the user rule determines a distance the vehicle can travel to the third party.

Any of the one or more above aspects, wherein the user rule determines a monetary amount the vehicle can pay to the third party.

Any of the one or more above aspects, wherein the user rule allows the processor to bargain with the third party.

Any of the one or more above aspects, wherein the third party also has a vendor rule to govern an interaction with the vehicle.

Any of the one or more above aspects, wherein the user rule allows a search of two or more third parties that can address the need.

Any of the one or more above aspects, wherein the user rule is a time limit to address the need.

A method for communicating information with a vehicle, comprising: a memory storing a user rule applicable to communications associated with a user in the vehicle; a processor determining a need for communication with a third party; retrieving the user rule from the memory; based on the user rule, determining to which third party the vehicle can send a first communication to address the need; selecting the third party; and when determined by the user rule, automatically sending the first communication to the selected third party to address the need.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service.

Any of the one or more above aspects, wherein one or more of: wherein the user rule determines a distance the vehicle can travel to the third party, wherein the user rule determines a monetary amount the vehicle can pay to the third party, wherein the user rule allows the processor to bargain with the third, and/or wherein the user rule is a time limit to address the need.

Any of the one or more above aspects, wherein the user rule allows a search of two or more third parties that can address the need.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one

or more processors, cause a vehicle to perform a method, the method comprising: storing a user rule applicable to communications associated with a user in the vehicle; determining a need for communication with a third party; retrieving the user rule from the memory; based on the user rule, determining to which third party the vehicle can send a first communication to address the need; selecting the third party; and when determined by the user rule, automatically sending the first communication to the selected third party to address the need.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service.

Any of the one or more above aspects, wherein one or more of: wherein the user rule determines a distance the vehicle can travel to the third party, wherein the user rule determines a monetary amount the vehicle can pay to the third party, wherein the user rule allows the processor to bargain with the third, and/or wherein the user rule is a time limit to address the need.

Any of the one or more above aspects, wherein the user rule allows a search of two or more third parties that can address the need.

A vehicle, comprising: a memory to store triggering event information applicable to communications associated with a user in the vehicle; a processor in communication with the memory, the processor to: determine a triggering event has occurred; retrieve the triggering event information from the memory; based on the triggering event information, determine a third party to which the vehicle send a first communication; and when determined by the trigger event information, automatically send the first communication to the selected third party to address the need.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger.

Any of the one or more above aspects, wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service.

Any of the one or more above aspects, wherein the triggering event information causes a change to a user interface in the vehicle.

Any of the one or more above aspects, wherein the triggering event is a weather related event.

Any of the one or more above aspects, wherein the first communication purchases weather information to be overlaid on the user interface.

Any of the one or more above aspects, wherein the triggering event is a police action.

Any of the one or more above aspects, wherein the first communication purchases real time traffic information to be overlaid on the user interface to avoid the police action.

Any of the one or more above aspects, wherein the triggering event is a malfunction of the vehicle, and wherein the first communication purchases a tow service or a part to address the malfunction.

A method for communicating information with a vehicle, comprising: a memory storing triggering event information applicable to communications associated with a user in the vehicle; a processor determining a triggering event has occurred; retrieving the triggering event information from

the memory; based on the triggering event information, determining a third party to which the vehicle send a first communication; and when determined by the trigger event information, automatically sending the first communication to the selected third party to address the need.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service.

Any of the one or more above aspects, wherein the triggering event information causes a change to a user interface in the vehicle, wherein the triggering event is a weather related event, and wherein the first communication purchases weather information to be overlaid on the user interface.

Any of the one or more above aspects, wherein the triggering event information causes a change to a user interface in the vehicle, wherein the triggering event is a police action, and wherein the first communication purchases real time traffic information to be overlaid on the user interface to avoid the police action.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one or more processors, cause a vehicle to perform a method, the method comprising: storing triggering event information applicable to communications associated with a user in the vehicle; determining a triggering event has occurred; retrieving the triggering event information from the memory; based on the triggering event information, determining a third party to which the vehicle send a first communication; and when determined by the trigger event information, automatically sending the first communication to the selected third party to address the need.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is an order for a good or service.

Any of the one or more above aspects, wherein the triggering event information causes a change to a user interface in the vehicle, wherein the triggering event is a weather related event, and wherein the first communication purchases weather information to be overlaid on the user interface.

Any of the one or more above aspects, wherein the triggering event information causes a change to a user interface in the vehicle, wherein the triggering event is a police action, and wherein the first communication purchases real time traffic information to be overlaid on the user interface to avoid the police action.

A vehicle, comprising: two or more soft touch radio frequency (RF) antennas to communicate sensitive information associated with a user of the vehicle; two or more RF transceivers, each RF transceiver associated with one of the two or more soft touch RF antennas, the two or more RF transceivers to communicate sensitive information associated with a user of the vehicle; a processor in communication with the two or more RF transceivers, the processor to: receive an input to deploy one of the two or more RF antennas; select a first RF transceiver associated with the deployed RF antenna to send the sensitive information; and send the sensitive information to the first RF transceiver.

75

Any of the one or more above aspects, wherein the RF transceiver and RF antenna are a radio frequency identification device.

Any of the one or more above aspects, wherein the RFID device is an active RFID device.

Any of the one or more above aspects, wherein the deployed RF antenna is located near a side mirror of the vehicle.

Any of the one or more above aspects, wherein the deployed RF antenna contacts a pad physically attached to a structure, associated with a second RF antenna, in physical proximity with a drive through window of a drive through restaurant.

Any of the one or more above aspects, wherein the deployed RF antenna is located on a roof of the vehicle.

Any of the one or more above aspects, wherein the deployed RF antenna contacts a pad physically attached to a structure, associated with a second RF antenna, above the vehicle in a toll lane.

Any of the one or more above aspects, wherein the deployed RF antenna is located near a charging port or a gas refill door.

Any of the one or more above aspects, wherein the deployed RF antenna contacts a pad physically attached to a structure on a charging station or gas pump.

Any of the one or more above aspects, wherein the vehicle contemporaneously communicates through two or more soft touch RF antennas.

A method for communicating information with a vehicle, comprising: receiving an input to deploy one of two or more soft touch radio frequency (RF) antennas to communicate sensitive information associated with a user of the vehicle; selecting a first RF transceiver associated with the deployed RF antenna to send the sensitive information; and sending the sensitive information through the first RF transceiver.

Any of the one or more above aspects, wherein the RF transceiver and RF antenna are a radio frequency identification device, and wherein the RFID device is an active RFID device.

Any of the one or more above aspects, wherein the deployed RF antenna is located near a side mirror of the vehicle, and wherein the deployed RF antenna contacts a pad physically attached to a structure, associated with a second RF antenna, in physical proximity with a drive through window of a drive through restaurant.

Any of the one or more above aspects, wherein the deployed RF antenna is located on a roof of the vehicle, and wherein the deployed RF antenna contacts a pad physically attached to a structure, associated with a second RF antenna, above the vehicle in a toll lane.

Any of the one or more above aspects, wherein the deployed RF antenna is located near a charging port or a gas refill door, and wherein the deployed RF antenna contacts a pad physically attached to a structure on a charging station or gas pump.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one or more processors, cause a vehicle to perform a method, the method comprising: receiving an input to deploy one of two or more soft touch radio frequency (RF) antennas to communicate sensitive information associated with a user of the vehicle; selecting a first RF transceiver associated with the deployed RF antenna to send the sensitive information; and sending the sensitive information through the first RF transceiver.

76

Any of the one or more above aspects, wherein the RF transceiver and RF antenna are a radio frequency identification device, and wherein the RFID device is an active RFID device.

Any of the one or more above aspects, wherein the deployed RF antenna is located near a side mirror of the vehicle, and wherein the deployed RF antenna contacts a pad physically attached to a structure, associated with a second RF antenna, in physical proximity with a drive through window of a drive through restaurant.

Any of the one or more above aspects, wherein the deployed RF antenna is located on a roof of the vehicle, and wherein the deployed RF antenna contacts a pad physically attached to a structure, associated with a second RF antenna, above the vehicle in a toll lane.

Any of the one or more above aspects, wherein the deployed RF antenna is located near a charging port or a gas refill door, and wherein the deployed RF antenna contacts a pad physically attached to a structure on a charging station or gas pump.

A vehicle, comprising: a memory to: store sensitive information associated with a user in the vehicle; store user preferences associated with a user in the vehicle a processor in communication with the memory, the processor to: based on the user preferences, determine the user desires to communicate with a third party in an interaction; automatically send a first communication to the third party; and send a second communication to the third party for the user to complete the interaction.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger.

Any of the one or more above aspects, wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is a pre-order for a good or service.

Any of the one or more above aspects, wherein user preference is a usual order based on historical information from a user's past behavior.

Any of the one or more above aspects, wherein the user is prompted to approve the first communication with a user interface displayed in a display in the vehicle.

Any of the one or more above aspects, wherein the second communication is an authorization to complete the order with the third party.

Any of the one or more above aspects, wherein the second communication is sent when the vehicle is in physical proximity to the third party.

Any of the one or more above aspects, wherein the first communication is sent over a first communication network, wherein the second communication is sent over a second communication network, and wherein the first and second communication networks are different.

Any of the one or more above aspects, wherein the first communication is sent when the vehicle is distant from the third party.

A method for communicating information with a vehicle, comprising: storing sensitive information associated with a user in the vehicle; storing user preferences associated with a user in the vehicle based on the user preferences, determining the user desires to communicate with a third party in an interaction; automatically sending a first communication to the third party; and sending a second communication to the third party for the user to complete the interaction.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information

associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is a pre-order for a good or service.

Any of the one or more above aspects, wherein user preference is a usual order based on historical information from a user's past behavior, and wherein the user is prompted to approve the first communication with a user interface displayed in a display in the vehicle.

Any of the one or more above aspects, wherein the second communication is sent when the vehicle is in physical proximity to the third party, wherein the first communication is sent over a first communication network, wherein the second communication is sent over a second communication network, and wherein the first and second communication networks are different, and wherein the first communication is sent when the vehicle is distant from the third party.

A non-transitory information storage media having stored thereon one or more instructions, that when executed by one or more processors, cause a vehicle to perform a method, the method comprising: storing sensitive information associated with a user in the vehicle; storing user preferences associated with a user in the vehicle based on the user preferences, determining the user desires to communicate with a third party in an interaction; automatically sending a first communication to the third party; and sending a second communication to the third party for the user to complete the interaction.

Any of the one or more above aspects, wherein a sensor associated with the vehicle receives biometric information associated with the passenger, and wherein, when the passenger enters the vehicle a second time, the biometric information identifies the passenger.

Any of the one or more above aspects, wherein the first communication is a pre-order for a good or service.

Any of the one or more above aspects, wherein user preference is a usual order based on historical information from a user's past behavior, and wherein the user is prompted to approve the first communication with a user interface displayed in a display in the vehicle.

Any of the one or more above aspects, wherein the second communication is sent when the vehicle is in physical proximity to the third party, wherein the first communication is sent over a first communication network, wherein the second communication is sent over a second communication network, and wherein the first and second communication networks are different, and wherein the first communication is sent when the vehicle is distant from the third party.

A means, system, SOC, ASIC, FPGA, device, circuit, component, software component, or other module for conducting any of the methods and/or any of the one or more aspects above.

The exemplary systems and methods of this disclosure have been described in relation to vehicle systems and electric vehicles. However, to avoid unnecessarily obscuring the present disclosure, the preceding description omits a number of known structures and devices. This omission is not to be construed as a limitation of the scope of the claimed disclosure. Specific details are set forth to provide an understanding of the present disclosure. It should, however, be appreciated that the present disclosure may be practiced in a variety of ways beyond the specific detail set forth herein.

Furthermore, while the exemplary embodiments illustrated herein show the various components of the system collocated, certain components of the system can be located remotely, at distant portions of a distributed network, such as

a LAN and/or the Internet, or within a dedicated system. Thus, it should be appreciated, that the components of the system can be combined into one or more devices, such as a server, communication device, or collocated on a particular node of a distributed network, such as an analog and/or digital telecommunications network, a packet-switched network, or a circuit-switched network. It will be appreciated from the preceding description, and for reasons of computational efficiency, that the components of the system can be arranged at any location within a distributed network of components without affecting the operation of the system. For example, the various components can be located in a switch such as a PBX and media server, gateway, in one or more communications devices, at one or more users' premises, or some combination thereof. Similarly, one or more functional portions of the system could be distributed between a telecommunications device(s) and an associated computing device.

Furthermore, it should be appreciated that the various links connecting the elements can be wired or wireless links, or any combination thereof, or any other known or later developed element(s) that is capable of supplying and/or communicating data to and from the connected elements. These wired or wireless links can also be secure links and may be capable of communicating encrypted information. Transmission media used as links, for example, can be any suitable carrier for electrical signals, including coaxial cables, copper wire, and fiber optics, and may take the form of acoustic or light waves, such as those generated during radio-wave and infra-red data communications.

While the flowcharts have been discussed and illustrated in relation to a particular sequence of events, it should be appreciated that changes, additions, and omissions to this sequence can occur without materially affecting the operation of the disclosed embodiments, configuration, and aspects.

A number of variations and modifications of the disclosure can be used. It would be possible to provide for some features of the disclosure without providing others.

In yet another embodiment, the systems and methods of this disclosure can be implemented in conjunction with a special purpose computer, a programmed microprocessor or microcontroller and peripheral integrated circuit element(s), an ASIC or other integrated circuit, a digital signal processor, a hard-wired electronic or logic circuit such as discrete element circuit, a programmable logic device or gate array such as PLD, PLA, FPGA, PAL, special purpose computer, any comparable means, or the like. In general, any device(s) or means capable of implementing the methodology illustrated herein can be used to implement the various aspects of this disclosure. Exemplary hardware that can be used for the present disclosure includes computers, handheld devices, telephones (e.g., cellular, Internet enabled, digital, analog, hybrids, and others), and other hardware known in the art. Some of these devices include processors (e.g., a single or multiple microprocessors), memory, nonvolatile storage, input devices, and output devices. Furthermore, alternative software implementations including, but not limited to, distributed processing or component/object distributed processing, parallel processing, or virtual machine processing can also be constructed to implement the methods described herein.

In yet another embodiment, the disclosed methods may be readily implemented in conjunction with software using object or object-oriented software development environments that provide portable source code that can be used on a variety of computer or workstation platforms. Alterna-

tively, the disclosed system may be implemented partially or fully in hardware using standard logic circuits or VLSI design. Whether software or hardware is used to implement the systems in accordance with this disclosure is dependent on the speed and/or efficiency requirements of the system, the particular function, and the particular software or hardware systems or microprocessor or microcomputer systems being utilized.

In yet another embodiment, the disclosed methods may be partially implemented in software that can be stored on a storage medium, executed on programmed general-purpose computer with the cooperation of a controller and memory, a special purpose computer, a microprocessor, or the like. In these instances, the systems and methods of this disclosure can be implemented as a program embedded on a personal computer such as an applet, JAVA® or CGI script, as a resource residing on a server or computer workstation, as a routine embedded in a dedicated measurement system, system component, or the like. The system can also be implemented by physically incorporating the system and/or method into a software and/or hardware system.

Although the present disclosure describes components and functions implemented in the embodiments with reference to particular standards and protocols, the disclosure is not limited to such standards and protocols. Other similar standards and protocols not mentioned herein are in existence and are considered to be included in the present disclosure. Moreover, the standards and protocols mentioned herein and other similar standards and protocols not mentioned herein are periodically superseded by faster or more effective equivalents having essentially the same functions. Such replacement standards and protocols having the same functions are considered equivalents included in the present disclosure.

The present disclosure, in various embodiments, configurations, and aspects, includes components, methods, processes, systems and/or apparatus substantially as depicted and described herein, including various embodiments, sub-combinations, and subsets thereof. Those of skill in the art will understand how to make and use the systems and methods disclosed herein after understanding the present disclosure. The present disclosure, in various embodiments, configurations, and aspects, includes providing devices and processes in the absence of items not depicted and/or described herein or in various embodiments, configurations, or aspects hereof, including in the absence of such items as may have been used in previous devices or processes, e.g., for improving performance, achieving ease, and/or reducing cost of implementation.

The foregoing discussion of the disclosure has been presented for purposes of illustration and description. The foregoing is not intended to limit the disclosure to the form or forms disclosed herein. In the foregoing Detailed Description for example, various features of the disclosure are grouped together in one or more embodiments, configurations, or aspects for the purpose of streamlining the disclosure. The features of the embodiments, configurations, or aspects of the disclosure may be combined in alternate embodiments, configurations, or aspects other than those discussed above. This method of disclosure is not to be interpreted as reflecting an intention that the claimed disclosure requires more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive aspects lie in less than all features of a single foregoing disclosed embodiment, configuration, or aspect. Thus, the following claims are hereby incorporated into this Detailed

Description, with each claim standing on its own as a separate preferred embodiment of the disclosure.

Moreover, though the description of the disclosure has included description of one or more embodiments, configurations, or aspects and certain variations and modifications, other variations, combinations, and modifications are within the scope of the disclosure, e.g., as may be within the skill and knowledge of those in the art, after understanding the present disclosure. It is intended to obtain rights, which include alternative embodiments, configurations, or aspects to the extent permitted, including alternate, interchangeable and/or equivalent structures, functions, ranges, or steps to those claimed, whether or not such alternate, interchangeable and/or equivalent structures, functions, ranges, or steps are disclosed herein, and without intending to publicly dedicate any patentable subject matter.

The phrases “at least one,” “one or more,” “or,” and “and/or” are open-ended expressions that are both conjunctive and disjunctive in operation. For example, each of the expressions “at least one of A, B and C,” “at least one of A, B, or C,” “one or more of A, B, and C,” “one or more of A, B, or C,” “A, B, and/or C,” and “A, B, or C” means A alone, B alone, C alone, A and B together, A and C together, B and C together, or A, B and C together.

The term “a” or “an” entity refers to one or more of that entity. As such, the terms “a” (or “an”), “one or more,” and “at least one” can be used interchangeably herein. It is also to be noted that the terms “comprising,” “including,” and “having” can be used interchangeably.

The term “automatic” and variations thereof, as used herein, refers to any process or operation, which is typically continuous or semi-continuous, done without material human input when the process or operation is performed. However, a process or operation can be automatic, even though performance of the process or operation uses material or immaterial human input, if the input is received before performance of the process or operation. Human input is deemed to be material if such input influences how the process or operation will be performed. Human input that consents to the performance of the process or operation is not deemed to be “material.”

Aspects of the present disclosure may take the form of an embodiment that is entirely hardware, an embodiment that is entirely software (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as a “circuit,” “module,” or “system.” Any combination of one or more computer-readable medium(s) may be utilized. The computer-readable medium may be a computer-readable signal medium or a computer-readable storage medium.

A computer-readable storage medium may be, for example, but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, or device, or any suitable combination of the foregoing. More specific examples (a non-exhaustive list) of the computer-readable storage medium would include the following: an electrical connection having one or more wires, a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, a portable compact disc read-only memory (CD-ROM), an optical storage device, a magnetic storage device, or any suitable combination of the foregoing. In the context of this document, a computer-readable storage medium may be any tangible medium that can contain or store a program for use by or in connection with an instruction execution system, apparatus, or device.

81

A computer-readable signal medium may include a propagated data signal with computer-readable program code embodied therein, for example, in baseband or as part of a carrier wave. Such a propagated signal may take any of a variety of forms, including, but not limited to, electro-
magnetic, optical, or any suitable combination thereof. A computer-readable signal medium may be any computer-readable medium that is not a computer-readable storage medium and that can communicate, propagate, or transport a program for use by or in connection with an instruction execution system, apparatus, or device. Program code embodied on a computer-readable medium may be transmitted using any appropriate medium, including, but not limited to, wireless, wireline, optical fiber cable, RF, etc., or any suitable combination of the foregoing.

The terms “determine,” “calculate,” “compute,” and variations thereof, as used herein, are used interchangeably and include any type of methodology, process, mathematical operation or technique.

Examples of the processors as described herein may include, but are not limited to, at least one of Qualcomm® Snapdragon® 800 and 801, Qualcomm® Snapdragon® 610 and 615 with 4G LTE Integration and 64-bit computing, Apple® A7 processor with 64-bit architecture, Apple® M7 motion coprocessors, Samsung® Exynos® series, the Intel® Core™ family of processors, the Intel® Xeon® family of processors, the Intel® Atom™ family of processors, the Intel Itanium® family of processors, Intel® Core® i5-4670K and i7-4770K 22 nm Haswell, Intel® Core® i5-3570K 22 nm Ivy Bridge, the AMD® FX™ family of processors, AMD® FX-4300, FX-6300, and FX-8350 32 nm Vishera, AMD® Kaveri processors, Texas Instruments® Jacinto C6000™ automotive infotainment processors, Texas Instruments® OMAP™ automotive-grade mobile processors, ARM® Cortex™-M processors, ARM® Cortex-A and ARM926EJ-S™ processors, other industry-equivalent processors, and may perform computational functions using any known or future-developed standard, instruction set, libraries, and/or architecture.

The term “means” as used herein shall be given its broadest possible interpretation in accordance with 35 U.S.C., Section 112(f) and/or Section 112, Paragraph 6. Accordingly, a claim incorporating the term “means” shall cover all structures, materials, or acts set forth herein, and all of the equivalents thereof. Further, the structures, materials or acts and the equivalents thereof shall include all those described in the summary, brief description of the drawings, detailed description, abstract, and claims themselves.

What is claimed is:

1. A vehicle, comprising:

a memory to store a user rule applicable to third party vendor communications associated with a user in the vehicle;

a processor in communication with the memory, the processor is programmed to:

determine a need for communication with a third party vendor;

retrieve the user rule from the memory, wherein the user rule defines to which third party vendor the vehicle can send a first communication to address the need, the need relating to a product or service of the third party vendor and wherein the user rule defines one or more of a geographic location of the third party vendor relative to a current location of the vehicle, a monetary amount the vehicle can pay to a third party vendor for a product or service to address

82

the need, and a time limit for the third party vendor to provide the product or service to address the need; based on the user rule, select a third party vendor from among multiple possible third party vendors, wherein each of the multiple possible third party vendors is capable of providing the product or service to meet the need; and

when determined by the user rule, automatically send the first communication to the selected third party vendor to address the need, wherein the first communication is associated with an order for the product or service, wherein the processor provides an authorization to the selected third party vendor to complete the order, wherein the authorization comprises the financial information of the user, and wherein the vehicle uses different antennas positioned at different physical locations on an exterior of the vehicle to provide the first communication and authorization to the selected third party vendor.

2. The vehicle of claim 1, wherein the memory stores one or more limits on third party vendor communications associated with a user in the vehicle, wherein the one or more limits restrict financial transactions of the user with third party vendors, the one or more limits comprising one or more of a financial transaction amount limit and a limit on a number of financial transactions, and wherein the processor, based on the one or more limits, determines whether the vehicle can send the first communication to one of the multiple possible third party vendors, the first communication being related to initiating or completing a financial transaction with the third party vendor regarding the order for the product or service; when allowed by the one or more limits, automatically sends the first communication to the selected third party vendor for the user; and when not allowed by the one or more limits, does not send the first communication to the selected third party vendor for the user.

3. The vehicle of claim 1, wherein the different antennas transmit the first communication and authorization using different communication protocols, wherein a first of the different communication protocols is one or more of a near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol and a second of the different communication protocols is a cellular network communication protocol, wherein one or more of the first communication and authorization comprises vehicle information and user information, wherein the vehicle information comprises a vehicle identification number of the vehicle, an electronic serial number associated with the vehicle, and/or an engine code of the vehicle, wherein the first communication enables the selected third party vendor to authenticate the user, wherein the user information comprises biometric information of the user, the biometric information being received by a sensor associated with the vehicle, wherein the biometric information comprises one or more of facial structure, facial recognition information, voiceprint, voice recognition information, eye color, DNA information, and fingerprint information, wherein the selected third party vendor authenticates the user to enable the financial transaction between the selected third party vendor and user using the user information while the vehicle is in motion, and wherein the processor is programmed to initiate automatically, on behalf of the user and subject to the one or more limits, the financial transaction with the selected third party vendor in response to a sensed state or location of the vehicle.

4. The vehicle of claim 1, wherein the different antennas transmit the first communication and authorization using different communication protocols, wherein a first of the different communication protocols is one or more of a near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol and a second of the different communication protocols is a cellular network communication protocol, wherein one or more of the first communication and authorization comprises vehicle information and user information, wherein the vehicle information comprises a vehicle identification number of the vehicle, an electronic serial number associated with the vehicle, and/or an engine code of the vehicle, wherein the first communication enables the selected third party vendor to authenticate the user, wherein the user is a passenger of the vehicle, wherein the sensor detects a second presence of the passenger in the vehicle, wherein the processor receives the second presence, provides a user interface for the passenger to enter the user information; wherein the user information comprises financial information of the passenger, wherein the financial transaction is initiated by a request from the selected third party vendor, wherein the processor, as part of the request, communicates the user and vehicle information to the selected third party vendor to authenticate the passenger to enable the selected third party vendor to perform the financial transaction with the passenger using the user information, and wherein the processor is programmed to: while the vehicle is in motion, receive a plurality of transaction options from a plurality of vendors, each transaction option comprising an offer for the user to purchase a product or service; retrieve user preferences from the memory; in response to the transaction options and based on the user preferences, pre-filter the plurality of transaction options to identify which of the plurality of transaction options to present to the user by a user interface; in response to identifying a transaction option to present to the user, render the user interface for the display to request authorization from the user to allow a communication to the selected third party vendor associated with the identified transaction option; receive user input associated with the identified transaction option regarding authorization of the associated transaction, the associated transaction being the financial transaction, the user input indicating that the user authorizes the communication; and based on the user input and while the vehicle is in motion, automatically send, by a secure session, the first communication to the selected third party vendor on behalf of the user, the first communication enabling the selected third party vendor to complete the associated transaction.

5. The vehicle of claim 1, wherein the different antennas transmit the first communication and authorization using different communication protocols, wherein a first of the different communication protocols is one or more of a near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol and a second of the different communication protocols is a cellular network communication protocol, wherein the user rule determines a distance the vehicle can travel to the third party, wherein one or more of the first communication and authorization comprises vehicle information and user information, wherein the vehicle information comprises a vehicle identification number of the vehicle, an electronic serial number associated with the vehicle, and/or an engine code of the vehicle, wherein the first communication enables the selected third party vendor to authenticate the user, wherein user information and

vehicle information authenticate the user for the order, wherein the user information comprises mobile device information of a device associated with the user, and wherein the mobile device information comprises one or more of the mobile device number, the media access control (MAC) address, and a uniform resource locator (URL).

6. The vehicle of claim 5, wherein the user rule allows the processor to bargain automatically with the third party, wherein the one or more limits applies only to the user and to two or more vehicles, wherein the user information comprises a triggering event, the triggering event being a weather condition, and wherein the processor provides to the selected third party vendor, by the first communication protocol, the order of a product or service and by the different second protocol, financial information of the user.

7. The vehicle of claim 1, wherein the different antennas transmit the first communication and authorization using different communication protocols, wherein the user rule determines a monetary amount the vehicle can pay to the selected third party vendor, wherein the first communication comprises vehicle information and user information, wherein the vehicle information comprises a vehicle identification number of the vehicle, an electronic serial number associated with the vehicle, and/or an engine code of the vehicle, wherein the first communication enables the selected third party vendor to authenticate the user, wherein the user information comprises financial information, biometric information, and/or a PIN, wherein the authorization comprises the financial information of the user, wherein the vehicle uses different communication protocols to provide the vehicle information and financial information, and wherein a first of the different communication protocols is one or more of a near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol and a second of the different communication protocols is a cellular network communication protocol, wherein the user information is encrypted in the memory, wherein the processor authorizes the financial transaction in response to a plurality of a vehicle location, speed, proximity to a location, preference data and historical information associated with the user, wherein the user information comprises one or more of a biometric, a username, a password, mobile device information, payment information, a personal identification number, identifiers, an address, limits, preferences, and/or rules, wherein the processor, in response to a first event, the first event being a vehicle route, automatically forwards a first portion of a secure communication to the selected third party vendor to preorder a product or service of the selected third party vendor in connection with a transaction with the user, wherein the processor, in response to a later second event, the second event being a vehicle location, automatically completes the transaction by providing financial information to the selected third party vendor, and wherein the one or more limits applies only to the user and the vehicle.

8. The vehicle of claim 1, wherein the third party also has a vendor rule to govern an interaction with the vehicle, wherein the one or more limits applies only to two or more users and the vehicle, wherein the processor is authorized and programmed to initiate automatically on behalf of the user and without further input from the user the financial transaction with the selected third party vendor, wherein the authorization is restricted temporally or limited to a selected route or spatial location of the vehicle, wherein the user interface receives input from the user in the user interface and further comprising an active or passive payment device positioned on or near an outer surface of the vehicle, the

85

payment device using one or more of near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol to provide wirelessly financial information of the user to the selected third party vendor, and wherein the payment device comprises one of the antennas, wherein the processor:

determines, at a first time, which one of the different antennas is receiving a strongest signal from a common signal source associated with the third party vendor; selects a first transceiver associated with the first antenna receiving the strongest signal to send the first communication or authorization to the common signal source; sends the first communication or authorization to the first transceiver for transmission to the common signal source;

determines, at a second time, which one of the different antennas is receiving a strongest signal from the common signal source;

selects a second transceiver associated with the second antenna receiving the strongest signal to send the other of the first communication or authorization to the common signal source; and

sends the other of the first communication or authorization to the second transceiver for transmission to the common signal source.

9. The vehicle of claim 1, wherein the one or more limits is set on the user by a second user and further comprising a deployable antenna that one or more of physically contacts a receiving pad of the selected third party vendor as the vehicle is in proximity to the selected third party vendor and communicates with a receiver of the selected third party vendor by a near field communication protocol to provide the financial information to the selected third party vendor, the deployable antenna being one of the antennas.

10. The vehicle of claim 1, wherein the user rule is a time limit to address the need and wherein the one or more limits is on a number of communications that may be completed between the vehicle and third party.

11. A method for communicating information with a vehicle, comprising:

providing a vehicle comprising a memory storing a user rule applicable to communications associated with a user in the vehicle and a processor determining a need for communication with a third party;

determining, by the processor, a need for communication with a third party vendor;

retrieving, by the processor, the user rule from the memory, wherein the user rule defines to which third party vendor the vehicle can send a first communication to address the need, the need relating to a product or service of the third party vendor and wherein the user rule defines one or more of a geographic location of the third party vendor relative to a current location of the vehicle, a monetary amount the vehicle can pay to a third party vendor for a product or service to address the need, and a time limit for the third party vendor to provide the product or service to address the need;

based on the user rule, selecting, by the processor, a third party vendor from among multiple possible third party vendors, wherein each of the multiple possible third party vendors is capable of providing the product or service to meet the need; and

when determined by the user rule, automatically sending, by the processor, the first communication to the selected third party vendor to address the need, wherein the first communication is associated with an order for the product or service, wherein the processor provides an authorization to the selected third party vendor to complete the order, wherein the authorization comprises the financial information of the user, and wherein

86

the vehicle uses different antennas positioned at different physical locations on an exterior of the vehicle to provide the first communication and authorization to the selected third party vendor.

12. The method of claim 10, wherein the memory stores one or more limits on third party vendor communications associated with a user in the vehicle, wherein the one or more limits restrict financial transactions of the user with third party vendors, the one or more limits comprising one or more of a financial transaction amount limit and a limit on a number of financial transactions, and wherein the processor, based on the one or more limits, determines whether the vehicle can send the first communication to one of the multiple possible third party vendors, the first communication being related to initiating or completing a financial transaction with the third party vendor regarding the order for the product or service; when allowed by the one or more limits, automatically sends the first communication to the selected third party vendor for the user; and when not allowed by the one or more limits, does not send the first communication to the selected third party vendor for the user.

13. The method of claim 11, wherein the different antennas transmit the first communication and authorization using different communication protocols, wherein a first of the different communication protocols is one or more of a near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol and a second of the different communication protocols is a cellular network communication protocol, wherein one or more of the first communication and authorization comprises vehicle information and user information, wherein the vehicle information comprises a vehicle identification number of the vehicle, an electronic serial number associated with the vehicle, and/or an engine code of the vehicle, wherein the first communication enables the selected third party vendor to authenticate the user, wherein the user information comprises biometric information of the user, the biometric information being received by a sensor associated with the vehicle, wherein the biometric information comprises one or more of facial structure, facial recognition information, voiceprint, voice recognition information, eye color, DNA information, and fingerprint information, wherein the selected third party vendor authenticates the user to enable the financial transaction between the selected third party vendor and user using the user information while the vehicle is in motion, and wherein the processor is programmed to initiate automatically, on behalf of the user and subject to the one or more limits, the financial transaction with the selected third party vendor in response to a sensed state or location of the vehicle.

14. The method of claim 11, wherein the different antennas transmit the first communication and authorization using different communication protocols, wherein a first of the different communication protocols is one or more of a near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol and a second of the different communication protocols is a cellular network communication protocol, wherein one or more of the first communication and authorization comprises vehicle information and user information, wherein the vehicle information comprises a vehicle identification number of the vehicle, an electronic serial number associated with the vehicle, and/or an engine code of the vehicle, wherein the first communication enables the selected third party vendor to authenticate the user, wherein the user is a passenger of the vehicle, wherein the sensor detects a second presence of the passenger in the vehicle, wherein the processor receives the second presence, provides a user interface for the passenger to enter the user

information; wherein the user information comprises financial information of the passenger, wherein the financial transaction is initiated by a request from the selected third party vendor, wherein the processor, as part of the request, communicates the user and vehicle information to the selected third party vendor to authenticate the passenger to enable the selected third party vendor to perform the financial transaction with the passenger using the user information, and wherein the processor is programmed to: while the vehicle is in motion, receive a plurality of transaction options from a plurality of vendors, each transaction option comprising an offer for the user to purchase a product or service; retrieve user preferences from the memory; in response to the transaction options and based on the user preferences, pre-filter the plurality of transaction options to identify which of the plurality of transaction options to present to the user by a user interface; in response to identifying a transaction option to present to the user, render the user interface for the display to request authorization from the user to allow a communication to the selected third party vendor associated with the identified transaction option; receive user input associated with the identified transaction option regarding authorization of the associated transaction, the associated transaction being the financial transaction, the user input indicating that the user authorizes the communication; and based on the user input and while the vehicle is in motion, automatically send, by a secure session, the first communication to the selected third party vendor on behalf of the user, the first communication enabling the selected third party vendor to complete the associated transaction.

15. The method of claim 11, wherein the different antennas transmit the first communication and authorization using different communication protocols, wherein a first of the different communication protocols is one or more of a near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol and a second of the different communication protocols is a cellular network communication protocol, wherein the user rule determines a distance the vehicle can travel to the third party, wherein one or more of the first communication and authorization comprises vehicle information and user information, wherein the vehicle information comprises a vehicle identification number of the vehicle, an electronic serial number associated with the vehicle, and/or an engine code of the vehicle, wherein the first communication enables the selected third party vendor to authenticate the user, wherein user information and vehicle information authenticate the user for the order, wherein the user information comprises mobile device information of a device associated with the user, and wherein the mobile device information comprises one or more of the mobile device number, the media access control (MAC) address, and a uniform resource locator (URL).

16. The method of claim 11, wherein the different antennas transmit the first communication and authorization using different communication protocols, wherein the user rule determines a monetary amount the vehicle can pay to the selected third party vendor, wherein the first communication comprises vehicle information and user information, wherein the vehicle information comprises a vehicle identification number of the vehicle, an electronic serial number associated with the vehicle, and/or an engine code of the vehicle, wherein the first communication enables the selected third party vendor to authenticate the user, wherein the user information comprises financial information, biometric information, and/or a PIN, wherein the authorization comprises the financial information of the user, wherein the vehicle uses different communication protocols to provide the vehicle information and financial information, and

wherein a first of the different communication protocols is one or more of a near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol and a second of the different communication protocols is a cellular network communication protocol, wherein the user information is encrypted in the memory, wherein the processor authorizes the financial transaction in response to a plurality of a vehicle location, speed, proximity to a location, preference data and historical information associated with the user, wherein the user information comprises one or more of a biometric, a username, a password, mobile device information, payment information, a personal identification number, identifiers, an address, limits, preferences, and/or rules, wherein the processor, in response to a first event, the first event being a vehicle route, automatically forwards a first portion of a secure communication to the selected third party vendor to preorder a product or service of the selected third party vendor in connection with a transaction with the user, wherein the processor, in response to a later second event, the second event being a vehicle location, automatically completes the transaction by providing financial information to the selected third party vendor, and wherein the one or more limits applies only to the user and the vehicle.

17. The method of claim 15, wherein the user rule allows the processor to bargain automatically with the third party, wherein the one or more limits applies only to the user and to two or more vehicles, wherein the user information comprises a triggering event, the triggering event being a weather condition, and wherein the processor provides to the selected third party vendor, by the first communication protocol, the order of a product or service and by the different second protocol, financial information of the user.

18. The method of claim 11, wherein the third party also has a vendor rule to govern an interaction with the vehicle, wherein the one or more limits applies only to two or more users and the vehicle, wherein the processor is authorized and programmed to initiate automatically on behalf of the user and without further input from the user the financial transaction with the selected third party vendor, wherein the authorization is restricted temporally or limited to a selected route or spatial location of the vehicle, wherein the user interface receives input from the user in the user interface and further comprising an active or passive payment device positioned on or near an outer surface of the vehicle, the payment device using one or more of near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol to provide wirelessly financial information of the user to the selected third party vendor, and wherein the payment device comprises one of the antennas and further comprising:

determining, by the processor and at a first time, which one of the different antennas is receiving a strongest signal from a common signal source associated with the third party vendor;

selecting, by the processor, a first transceiver associated with the first antenna receiving the strongest signal to send the first communication or authorization to the common signal source;

sending, by the processor, the first communication or authorization to the first transceiver for transmission to the common signal source;

determining, by the processor and at a second time, which one of the different antennas is receiving a strongest signal from the common signal source;

selecting, by the processor, a second transceiver associated with the second antenna receiving the strongest signal to send the other of the first communication or authorization to the common signal source; and

89

sending, by the processor, the other of the first communication or authorization to the second transceiver for transmission to the common signal source.

19. The method of claim 11, wherein the one or more limits is set on the user by a second user and further comprising a deployable antenna that one or more of physically contacts a receiving pad of the selected third party vendor as the vehicle is in proximity to the selected third party vendor and communicates with a receiver of the selected third party vendor by a near field communication protocol to provide the financial information to the selected third party vendor, the deployable antenna being one of the antennas.

20. The method of claim 11, wherein the user rule is a time limit to address the need and wherein the one or more limits is on a number of communications that may be completed between the vehicle and third party.

21. A vehicle, comprising:

a non-transitory memory to store a user rule applicable to third party vendor communications associated with a user in the vehicle;

a processor in communication with the memory, the processor to:

determine a need for communication with a third party vendor;

retrieve the user rule from the memory, wherein the user rule defines to which third party vendor the vehicle can send a first communication to address the need, the need relating to a product or service of the third party vendor and wherein the user rule defines one or more of a geographic location of the third

90

party vendor relative to a current location of the vehicle, a monetary amount the vehicle can pay to a third party vendor for a product or service to address the need, and a time limit for the third party vendor to provide the product or service to address the need; based on the user rule, select a third party vendor from among multiple possible third party vendors, wherein each of the multiple possible third party vendors is capable of providing the product or service to meet the need; and

when determined by the user rule, automatically send the first communication to the selected third party vendor to address the need, wherein the first communication is associated with an order for the product or service, wherein the processor provides an authorization to the selected third party vendor to complete the order, wherein the authorization comprises the financial information of the user, wherein the vehicle uses different antennas, positioned at different physical locations on the vehicle, and different communication protocols to provide the first communication and authorization to the selected third party vendor, and wherein a first of the different communication protocols is one or more of a near field communications (NFC), BLUETOOTH™, Low Energy (BLE), and radio frequency identification (RFID) protocol and a second of the different communication protocols is a cellular network communication protocol.

* * * * *