



US010015679B2

(12) **United States Patent**  
**Berry**

(10) **Patent No.:** **US 10,015,679 B2**

(45) **Date of Patent:** **\*Jul. 3, 2018**

(54) **SYSTEM AND METHOD FOR MOBILE DATA EXPANSION**

(71) Applicant: **Neutronic Perpetual Innovations Operating, LLC**, Irving, TX (US)

(72) Inventor: **Terrance Berry**, Irving, TX (US)

(73) Assignee: **Neutronic Perpetual Innovations Operating, LLC**, Irving, TX (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 107 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/145,732**

(22) Filed: **May 3, 2016**

(65) **Prior Publication Data**

US 2016/0249273 A1 Aug. 25, 2016

**Related U.S. Application Data**

(63) Continuation of application No. 14/876,673, filed on Oct. 6, 2015, now Pat. No. 9,596,611, which is a (Continued)

(51) **Int. Cl.**  
**H04L 1/00** (2006.01)  
**H04W 16/26** (2009.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **H04W 16/26** (2013.01); **G01S 1/68** (2013.01); **G01S 7/003** (2013.01); **G01S 13/92** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... H04L 43/00; H04L 43/50; H04L 43/0876; H04L 43/0882; H04L 43/0888;  
(Continued)

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,002,898 A 1/1977 Milton  
7,113,098 B1 9/2006 Hayes  
(Continued)

**FOREIGN PATENT DOCUMENTS**

WO 0191353 A2 11/2001  
WO WO 2011/042038 4/2011

**OTHER PUBLICATIONS**


International Search Report dated Aug. 5, 2014 in connection with International Patent Application No. PCT/US2014/028579; 4 pp.  
(Continued)

*Primary Examiner* — Dady Chery

(57) **ABSTRACT**

In a system of spaced surface markers disposed on a travel surface, each surface marker includes a housing, a power system within the housing producing electrical power from solar energy or vibration, and wireless transceiver(s) within the housing wirelessly communicating with neighboring surface markers. One surface marker relays data from and to another, while a third surface marker relays data from and to a network connection to a remote network. All surface markers may communicate via WiFi. The travel surface may be for vehicles. Each surface marker may communication with a vehicle or mobile device within communication range, to provide location or other information.

**20 Claims, 13 Drawing Sheets**



**Related U.S. Application Data**

continuation of application No. 13/840,578, filed on Mar. 15, 2013, now Pat. No. 9,219,991, which is a continuation-in-part of application No. 13/646,537, filed on Oct. 5, 2012, now Pat. No. 8,447,239.

(60) Provisional application No. 61/668,867, filed on Jul. 6, 2012.

(51) **Int. Cl.**

*H04W 4/02* (2018.01)  
*H04W 88/08* (2009.01)  
*H04W 4/029* (2018.01)  
*H04W 76/10* (2018.01)  
*H04B 1/3888* (2015.01)  
*G01S 7/00* (2006.01)  
*G01S 13/92* (2006.01)  
*G01S 19/48* (2010.01)  
*G01S 1/68* (2006.01)  
*H04B 1/40* (2015.01)  
*H04L 29/08* (2006.01)  
*H04W 36/14* (2009.01)  
*H04W 36/32* (2009.01)  
*G06K 9/18* (2006.01)  
*G06K 9/20* (2006.01)  
*G06K 9/78* (2006.01)  
*H04W 48/08* (2009.01)  
*H04W 76/02* (2009.01)  
*H02J 7/14* (2006.01)  
*H02J 7/35* (2006.01)  
*H04W 4/04* (2009.01)  
*H04W 40/02* (2009.01)  
*G01S 19/10* (2010.01)  
*H04W 84/12* (2009.01)

(52) **U.S. Cl.**

CPC ..... *G01S 19/48* (2013.01); *G06K 9/18* (2013.01); *G06K 9/2063* (2013.01); *G06K 9/78* (2013.01); *H02J 7/14* (2013.01); *H02J 7/35* (2013.01); *H04B 1/3888* (2013.01); *H04B 1/40* (2013.01); *H04L 67/12* (2013.01); *H04W 4/025* (2013.01); *H04W 4/027* (2013.01); *H04W 4/028* (2013.01); *H04W 4/029* (2018.02); *H04W 4/046* (2013.01); *H04W 36/14* (2013.01); *H04W 36/32* (2013.01); *H04W 40/02* (2013.01); *H04W 48/08* (2013.01); *H04W 76/02* (2013.01); *H04W 76/10* (2018.02); *H04W 88/08*

(2013.01); *G01S 19/10* (2013.01); *G06K 2209/15* (2013.01); *H04W 84/12* (2013.01)

(58) **Field of Classification Search**

CPC .. *H04L 43/0894*; *H04W 24/00*; *H04W 52/02*; *H04W 52/0203*; *H04B 17/00*; *H04B 3/46*; *H04B 7/00*; *H04J 3/14*; *H04J 2203/0069*  
 USPC ..... 370/328, 329, 241, 252, 253, 310, 311, 370/341; 455/73, 106, 436, 572, 573  
 See application file for complete search history.

(56)

**References Cited**

U.S. PATENT DOCUMENTS

7,499,429	B2	3/2009	Dawidowsky et al.
8,447,239	B1	5/2013	Berry
9,171,459	B2	10/2015	Yorke et al.
9,219,991	B2	12/2015	Berry
2003/0174054	A1	9/2003	Shimomura
2004/0219924	A1	11/2004	Flynn
2004/0252193	A1	12/2004	Higgins
2005/0238425	A1	10/2005	Safir
2007/0167174	A1	7/2007	Halcrow et al.
2008/0235360	A1	9/2008	Li et al.
2009/0215488	A1	8/2009	Causey et al.
2009/0257564	A1	10/2009	Kito et al.
2010/0142427	A1	6/2010	Ramsey
2010/0203892	A1	8/2010	Nagaraja et al.
2010/0315045	A1	12/2010	Zeine
2011/0194733	A1	8/2011	Wilson
2012/0250457	A1	10/2012	Rickert, Jr. et al.
2012/0286988	A1	11/2012	Sepehri et al.
2013/0014807	A1	1/2013	Childs et al.
2013/0038681	A1	2/2013	Osipov et al.

OTHER PUBLICATIONS

Written Opinion dated Aug. 5, 2014 in connection with International Patent Application No. PCT/US2014/028579; 10 pp.  
 Lim, et al.; "Fiber-Wireless Networks and Subsystem Technologies;" IEEE Journal of Lightwave Technology; vol. 28, No. 4; Feb. 15, 2010; 16 pp.  
 International Search Report dated Jun. 27, 2013 in connection with International Patent Application No. PCT/US2013/041881, 3 pp.  
 Written Opinion of International Searching Authority dated Jun. 27, 2013 in connection with International Patent Application No. PCT/US2013/041881; 6 pp.  
 USPTO Final Office Action, U.S. Appl. No. 14/876,673, dated Aug. 10, 2016, 10 pages.  
 Office Action dated Oct. 11, 2016 in connection with Canadian Application No. 2,906,021, 4 pages.  
 European Search Report issued for EP 13813585.0 dated Feb. 17, 2016, 9 pgs.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9

900




FIG. 10




FIG. 11

1100




FIG. 12

1200




FIG. 13

## SYSTEM AND METHOD FOR MOBILE DATA EXPANSION

### CROSS-REFERENCE TO RELATED APPLICATIONS AND CLAIMS OF PRIORITY

This application is a continuation of U.S. Non-Provisional patent application Ser. No. 14/876,673 entitled "SYSTEM AND METHOD FOR MOBILE DATA EXPANSION" and filed Oct. 6, 2015, which is a continuation of U.S. Non-Provisional patent application Ser. No. 13/840,578 entitled "SYSTEM AND METHOD FOR MOBILE DATA EXPANSION" and filed Mar. 15, 2013, now U.S. Pat. No. 9,219,991, which is a continuation-in-part of U.S. Non-Provisional patent application Ser. No. 13/646,537 entitled "SYSTEM AND METHOD FOR MOBILE DATA EXPANSION" and filed on Oct. 5, 2012, now U.S. Pat. No. 8,447,239, and claims priority through those applications to U.S. Provisional Patent Application No. 61/668,867 entitled "SYSTEM AND METHOD FOR MOBILE DATA EXPANSION" and filed on Jul. 6, 2012. The content of the above-identified patent documents is incorporated herein by reference.

### TECHNICAL FIELD

The present application relates generally to mobile broadband data services, and more specifically to discrete WiFi hotspots for mobile devices.

### BACKGROUND

Wireless data communications are increasing in demand and popularity. Mobile devices use cellular data networks or small wireless fidelity (WiFi) networks (WiFi hotspots) to access broadband data services for mobile devices. While cellular data networks provide a wider coverage, WiFi hotspots are capable of higher data transfer rates and lower power usage at a lower cost. However, WiFi hotspots provide a limited coverage area inhibiting use when the user is moving between locations.

### SUMMARY

In a system of spaced surface markers disposed on a travel surface, each surface marker includes a housing, a power system within the housing producing electrical power from solar energy or vibration, and wireless transceiver(s) within the housing wirelessly communicating with neighboring surface markers. One surface marker relays data from and to another, while a third surface marker relays data from and to a network connection to a remote network. All surface markers may communicate via WiFi. The travel surface may be for vehicles. Each surface marker may communicate with a vehicle or mobile device within communication range, to provide location or other information.

Before undertaking the DETAILED DESCRIPTION below, it may be advantageous to set forth definitions of certain words or phrases used throughout this patent document: the terms "include" and "comprise," as well as derivatives thereof, mean inclusion without limitation; the term "or" is inclusive, meaning and/or; the phrases "associated with" and "associated therewith," as well as derivatives thereof, may mean to include, be included within, interconnect with, contain, be contained within, connect to or with, couple to or with, be communicable with, cooperate with, interleave, juxtapose, be proximate to, be bound to or with,

have, have a property of, or the like; and the term "controller" means any device, system or part thereof that controls at least one operation, whether such a device is implemented in hardware, firmware, software or some combination of at least two of the same. It should be noted that the functionality associated with any particular controller might be centralized or distributed, whether locally or remotely. Definitions for certain words and phrases are provided throughout this patent document, and those of ordinary skill in the art will understand that such definitions apply in many, if not most, instances to prior as well as future uses of such defined words and phrases. While some terms may include a wide variety of embodiments, the appended claims may expressly limit these terms to specific embodiments.

### BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present disclosure, and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, wherein like numbers designate like objects, and in which:

FIG. 1 illustrates a small cell data expansion reflector (DER) according to embodiments of the present disclosure;

FIG. 2 illustrates a DER that includes a solar array panel according to embodiments of the present disclosure;

FIG. 3 illustrates a DER with a cylindrical housing according to embodiments of the present disclosure;

FIG. 4 illustrates selected electrical and electronic components of a control system inside a DER according to embodiments of the present disclosure;

FIG. 5 illustrates a string of DERs according to embodiments of the present disclosure;

FIG. 6 illustrates a network of DERs according to embodiments of the present disclosure;

FIG. 7 illustrates a process for providing mobile broadband data access according to embodiments of the present disclosure;

FIG. 8 illustrates a DER providing mobile broadband access according to embodiments of the present disclosure;

FIG. 9 illustrates a DER system according to embodiments of the present disclosure;

FIG. 10 illustrates a network of DERs according to embodiments of the present disclosure;

FIG. 11 illustrates a process for reporting vehicle velocity and identification information according to embodiments of the present disclosure;

FIG. 12 illustrates a process for reporting vehicle location and identification information according to embodiments of the present disclosure; and

FIG. 13 illustrates a process for sequentially transmitting segments of a data file to a mobile station based on projected geographical location of the mobile station according to embodiments of the present disclosure.

### DETAILED DESCRIPTION

FIGS. 1 through 8, discussed below, and the various embodiments used to describe the principles of the present disclosure in this patent document are by way of illustration only and should not be construed in any way to limit the scope of the disclosure. Those skilled in the art will understand that the principles of the present disclosure may be implemented in any suitably arranged device. The numerous innovative teachings of the present application will be described with reference to exemplary non-limiting embodiments.



FIG. 1 illustrates a small cell-Data Expansion reflector (DER) 100 according to embodiments of the present disclosure. Although certain details will be provided with reference to the components of the DER 100, it should be understood that other embodiments may include more, less, or different components.

The DER 100 is a small cell device configured to provide a wireless communication link between a mobile device and a backhaul network. The DER 100 is adapted to couple to one or more mobile devices to enable the mobile devices to send and receive information, such as data and control signals, to the backhaul network. As such, the DER 100 is configured to provide one or more of: a wireless coverage area; a cellular coverage area; a hotspot, such as a WiFi hotspot; and the like.

The DER 100 can be configured as a street surface reflector (also called a surface marker), such as a road reflector, raised pavement marker, street reflector, road stud, and pavement reflector, used for traffic control and safety. In certain embodiments, the DER 100 with a cylindrical housing is disposed in the road surface such that a highest portion of the housing is substantially flush (i.e., within one centimeter) with the road surface.

The DER 100 includes one or more surfaces that are comprised of a reflective material 120. For example, the DER housing 110 includes a mounting surface, a top surface, and a plurality of side surfaces. In certain embodiments, the surfaces of the reflective material include the plurality of side surfaces, the top surface, or a combination thereof. The DER 100 is made up of a combination of the reflective material, plastic, a ceramic, or other suitable materials. In certain embodiments, only selected ones of the plurality of side surfaces and the top surface include the reflective material. That is, the portions of the DER 100 that are made of the reflective material are less than a whole portion. For example, in the example shown in FIG. 1, two rectangular sides of the DER 100 include the reflective material. In certain embodiments, the DER 100 housing can be in any of a variety of shapes, such as circular, oval, rectangular, octagonal, hexagonal, trapezoidal, or any suitable shape.

FIG. 2 illustrates a DER 100 that includes a solar array panel 210 according to embodiments of the present disclosure. Although certain details will be provided with reference to the components of the DER 100, it should be understood that other embodiments may include more, less, or different components.

In certain embodiments, the DER 100 includes a self-sustaining power source or power supply. In certain embodiments, at least one surface, such as the top surface, is comprised of the self-sustaining power source. The self-sustaining power source can include solar cells 220 (e.g., forming a solar array panel) that include a plurality of photo-voltaic cells. In certain embodiments, the DER 100 includes a power interface configured to couple to a self-sustaining power source, such as a solar cell 220. In certain embodiments, the power interface is configured to removably couple to the self-sustaining power source.

In certain embodiments, the DER 100 includes a housing that is a truncated pyramid shape. The solar array panel 210 can be disposed atop the housing 110. One or more sides of the housing can include the solar cells 220. Reflective material 120 is disposed on one or more remaining sides of the housing 110. The sides of the housing 110 that include the solar cells 220 can be oriented to correspond to the sides that allow the greatest amount of solar energy to be absorbed throughout a day and a year. In certain embodiments, the

housing includes a clear protective cover disposed over or around the solar array panel 210. The clear protective cover is comprised of any suitable clear material such as a PLEXIGLAS material or other hard plastic, glass or composite material. In certain embodiments, the clear material is comprised of a reflective material and configured as a portion of the reflective surfaces. In certain embodiments, the solar array panel 210 is embedded into the reflective surface or disposed beneath the clear material as a reflective surface.

FIG. 3 illustrates a DER 100 with a cylindrical housing 300 according to embodiments of the present disclosure. Although certain details will be provided with reference to the components of the DER 100, it should be understood that other embodiments may include more, less, or different components.

The DER 100 with a cylindrical housing 300 that has at least one reflective surface. In certain embodiments, the DER 100 with a cylindrical housing 300 includes a solar array panel 310 disposed atop the reflective surface or disposed beneath a clear reflective surface. The housing 300 can be a truncated sphere atop a cylinder shape. In certain embodiments, the solar array panel 310 is embedded or cut into the reflective surface. In certain embodiments, the DER 100 with a cylindrical housing 300 is disposed in the road surface such that a highest portion of the housing 300 is substantially flush (i.e., within one centimeter) with the road surface.

In certain embodiments, a portion of the DER 100 with a cylindrical housing 300 includes a reflective surface. In certain embodiments, a portion of the DER 100 with a cylindrical housing 300 includes a solar array 310. In certain embodiments, a portion of the DER 100 with a cylindrical housing 300 includes a reflective material and a separate portion of the reflector 100 includes a reflective surface. In certain embodiments, the DER 100 with a cylindrical housing 300 includes a solar array 310 that is also a reflective surface.

FIG. 4 illustrates components of a control system 400 inside a DER 100 according to embodiments of the present disclosure. Although certain details will be provided with reference to the components of the control system 400, it should be understood that other embodiments may include more, less, or different components. The DER 100 includes the control system 400. The control system 400 is configured to enable the DER 100 to provide access to broadband data services for mobile terminals. The control system 400 includes processing circuitry 410, a transceiver 420, a communication interface 430, a power source 440, and an antenna 450. In certain embodiments, the control system 400 includes one or more of the following: a Radio Detection And Ranging (RADAR) unit 415, a camera 425, a global positioning system (GPS) receiver 435, and a climate control unit 445. The housing 460 is configured to contain the control system 400. In certain embodiments, the control system 400 also includes a network node 470. The network node 470 operates as an access point, providing features such as access control, theft prevention, data traffic monitoring, data traffic shaping, network node to network node signaling, and various other features associated with network access and control.

The processing circuitry 410 is coupled to the RADAR unit 415, the transceiver 420, the camera 425, the communication interface 430, the GPS receiver 435, the power source 440, and the climate control unit 445. The processing circuitry 410 is configured to establish a communication with at least one mobile terminal 490 through a coupling

with the transceiver **420**. The processing circuitry **410**, communicably coupled to the mobile terminal **490**, enables communications between the mobile terminal **490** and a network **495** of computers, such as the Internet (namely, a world-wide-web; a world-wide-network) or a private network. The processing circuitry **410** forms one or more communication channels to communicate information between the mobile terminal **490** and the network **495**. The control system **400** establishes a secure channel for sending and receiving control and data signals to and from one or more mobile terminal **490**. The processing circuitry **410** provides a virtual private network (VPN) initialization and termination for communications between the control system **400** and the mobile terminal **490**. That is, the DER **100** communicates with the mobile terminal **490** via a secured channel using a VPN. In certain embodiments, the processing circuitry **410** is configured to send encrypted data and to decipher encrypted data received from the mobile terminal **490**. That is, the processing circuitry **410** and mobile terminal **490** establish an encryption agreement or share a common encryption key used to secure the data transmitted between the mobile terminal **490** and the DER **100**.

In certain embodiments, the processing circuitry **410** includes a programmable controller. The programmable controller is configured to be reprogrammable to control one or more functions of the processing circuitry, at a later date. In certain embodiments, the programmable controller is configured (such as pre-configured) to control one or more functions of the processing circuitry **410**. In certain embodiments, the processing circuitry **410** is embodied as a programmable controller. In the present disclosure, any description of a function or coupling of the processing circuitry **410** is understood to be a function or coupling of the programmable controller.

In certain embodiments, the processing circuitry **410** includes a memory **412**. In certain embodiments, the processing circuitry **410** is coupled to the memory **412** (as shown in FIG. 9). The memory **412** includes any suitable volatile or non-volatile storage and retrieval device(s). For example, the memory **412** can include any electronic, magnetic, electromagnetic, optical, electro-optical, electro-mechanical, or other physical device that can contain, store, communicate, propagate, or transmit information. The memory **412** stores data and instructions for use by the processor or programmable controller of the processing circuitry **410**. In certain embodiments, the memory **412** stores location information. For example, the memory **412** is programmed to store a location of the DER **100**, such as a global positioning system (GPS) location or a location provide by the network. For example, the network or operator can program the DER **100** with a geographic location at the time of installation of the DER **100**. In certain embodiments, in response to receiving a signal indicating the location of the DER **100**, the processing circuitry **410** stores the location in the memory **412**.

The control system **400** includes the RADAR unit **415** configured to perform a RADAR gun function. The RADAR unit **415** is configured to transmit RADAR waves toward one or more objects and to receive return reflected waves. That is, the RADAR unit **415** includes a radio signal transmitter configured to transmit radio waves outward from the DER **100**. When incident upon an object (for example, a vehicle, the radio waves reflect off the object and return to the control system of the DER **100**. The RADAR unit **415** includes a radio signal receiver configured to receive the return reflected waves. The RADAR unit **415** transmits waveform information corresponding to the transmitted and

reflected waves to the processing circuitry **410**. The RADAR unit **415** and processing circuitry **410** use the RADAR wave information to determine the speed and direction of travel of the vehicle (together, the vehicle velocity). The RADAR unit **415** and processing circuitry **410** use the RADAR wave information to determine a proximal distance from the RADAR unit to the vehicle. The RADAR unit **415** within the DER **100** can be used to monitor the flow of traffic on streets and highways.

For example, the roadway speed limit corresponding to the location of the DER **100** is stored in the memory **412**. As vehicles, drive by the DER **100**, the RADAR unit **415** measures the speed and direction of the traffic. The processing circuitry **410** compares the speed of one or more vehicles to the stored speed limit. The control system **400** sends the vehicle speed information and the speed comparison to a network **495** computer or network user, such as a traffic law enforcement system, a government department of transportation traffic controller or a roadway traffic monitoring service system. The information can include an estimated amount of time travel between certain mile markers, or an estimated time of arrival at a highway junction or exit ramp.

The control system **400** includes a transceiver **420**. The transceiver **420** is configured to transmit data and to receive data. In certain embodiments, the transceiver **420** is a wireless transceiver, for example a WiFi transceiver. In certain embodiments, the transceiver **420** includes an antenna **450**. The antenna **450** is configured to enable the transceiver **420** to send data to mobile terminal **490** and to receive data from the mobile terminal **490**. In certain embodiments, the transceiver **420** is coupled to antenna **450**, enabling the transceiver to send data to a mobile terminal **490** and to receive data from the mobile terminal **490**. The transceiver **420** communicates data between the processing circuitry **410** and the mobile terminal **490**. That is, the transceiver **420** receives data from the processing circuitry **410** and transmits the data received from the processing circuitry **410** to the mobile terminal **490**. The transceiver **420** also receives data from the mobile terminal **490** and transmits the data received from the mobile terminal **490** to the processing circuitry **410**. The processing circuitry **410** is communicably coupled to the network node **470**. The processing circuitry **410** sends signals to the node **470** and receives signals from the node **470**. For example, in response to a signal sent from the processing circuitry **410** to the node **470**, the processing circuitry **410** receives one or more signals from the node **470**. The processing circuitry **410** sends communications to a network **495** of computers (also referred to as the Internet) and receives communications from the network **495** via the node **470**. When the processing circuitry **410** is communicably coupled to the network **495**, the processing circuitry **410** is configured to enable the mobile terminal **490** to communicate with the network **495** via the transceiver **420** and the node **470**.

The control system **400** includes a communication interface **430**. The communication interface **430** enables communications with one or more of: the processing circuitry **410**, a node **470**, the backhaul network **480**, one or a plurality of mobile terminals **490**, and the network **495**. Communications can be through a wireless data transfer communication, a wireless local area network (WLAN) Internet communication, an optic communication medium, infrared communication medium, or through wireless-fidelity (WiFi) communication.

The control system **400** includes a camera **425**. The camera is configured to capture images of the environment surrounding the DER **100**. The camera **425** is configured to

capture images of vehicle that is approaching or departing from the DER 100, including images of the vehicle license plates. For example, the processing circuitry can instruct the camera 425 to capture images of a vehicle driving faster than the speed limit or driving slower than the highway minimum speed.

For example, the processing circuitry 410 receives a targeted license plate number. The mobile phone 490 can forward an AMBER alert to the control system 400 via the link 455, including a corresponding targeted license plate number. The processing circuitry stores the targeted license plate number in the memory 412. The control system 400 is configured to perform image processing, including optical character recognition (OCR). That is, the camera 425 or the processing circuitry 410 performs an OCR on the images of vehicle license plates captured by the camera 425. The processing circuitry 425 is configured to compare the license plate numbers recognized in the images to the targeted license plate numbers stored in memory 412. When the recognized license plate number matches one or more targeted license plate numbers, the processing circuitry 410 sends the location of the DER 100, the matching license plate information, and the corresponding image to a user in the network 495. The network 495 user may be a law enforcement officer within close proximity to the DER 100.

The control system 400 includes a GPS receiver 435 configured to receive a signal indicating the GPS location of the DER 100. The control system 400 is configured to store the received GPS location in the memory 412 as the location of the DER 100.

The power source 440 is configured to provide power to the control system 400. The power source 440 is coupled to each electrical component of the control system 400. The power source 440 can be directly coupled to each electrical component of the control system 400. In certain embodiments, the power source is directly coupled to the processing circuitry 410, enabling each electrical component coupled to the processing circuitry 410 to indirectly receive power from the power source 440. The power source 440 can be a renewable energy source, such as solar energy, wind energy, geothermal energy, biomass energy, or any combination thereof. For example, the power source 440 can include a connection with a local utility company's distribution system, or an off-the-grid island distribution system, or a combination thereof. In certain embodiments, the power source 440 is a solar array panel 210, 310. In certain embodiments, the power source 440 is a photovoltaic source embodied as photovoltaic paint or another suitable material configured to convert solar energy into electrical energy. In particular embodiments, the power source 440 includes a port or power interface adapted to couple an external power source, which is outside the DER 100 and provides power to the control system 400. In certain embodiments, the port or power interface is configured to removably couple to the external power source. In certain embodiments, the power source 440 includes one or more of the following: a solar-charging battery; a vibration-powered energy harvester configured to capture and store energy derived from ambient vibrations; a wireless power transmission receiver configured to couple to a wireless power transmitter; a conductor transmitting electricity generated from solar energy, geothermal energy, or heat; a number of solar cells; a number of solar cells disposed beneath a clear (e.g., PLEXIGLASS) cover of the housing; and a painted stripe on the road or pedestrian walk-way surface. In certain embodiments, a portion of the painted stripe is disposed within or beneath the housing 460. The vibration-powered energy harvester cap-

tures energy from ambient road vibrations or vibrations from wind against the housing 460 and converts the energy into electricity for the control system 400.

The control system 400 includes a climate control unit 445. The climate control unit 445 includes one or more sensors configured to measure temperature and moisture levels internal and external to the housing 460. The climate control unit 445 includes a heating element 447 configured to increase the temperature of the DER. In certain embodiments, the heating element 447 is disposed within the material of the housing 460. In certain embodiments, the heating element 447 is disposed on top of the housing and heats the external surface of the DER 100. In certain embodiments, the heating element 447 is disposed around a perimeter of the housing 460. As an example, when the climate control unit 445 measures an external temperature of below freezing and senses snow or ice disposed on the surface of the DER 100, then the climate control sensor turns on the heating element to increase the temperature of the DER 100 and to melt away the ice or snow. By melting away snow and ice, driverless vehicles can detect the lane markers of the roadway and control the vehicle to remain within the lane.

The antenna 450 is configured to communicably couple to the mobile terminal 490. The antenna 450 can be configured to communicate with the mobile terminal 490 using a suitable wireless communication, such as a WiFi (namely, IEEE 802.11x) communication, a near field communication (NFC), a BLUETOOTH low energy (BLE) communication, a general packet radio service (GPRS) for global system for mobile communications (GSM), an Enhanced Data rates for GSM Evolution (EDGE) communication, a third generation (3G) Universal Mobile Telecommunications System (UMTS) communication, 3G High Speed Packet Access (HSPA) communication, a 3G High Speed Downlink Packet Access (HSDPA) communication, a Worldwide Interoperability for Microwave Access (WiMax) communication, a fourth generation (4G) Long Term Evolution (LTE) communication, or any other suitable wireless communications protocol. In certain embodiments, the antenna 450 is included in the transceiver 420. In certain embodiments, the antenna 450 is coupled to the transceiver 420. The antenna 450 can be configured with omni-directional characteristics, or uni-directional characteristics. Additionally, the antenna 450 can be a directional antenna configured to communicate data in particular directions.

In certain embodiments, the control system 400 is included in housing 460. The housing 460 can be embodied as a raised reflective surface. Some examples of raised reflective surfaces include: a road reflector, raised pavement marker, street reflector, road stud, and pavement reflector, used for traffic control and safety. The housing 460 can be rectangular, cylindrical, oval, trapezoidal or any suitable shape. In certain embodiments, the housing 460 is dimensioned not to exceed (e.g., be equal in size or smaller than) four inches by four inches wide and two and a quarter inches high (4"×4"×2.25"). For example, when in a truncated sphere configuration, the housing 460 can be dimensioned to include a four inch (4") diameter and a height of two and a quarter inches (2.25"). The housing 460 is configured to contain the transceiver 420 and the processing circuitry 410. In certain embodiments, the housing 460 is configured to contain at least a portion of the power source 440. In certain embodiments, the housing 460 is configured to contain the entire control system 440.

In certain embodiments, the network node 470 is communicably coupled to a backhaul network 480 (for example,

a private or 3<sup>rd</sup> Party telecommunication network). The network node **470** sends signals to and receives signals from the backhaul network **480**. Through the backhaul network, the network node **470** sends signals to and receives signals from the network **495**. In certain embodiments, the control system **400** includes the network node **470**. In certain embodiments, the control system **400** is communicably coupled to the network node **470**. The network node **470** is configured to enable the control system **400**, and respective components therein, to communicate via the network node **470** to one or more of the backhaul network **480** and the network **495**. The network node **470** is configured to be connected to or communicably coupled (for example, logically coupled) with one or more other nodes of other control systems **400**, such as of different DERs. Accordingly, through the network node **470**, the control system **400** of a first DER is configured to enable a second DER to be indirectly and communicably coupled to the backhaul network **480** and the network **495**. That is, the second DER **100** is configured to couple to one or more of the backhaul network **480** and the network **495** via the first DER **100**. In certain embodiments, the network node **470** is configured to communicate to the backhaul network **480** using Ethernet, fiber, wireless communication, or any form of Local Area Network, or Wide Area Network technology.

The backhaul **480** is communicably coupled to the network node **470** and the network **495**, enabling communications between the network node **470** and the network **495**. The backhaul network **480** sends signals to and receives signals from the network **495** and one or more network nodes **470**. The backhaul **480** enables two-way communication between the node **470** and the network **495**. The backhaul **480** can be a wired or wireless network.

The control system **400** is configured to communicate with a number of mobile terminals **490**. The control system **400** sends signals to and receives signals from the mobile device **490** via a link **455**. The mobile terminal **490** can be a portable computer, a “smart phone”, personal data assistant, a touchscreen tablet, an electronic wallet, a vehicle or the like.

FIG. 5 illustrates a string of DERs **500** according to embodiments of the present disclosure. Although certain details will be provided with reference to the components of the string of DERs **500**, it should be understood that other embodiments may include more, less, or different components. The string of DERs **500** includes a number of DERs, such as DERs **100a** and **100b**. Each of the DERs **100a** and **100b** contains a control system **400**. The DERs **100a** and **100b** are communicably coupled to a common node, such as network node **470**, thereby establishing an interlinked string of DERs **500**. As described in further detail below, a set of surface reflectors **500** may include various embodiments of DERs and DER assemblies as well as various quantities of the DERs.

DER **100a** is embodied as a truncated pyramid pavement marker having reflective material on at least one side. The DER **100a** includes a power source **440** configured as a port connected to an external power source **510a** via a conductor **515**. In certain embodiments, the external power source **510a** and **510b** is embodied as one or more of: a lane marker; pedestrian marker; or other road or pedestrian way markings. The solar power panels **510a** and **510b** include a photovoltaic material that converts solar light or solar energy into electricity. For example, the external power source **510a** and **510b** includes a plurality of photovoltaic cells configured to convert solar energy into electrical energy, such as a plurality of solar cells or a solar power

panel. The conductor **515** can be any suitable conductor. The DER **100a** includes a communication interface **430** that is coupled to the external network node **470**. The connection between the communication interface **430** and the external network node **470** may be on the surface or below the surface of the object to which the DER **100** is attached.

The DER **100b** and the solar power panel **510b** together form a DER assembly **520**. The DER assembly **520** includes a plurality of power sources **440** and **510b**.

The DER **100b** is embodied as a truncated sphere pavement marker having a reflective material disposed on the entire surface. The DER **100b** includes a power source **440** configured as a power port or power interface. The power port or power interface **440** is adapted to connect to a plurality of different power sources (**510b**, **510a**). In certain embodiments, as illustrated in FIG. 5, a portion of the solar power panel **510b** is disposed beneath, or otherwise in physical contact with, the housing **460**, and another portion is disposed outside the housing **460**. In certain embodiments, the DER assembly **520** does not include a portion of the external power source (e.g., solar power panel) **510b** contained within the housing **460**.

The DER **100b** includes communication interface **430b**. The communication interface **430b** of DER **100b** is coupled to (e.g., in data communication with) the communication interface **430a** of DER **100a**, which is connected to a node **470**. Where one of the communication interfaces **430a** and **430b** is connected to the network node **470**. The connection between the communication interfaces **430a** and **430b** of the DERs **100a** and **100b**, forms a daisy chain **530**. In certain embodiments, the daisy chain **530** is a logical daisy chain. The daisy chain **530** enables a communication interface **430b** that is not directly connected to the network node **470** to connect to the node **470** via the connection to a communication interface **430** of the first DER **100a**, which is coupled to the network node **470**. The daisy chain **530** may extend by connecting a subsequent DER **100c** to one of the communication interfaces **430b** and **430a** of either the surface reflector **100b** or the surface reflector **100a**.

FIG. 6 illustrates a network of DERs according to embodiments of the present disclosure. The embodiment of the DER network **600** shown in FIG. 6 is for illustration only. Other embodiments could be used without departing from the scope of this disclosure. Although in FIG. 6, each set of DERs **610** includes four surface reflectors, a set of DERs **610** can include any number of DERs. In certain embodiments, a set of DERs **610** spans a quarter of a mile (1609 meters).

The network of DERs **600** includes a plurality of sets of DERs. For example, the network of DERs **600** includes a first set of DERs **610a** and a second set of DERs **610b**. Network node **470b** of a second set of DERs **610b** is connected to network node **470a** of a first set of DERs **610a**. In certain embodiments, the network node **470b** is logically connected to network node **470a**. The first set of DERs **610a** is connected to the backhaul network **480**. The connection between the network nodes **470a** and **470b**, in which one of the first network nodes **470a** is connected to the backhaul **480**, forms a daisy chain **620** of nodes. The daisy chain **620** enables network node **470b** to connect to the backhaul **480** via the connection to the network node **470a** of the first set of DERs **610a**, which is coupled to the backhaul **480** directly (for example, wherein a signal from the network node **470a** is not received by an intermediary before the backhaul network receives the signal). In certain embodiments, the daisy chain **620** is a logical daisy chain such that the second network node **470b** sends signals to and

receives signals from the first network node **470a** via the backhaul network **480** and the network **495**. The daisy chain **620** can be extended by connecting a subsequent network node **470** of another set of DERs **610** to either the network node **470a** or the network node **470b**. In certain embodiments of the network of DERs **600**, the first network node **470a** is connected to the backhaul network **480**, and the second network node **470b** is directly coupled to the backhaul network **480** independent of the daisy chain **620** connection. In certain embodiments of the network of DERs **600**, the first network node **470a** is connected to the backhaul network **480**, and the second network node **470b** is coupled to the backhaul network **480** through one or more of a direct connection independent of the daisy chain **620** and through the first network node **470a** via the daisy chain **620**. For example, the second set of DERs **610b** select to the backhaul network via the independent direct connection to the backhaul network **480** or alternatively via the daisy chain to the first network node **470a**. In certain embodiments of the network of DERs **600**, the daisy chain is extended by connecting either the network node **470a** or the network node **470b** to a third network node **470** (of a third set of DERs **610**) that is directly connected to the backhaul network **480**. In certain embodiments, when a plurality of network nodes **470a** and **470b** have established a communication (such as a channel of communication) with the network **495**, each network node **470** sends signals to and receives signals from the other network nodes **470**. For example, the first network node **470a** sends signals to and receives signals from the second network node **470b** via one or more of the backhaul network **480** and the network **495**.

The set of DERs **610a** includes truncated pyramid shaped surface reflectors. Each DER of **610a** includes a communication interface **430** that is coupled to the network node **470a**. The second set of DERs **610b** includes truncated sphere shaped DERs. Each DER of the set **610b** includes a communication interface **430** coupled to the communication interface **430** of an adjacent DER, creating a daisy chain to the communication interface **430** that is coupled to the network node **470b**. In certain embodiments, the coupling is a logical daisy chain between a first communication interface **430** of a DER of the set **610b** and a second communication interface **430** of a second DER of the set **610b** that is coupled to the network node **470b**.

FIG. 7 illustrates a process for providing mobile broadband data access according to embodiments of the present disclosure. The embodiment of the process **700** shown in FIG. 7 is for illustration only. Other embodiments could be used without departing from the scope of this disclosure.

The process **700** can be performed, for example, by one or more control systems **400**, hereinafter referred to in the singular as “the system.” The process **700** can be implemented by executable instructions stored in a non-transitory computer-readable medium that cause one or more surface reflector control systems **400** to perform such a process.

In block **705**, when a mobile terminal **490** is within a range close enough to communicably couple to at least one control system **400** of a surface reflector, the processing circuitry **410** is within a communicable coupling range and will initialize and establish a wireless connection with the mobile terminal **490**. The processing circuitry **410** is configured to determine when the mobile terminal **490** is within a communicable coupling range, such as based in part on the strength of the signal between the mobile terminal **490** and the antenna **450**.

In block **710**, once a mobile terminal **490** is communicably coupled to at least one DER **100**, the DER **100** transmits

data back and forth between the mobile terminal **490** and the network **495**. The data communication path includes the mobile terminal **490**, the antenna **450**, the transceiver **420**, the processing circuitry **410**, the communication interface **430**, the node **470**, the backhaul **480**, and the network **495**.

In block **715**, as the mobile terminal **490** moves, the mobile terminal **490** moves out of a communicable coupling range of a first DER to which the mobile terminal **490** is connected. The mobile terminal **490** moves into a communicable coupling range of a second DER that belongs to the same set **610** of DERs as the first surface reflector. In certain embodiments, the second DER initiates and establishes a wireless connection with the mobile terminal **490**. In response to the establishment a connection of the mobile terminal **490** to the second DER, the first DER terminates the data connection to the mobile terminal **490**. This process is referred to as a same-node handover.

In certain embodiments, the processing circuitry **410** is configured to perform a different-node handover in block **720**. As the mobile terminal **490** continues to move, the mobile terminal **490** moves out of a communicable coupling range with all of the DERs in the first set of DERs that are coupled to the node of the first DER. In the different-node handover **720**, in response to the establishment of a connection with a second DER that does not belong to the same set **610** of DERs as the first DER (e.g., not included in the first set of DERs), the first DER terminates the data connection between the mobile terminal **490** and the first DER. In certain embodiments, the different-node handover process is conducted using a hardwire handover in which the first node and second node are communicably coupled via a wired connection. In certain embodiments, the different-node handover process is conducted using a wireless handover—in which the first node and second node are communicably coupled via a wireless connection. In certain embodiments, one or more of the same node handovers and different node handovers are controlled by a central switch. In certain embodiments, one or more of the same node handovers and different node handovers are controlled by one of the network nodes **470**. In certain embodiments, one or more of the same node handover and different node handover are controlled in part by the mobile terminal. In certain embodiments, one or more of the same node handover and different node handover are controlled by one or more components in the backhaul network **480**.

FIG. 8 illustrates a DER **100** providing mobile broadband access to a vehicle **800** according to embodiments of the present disclosure. In certain embodiments, the mobile terminal **490** is a vehicle **800** (e.g., car; truck; van; bus) that includes an antenna **810** adapted to receive wireless data signals from one or more DERs **100**. The control system **400** of the DER **100** sends signals to and receives signals from the vehicle **800** via a link **850a**.

The vehicle **800** includes a transmitter **820** to send wireless data signals to one of more DERs **100**. In certain embodiments, the vehicle’s antenna **810** and transmitter **820** (together “vehicle transceiver” **830**) are located physically close to the ground, such as at or near the bottom of the vehicle, under the passenger cabin. When the DER **100** is located on the street and the vehicle transceiver **830** is disposed under the vehicle, the vehicle can receive a stronger signal link **850a** from the DER **100** as compared with the strength of the signal link **850b** to the mobile terminal **860** within the passenger cabin. In certain embodiments, the vehicle’s antenna **810** positioned on the vehicle in any one or more of: atop, on a side, internally, externally, beneath,

the so forth, to enhance transmission and reception of signals between the antenna **810** and the DER **100**.

In certain embodiments, the antenna **810** is coupled to a control unit located in the vehicle **800**. The vehicle's control unit **840** includes processing circuitry, a memory **842**, and an interface **844** to link **870** to a mobile terminal **860** within the passenger cabin of the vehicle. The link **870** can be a wired or wireless link, such as via BLUETOOTH Low Energy, infrared, Universal Serial Bus (USB), or any other suitable data transmission medium link. The control unit **840** is adapted to boost the strength of the signal from the DER **100** to the mobile terminal **860**. For example, when the signal strength link **850b** (between the DER **100** and the mobile terminal **860** within the passenger cabin of the vehicle) is weak compared to the signal strength of link **850a** (between the DER **100** and the vehicle **800**), then the DER **100** sends signals to the mobile terminal **860** through the control unit **840** and through the vehicle interface link **870** to the mobile terminal **860**.

In certain embodiments, the control unit **840** includes a memory **842** adapted to buffer data transferred from the network **495** to the mobile device **860**. The control unit **840** monitors a transfer of data from the network **495** to the memory of the mobile terminal **860**. In the event a connection between the mobile terminal **860** and the control unit **840** is lost or severed during a download of a file from the network **495**, the control unit **840** continues to download data from the network **495** via the connection **850a** between the control unit **840** and the DER **100**. The control unit **840** stores the download data in the memory **842** for retrieval by the mobile terminal **860**. Upon a re-connection between the mobile terminal **860** and the controller **840**, the downloaded data stored in the memory **842** is transferred to the mobile terminal **860**.

As an illustrative and non-limiting example: a user commences downloading a movie. During the download of the movie, the user exits the vehicle **800** along with the mobile terminal **860**, thus severing the connection between the mobile terminal **860** and the control unit **840**. Thereafter, the control unit **840** continues to download and store the remaining portion of the movie. When the user returns to the vehicle and re-connects the mobile terminal **860** to the control unit **840** via the interface **844**, the remaining portion of the movie is downloaded to the mobile terminal. The mobile terminal can prompt the user to request a download of the buffered data after the marker. Alternatively, in response to a re-establishment of the link **870**, the controller **840** can initiate the download of the buffered data without user interaction. Therefore, the user is able to complete the download without being required to re-start the entire download.

In certain embodiments, the control unit **840** stores a file marker indicating when the download was interrupted. The control unit **840** stores a first file marker in the memory **842**. The file marker identifies the portion (transferred portion) of the file that has been transferred to the memory of the mobile terminal **860** and the portion (un-transferred portion) of the file that has not been transferred to the memory of the mobile terminal **860**. If before the entire file is transferred to the memory of the mobile terminal **860**, the user removes the mobile terminal **860** from the vehicle **800** or otherwise disconnects the mobile terminal **860** from interface link **870**, then the control unit **840** will continue to download the un-transferred portion and store or buffer the un-transferred portion in the memory **842** of the control unit **840**.

When the mobile terminal **860** re-establishes the link **870** to the control unit **840** through the interface **844**, then

un-transferred portion of the data is downloaded to the memory of the mobile terminal **860**. That is, in response to a reconnection of the mobile terminal **860** with the control unit **840**, the download is re-initiated at the point indicated by the marker. The mobile terminal can prompt the user to request a download of the un-transferred portion of the data after the marker. Alternatively, in response to a re-establishment of the link **870**, the controller **840** can initiate the download of the un-transferred data after the marker without user interaction. In both cases, however, the data downloaded prior to the marker is not required to be downloaded again.

FIG. 9 illustrates a DER system **900** according to embodiments of the present disclosure. Although certain details will be provided with reference to the components of the DER system **900**, it should be understood that other embodiments may include more, less, or different components. The DER system **900** includes a DER **100** coupled to a mobile terminal **490** and to a controller unit **905**. The DER **100** includes the control system **400**.

The controller unit **905** operates as an access point, providing features such as access control, theft prevention, data traffic monitoring, data traffic shaping, network node to network node signaling, and various other features associated with network access and control. In certain embodiments, the controller unit **905** includes the features and functions of the node network **470**. In certain embodiments, the controller unit **905** and the network node **470** are interchangeable. The controller unit **905** is coupled to the backhaul network **480** via a wire line or wireless connection. The controller unit **905** couples to one or more computer networks via the backhaul network **480**.

The controller unit **905** includes processing circuitry **910** configured to control components within the controller unit **905**. In certain embodiments, the processing circuitry **910** controls the memory **920a-b**, the communication interface **930**, and the energy unit **940**. The controller unit **905** establishes a secure channel for sending and receiving control and data signals to and from one or more DERs **100**. The processing circuitry **910** provides a virtual private network (VPN) initialization and termination for communications between the controller unit **905** and the DER **100**. That is, the controller unit **905** communicates with the DER **100** via a secured channel using a VPN. In certain embodiments, the processing circuitry **910** is configured to send encrypted data and to decipher encrypted data received from the DER **100**. That is, the processing circuitry **910** and control system **400** establish an encryption agreement or share a common encryption key used to secure the data transmitted between the controller unit **905** and the DER **100**.

The controller unit **905** includes memory **920** configured to store instructions for the processing circuitry **910** and to store information used in functions performed by the processing circuitry **910**. In certain embodiments, the processing circuitry **910** includes the memory **920a** within the same integrated circuitry. In certain embodiments, the processing circuitry **910** is coupled to the memory **920b**.

The controller unit **905** includes a communication interface **930** configured to send and receive control signals and data between the DER **100** and the controller unit **905**. The communication interface **930** is coupled to the backhaul network **480** via a wire line or wireless connection. The controller unit **905** uses the communication interface **930** to send signals to and receive signals from the network **495** via the backhaul network **480**. That is, the controller unit **905** is communicably coupled to the network **495** through the

backhaul network **480**. The communication interface **930** includes the network node **470**, a GPS receiver **950**, and an optical communication terminal **960**.

The GPS receiver **950** is configured to locate GPS satellites and to deduce the location of the controller unit **905** using signals received from the satellites. In certain embodiments, the controller unit **905** sends a message indicating the location to each DER **100** within the set of DERs **610** controlled by that controller unit **905**. The location message can include a GPS location, a geographic coordinate system coordinate pair, an approximate address, and an intersection. In response to receiving the location message, the DER **100** saves the location information in memory **412**.

For example, the DER **100** receives and stores the location information derived from the GPS **950** from the controller unit **905**. The user of the mobile terminal **490** uses a maps or navigation application to track a selected path from point A to point B. Between point A and point B, the mobile terminal **490** loses connection with GPS satellites and cannot determine the location of the mobile terminal. The DER **100** forwards the location information to the mobile terminal **490**, thereby enabling the mobile device's maps or navigation application to determine the location of the mobile terminal. Accordingly, the DER system **900** enhances the user's GPS navigation experience.

The optical communication terminal **960** configured to send and receive signals via light, wherein the signals comprise data or control signals. That is, the optical communication terminal **960** sends and receives signals by way of an optical communication channel. The optical communication terminal **960** includes an input/output (I/O) terminal configured for receiving input signals via a light input and sending output signals via a light output. In certain embodiments, the optical communication terminal **960** is configured to communicate using laser I/O signals. In certain embodiments, the optical communication device is configured to communicate using white space frequency. As an example, when television channel 4 and channel 5 represent the government designated frequencies of 8.0 mega-Hertz and 9.0 mega-Hertz, then white space frequency represents band of 8.5-8.9 mega-Hertz that the government has not reserved for a specified purpose (e.g., television channel 4 and 5).

In certain embodiments, the optical communication terminal **960** is configured to communicate photonically, using photons of light. Photonic communication uses a subset of a light wave and transmits signals faster than signals transmitted via laser light. The optical communication terminal **960** is configured to detect a breach in the security of the signal transmission channel. For example, the optical communication terminal **960** detects an interruption of light within the transmission path and interprets the interruption as an indication of a breach of security. As another example, the optical communication terminal **960** detects a change in polarity of the photons of a photonic signal within the transmission path and interprets the changed polarity as an indication of a breach of security.

In certain embodiments, the communication interface **430** of the control system **400** includes an optical communication terminal **960**. For example, a first DER **100a** and a second DER **100b** each include an optical communication terminal **960** and communicate by laser or photonically with each other using the respective optical communication terminals **960**. As another example, the DER **100** includes an optical communication terminal **960b** and sends and receives signals by laser or photonically with the optical communication terminal **960a** of the controller unit **905**.

The controller unit **905** includes an energy unit **940** configured to provide electric energy to the constituent electrical components of the controller unit **905**. The energy unit **940** receives electricity from one or more of the following sources: a local utility power line, heat, such as geothermal heat, and vibrations. In certain embodiments, the energy unit **940** is configured to convert geothermal energy into electricity for the controller unit **905**. In certain embodiments, the energy unit **940** is configured to convert energy from road vibrations into electricity for the controller unit **905**. In certain embodiments, the energy unit **940** is configured to transmit wireless power signals to the power source **440**, and the wireless power signals charge an energy storage device within the power source **440**. The wireless power transmission transmitter of the energy unit **940** is configured to couple to the wireless power receiver of the DER's power source **440**, such as a shared frequency coupling.

That is, in certain embodiments, the power source **440** within the control system **400** is configured to receive and use wireless power to supply electricity to components within the control system **400** and to charge an energy storage device, such as a battery.

According to embodiments of the present disclosure, The DER system **900** is configured to receive information from a police officer mobile **490**, such as information regarding the geographical location of a police officer. In certain embodiments, the DER system **900** is configured to determine the proximal distance of the police officer from the DER **100** based on the geographical location of a police officer.

The DER system **900** is configured to implement a process for reporting vehicle velocity and identification information as will be described more particularly in reference to FIGS. **9** and **11**.

FIG. **10** illustrates a network of DERs **1000** according to embodiments of the present disclosure. Although certain details will be provided with reference to the components of the network of DERs **1000**, it should be understood that other embodiments may include more, less, or different components. Although in FIG. **10**, the network of DERs **1000** includes four controller units **905a-d**, each controlling a corresponding set of DERs **610a-d** of four surface reflectors each, the network of DERs **1000** can include any number of sets of DERs **610**. The components of FIG. **10** share the features and functions of the components of FIG. **6**.

The network of DERs **1000** includes a plurality of sets of DERs. For example, the network of DERs **1000** includes a first set of DERs **610a**, a second set of DERs **610b**, a third set of DERs **610c**, and a fourth set of DERs **610d**. The first controller unit **605a** controls the first set of DERs **610a**; the second controller unit **605b** controls the a second set of DERs **610b**; the third controller unit **605c** controls the third set of DERs **610c**; and the fourth controller unit **605d** controls the a fourth set of DERs **610d**.

The controller unit **905a** of a first set of DERs **610a** is connected to controller unit **905b** of the second set of DERs **610b** via a wire line or a wireless connection, forming a daisy chain from the controller unit **905a** to the backhaul network **480**. That is, the controller unit **905a** is not directly connected to the backhaul network **480**, but instead, the second controller unit **905b** is an intermediary between the backhaul network **480** and the first controller unit **905a**. The first controller unit **905a** is coupled to the controller units **905c** and **905d** via a logical connection in combination with the wire line or wireless connection to the backhaul network **480**. The first controller unit **905a** sends control signals and

17

data signals to the controller units **905c** and **905d** via the logical connection (through **905b** and **480**) and in return, receives response messages from the controller units **905c** and **905d**.

In reference to FIGS. **10** and **13**, the network of DERs **1000** is configured to implement a process for sequentially transmitting segments of a data file to a mobile station **860** within a vehicle **800** based on projected geographical location of the vehicle **800**.

FIG. **11** illustrates a process **1100** for reporting vehicle velocity and identification information according to embodiments of the present disclosure. The embodiment of the process **1100** shown in FIG. **11** is for illustration only. Other embodiments could be used without departing from the scope of this disclosure.

A vehicle **800** travels in near proximity to a DER **100** at a velocity  $\vec{v}$ , including a direction and a speed. In block **1105**, the DERs **100** broadcasts one or more RADAR signals. When the RADAR signals are incident upon a vehicle **800** or other object, the signals reflect off the vehicle **800** and return toward the RADAR transceiver within the RADAR unit **415**.

In block **1110**, the RADAR unit **415** receives the reflected return RADAR signals. In certain embodiments, block **1110** further comprises receiving an image associated with the reflected return RADAR signals. The processing circuitry **410** is configured to instruct the camera **425** to capture a picture of the object the broadcasted RADAR waves were incident upon. That is, the camera captures an image of the vehicle **800** or vehicle license plates corresponding to the reflected return RADAR signals.

In block **1115**, the control system **900** determines the velocity  $\vec{v}$  of the vehicle **800**. In certain embodiments, the control system **400** of the DER **100** determines the velocity  $\vec{v}$  of the vehicle using the waveform information from the RADAR unit **415**. In certain embodiments, the controller unit **905** determines the direction and speed of the vehicle **800**. The controller unit **905** makes the determination using information received from the RADAR unit **415** of the DER **100**.

In block **1120**, the control system **900** compares a threshold speed to the vehicle speed determined in block **1115**. Examples of the threshold speed include: a user determined speed to be monitored, a specified speed stored within the control system, a speed limit corresponding to the location of the DER **100**, a speed above the speed limit selected by a law enforcement officer seeking to confront or issue citations to speed limit violators. The control system **900** determines whether the vehicle speed is greater than or equal to the threshold speed. When the vehicle speed is at least the threshold speed, then the control system **900** moves to block **1125**. When the speed is less than the threshold speed, the control system moves to block **1105**.

In certain embodiments, in block **1125**, the control system **900** sends the speed information to an external device. For example, the control system **900** can send the speed information to one or more of a computer within the network **495**, a network user, an operator of the vehicle, or a third party. The speed information includes the image of the vehicle captured in block **1110**, the velocity  $\vec{v}$  of the vehicle determined in block **1115**, and the results of the speed comparison derived in block **1120**.

FIG. **12** illustrates a process **1200** for reporting vehicle location and identification information according to embodiments of the present disclosure. The embodiment of the

18

process **1200** shown in FIG. **12** is for illustration only. Other embodiments could be used without departing from the scope of this disclosure. At the start, a vehicle **800** travels

nearby a DER **100** at a velocity  $\vec{v}$ , including a direction and a speed. In block **1205**, the control system **400** of the DER **100** receives a targeted license plate number. For example, the mobile phone within the vehicle receives an AMBER (America's Missing: Broadcast Emergency Response) alert containing the color and license plates number of a vehicle of interest and forwards the AMBER alert information to the control system **400** via the link **455**. As another example, the network **495** includes a government law enforcement system or a government department of transportation system. A computer within the network sends a message to the controller unit **905** indicating targeted license plates numbers of one or more vehicles used in an illegal act. The controller unit **905** forwards the targeted license plates numbers to at least one of the DERs **100** within the set of DERs **610** controlled by the controller unit **905**. The targeted license plates numbers are stored in memory **412**, **920a-b**.

In block **1210**, the camera **425** captures an image of the vehicle **800**, including the vehicle license plate and the color of the vehicle. The image received for processing by processing circuitry **410** or **910**.

In block **1215**, the processing circuitry **410** or **910** recognizes the string of characters within the image that was captured in Block **1210**. The processing circuitry **410,910** uses an OCR capability to determine the characters in within the image of the vehicle license plate. In certain embodiments, the processing circuitry **410,910** is configured to determine a color of the car bearing the license plate in the image.

In block **1220**, the processing circuitry **410** or **910** compares one or more targeted license plate numbers to the string of characters recognized in image of the vehicle license plate. When the string of characters recognized in image of the vehicle license plate is substantially similar to or equal to a targeted license plate number, the control system moves to block **1225**. When matching license plate number is found, the control system moves to block **1205**. In certain embodiments, the processing circuitry **410,910** looks for matching colors by comparing the color of the car to the color in the AMBER alert.

In block **1225**, the control system **900** sends location information and the vehicle information to a computer within the network **495** or a network user. The vehicle information includes the color of the vehicle, the string of characters recognized in the image of the vehicle license plate. The location information includes the location of the DER. In certain embodiments, the vehicle information includes the velocity  $v$  of the vehicle.

FIG. **13** illustrates a process **1300** for sequentially transmitting segments of a data file to a mobile station based on projected geographical location of the mobile station according to embodiments of the present disclosure. The embodiment of the process **1300** shown in FIG. **13** is for illustration only. Other embodiments could be used without departing from the scope of this disclosure.

In block **1305**, mobile terminal **860** sends a request to the DER **100** to download a file from the network **495**. In certain embodiments, the mobile terminal can be associated with a user that is not within a motor vehicle **800**. The DER **100** receives the request to download a file from the mobile terminal **860**.

In block **1310**, the control system **400** of the DER retrieves the requested file from the network **495** via the



control unit **905** and the backhaul network **480**. The processing circuitry **910** of the controller unit **905a-d** is configured to receive request to retrieve a file from the network **495**. In response to receiving the request to retrieve the file, the controller unit **905a-d** retrieves the file from a location within the network **495**. The processing circuitry **910** of the controller unit **905a-d** is configured to determine the number of file segments into which the retrieved file is divided. The processing circuitry **910** is configured to assemble scrambled file segments into a time dependent sequential order when the retrieved file is divided in to file segments and transmitted out of time dependent order for increased speed of transmission. For example, a movie file may be divided into four file segments A-D. The network computer storage of the movie file may transmit to the controller unit **905a** the file segment A (containing the first 10 minutes of the movie), followed by the file segment D (containing the fourth 10 minutes of the movie), then file segment C (containing the third 10 minutes of the movie), and then file segment B (containing the second 10 minutes of the movie). The processing circuitry **910** uses a marker within each file segment to determine the time dependent order of the file segments, such as determining that file segment A contains the first portion of the file. The processing circuitry **910** assembles file segment D to be immediately follow file segment C; assembles file segment C to be immediately follow file segment B; and assembles file segment B to be immediately follow file segment A. That is, processing circuitry **910** receives a scrambled set of file segments {A, D, C, B} and assembles the file segments into a time dependent sequence {A, B, C, D}.

In block **1315**, the controller unit **905a** determines the number of file segments to be transferred to the mobile station **860**. In some instances, the computer (within the network **495**) from which the controller unit **905s** retrieves the file divided the file into a number of file segments before the controller unit **905** retrieved the file. In some instances, the controller unit **905a** retrieves the requested file from the computer (within the network **495**) as one large undivided file. The controller unit **905a** is configured to divide the retrieved file into a number of file segments to hasten transmission of the retrieved file to the mobile station **860**. The controller unit **905a** is configured to further divide the retrieved file segments into a larger number of file segments to hasten the transmission.

Also in block **1315**, the controller unit **905a** determines a sequence in which the file segments should be transferred to the mobile station **860**. For example, the controller unit **905** can determine to first transmit two small, non-consecutive (e.g., file segments A and D) to a DER **100**, and next transmit a single file segment C.

In block **1320**, the DER **100** broadcasts RADAR signals **1320**, such as in block **1105**. In block **1325**, the DER **100** receives reflected return radar signals, such as in block **1110**. In block **1330**, the processing circuitry **410, 910** of the DER or the controller unit **905a** determines the velocity  $\vec{v}$  of the vehicle **800**, such as in block **1115**.

In block **1335**, the controller unit **905a** determines a schedule of times at which each file segment should be transmitted to the mobile terminal **860** from a DER **100**. The controller unit **905a** makes this determination by using the speed and direction of the vehicle **800** that was determined in step **1330**, by using the speed of data transfer, and by using the size and number of file segments to be transferred. For example, the controller unit **905a** determines that at a first time **t1**, the file transfer should begin by transferring file

segment A to the mobile terminal **860** and should end before **t2**. That is, each scheduled file transfer should end before the next schedule file transfer begins. At a second time **t2**, file segment B should be transferred to the mobile terminal **860**. At a third time **t3**, file segment C should be transferred to the mobile terminal **860**. At a fourth time **t4**, the last file segment D should be transferred to the mobile terminal **860**.

In block **1340**, the controller unit **905a** determines projected locations of the vehicle **800** based on the velocity  $\vec{v}$  of the vehicle. For example, a first reference time **t1**, the controller unit **905a** determines that the vehicle **800** is located at a first location **L1** using the reflected RADAR signals of block **1325**. The controller unit **905a** calculates a forecast of the locations of the vehicle **800** at times **t2, t3, and t4** (as scheduled in block **1335**). The controller unit **905a** calculates that the vehicle **800** will be located at projected location **L2** at time **t2**, will be located at projected location **L3** at time **t3**, and will be located at projected location **L4** at time **t4**.

In block **1345**, the controller unit **905a** determines which control unit would be coupled to the mobile station at each scheduled file transfer time. The determination is based on the velocity  $\vec{v}$  of the vehicle. For example, the controller unit **905a** is coupled to the mobile station **860** via the first set of DERs **610a** determines that at a first time **t1**, and that the first controller unit **905a** should instruct the first set of DERs **610a** to begin transferring file segment A to the mobile terminal **860**. The controller unit **905a** determines that at a second time **t2**; that the second controller unit **905b** will be coupled to the mobile station **860** via the second set of DERs **610b** and should instruct the second set of DERs **610b** to begin transferring file segment B to the mobile terminal **860**. The controller unit **905a** determines that at a third time **t3**; that the third controller unit **905c** will be coupled to the mobile station **860** via the third set of DERs **610c** and should instruct the third set of DERs **610c** to begin transferring file segment C to the mobile terminal **860**. The controller unit **905a** determines that at a fourth time **t4**; that the fourth controller unit **905d** will be coupled to the mobile station **860** via the fourth set of DERs **610d** and should instruct the fourth set of DERs **610d** to begin transferring file segment D to the mobile terminal **860**.

In block **1350**, the control unit **905a** causes each control unit **905a-d** to receive an assigned file segment to be transferred by that control unit to the mobile station. The control unit **905a** uses the determination of block **1345** that the file segment B is assigned to be transferred by the second controller unit **905b**. Accordingly, the controller unit **905a** causes the second controller unit **905b** to receive the second file segment to be transferred, file segment B. Likewise, the controller unit **905a** causes the third controller unit **905c** to receive the third file segment to be transferred, file segment C. The controller unit **905a** causes the fourth controller unit **905d** to receive the fourth file segment to be transferred, file segment D.

In certain embodiments, the controller unit **905a** causes the second controller **905b** to receive the assigned file segment by sending the assigned file segment to the second controller **905b** via mutual coupling. In certain embodiments, the controller unit **905a** causes the second controller **905b** to receive the assigned file segment by sending an signal to the second controller **905b** instructing the second controller **905b** to retrieve the assigned file segment from the network.

In block **1355**, the controller unit **905a** instructs each control unit **905a-d** to transfer the respective assigned file

segment to the mobile station **860** at the scheduled time (according to the schedule of block **1335**).

Although various features have been shown in the figures and described above, various changes may be made to the figures. For example, the size, shape, arrangement, and layout of components shown in FIGS. **1** through **6** and **8** are for illustration only. Each component could have any suitable size, shape, and dimensions, and multiple components could have any suitable arrangement and layout. Also, various components in FIGS. **1** through **6** could be combined, further subdivided, or omitted and additional components could be added according to particular needs. For instance, a system using GTDs could support only cellular or satellite communications. Further, each component in a device or system could be implemented using any suitable structure(s) for performing the described function(s). In addition, while FIG. **7** illustrates various series of steps, various steps in FIG. **7** could overlap, occur in parallel, occur multiple times, or occur in a different order.

Although an exemplary embodiment of the present disclosure has been described in detail, those skilled in the art will understand that various changes, substitutions, variations, and improvements disclosed herein may be made without departing from the spirit and scope of the disclosure in its broadest form.

None of the description in the present application should be read as implying that any particular element, step, or function is an essential element which must be included in the claim scope: the scope of patented subject matter is defined only by the allowed claims. Moreover, none of these claims are intended to invoke paragraph six of 35 USC § 112 unless the exact words “means for” are followed by a participle.

What is claimed is:

**1.** A system, comprising:

a plurality of spaced surface markers disposed on a travel surface, each surface marker comprising:

a housing,

a power system disposed within the housing and configured to produce electrical power from at least one of solar energy and vibration of the respective surface marker,

at least one wireless transceiver disposed within the housing, powered by the power system, and configured to wirelessly communicate with transceivers within neighboring ones of the plurality of spaced surface markers, and

processing circuitry disposed within the housing, powered by the power system, and coupled to the wireless transceiver,

wherein a first of the surface markers is configured to receive data from and transmit data to a second of the surface markers,

wherein the second surface marker is configured to relay data from the first surface marker to a third of the surface markers and to relay data from the third surface marker to the first surface marker, and

wherein at least the third surface marker is further configured to

communicate with a network connection device, relay data originating from one of the first and second surface markers to a remote network via the network connection device, and

relay data originating from the remote network and directed to one of the first and second surface markers to the second surface marker.

**2.** The system of claim **1**, wherein the network connection device is an access point.

**3.** The system of claim **1**, wherein the network connection device is a cellular communications station.

**4.** The system of claim **1**, wherein the network connection device is a mobile telecommunications device.

**5.** The system of claim **1**, wherein the first and second surface markers and the second and third surface markers communicate via wireless fidelity (WiFi) communications.

**6.** The system of claim **1**, wherein the travel surface is a vehicle travel surface.

**7.** The system of claim **1**, wherein each of the plurality of spaced surface markers is configured to communicate with a vehicle traveling on the travel surface within communication range of the respective surface marker.

**8.** The system of claim **7**, wherein each of the plurality of spaced surface markers is configured to provide location information to the vehicle when the vehicle is within communication range of the surface marker.

**9.** The system of claim **1**, wherein each of the plurality of spaced surface markers is configured to communicate with a mobile telecommunications device within communication range of the respective surface marker.

**10.** The system of claim **9**, wherein each of the plurality of spaced surface markers is configured to provide location information to the mobile telecommunications device when the mobile telecommunications device is within communication range of the respective surface marker.

**11.** A surface marker configured to be disposed on a travel surface as one of a plurality of spaced surface markers, the surface marker comprising:

a housing,

a power system disposed within the housing and configured to produce electrical power from at least one of solar energy and vibration of the respective surface marker,

a first transceiver disposed within the housing, powered by the power system, wherein the first transceiver is a wireless transceiver configured to wirelessly communicate with wireless transceivers within neighboring ones of the plurality of spaced surface markers, and processing circuitry disposed within the housing, powered by the power system, and coupled to the wireless transceiver,

wherein the surface marker is configured to

receive data originating from a remote network that has been relayed by at least a second surface marker and a third surface marker of the surface markers, and transmit data directed to the remote network to the second surface marker to be relayed to the remote network via the third surface marker.

**12.** The surface marker of claim **11**, further comprising: a second transceiver disposed within the housing, powered by the power system, and configured to communicate with an access point.

**13.** The surface marker claim **11**, further comprising: a second wireless transceiver disposed within the housing, powered by the power system, and configured to communicate with a cellular communications station.

**14.** The surface marker of claim **13**, wherein the cellular communications station is a mobile telecommunications device.

**15.** The surface marker of claim **11**, wherein the first transceiver is configured to communicate with the neighboring ones of the plurality of spaced surface markers via wireless fidelity (WiFi) communications.

16. The surface marker of claim 11, wherein the travel surface is a vehicle travel surface.

17. The surface marker of claim 11, wherein the surface marker is configured to communicate with a vehicle traveling on the travel surface within communication range of the surface marker. 5

18. The surface marker of claim 17, wherein the surface marker is configured to provide location information to the vehicle when the vehicle is within communication range of the surface marker. 10

19. The surface marker of claim 11, wherein the surface marker is configured to communicate with a mobile telecommunications device within communication range of the surface marker.

20. The surface marker of claim 19, wherein the surface marker is configured to provide location information to the mobile telecommunications device when the mobile telecommunications device is within communication range of the surface marker. 15

\* \* \* \* \*