



(12) **United States Patent**  
**McGeer**

(10) **Patent No.:** **US 7,104,495 B2**  
(45) **Date of Patent:** **Sep. 12, 2006**

(54) **METHODS AND APPARATUSES FOR LAUNCHING, CAPTURING, AND STORING UNMANNED AIRCRAFT, INCLUDING A CONTAINER HAVING A GUIDE STRUCTURE FOR AIRCRAFT COMPONENTS**

(75) Inventor: **Brian T. McGeer**, Underwood, WA (US)

(73) Assignee: **The Insitu Group, Inc.**, Bingen, WA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/269,395**

(22) Filed: **Nov. 8, 2005**

(65) **Prior Publication Data**

US 2006/0175463 A1 Aug. 10, 2006

**Related U.S. Application Data**

(62) Division of application No. 10/759,541, filed on Jan. 16, 2004.

(60) Provisional application No. 60/440,849, filed on Jan. 17, 2003.

(51) **Int. Cl.**  
**B64F 5/00** (2006.01)

(52) **U.S. Cl.** ..... **244/1 R; 244/63**

(58) **Field of Classification Search** ..... **244/1 R, 244/129.1, 63, 117 R**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

965,881 A 8/1910 Draper  
968,339 A 8/1910 Geraldson  
975,953 A 11/1910 Hourwich  
1,144,505 A 6/1915 Steffan

1,164,967 A 12/1915 Thorp  
1,317,631 A 9/1919 Kinser  
1,383,595 A 7/1921 Black  
1,384,036 A 7/1921 Anderson  
1,428,163 A 9/1922 Harriss  
1,499,472 A 7/1924 Hazen  
1,530,010 A 3/1925 Neilson  
1,556,348 A 10/1925 Ray et al.  
1,624,188 A 4/1927 Simon  
1,634,964 A 7/1927 Steinmetz  
1,680,473 A 8/1928 Parker  
1,686,298 A 10/1928 Uhl  
1,712,164 A 5/1929 Peppin  
1,716,670 A 6/1929 Sperry  
1,731,091 A 10/1929 Belleville

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE 4301671 A1 7/1993

(Continued)

**OTHER PUBLICATIONS**

U.S. Appl. No. 10/758,940, filed Jan. 16, 2004, Dennis.



(Continued)

*Primary Examiner*—Galen Barefoot  
(74) *Attorney, Agent, or Firm*—Perkins Coie LLP

(57) **ABSTRACT**

Methods and apparatuses for launching, capturing, and storing unmanned aircraft and other flight devices or projectiles are described. In one embodiment, the aircraft can be assembled from a container with little or no manual engagement by an operator. The container can include a guide structure to control motion of the aircraft components. The aircraft can be launched from an apparatus that includes an extendable boom. The boom can be extended to deploy a recovery line to capture the aircraft in flight. The aircraft can then be returned to its launch platform, disassembled, and stored in the container, again with little or no direct manual contact between the operator and the aircraft.

**34 Claims, 26 Drawing Sheets**



U.S. PATENT DOCUMENTS

1,737,483 A 11/1929 Verret  
 1,738,261 A 12/1929 Perkins  
 1,748,663 A 2/1930 Tucker  
 1,756,747 A 4/1930 Holland  
 1,777,167 A 9/1930 Forbes  
 1,836,010 A 12/1931 Audrain  
 1,842,432 A 1/1932 Stanton  
 1,869,506 A 8/1932 Richardson  
 1,892,357 A 12/1932 Moe  
 1,912,723 A 6/1933 Perkins  
 1,925,212 A 9/1933 Steiber  
 1,940,030 A 12/1933 Steiber  
 1,960,264 A 5/1934 Heinkel  
 2,333,559 A 11/1943 Grady et al.  
 2,347,561 A 4/1944 Howard et al.  
 2,360,220 A 10/1944 Goldman  
 2,364,527 A 12/1944 Haygood  
 2,365,778 A 12/1944 Schwab  
 2,365,827 A 12/1944 Liebert  
 2,380,702 A 7/1945 Persons  
 2,390,754 A 12/1945 Valdene  
 2,435,197 A 2/1948 Brodie  
 2,436,240 A 2/1948 Wiertz  
 2,448,209 A 8/1948 Boyer et al.  
 2,465,936 A 3/1949 Schultz  
 2,488,050 A 11/1949 Brodie  
 2,515,205 A 7/1950 Fieux  
 2,526,348 A 10/1950 Gouge  
 2,669,403 A 2/1954 Milligan  
 2,735,391 A 2/1956 Buschers  
 2,814,453 A 11/1957 Trimble et al.  
 2,843,342 A 7/1958 Ward  
 2,844,340 A 7/1958 Daniels et al.  
 2,908,240 A 10/1959 Hodge  
 2,919,871 A 1/1960 Sorensen  
 2,933,183 A 4/1960 Koelsch  
 3,069,118 A 12/1962 Bernard  
 RE25,406 E 6/1963 Byrne et al.  
 3,163,380 A 12/1964 Brodie  
 3,268,090 A 8/1966 Wirkkala  
 3,454,244 A 7/1969 Walander  
 3,468,500 A 9/1969 Carlsson  
 3,484,061 A 12/1969 Niemkiewicz  
 3,516,626 A 6/1970 Strance et al.  
 3,684,219 A 8/1972 King  
 3,708,200 A 1/1973 Richards  
 3,765,625 A 10/1973 Myhr et al.  
 3,827,660 A 8/1974 Doolittle  
 3,939,988 A 2/1976 Wellman  
 3,943,657 A 3/1976 Leckie  
 3,980,259 A 9/1976 Greenhalgh et al.  
 4,067,139 A 1/1978 Pinkerton et al.  
 4,079,901 A 3/1978 Mayhew et al.  
 4,143,840 A 3/1979 Bernard et al.  
 4,147,317 A 4/1979 Mayhew et al.  
 D256,816 S 9/1980 McMahan et al.  
 4,236,686 A 12/1980 Barthelme et al.  
 4,238,093 A 12/1980 Siegel et al.  
 4,279,195 A 7/1981 Miller  
 4,311,290 A 1/1982 Koper  
 4,408,737 A 10/1983 Schwaerzler

4,471,923 A 9/1984 Hoppner et al.  
 4,523,729 A 6/1985 Frick  
 4,566,658 A 1/1986 Di Giovanniantonio et al.  
 4,678,143 A 7/1987 Griffin  
 4,730,793 A 3/1988 Thurber, Jr. et al.  
 4,753,400 A 6/1988 Reuter et al.  
 4,809,933 A 3/1989 Buzby et al.  
 4,842,222 A 6/1989 Baird  
 4,909,458 A 3/1990 Martin  
 4,979,701 A 12/1990 Colarik et al.  
 5,007,875 A 4/1991 Dasa  
 5,039,034 A 8/1991 Burgess et al.  
 5,042,750 A 8/1991 Winter  
 5,054,717 A 10/1991 Taylor  
 5,109,788 A 5/1992 Heinzmann  
 5,119,935 A 6/1992 Stump et al.  
 5,253,605 A 10/1993 Collins  
 5,253,606 A 10/1993 Orтели  
 5,509,624 A 4/1996 Takahashi  
 5,583,311 A 12/1996 Rieger  
 5,655,944 A 8/1997 Fusselman  
 5,687,930 A 11/1997 Wagner et al.  
 5,906,336 A 5/1999 Eckstein  
 6,264,140 B1 7/2001 McGeer et al.  
 6,457,673 B1 10/2002 Miller  
 6,478,650 B1 11/2002 Tsai  
 2002/0100838 A1 8/2002 McGeer et al.  
 2003/0222173 A1 12/2003 McGeer et al.  
 2005/0133665 A1 6/2005 Dennis et al.

FOREIGN PATENT DOCUMENTS

FR 854371 4/1940  
 GB 2 080 216 A 2/1982  
 GB 2 150 895 A 7/1985  
 GB 2 219 777 A 12/1989  
 JP 07-304498 11/1995  
 WO WO-00/75014 A1 12/2000  
 WO WO-01/07318 A1 A1 2/2001

OTHER PUBLICATIONS

U.S. Appl. No. 10/758,943, filed Jan. 16, 2004, Dennis et al.  
 U.S. Appl. No. 10/758,948, filed Jan. 16, 2004, Dennis et al.  
 U.S. Appl. No. 10/758,955, filed Jan. 16, 2004, McGeer et al.  
 U.S. Appl. No. 10/758,956, filed Jan. 16, 2004, Dennis et al.  
 U.S. Appl. No. 10/759,541, filed Jan. 16, 2004, McGeer.  
 U.S. Appl. No. 10/759,742, filed Jan. 16, 2004, Dennis.  
 "Ames Builds Advanced Yawed-Wing RPV," Aviation Week and Space Technology, Jan. 22, 1973, p. 73.  
 Dickard, H. E. "Mini-RPV Recovery System Conceptual Study," final report, U.S. Army Air Mobility Research and Development Laboratory, Fort Eustis, Virginia, Aug. 1977, Contract DAAJ02-76-C-0048, Report No. USAAMRDL-TR-77-24.  
 Robinson, Russell Norman, "Dynamic Analysis of a Carousel Remotely Piloted Vehicle Recovery System," master's thesis, Naval Post-Graduate School, Monterey, California, Dec. 1977, Thesis No. ADA052401.  
 Whitmore, Stephen A. et al., "Development of a Closed-Loop Strap Down Attitude System for an Ultrahigh Altitude Flight Experiment," technical memorandum, NASA Dryden Flight Research Center, Edwards, California, Jan. 1997, Report No. NASA TM-4775.




Fig. 1B




Fig. 1D




Fig. 1A




Fig. 1C




Fig. 1F




Fig. 1H




Fig. 1E




Fig. 1G




Fig. 2




Fig. 3A






Fig. 3B






Fig. 5A




Fig. 5B






Fig. 5C





Fig. 5D



*Fig. 5E*




Fig. 6A




Fig. 6B




Fig. 6C






Fig. 6D



*Fig. 6E*



*Fig. 6F*




Fig. 6G




Fig. 7A




Fig. 7B






Fig. 7C




Fig. 8A




Fig. 8B




Fig. 9A






Fig. 9B






Fig. 10A




Fig. 10B




Fig. 10C







Fig. 10D




*Fig. 10E*



*Fig. 10F*



*Fig. 11A*



*Fig. 11B*






Fig. 11C




Fig. 11D




Fig. 11E




Fig. 11F




Fig. 11G




Fig. 12A







Fig. 12B




*Fig. 12C*




*Fig. 12D*




*Fig. 12E*




*Fig. 13A*




*Fig. 13B*




*Fig. 13C*



*Fig. 13D*



*Fig. 13E*



*Fig. 13F*

1

**METHODS AND APPARATUSES FOR  
LAUNCHING, CAPTURING, AND STORING  
UNMANNED AIRCRAFT, INCLUDING A  
CONTAINER HAVING A GUIDE  
STRUCTURE FOR AIRCRAFT  
COMPONENTS**

CROSS-REFERENCE TO RELATED  
APPLICATION

The present application is a divisional of U.S. application Ser. No. 10/759,541 filed Jan. 16, 2004, which claims priority to U.S. Provisional Application No. 60/440,849, filed Jan. 17, 2003, the disclosures of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

The present disclosure describes methods and apparatuses for launching, capturing, and storing unmanned aircraft, including methods and apparatuses for securing the aircraft after capture.

BACKGROUND

Unmanned aircraft or air vehicles (UAVs) provide enhanced and economical access to areas where manned flight operations are unacceptably costly and/or dangerous. For example, unmanned aircraft outfitted with remotely controlled cameras can perform a wide variety of surveillance missions, including spotting schools of fish for the fisheries industry, monitoring weather conditions, providing border patrols for national governments, and providing military surveillance before, during and/or after military operations.

Existing unmanned aircraft systems suffer from a variety of drawbacks. For example, existing unmanned aircraft systems (which can include the aircraft itself along with launch devices, recovery devices, and storage devices) typically require substantial space. Accordingly, these systems can be difficult to install and operate in cramped quarters, such as the deck of a small fishing boat, land vehicle, or other craft. Another drawback with some existing unmanned aircraft is that, due to small size and low weight, they can be subjected to higher acceleration and deceleration forces than larger, manned air vehicles and can accordingly be prone to damage, particularly when manually handled during recovery and launch operations in hostile environments, such as a heaving ship deck. Yet another drawback with some existing unmanned aircraft systems is that they may not be suitable for recovering aircraft in tight quarters, without causing damage to either the aircraft or the platform from which the aircraft is launched and/or recovered.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A–1H illustrate an apparatus and process for storing and assembling an unmanned aircraft prior to launch in accordance with an embodiment of the invention.

FIG. 2 is a partially schematic illustration of an apparatus configured to both launch and recover an unmanned aircraft in accordance with an embodiment of the invention.

FIGS. 3A–3B schematically illustrate an apparatus for providing acceleration to launch an unmanned aircraft, and a corresponding deceleration of parts of the apparatus, which deceleration acts as a brake.

2

FIGS. 4A–4C schematically illustrate one type of energy source to provide motive power to an apparatus for accelerating an unmanned aircraft and braking moving components of the apparatus in accordance with an embodiment of the invention.

FIGS. 5A–5E are partially schematic illustrations of an apparatus having at least one movable link for launching an unmanned aircraft in accordance with another embodiment of the invention.

FIGS. 6A–6B are partially schematic illustrations of an apparatus having a movable link for launching an unmanned aircraft in accordance with another embodiment of the invention.

FIGS. 6C–6F are partially schematic illustrations of a carriage having a gripper arrangement for releasably carrying an unmanned aircraft in accordance with an embodiment of the invention.

FIG. 6G illustrates an apparatus for launching an unmanned aircraft in accordance with another embodiment of the invention.

FIGS. 7A–7C illustrate apparatuses for storing and/or launching multiple unmanned aircraft in accordance with yet further embodiments of the invention.

FIGS. 8A–8B illustrate an apparatus configured to recover an unmanned aircraft in accordance with an embodiment of the invention.

FIGS. 9A–9D illustrate a line capture device configured in accordance with an embodiment of the invention.

FIGS. 10A–10D are partially schematic illustrations of a portion of a recovery system, configured to recover an unmanned aircraft and control post-recovery motion of the aircraft in accordance with an embodiment of the invention.

FIGS. 10E–10F are schematic illustrations of portions of recovery systems configured to provide tension in a recovery line in accordance with further embodiments of the invention.

FIGS. 11A–11G are partially schematic illustrations of a system and method for securing and stowing an unmanned aircraft after capture in accordance with an embodiment of the invention.

FIGS. 12A–12E are partially schematic illustrations of a container and method for disassembling and stowing an unmanned aircraft in accordance with another embodiment of the invention.

FIGS. 13A–13F are partially schematic illustrations of aircraft configurations in accordance with further embodiments of the invention.

DETAILED DESCRIPTION

The present disclosure describes unmanned aircraft and corresponding methods and apparatuses for launching and retrieving or recovering such aircraft. Included in the disclosure are methods and apparatuses for handling small unmanned aircraft in a secure and efficient cycle from flight through retrieval, dismantling, storage, servicing, assembly, checkout, launch, and back to flight. Many specific details of certain embodiments of the invention are set forth in the following description and in FIGS. 1A–13F to provide a thorough understanding of these embodiments. One skilled in the art, however, will understand that the present invention may have additional embodiments, and that the invention may be practiced without several of the details described below. For example, many of the aspects described below in the context of launching, recovering, and storing unmanned aircraft may be applicable as well to other self-propelled and/or projectile airborne devices.

3

In particular embodiments, aspects of the invention can enable and improve handling of unmanned aircraft from retrieval to launch. They address the problem of vulnerability to damage during manual handling and storage, retrieval, and launch aboard ship or in a similarly confined space, and efficient operation of multiple aircraft. Components of the invention can be used individually or together in a secure and efficient handling cycle. Aspects of the apparatuses and methods can include (1) compact storage; and (2) constrained motion. Accordingly, embodiments of the system can discourage freehanding of the unprotected aircraft, whole or in pieces, and instead can include provisions for dismantling, packing, and assembling the aircraft along prescribed paths, with the storage apparatus and its interfaces with the launch and retrieval apparatus shielding the aircraft from abuse.

The following description includes four sections, each focused on a particular aspect of unmanned aircraft operation. Section 1 focuses on methods and apparatuses for assembling unmanned aircraft, Section 2 focuses on methods and apparatuses for launching unmanned aircraft, Section 3 focuses on methods and apparatuses for retrieving unmanned aircraft, and Section 4 focuses on methods and apparatuses for disassembling and stowing unmanned aircraft. Each of the following Sections describes several embodiments of the corresponding structures and methods that are the focus of that Section. Overall systems in accordance with other embodiments of the invention can include any of a wide variety of combinations and variations of the following embodiments.

### 1. Aircraft Assembly

FIGS. 1A–1H illustrate a method and apparatus for storing and assembling an unmanned aircraft prior to launch, in accordance with an embodiment of the invention. In anticipation of launch, a closed storage container as shown in FIG. 1A can be secured to a launch apparatus as shown in FIG. 1G, thereby establishing a secure workstand for assembly, and a path for constrained motion of the aircraft onto the launcher.

Beginning with FIG. 1A, a stowage system 110 in accordance with one aspect of this embodiment can include a container 111 (shown in phantom lines in FIG. 1A) having one or more movable panels defining a volume in which an unmanned aircraft 140 is stowed. The aircraft 140 can be carried on an aircraft support member, which can include a cradle 116, which is in turn supported by a movable dolly or car 117. The car 117 can be mounted on a rail 118 or another controlled motion system for movement relative to the container 111, as described in greater detail below with reference to FIG. 1G. In one aspect of this embodiment, the cradle 116 can be mounted to the car 117 with a jack 121 to move the aircraft 140 vertically relative to the container 111, as described in greater detail below with reference to FIG. 1B.

The container 111 can have a generally box-like shape and can include a bottom 112 (which supports the rail 118), opposing ends 114 extending upwardly from the bottom 112, and sides 115 positioned between the opposing ends 114. A removable top 113 can seal the aircraft 140 within the container 111. In one embodiment, the aircraft 140 can include a fuselage 141, an aft-mounted propeller 148, and a wing stub 142. Wings 143 can be stowed against the sides 115 of the container 111 and can be attached to the wing stub 142 as described in greater detail below with reference to FIGS. 1B–1E. In other embodiments, the aircraft 140 can have other configurations when stowed.

4

Referring now to FIG. 1B, the jack 121 can be activated to elevate the aircraft 140 relative to the container 111. For example, in one embodiment, the aircraft 140 can be elevated at least until the wing stub 142 is positioned above the upper edges of the container sides 115. With the wing stub 142 in this position, the wings 143 can be aligned for attachment to the aircraft 140. Each wing 143 can have a wing gripper 119 attached to it. As described in greater detail below, the wing grippers 119 can eliminate the need for the operator (not shown in FIGS. 1A–1H) to have direct manual contact with the wings 143 during wing assembly.

Referring now to FIG. 1C, a section 122 of one of the container sides 115 can be pivoted outwardly from the container 111 and slid aft, parallel to a longitudinal axis L of the aircraft 140. This motion can position a corresponding one of the wings 143 proximate to the wing stub 142. In one aspect of this embodiment, the degrees to which the section 122 pivots outwardly and slides longitudinally are controlled by stops (not visible in FIG. 1C) positioned in the bottom 112 of the container 111. Accordingly, the stops can orient the wing 143 for attachment to the wing stub 142 with precision. The overall motion of the section 122 relative to the container 111 is constrained by a guide structure (e.g., a pin of the section 122 received in a slot of the container). Accordingly, the section 122 moves along a constrained, section guide path.

Referring now to FIG. 1D, the wing 143 can be rotated upwardly (as indicated by arrow R) until forward and aft spars 144 of the wing 143 are aligned with corresponding spar receptacles 145 in the wing stub 142. In one aspect of this embodiment, the operator can rotate the wing 143 by engaging only the wing gripper 119, reducing the likelihood for contaminating the wing surfaces with debris and/or damaging the wing surfaces. Once the spars 144 are aligned with the corresponding spar receptacles 145, the operator can slide the wing gripper 119 along a track located on the inner surface of the section 122 of the container 111 to insert the spars 144 into the corresponding spar receptacles 145, as indicated by arrow S. Accordingly, the motion of the wing gripper 119 is constrained to be along a gripper guide path. For purposes of illustration, communication lines (such as electrical cables) which run between the fuselage 141 and the wing 143 are not shown in FIG. 1D. These lines can include sufficient extra length to allow the wing 143 to be moved toward and away from the fuselage 141 during assembly and disassembly, and take-up devices such as reels or spring-loaded loops to adjust the lines appropriately.

Referring now to FIG. 1E, the operator can lock the wing 143 relative to the wing stub 142 by removing a hatch 147 from the wing stub 142 and inserting wing retainers (not visible in FIG. 1E) which lock the spars 144 in firm engagement with the wing stub 142. The process described above with reference to FIGS. 1B–1E can then be repeated for the other wing 143 to fully assemble the aircraft 140 in preparation for launch. While the aircraft 140 is carried on the cradle 116, it can be serviced. For example, the aircraft 140 can be fueled and/or electrically powered prior to flight, de-fueled and/or powered down after flight, and can receive/transmit data before and/or after flight.

FIG. 1F shows the container 111 with the fully assembled aircraft 140 positioned in preparation for a controlled transfer of the aircraft 140 onto a launch system 125. In one embodiment, the forward end 114 of the container 111 can then be removed or pivoted out of the way to allow the aircraft 140 to slide onto the launch system 125, as described below with reference to FIG. 1G.

In one embodiment (shown in FIG. 1G), an operator or motorized device can slide the car 117, the cradle 116, and the aircraft 140 (as a unit) relative to the rail 118 to position the aircraft 140 on the launch system 125. In other embodiments, the container 111 can include other arrangements for moving the aircraft 140 into position for launch via the launch system 125. In any of these embodiments, the aircraft 140 can be moved from the container 111 to the launch system 125 without unconstrained motion or manual handling of the aircraft 140. For example, an operator can move the car 117 by grasping or engaging the cradle 116 or the car 117 rather than the aircraft 140. In another embodiment, all of the motions made after securing the storage container to the launch apparatus can be fully automated.

As shown in FIG. 1H, the launch system 125 can include a launch carriage 126 which is moved into position to receive the aircraft 140 from the cradle 116. The launch carriage 126 can releasably support the wings 143 (as shown in FIG. 1H) or the fuselage 141, or other portions of the aircraft 140 during launch. In any of these embodiments, once the aircraft 140 is supported by the launch carriage 126, the operator can retract the cradle 116 downwardly by activating the jack 121. The operator can then slide the car 117, with the retracted cradle 116, back along the rail 118 into the container 111. The container 111 can then be moved away from the launch system 125 so as not to interfere with the propeller 148 or any other portion of the aircraft 140.

## 2. Aircraft Launch

FIG. 2 is a partially schematic, rear isometric illustration of an apparatus 100 that includes the aircraft 140 positioned on an aircraft handling system 103. The aircraft handling system 103 can include an embodiment of the launch system 125 (described briefly above) configured to launch the aircraft 140, and a recovery system 150 configured to recover the same aircraft 140 at the end of its flight.

In one aspect of an embodiment shown in FIG. 2, the launch system 125 can include a launch support member 128 that carries a launch track 130 having two launch rails 129. The launch system 125 can further include a launch carriage 126, such as that described above with reference to FIG. 1H. In one embodiment, the launch carriage 126 can include two independent components, each of which supports one of the wings 143 and each of which travels along one of the launch rails 129. In other embodiments, the launch carriage 126 can include a generally unitary structure that supports both wings 143 and travels along both launch rails 129. In still further embodiments, the launch carriage 126 can support other portions of the aircraft 140, such as the fuselage 141. In yet another embodiment, only one launch rail can support the launch carriage 126. In any of these embodiments, the carriage 126 can be propelled along the launch track 130 to launch the aircraft 140, as described below with reference to FIGS. 4A–6F.

In another aspect of an embodiment of the apparatus shown in FIG. 2, the recovery system 150 can be integrated with the launch system 125 to reduce the overall volume occupied by these two systems. For example, in one particular embodiment, the recovery system 150 can include an extendable (and retractable) boom 151 having a plurality of nested segments 152. An operator can extend the nested segments 152 along a launch axis K defined by the launch track 130 to retrieve the aircraft 140 after its flight. Further details of embodiments of the extendable boom 151 and its operation are described below with reference to FIGS. 11A–11G.

FIG. 3A is a partially schematic, side elevational view of a portion of the apparatus 100 described above with reference to FIG. 2, illustrating an energy reservoir 135 that provides power to and receives power from the launch carriage 126. Accordingly, the energy reservoir 135 can accelerate the launch carriage 126 to launch the aircraft 140 and then absorb the kinetic energy of the launch carriage 126 to slow it down. In one aspect of this embodiment, the energy reservoir 135 can include a hydraulic cylinder, a spring, a pneumatic cylinder, an electric motor, a flywheel, a steam-powered apparatus, an explosive charge, and/or a weight (as described below with respect to FIGS. 4A–4C). In another aspect of this embodiment, the energy reservoir 135 is coupled to the launch carriage 126 with a transmission 131. In a further aspect of this embodiment, the transmission 131 can include a cable 133, a plurality of fixed pulleys 132 (shown as first, second, and third fixed pulleys 132a–c, respectively) and a plurality of traveling pulleys 134 (shown as first and second traveling pulleys 134a–b, respectively) arranged in a block and tackle configuration. When the energy reservoir 135 moves the traveling pulleys 134 aft (as indicated by arrow P), the carriage 126 and the aircraft 140 accelerate and move forward (as indicated by arrow Q). In one aspect of this embodiment, the energy reservoir 135 can be configured to provide a relatively high force with a relatively low acceleration over a relatively short distance, and the transmission 131 can provide to the carriage 126 a relatively smaller force with a relatively higher acceleration over a relatively longer distance. For example, in one aspect of an embodiment shown in FIG. 3A, the acceleration at the carriage 126 can be about four times the acceleration of the traveling pulleys 134. In other embodiments, the apparatus 100 can include other block and tackle configurations or other transmissions 131 that provide the same or different acceleration levels to the carriage 126. In any of these embodiments, the energy reservoir 135 and the transmission 131 can be tailored to the aerodynamic characteristics of the aircraft 140 to provide the aircraft 140 with an adequate takeoff velocity.

FIG. 3B schematically illustrates the apparatus 100 with the energy reservoir 135 activated to move the carriage 126 from a position aft of the fixed pulleys 132 to a position forward of the fixed pulleys 132. As the carriage 126 passes the first fixed pulley 132a and the cable 133 begins to engage the second fixed pulley 132b, the carriage 126 rapidly decelerates. At the same time, the aircraft 140 continues forward to lift off the carriage 126 and become airborne.

As the carriage 126 passes the first fixed pulley 132a, it also begins to exert a force on the energy reservoir 135 via the cable 133. One effect of this coupling between the carriage 126 and the energy reservoir 135 is that the carriage 126 rapidly decelerates. Accordingly, the apparatus 100 need not accommodate a long post-launch travel distance for the carriage 126. As a result, the apparatus 100 can be more compact than some existing launch/recovery devices. Another effect is that the energy associated with decelerating the carriage 126 can be reversibly absorbed by the energy reservoir 135. Accordingly, the energy reservoir 135 can be returned partially to its pre-launch state and can accordingly be closer to a state of readiness for the next launch.

FIGS. 4A–4C schematically illustrate a particular embodiment of the apparatus 100 for which the energy reservoir 135 includes a weight 436. Prior to launch, the weight 436 is positioned as shown in FIG. 4A so that it has an available potential energy determined by a height H. The weight is then released, accelerating the aircraft 140, as indicated by arrow Q. The acceleration provided by the

falling weight **436** is completed when the weight **436** reaches its lower limit. Just before the weight **436** reaches its lower limit, the cable **133** passes from the first fixed pulley **132a** to the second fixed pulley **132b**, as shown in FIG. 4B, which reverses the accelerating force on the carriage **126**. The carriage **126** immediately begins to decelerate, as shown in FIG. 4C, releasing the aircraft **140** into flight. As the carriage **126** continues for some distance beyond the second fixed pulley **132b**, it raises the weight **436** by some fraction of the height *H*. Prior to a subsequent launch operation, the weight **436** can be raised completely to the height *H*, and the carriage **126** can be moved to the position shown in FIG. 4A for another launch.

One feature of embodiments of the apparatus **100** described above with reference to FIGS. 3A–4C is that the energy provided by the energy reservoir **135** can accelerate the aircraft **140** at a rapid rate. Accordingly, the aircraft **140** can be accelerated to its lift-off speed without requiring a lengthy takeoff run. An advantage of this feature is that the apparatus **100** can be compact and suitable for operation in cramped quarters.

Another feature of an embodiment of the apparatus described above with reference to FIGS. 3A–4C is that the energy reservoir **135** can be configured to absorb energy from the carriage **126** after the carriage **126** has released the aircraft **140**. In some cases, as described above, the energy reservoir **135** can reversibly regain a portion of the energy required to conduct a subsequent launch. An advantage of this feature is that the time and energy required to ready the apparatus **100** for a subsequent launch can be reduced. A further advantage of this arrangement is that the apparatus **100** does not require a braking device separate from the energy reservoir **135**.

FIGS. 5A–6F illustrate launch systems configured in accordance with further embodiments of the invention. Beginning with FIG. 5A, a launch system **525** in accordance with one embodiment of the invention can include a base **530** carrying two or more supports **529** (shown in FIG. 5A as a first support **529a** and a second support **529b**). The base **530** can be configured to incline relative to the ground (for example, with a jack **539**) to orient the aircraft **140** for launch. The base **530** can be mounted to a vehicle, including a trailer or a boat, or to a fixed platform, including a building.

The launch system **525** can further include a first member **527** (e.g., a first launch member **527**) and a second member **528** (e.g., a second launch member **528**), both of which support a carriage **526**, which in turn carries the aircraft **140** via a releasable gripper **520**. At least one of the first member **527** and the second member **528** is movable relative to the other. For example, in one embodiment, the first member **527** can be fixed relative to the base **530**, and the second member **528** can be movable relative to the base **530**. In other embodiments, the first and second members **527**, **528** can have different arrangements. In any of these embodiments, the movement of at least one of the first and second members **527**, **528** can accelerate the carriage **526** to launch the aircraft **140**, as described in greater detail below.

In one embodiment, the second member **528** can translate and/or rotate relative to the first member **527**. In a particular aspect of this embodiment, the motion of the second member **528** relative to the first member **527** can be controlled by a pin **532**, which depends from the second member **528** and which is received in an elongated guide slot **531** of the support **529b**. The motion of the second member **528** can be further controlled by a block and tackle **533**. In one embodiment, the block and tackle **533** can include a coupling line

**535** attached to the second member **528** at a first line attachment point **536a**. The coupling line **535** passes through a series of pulleys **534a–534e** to a second attachment point **536b**, also on the second member **528**. In other embodiments, the second member **528** can be supported relative to the first member **527** in other arrangements.

In any of the embodiments described above, the carriage **526** can engage both the first member **527** and the second member **528**. For example, in one embodiment, the first member **527** can include a first roller surface **537** (which engages first wheels **524a** of the carriage **526**), and the second member **528** can include a second roller surface **538** (which engages second wheels **524b** of the carriage **526**). Carriage arms or links **523** can support the second wheels **524b** relative to the first wheels **524a**.

In one embodiment, the second roller surface **538** can have a curved profile to control the acceleration of the carriage **526**. In other embodiments, the second roller surface **538** can have other shapes. In any of these embodiments, the carriage **526** can travel (from left to right as shown in FIG. 5A) along the first roller surface **537** while engaging the second surface roller surface **538**. In a particular aspect of this embodiment, the second roller surface **538** can be inclined relative to the first roller surface **537** and can move in a wedge fashion, so as to force the carriage **526** from left to right to launch the aircraft **140**.

In one embodiment, the force required to move the second member **528** relative to the first member **527** can be provided by an actuator **510**. The actuator can be coupled with an actuator line **511** to the second member **528**, after passing around an actuator pulley **512**. In one aspect of this embodiment, the actuator **510** can include a compressed gas cylinder, having a piston that retracts the actuator line **511** to draw the second member **528** downwardly away from the first member **527**, as described in greater detail below with reference to FIG. 5B. In other embodiments, the actuator **510** can have other arrangements, such as a hydraulic cylinder, a bungee, or a spring. In any of these embodiments, the actuator **510** can move the second member **528** relative to the first member **527**, forcing movement of the carriage **526** from left to right.

The launch system **525** can include a carriage return crank or winch **522** having a carriage return line **521** with a releasable trigger **522a** connected to the carriage **526**. The launch carriage **526** is held back in a pre-launch position by the carriage return line **521** while a launch force is applied to the launch carriage **526**. The releasable trigger **522a** is then disengaged, allowing the launch carriage **526** to accelerate. The carriage return line **521** can be used to reset the carriage **526** after launch, as described in greater detail below with reference to FIG. 5B.

FIG. 5B illustrates the launch system **525** after the carriage **526** has been accelerated to launch the aircraft **140**. In one aspect of this embodiment, the actuator **510** has rapidly drawn the second member **528** downwardly in a manner controlled by the block and tackle **533** and the pin **532** positioned in the slot **531**. As the second member **528** moves downwardly relative to the first member **527**, the carriage **526** is forced from left to right at a high rate of speed, until the second wheels **524b** engage a braking portion **519** of the second roller surface **538**. Accordingly, the angle between the second roller surface **538** and the first roller surface **537** changes at the braking portion **519**. At this point, the carriage **526** rapidly decelerates, while the gripper **520** releases, allowing the aircraft **140** to continue forward as it is launched into flight.



Once the actuator 510 has moved the second member 528, it can be effectively decoupled while an operator couples the carriage return line 521 to the launch carriage and activates the carriage return crank 522 to return the carriage 526 to the position shown in FIG. 5A. For example, when the actuator 510 includes a gas powered piston, the volume of the cylinder in which the piston moves can be opened to atmospheric pressure so that the operator does not need to compress the air within the cylinder when returning the carriage 526 to the launch position. Once the carriage 526 has been returned to the position shown in FIG. 5A, the actuator 510 can be readied for the next launch, for example, by charging the cylinder in which the piston operates with a compressed gas. In other embodiments, the energy of deceleration can be used to reversibly regain energy to be used during the next launch. In still further embodiments, the actuator 510 can be recharged by the carriage return crank 522. As the carriage return crank 522 is actuated, it can force the second member 528 to its original position as the carriage 526 returns. This movement can also force the piston on the actuator 510 to its starting position and restore gas pressure in the actuator 510.

FIG. 5C is a partially schematic illustration of a portion of the launch system 525 illustrating the first member 527, along with the second member 528 (shown in its pre-launch configuration in solid lines and in its post-launch configuration in dashed lines). As shown in FIG. 5C, the portion of the second member 528 to which the coupling line 535 is attached can move by distance 3X, which is three times the distance X moved by the right most portion of the second member 528. The wedge angle between the first member 527 and the second member 528 increases by translating and pivoting the second member 528 relative to the first member 527. By increasing the wedge angle during the launch process, the carriage 526 is accelerated at a constant or nearly constant rate, even as the force from the actuator decreases near the end of the actuator's power stroke.

FIG. 5D is a graph illustrating predicted acceleration and velocity values for a carriage 526 propelled by a launch system 525 in accordance with an embodiment of the invention. In one aspect of this embodiment, the launch system 525 can provide a generally constant acceleration to the carriage 526, which instantaneously reverses (when the carriage 526 reaches the braking portion 519 described above). This acceleration profile can provide a generally uniform increase in velocity, as is also shown in FIG. 5D, up to at least the take-off velocity of the aircraft 140. In other embodiments, the carriage 526 can be propelled in manners that result in different acceleration and velocity profiles.

FIG. 5E is a partially schematic illustration of a launch system 525a configured in accordance with another embodiment of the invention and having many characteristics in common with the launch system 525 described above with reference to FIGS. 5A–5C. In one aspect of this embodiment, the launch system 525a includes a first link 518a and a second link 518b coupled between the first member 527 and the second member 528, in lieu of the block and tackle 533 and pin 532 arrangement described above. The motion of the second member 528 relative to the first member 527 can be generally similar to that described above with reference to FIGS. 5A and 5B, to provide acceleration and velocity profiles generally similar to those described above with reference to FIG. 5D.

FIGS. 6A–6B illustrate a launch system 625 configured in accordance with still another embodiment of the invention. In one aspect of this embodiment, the launch system 625 can include a first member 627 coupled to a second member 628

at a pivot point 633. An actuator 610 can be coupled to the first member 627 and the second member 628 with actuator rods 611 to force the first and second members 627, 628 apart from each other in a transverse plane. A carriage 626 can carry the aircraft 140 and can engage a first roller surface 637 of the first member 627 with first wheels 624a. The carriage 626 can also engage a second roller surface 638 of the second member 628 with second wheels 624b.

Referring now to FIG. 6B, the actuator 610 can be activated to spread the first member 627 and the second member 628 apart from each other, forcing the carriage 626 from left to right. When the carriage 626 reaches braking portions 619 of the first and second members 627, 628, it rapidly decelerates, causing a gripper 620 to open (as indicated by arrows Y) while the aircraft 140 continues forward and is launched into flight. In other embodiments, the launch system 625 can have other arrangements.

One feature of embodiments of the launch systems described above with reference to FIG. 5A–6B is that the “wedge action” of the first and second members relative to each other can rapidly accelerate the carriage (and therefore the aircraft 140) in a relatively short distance. An advantage of this arrangement is that the launch systems can be used in cramped quarters, including the deck of a fishing vessel or a towed trailer.

Another feature of embodiments of the launch systems described above is that the wedge angle between the first and second members can increase as they move relative to one another. This arrangement can provide a constant or nearly constant acceleration to the carriage (and the aircraft 140), even if the force provided by the actuator decreases near the end of the actuator's power stroke. An advantage of this arrangement is that the aircraft 140 is less likely to be subject to sudden changes in acceleration, which can damage the aircraft 140.

Yet another feature of the launch systems described above with reference to FIGS. 5A–6B is that at least one of the first and second members can include a braking portion which rapidly and safely decelerates the carriage carried by the launch system. An advantage of this feature is that the rail length required for deceleration can be short relative to that for acceleration, and the overall length of the system can be correspondingly limited. Further details of the manner in which the carriage releases the aircraft are described below with reference to FIGS. 6C–6F.

Another feature of the launch systems described above with reference to FIGS. 5A–6B is that the number of components that move at high speed during the launch process is relatively small. For example, in a particular embodiment, the only rolling elements that are traveling at high speed are the carriage wheels, and no high speed pulleys are included. Accordingly, the potential losses associated with components moving at high speed, including losses caused by ropes attached to the carriage suddenly accelerating and decelerating (e.g., “rope slurping”) can be reduced and/or eliminated.

FIGS. 6C–6F illustrate an arrangement for supporting the aircraft 140 during launch, suitable for use with any of the launch systems described above. In one embodiment, shown in FIG. 6C, the arrangement can include a carriage 626 having a gripper 620 which includes two gripper arms 618. Each gripper arm 618 can include a forward contact portion 617a and an aft contact portion 617b configured to releasably engage the fuselage 141 of the aircraft 140.

FIG. 6D is a front end view of the carriage 626 and the aircraft 140. As shown in FIG. 6D, each contact portion 617a can have a curved shape so as to conform to the curved

## 11

shape of the fuselage **141**. Each gripper arm **618** can be pivotably coupled to the carriage **626** to rotate about a pivot axis P. In one aspect of this embodiment, each pivot axis P is canted outwardly away from the vertical by an angle Z. As described in greater detail below, this arrangement can prevent interference between the gripper arms **618** and the aircraft **140** as the aircraft **140** is launched. In another aspect of this embodiment, the gripper arms **618** can pivot to a slightly over-center position to securely engage the fuselage **141** and to resist ambient wind loads, gravity, propeller thrust (e.g., the maximum thrust provided to the aircraft **140**), and other external transitory loads.

FIG. 6E is a top plan view of the carriage **626** as it reaches the end of its launch stroke. As the carriage **626** decelerates, the forward momentum of the gripper arms **618** causes them to fling open by pivoting around the pivot axes P, as indicated by arrows M, which can overcome the over-center action described above. As the gripper arms **618** begin to open, the contact portions **617a**, **617b** begin to disengage from the aircraft **140**.

Referring now to FIG. 6F, the carriage **626** has come to a stop and the gripper arms **618** have pivoted entirely away from the aircraft **140**, allowing the aircraft **140** to become airborne. As shown in FIG. 6F, the gripper arms **618** have pivoted in a manner so as not to interfere with the fuselage **141**, the wings **143** or the propeller **148** of the aircraft **140**. For example, as described above, the gripper arms **618** pivot about a canted pivot axis P. As a result, the gripper arms **618** can rotate downwardly (as well as outwardly) away from the aircraft **140** as the aircraft **140** takes flight.

One feature of an embodiment of the carriage **626** described above with reference to FIGS. 6C–6F is that the gripper arms **618** can engage the fuselage **141** of the aircraft **140**. An advantage of this arrangement is that the gripping action provided by the gripper arms **618** can be distributed fore and aft over the fuselage **141**, thus distributing the gripping load. A further advantage of embodiments of the foregoing arrangement is that the gripper arms **618** can be configured to quickly and completely rotate out of the way of the aircraft **140** as the aircraft **140** takes flight. Still a further advantage of the foregoing arrangement is that no additional hardware, with associated weight and drag, need be provided to the aircraft **140** to allow it to be releasably carried by the carriage **626**.

FIG. 6G illustrates a launch system **625a** configured in accordance with still another embodiment of the invention. In one aspect of this embodiment, the launch system **625a** can include a launch support member **128**. A carriage **126** can carry the aircraft **140** along the launch support member **128** for takeoff. The force required to move the carriage **126** relative to the launch support member **128** can be provided by one or more constant force springs **690** (six are shown in FIG. 6G as springs **690a–690f**). The springs **690** can be operatively coupled to the carriage **126** to force movement of the carriage **126** from left to right. In the illustrated embodiment, the springs **690a–690f** are arranged in parallel. The number of springs **690** required to provide the necessary launch force can be adjusted based on specific operating conditions (e.g., the size of the aircraft **140**, the length of the launch support member **128**, and the local atmospheric conditions). Suitable constant force springs are available from Vulcan Spring and Mfg. Company of Telford, Pa. The launch system **625a** can further include a carriage return crank or winch **522** (FIG. 5A) which can operate as described above to return the carriage from a post-launch position to a pre-launch position.

## 12

In one aspect of this embodiment, the springs **690** provide a constant force to the launch carriage **126**. One advantage of using one or more constant force springs is that the resulting launch distance is reduced. Furthermore, when using a constant force spring, the acceleration of the launch carriage can be constant or nearly constant during launch, which can reduce the stresses applied to the aircraft **140**. Another advantage of this arrangement is that the peak force on the launch system can be reduced by providing a constant force, which can in turn reduce the amount of structure (and therefore weight) required by the launch system.

In other embodiments, the apparatus can be configured to rapidly launch a plurality of the aircraft **140**. For example, as shown in FIG. 7A, an apparatus **700a** configured in accordance with an embodiment of the invention can include multiple containers **111** positioned proximate to a launch system **125**. In one aspect of this embodiment, the containers **111** can be positioned in one or more container groups **720** (shown in FIG. 7A as a vertical container group **720a**, a horizontal container group **720b**, and a diagonal container group **720c**). In one embodiment, a single type of container group (e.g., a vertical container group **720a**) can be positioned adjacent to a single launch system **125**. In other embodiments, multiple container groups of different types can be positioned adjacent to a single launch system **125**. In any of these embodiments, the containers **111** within each container group **720** can be easily accessible to operators preparing the aircraft **140** within the containers **111** for launch. Furthermore, the containers can be mechanically fed to the launcher, and assembly and positioning for launch then completed automatically as previously discussed. Accordingly, multiple aircraft **140** can be rapidly launched from a single launch system **125**. An advantage of this arrangement is that in some circumstances, the targets toward which the aircraft **140** are launched extend over a wide territorial range, and/or change rapidly enough that a single aircraft **140** is unable to provide suitable coverage. By rapidly launching multiple aircraft **140**, widely dispersed targets that change rapidly with time can more easily be surveilled or otherwise engaged.

In other embodiments, multiple launchers can be employed in combination with multiple containers to quickly deploy a plurality of the aircraft **140**. For example, referring now to FIG. 7B, an apparatus **700b** can include multiple aircraft handling systems **703b** arranged vertically, and multiple container groups **720b**, also arranged vertically. Each container group **720b** can have horizontally grouped containers **111**. In another arrangement shown in FIG. 7C, an apparatus **700c** can include horizontally spaced-apart aircraft handling systems **703c**, each supplied with aircraft **140** from containers **111** positioned in vertically stacked container groups **720a**.

In any of the embodiments described above with reference to FIGS. 7A–7C, the aircraft handling systems can be supplied with containers **111** via gravity feed systems, mechanical rollers, slides, or other mechanisms. In a further aspect of these embodiments, each container group can also be mobile, for example, by placing stacks or rows of containers **111** on independently wheeled carriages, or on rails, skids, bearings, or floats. Accordingly, in still another aspect of these embodiments, the aircraft handling systems (in addition to the container groups) can also be mobile, for example, by positioning the aircraft handling systems on independently wheeled carriages, rails, skids, bearings or floats. As described above, an advantage of any of these embodiments is that multiple aircraft **140** can be deployed in rapid succession.

## 3. Vehicle Capture

FIGS. 8A–10F illustrate apparatuses and methods for capturing unmanned aircraft (including the aircraft 140 described above) in accordance with several embodiments of the invention. Beginning with FIG. 8A, the aircraft 140 can be captured by an aircraft handling system 803 positioned on a support platform 801. In one embodiment, the support platform 801 can include a boat 802 or other water vessel. In other embodiments, the support platform 801 can include other structures, including a building, a truck or other land vehicle, or an airborne vehicle, such as a balloon. In many of these embodiments, the aircraft handling system 803 can be configured solely to retrieve the aircraft 140 or, as described above with reference to FIG. 2, it can be configured to both launch and retrieve the aircraft 140.

Referring now to FIG. 8B, the aircraft handling system 803 can include a recovery system 850 integrated with a launch system 825. In one aspect of this embodiment, the recovery system 850 can include an extendable boom 851 having a plurality of segments 852. The boom 851 can be mounted on a rotatable base 856 or turret for ease of positioning. The segments 852 are initially stowed in a nested or telescoping arrangement (generally similar to that described above with reference to FIG. 2) and are then deployed to extend outwardly as shown in FIG. 8B. In other embodiments, the extendable boom 851 can have other arrangements, such as a scissors arrangement, a parallel linkage arrangement or a knuckle boom arrangement. In any of these embodiments, the extendable boom 851 can include a recovery line 853 extended by gravity or other forces. In one embodiment, the recovery line 853 can include 0.25 inch diameter polyester rope, and in other embodiments, the recovery line 853 can include other materials and/or can have other dimensions. In any of these embodiments, a spring or weight 854 at the end of the recovery line 853 can provide tension in the recovery line 853. The aircraft handling system 803 can also include a retrieval line 855 connected to the weight 854 to aid in retrieving and controlling the motion of the weight 854 after the aircraft recovery operation has been completed. In another embodiment, a recovery line 853a can be suspended from one portion of the boom 851 and attachable to another point on the boom 851, in lieu of the recovery line 853 and the weight 854.

In one aspect of this embodiment, the end of the extendable boom 851 can be positioned at an elevation E above the local surface (e.g., the water shown in FIG. 8B), and a distance D away from the nearest vertical structure projecting from the local surface. In one aspect of this embodiment, the elevation E can be about 15 meters and the distance D can be about 10 meters. In other embodiments, E and D can have other values, depending upon the particular installation. For example, in one particular embodiment, the elevation E can be about 17 meters when the boom 851 is extended, and about 4 meters when the boom 851 is retracted. The distance D can be about 8 meters when the boom 851 is extended, and about 4 meters when the boom 851 is retracted. In a further particular aspect of this embodiment, the boom 851 can be configured to carry both a vertical load and a lateral load via the recovery line. For example, in one embodiment, the boom 851 can be configured to capture an aircraft 140 having a weight of about 30 pounds, and can be configured to withstand a side load of about 400 pounds, corresponding to the force of the impact between the aircraft 140 and the recovery line 853 with appropriate factors of safety.

In any of the foregoing embodiments, the aircraft 140 is captured when it flies into the recovery line 853. Once captured, the aircraft 140 is suspended from the recovery line by the wing 143. Further details of apparatuses and methods for capturing the aircraft 140 are described below with reference to FIGS. 9A–10D.

FIG. 9A is a partially schematic, isometric illustration of an outboard portion of the wing 143 and the winglet 146 of the aircraft 140 shown in FIG. 8B. In one aspect of this embodiment, the wing 143 includes a leading edge 949 (which can be swept), an outboard edge 939, and a line capture device 960 positioned at the outboard edge 939. In other embodiments, each wing 143 can include a plurality of line capture devices 960 located along the span of the wing 143. In any of these embodiments, the line capture device 960 can include a cleat 961 fixedly attached to the wing 143 that engages the recovery line 853 to releasably and securely attach the aircraft 140 to the recovery line 853. The cleat 961 can include a cleat body 962, a cleat slot 963 positioned in the cleat body 962, and a gate or retainer 964 attached to the cleat body 962. As the aircraft 140 flies toward the recovery line 853 (as indicated by arrow A), the recovery line 853 strikes the wing leading edge 949 and causes the aircraft to yaw toward the recovery line 853, which then slides outboard along the leading edge 949 toward the line capture device 960 (as indicated by arrow B). The recovery line 853 then passes into the cleat slot 963 and is retained in the cleat slot 963 by the retainer 964, as described in greater detail below with reference to FIGS. 9B–9C. In other embodiments, the retainer 964 can be eliminated and the recovery line 853 can still be securely pinched in the cleat slot 963.

If the aircraft 140 is not properly aligned with the recovery line 853 during its approach, the recovery line 853 may strike the line capture device 960 instead of the leading edge 949. In one embodiment, the cleat body 962 includes a cleat leading edge 969 which is swept aft so as to deflect the recovery line 853 away from the aircraft 140. This can prevent fouling of the line 853 and can reduce the yawing moment imparted to the aircraft 140, allowing the aircraft 140 to recover from the missed capture and to return for another capture attempt.

FIG. 9B is an enlarged, isometric illustration of a portion of the wing 143 and the line capture device 960 described above with reference to FIG. 9A. As described above with reference to FIG. 9A, the recovery line 853 travels outboard along the wing leading edge 949 to position the recovery line 853 at the cleat slot 963 of the line capture device 960. In one aspect of this embodiment, the retainer 964 of the cleat 961 includes two or more closure arms 965 (two are shown in FIG. 9B as a first closure arm 965a and a second closure arm 965b) that extend over the cleat slot 963. The retainer 964 is pivotally mounted to the cleat body 962 at a pivot joint 968, and is forced toward a closed position (shown in FIG. 9B) by a spring 967. As the recovery line 853 strikes the first closure arm 965a from outside the cleat slot 963, the force on the first closure arm 965a forces the retainer 964 to rotate about the pivot joint 968 (as indicated by arrow C) to an open position, allowing the recovery line 853 to move into the cleat slot 963. The recovery line 853 continues through the cleat slot 963, allowing the retainer 964 to begin closing as it passes the first closure arm 965a. The recovery line 853 then strikes the second closure arm 965b to force the retainer 964 back open again, and then travels further in the slot 963. In one aspect of this embodiment, the slot 963 (which can be tapered) has a width that is less than a diameter of the recovery line 853. Accordingly, the recovery line 853 can be pinched in the slot 963 as the recovery line 853 travels

15

outboard and aft, securing the aircraft 140 to the recovery line 853. The momentum of the aircraft 140 relative to the recovery line 853 provides the impetus to securely engage the recovery line 853 with the line capture device 960.

As described above, the retainer 964 can include a first closure arm 965a and a second closure arm 965b. One advantage of a retainer 964 having a first closure arm 965a and a second closure arm 965b is that, if the relative velocity between the recovery line 853 and the aircraft 140 is insufficient to cause the recovery line 853 to travel to the end of the cleat slot 963, the retainer 964 can close around the recovery line 853, with the recovery line 853 positioned between the first closure arm 965a, and the second closure arm 965b. Accordingly, this arrangement can arrest and secure the aircraft 140 even though the recovery line 853 has a relatively low outboard and aft velocity component relative to the capture device 960.

Another advantage of the foregoing features, as shown in FIG. 9C is that, as the aircraft 140 is captured on the recovery line 853, the recovery line 853 may twist so as to form a looping portion 953. The retainer 964 can prevent the recovery line 853 from passing out of the cleat slot 963, even if the recovery line 853 experiences forces inboard and forward relative to the capture device 960. The recovery line 853, secured in the cleat slot 963, also serves to resist further opening of the retainer 964. Furthermore, without the closure arms 965, tension on the end of a loop 953 could pull the recovery line 853 free of the cleat slot 963. The closure arms 965 can prevent this by admitting only one diameter of the recovery line 853.

FIG. 9D is a partially schematic, isometric illustration of a portion of a wing 143 of the aircraft 140 with a line capture device 960d positioned at the outboard edge 939 of the wing 143 in accordance with another embodiment of the invention. In one aspect of this embodiment, the line capture device 960d includes a cleat body 962 and a retainer 964d having two cleat arms 965c, 965d that pivot independently relative to the cleat slot 963. Each cleat arm 965c, 965d is pivotally mounted to the cleat body 962 at a corresponding pivot joint 968c, 968d, and is forced toward a closed position by a corresponding spring 967c, 967d. The individual cleat arms 965c, 965d can provide generally the same function as the cleat arms 965a, 965b described above with respect to FIGS. 9B–9C, e.g., to consistently and securely capture the recovery line 853.

FIGS. 10A–10D illustrate a method and apparatus for further securing the aircraft 140 after it is attached to the recovery line 853. Referring first to FIG. 10A, an aircraft handling system 1003 in accordance with an embodiment of the invention can include a hoist device 1080 coupled to the recovery line 853. The recovery line 853 can pass over a series of pulleys 956, shown in FIG. 10A as a first pulley 956a, a second pulley 956b and a third pulley 956c. The recovery line 853 can also pass through a restraining device 1070 operatively coupled to the extendable boom 1051.

The hoist device 1080 can include a spring 1085 or other forcing mechanism (including a weight, a hydraulic or pneumatic actuator, or an electric motor) coupled to the recovery line 853 in a deployable or triggerable manner that allows the spring 1085 to take up the recovery line 853. The hoist device 1080 can also include a damper (not shown in FIG. 10A) to smooth out the action of the spring 1085. In one aspect of this embodiment, the hoist device 1080 can include a release mechanism 1081 configured to activate the spring 1085. In a further aspect of this embodiment, the release mechanism 1081 can include a release link 1082 coupled to the recovery line 853. The release link 1082 can

16

include a trigger 1083 received in a corresponding trigger receptacle 1084. The trigger receptacle 1084 is positioned at an interface between the spring 1085 and the recovery line 853. Before the aircraft 140 strikes the recovery line 853, the trigger 1083 can be engaged with the trigger receptacle 1084, so that the spring 1085 does not act on the recovery line 853.

Referring now to FIG. 10B, as the aircraft 140 strikes and engages with the recovery line 853, it imparts a vertical force on the release link 1082 (as indicated by arrow C), causing the trigger 1083 to pull out of the trigger receptacle 1084, as indicated by arrow D. Accordingly, in this embodiment, the trigger 1083 is activated when a threshold extension or travel of the recovery line 853 is exceeded. In other embodiments, the trigger 1083 can be activated by other mechanisms, for example, when a threshold tension in the recovery line 853 is exceeded.

Referring next to FIG. 10C, once the trigger 1083 has been released from the trigger receptacle 1084, the spring 1085 begins to exert a force (indicated by arrow F) on the recovery line 853. Concurrently, the aircraft 140 may be swinging from side to side as it is suspended from the recovery line 853, thus exerting a centrifugal force on the recovery line 853. The force F exerted by the spring 1085 on the recovery line 853 compensates for the weight of the aircraft 140 hanging on the recovery line 853 and the centrifugal force caused by the aircraft swinging on the line after capture. As shown in FIG. 10D, the spring 1085 can draw the recovery line 853 around the pulleys 956 to reduce the line length between the first pulley 956a and the aircraft 140. As the spring 1085 acts, it hoists the aircraft 140 up toward the restraining device 1070 at the end of the extendable boom 1051. The spring 1085 can be sized so as not to exert so much force on the recovery line 853 that the aircraft 140 strikes the restraining device 1070 with excessive force and damages the aircraft 140.

The restraining device 1070 is configured to releasably engage a portion of the aircraft 140, thus stabilizing the aircraft 140 after it is hoisted up by the recovery line 853 to the extendable boom 1051. In one embodiment, the restraining device 1070 can include a piece of pipe operatively connected to the end of the boom 1051. In other embodiments, the restraining device 1070 can include both active and passive devices to engage and restrain at least a portion of the aircraft 140, including an innertube apparatus configured to surround at least a portion of the aircraft 140, a plurality of cushions configured to “sandwich” the aircraft 140, or an umbrella which softly closes around the aircraft 140. In other embodiments, the restraining device can have other arrangements, or the restraining device may be omitted.

If, after the aircraft 140 is caught and substantially decelerated, it is allowed to swing freely on the recovery line 853 (in response to wind or motion of the boom 1051) then it may be damaged by collision with structures in the swing space including (when the boom 1051 is carried by a ship) the ship’s mast and deck. The vulnerability of the aircraft 140 to damage can be much reduced by hoisting the recovery line 853 such that the line capture device 960 (FIGS. 9A–9B) or nearby surfaces of the aircraft 140 are pulled firmly against the restraining device 1070 or a stiff object attached to the boom 1051. The aircraft’s freedom to swing is thereby much reduced. Firm contact between the aircraft 140 and the boom 1051 can be maintained as the aircraft 140 is lowered, for example, by articulation of the boom 1051 or by translation on a trolley. When sufficiently close to the

deck, the aircraft **140** can be securely removed from the recovery line **853** and stowed.

FIGS. **10E–10F** are schematic illustrations of apparatuses for providing tension in the recovery line **853** before, during, and after aircraft capture. Referring first to FIG. **10E**, the recovery line **853** can pass over a series of pulleys **1056**, shown as a first pulley **1056a** and a second pulley **1056b**. In another aspect of this embodiment, the recovery line **853** can be operatively coupled to a first axially resilient member **1086** and a second axially resilient member **1087**. The first and second axially resilient members **1086**, **1087** can provide tension in the recovery line **853** before the aircraft (not shown) intercepts the recovery line at a location between the first pulley **1056a** and the second pulley **1056b**. In one embodiment, the axially resilient members **1086**, **1087** can include a spring or other forcing mechanism (including a weight, a hydraulic or pneumatic actuator, or an electric motor) coupled to the recovery line **853**. In another aspect of this embodiment, a damper **1089** can be operatively coupled to the recovery line **853** in parallel or in series with at least one of the axially resilient members **1086**, **1087** to smooth out the action of the axially resilient members **1086**, **1087**. In another embodiment, the axially resilient members **1086**, **1087** can be omitted and the recovery line **853** can be operatively coupled to only the damper **1089**. In this embodiment, the damper **1089** provides only a drag force on the recovery line **853**.

Referring next to FIG. **10F**, in another embodiment, the recovery line **853** can be operatively coupled to a weight **854** and an axially resilient member **1086** to provide tension in the line. In one embodiment, the axially resilient member **1086** can include a constant force spring similar to the constant force spring **690** described above with respect to FIG. **6G**.

An advantage of the foregoing arrangements is that the aircraft **140** can be less likely to swing about in an uncontrolled manner (e.g., when acted on by the wind) during subsequent portions of the recovery operation. Accordingly, the aircraft **140** will be less likely to become damaged by inadvertent contact with the ground, water, or the support platform from which the aircraft handling system **1003** extends. The aircraft will also be less likely to damage surrounding structures. In other embodiments, the boom **1051** can also be elevated as or after the recovery line **853** is taken up, to keep the aircraft **140** clear of surrounding structures.

#### 4. Vehicle Disassembly and Stowage

FIGS. **11A–11G** illustrate a method for removing the aircraft **140** from the recovery line **853** and further securing and disassembling the aircraft **140**. FIG. **11A** is an isometric view of the aircraft **140** suspended from the extendable boom **1051**, which is in turn carried by the boat **802** or other support platform. As shown in FIG. **11A**, the motion of the aircraft **140** has been arrested and the aircraft **140** has been hoisted to the end of the boom **1051**. Referring now to FIG. **11B**, the boom **1051** can be retracted (as indicated by arrow **G**), by nesting the segments **1052** of the boom **1051**. The aircraft **140** is accordingly brought closer to the boat **802** or other support platform while its motion is constrained (e.g., by the restraining device **1070**). For purposes of illustration, the portion of the recovery line **853** below the aircraft **140** is not shown in FIGS. **11B–11E**.

Referring next to FIG. **11C**, the boom **1051** can then be swiveled (as indicated by arrow **J**) to align one of the wings **143** of the aircraft **140** with a securement hook **1190** positioned on a deck **1104** of the boat **802**. In one aspect of

this embodiment, the securement hook **1190** can engage the line capture device **960** at the end of the wing **143**, and in other embodiments, the securement hook **1190** can engage other portions of the aircraft **140**. In any of these embodiments, the securement hook **1190** can be positioned proximate to a bracket **1191** that includes a cradle **116** connected to a container bottom **112**. As described in greater detail below with reference to FIGS. **11D–G**, the bracket **1191** can be movable to position the cradle **116** proximate to the aircraft **140** in preparation for stowage.

FIG. **11D** is an aft isometric view of the aircraft **140** releasably suspended between the retracted boom **1051** and the securement hook **1190** in accordance with an embodiment of the invention. The bracket **1191** can be mounted to the deck **1104** such that the cradle **116** is positioned properly for receiving the fuselage **141** of the aircraft **140**. In one aspect of this embodiment, the aircraft **140** can be engaged with the cradle **116** by lowering the boom **1051** until the fuselage **141** rests in the cradle **116**. In another embodiment, the bracket **1191** can be pivotably coupled to the deck **1104** at a pair of pivot joints **1192**. Accordingly (referring now to FIG. **11E**), the bracket **1191** (with the container floor **112** and the cradle **116** attached) can be rotated upwardly as indicated by arrow **K** to engage the cradle **116** with the fuselage **141**. An operator can then secure clamps **1193** around the fuselage **141** to firmly and releasably attach the aircraft **140** to the cradle **116**.

Referring now to FIG. **11F**, the operator can detach the two wings **143** from the extendable boom **1051** and the securement hook **1190**, respectively. The wings **143** can then be detached from the aircraft **140**. In a further aspect of this embodiment, the removed wings **143** can be stowed on the container floor **112** adjacent to the fuselage **141** of the aircraft **140**.

Referring now to FIG. **11G**, the bracket **1191** can be rotated downwardly as indicated by arrow **I** until the container bottom **112** rests on the deck **1104**. The aircraft **140** (not visible in FIG. **11G**) can then be completely enclosed by adding ends **114**, sides **115**, and a top **113** to the container bottom **112**, forming a protective sealed container **111** around the aircraft **140**.

In another embodiment, illustrated schematically in FIGS. **12A–12E**, the aircraft **140** can be disassembled and stowed in a manner that is generally the reverse of the method described above with reference to FIGS. **1A–1E**. Accordingly, (referring first to FIG. **12A**), the aircraft **140** can be attached to the cradle **116**, with the container **111** fully assembled except for the container top **113** (not shown in FIG. **12A**). The wing retainers (which connect the wings **143** to the wing stub **142**) can be accessed for removal by opening the hatch **147** positioned in the wing stub **142**. As shown in FIG. **12B**, an operator can detach the wing **143** from the wing stub **142** by translating and rotating the container section **122** to engage the gripper **119** with the wing **143**. The operator can then slide the gripper **119** along a track on the inner surface of the container section **122** to withdraw the spars **144** from the spar receptacles **145**, and to fully release the wing **143** from the rest of the aircraft **140**. The wing **143** can then be folded downwardly against the inner surface of the container section **122**, as shown in FIG. **12C**, and the container section **122** can be pivoted back into position as shown in FIG. **12D**. The foregoing steps can be repeated for the other wing **143** to complete the disassembly of the aircraft **140**. In one aspect of this embodiment, the wings **143** can be offset longitudinally from each other when stowed so that the stowed winglets **146** (if long enough) do not interfere with each other within the container **111**.

Referring now to FIG. 12E, the cradle 116 can be lowered into the container 111 and the top 113 placed on the container 111 to complete the stowage operation.

The above-described process can be fully automated following the initial attachment of the aircraft 140 to the cradle 116 by the addition of actuators. Referring to FIG. 12B, in an exemplary embodiment an actuator 1202 (shown schematically) can move the container section 122 relative to the rest of the container 111. Actuator 1204 (shown schematically) can move the gripper 119 relative to the container section 122. Further actuators (not shown) can move other portions of the container 111 and/or aircraft 140. This process can operate in reverse order to fully automate the aircraft assembly process, as described above with respect to FIGS. 1A–1E.

One feature of embodiments of the apparatuses and methods described above for securing and stowing the aircraft 140 is that at least one portion of the container can move relative to the aircraft for disassembly of at least portions of the aircraft. This can limit the amount of unstrained or freehand handling that an operator must undertake when stowing the aircraft 140. An advantage of this feature is that the likelihood for inadvertently damaging the aircraft 140 as it is being secured and stowed can be reduced when compared with existing manual techniques for securing and stowing such aircraft. Another advantage of this feature is that the potential risk to people and nearby objects can be reduced. A system in accordance with an embodiment of the invention can provide for a secure and efficient cycle from flight through retrieval, dismantling, storing, servicing, assembly, checkout, launch, and back to flight and can include (a) a storage and assembly apparatus (such as a container); (b) means for supporting the storage and assembly apparatus at a station positioned for retrieval of the aircraft; (c) means for attaching the assembled aircraft to the storage and assembly apparatus; (d) means for controllably dismantling the aircraft and storing dismantled components of the aircraft within the storage and assembly apparatus; (e) means for servicing the aircraft within the container, including for example, means for transferring fuel and electrical power to the aircraft, and data to and/or from the aircraft; (f) means for supporting the storage and assembly apparatus at least proximate to a launch apparatus; (g) means for controlled assembly of the aircraft; and (h) means for controlled transfer of the aircraft to the launch apparatus such that the aircraft is available for launching.

In other embodiments, the systems and methods described above with reference to FIGS. 1A–12E can be used in conjunction with aircraft having configurations different than those described above. For example, in one embodiment shown in FIG. 13A, an aircraft 140a can include generally unswept wings 143a. In another embodiment shown in FIG. 13B, an aircraft 140b can include forward swept wings 143b. Line capture devices on the wings 143b can be installed toward the wing roots. In still another embodiment shown in FIG. 13C, an aircraft 140c can include delta wings 143c.

In still further embodiments, the aircraft can have propulsion systems that are different than, and/or are arranged differently than, those described above with reference to FIGS. 1A–12E. For example, as shown in FIG. 13D, an aircraft 140d can include a nose-mounted propeller 148d. In an embodiment shown in FIG. 13E, an aircraft 140e can include twin propellers 148e, each mounted to one of the wings 143. In still another embodiment shown in FIG. 13F, an aircraft 140f can include jet engines 1348 mounted to the wings 143. In still further embodiments, the aircraft can

have other configurations, while remaining compatible with some or all of the systems and methods described above for storing, launching, and capturing the aircraft.

From the foregoing, it will be appreciated that specific embodiments of the invention have been described herein for purposes of illustration, but that various modifications may be made without deviating from the spirit and scope of the invention. For example, the systems described above can be used to store, launch and recover aircraft having arrangements different than those described above. In other embodiments, these systems can handle projectiles or other airborne devices. Further details of related systems and methods are described in the following co-pending U.S. Applications, filed concurrently herewith and incorporated herein by reference: U.S. application Ser. No. 10/758,943, entitled “Methods and Apparatuses for Capturing and Storing Unmanned Aircraft, Including Methods and Apparatuses for Securing the Aircraft After Capture”; U.S. application Ser. No. 10/758,948, entitled “Methods and Apparatuses for Launching Unmanned Aircraft, Including Methods and Apparatuses for Transmitting Forces to the Aircraft During Launch”; U.S. application Ser. No. 10/758,956, entitled “Methods and Apparatuses for Capturing and Recovering Unmanned Aircraft, Including Extendable Capture Devices”; U.S. application Ser. No. 10/759,742, entitled “Methods and Apparatuses for Launching and Capturing Unmanned Aircraft, Including a Combined Launch and Recovery System”; U.S. application Ser. No. 10/759,545, entitled “Methods and Apparatuses for Capturing Unmanned Aircraft and Constraining Motion of the Captured Aircraft”; U.S. application Ser. No. 10/758,940, entitled “Methods and Apparatuses for Capturing and Recovering Unmanned Aircraft, Including a Cleat for Capturing Aircraft on a Line”; U.S. application Ser. No. 10/760,150, entitled “Methods and Apparatuses for Launching Unmanned Aircraft, Including Methods and Apparatuses for Launching Aircraft with a Wedge Action”; and U.S. application Ser. No. 10/758,955, entitled “Methods and Apparatuses for Launching Unmanned Aircraft, Including Methods and Apparatuses for Releasably Gripping Aircraft During Launch”. Accordingly, the invention is not limited except as by the appended claims.

I claim:

1. A method for handling an unmanned aircraft, comprising:
  - releasably securing a portion of an unmanned aircraft to a storage apparatus;
  - removing a lifting surface of the aircraft using a movable portion of the storage apparatus; and
  - at least partially enclosing the aircraft in the storage apparatus.
2. The method of claim 1 wherein releasably securing a portion of the aircraft to the storage apparatus includes pivoting the storage apparatus to contact and releasably engage a fuselage of the aircraft.
3. The method of claim 1 wherein the storage apparatus is pivotally mounted to a support platform, and wherein releasably securing the aircraft to the storage apparatus includes pivoting the storage apparatus from the support platform to contact a fuselage of the aircraft.
4. The method of claim 1 wherein releasably securing a portion of the aircraft to the storage apparatus includes pivoting the storage apparatus from a first position to a second position, the storage apparatus being oriented to contact and releasably receive the aircraft when in the second position.

## 21

5. The method of claim 1 wherein releasably securing a portion of the aircraft to the storage apparatus includes releasably securing a portion of a fuselage of the aircraft to a cradle movably carried by a storage apparatus.

6. The method of claim 1 wherein releasably securing a portion of the aircraft to the storage apparatus includes releasably securing a portion of the aircraft to a storage container.

7. The method of claim 1, further comprising translating and rotating the movable portion of the storage apparatus relative to the lifting surface of the aircraft to align a gripper carried by the movable portion for contact with the lifting surface of the aircraft.

8. The method of claim 1, further comprising:

slidably moving and pivoting a gripper carried by the movable portion of the storage apparatus for contact with the lifting surface of the aircraft; and pivoting the gripper toward the movable portion after removing the lifting surface of the aircraft.

9. The method of claim 1 wherein removing the lifting surface of the aircraft includes:

releasably attaching the lifting surface to the movable portion of the storage apparatus; and moving the movable portion and the lifting surface along a constrained guide path of the storage apparatus.

10. The method of claim 1 wherein removing the lifting surface of the aircraft includes:

contacting and releasably engaging the lifting surface with a gripper carried by the movable portion of the storage apparatus, the gripper being positioned to slidably move along a guide path of the movable portion; and

detaching the lifting surface from the aircraft by slidably moving the gripper along the guide path from a first position with the lifting surface attached to the aircraft to a second position with the lifting surface detached from the aircraft.

11. The method of claim 1 wherein removing the lifting surface of the aircraft includes:

translating and rotating the movable portion of the storage apparatus relative to the lifting surface of the aircraft to align a gripper carried by the movable portion with the lifting surface;

contacting and releasably engaging the gripper with the lifting surface; and

detaching the lifting surface from the aircraft by slidably moving the gripper along a guide path of the movable portion from a first position with the lifting surface attached to the aircraft to a second position with the lifting surface detached from the aircraft.

12. The method of claim 1, further comprising servicing the aircraft after releasably securing the aircraft to the storage apparatus.

13. A method for handling an unmanned aircraft, comprising:

deploying a flexible recovery line from an extendable boom mounted at least proximate to a support platform; releasably capturing a first lifting surface portion of the aircraft in flight with the flexible recovery line;

while the first lifting surface portion of the aircraft is releasably coupled to the flexible recovery line, securing a second lifting surface portion of the aircraft to the support platform;

releasably securing at least a portion of a fuselage of the aircraft to a storage container;

releasing the aircraft from the flexible recovery line and the support platform;

## 22

removing at least one of the lifting surfaces of the aircraft using a movable portion of the storage container; and at least partially enclosing the aircraft in the storage container.

14. The method of claim 13 wherein the aircraft includes a capture device mounted to the lifting surface, and wherein releasably capturing the aircraft in flight includes releasably capturing a portion of the recovery line with the capture device.

15. The method of claim 13, further comprising retracting at least a portion of the extendable boom after releasably capturing the aircraft and before releasably securing the second lifting surface portion of the aircraft to the support platform.

16. The method of claim 13 wherein at least a portion of the storage container is pivotally mounted to the support platform, and wherein releasably securing the aircraft to the storage container includes pivoting at least a portion of the storage container from the support platform to contact a fuselage of the aircraft.

17. The method of claim 13 wherein releasably securing a portion of the aircraft to the storage container includes pivoting at least a portion of the storage container from a first position to a second position, the portion of the storage container being oriented to contact and releasably receive the aircraft when in the second position.

18. The method of claim 13 wherein releasably securing at least a portion of the fuselage of the aircraft to the storage container includes releasably securing a portion of the fuselage of the aircraft to a cradle movably carried by a storage container.

19. The method of claim 13, further comprising translating and rotating the movable portion of the storage container relative to at least one lifting surface of the aircraft to align a gripper carried by the movable portion for contact with the lifting surface of the aircraft.

20. The method of claim 13, further comprising:

slidably moving and pivoting a gripper carried by the movable portion of the storage container for contact with the lifting surface of the aircraft; and pivoting the gripper toward the movable portion after removing the lifting surface of the aircraft.

21. The method of claim 13 wherein removing at least one lifting surface of the aircraft includes:

releasably attaching the at least one lifting surface to the movable portion of the storage container; and moving the movable portion and the at least one lifting surface along a constrained guide path of the storage container.

22. The method of claim 13 wherein removing the at least one lifting surface of the aircraft includes:

translating and rotating the movable portion of the storage container relative to the at least one lifting surface of the aircraft to align a gripper carried by the movable portion with the at least one lifting surface;

contacting and releasably engaging the gripper with the at least one lifting surface; and

detaching the at least one lifting surface from the aircraft by slidably moving the gripper along a guide path of the movable portion from a first position with the at least one lifting surface attached to the aircraft to a second position with the at least one lifting surface detached from the aircraft.

23. The method of claim 13, further comprising directing an actuator to move the movable portion of the storage container after releasably securing the aircraft to the storage apparatus.

23

24. The method of claim 13, further comprising servicing the aircraft after releasably securing the aircraft to the storage apparatus.

25. A method for handling an unmanned aircraft, comprising:

removing at least a portion of a storage apparatus at least partially enclosing an unmanned aircraft to provide access to the aircraft;

attaching a lifting surface to the aircraft using a movable portion of the storage apparatus; and

moving the aircraft from the storage apparatus into position for takeoff.

26. The method of claim 25, further comprising moving the fuselage from a first position within the storage apparatus to a second position elevated from the first position before attaching the lifting surface to the aircraft.

27. The method of claim 25 wherein moving a movable portion of a storage apparatus includes moving a movable portion of a storage container.

28. The method of claim 25, further comprising translating and rotating the movable portion of the storage apparatus relative to the lifting surface of the aircraft to align the lifting surface with the aircraft.

29. The method of claim 25 wherein attaching the lifting surface to the aircraft includes:

releasably attaching the lifting surface to the movable portion of the storage apparatus; and

moving the movable portion and the lifting surface along a constrained guide path of the storage apparatus.

30. The method of claim 25 wherein attaching the lifting surface to the aircraft includes:

24

contacting and releasably engaging the lifting surface with a gripper carried by the movable portion of the storage apparatus, the gripper being positioned to slidably move along a guide path of the movable portion; and

attaching the lifting surface to the aircraft by slidably moving the gripper along the guide path from a first position with the lifting surface detached from the aircraft to a second position with the lifting surface attached to the aircraft.

31. The method of claim 25 wherein moving the aircraft into position for takeoff includes moving the aircraft from a cradle movably carried by the storage apparatus to a launch carriage movably carried by a launch guide structure.

32. The method of claim 25, further comprising slidably moving and pivoting a gripper carried by the movable portion of the storage apparatus for contact with the lifting surface of the aircraft, and wherein the gripper is pivoted against the movable portion after removing the lifting surface of the aircraft.

33. The method of claim 25, further comprising directing an actuator to move the movable portion of the storage apparatus.

34. The method of claim 25, further comprising servicing the aircraft after providing access to the aircraft and before moving the assembled aircraft into position for takeoff.

\* \* \* \* \*