



(12) **United States Patent**
McGeer et al.

(10) **Patent No.:** **US 7,165,745 B2**
(45) **Date of Patent:** **Jan. 23, 2007**

(54) **METHODS AND APPARATUSES FOR LAUNCHING UNMANNED AIRCRAFT, INCLUDING RELEASABLY GRIPPING AIRCRAFT DURING LAUNCH AND BRAKING SUBSEQUENT GRIP MOTION**

975,953 A 11/1910 Hourwich
1,144,505 A 6/1915 Steffan
1,164,967 A 12/1915 Thorp
1,317,631 A 9/1919 Kinser
1,383,595 A 7/1921 Black
1,384,036 A 7/1921 Anderson
1,428,163 A 9/1922 Harriss

(75) Inventors: **Brian T. McGeer**, Underwood, WA (US); **Andreas H. von Flotow**, Hood River, OR (US); **Cory Roeseler**, Hood River, OR (US)

(Continued)

(73) Assignee: **The Insitu Group, Inc.**, Bingen, WA (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 75 days.

DE 4301671 A1 7/1993

(Continued)

(21) Appl. No.: **10/808,725**

OTHER PUBLICATIONS

(22) Filed: **Mar. 24, 2004**

U.S. Appl. No. 10/758,940, Dennis.

(65) **Prior Publication Data**

US 2005/0178895 A1 Aug. 18, 2005

(Continued)

Related U.S. Application Data

Primary Examiner—Timothy D. Collins
(74) *Attorney, Agent, or Firm*—Perkins Coie LLP

(63) Continuation-in-part of application No. 10/758,955, filed on Jan. 16, 2004.

(60) Provisional application No. 60/554,824, filed on Mar. 19, 2004, provisional application No. 60/440,727, filed on Jan. 17, 2003.

(57) **ABSTRACT**

Methods and apparatuses for launching unmanned aircraft and other flight devices or projectiles are described. In one embodiment, the aircraft can be launched from an apparatus that includes a launch carriage that moves along a launch guide. The carriage can accelerate when portions of the carriage and/or the launch guide move relative to each other. A gripper carried by the launch carriage can have at least one grip portion in contact with the aircraft while the launch carriage accelerates along the launch axis. The at least one grip portion can move out of contact with the aircraft as the launch carriage decelerates, releasing the aircraft for takeoff. A brake can arrest the motion of the gripper after launch.

(51) **Int. Cl.**

B64F 1/06 (2006.01)

(52) **U.S. Cl.** **244/63; 244/114 R**

(58) **Field of Classification Search** **244/63, 244/114 R; 89/1.8–1.82; 446/63–65**


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

965,881 A 8/1910 Draper
968,339 A 8/1910 Geraldson

13 Claims, 9 Drawing Sheets



U.S. PATENT DOCUMENTS

1,499,472	A	7/1924	Hazen	4,279,195	A	7/1981	Miller
1,530,010	A	3/1925	Neilson	4,311,290	A	1/1982	Koper
1,556,348	A	10/1925	Ray et al.	4,408,737	A	10/1983	Schwaerzler
1,624,188	A	4/1927	Simon	4,471,923	A	9/1984	Hoppner et al.
1,634,964	A	7/1927	Steinmetz	4,523,729	A	6/1985	Frick
1,680,473	A	8/1928	Parker	4,566,658	A	1/1986	DiGiovanniantonio et al.
1,686,298	A	10/1928	Uhl	4,678,143	A	7/1987	Griffin
1,712,164	A	5/1929	Peppin	4,730,793	A	3/1988	Thurber, Jr. et al.
1,716,670	A	6/1929	Sperry	4,753,400	A	6/1988	Reuter et al.
1,731,091	A	10/1929	Belleville	4,809,933	A	3/1989	Buzby et al.
1,737,483	A	11/1929	Verret	4,842,222	A	6/1989	Baird
1,738,261	A	12/1929	Perkins	4,909,458	A	3/1990	Martin
1,748,663	A	2/1930	Tucker	4,979,701	A	12/1990	Colarik et al.
1,756,747	A	4/1930	Holland	5,007,875	A	4/1991	Dasa
1,777,167	A	9/1930	Forbes	5,039,034	A	8/1991	Burgess et al.
1,836,010	A	12/1931	Audrain	5,042,750	A	8/1991	Winter
1,842,432	A	1/1932	Stanton	5,054,717	A	10/1991	Taylor
1,869,506	A	8/1932	Richardson	5,109,788	A	5/1992	Heinzmann
1,892,357	A	12/1932	Moe	5,119,935	A	6/1992	Stump et al.
1,912,723	A	6/1933	Perkins	5,253,605	A	10/1993	Collins
1,925,212	A	9/1933	Steiber	5,253,606	A	10/1993	Ortelli
1,940,030	A	12/1933	Steiber	5,509,624	A	4/1996	Takahashi
1,960,264	A	5/1934	Heinkel	5,583,311	A	12/1996	Rieger
2,333,559	A	11/1943	Grady et al.	5,655,944	A	8/1997	Fusselman
2,347,561	A	4/1944	Howard et al.	5,687,930	A	11/1997	Wagner et al.
2,360,220	A	10/1944	Goldman	5,906,336	A	5/1999	Eckstein
2,364,527	A	12/1944	Haygood	6,264,140	B1	7/2001	McGeer et al.
2,365,778	A	12/1944	Schwab	6,457,673	B1	10/2002	Miller
2,365,827	A	12/1944	Liebert	6,478,650	B1	11/2002	Tsai
2,380,702	A	7/1945	Persons	2002/0100838	A1	8/2002	McGeer et al.
2,390,754	A	12/1945	Valdene	2003/0222173	A1	12/2003	McGeer et al.
2,435,197	A	2/1948	Brodie	2005/0133665	A1	6/2005	Dennis et al.
2,436,240	A	2/1948	Wiertz				
2,448,209	A	8/1948	Boyer et al.				
2,465,936	A	3/1949	Schultz				
2,488,050	A	11/1949	Brodie				
2,515,205	A	7/1950	Fieux				
2,526,348	A	10/1950	Gouge				
2,669,403	A	2/1954	Milligan				
2,735,391	A	2/1956	Buschers				
2,814,453	A	11/1957	Trimble et al.				
2,843,342	A	7/1958	Ward				
2,844,340	A	7/1958	Daniels et al.				
2,908,240	A	10/1959	Hodge				
2,919,871	A	1/1960	Sorensen				
2,933,183	A	4/1960	Koetsch				
3,069,118	A	12/1962	Bernard				
RE25,406	E	6/1963	Byrne et al.				
3,163,380	A	12/1964	Brodie				
3,268,090	A	8/1966	Wirkkala				
3,454,244	A	7/1969	Walander				
3,468,500	A	9/1969	Carlsson				
3,484,061	A	12/1969	Niemkiewicz				
3,516,616	A	6/1970	Strance et al.				
3,684,219	A	8/1972	King				
3,708,200	A	1/1973	Richards				
3,765,625	A	10/1973	Myhr et al.				
3,827,660	A	8/1974	Doolittle				
3,939,988	A	2/1976	Wellman				
3,943,657	A	3/1976	Leckie				
3,980,259	A	9/1976	Greenhalgh et al.				
4,067,139	A	1/1978	Pinkerton et al.				
4,079,901	A	3/1978	Mayhew et al.				
4,143,840	A	3/1979	Bernard et al.				
4,147,317	A	4/1979	Mayhew et al.				
D256,816	S	9/1980	McMahon et al.				
4,236,686	A	12/1980	Barthelme et al.				
4,238,093	A	12/1980	Siegel et al.				

FOREIGN PATENT DOCUMENTS

FR	854371	4/1940
GB	2 080 216 A	2/1982
GB	2 150 895 A	7/1985
GB	2150895 A *	7/1985
GB	2 219 777 A	12/1989
JP	07-304498	11/1995
WO	WO 00/75014 A1	12/2000
WO	WO 01/07318 A1	2/2001

OTHER PUBLICATIONS

U.S. Appl. No. 10/758,943, Dennis et al.
 U.S. Appl. No. 10/758,948, Dennis et al.
 U.S. Appl. No. 10/758,955, McGeer et al.
 U.S. Appl. No. 10/758,956, Dennis et al.
 U.S. Appl. No. 10/759,541, McGeer.
 U.S. Appl. No. 10/759,545, Dennis et al.
 U.S. Appl. No. 10/759,742, Dennis.
 U.S. Appl. No. 10/760,150, Roeseler et al.
 U.S. Appl. No. 10/813,906, Roeseler.
 Robinson, Russell Norman, "Dynamic Analysis of a Carousel Remotely Piloted Vehicle Recovery System," master's thesis, Naval Post-Graduate School, Monterey, California, Dec. 1977, Thesis No. ADA52401.
 Dickard, H. E. "Mini-RPV Recovery System Conceptual Study," final report, U.S. Army Air Mobility Research and Development Laboratory, Fort Eustis, Virginia, Aug. 1977, Contract DAAJ02-76-C-0048, Report No. USAAMRDL-TR-77-24.
 Whitmore, Stephen A. et al., "Development of a Closed-Loop Strap Down Attitude System for an Ultrahigh Altitude Flight Experiment," technical memorandum, NASA Dryden Flight Research Center, Edwards, California, Jan. 1997, Report No. NASA TM-4775.
 "Ames Builds Advanced Yawed-Wing RPV," Aviation Week and Space Technology, Jan. 22, 1973, p. 73.

* cited by examiner




Fig. 1A




Fig. 1B




Fig. 1C




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7A




Fig. 7B




Fig. 7C




Fig. 7D




Fig. 7E




Fig. 8A




Fig. 8B

1

**METHODS AND APPARATUSES FOR
LAUNCHING UNMANNED AIRCRAFT,
INCLUDING RELEASABLY GRIPPING
AIRCRAFT DURING LAUNCH AND
BRAKING SUBSEQUENT GRIP MOTION**

CROSS-REFERENCE TO RELATED
APPLICATIONS

The present application is a continuation-in-part of U.S. application Ser. No. 10/758,955, entitled "Methods and Apparatuses for Launching Unmanned Aircraft, Including Methods and Apparatuses for Releasably Gripping Aircraft During Launch," filed Jan. 16, 2004 and incorporated herein in its entirety by reference, and which claims priority to U.S. Provisional Application Ser. No. 60/440,727, entitled "Methods and Apparatuses for Launching Unmanned Aircraft, Including Methods and Apparatuses for Releasably Gripping Aircraft During Launch," filed Jan. 17, 2003. This application also claims priority to pending U.S. Provisional Application No. 60/554,824, entitled "Methods and Systems for Accelerating Aircraft for Launch," filed Mar. 19, 2004 and incorporated herein in its entirety by reference.

TECHNICAL FIELD

The present disclosure describes methods and apparatuses for launching unmanned aircraft, including methods and apparatuses for releasably gripping aircraft during launch and braking subsequent grip motion.

BACKGROUND

Unmanned aircraft or air vehicles (UAVs) provide enhanced and economical access to areas where manned flight operations are unacceptably costly and/or dangerous. For example, unmanned aircraft outfitted with remotely controlled cameras can perform a wide variety of surveillance missions, including spotting schools of fish for the fisheries industry, monitoring weather conditions, providing border patrols for national governments, and providing military surveillance before, during and/or after military operations.

Existing unmanned aircraft systems suffer from a variety of drawbacks. For example, existing unmanned aircraft systems (which can include the aircraft itself along with launch devices, recovery devices, and storage devices) typically require substantial space. Accordingly, these systems can be difficult to install and operate in cramped quarters, such as the deck of a small fishing boat, land vehicle, or other craft. Another drawback with some existing unmanned aircraft is that, due to small size and low weight, they can be subjected to higher acceleration and deceleration forces than are larger, manned air vehicles, and can accordingly be prone to damage. Still another drawback with existing launch devices is that they may not absorb the energy associated with a launch in a manner that effectively prevents or limits loads placed on the launch device and/or the aircraft, exposing the launch device and the aircraft to damage.

SUMMARY

The present invention is directed generally toward methods and apparatuses for launching unmanned aircraft. An apparatus in accordance with one aspect of the invention includes a support, a launch carriage movably carried by the

2

support, and a gripper movably coupled to the launch carriage. The gripper can include at least one grip portion positioned to releasably engage an unmanned aircraft. The gripper can be movable relative to the launch carriage between a first position with the at least one grip portion positioned to contact the aircraft, and a second position with the at least one grip portion positioned to be out of contact with the aircraft. A brake can be positioned at least proximate to the gripper and can be changeable from a first configuration in which the brake inhibits motion of the gripper by a first amount, and a second configuration in which the brake does not inhibit motion of the gripper, or inhibits motion of the gripper by a second amount less than the first amount. Accordingly, the brake can control the motion of the gripper after the aircraft has been released.

An apparatus in accordance with another aspect of the invention includes a first launch member, a second launch member positioned at least proximate to the first launch member, and a launch carriage having support positioned to releasably carry an unmanned aircraft during a takeoff operation. The launch carriage can include a first portion in contact with the first launch member and a second portion in contact with the second launch member. The launch carriage can be movable relative to the launch members between a first launch carriage location and a second launch carriage location as at least one of the first and second launch members moves relative to the other, or at least one of the carriage portions moves relative to the other, or both.

A method in accordance with a further aspect of the invention includes releasably supporting an unmanned aircraft with a launch carriage, releasably engaging the aircraft with a gripper carried by the launch carriage and accelerating the launch carriage along a launch axis. The method can further include disengaging the gripper from the aircraft by moving the gripper relative to the launch carriage from a first position to a second position, releasing the aircraft from the launch carriage for flight, and at least restricting motion of the gripper relative to the launch carriage after disengaging the gripper.

A method in accordance with another aspect of the invention includes releasably supporting an unmanned aircraft with a launch carriage that is movably carried by and in contact with a first launch member and a second launch member. The launch carriage can be accelerated from a first launch carriage location to a second launch carriage location by moving at least one of the first and second launch members relative to the other while the launch members contact the launch carriage, or by moving at least one portion of the launch carriage relative to the other while the launch members contact the launch carriage, or both. The method can further include releasing the unmanned aircraft from the launch carriage for flight.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A–1C illustrate an arrangement for launching an unmanned aircraft in accordance with an embodiment of the invention.

FIG. 2 illustrates an embodiment of the arrangement shown in FIGS. 1A–1C after having been reset for a subsequent launch.

FIGS. 3 and 4 illustrate systems for launching an aircraft with a carriage that carries both the aircraft and an actuator.

FIG. 5 illustrates a predicted carriage acceleration associated with an embodiment of the invention.

FIG. 6 is a partially cut-away illustration of a gripper and gripper brake for releasably supporting an aircraft during launch.

FIGS. 7A–7E are partially schematic illustrations of an apparatus having at least one movable launch member for launching an unmanned aircraft in accordance with another embodiment of the invention.

FIGS. 8A–8B are partially schematic illustrations of an apparatus having a movable launch member for launching an unmanned aircraft in accordance with another embodiment of the invention.

DETAILED DESCRIPTION

The following disclosure describes systems and methods for launching aircraft, for example, unmanned aerial vehicles (UAVs). Certain specific details are set forth in the following description and in FIGS. 1A–8B to provide a thorough understanding of various embodiments of the invention. Well-known structures, systems and methods often associated with aircraft launch systems have not been shown or described in detail below to avoid unnecessarily obscuring the description of the various embodiments of the invention. In addition, those of ordinary skill in the relevant art will understand that additional embodiments of the present invention may be practiced without several of the details described below.

FIG. 1A illustrates a launch system 110 having a launch guide 140 and a carriage 120 that together accelerate and guide an aircraft 150 along an initial flight path 111 at the outset of a flight. The launch guide 140 can include a support structure 141 carrying a first or upper launch member 142 (e.g., a track) and a second or lower launch member 143, both of which are generally aligned with the initial flight path 111. The support structure 141 can be mounted to a vehicle (e.g., a trailer or a boat) or to a fixed platform (e.g., a building). Portions of the first launch member 142 and the second launch member 143 can be non-parallel to each other (e.g., they can converge in a direction aligned with the initial flight path 111) to accelerate the carriage 120, as described below.

The carriage 120 can include a gripper 180 having a pair of gripper arms 181 that releasably carry the aircraft 150. The carriage 120 can also include a first or upper portion 122 and a second or lower portion 123, each of which has rollers 121 (shown in hidden lines in FIG. 1A). The rollers 121 can guide the carriage 120 along the launch members 142, 143 while the carriage portions 122, 123 are driven toward each other. Accordingly, normal forces applied to the rollers 121 can drive the rollers 121 against the launch members 142, 143, drive the carriage portions 122, 123 together, and drive the carriage 120 forward, thereby accelerating the aircraft 150 to flight speed.

An actuator 113 can be linked to the carriage 120 to provide the squeezing force that drives the carriage portions 122, 123 toward each other and drives the carriage 120 along the launch guide 140. Many actuators 113 that are configured to release energy fast enough to launch the aircraft 150 also have a spring-like behavior. Accordingly, the actuators 113 tend to exert large forces at the beginning of a power stroke and smaller forces as the power stroke progresses and the carriage 120 moves along the launch guide 140. An embodiment of the system 110 shown in FIG. 1A can compensate for this spring-like behavior by having a relative angle between the first launch member 142 and the second launch member 143 that becomes progressively steeper in the launch direction. In one example, the force provided by

the actuator 113 can decrease from 6000 lbs to 3000 lbs as the carriage 120 accelerates. Over the same distance, the relative slope between the first launch member 142 and the second launch member 143 can change from 6:1 to 3:1. Accordingly, the resulting thrust imparted to the carriage 120 and the aircraft 150 can remain at least approximately constant.

At or near a launch point L, the carriage 120 reaches the launch speed of the aircraft 150. The first launch member 142 and the second launch member 143 can diverge (instead of converge) forward of the launch point L to form a braking ramp 144. At the braking ramp 144, the carriage 120 rapidly decelerates to release the aircraft 150. The carriage 120 then stops and returns to a rest position at least proximate to or coincident with the launch position L.

In one embodiment, the actuator 113 includes a piston 114 that moves within a cylinder 115. The piston 114 is attached to a flexible, elongated transmission element 116 (e.g., a rope or cable) via a piston rod 117. The transmission element 116 can pass through a series of guide pulleys 145 (carried by the launch guide 140) and carriage pulleys 124 (carried by the carriage 120). The guide pulleys 145 can include first guide pulleys 145a on a first side of the support structure 141, and corresponding second guide pulleys 145b on a second (opposite) side of the support structure 141. The carriage pulleys 124 can also include first carriage pulleys 124a on a first side of the carriage 120 and second pulleys 124b on a second (opposite) side of the carriage 120. One or more equalizing pulleys 146, located in a housing 147 can be positioned between (a) the first guide pulleys 145a and the first carriage pulleys 124a on the first side of the support structure 141, and (b) the second guide pulleys 145b and the second carriage pulleys 124b on the second side of the support structure 141.

In operation, one end of the transmission element 116 can be attached to the first side of the support structure 141, laced through the first pulleys 145a, 124a, around the equalizing pulley(s) 146, and then through the second pulleys 145b, 124b. The opposite end of the transmission element 116 can be attached to the second side of the support structure 141. The equalizing pulley(s) 146 can (a) guide the transmission element 116 from the first side of the support structure 141 to the second side of the support structure 141, and (b) equalize the tension in the transmission element 116 on the first side of the support structure 141 with that on the second side of the support structure 141.

When the transmission element 116 is tensioned, it squeezes the carriage portions 122, 123 together, forcing the carriage 120 along the converging launch members 142, 143. The carriage pulleys 124 and the rollers 121 (which can be coaxial with the carriage pulleys 124) are secured to the carriage 120 so that the carriage 120 rides freely along the initial flight path 111 of the aircraft 150 as the carriage portions 122, 123 move together.

FIG. 1B illustrates the launch of the carriage 120 in accordance with an embodiment of the invention. The carriage 120 is held in place prior to launch by a trigger device 139, e.g., a restraining shackle. When the trigger device 139 is released, the carriage 120 accelerates along the launch members 142, 143, moving from a first launch carriage location to a second launch carriage location (e.g., to the launch point L). At the launch point L, the carriage 120 achieves its maximum velocity and begins to decelerate by rolling along the braking ramp 144. In this embodiment, one or more arresting pulleys 148 can be positioned along the braking ramp 144 to intercept the transmission element 116 and further decelerate the carriage 120.

As shown in FIG. 1C, once the carriage 120 begins to decelerate along the braking ramp 144, the aircraft 150 is released by the gripper arms 181. Each gripper arm 181 can include a forward contact portion 182a and an aft contact portion 182b configured to releasably engage a fuselage 151 of the aircraft 150. Accordingly, each contact portion 182 can have a curved shape so as to conform to the curved shape of the fuselage 151. In other embodiments, the gripper arms 181 can engage different portions of the aircraft 150 (e.g., the wings 152). Each gripper arm 181 can be pivotably coupled to the carriage 120 to rotate about a pivot axis P. The gripper arms 181 can pivot about the pivot axes P to slightly over-center positions when engaged with the aircraft 150. Accordingly, the gripper arms 181 can securely grip the fuselage 151 and resist ambient windloads, gravity, propeller thrust (e.g., the maximum thrust provided to the aircraft 150), and other external transitory loads as the carriage 120 accelerates. In one aspect of this embodiment, each pivot axis P is canted outwardly away from the vertical. As described in greater detail below, this arrangement can prevent interference between the gripper arms 181 and the aircraft 150 as the aircraft 150 is launched.

At least a portion of the mass of the gripper arms 181 can be eccentric relative to the first axis P. As a result, when the carriage 120 decelerates, the forward momentum of the gripper arms 181 causes them to fling open by pivoting about the pivot axis P, as indicated by arrows M. The forward momentum of the gripper arms 181 can accordingly overcome the over-center action described above. As the gripper arms 181 begin to open, the contact portions 182a, 182b begin to disengage from the aircraft 150. In a particular aspect of this embodiment, the gripper arms 181 pivot downwardly and away from the aircraft 150.

An advantage of a gripper arrangement described above with reference to FIG. 1C is that the gripping action provided by the gripper arms 181 can be distributed fore and aft over the fuselage 151, thus distributing the gripping load. A further advantage of embodiments of the foregoing arrangement is that the gripper arms 181 can be configured to quickly and completely rotate out of the way of the aircraft 150 as the aircraft 150 takes flight. Still a further advantage of the foregoing arrangement is that no additional hardware (with associated weight and drag), need be provided to the aircraft 150 to allow it to be releasably carried by the carriage 120. In still further embodiments, the motion of the gripper arms 181 after the aircraft 150 has been released can be controlled, as described in greater detail below with reference to FIG. 6.

After the aircraft 150 is launched, a pull-back winch 149 can be used to cock the launch system 110 (e.g., return the carriage 120 to its launch position) in preparation for the next launch. FIG. 2 illustrates the system 110 in the cocked position. A rope or strap extends from the pull-back winch 149 to the trigger device 139 which engages with the carriage 120. The actuator 113 can then be energized (e.g., by pressurizing the cylinder 115), prior to the next launch.

FIG. 3 illustrates a launch system 110 configured in accordance with another embodiment of the invention. In one aspect of this embodiment, the system 110 includes a carriage 320 having carriage portions 322, 323 coupled to each other with an actuator 313 that is carried by the carriage 320. As the actuator 313 contracts, it draws the two carriage portions 322, 323 toward each other which, because the launch members 142, 143 converge, causes the carriage 320 to roll forward on the rollers 121.

In one aspect of this embodiment, the actuator 313 includes a spring that links the carriage portions 322, 323.

The mass of the carriage 320 accordingly includes that of the actuator 313, and the energy requirements are correspondingly larger than that of the carriage 120 described above with reference to FIGS. 1C. On the other hand, the carriage 320 shown in FIG. 3 requires no transmission element 116 or pulleys 145, 124 (FIG. 1A).

In yet another embodiment, (shown in FIG. 4) the carriage 320 carries an actuator 413, but at least a portion of the energy required by the actuator 413 is provided to the actuator 413 from a ground-based link 418 (e.g., a hose or wire). Accordingly, in one aspect of this embodiment, the actuator 413 can include a pneumatic or hydraulic actuator. In other embodiments, the actuator 413 can include an electric linear actuator or a lead screw-actuator.

Embodiments of the present invention can include a relatively small spring (or other actuator) and no rotating cam system to achieve a constant force launch acceleration. Embodiments of the present invention can also employ a movable carriage (or shuttle), and an actuator that strokes through only a fraction of the carriage stroke. The "gain" or amplification of this motion amplifier can correspond to the slope of one launch member relative to one or more opposing launch members. For example, in one embodiment, the piston 114 described above with reference to FIG. 1A can stroke through a distance of two feet, while accelerating the carriage 120 with a constant force over a distance of ten feet.

FIG. 5 illustrates a graph of predicted carriage acceleration as a function of launch member length for an existing system having a single track and a spring or spring-like actuator, along with a system having two non-parallel launch members (e.g., as shown in FIG. 1A), also with a spring-like actuator. As shown in FIG. 5, by tailoring the relative angle between the non-parallel launch members to compensate for the reduced force provided by the actuator over the length of the launch guide, the force applied to the carriage (and therefore the acceleration of the carriage) can be maintained at a constant or nearly constant level until the carriage is deliberately decelerated to launch the aircraft. An advantage of this arrangement is that it can significantly reduce the peak force applied to the aircraft without significantly increasing the energy required by the launch mechanism, or the distance required to accelerate the aircraft to launch velocity.

FIG. 6 is a partially cut-away illustration of an embodiment of the carriage 120 as the gripper 180 supports the aircraft 150 prior to release. For purposes of illustration, only one of the gripper arms 181 is shown in FIG. 6. The carriage upper portion 122 can include a pivot post 693 extending along the pivot axis P. The gripper arm 181 can include an upper portion 688 and a lower portion 687. A gripper sleeve 699 can be attached to the upper portion 688 and disposed coaxially about the pivot post 693. One or more bearings 686 can support the gripper sleeve 699 relative to the pivot post 693. Accordingly, the gripper arm 181 can rotate smoothly about the pivot axis P as indicated by arrow M.

As discussed above, the gripper arm 181 can pivot both downwardly and outwardly away from the aircraft 150 during release so as to reduce the likelihood that the gripper arm 181 will strike the aircraft 150 as the aircraft 150 takes off. To further reduce the likelihood that the gripper arm 181 will strike either the aircraft 150 or the opposing gripper arm, the system 110 can include a gripper brake 690 that arrests the rotational motion of the gripper arm 181 once the aircraft 150 has been released.

The gripper brake 690 can include a first brake member 691a that is fixed relative to the pivot post 693, and a second

brake member **691b** that is fixed to the gripper sleeve **698** to rotate with the gripper arm **181**. The second brake member **691b** can also move axially toward the first brake member **691a** along the pivot axis P during braking. The first brake member **691a** can include a first brake surface **685a**, and the second brake member **691b** can include a second brake surface **685b**. As the second brake member **691b** moves toward and rotates relative to the first brake member **691a**, the brake surfaces **685a**, **685b** contact each other and halt the rotation of the gripper arm **181**. Accordingly, the brake **690** can be changeable between a first configuration in which it inhibits motion of the gripper **181** by a first amount (e.g., after launch) and a second configuration in which it does not inhibit motion of the gripper arm **181**, or inhibits motion of the gripper arm **181** by a second, lesser amount (e.g., prior to launch).

To control the motion of the second brake member **691b** relative to the first brake member **691a**, the gripper brake **690** can further include a first threaded member **692a** that can be generally fixed relative to the pivot post **693** and can be supported with a first threaded member support **694**. The first threaded member **692a** can include external threads **695a** that engage internal threads **695b** of a second threaded member **692b**, carried by the gripper sleeve **699**. As the gripper arm **181** rotates about the pivot axis P, it rotates the second threaded member **692b** relative to the first threaded member **692a**. The first threaded member **692a** and the second threaded member **692b** can have left-hand threads, so that the second threaded member **692b** moves axially downwardly as it rotates. This axial motion drives the second brake member **691b** into engagement with the first brake member **691a**. As the second threaded member **692b** continues to rotate, it drives the second brake surface **685b** against the first brake surface **685a** with increasing pressure. This action stops the gripper arm **181** from rotating. A corresponding pair of threaded members on the opposite gripper arm can have right-hand threads to provide a generally similar brake action to that gripper arm.

In a particular embodiment, the position of the second brake member **691b** relative to the first brake member **691a** when the gripper arm **181** is in the gripping position (as shown in FIG. 6) can be adjusted so that there is at least a slight gap (or, in one embodiment, no gap, but little or no pressure) between the second brake surface **685b** and the first brake surface **685a**. Accordingly, the gripper sleeve **699** can include an adjustment flange **689** having multiple adjustment holes **697**. The second threaded member **692b** can include an alignment hole **696** that can be selectively aligned with any of the adjustment holes **697** as the second threaded member **692b** is rotated independently of the gripper arm **181**. Accordingly, a user can rotate the second threaded member **692b** about the first threaded member **692a** until a small gap exists between the second brake surface **685b** and the first brake surface **685a**. The user can then lock the second threaded member **692b** relative to the gripper arm **181** by inserting a pin or other fastener through the alignment hole **696** and into a corresponding adjustment hole **697** of the adjustment flange **689**. If, over the course of time, the first and second brake surfaces **685a**, **685b** move apart from each other (e.g., as a result of wear), the initial gap between the brake surfaces **685a**, **685b** can be readjusted by simply repositioning the second threaded member **692b** relative to the adjustment flange **689**.

The materials of at least some of the system components described above can be selected to reduce and/or eliminate interference caused by differential thermal expansion of one component relative to another. For example, the first

threaded member support **694**, the pivot post **693**, and/or the first threaded member **692a** can be formed from the same material as the gripper arm **181**. Accordingly, the position of the second brake member **691b** relative to the first brake member **691a** can be less likely to change as the ambient temperature changes. In other embodiments, the materials selected for these or other components can be selected to increase the life expectancy of the components. For example, the first threaded member **692a** can be selected to include steel and the second threaded member **692b** can be selected to include brass. In other embodiments, these components can have other material properties and/or arrangements. For example, the gripper brake **690** can brake the gripper arms **181** via an action different than the axial and rotational action described above.

A feature of an embodiment of the system described above with reference to FIG. 6 is that the gripper brake **690** can rapidly, predictably, and repeatably stop the motion of the gripper arm **181** as it pivots away from the aircraft **150** during release. An advantage of this arrangement is that the gripper arm **181** can be less likely to strike either the aircraft **150** or the opposing gripper arm (not shown in FIG. 6).

In the embodiments of the launch system **110** described above, the portions of the carriage **120** move relative to each other while the launch members **142**, **143** remain fixed. In other embodiments, the launch members can move, in lieu of, or in addition to the movement of the carriage portions. FIGS. 7A–8B illustrate launch systems having moving launch members in accordance with further embodiments of the invention. Beginning with FIG. 7A, a launch system **710** in accordance with one embodiment of the invention can include a base **730** carrying two or more supports **731** (shown in FIG. 7A as a first support **731a** and a second support **731b**). The base **730** can be configured to incline relative to the ground (for example, with a jack **732**) to orient the aircraft **150** for launch.

The launch system **710** can further include a first launch member **742** (e.g., a first track) and a second launch member **743** (e.g., a second track), both of which support a carriage **720**, which in turn carries the aircraft **150** via a releasable gripper **780**. At least one of the first launch member **742** and the second launch member **743** is movable relative to the other. For example, in one embodiment, the first launch member **742** can be fixed relative to the base **730**, and the second launch member **743** can be movable relative to the base **730**. In other embodiments, the first and second launch members **742**, **743** can have different arrangements. In any of these embodiments, the movement of at least one of the first and second launch members **742**, **743** can accelerate the carriage **720** to launch the aircraft **150**, as described in greater detail below.

In one embodiment, the second launch member **743** can translate and/or rotate relative to the first launch member **742**. In a particular aspect of this embodiment, the motion of the second launch member **743** relative to the first launch member **742** can be controlled by a pin **729**, which depends from the second launch member **743** and which is received in an elongated guide slot **728** of the second support **731b**. The motion of the second launch member **743** can be further controlled by a block and tackle **733**. In one embodiment, the block and tackle **733** can include a coupling line **735** attached to the second launch member **743** at a first line attachment point **736a**. The coupling line **735** passes through a series of pulleys **745a–745e** to a second attachment point **736b**, also on the second launch member **743**. In other

embodiments, the second launch member 743 can be supported relative to the first launch member 742 in other arrangements.

The carriage 720 can engage both the first launch member 742 and the second launch member 743. For example, in one embodiment, the first launch member 742 can include a first roller surface 737a (which engages first rollers or wheels 721a of the carriage 720), and the second launch member 743 can include a second roller surface 737b (which engages second rollers or wheels 721b of the carriage 720). Carriage arms or links 725 can support the second wheels 721b relative to the first wheels 721a.

The second roller surface 737b can have a curved profile (or other shape) to control the acceleration of the carriage 720. Accordingly, the carriage 720 can travel (from left to right as shown in FIG. 7A) along the first roller surface 737a while engaging the second surface roller surface 737b. In a particular aspect of this embodiment, the second roller surface 737b can be inclined relative to the first roller surface 737a and can move in a wedge fashion, so as to force the carriage 720 from left to right to launch the aircraft 150.

The force required to move the second launch member 743 relative to the first launch member 742 can be provided by an actuator 713. The actuator 713 can be coupled with an actuator line 716 to the second launch member 743, after passing around an actuator pulley 745f. In one aspect of this embodiment, the actuator 713 can include a compressed gas cylinder, having a piston that retracts the actuator line 716 to draw the second launch member 743 downwardly away from the first launch member 742, as described in greater detail below with reference to FIG. 7B. In other embodiments, the actuator 713 can have other arrangements, including a hydraulic cylinder, a bungee, or a spring. In any of these embodiments, the actuator 713 can move the second launch member 743 relative to the first launch member 742, forcing movement of the carriage 720 from left to right.

The launch system 710 can include a carriage return crank or winch 749 having a carriage return line 718 with a releasable trigger 739 connected to the carriage 720. The launch carriage 720 is held back in a pre-launch position by the carriage return line 718 while a launch force is applied to the launch carriage 720. The releasable trigger 739 is then disengaged, allowing the launch carriage 720 to accelerate. After launch, the carriage return line 718 can be used to reset the carriage 720.

FIG. 7B illustrates the launch system 710 after the carriage 720 has been accelerated to launch the aircraft 150. In one aspect of this embodiment, the actuator 713 has rapidly drawn the second launch member 743 downwardly in a manner controlled by the block and tackle 733 and the pin 729 positioned in the slot 728. As the second launch member 743 moves downwardly relative to the first launch member 742, the carriage 720 is forced from left to right at a high rate of speed, until the second wheels 721b engage a braking portion 744 of the second roller surface 737b. Accordingly, the angle between the second roller surface 737b and the first roller surface 737a changes at the braking portion 744. At this point, the carriage 720 rapidly decelerates, while the gripper 780 releases, allowing the aircraft 150 to continue forward as it is launched into flight.

Once the actuator 713 has moved the second launch member 743, it can be effectively decoupled while an operator couples the carriage return line 718 to the launch carriage 720 and activates the carriage return crank 749 to return the carriage 720 to the position shown in FIG. 7A. For example, when the actuator 713 includes a gas powered piston, the volume of the cylinder in which the piston moves

can be opened to atmospheric pressure so that the operator does not need to compress the air within the cylinder when returning the carriage 720 to the launch position. Once the carriage 720 has been returned to the position shown in FIG. 7A, the actuator 713 can be readied for the next launch, for example, by charging the cylinder in which the piston operates with a compressed gas. In other embodiments, the energy of deceleration can be used to reversibly regain energy to be used during the next launch. In still further embodiments, the actuator 713 can be recharged by the carriage return crank 749. As the carriage return crank 749 is actuated, it can force the second launch member 743 to its original position as the carriage 720 returns. This movement can also force the piston of the actuator 713 to its starting position and restore gas pressure in the actuator 713.

FIG. 7C is a partially schematic illustration of a portion of the launch system 710 illustrating the first launch member 742, along with the second launch member 743 (shown in its pre-launch configuration in solid lines and in its post-launch configuration in dashed lines). As shown in FIG. 7C, the portion of the second launch member 743 to which the coupling line 735 is attached can move by distance 3X, which is three times the distance X moved by the right-most portion of the second launch member 743. The wedge angle between the first launch member 742 and the second launch member 743 increases by translating and pivoting the second launch member 743 relative to the first launch member 742. By increasing the wedge angle during the launch process, the carriage 720 is accelerated at a constant or nearly constant rate, even as the force from the actuator 713 decreases near the end of the actuator's power stroke.

FIG. 7D is a graph illustrating predicted acceleration and velocity values for a carriage 720 propelled by a launch system 710 in accordance with an embodiment of the invention. In one aspect of this embodiment, the launch system 710 can provide a generally constant acceleration to the carriage 720, which instantaneously reverses (when the carriage 720 reaches the braking portion 744 described above). This acceleration profile can provide a generally uniform increase in velocity, as is also shown in FIG. 7D, up to at least the take-off velocity of the aircraft 150. In other embodiments, the carriage 720 can be propelled in manners that result in different acceleration and velocity profiles.

FIG. 7E is a partially schematic illustration of a launch system 710a configured in accordance with another embodiment of the invention and having many characteristics in common with the launch system 710 described above with reference to FIGS. 7A-7C. In one aspect of this embodiment, the launch system 710a includes a first link 719a and a second link 719b coupled between the first launch member 742 and the second launch member 743, in lieu of the block and tackle 733 and pin 729 described above. The motion of the second launch member 743 relative to the first launch member 742 can be generally similar to that described above with reference to FIGS. 7A and 7B, to provide acceleration and velocity profiles generally similar to those described above with reference to FIG. 7D.

FIGS. 8A-8B illustrate a launch system 810 configured in accordance with still another embodiment of the invention. In one aspect of this embodiment, the launch system 810 can include a first launch member 842 coupled to a second launch member 843 at a pivot point 827. An actuator 813 can be coupled to the first launch member 742 and the second launch member 743 with actuator rods 814 to force the first and second launch members 842, 843 apart from each other in a transverse plane. A carriage 820 can carry the aircraft 150 and can engage a first roller surface 837a of the first

11

launch member **842** with first wheels **821a**. The carriage **820** can also engage a second roller surface **837b** of the second launch member **843** with second wheels **821b**.

Referring now to FIG. 8B, the actuator **813** can be activated to spread the first launch member **842** and the second launch member **843** apart from each other, forcing the carriage **820** from left to right. When the carriage **820** reaches braking portions **844** of the first and second launch members **842**, **843**, it rapidly decelerates, causing a gripper **880** to open (as indicated by arrows M) while the aircraft **150** continues forward and is launched into flight. In other embodiments, the launch system **810** can have other arrangements.

One feature of embodiments of the launch systems described above with reference to FIG. 1A–8B is that the “wedge action” of the first and second members relative to each other can rapidly accelerate the carriage (and therefore the aircraft **150**) in a relatively short distance. An advantage of this arrangement is that the launch systems can be used in cramped quarters, including the deck of a fishing vessel or a towed trailer.

Another feature of embodiments of the launch systems described above is that the wedge angle between the first and second members can increase as a function of distance (e.g., as shown in FIGS. 1A–5) and/or time (e.g., as shown in FIGS. 7A–8B). This arrangement can provide a constant or nearly constant acceleration to the carriage (and the aircraft **150**), even if the force provided by the actuator decreases near the end of the actuator’s power stroke. An advantage of this arrangement is that the aircraft **150** is less likely to be subject to sudden changes in acceleration, which can damage the aircraft **150**.

Yet another feature of the launch systems described above with reference to FIGS. 7A–8B is that they can include a braking portion that rapidly and safely decelerates the carriage carried by the launch system. An advantage of this feature is that the system length required for deceleration can be short relative to that required for acceleration, and the overall length of the system can be correspondingly limited.

Another feature of embodiments of the launch systems described above is that the number of components that move at high speed during the launch process is relatively small. For example, in a particular embodiment (e.g., as shown in FIGS. 7A–8B), the only rolling elements that are traveling at high speed are the carriage wheels, and no high speed pulleys are included. Accordingly, the potential losses associated with components moving at high speed, including losses caused by ropes attached to the carriage suddenly accelerating and decelerating (e.g., “rope slurping”) can be reduced and/or eliminated.

From the foregoing, it will be appreciated that specific embodiments of the invention have been described herein for purposes of illustration, but that various modifications may be made without deviating from the spirit and scope of the invention. For example, the systems described above can be used to launch aircraft having arrangements different than those described above. In other embodiments, these systems can handle projectiles or other airborne devices. Aspects of the systems described in the context of particular embodiments can be combined or eliminated in other embodiments. For example, the system described above with reference to FIG. 1A can be arranged transversely, as described above with reference to FIGS. 8A–8B. The gripper brake can also have arrangements different than those described above. Further details of related systems and methods are described in the following co-pending U.S. application Ser. No. 10/760,150 entitled “Methods and Apparatuses for Launch-

12

ing Unmanned Aircraft, Including Methods and Apparatuses for Launching Aircraft with a Wedge Action,” filed Jan. 16, 2004 and incorporated herein in its entirety by reference. Accordingly, the invention is not limited except as by the appended claims.

We claim:

1. An apparatus for carrying an unmanned aircraft, comprising:
 - a support;
 - a launch carriage movably carried by the support;
 - a gripper movably coupled to the launch carriage, the gripper positioned to releasably engage an unmanned aircraft, the gripper being movable relative to the launch carriage between a first position with the gripper portion positioned to contact the aircraft and a second position with the gripper positioned to be out of contact with the aircraft; and
 - a brake positioned at least proximate to the gripper, the brake being changeable from a first configuration in which the brake inhibits motion of the gripper relative to the launch carriage by a first amount, and a second configuration in which the brake does not inhibit motion of the gripper relative to the launch carriage, or inhibits motion of the gripper by a second amount less than the first amount.
2. The apparatus of claim 1 wherein the brake includes a first brake member and a second brake member, with at least one of the brake members being movable relative to the other.
3. The apparatus of claim 1 wherein the brake includes a first brake member coupled to the carriage and a second brake member coupled to the gripper, and wherein the second brake member is rotatable about an axis and translatable along the axis between a first position relative to the first brake member and a second position relative to the first brake member.
4. The apparatus of claim 1 wherein the gripper is positioned to releasably engage a fuselage of the aircraft, the gripper being movable relative to the launch carriage between a first position with the at least one grip portion positioned to contact the fuselage and a second position with the at least one grip portion positioned to be out of contact with the fuselage.
5. The apparatus of claim 1 wherein the gripper includes two gripper arms pivotally coupled to the launch carriage, the individual gripper arms including at least one grip portion positioned to releasably engage the fuselage of the aircraft.
6. The apparatus of claim 1 wherein the gripper is movable between the first and second position when the launch carriage decelerates relative to the support.
7. The apparatus of claim 1 wherein:
 - the launch carriage is movable relative to the support along a launch axis; and
 - the gripper is pivotable relative to the launch carriage about a pivot axis offset from the launch axis to pivot downwardly and outwardly away from the launch axis as the gripper moves from the first position to the second position, and wherein at least a portion of the mass of the gripper is eccentrically offset from the pivot axis to swing the gripper from the first position to the second position as the carriage decelerates.
8. The apparatus of claim 1, further comprising the aircraft.

13

9. The apparatus of claim 1 wherein the support includes a launch guide structure having a launch axis, and wherein the launch carriage is movable relative to the support along the launch axis.

10. An apparatus for carrying an unmanned aircraft, 5 comprising:

a support;

a launch carriage movably carried by the support;

a gripper movably coupled to the launch carriage, the gripper including positioned to releasably engage an unmanned aircraft, the gripper being movable relative to the launch carriage between a first gripper position with a positioned to contact the aircraft and a second gripper position with the positioned to be out of contact with the aircraft; and

a gripper brake positioned proximate to the gripper, the gripper brake including a first brake portion carried by the launch carriage and a second brake portion carried by the gripper, the second brake portion being movable relative to the first brake portion between a first brake position and a second brake position, with the second brake portion in contact with the first brake portion and

14

applying a first force to the first brake portion when in the first position, and with the second brake portion out of contact with the first brake portion or applying a second force less than the first force when in the second position.

11. The system of claim 10 wherein the first brake portion is configured to rotate about an axis and translate along the axis between the first and second positions.

12. The system of claim 10 wherein the first brake portion is coupled to a first threaded member and the second brake portion is coupled to a second threaded member that is threadably engaged with the first threaded member.

13. The system of claim 10 wherein the first brake portion is coupled to a first threaded member and the second brake portion is coupled to a second threaded member that is threadably engaged with the first threaded member, and wherein the second threaded member is movable relative to the gripper to adjust an axial separation between the first and second brake portions.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,165,745 B2
APPLICATION NO. : 10/808725
DATED : January 23, 2007
INVENTOR(S) : McGeer et al.

Page 1 of 1


It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title Page, Page 2

References Cited, Line 46, "Koetsch" should be --Koelsch--;

Signed and Sealed this

Thirty-first Day of July, 2007

A handwritten signature in black ink on a light gray dotted background. The signature reads "Jon W. Dudas" in a cursive style.

JON W. DUDAS

Director of the United States Patent and Trademark Office